

Detailed Member Calculations

Units: N&mm

Regulation: ASCE 41-17

Calculation No. 1

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 33 and 34)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 12.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 19940.411$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 8.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$
 Concrete Elasticity, $E_c = 16281.278$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of γ for displacement ductility demand,
 the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
 Deformation-Controlled Action (Table C7-1, ASCE 41-17).
 Jacket
 New material: Concrete Strength, $f_c = f_{cm} = 18.00$
 New material: Steel Strength, $f_s = f_{sm} = 625.00$
 Existing Column
 Existing material: Concrete Strength, $f_c = f_{cm} = 12.00$
 Existing material: Steel Strength, $f_s = f_{sm} = 525.00$
 #####
 Max Height, $H_{max} = 750.00$
 Min Height, $H_{min} = 450.00$
 Max Width, $W_{max} = 950.00$
 Min Width, $W_{min} = 450.00$
 Eccentricity, $E_{cc} = 250.00$
 Jacket Thickness, $t_j = 100.00$
 Cover Thickness, $c = 25.00$
 Element Length, $L = 3000.00$
 Primary Member
 Ribbed Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d >= 1$)
 No FRP Wrapping

 Stepwise Properties

EDGE -A-
 Bending Moment, $M_a = -1.9854E+009$
 Shear Force, $V_a = -716139.537$
 EDGE -B-
 Bending Moment, $M_b = -3.5795E+008$
 Shear Force, $V_b = 716139.537$
 BOTH EDGES
 Axial Force, $F = -5.0716E+006$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{sl,t} = 3191.858$
 -Compression: $A_{sl,c} = 3499.734$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{sl,ten} = 1539.38$
 -Compression: $A_{sl,com} = 1539.38$
 -Middle: $A_{sl,mid} = 3612.832$
 Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.57143$

 Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 793342.593$
 V_n ((10.3), ASCE 41-17) = $k_n l V_{Co10} = 991678.242$
 $V_{Co10} = 1.1571E+006$
 $k_n l = 0.85705856$
 displacement_ductility_demand = 3.90589

NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + \phi V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

 $\phi = 1$ (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 10.13333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 3.64793$

$\mu_u = 1.9854E+009$

$V_u = 716139.537$

$d = 0.8 \cdot h = 760.00$

$N_u = 5.0716E+006$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 980981.156$

where:

$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 879645.943$

$V_{s,j1} = 282743.339$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

$V_{s,j1}$ is multiplied by $\text{Col},j1 = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 596902.604$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

$V_{s,j2}$ is multiplied by $\text{Col},j2 = 1.00$

$s/d = 0.13157895$

$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 101335.213$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 420.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $\text{Col},c1 = 0.00$

$s/d = 1.25$

$V_{s,c2} = 101335.213$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 420.00$

$s = 250.00$

$V_{s,c2}$ is multiplied by $\text{Col},c2 = 1.00$

$s/d = 0.41666667$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 723217.666$

$bw = 450.00$

displacement_ductility_demand is calculated as ϕ / y

- Calculation of ϕ / y for END A -
for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 0.01287864$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00329724$ ((4.29), Biskinis Phd)

$M_y = 1.6308E+009$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 2772.431

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 4.5707E+014$

factor = 0.70

$A_g = 562500.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$

$N = 5.0716E+006$

$E_c \cdot I_g = E_{c,\text{jacket}} \cdot I_{g,\text{jacket}} + E_{c,\text{core}} \cdot I_{g,\text{core}} = 6.5295E+014$

Calculation of Yielding Moment M_y

Calculation of ϕ and M_y according to Annex 7 -

y = Min(y_ten, y_com)
y_ten = 6.3767581E-006
with fy = 601.9953
d = 907.00
y = 0.47957772
A = 0.0370359
B = 0.02922707
with pt = 0.0037716
pc = 0.0037716
pv = 0.00885172
N = 5.0716E+006
b = 450.00
" = 0.04740904
y_comp = 2.6024973E-006
with fc = 18.00
Ec = 19940.411
y = 0.68835635
A = -0.02184193
B = 0.0085861
with Es = 200000.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 2

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 33 and 34)

Analysis: Uniform +X

Check: Chord rotation capacity (u)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rcjtcs

Constant Properties

 Knowledge Factor, $\gamma = 0.80$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
 Concrete Elasticity, $E_c = 19940.411$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
 Concrete Elasticity, $E_c = 16281.278$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 Jacket
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$
 Existing Column
 Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$
 #####
 Max Height, $H_{max} = 750.00$
 Min Height, $H_{min} = 450.00$
 Max Width, $W_{max} = 950.00$
 Min Width, $W_{min} = 450.00$
 Eccentricity, $E_{cc} = 250.00$
 Jacket Thickness, $t_j = 100.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.42131
 Element Length, $L = 3000.00$
 Primary Member
 Ribbed Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_o/l_{ou,min} >= 1$)
 No FRP Wrapping

Stepwise Properties

 At local axis: 3
 EDGE -A-
 Shear Force, $V_a = -1.7986448E-005$
 EDGE -B-

Shear Force, $V_b = 1.7986448E-005$

BOTH EDGES

Axial Force, $F = -5.0813E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 314.1593$

-Compression: $As_c = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1539.38$

-Compression: $As_{l,com} = 2475.575$

-Middle: $As_{l,mid} = 2676.637$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.92314$

Member Controlled by Shear ($V_e/V_r > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 2.0922E+006$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.1383E+009$

$Mu_{1+} = 3.1383E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.6290E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.1383E+009$

$Mu_{2+} = 3.1383E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.6290E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.9524665E-005$

$M_u = 3.1383E+009$

with full section properties:

$b = 950.00$

$d = 707.00$

$d' = 43.00$

$v = 0.420296$

$N = 5.0813E+006$

$f_c = 18.00$

α_1 (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.01486841$

ω_e (5.4c) = 0.08077545

ω_{ase} ((5.4d), TBDY) = $(\omega_{ase1} * A_{ext} + \omega_{ase2} * A_{int}) / A_{sec} = 0.53375773$

$\omega_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$\omega_{ase2} (>= \omega_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.
 $A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$
 $psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 $psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$
 $psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 $psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 781.25$
 $f_{ywe2} = 656.25$
 $f_{ce} = 18.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 907.50$
 $fy1 = 756.25$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{min} = lb/ld = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 756.25$

with $Es1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 900.1904$
 $fy2 = 750.1586$
 $su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 1.00$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 750.1586$

with $Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.0025$

```

shv = 0.008
ftv = 902.993
fyv = 752.4941
suv = 0.032
  using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
  and also multiplied by the shear_factor according to 15.7.1.4, with
  Shear_factor = 1.00
  lo/lou,min = lb/lb = 1.00
  suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032
  From table 5A.1, TBDY: esuv_nominal = 0.08,
  considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
  For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
  characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.
  y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.
  with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941
  with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
  1 = Asl,ten/(b*d)*(fs1/fc) = 0.09629324
  2 = Asl,com/(b*d)*(fs2/fc) = 0.15360794
  v = Asl,mid/(b*d)*(fsv/fc) = 0.16660079
and confined core properties:
b = 890.00
d = 677.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
  c = confinement factor = 1.42131
  1 = Asl,ten/(b*d)*(fs1/fc) = 0.10733965
  2 = Asl,com/(b*d)*(fs2/fc) = 0.17122928
  v = Asl,mid/(b*d)*(fsv/fc) = 0.18571261
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.42075151
MRc (4.17) = 2.3432E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*,y1 - RHS eq.(4.6) is not satisfied

```

--->

$$*cu(4.11) = 0.47003883$$

$$MRo(4.18) = 3.1383E+009$$

--->

$$u = cu(4.2) = 1.9524665E-005$$

$$Mu = MRo$$

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 1.0952761E-005$$

$$Mu = 1.6290E+009$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.88729156$$

$$N = 5.0813E+006$$

$$fc = 18.00$$

$$co(5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01486841$$

$$we(5.4c) = 0.08077545$$

$$ase((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $bi^2/6$ as defined at (A.2).

$$ase2 (>=ase1) = \text{Max}(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $bi^2/6$ as defined at (A.2).

$$psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 2.724$$

$$psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.724$$

$$psh1((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00301593$$

$$Lstir1(\text{Length of stirrups along Y}) = 2160.00$$

$$Astir1(\text{stirrups area}) = 78.53982$$

$$psh2(5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047$$

$$Lstir2(\text{Length of stirrups along Y}) = 1568.00$$

$$\text{Astir2 (stirrups area)} = 50.26548$$

$$\begin{aligned} \text{psh}_y * \text{Fywe} &= \text{psh}_1 * \text{Fywe}_1 + \text{ps}_2 * \text{Fywe}_2 = 3.25416 \\ \text{psh}_1 ((5.4d), \text{TBDY}) &= \text{Lstir}_1 * \text{Astir}_1 / (\text{Asec} * \text{s}_1) = 0.00357443 \\ \text{Lstir}_1 (\text{Length of stirrups along X}) &= 2560.00 \\ \text{Astir}_1 (\text{stirrups area}) &= 78.53982 \\ \text{psh}_2 ((5.4d), \text{TBDY}) &= \text{Lstir}_2 * \text{Astir}_2 / (\text{Asec} * \text{s}_2) = 0.00070345 \\ \text{Lstir}_2 (\text{Length of stirrups along X}) &= 1968.00 \\ \text{Astir}_2 (\text{stirrups area}) &= 50.26548 \end{aligned}$$

$$\text{Asec} = 562500.00$$

$$\text{s}_1 = 100.00$$

$$\text{s}_2 = 250.00$$

$$\text{fywe}_1 = 781.25$$

$$\text{fywe}_2 = 656.25$$

$$\text{fce} = 18.00$$

$$\text{From } ((5.A.5), \text{TBDY}), \text{TBDY: } \text{cc} = 0.00621307$$

$$\text{c} = \text{confinement factor} = 1.42131$$

$$\text{y}_1 = 0.0025$$

$$\text{sh}_1 = 0.008$$

$$\text{ft}_1 = 900.1904$$

$$\text{fy}_1 = 750.1586$$

$$\text{su}_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou, min} = \text{lb/ld} = 1.00$$

$$\text{su}_1 = 0.4 * \text{esu}_1 \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$\text{y}_1, \text{sh}_1, \text{ft}_1, \text{fy}_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from } 10.3.5, \text{ ASCE } 41-17.$$

$$\text{with } \text{fs}_1 = (\text{fs}_{\text{jacket}} * \text{Asl, ten, jacket} + \text{fs}_{\text{core}} * \text{Asl, ten, core}) / \text{Asl, ten} = 750.1586$$

$$\text{with } \text{Es}_1 = (\text{Es}_{\text{jacket}} * \text{Asl, ten, jacket} + \text{Es}_{\text{core}} * \text{Asl, ten, core}) / \text{Asl, ten} = 200000.00$$

$$\text{y}_2 = 0.0025$$

$$\text{sh}_2 = 0.008$$

$$\text{ft}_2 = 907.50$$

$$\text{fy}_2 = 756.25$$

$$\text{su}_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou, min} = \text{lb/lb, min} = 1.00$$

$$\text{su}_2 = 0.4 * \text{esu}_2 \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$$\text{y}_2, \text{sh}_2, \text{ft}_2, \text{fy}_2, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from } 10.3.5, \text{ ASCE } 41-17.$$

$$\text{with } \text{fs}_2 = (\text{fs}_{\text{jacket}} * \text{Asl, com, jacket} + \text{fs}_{\text{core}} * \text{Asl, com, core}) / \text{Asl, com} = 756.25$$

$$\text{with } \text{Es}_2 = (\text{Es}_{\text{jacket}} * \text{Asl, com, jacket} + \text{Es}_{\text{core}} * \text{Asl, com, core}) / \text{Asl, com} = 200000.00$$

$$\text{y}_v = 0.0025$$

$$\text{sh}_v = 0.008$$

$$\text{ft}_v = 902.993$$

$$\text{fy}_v = 752.4941$$

$$\text{suv} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou, min} = \text{lb/ld} = 1.00$$

$$\text{suv} = 0.4 * \text{esuv}_v \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv, ftv, fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

$$\text{y}_v, \text{sh}_v, \text{ft}_v, \text{fy}_v, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from } 10.3.5, \text{ ASCE } 41-17.$$

$$\text{with } \text{fs}_v = (\text{fs}_{\text{jacket}} * \text{Asl, mid, jacket} + \text{fs}_{\text{mid}} * \text{Asl, mid, core}) / \text{Asl, mid} = 752.4941$$

$$\text{with } \text{Es}_v = (\text{Es}_{\text{jacket}} * \text{Asl, mid, jacket} + \text{Es}_{\text{mid}} * \text{Asl, mid, core}) / \text{Asl, mid} = 200000.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.32428344$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.20328574$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.35171278$$

and confined core properties:

$$b = 390.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 25.58352$$

$$c_c (5A.5, TBDY) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.39075399$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.24495458$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.42380571$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < v_{s,y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

$$c_u (4.10) = 0.82478813$$

$$M_{Rc} (4.17) = 1.5333E+009$$

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- N_1, N_2, v normalised to b_o*d_o , instead of $b*d$
- parameters of confined concrete, f_{cc}, c_c , used in lieu of f_c, c_c

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$$^*c_u (4.11) = 0.83790293$$

$$M_{Ro} (4.18) = 1.6290E+009$$

---->

$$u = c_u (4.2) = 1.0952761E-005$$

$$\mu_u = M_{Ro}$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 1.9524665E-005$$

$$\mu = 3.1383E+009$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.420296$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.01486841$$

$$\phi_{cc}(5.4c) = 0.08077545$$

$$\text{ase ((5.4d), TBDY) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.53375773$$

$$\text{ase1 = Max}(\frac{A_{conf,max1} - A_{noConf1}}{A_{conf,max1}} * \frac{A_{conf,min1}}{A_{conf,max1}}, 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{ase2 } (>= \text{ase1}) = \text{Max}(\frac{A_{conf,max2} - A_{noConf2}}{A_{conf,max2}} * \frac{A_{conf,min2}}{A_{conf,max2}}, 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{psh}_{min} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 2.724$$

$$\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.724$$

$$\text{psh}_1 \text{ ((5.4d), TBDY) = } L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y) = } 2160.00$$

$$A_{stir1} \text{ (stirrups area) = } 78.53982$$

$$\text{psh}_2 \text{ (5.4d) = } L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y) = } 1568.00$$

$$A_{stir2} \text{ (stirrups area) = } 50.26548$$

$$\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 3.25416$$

$$\text{psh}_1 \text{ ((5.4d), TBDY) = } L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X) = } 2560.00$$

$$A_{stir1} \text{ (stirrups area) = } 78.53982$$

$$\text{psh}_2 \text{ ((5.4d), TBDY) = } L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X) = } 1968.00$$

$$A_{stir2} \text{ (stirrups area) = } 50.26548$$

$$A_{sec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 907.50$
 $fy1 = 756.25$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou,min = lb/ld = 1.00$

$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 756.25$

with $Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 900.1904$
 $fy2 = 750.1586$
 $su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou,min = lb/lb,min = 1.00$

$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 750.1586$

with $Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00$

$yv = 0.0025$
 $shv = 0.008$
 $ftv = 902.993$
 $fyv = 752.4941$
 $suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou,min = lb/ld = 1.00$

$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 752.4941$

with $Es_v = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$

$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.09629324$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.15360794$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.16660079$

and confined core properties:

$b = 890.00$
 $d = 677.00$
 $d' = 13.00$

$fcc (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.10733965$

$2 = Asl,com / (b * d) * (fs2 / fc) = 0.17122928$

$v = Asl,mid / (b * d) * (fsv / fc) = 0.18571261$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is not satisfied

---->

v < vs,c - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)

---->

v < vs,y1 - LHS eq.(4.7) is not satisfied

---->

v < vc,y1 - RHS eq.(4.6) is satisfied

---->

cu (4.10) = 0.42075151

MRC (4.17) = 2.3432E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu

---->

Subcase: Rupture of tension steel

---->

v* < v*s,y2 - LHS eq.(4.5) is not satisfied

---->

v* < v*s,c - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

v* < v*c,y2 - LHS eq.(4.6) is not satisfied

---->

v* < v*c,y1 - RHS eq.(4.6) is not satisfied

---->

*cu (4.11) = 0.47003883

MRO (4.18) = 3.1383E+009

---->

u = cu (4.2) = 1.9524665E-005

Mu = MRO

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0952761E-005

Mu = 1.6290E+009

with full section properties:

b = 450.00

d = 707.00

d' = 43.00

v = 0.88729156

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00621307$

c = confinement factor = 1.42131

$y_1 = 0.0025$

$sh_1 = 0.008$

$ft_1 = 900.1904$

$fy_1 = 750.1586$

$su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o / l_{ou,min} = l_b / l_d = 1.00$

$su_1 = 0.4 * esu_{1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1 / 1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s,jacket} \cdot A_{s,ten,jacket} + f_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 750.1586$
with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_{b,min} = 1.00$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 756.25$
with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 902.993$
 $fy_v = 752.4941$
 $suv = 0.032$
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_d = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 752.4941$
with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.32428344$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.20328574$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.35171278$
and confined core properties:
 $b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.39075399$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.24495458$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.42380571$
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
---->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
 $v < s_y1$ - LHS eq.(4.7) is not satisfied
---->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
---->
 $cu (4.10) = 0.82478813$
 $MRC (4.17) = 1.5333E+009$
---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, ν_1 , ν_2 , ν normalised to b_o*d_o , instead of $b*d$
- parameters of confined concrete, f_{cc} , ϵ_{cc} , used in lieu of f_c , ϵ_{cu}

--->

Subcase: Rupture of tension steel

--->

$\nu^* < \nu^*s_y2$ - LHS eq.(4.5) is not satisfied

--->

$\nu^* < \nu^*s_c$ - LHS eq.(4.5) is not satisfied

--->

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$\nu^* < \nu^*c_y2$ - LHS eq.(4.6) is not satisfied

--->

$\nu^* < \nu^*c_y1$ - RHS eq.(4.6) is not satisfied

--->

ϵ^*_{cu} (4.11) = 0.83790293

M_{Ro} (4.18) = 1.6290E+009

--->

$u = \epsilon_{cu}$ (4.2) = 1.0952761E-005

$\mu_u = M_{Ro}$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0879E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0879E+006$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l V_{Col0}$

$V_{Col0} = 1.0879E+006$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + f^* V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_c \text{ jacket} * \text{Area jacket} + f'_c \text{ core} * \text{Area core}) / \text{Area section} = 15.20$, but $f'_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 4.8236E+008$

$V_u = 1.7986448E-005$

$d = 0.8 * h = 600.00$

$N_u = 5.0813E+006$

$A_g = 337500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0354E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 942477.796$

$V_{s,j1} = 589048.623$ is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 699281.943$
 $bw = 450.00$

 Calculation of Shear Strength at edge 2, $V_{r2} = 1.0879E+006$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$
 $V_{Col0} = 1.0879E+006$
 $knl = 1$ (zero step-static loading)

 NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)
 Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 15.20$, but $f'_c^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $M_u = 4.5550E+008$
 $V_u = 1.7986448E-005$
 $d = 0.8 * h = 600.00$
 $N_u = 5.0813E+006$
 $Ag = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0354E+006$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 942477.796$
 $V_{s,j1} = 589048.623$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$

Av = 100530.965
fy = 525.00
s = 250.00
Vs,c2 is multiplied by Col,c2 = 0.00
s/d = 1.25
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 699281.943
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 0.80
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Primary Member: Concrete Strength, fc = fcm = 18.00
New material of Primary Member: Steel Strength, fs = fsm = 625.00
Concrete Elasticity, Ec = 19940.411
Steel Elasticity, Es = 200000.00
Existing Column
Existing material of Primary Member: Concrete Strength, fc = fcm = 12.00
Existing material of Primary Member: Steel Strength, fs = fsm = 525.00
Concrete Elasticity, Ec = 16281.278
Steel Elasticity, Es = 200000.00

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength, fs = 1.25*fsm = 781.25
Existing Column
Existing material: Steel Strength, fs = 1.25*fsm = 656.25

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.42131
Element Length, L = 3000.00
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lo/lo_u,min >= 1)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -5.5168185E-006

EDGE -B-

Shear Force, $V_b = 5.5168185E-006$

BOTH EDGES

Axial Force, $F = -5.0813E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 314.1593$

-Compression: $A_{sc} = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{s,ten} = 1539.38$

-Compression: $A_{s,com} = 1539.38$

-Middle: $A_{s,mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.44711$

Member Controlled by Shear ($V_e/V_r > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 1.9243E+006$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 2.8865E+009$

$Mu_{1+} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 2.8865E+009$

$Mu_{2+} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 9.9083764E-006$

$M_u = 2.8865E+009$

with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.69163741$

$N = 5.0813E+006$

$f_c = 18.00$

α_1 (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.01486841$

ω_e (5.4c) = 0.08077545

α_{se} ((5.4d), TBDY) = $(\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.53375773$

$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$\alpha_{se2} (> \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{,min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 756.25$

with $Es1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 907.50$

$fy2 = 756.25$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (f_{s,jacket} * A_{s2,com,jacket} + f_{s,core} * A_{s2,com,core}) / A_{s2,com} = 756.25$

with $Es2 = (E_{s,jacket} * A_{s2,com,jacket} + E_{s,core} * A_{s2,com,core}) / A_{s2,com} = 200000.00$

$y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 899.1522$
 $fy_v = 749.2935$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 1.00$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 749.2935$
 with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.15845977$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.15845977$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.36847443$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.18909264$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.18909264$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.43970658$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s_{y1}$ - LHS eq.(4.7) is not satisfied
 --->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.6344264$
 $MRC (4.17) = 2.3433E+009$
 --->
 New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
 In expressions below, the following modifications have been made
 - b, d, d' replaced by geometric parameters of the core: $bo, do, d'o$
 - $N, 1, 2, v$ normalised to $bo * do$, instead of $b * d$
 - - parameters of confined concrete, fcc, cc , used in lieu of fc, ecu
 --->
 Subcase: Rupture of tension steel
 --->
 $v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied
 --->
 $v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied
 --->
 Subcase rejected
 --->
 New Subcase: Failure of compression zone
 --->
 $v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied
 --->

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

---->

$$*cu(4.11) = 0.71499649$$

$$MRo(4.18) = 2.8865E+009$$

---->

$$u = cu(4.2) = 9.9083764E-006$$

$$Mu = MRo$$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.9083764E-006$$

$$Mu = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$fc = 18.00$$

$$co(5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01486841$$

$$we(5.4c) = 0.08077545$$

$$ase((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of $AnoConf$, $Aconf,min$ and $Aconf,max$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$Aconf,max1 = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$Aconf,min1 = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $Aconf,max1$ by a length equal to half the clear spacing between external hoops.

$AnoConf1 = 173066.667$ is the unconfined external core area which is equal to $bi^2/6$ as defined at (A.2).

$$ase2 (\geq ase1) = \text{Max}(((Aconf,max2 - AnoConf2) / Aconf,max2) * (Aconf,min2 / Aconf,max2), 0) = 0.53375773$$

The definitions of $AnoConf$, $Aconf,min$ and $Aconf,max$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$Aconf,max2 = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$Aconf,min2 = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $Aconf,max2$ by a length equal to half the clear spacing between internal hoops.

$AnoConf2 = 110709.333$ is the unconfined internal core area which is equal to $bi^2/6$ as defined at (A.2).

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.724$$

$$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.724$$

$$psh1((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1 (\text{Length of stirrups along } Y) = 2160.00$$

$$Astir1 (\text{stirrups area}) = 78.53982$$

$$psh2(5.4d) = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.25416
psh₁ ((5.4d), TBDY) = Lstir₁*Astir₁/(Asec*s₁) = 0.00357443
Lstir₁ (Length of stirrups along X) = 2560.00
Astir₁ (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = Lstir₂*Astir₂/(Asec*s₂) = 0.00070345
Lstir₂ (Length of stirrups along X) = 1968.00
Astir₂ (stirrups area) = 50.26548

Asec = 562500.00
s₁ = 100.00
s₂ = 250.00

fywe₁ = 781.25
fywe₂ = 656.25
fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307
c = confinement factor = 1.42131

y₁ = 0.0025
sh₁ = 0.008
ft₁ = 907.50
fy₁ = 756.25
su₁ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 1.00

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*Asl_{ten,jacket} + fs_{core}*Asl_{ten,core})/Asl_{ten} = 756.25

with Es₁ = (Es_{jacket}*Asl_{ten,jacket} + Es_{core}*Asl_{ten,core})/Asl_{ten} = 200000.00

y₂ = 0.0025
sh₂ = 0.008
ft₂ = 907.50
fy₂ = 756.25
su₂ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 1.00

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*Asl_{com,jacket} + fs_{core}*Asl_{com,core})/Asl_{com} = 756.25

with Es₂ = (Es_{jacket}*Asl_{com,jacket} + Es_{core}*Asl_{com,core})/Asl_{com} = 200000.00

y_v = 0.0025
sh_v = 0.008
ft_v = 899.1522
fy_v = 749.2935
su_v = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 1.00

su_v = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_{nominal} = 0.08,

considering characteristic value fsy_v = fs_v/1.2, from table 5.1, TBDY
For calculation of esuv_{nominal} and y_v, sh_v,ft_v,fy_v, it is considered

characteristic value fsy_v = fs_v/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs_v = (fs_{jacket}*Asl_{mid,jacket} + fs_{mid}*Asl_{mid,core})/Asl_{mid} = 749.2935

```

with Esv = (Esjacket*Asl,mid,jacket + Esmid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977
2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977
v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443
and confined core properties:
b = 390.00
d = 877.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264
2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264
v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < sy1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*sy2 - LHS eq.(4.5) is not satisfied
---->
v* < v*sc - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*cy2 - LHS eq.(4.6) is not satisfied
---->
v* < v*cy1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009
---->
u = cu (4.2) = 9.9083764E-006
Mu = MRo
-----

Calculation of ratio lb/d
-----
Adequate Lap Length: lb/d >= 1
-----
-----
-----
Calculation of Mu2+

```

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.9083764E-006$$

$$\mu = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.01486841$$

$$w_e(5.4c) = 0.08077545$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2}((5.4d)) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2}((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$

$$c = \text{confinement factor} = 1.42131$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 907.50$$

$$fy_1 = 756.25$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu_{1, \text{nominal}}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{\text{jacket}} * Asl, \text{ten, jacket} + fs_{\text{core}} * Asl, \text{ten, core}) / Asl, \text{ten} = 756.25$$

$$\text{with } Es_1 = (Es_{\text{jacket}} * Asl, \text{ten, jacket} + Es_{\text{core}} * Asl, \text{ten, core}) / Asl, \text{ten} = 200000.00$$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 907.50$$

$$fy_2 = 756.25$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 1.00$$

$$su_2 = 0.4 * esu_{2, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{2, \text{nominal}} = 0.08$,

For calculation of $esu_{2, \text{nominal}}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{\text{jacket}} * Asl, \text{com, jacket} + fs_{\text{core}} * Asl, \text{com, core}) / Asl, \text{com} = 756.25$$

$$\text{with } Es_2 = (Es_{\text{jacket}} * Asl, \text{com, jacket} + Es_{\text{core}} * Asl, \text{com, core}) / Asl, \text{com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 899.1522$$

$$fy_v = 749.2935$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsy_v = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{\text{jacket}} * Asl, \text{mid, jacket} + fs_{\text{mid}} * Asl, \text{mid, core}) / Asl, \text{mid} = 749.2935$$

$$\text{with } Es_v = (Es_{\text{jacket}} * Asl, \text{mid, jacket} + Es_{\text{mid}} * Asl, \text{mid, core}) / Asl, \text{mid} = 200000.00$$

$$1 = Asl, \text{ten} / (b * d) * (fs_1 / fc) = 0.15845977$$

$$2 = Asl, \text{com} / (b * d) * (fs_2 / fc) = 0.15845977$$

$$v = Asl, \text{mid} / (b * d) * (fsv / fc) = 0.36847443$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{TBDY}) = 25.58352$$

$$cc (5A.5, \text{TBDY}) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = Asl, \text{ten} / (b * d) * (fs_1 / fc) = 0.18909264$$

$$2 = Asl, \text{com} / (b * d) * (fs_2 / fc) = 0.18909264$$

$$v = Asl, \text{mid} / (b * d) * (fsv / fc) = 0.43970658$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

v < vs,y2 - LHS eq.(4.5) is not satisfied

v < vs,c - RHS eq.(4.5) is not satisfied

Case/Assumption Rejected.

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

v < vs,y1 - LHS eq.(4.7) is not satisfied

v < vc,y1 - RHS eq.(4.6) is satisfied

cu (4.10) = 0.6344264

MRC (4.17) = 2.3433E+009

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o

- N, ν_1 , ν_2 , ν normalised to bo*do, instead of b*d

- parameters of confined concrete, fcc, cc, used in lieu of fc, ecu

Subcase: Rupture of tension steel

v* < v*s,y2 - LHS eq.(4.5) is not satisfied

v* < v*s,c - LHS eq.(4.5) is not satisfied

Subcase rejected

New Subcase: Failure of compression zone

v* < v*c,y2 - LHS eq.(4.6) is not satisfied

v* < v*c,y1 - RHS eq.(4.6) is not satisfied

*cu (4.11) = 0.71499649

MRO (4.18) = 2.8865E+009

u = cu (4.2) = 9.9083764E-006

Mu = MRO

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

u = 9.9083764E-006

Mu = 2.8865E+009

with full section properties:

b = 450.00

d = 907.00

d' = 43.00

v = 0.69163741

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00621307$

c = confinement factor = 1.42131

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * e_{su1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,

For calculation of $e_{su1,nominal}$ and $y1$, $sh1$, $ft1$, $fy1$, it is considered

characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 756.25$
 with $Es_1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou_{min} = lb/lb_{min} = 1.00$
 $su_2 = 0.4 \cdot esu_2_{nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu_2_{nominal} = 0.08$,
 For calculation of $esu_2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2 / 1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 756.25$
 with $Es_2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 899.1522$
 $fy_v = 749.2935$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou_{min} = lb/ld = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsyv = fsv / 1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsyv = fsv / 1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 749.2935$
 with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.15845977$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.15845977$
 $v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.36847443$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $f_{cc} (5A.2, \text{TBDY}) = 25.58352$
 $cc (5A.5, \text{TBDY}) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.18909264$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.18909264$
 $v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.43970658$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 ---->
 $v < v_{s,y_2}$ - LHS eq.(4.5) is not satisfied
 ---->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
 ---->
 Case/Assumption Rejected.
 ---->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 ---->
 $v < s_{y_1}$ - LHS eq.(4.7) is not satisfied
 ---->
 $v < v_{c,y_1}$ - RHS eq.(4.6) is satisfied
 ---->
 $cu (4.10) = 0.6344264$
 $MRC (4.17) = 2.3433E+009$

```

--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ec
--->
Subcase: Rupture of tension steel
--->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
--->
v* < v*s,c - LHS eq.(4.5) is not satisfied
--->
Subcase rejected
--->
New Subcase: Failure of compression zone
--->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
--->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
--->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009
--->
u = cu (4.2) = 9.9083764E-006
Mu = MRo
-----

Calculation of ratio lb/d
-----
Adequate Lap Length: lb/d >= 1
-----
-----
-----
-----
Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 1.3298E+006
-----
Calculation of Shear Strength at edge 1, Vr1 = 1.3298E+006
Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 1.3298E+006
knl = 1 (zero step-static loading)
-----
NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).
-----
= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 15.20, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)
M/Vd = 4.00
Mu = 1.7267E+008
Vu = 5.5168185E-006
d = 0.8*h = 760.00
Nu = 5.0813E+006
Ag = 427500.00
From (11.5.4.8), ACI 318-14: Vs = Vs_jacket + Vs_core = 1.2262E+006
where:
Vs_jacket = Vs_j1 + Vs_j2 = 1.0996E+006
Vs_j1 = 353429.174 is calculated for section web jacket, with:
d = 360.00
Av = 157079.633
fy = 625.00
s = 100.00
Vs_j1 is multiplied by Col_j1 = 1.00
s/d = 0.27777778
Vs_j2 = 746128.255 is calculated for section flange jacket, with:
d = 760.00
Av = 157079.633

```

$f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.13157895$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 0.00$
 $s/d = 1.25$
 $V_{s,c2} = 126669.016$ is calculated for section flange core, with:
 $d = 600.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 1.00$
 $s/d = 0.41666667$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 885757.128$
 $bw = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.3298E+006$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$
 $V_{Col0} = 1.3298E+006$
 $knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)
 Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$, but $f_c'^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 1.6609E+008$
 $V_u = 5.5168185E-006$
 $d = 0.8 * h = 760.00$
 $N_u = 5.0813E+006$
 $A_g = 427500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.2262E+006$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 1.0996E+006$
 $V_{s,j1} = 353429.174$ is calculated for section web jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.27777778$
 $V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:
 $d = 760.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.13157895$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 0.00$
 $s/d = 1.25$
 $V_{s,c2} = 126669.016$ is calculated for section flange core, with:

d = 600.00
Av = 100530.965
fy = 525.00
s = 250.00
Vs,c2 is multiplied by Col,c2 = 1.00
s/d = 0.41666667
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 885757.128
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (a)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, γ = 0.80
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
Concrete Elasticity, $E_c = 19940.411$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
Concrete Elasticity, $E_c = 16281.278$
Steel Elasticity, $E_s = 200000.00$
Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$
Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $E_{cc} = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/l_d >= 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -5.5401E+008$
Shear Force, $V_2 = -716139.537$
Shear Force, $V_3 = 3.11526$
Axial Force, $F = -5.0716E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 3191.858$
-Compression: $A_{sc} = 3499.734$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{s,ten} = 2475.575$
-Compression: $A_{s,com} = 1539.38$

-Middle: Asl,mid = 2676.637

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: Asl,ten,jacket = 1859.823

-Compression: Asl,com,jacket = 1231.504

-Middle: Asl,mid,jacket = 2060.885

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: Asl,ten,core = 615.7522

-Compression: Asl,com,core = 307.8761

-Middle: Asl,mid,core = 615.7522

Mean Diameter of Tension Reinforcement, DbL = 16.72727

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u,R = \phi u = 0.01009045$
 $u = y + p = 0.01261306$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.01261306$ ((4.29),Biskinis Phd)

$M_y = 1.9034E+009$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 6000.00

From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 3.0181E+014$

factor = 0.70

$A_g = 562500.00$

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$

$N = 5.0716E+006$

$E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 4.3116E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, $b = 950.00$

web width, $b_w = 450.00$

flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 7.3868598E-006$

with $f_y = 601.9953$

$d = 707.00$

$y = 0.42365327$

$A = 0.02250607$

$B = 0.01848214$

with $p_t = 0.00368581$

$p_c = 0.00229194$

$p_v = 0.00398517$

$N = 5.0716E+006$

$b = 950.00$

$\beta = 0.06082037$

$y_{comp} = 4.5684036E-006$

with $f_c = 18.00$

$E_c = 19940.411$

$y = 0.50306838$

$A = -0.01327296$

$B = 0.00593898$

with $E_s = 200000.00$

CONFIRMATION: $y = 0.50306838 < t/d$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ -

From table 10-8: $\rho = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$

shear control ratio $V_{yE}/V_{CoIE} = 1.92314$

$d = d_{\text{external}} = 707.00$

$s = s_{\text{external}} = 100.00$

- $t = s_1 + s_2 + 2 \cdot t_f/bw \cdot (f_{fe}/f_s) = 0.0035764$

jacket: $s_1 = A_{v1} \cdot L_{\text{stir1}} / (s_1 \cdot A_g) = 0.00301593$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir1}} = 2160.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot L_{\text{stir2}} / (s_2 \cdot A_g) = 0.00056047$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir2}} = 1568.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 \cdot t_f/bw \cdot (f_{fe}/f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f/bw$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe}/f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5.0716E+006$

$A_g = 562500.00$

$f_{cE} = (f_{c_jacket} \cdot \text{Area_jacket} + f_{c_core} \cdot \text{Area_core}) / \text{section_area} = 15.20$

$f_{yE} = (f_{y_ext_Long_Reinf} \cdot \text{Area_ext_Long_Reinf} + f_{y_int_Long_Reinf} \cdot \text{Area_int_Long_Reinf}) / \text{Area_Tot_Long_Rein} = 601.9953$

$f_{yE} = (f_{y_ext_Trans_Reinf} \cdot s_1 + f_{y_int_Trans_Reinf} \cdot s_2) / (s_1 + s_2) = 609.3286$

$\rho = \text{Area_Tot_Long_Rein} / (b \cdot d) = 0.00996292$

$b = 950.00$

$d = 707.00$

$f_{cE} = 15.20$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 3

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 33 and 34)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjctcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 12.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 8.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 18.00$

New material: Steel Strength, $f_s = f_{sm} = 625.00$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material: Steel Strength, $f_s = f_{sm} = 525.00$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -5.5401E+008$
Shear Force, $V_a = 3.11526$
EDGE -B-
Bending Moment, $M_b = 4.5517E+008$
Shear Force, $V_b = -3.11526$
BOTH EDGES
Axial Force, $F = -5.0716E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 3191.858$
-Compression: $A_{sl,c} = 3499.734$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 2475.575$
-Compression: $A_{sl,com} = 1539.38$
-Middle: $A_{sl,mid} = 2676.637$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.72727$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 734492.961$
 V_n ((10.3), ASCE 41-17) = $k_n I V_{CoIO} = 918116.201$
 $V_{CoI} = 918116.201$
 $k_n I = 1.00$
displacement_ductility_demand = 0.51126198

NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + \phi V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 10.13333$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/d = 4.00$
 $M_u = 5.5401E+008$
 $V_u = 3.11526$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0716E+006$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 828294.726$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 753982.237$
 $V_{s,j1} = 471238.898$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 282743.339$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col_{j2} = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 74312.489$
 $V_{s,c1} = 74312.489$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col_{c1} = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 570961.316$
 $bw = 450.00$

displacement_ductility_demand is calculated as ϕ / y

- Calculation of ϕ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 0.00644858$
 $y = (M_y * L_s / 3) / E_{eff} = 0.01261306$ ((4.29), Biskinis Phd))
 $M_y = 1.9034E+009$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 6000.00
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 3.0181E+014$
factor = 0.70
 $A_g = 562500.00$
Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$
 $N = 5.0716E+006$
 $E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 4.3116E+014$

Calculation of Yielding Moment M_y

Calculation of ϕ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:
flange width, $b = 950.00$
web width, $bw = 450.00$
flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 7.3868598E-006$
with $f_y = 601.9953$
 $d = 707.00$
 $y = 0.42365327$
 $A = 0.02250607$
 $B = 0.01848214$
with $pt = 0.00368581$
 $pc = 0.00229194$
 $pv = 0.00398517$
 $N = 5.0716E+006$
 $b = 950.00$
 $" = 0.06082037$
 $y_{comp} = 4.5684036E-006$
with $f_c = 18.00$
 $E_c = 19940.411$
 $y = 0.50306838$
 $A = -0.01327296$
 $B = 0.00593898$
with $E_s = 200000.00$
CONFIRMATION: $y = 0.50306838 < t/d$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 4

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 33 and 34)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\phi = 0.80$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

Max Height, $H_{max} = 750.00$

Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.42131
Element Length, L = 3000.00
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{o,u,min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, Va = -1.7986448E-005
EDGE -B-
Shear Force, Vb = 1.7986448E-005
BOTH EDGES
Axial Force, F = -5.0813E+006
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 314.1593
-Compression: Aslc = 6377.433
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1539.38
-Compression: Asl,com = 2475.575
-Middle: Asl,mid = 2676.637

Calculation of Shear Capacity ratio , $V_e/V_r = 1.92314$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 2.0922E+006$
with
 $M_{pr1} = \text{Max}(\mu_{u1+}, \mu_{u1-}) = 3.1383E+009$
 $\mu_{u1+} = 3.1383E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{u1-} = 1.6290E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{u2+}, \mu_{u2-}) = 3.1383E+009$
 $\mu_{u2+} = 3.1383E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $\mu_{u2-} = 1.6290E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of μ_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.9524665E-005$
 $M_u = 3.1383E+009$

with full section properties:

b = 950.00
d = 707.00
d' = 43.00
v = 0.420296
N = 5.0813E+006

$$f_c = 18.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01486841$$

$$w_e \text{ (5.4c)} = 0.08077545$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 907.50$$

$$fy1 = 756.25$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{ou,min} = l_b / l_d = 1.00$$

$$su1 = 0.4 * e_{su1_nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_jacket \cdot Asl,ten,jacket + fs_core \cdot Asl,ten,core) / Asl,ten = 756.25$

with $Es1 = (Es_jacket \cdot Asl,ten,jacket + Es_core \cdot Asl,ten,core) / Asl,ten = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 900.1904$

$fy2 = 750.1586$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lou,min = lb/lb,min = 1.00$

$su2 = 0.4 \cdot esu2_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_jacket \cdot Asl,com,jacket + fs_core \cdot Asl,com,core) / Asl,com = 750.1586$

with $Es2 = (Es_jacket \cdot Asl,com,jacket + Es_core \cdot Asl,com,core) / Asl,com = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 902.993$

$fyv = 752.4941$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lou,min = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_jacket \cdot Asl,mid,jacket + fs_mid \cdot Asl,mid,core) / Asl,mid = 752.4941$

with $Esv = (Es_jacket \cdot Asl,mid,jacket + Es_mid \cdot Asl,mid,core) / Asl,mid = 200000.00$

$1 = Asl,ten / (b \cdot d) \cdot (fs1 / fc) = 0.09629324$

$2 = Asl,com / (b \cdot d) \cdot (fs2 / fc) = 0.15360794$

$v = Asl,mid / (b \cdot d) \cdot (fsv / fc) = 0.16660079$

and confined core properties:

$b = 890.00$

$d = 677.00$

$d' = 13.00$

$fcc (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = Asl,ten / (b \cdot d) \cdot (fs1 / fc) = 0.10733965$

$2 = Asl,com / (b \cdot d) \cdot (fs2 / fc) = 0.17122928$

$v = Asl,mid / (b \cdot d) \cdot (fsv / fc) = 0.18571261$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < vs,y2$ - LHS eq.(4.5) is not satisfied

--->

$v < vs,c$ - RHS eq.(4.5) is not satisfied

--->

Case/Assumption Rejected.

--->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

--->

$v < s,y1$ - LHS eq.(4.7) is not satisfied

--->

$v < vc,y1$ - RHS eq.(4.6) is satisfied

--->

cu (4.10) = 0.42075151
MRc (4.17) = 2.3432E+009

--->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu

--->

Subcase: Rupture of tension steel

--->

$v^* < v^*s_y2$ - LHS eq.(4.5) is not satisfied

--->

$v^* < v^*s_c$ - LHS eq.(4.5) is not satisfied

--->

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$v^* < v^*c_y2$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*c_y1$ - RHS eq.(4.6) is not satisfied

--->

*cu (4.11) = 0.47003883

MRo (4.18) = 3.1383E+009

--->

u = cu (4.2) = 1.9524665E-005

Mu = MRo

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0952761E-005

Mu = 1.6290E+009

with full section properties:

b = 450.00

d = 707.00

d' = 43.00

v = 0.88729156

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01486841$

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{,min} * F_{ywe} = \text{Min}(psh_{,x} * F_{ywe}, psh_{,y} * F_{ywe}) = 2.724$

 $psh_{,x} * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 2.724$
 psh_1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 psh_2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $psh_{,y} * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.25416$
 psh_1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 psh_2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$
 $s_1 = 100.00$
 $s_2 = 250.00$
 $f_{ywe1} = 781.25$
 $f_{ywe2} = 656.25$
 $f_{ce} = 18.00$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$
 c = confinement factor = 1.42131

$y_1 = 0.0025$
 $sh_1 = 0.008$
 $ft_1 = 900.1904$
 $fy_1 = 750.1586$
 $su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su_1 = 0.4 * esu_{1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (f_{s,jacket} * A_{s,t,en,jacket} + f_{s,core} * A_{s,t,en,core}) / A_{s,t,en} = 750.1586$

with $Es_1 = (E_{s,jacket} * A_{s,t,en,jacket} + E_{s,core} * A_{s,t,en,core}) / A_{s,t,en} = 200000.00$

$y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$

$su_2 = 0.4 * esu_{2,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_jacket \cdot Asl,com,jacket + fs_core \cdot Asl,com,core) / Asl,com = 756.25$

with $Es2 = (Es_jacket \cdot Asl,com,jacket + Es_core \cdot Asl,com,core) / Asl,com = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 902.993$

$fyv = 752.4941$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lou,min = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_jacket \cdot Asl,mid,jacket + fs_mid \cdot Asl,mid,core) / Asl,mid = 752.4941$

with $Esv = (Es_jacket \cdot Asl,mid,jacket + Es_mid \cdot Asl,mid,core) / Asl,mid = 200000.00$

$1 = Asl,ten / (b \cdot d) \cdot (fs1 / fc) = 0.32428344$

$2 = Asl,com / (b \cdot d) \cdot (fs2 / fc) = 0.20328574$

$v = Asl,mid / (b \cdot d) \cdot (fsv / fc) = 0.35171278$

and confined core properties:

$b = 390.00$

$d = 677.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

$1 = Asl,ten / (b \cdot d) \cdot (fs1 / fc) = 0.39075399$

$2 = Asl,com / (b \cdot d) \cdot (fs2 / fc) = 0.24495458$

$v = Asl,mid / (b \cdot d) \cdot (fsv / fc) = 0.42380571$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs,y2$ - LHS eq.(4.5) is not satisfied

$v < vs,c$ - RHS eq.(4.5) is not satisfied

Case/Assumption Rejected.

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

$v < sy1$ - LHS eq.(4.7) is not satisfied

$v < vc,y1$ - RHS eq.(4.6) is satisfied

cu (4.10) = 0.82478813

MRC (4.17) = 1.5333E+009

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: $bo, do, d'o$

- $N, 1, 2, v$ normalised to $bo \cdot do$, instead of $b \cdot d$

- parameters of confined concrete, fcc, cc , used in lieu of fc, ecu

Subcase: Rupture of tension steel

$v^* < v^*sy2$ - LHS eq.(4.5) is not satisfied

$v^* < v^*sc$ - LHS eq.(4.5) is not satisfied

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

--->

*cu (4.11) = 0.83790293

MRo (4.18) = 1.6290E+009

--->

u = cu (4.2) = 1.0952761E-005

Mu = MRo

Calculation of ratio lb/l_d

Adequate Lap Length: lb/l_d >= 1

Calculation of Mu₂₊

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.9524665E-005

Mu = 3.1383E+009

with full section properties:

b = 950.00

d = 707.00

d' = 43.00

v = 0.420296

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to bi²/6 as defined at (A.2).

ase2 (>=ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to bi²/6 as defined at (A.2).

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 2.724

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.724
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00301593
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
psh2 (5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.25416
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00357443
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00070345
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00
s1 = 100.00
s2 = 250.00
fywe1 = 781.25
fywe2 = 656.25
fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307
c = confinement factor = 1.42131

y1 = 0.0025
sh1 = 0.008
ft1 = 907.50
fy1 = 756.25
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 900.1904
fy2 = 750.1586
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 750.1586

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 902.993
fyv = 752.4941
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered
 characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.
 $y1$, $sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941$
 with $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.09629324$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.15360794$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.16660079$

and confined core properties:

$b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 fcc (5A.2, TBDY) = 25.58352
 cc (5A.5, TBDY) = 0.00621307
 $c =$ confinement factor = 1.42131
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.10733965$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.17122928$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.18571261$

Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

---->
 $v < vs,y2$ - LHS eq.(4.5) is not satisfied

---->
 $v < vs,c$ - RHS eq.(4.5) is not satisfied

---->
 Case/Assumption Rejected.

---->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)

---->
 $v < s,y1$ - LHS eq.(4.7) is not satisfied

---->
 $v < vc,y1$ - RHS eq.(4.6) is satisfied

---->
 cu (4.10) = 0.42075151
 MRC (4.17) = 2.3432E+009

---->
 New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
 In expressions below, the following modifications have been made

- b , d , d' replaced by geometric parameters of the core: bo , do , $d'o$
- N , 1 , 2 , v normalised to $bo*do$, instead of $b*d$
- parameters of confined concrete, fcc , cc , used in lieu of fc , ecu

---->
 Subcase: Rupture of tension steel

---->
 $v^* < v^*,y2$ - LHS eq.(4.5) is not satisfied

---->
 $v^* < v^*,c$ - LHS eq.(4.5) is not satisfied

---->
 Subcase rejected

---->
 New Subcase: Failure of compression zone

---->
 $v^* < v^*,y2$ - LHS eq.(4.6) is not satisfied

---->
 $v^* < v^*,y1$ - RHS eq.(4.6) is not satisfied

---->
 $*cu$ (4.11) = 0.47003883
 MRO (4.18) = 3.1383E+009

---->
 $u = cu$ (4.2) = 1.9524665E-005
 $Mu = MRO$

 Calculation of ratio lb/ld

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0952761E-005$$

$$\mu_u = 1.6290E+009$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.88729156$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_u: \mu_u^* = \text{shear_factor} * \text{Max}(\mu_u, c_o) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_u = 0.01486841$$

$$\mu_{we} \text{ (5.4c)} = 0.08077545$$

$$\mu_{ase} \text{ ((5.4d), TBDY)} = (\mu_{ase1} * A_{ext} + \mu_{ase2} * A_{int}) / A_{sec} = 0.53375773$$

$$\mu_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\mu_{ase2} (\geq \mu_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A.5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 900.1904

fy1 = 750.1586

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fsjacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 750.1586

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 902.993

fyv = 752.4941

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.32428344

2 = Asl,com/(b*d)*(fs2/fc) = 0.20328574

v = Asl,mid/(b*d)*(fsv/fc) = 0.35171278

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

1 = $A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.39075399$

2 = $A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.24495458$

v = $A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.42380571$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

Case/Assumption Rejected.

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

c_u (4.10) = 0.82478813

M_{Rc} (4.17) = 1.5333E+009

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o

- N, 1, 2, v normalised to b_o*d_o, instead of b*d

- - parameters of confined concrete, f_{cc}, c_c, used in lieu of f_c, e_c

Subcase: Rupture of tension steel

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

Subcase rejected

New Subcase: Failure of compression zone

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

*c_u (4.11) = 0.83790293

M_{Ro} (4.18) = 1.6290E+009

u = c_u (4.2) = 1.0952761E-005

M_u = M_{Ro}

Calculation of ratio l_b/l_d

Adequate Lap Length: l_b/l_d >= 1

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0879E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0879E+006$

$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = knl * V_{Co10}$

$V_{Co10} = 1.0879E+006$

kn_l = 1 (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} = f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 15.20$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 4.8236E+008$
 $V_u = 1.7986448E-005$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0813E+006$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0354E+006$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 942477.796$
 $V_{s,j1} = 589048.623$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 699281.943$
 $bw = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0879E+006$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl \cdot V_{Col0}$
 $V_{Col0} = 1.0879E+006$
 $knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 15.20$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 4.5550E+008$
 $V_u = 1.7986448E-005$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0813E+006$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0354E+006$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 942477.796$
 $V_{s,j1} = 589048.623$ is calculated for section web jacket, with:

$d = 600.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 699281.943$
 $bw = 450.00$

 End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rcjtcs

Constant Properties

 Knowledge Factor, $\phi = 0.80$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
 Concrete Elasticity, $E_c = 19940.411$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
 Concrete Elasticity, $E_c = 16281.278$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 Jacket
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$
 Existing Column
 Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$
 #####

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.42131
Element Length, L = 3000.00
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} \geq 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -5.5168185E-006
EDGE -B-
Shear Force, Vb = 5.5168185E-006
BOTH EDGES
Axial Force, F = -5.0813E+006
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 314.1593
-Compression: Asc = 6377.433
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1539.38
-Compression: Asl,com = 1539.38
-Middle: Asl,mid = 3612.832

Calculation of Shear Capacity ratio, $V_e/V_r = 1.44711$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 1.9243E+006$
with
 $M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 2.8865E+009$
 $Mu_{1+} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 2.8865E+009$
 $Mu_{2+} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 9.9083764E-006$
 $Mu = 2.8865E+009$

with full section properties:
b = 450.00
d = 907.00
d' = 43.00
v = 0.69163741

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01486841$$

$$w_e (5.4c) = 0.08077545$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along } Y) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along } Y) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along } X) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along } X) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 907.50$$

$$fy_1 = 756.25$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{ou,min} = l_b / l_d = 1.00$$

$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs_jacket * Asl,ten,jacket + fs_core * Asl,ten,core) / Asl,ten = 756.25$
 with $Es1 = (Es_jacket * Asl,ten,jacket + Es_core * Asl,ten,core) / Asl,ten = 200000.00$
 $y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 907.50$
 $fy2 = 756.25$
 $su2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/lb,min = 1.00$
 $su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs_jacket * Asl,com,jacket + fs_core * Asl,com,core) / Asl,com = 756.25$
 with $Es2 = (Es_jacket * Asl,com,jacket + Es_core * Asl,com,core) / Asl,com = 200000.00$
 $yv = 0.0025$
 $shv = 0.008$
 $ftv = 899.1522$
 $fyv = 749.2935$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 1.00$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_jacket * Asl,mid,jacket + fs_mid * Asl,mid,core) / Asl,mid = 749.2935$
 with $Esv = (Es_jacket * Asl,mid,jacket + Es_mid * Asl,mid,core) / Asl,mid = 200000.00$
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.15845977$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.15845977$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.36847443$

and confined core properties:

$b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.18909264$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.18909264$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs,y2$ - LHS eq.(4.5) is not satisfied

$v < vs,c$ - RHS eq.(4.5) is not satisfied

Case/Assumption Rejected.

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

$v < s,y1$ - LHS eq.(4.7) is not satisfied

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

c_u (4.10) = 0.6344264

M_{Rc} (4.17) = 2.3433E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, 1, 2, v$ normalised to b_o*d_o , instead of $b*d$
- - parameters of confined concrete, f_{cc}, c_c , used in lieu of f_c, e_c

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$*c_u$ (4.11) = 0.71499649

M_{Ro} (4.18) = 2.8865E+009

---->

$u = c_u$ (4.2) = 9.9083764E-006

$\mu_u = M_{Ro}$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_{u1} -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 9.9083764E-006$

$\mu_u = 2.8865E+009$

with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.69163741$

$N = 5.0813E+006$

$f_c = 18.00$

c_o (5A.5, TBDY) = 0.002

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
ase2 (\geq ase1) = $\text{Max}(((A_{\text{conf,max2}} - A_{\text{noConf2}})/A_{\text{conf,max2}}) * (A_{\text{conf,min2}}/A_{\text{conf,max2}}), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
psh,min*Fywe = $\text{Min}(psh_x * Fywe, psh_y * Fywe) = 2.724$

psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.724
psh1 ((5.4d), TBDY) = $L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s1) = 0.00301593$
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
psh2 (5.4d) = $L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s2) = 0.00056047$
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 3.25416
psh1 ((5.4d), TBDY) = $L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = $L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 907.50

fy1 = 756.25

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = $0.4 * esu1_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(f_{s,\text{jacket}} * A_{s,\text{ten,jacket}} + f_{s,\text{core}} * A_{s,\text{ten,core}}) / A_{s,\text{ten}} = 756.25$

with Es1 = $(E_{s,\text{jacket}} * A_{s,\text{ten,jacket}} + E_{s,\text{core}} * A_{s,\text{ten,core}}) / A_{s,\text{ten}} = 200000.00$

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

```

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esu2_nominal = 0.08,
For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lc)^ 2/3), from 10.3.5, ASCE 41-17.
with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25
with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00
yv = 0.0025
shv = 0.008
ftv = 899.1522
fyv = 749.2935
suv = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/lc = 1.00
suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esuv_nominal = 0.08,
considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lc)^ 2/3), from 10.3.5, ASCE 41-17.
with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935
with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977
2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977
v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443
and confined core properties:
b = 390.00
d = 877.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264
2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264
v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658
Case/Assumption: Unconfined full section - Steel rupture
'satisfies Eq. (4.3)
--->
v < vs,y2 - LHS eq.(4.5) is not satisfied
--->
v < vs,c - RHS eq.(4.5) is not satisfied
--->
Case/Assumption Rejected.
--->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
'satisfies Eq. (4.4)
--->
v < sy1 - LHS eq.(4.7) is not satisfied
--->
v < vc,y1 - RHS eq.(4.6) is satisfied
--->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N1, N2, v normalised to bo*do, instead of b*d
- parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
--->
Subcase: Rupture of tension steel
--->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
--->
v* < v*s,c - LHS eq.(4.5) is not satisfied

```

--->
 Subcase rejected
 --->
 New Subcase: Failure of compression zone
 --->
 $v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied
 --->
 $v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied
 --->
 $*c_u$ (4.11) = 0.71499649
 M_{Ro} (4.18) = 2.8865E+009
 --->
 $u = c_u$ (4.2) = 9.9083764E-006
 $\mu = M_{Ro}$

 Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

 Calculation of μ_{2+}

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 9.9083764E-006$
 $\mu = 2.8865E+009$

with full section properties:

$b = 450.00$
 $d = 907.00$
 $d' = 43.00$
 $v = 0.69163741$
 $N = 5.0813E+006$
 $f_c = 18.00$
 c_o (5A.5, TBDY) = 0.002
 Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$a_{se2} (\geq a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 2.724$$

$$psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 2.724$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1 \text{ (Length of stirrups along Y)} = 2160.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

$$Lstir2 \text{ (Length of stirrups along Y)} = 1568.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.25416$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

$$Lstir1 \text{ (Length of stirrups along X)} = 2560.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

$$Lstir2 \text{ (Length of stirrups along X)} = 1968.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fy_{we1} = 781.25$$

$$fy_{we2} = 656.25$$

$$f_{ce} = 18.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 907.50$$

$$fy1 = 756.25$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/ld = 1.00$$

$$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_{nominal} = 0.08,$$

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs_{jacket} * Asl_{ten,jacket} + fs_{core} * Asl_{ten,core}) / Asl_{ten} = 756.25$$

$$\text{with } Es1 = (Es_{jacket} * Asl_{ten,jacket} + Es_{core} * Asl_{ten,core}) / Asl_{ten} = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 907.50$$

$$fy2 = 756.25$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/lb_{min} = 1.00$$

$$su2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_{nominal} = 0.08,$$

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs2 = (fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 756.25$$

$$\text{with } Es2 = (Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 899.1522$$

$$fy_v = 749.2935$$

$$su_v = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/ld = 1.00$$

```

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esuv_nominal = 0.08,
considering characteristic value fsv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsv = fsv/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lc)^2/3), from 10.3.5, ASCE 41-17.
with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935
with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977
2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977
v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443
and confined core properties:
b = 390.00
d = 877.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264
2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264
v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < sy1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*s,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009
---->
u = cu (4.2) = 9.9083764E-006
Mu = MRo

```

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 9.9083764E-006$$

$$\mu_2 = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_c: \mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01486841$$

$$\mu_{we} \text{ (5.4c)} = 0.08077545$$

$$\mu_{ase} \text{ ((5.4d), TBDY)} = (\mu_{ase1} * A_{ext} + \mu_{ase2} * A_{int}) / A_{sec} = 0.53375773$$

$$\mu_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\mu_{ase2} (\geq \mu_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A.5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 907.50

fy1 = 756.25

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 899.1522

fyv = 749.2935

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977

2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977

v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443

and confined core properties:

b = 390.00

d = 877.00

d' = 13.00

fcc (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

1 = $Asl,ten/(b*d)*(fs1/fc)$ = 0.18909264

2 = $Asl,com/(b*d)*(fs2/fc)$ = 0.18909264

v = $Asl,mid/(b*d)*(fsv/fc)$ = 0.43970658

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs,y2$ - LHS eq.(4.5) is not satisfied

$v < vs,c$ - RHS eq.(4.5) is not satisfied

Case/Assumption Rejected.

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

$v < s,y1$ - LHS eq.(4.7) is not satisfied

$v < vc,y1$ - RHS eq.(4.6) is satisfied

cu (4.10) = 0.6344264

MRC (4.17) = 2.3433E+009

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: $bo, do, d'o$
- $N, 1, 2, v$ normalised to $bo*do$, instead of $b*d$
- - parameters of confined concrete, fcc, cc , used in lieu of fc, ecu

Subcase: Rupture of tension steel

$v^* < v^*s,y2$ - LHS eq.(4.5) is not satisfied

$v^* < v^*s,c$ - LHS eq.(4.5) is not satisfied

Subcase rejected

New Subcase: Failure of compression zone

$v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

$*cu$ (4.11) = 0.71499649

MRO (4.18) = 2.8865E+009

$u = cu$ (4.2) = 9.9083764E-006

$Mu = MRO$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 1.3298E+006$

Calculation of Shear Strength at edge 1, $Vr1 = 1.3298E+006$

$Vr1 = VCol$ ((10.3), ASCE 41-17) = $knl*VColO$

$VColO = 1.3298E+006$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $Vs = Av*fy*d/s$ ' is replaced by ' $Vs+ f*Vf$ '
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$, but $f_c'^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 1.7267E+008$
 $V_u = 5.5168185E-006$
 $d = 0.8 \cdot h = 760.00$
 $N_u = 5.0813E+006$
 $A_g = 427500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.2262E+006$
 where:
 $V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 1.0996E+006$
 $V_{s,j1} = 353429.174$ is calculated for section web jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $\text{Col},j1 = 1.00$
 $s/d = 0.27777778$
 $V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:
 $d = 760.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $\text{Col},j2 = 1.00$
 $s/d = 0.13157895$
 $V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 126669.016$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $\text{Col},c1 = 0.00$
 $s/d = 1.25$
 $V_{s,c2} = 126669.016$ is calculated for section flange core, with:
 $d = 600.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $\text{Col},c2 = 1.00$
 $s/d = 0.41666667$
 $V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 885757.128$
 $b_w = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.3298E+006$
 $V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col}0}$
 $V_{\text{Col}0} = 1.3298E+006$
 $k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$, but $f_c'^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 1.6609E+008$
 $V_u = 5.5168185E-006$
 $d = 0.8 \cdot h = 760.00$
 $N_u = 5.0813E+006$
 $A_g = 427500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.2262E+006$
 where:
 $V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 1.0996E+006$

Vs,j1 = 353429.174 is calculated for section web jacket, with:

d = 360.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.27777778

Vs,j2 = 746128.255 is calculated for section flange jacket, with:

d = 760.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.13157895

Vs,core = Vs,c1 + Vs,c2 = 126669.016

Vs,c1 = 0.00 is calculated for section web core, with:

d = 200.00

Av = 100530.965

fy = 525.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 0.00

s/d = 1.25

Vs,c2 = 126669.016 is calculated for section flange core, with:

d = 600.00

Av = 100530.965

fy = 525.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 1.00

s/d = 0.41666667

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 885757.128

bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 0.80

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, fc = fcm = 18.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 19940.411

Steel Elasticity, Es = 200000.00

Existing Column

Existing material of Primary Member: Concrete Strength, fc = fcm = 12.00

Existing material of Primary Member: Steel Strength, fs = fsm = 525.00

Concrete Elasticity, Ec = 16281.278

Steel Elasticity, Es = 200000.00

Max Height, Hmax = 750.00

Min Height, Hmin = 450.00

Max Width, Wmax = 950.00

Min Width, Wmin = 450.00

Eccentricity, Ecc = 250.00

Jacket Thickness, tj = 100.00

Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -1.9854E+009$
Shear Force, $V2 = -716139.537$
Shear Force, $V3 = 3.11526$
Axial Force, $F = -5.0716E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 3191.858$
-Compression: $A_{sc} = 3499.734$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{s,ten} = 1539.38$
-Compression: $A_{s,com} = 1539.38$
-Middle: $A_{s,mid} = 3612.832$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{s,ten,jacket} = 1231.504$
-Compression: $A_{s,com,jacket} = 1231.504$
-Middle: $A_{s,mid,jacket} = 2689.203$
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{s,ten,core} = 307.8761$
-Compression: $A_{s,com,core} = 307.8761$
-Middle: $A_{s,mid,core} = 923.6282$
Mean Diameter of Tension Reinforcement, $D_bL = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_R = \alpha \cdot u = 0.00263779$
 $u = \gamma + \rho = 0.00329724$

- Calculation of γ -

$\gamma = (M \cdot L_s / 3) / E_{eff} = 0.00329724$ ((4.29), Biskinis Phd))
 $M_y = 1.6308E+009$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 2772.431
From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} \cdot E_c \cdot I_g = 4.5707E+014$
factor = 0.70
 $A_g = 562500.00$
Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot \text{Area}_{jacket} + f_c'_{core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 15.20$
 $N = 5.0716E+006$
 $E_c \cdot I_g = E_c \cdot I_{g,jacket} + E_c \cdot I_{g,core} = 6.5295E+014$

Calculation of Yielding Moment M_y

Calculation of γ and M_y according to Annex 7 -

$\gamma = \text{Min}(\gamma_{ten}, \gamma_{com})$
 $\gamma_{ten} = 6.3767581E-006$
with $f_y = 601.9953$
 $d = 907.00$
 $\gamma = 0.47957772$
 $A = 0.0370359$
 $B = 0.02922707$
with $p_t = 0.0037716$

$p_c = 0.0037716$
 $p_v = 0.00885172$
 $N = 5.0716E+006$
 $b = 450.00$
 $" = 0.04740904$
 $y_{comp} = 2.6024973E-006$
 with $f_c = 18.00$
 $E_c = 19940.411$
 $y = 0.68835635$
 $A = -0.02184193$
 $B = 0.0085861$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

 Adequate Lap Length: $l_b/l_d \geq 1$

 - Calculation of p -

 From table 10-8: $p = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$

shear control ratio $V_y E / V_{CoI} O E = 1.44711$

$d = d_{external} = 907.00$

$s = s_{external} = 100.00$

- $t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00427788$

jacket: $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00357443$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2560.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00070345$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1968.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5.0716E+006$

$A_g = 562500.00$

$f_{cE} = (f_{c,jacket} * Area_{jacket} + f_{c,core} * Area_{core}) / section_area = 15.20$

$f_{yIE} = (f_{y,ext_Long_Reinf} * Area_{ext_Long_Reinf} + f_{y,int_Long_Reinf} * Area_{int_Long_Reinf}) / Area_{Tot_Long_Rein} = 601.9953$

$f_{yIE} = (f_{y,ext_Trans_Reinf} * s_1 + f_{y,int_Trans_Reinf} * s_2) / (s_1 + s_2) = 608.5561$

$p_l = Area_{Tot_Long_Rein} / (b * d) = 0.01639493$

$b = 450.00$

$d = 907.00$

$f_{cE} = 15.20$

 End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 5

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 33 and 34)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 12.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 8.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 18.00$

New material: Steel Strength, $f_s = f_{sm} = 625.00$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material: Steel Strength, $f_s = f_{sm} = 525.00$

#####

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, Ma = -1.9854E+009
Shear Force, Va = -716139.537
EDGE -B-
Bending Moment, Mb = -3.5795E+008
Shear Force, Vb = 716139.537
BOTH EDGES
Axial Force, F = -5.0716E+006
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 314.1593
-Compression: Asc = 6377.433
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1539.38
-Compression: Asl,com = 1539.38
-Middle: Asl,mid = 3612.832
Mean Diameter of Tension Reinforcement, DbL,ten = 16.57143

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 1.2116E+006$
 V_n ((10.3), ASCE 41-17) = $k_n l V_{CoI} = 1.5146E+006$
 $V_{CoI} = 1.5146E+006$
 $k_n l = 1.00$
displacement_ductility_demand = 1.56089

NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + \phi V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{jacket} \text{Area}_{jacket} + f_c'_{core} \text{Area}_{core}) / \text{Area}_{section} = 10.13333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/d = 2.00$
 $M_u = 3.5795E+008$
 $V_u = 716139.537$
 $d = 0.8 \cdot h = 760.00$
 $N_u = 5.0716E+006$
 $A_g = 427500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 980981.156$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 879645.943$
 $V_{s,j1} = 282743.339$ is calculated for section web jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.27777778$

$V_{s,j2} = 596902.604$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 101335.213$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 420.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 101335.213$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 420.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 723217.666$

$$bw = 450.00$$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END B -

for rotation axis 3 and integ. section (b)

From analysis, chord rotation $\theta = 0.00092788$

$$y = (M_y * L_s / 3) / E_{eff} = 0.00059446 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 1.6308E+009$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 499.8385$$

From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} * E_c * I_g = 4.5707E+014$

$$\text{factor} = 0.70$$

$$A_g = 562500.00$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{\text{jacket}} * \text{Area}_{\text{jacket}} + f_c'_{\text{core}} * \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$$

$$N = 5.0716E+006$$

$$E_c * I_g = E_c_{\text{jacket}} * I_{g_{\text{jacket}}} + E_c_{\text{core}} * I_{g_{\text{core}}} = 6.5295E+014$$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 6.3767581E-006$$

with $f_y = 601.9953$

$$d = 907.00$$

$$y = 0.47957772$$

$$A = 0.0370359$$

$$B = 0.02922707$$

$$\text{with } p_t = 0.0037716$$

$$p_c = 0.0037716$$

$$p_v = 0.00885172$$

$$N = 5.0716E+006$$

$$b = 450.00$$

$$\epsilon = 0.04740904$$

$$y_{\text{comp}} = 2.6024973E-006$$

with $f_c = 18.00$

$$E_c = 19940.411$$

$$y = 0.68835635$$

A = -0.02184193
B = 0.0085861
with Es = 200000.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 6

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 33 and 34)

Analysis: Uniform +X

Check: Chord rotation capacity (u)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 0.80

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.42131

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou}, \min > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.7986448E-005$

EDGE -B-

Shear Force, $V_b = 1.7986448E-005$

BOTH EDGES

Axial Force, $F = -5.0813E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 314.1593$

-Compression: $A_{sl,c} = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 2475.575$

-Middle: $A_{sl,mid} = 2676.637$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.92314$

Member Controlled by Shear ($V_e/V_r > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 2.0922E+006$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 3.1383E+009$

$M_{u1+} = 3.1383E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.6290E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 3.1383E+009$

$M_{u2+} = 3.1383E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 1.6290E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu1+

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 1.9524665E-005$$

$$\mu = 3.1383E+009$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.420296$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01486841$$

$$w_e (5.4c) = 0.08077545$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$fy_{we2} = 656.25$$

$$f_{ce} = 18.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$

$$c = \text{confinement factor} = 1.42131$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 907.50$$

$$fy_1 = 756.25$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu_{1, \text{nominal}}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{\text{jacket}} * A_{sl, \text{ten, jacket}} + fs_{\text{core}} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 756.25$$

$$\text{with } Es_1 = (Es_{\text{jacket}} * A_{sl, \text{ten, jacket}} + Es_{\text{core}} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 200000.00$$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 900.1904$$

$$fy_2 = 750.1586$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 1.00$$

$$su_2 = 0.4 * esu_{2, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{2, \text{nominal}} = 0.08$,

For calculation of $esu_{2, \text{nominal}}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{\text{jacket}} * A_{sl, \text{com, jacket}} + fs_{\text{core}} * A_{sl, \text{com, core}}) / A_{sl, \text{com}} = 750.1586$$

$$\text{with } Es_2 = (Es_{\text{jacket}} * A_{sl, \text{com, jacket}} + Es_{\text{core}} * A_{sl, \text{com, core}}) / A_{sl, \text{com}} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 902.993$$

$$fy_v = 752.4941$$

$$su_v = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su_v = 0.4 * esu_{v, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{v, \text{nominal}} = 0.08$,

considering characteristic value $fsy_v = fsv/1.2$, from table 5.1, TBDY

For calculation of $esu_{v, \text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsy_v = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{\text{jacket}} * A_{sl, \text{mid, jacket}} + fs_{\text{mid}} * A_{sl, \text{mid, core}}) / A_{sl, \text{mid}} = 752.4941$$

$$\text{with } Es_v = (Es_{\text{jacket}} * A_{sl, \text{mid, jacket}} + Es_{\text{mid}} * A_{sl, \text{mid, core}}) / A_{sl, \text{mid}} = 200000.00$$

$$1 = A_{sl, \text{ten}} / (b * d) * (fs_1 / f_c) = 0.09629324$$

$$2 = A_{sl, \text{com}} / (b * d) * (fs_2 / f_c) = 0.15360794$$

$$v = A_{sl, \text{mid}} / (b * d) * (fsv / f_c) = 0.16660079$$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{TBDY}) = 25.58352$$

$$cc (5A.5, \text{TBDY}) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = A_{sl, \text{ten}} / (b * d) * (fs_1 / f_c) = 0.10733965$$

$$2 = A_{sl, \text{com}} / (b * d) * (fs_2 / f_c) = 0.17122928$$

$$v = A_{sl, \text{mid}} / (b * d) * (fsv / f_c) = 0.18571261$$

Case/Assumption: Unconfined full section - Steel rupture

```

' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < vs,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.42075151
MRc (4.17) = 2.3432E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*s,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.47003883
MRo (4.18) = 3.1383E+009
---->
u = cu (4.2) = 1.9524665E-005
Mu = MRo
-----

Calculation of ratio lb/d
-----
Adequate Lap Length: lb/d >= 1
-----
-----

Calculation of Mu1-
-----
-----

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
u = 1.0952761E-005
Mu = 1.6290E+009
-----

with full section properties:
b = 450.00
d = 707.00
d' = 43.00
v = 0.88729156
N = 5.0813E+006
fc = 18.00
co (5A.5, TBDY) = 0.002

```

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01486841$

w_e (5.4c) = 0.08077545

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

c = confinement factor = 1.42131

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 900.1904$

$fy1 = 750.1586$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered

characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s,jacket} \cdot A_{s,ten,jacket} + f_{s,core} \cdot A_{s,ten,core})/A_{s,ten} = 750.1586$

with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core})/A_{s,ten} = 200000.00$

$y_2 = 0.0025$

$sh_2 = 0.008$

$ft_2 = 907.50$

$fy_2 = 756.25$

$su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$

$su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core})/A_{s,com} = 756.25$

with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core})/A_{s,com} = 200000.00$

$y_v = 0.0025$

$sh_v = 0.008$

$ft_v = 902.993$

$fy_v = 752.4941$

$su_v = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 1.00$

$su_v = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 752.4941$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 200000.00$

$1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.32428344$

$2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.20328574$

$v = A_{s,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.35171278$

and confined core properties:

$b = 390.00$

$d = 677.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.39075399$

$2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.24495458$

$v = A_{s,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.42380571$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

$cu (4.10) = 0.82478813$

MRC (4.17) = 1.5333E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ec

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*s,y2$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*s,c$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

---->

*cu (4.11) = 0.83790293

MRO (4.18) = 1.6290E+009

---->

u = cu (4.2) = 1.0952761E-005

Mu = MRO

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2+

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.9524665E-005

Mu = 3.1383E+009

with full section properties:

b = 950.00

d = 707.00

d' = 43.00

v = 0.420296

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - \text{AnoConf}_2)/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$
 The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
 J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.
 $A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.
 $\text{AnoConf}_2 = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 2.724$
 psh_1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 psh_2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.25416$
 psh_1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 psh_2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$
 $s_1 = 100.00$
 $s_2 = 250.00$
 $f_{ywe1} = 781.25$
 $f_{ywe2} = 656.25$
 $f_{ce} = 18.00$
 From ((5.A5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$

$y_1 = 0.0025$
 $sh_1 = 0.008$
 $ft_1 = 907.50$
 $fy_1 = 756.25$
 $su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{min} = lb/ld = 1.00$

$su_1 = 0.4 * esu_{1_nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1_nominal} = 0.08$,

For calculation of $esu_{1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 756.25$

with $Es_1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

$y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 900.1904$
 $fy_2 = 750.1586$
 $su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 1.00$

$su_2 = 0.4 * esu_{2_nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,

For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core})/A_{s,com} = 750.1586$
with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core})/A_{s,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 902.993$
 $f_{y_v} = 752.4941$
 $s_{u_v} = 0.032$
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 1.00$
 $s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}}((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,
considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY
For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{s_v} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 752.4941$
with $E_{s_v} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 200000.00$
 $1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.09629324$
 $2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15360794$
 $v = A_{s,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.16660079$
and confined core properties:
 $b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc}(5A.2, TBDY) = 25.58352$
 $cc(5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.10733965$
 $2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.17122928$
 $v = A_{s,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.18571261$
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
--->
Case/Assumption Rejected.
--->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
--->
 $v < s_{y1}$ - LHS eq.(4.7) is not satisfied
--->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
--->
 $cu(4.10) = 0.42075151$
 $M_{Rc}(4.17) = 2.3432E+009$
--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, 1, 2, v$ normalised to $b_o \cdot d_o$, instead of $b \cdot d$
- f_{cc}, cc parameters of confined concrete, f_{cc}, cc , used in lieu of f_c, e_{cu}
--->
Subcase: Rupture of tension steel
--->
 $v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied
--->
Subcase rejected
--->

New Subcase: Failure of compression zone

--->

$v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

--->

*cu (4.11) = 0.47003883

M_{Ro} (4.18) = 3.1383E+009

--->

u = cu (4.2) = 1.9524665E-005

Mu = M_{Ro}

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0952761E-005

Mu = 1.6290E+009

with full section properties:

b = 450.00

d = 707.00

d' = 43.00

v = 0.88729156

N = 5.0813E+006

f_c = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to bi2/6 as defined at (A.2).

ase2 (>= ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to bi2/6 as defined at (A.2).

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 2.724

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.724

psh1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
psh2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.25416
psh1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 900.1904

fy1 = 750.1586

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = $0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 750.1586$

with Es1 = $(Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = $0.4 * esu2_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = $(fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 756.25$

with Es2 = $(Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.0025

shv = 0.008

ftv = 902.993

fyv = 752.4941

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = $0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and y_v , sh_v , ft_v , fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 752.4941$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.32428344$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.20328574$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.35171278$

and confined core properties:

$b = 390.00$

$d = 677.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

$c =$ confinement factor = 1.42131

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.39075399$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.24495458$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.42380571$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

c_u (4.10) = 0.82478813

M_{Rc} (4.17) = 1.5333E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b , d , d' replaced by geometric parameters of the core: b_o , d_o , d'_o

- N , 1 , 2 , v normalised to $b_o \cdot d_o$, instead of $b \cdot d$

- f_{cc} , cc , used in lieu of f_c , e_{cu}

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$*c_u$ (4.11) = 0.83790293

M_{Ro} (4.18) = 1.6290E+009

---->

$u = c_u$ (4.2) = 1.0952761E-005

$\mu = M_{Ro}$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0879\text{E}+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0879\text{E}+006$

$V_{r1} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = \text{knl} * V_{\text{ColO}}$

$V_{\text{ColO}} = 1.0879\text{E}+006$

$\text{knl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{\text{jacket}} * \text{Area}_{\text{jacket}} + f'_{\text{core}} * \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$, but $f'_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 4.8236\text{E}+008$

$V_u = 1.7986448\text{E}-005$

$d = 0.8 * h = 600.00$

$N_u = 5.0813\text{E}+006$

$A_g = 337500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.0354\text{E}+006$

where:

$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 942477.796$

$V_{s,j1} = 589048.623$ is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$ is multiplied by $\text{Col},j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$ is multiplied by $\text{Col},j2 = 1.00$

$s/d = 0.27777778$

$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 92890.612$

$V_{s,c1} = 92890.612$ is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $\text{Col},c1 = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c2}$ is multiplied by $\text{Col},c2 = 0.00$

$s/d = 1.25$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 699281.943$

$b_w = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0879\text{E}+006$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = \text{knl} * V_{\text{ColO}}$

$V_{\text{ColO}} = 1.0879\text{E}+006$

$\text{knl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 15.20$, but $f_c'^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 4.5550E+008$
 $V_u = 1.7986448E-005$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0813E+006$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0354E+006$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 942477.796$
 $V_{s,j1} = 589048.623$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 699281.943$
 $bw = 450.00$

 End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At local axis: 3

 Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rcjtcs

Constant Properties

 Knowledge Factor, $\phi = 0.80$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
 Concrete Elasticity, $E_c = 19940.411$

```

Steel Elasticity, Es = 200000.00
Existing Column
Existing material of Primary Member: Concrete Strength, fc = fcm = 12.00
Existing material of Primary Member: Steel Strength, fs = fsm = 525.00
Concrete Elasticity, Ec = 16281.278
Steel Elasticity, Es = 200000.00
#####
Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength, fs = 1.25*fsm = 781.25
Existing Column
Existing material: Steel Strength, fs = 1.25*fsm = 656.25
#####
Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.42131
Element Length, L = 3000.00
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lo/lou,min>=1)
No FRP Wrapping
-----

Stepwise Properties
-----
At local axis: 2
EDGE -A-
Shear Force, Va = -5.5168185E-006
EDGE -B-
Shear Force, Vb = 5.5168185E-006
BOTH EDGES
Axial Force, F = -5.0813E+006
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 314.1593
-Compression: Aslc = 6377.433
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1539.38
-Compression: Asl,com = 1539.38
-Middle: Asl,mid = 3612.832
-----
-----

Calculation of Shear Capacity ratio , Ve/Vr = 1.44711
Member Controlled by Shear (Ve/Vr > 1)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 Ve = (Mpr1 + Mpr2)/ln = 1.9243E+006
with
Mpr1 = Max(Mu1+ , Mu1-) = 2.8865E+009
Mu1+ = 2.8865E+009, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
Mu1- = 2.8865E+009, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
Mpr2 = Max(Mu2+ , Mu2-) = 2.8865E+009
Mu2+ = 2.8865E+009, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
Mu2- = 2.8865E+009, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

```

Calculation of Mu1+

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 9.9083764E-006$$

$$Mu = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$co(5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01486841$$

$$we(5.4c) = 0.08077545$$

$$ase(5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase2 (>= ase1) = \text{Max}(((Aconf,max2 - AnoConf2) / Aconf,max2) * (Aconf,min2 / Aconf,max2), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.724$

$$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.724$$

$$psh1(5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1 \text{ (Length of stirrups along Y)} = 2160.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2(5.4d) = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

$$Lstir2 \text{ (Length of stirrups along Y)} = 1568.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.25416$$

$$psh1(5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

$$Lstir1 \text{ (Length of stirrups along X)} = 2560.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2(5.4d), TBDY) = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

$$Lstir2 \text{ (Length of stirrups along X)} = 1968.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fy_{we1} = 781.25$$

$$fy_{we2} = 656.25$$

$$f_{ce} = 18.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$

$$c = \text{confinement factor} = 1.42131$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 907.50$$

$$fy_1 = 756.25$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu_{1, \text{nominal}}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{\text{jacket}} * Asl, \text{ten, jacket} + fs_{\text{core}} * Asl, \text{ten, core}) / Asl, \text{ten} = 756.25$$

$$\text{with } Es_1 = (Es_{\text{jacket}} * Asl, \text{ten, jacket} + Es_{\text{core}} * Asl, \text{ten, core}) / Asl, \text{ten} = 200000.00$$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 907.50$$

$$fy_2 = 756.25$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 1.00$$

$$su_2 = 0.4 * esu_{2, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{2, \text{nominal}} = 0.08$,

For calculation of $esu_{2, \text{nominal}}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{\text{jacket}} * Asl, \text{com, jacket} + fs_{\text{core}} * Asl, \text{com, core}) / Asl, \text{com} = 756.25$$

$$\text{with } Es_2 = (Es_{\text{jacket}} * Asl, \text{com, jacket} + Es_{\text{core}} * Asl, \text{com, core}) / Asl, \text{com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 899.1522$$

$$fy_v = 749.2935$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{\text{jacket}} * Asl, \text{mid, jacket} + fs_{\text{mid}} * Asl, \text{mid, core}) / Asl, \text{mid} = 749.2935$$

$$\text{with } Es_v = (Es_{\text{jacket}} * Asl, \text{mid, jacket} + Es_{\text{mid}} * Asl, \text{mid, core}) / Asl, \text{mid} = 200000.00$$

$$1 = Asl, \text{ten} / (b * d) * (fs_1 / f_c) = 0.15845977$$

$$2 = Asl, \text{com} / (b * d) * (fs_2 / f_c) = 0.15845977$$

$$v = Asl, \text{mid} / (b * d) * (fsv / f_c) = 0.36847443$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{TBDY}) = 25.58352$$

$$cc (5A.5, \text{TBDY}) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = Asl, \text{ten} / (b * d) * (fs_1 / f_c) = 0.18909264$$

$$2 = Asl, \text{com} / (b * d) * (fs_2 / f_c) = 0.18909264$$

$$v = Asl, \text{mid} / (b * d) * (fsv / f_c) = 0.43970658$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
---->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
---->

Case/Assumption Rejected.

---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)

---->
 $v < v_{s,y1}$ - LHS eq.(4.7) is not satisfied
---->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
---->

ϵ_{cu} (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009

---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, \epsilon_1, \epsilon_2, v$ normalised to b_o*d_o , instead of $b*d$
- $\epsilon_c, \epsilon_{cc}$ parameters of confined concrete, f_{cc}, ϵ_{cc} , used in lieu of f_c, ϵ_{cu}

---->
Subcase: Rupture of tension steel

---->
 $v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied
---->
 $v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied
---->

Subcase rejected

---->
New Subcase: Failure of compression zone

---->
 $v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied
---->
 $v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied
---->

ϵ^*_{cu} (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009

---->
 $u = \epsilon^*_{cu}$ (4.2) = 9.9083764E-006
Mu = MRo

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u1} -

Calculation of ultimate curvature ϵ^*_{cu} according to 4.1, Biskinis/Fardis 2013:
 $u = 9.9083764E-006$
Mu = 2.8865E+009

with full section properties:

$b = 450.00$
 $d = 907.00$
 $d' = 43.00$
 $v = 0.69163741$
 $N = 5.0813E+006$
 $f_c = 18.00$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01486841$$

$$w_e \text{ (5.4c)} = 0.08077545$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 907.50$$

$$fy1 = 756.25$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o / l_{ou,min} = l_b / d = 1.00$$

$$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 756.25$

with $Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 907.50$

$fy2 = 756.25$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lo_{ou,min} = lb/lb_{,min} = 1.00$

$su2 = 0.4 \cdot esu2_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 756.25$

with $Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 899.1522$

$fyv = 749.2935$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lo_{ou,min} = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 749.2935$

with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.15845977$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.15845977$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.36847443$

and confined core properties:

$b = 390.00$

$d = 877.00$

$d' = 13.00$

$fcc (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.18909264$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.18909264$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is not satisfied

---->

$v < vs,c$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s,y1$ - LHS eq.(4.7) is not satisfied

---->

$v < vc,y1$ - RHS eq.(4.6) is satisfied

---->

cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009

--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu

--->
Subcase: Rupture of tension steel

--->
 $v^* < v^*s_y2$ - LHS eq.(4.5) is not satisfied

--->
 $v^* < v^*s_c$ - LHS eq.(4.5) is not satisfied

--->
Subcase rejected

--->
New Subcase: Failure of compression zone

--->
 $v^* < v^*c_y2$ - LHS eq.(4.6) is not satisfied

--->
 $v^* < v^*c_y1$ - RHS eq.(4.6) is not satisfied

--->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009

--->
u = cu (4.2) = 9.9083764E-006
Mu = MRo

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2+

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 9.9083764E-006
Mu = 2.8865E+009

with full section properties:

b = 450.00
d = 907.00
d' = 43.00
v = 0.69163741
N = 5.0813E+006

fc = 18.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01486841$

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - \text{AnoConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{,min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 2.724$
 psh_1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
 psh_2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.25416$
 psh_1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
 psh_2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 907.50

fy1 = 756.25

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su1 = $0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 756.25$

with Es1 = $(E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = $0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of $es_{u2_nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 756.25$

with $Es_2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$y_v = 0.0025$

$sh_v = 0.008$

$ft_v = 899.1522$

$fy_v = 749.2935$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 1.00$

$suv = 0.4 \cdot es_{uv_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{uv_nominal} = 0.08$,

considering characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered

characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot Asl_{mid,jacket} + f_{s,mid} \cdot Asl_{mid,core}) / Asl_{mid} = 749.2935$

with $E_{sv} = (E_{s,jacket} \cdot Asl_{mid,jacket} + E_{s,mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.15845977$

$2 = Asl_{com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.15845977$

$v = Asl_{mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.36847443$

and confined core properties:

$b = 390.00$

$d = 877.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = Asl_{ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.18909264$

$2 = Asl_{com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.18909264$

$v = Asl_{mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

Case/Assumption Rejected.

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

$cu (4.10) = 0.6344264$

$M_{Rc} (4.17) = 2.3433E+009$

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b , d , d' replaced by geometric parameters of the core: b_o , d_o , d'_o

- N , 1 , 2 , v normalised to $b_o \cdot d_o$, instead of $b \cdot d$

- f_{cc} , cc , parameters of confined concrete, f_{cc} , cc , used in lieu of f_c , ecu

Subcase: Rupture of tension steel

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

Subcase rejected

--->
New Subcase: Failure of compression zone

--->
 $v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

--->
 $v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

--->
 $*cu$ (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009

--->
 $u = cu$ (4.2) = 9.9083764E-006
Mu = MRo

Calculation of ratio lb/ld

Adequate Lap Length: lb/ld >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 9.9083764E-006$
Mu = 2.8865E+009

with full section properties:

b = 450.00
d = 907.00
d' = 43.00
v = 0.69163741
N = 5.0813E+006

fc = 18.00
co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01486841$

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = $(ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$

$ase1 = Max(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $bi^2/6$ as defined at (A.2).

$ase2 (>= ase1) = Max(((Aconf,max2 - AnoConf2) / Aconf,max2) * (Aconf,min2 / Aconf,max2), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $bi^2/6$ as defined at (A.2).

$psh,min * Fywe = Min(psh,x * Fywe, psh,y * Fywe) = 2.724$

$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.724$
 $psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
 $psh2 (5.4d) = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.25416$
 $psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
 $psh2 ((5.4d), TBDY) = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00
s1 = 100.00
s2 = 250.00
fywe1 = 781.25
fywe2 = 656.25
fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307
c = confinement factor = 1.42131

y1 = 0.0025
sh1 = 0.008
ft1 = 907.50
fy1 = 756.25
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 907.50
fy2 = 756.25
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 899.1522
fyv = 749.2935
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{suv_nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered
characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 749.2935$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.15845977$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.15845977$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.36847443$

and confined core properties:

$b = 390.00$

$d = 877.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.18909264$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.18909264$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

c_u (4.10) = 0.6344264

M_{Rc} (4.17) = 2.3433E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o

- $N, 1, 2, v$ normalised to $b_o \cdot d_o$, instead of $b \cdot d$

- parameters of confined concrete, f_{cc}, cc , used in lieu of f_c, e_{cu}

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$*c_u$ (4.11) = 0.71499649

M_{Ro} (4.18) = 2.8865E+009

---->

$u = c_u$ (4.2) = 9.9083764E-006

$M_u = M_{Ro}$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.3298\text{E}+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.3298\text{E}+006$

$V_{r1} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{\text{ColO}}$

$V_{\text{ColO}} = 1.3298\text{E}+006$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c, \text{jacket}} * \text{Area}_{\text{jacket}} + f'_{c, \text{core}} * \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1.7267\text{E}+008$

$V_u = 5.5168185\text{E}-006$

$d = 0.8 * h = 760.00$

$N_u = 5.0813\text{E}+006$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s, \text{jacket}} + V_{s, \text{core}} = 1.2262\text{E}+006$

where:

$V_{s, \text{jacket}} = V_{s, j1} + V_{s, j2} = 1.0996\text{E}+006$

$V_{s, j1} = 353429.174$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s, j1}$ is multiplied by $\text{Col}, j1 = 1.00$

$s/d = 0.27777778$

$V_{s, j2} = 746128.255$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s, j2}$ is multiplied by $\text{Col}, j2 = 1.00$

$s/d = 0.13157895$

$V_{s, \text{core}} = V_{s, c1} + V_{s, c2} = 126669.016$

$V_{s, c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s, c1}$ is multiplied by $\text{Col}, c1 = 0.00$

$s/d = 1.25$

$V_{s, c2} = 126669.016$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s, c2}$ is multiplied by $\text{Col}, c2 = 1.00$

$s/d = 0.41666667$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 885757.128$

$b_w = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.3298\text{E}+006$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{\text{ColO}}$

$V_{\text{ColO}} = 1.3298\text{E}+006$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1.6609E+008$

$\nu_u = 5.5168185E-006$

$d = 0.8 \cdot h = 760.00$

$N_u = 5.0813E+006$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.2262E+006$

where:

$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 1.0996E+006$

$V_{s,j1} = 353429.174$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$ is multiplied by $\text{Col},j1 = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$ is multiplied by $\text{Col},j2 = 1.00$

$s/d = 0.13157895$

$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 126669.016$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $\text{Col},c1 = 0.00$

$s/d = 1.25$

$V_{s,c2} = 126669.016$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c2}$ is multiplied by $\text{Col},c2 = 1.00$

$s/d = 0.41666667$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 885757.128$

$b_w = 450.00$

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
 Concrete Elasticity, $E_c = 19940.411$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
 Concrete Elasticity, $E_c = 16281.278$
 Steel Elasticity, $E_s = 200000.00$
 Max Height, $H_{max} = 750.00$
 Min Height, $H_{min} = 450.00$
 Max Width, $W_{max} = 950.00$
 Min Width, $W_{min} = 450.00$
 Eccentricity, $Ecc = 250.00$
 Jacket Thickness, $t_j = 100.00$
 Cover Thickness, $c = 25.00$
 Element Length, $L = 3000.00$
 Primary Member
 Ribbed Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_b/d >= 1$)
 No FRP Wrapping

 Stepwise Properties

Bending Moment, $M = 4.5517E+008$
 Shear Force, $V_2 = 716139.537$
 Shear Force, $V_3 = -3.11526$
 Axial Force, $F = -5.0716E+006$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 314.1593$
 -Compression: $A_{sc} = 6377.433$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 1539.38$
 -Compression: $A_{st,com} = 2475.575$
 -Middle: $A_{st,mid} = 2676.637$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten,jacket} = 1231.504$
 -Compression: $A_{st,com,jacket} = 1859.823$
 -Middle: $A_{st,mid,jacket} = 2060.885$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten,core} = 307.8761$
 -Compression: $A_{st,com,core} = 615.7522$
 -Middle: $A_{st,mid,core} = 615.7522$
 Mean Diameter of Tension Reinforcement, $Db_L = 16.57143$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.00988092$
 $u = y + p = 0.01235115$

 - Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.01235115$ ((4.29), Biskinis Phd)
 $M_y = 1.8639E+009$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 6000.00
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 3.0181E+014$
 $factor = 0.70$
 $A_g = 562500.00$
 Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$
 $N = 5.0716E+006$
 $E_c * I_g = E_c * I_{g,jacket} + E_c * I_{g,core} = 4.3116E+014$

Calculation of Yielding Moment M_y

Calculation of ρ_y and M_y according to Annex 7 -

Assuming neutral axis within flange ($\rho_y < t/d$, compression zone rectangular) with:

flange width, $b = 950.00$

web width, $b_w = 450.00$

flange thickness, $t = 450.00$

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 7.1326140\text{E-}006$$

with $f_y = 601.9953$

$$d = 707.00$$

$$y = 0.40310908$$

$$A = 0.02250607$$

$$B = 0.01717304$$

$$\text{with } p_t = 0.00229194$$

$$p_c = 0.00368581$$

$$p_v = 0.00398517$$

$$N = 5.0716\text{E}+006$$

$$b = 950.00$$

$$\rho_y = 0.06082037$$

$$y_{\text{comp}} = 4.9351105\text{E-}006$$

with $f_c = 18.00$

$$E_c = 19940.411$$

$$y = 0.46568752$$

$$A = -0.01327296$$

$$B = 0.00462988$$

$$\text{with } E_s = 200000.00$$

CONFIRMATION: $y = 0.46568752 < t/d$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ_p -

From table 10-8: $\rho_p = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/d \geq 1$

$$\text{shear control ratio } V_y/E/ColOE = 1.92314$$

$$d = d_{\text{external}} = 707.00$$

$$s = s_{\text{external}} = 100.00$$

$$- t = s_1 + s_2 + 2 \cdot t_f/b_w \cdot (f_{fe}/f_s) = 0.0035764$$

$$\text{jacket: } s_1 = A_{v1} \cdot L_{\text{stir1}} / (s_1 \cdot A_g) = 0.00301593$$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir1}} = 2160.00$, is the total Length of all stirrups parallel to loading (shear) direction

$$s_1 = 100.00$$

$$\text{core: } s_2 = A_{v2} \cdot L_{\text{stir2}} / (s_2 \cdot A_g) = 0.00056047$$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir2}} = 1568.00$, is the total Length of all stirrups parallel to loading (shear) direction

$$s_2 = 250.00$$

The term $2 \cdot t_f/b_w \cdot (f_{fe}/f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f/b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe}/f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$$N_{UD} = 5.0716\text{E}+006$$

$$A_g = 562500.00$$

$$f_cE = (f_c \cdot \text{Area}_{\text{jacket}} + f_c \cdot \text{Area}_{\text{core}}) / \text{section_area} = 15.20$$

$$f_yE = (f_y \cdot \text{ext_Long_Reinf} \cdot \text{Area}_{\text{ext_Long_Reinf}} + f_y \cdot \text{int_Long_Reinf} \cdot \text{Area}_{\text{int_Long_Reinf}}) / \text{Area}_{\text{Tot_Long_Rein}} = 601.9953$$

$$f_ytE = (f_y \cdot \text{ext_Trans_Reinf} \cdot s_1 + f_y \cdot \text{int_Trans_Reinf} \cdot s_2) / (s_1 + s_2) = 609.3286$$


$$p_l = \text{Area}_{\text{Tot_Long_Rein}} / (b \cdot d) = 0.00996292$$

b = 950.00
d = 707.00
f_{cE} = 15.20

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (b)

Calculation No. 7

column C1, Floor 1
Limit State: Operational Level (data interpolation between analysis steps 33 and 34)
Analysis: Uniform +X
Check: Shear capacity VR_d
Edge: End
Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (b)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$
Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.
Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 12.00$
New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$
Concrete Elasticity, $E_c = 19940.411$
Steel Elasticity, $E_s = 200000.00$
Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 8.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$
 Concrete Elasticity, $E_c = 16281.278$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of γ for displacement ductility demand,
 the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
 Deformation-Controlled Action (Table C7-1, ASCE 41-17).
 Jacket
 New material: Concrete Strength, $f_c = f_{cm} = 18.00$
 New material: Steel Strength, $f_s = f_{sm} = 625.00$
 Existing Column
 Existing material: Concrete Strength, $f_c = f_{cm} = 12.00$
 Existing material: Steel Strength, $f_s = f_{sm} = 525.00$
 #####
 Max Height, $H_{max} = 750.00$
 Min Height, $H_{min} = 450.00$
 Max Width, $W_{max} = 950.00$
 Min Width, $W_{min} = 450.00$
 Eccentricity, $Ecc = 250.00$
 Jacket Thickness, $t_j = 100.00$
 Cover Thickness, $c = 25.00$
 Element Length, $L = 3000.00$
 Primary Member
 Ribbed Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_o/l_{o,min} = l_b/d >= 1$)
 No FRP Wrapping

 Stepwise Properties

EDGE -A-
 Bending Moment, $M_a = -5.5401E+008$
 Shear Force, $V_a = 3.11526$
 EDGE -B-
 Bending Moment, $M_b = 4.5517E+008$
 Shear Force, $V_b = -3.11526$
 BOTH EDGES
 Axial Force, $F = -5.0716E+006$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{sl,t} = 314.1593$
 -Compression: $A_{sl,c} = 6377.433$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{sl,ten} = 1539.38$
 -Compression: $A_{sl,com} = 2475.575$
 -Middle: $A_{sl,mid} = 2676.637$
 Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.57143$

 Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 734492.961$
 V_n ((10.3), ASCE 41-17) = $k_n l^* V_{CoI} = 918116.201$
 $V_{CoI} = 918116.201$
 $k_n = 1.00$
 displacement_ductility_demand = 0.14955718

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + \phi * V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 Mean concrete strength: $f'_c = (f'_c_jacket * Area_jacket + f'_c_core * Area_core) / Area_section = 10.13333$, but $f'_c^{0.5} < =$
 8.3 MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$

$\mu_u = 4.5517E+008$
 $V_u = 3.11526$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0716E+006$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 828294.726$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 753982.237$
 $V_{s,j1} = 471238.898$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 282743.339$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 74312.489$
 $V_{s,c1} = 74312.489$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 570961.316$
 $bw = 450.00$

displacement ductility demand is calculated as ϕ / y

- Calculation of ϕ / y for END B -
for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 0.0018472$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.01235115$ ((4.29), Biskinis Phd))
 $M_y = 1.8639E+009$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 6000.00
 From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 3.0181E+014$
 $factor = 0.70$
 $A_g = 562500.00$
 Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 15.20$
 $N = 5.0716E+006$
 $E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 4.3116E+014$

Calculation of Yielding Moment M_y

Calculation of ϕ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:
flange width, $b = 950.00$

web width, bw = 450.00
flange thickness, t = 450.00

y = Min(y_ten, y_com)
y_ten = 7.1326140E-006
with fy = 601.9953
d = 707.00
y = 0.40310908
A = 0.02250607
B = 0.01717304
with pt = 0.00229194
pc = 0.00368581
pv = 0.00398517
N = 5.0716E+006
b = 950.00
" = 0.06082037
y_comp = 4.9351105E-006
with fc = 18.00
Ec = 19940.411
y = 0.46568752
A = -0.01327296
B = 0.00462988
with Es = 200000.00
CONFIRMATION: y = 0.46568752 < t/d

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (b)

Calculation No. 8

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 33 and 34)

Analysis: Uniform +X

Check: Chord rotation capacity (u)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
 Concrete Elasticity, $E_c = 19940.411$
 Steel Elasticity, $E_s = 200000.00$

Existing Column
 Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
 Concrete Elasticity, $E_c = 16281.278$
 Steel Elasticity, $E_s = 200000.00$

 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$
 Existing Column
 Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$
 #####

Max Height, $H_{max} = 750.00$
 Min Height, $H_{min} = 450.00$
 Max Width, $W_{max} = 950.00$
 Min Width, $W_{min} = 450.00$
 Eccentricity, $Ecc = 250.00$
 Jacket Thickness, $t_j = 100.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.42131
 Element Length, $L = 3000.00$

Primary Member
 Ribbed Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_o/l_{ou, min} >= 1$)
 No FRP Wrapping

Stepwise Properties

At local axis: 3
 EDGE -A-
 Shear Force, $V_a = -1.7986448E-005$
 EDGE -B-

Shear Force, $V_b = 1.7986448E-005$
BOTH EDGES
Axial Force, $F = -5.0813E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 314.1593$
-Compression: $As_c = 6377.433$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1539.38$
-Compression: $As_{c,com} = 2475.575$
-Middle: $As_{c,mid} = 2676.637$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.92314$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 2.0922E+006$
with
 $M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.1383E+009$
 $Mu_{1+} = 3.1383E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 1.6290E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.1383E+009$
 $Mu_{2+} = 3.1383E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 1.6290E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.9524665E-005$
 $Mu = 3.1383E+009$

with full section properties:

$b = 950.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.420296$
 $N = 5.0813E+006$
 $f_c = 18.00$
 α_1 (5A.5, TBDY) = 0.002
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.01486841$
 ω_e (5.4c) = 0.08077545
 ω_{se} ((5.4d), TBDY) = $(\omega_{se1} * A_{ext} + \omega_{se2} * A_{int}) / A_{sec} = 0.53375773$
 $\omega_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization
of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)
"Theoretical Stress-Strain Model for Confined Concrete."
J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and
is calculated as the area of core enclosed by the center lines of the external perimeter hoops.
 $A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and
is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length
equal to half the clear spacing between external hoops.
 $A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $\omega_{se2} (>= \omega_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization
of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.
 $A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$
 $psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 $psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$
 $psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 $psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 781.25$
 $f_{ywe2} = 656.25$
 $f_{ce} = 18.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 907.50$
 $fy1 = 756.25$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{min} = lb/ld = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 756.25$

with $Es1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 900.1904$
 $fy2 = 750.1586$
 $su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 1.00$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 750.1586$

with $Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.0025$

```

shv = 0.008
ftv = 902.993
fyv = 752.4941
suv = 0.032
  using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
  and also multiplied by the shear_factor according to 15.7.1.4, with
  Shear_factor = 1.00
  lo/lou,min = lb/lb = 1.00
  suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032
  From table 5A.1, TBDY: esuv_nominal = 0.08,
  considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
  For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
  characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.
  y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.
  with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941
  with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
  1 = Asl,ten/(b*d)*(fs1/fc) = 0.09629324
  2 = Asl,com/(b*d)*(fs2/fc) = 0.15360794
  v = Asl,mid/(b*d)*(fsv/fc) = 0.16660079
and confined core properties:
b = 890.00
d = 677.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
  c = confinement factor = 1.42131
  1 = Asl,ten/(b*d)*(fs1/fc) = 0.10733965
  2 = Asl,com/(b*d)*(fs2/fc) = 0.17122928
  v = Asl,mid/(b*d)*(fsv/fc) = 0.18571261
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.42075151
MRc (4.17) = 2.3432E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*,y1 - RHS eq.(4.6) is not satisfied

```

--->

$$*cu(4.11) = 0.47003883$$

$$MRo(4.18) = 3.1383E+009$$

--->

$$u = cu(4.2) = 1.9524665E-005$$

$$Mu = MRo$$

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 1.0952761E-005$$

$$Mu = 1.6290E+009$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.88729156$$

$$N = 5.0813E+006$$

$$fc = 18.00$$

$$co(5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01486841$$

$$we(5.4c) = 0.08077545$$

$$ase((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $bi^2/6$ as defined at (A.2).

$$ase2 (>=ase1) = \text{Max}(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $bi^2/6$ as defined at (A.2).

$$psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 2.724$$

$$psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.724$$

$$psh1((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00301593$$

$$Lstir1(\text{Length of stirrups along Y}) = 2160.00$$

$$Astir1(\text{stirrups area}) = 78.53982$$

$$psh2(5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047$$

$$Lstir2(\text{Length of stirrups along Y}) = 1568.00$$

Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.25416
psh₁ ((5.4d), TBDY) = Lstir₁*Astir₁/(Asec*s₁) = 0.00357443
Lstir₁ (Length of stirrups along X) = 2560.00
Astir₁ (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = Lstir₂*Astir₂/(Asec*s₂) = 0.00070345
Lstir₂ (Length of stirrups along X) = 1968.00
Astir₂ (stirrups area) = 50.26548

Asec = 562500.00

s₁ = 100.00

s₂ = 250.00

fywe₁ = 781.25

fywe₂ = 656.25

fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y₁ = 0.0025

sh₁ = 0.008

ft₁ = 900.1904

fy₁ = 750.1586

su₁ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*Asl_{ten,jacket} + fs_{core}*Asl_{ten,core})/Asl_{ten} = 750.1586

with Es₁ = (Es_{jacket}*Asl_{ten,jacket} + Es_{core}*Asl_{ten,core})/Asl_{ten} = 200000.00

y₂ = 0.0025

sh₂ = 0.008

ft₂ = 907.50

fy₂ = 756.25

su₂ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*Asl_{com,jacket} + fs_{core}*Asl_{com,core})/Asl_{com} = 756.25

with Es₂ = (Es_{jacket}*Asl_{com,jacket} + Es_{core}*Asl_{com,core})/Asl_{com} = 200000.00

y_v = 0.0025

sh_v = 0.008

ft_v = 902.993

fy_v = 752.4941

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_{nominal} = 0.08,

considering characteristic value fsy_v = fs_v/1.2, from table 5.1, TBDY

For calculation of esuv_{nominal} and y_v, sh_v,ft_v,fy_v, it is considered
characteristic value fsy_v = fs_v/1.2, from table 5.1, TBDY.

y_v, sh_v,ft_v,fy_v, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs_v = (fs_{jacket}*Asl_{mid,jacket} + fs_{mid}*Asl_{mid,core})/Asl_{mid} = 752.4941

with Es_v = (Es_{jacket}*Asl_{mid,jacket} + Es_{mid}*Asl_{mid,core})/Asl_{mid} = 200000.00

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.32428344$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.20328574$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.35171278$$

and confined core properties:

$$b = 390.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 25.58352$$

$$c_c (5A.5, TBDY) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.39075399$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.24495458$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.42380571$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < v_{s,y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

$$c_u (4.10) = 0.82478813$$

$$M_{Rc} (4.17) = 1.5333E+009$$

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- N_1, N_2, v normalised to b_o*d_o , instead of $b*d$
- parameters of confined concrete, f_{cc}, c_c , used in lieu of f_c, c_c

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$$*c_u (4.11) = 0.83790293$$

$$M_{Ro} (4.18) = 1.6290E+009$$

---->

$$u = c_u (4.2) = 1.0952761E-005$$

$$\mu_u = M_{Ro}$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 1.9524665E-005$$

$$\mu = 3.1383E+009$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.420296$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.01486841$$

$$\phi_{cc} \text{ (5.4c)} = 0.08077545$$

$$\text{ase (5.4d), TBDY) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.53375773$$

$$\text{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1})/A_{conf,max1}) * (A_{conf,min1}/A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{ase2} (>= \text{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{psh}_{min} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 2.724$$

$$\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.724$$

$$\text{psh}_1 \text{ (5.4d), TBDY) = } L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y) = } 2160.00$$

$$A_{stir1} \text{ (stirrups area) = } 78.53982$$

$$\text{psh}_2 \text{ (5.4d) = } L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y) = } 1568.00$$

$$A_{stir2} \text{ (stirrups area) = } 50.26548$$

$$\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 3.25416$$

$$\text{psh}_1 \text{ ((5.4d), TBDY) = } L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X) = } 2560.00$$

$$A_{stir1} \text{ (stirrups area) = } 78.53982$$

$$\text{psh}_2 \text{ ((5.4d), TBDY) = } L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X) = } 1968.00$$

$$A_{stir2} \text{ (stirrups area) = } 50.26548$$

$$A_{sec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 907.50$
 $fy1 = 756.25$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou,min = lb/ld = 1.00$

$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 756.25$

with $Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 900.1904$
 $fy2 = 750.1586$
 $su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou,min = lb/lb,min = 1.00$

$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 750.1586$

with $Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00$

$yv = 0.0025$
 $shv = 0.008$
 $ftv = 902.993$
 $fyv = 752.4941$
 $suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou,min = lb/ld = 1.00$

$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 752.4941$

with $Es_v = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$

$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.09629324$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.15360794$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.16660079$

and confined core properties:

$b = 890.00$
 $d = 677.00$
 $d' = 13.00$

$fcc (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.10733965$

$2 = Asl,com / (b * d) * (fs2 / fc) = 0.17122928$

$v = Asl,mid / (b * d) * (fsv / fc) = 0.18571261$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is not satisfied

---->

v < vs,c - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)

---->

v < vs,y1 - LHS eq.(4.7) is not satisfied

---->

v < vc,y1 - RHS eq.(4.6) is satisfied

---->

cu (4.10) = 0.42075151

MRC (4.17) = 2.3432E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu

---->

Subcase: Rupture of tension steel

---->

v* < v*s,y2 - LHS eq.(4.5) is not satisfied

---->

v* < v*s,c - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

v* < v*c,y2 - LHS eq.(4.6) is not satisfied

---->

v* < v*c,y1 - RHS eq.(4.6) is not satisfied

---->

*cu (4.11) = 0.47003883

MRO (4.18) = 3.1383E+009

---->

u = cu (4.2) = 1.9524665E-005

Mu = MRO

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0952761E-005

Mu = 1.6290E+009

with full section properties:

b = 450.00

d = 707.00

d' = 43.00

v = 0.88729156

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00621307$

c = confinement factor = 1.42131

$y_1 = 0.0025$

$sh_1 = 0.008$

$ft_1 = 900.1904$

$fy_1 = 750.1586$

$su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o / l_{ou,min} = l_b / l_d = 1.00$

$su_1 = 0.4 * esu_1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_1_{nominal} = 0.08$,

For calculation of $esu_1_{nominal}$ and y_1 , sh_1 , ft_1 , fy_1 , it is considered characteristic value $fsy_1 = fs_1 / 1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

```

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 750.1586
with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00
y2 = 0.0025
sh2 = 0.008
ft2 = 907.50
fy2 = 756.25
su2 = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/lb,min = 1.00
su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esu2_nominal = 0.08,
For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lc)^ 2/3), from 10.3.5, ASCE 41-17.
with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25
with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00
yv = 0.0025
shv = 0.008
ftv = 902.993
fyv = 752.4941
suv = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/lc = 1.00
suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esuv_nominal = 0.08,
considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lc)^ 2/3), from 10.3.5, ASCE 41-17.
with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941
with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.32428344
2 = Asl,com/(b*d)*(fs2/fc) = 0.20328574
v = Asl,mid/(b*d)*(fsv/fc) = 0.35171278
and confined core properties:
b = 390.00
d = 677.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.39075399
2 = Asl,com/(b*d)*(fs2/fc) = 0.24495458
v = Asl,mid/(b*d)*(fsv/fc) = 0.42380571
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.82478813
MRc (4.17) = 1.5333E+009
---->

```

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ec

Subcase: Rupture of tension steel

$v^* < v^*s,y2$ - LHS eq.(4.5) is not satisfied

$v^* < v^*s,c$ - LHS eq.(4.5) is not satisfied

Subcase rejected

New Subcase: Failure of compression zone

$v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

*cu (4.11) = 0.83790293

MRo (4.18) = 1.6290E+009

u = cu (4.2) = 1.0952761E-005

Mu = MRo

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 1.0879E+006

Calculation of Shear Strength at edge 1, Vr1 = 1.0879E+006

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0

VCol0 = 1.0879E+006

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 15.20, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 4.8236E+008

Vu = 1.7986448E-005

d = 0.8*h = 600.00

Nu = 5.0813E+006

Ag = 337500.00

From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 1.0354E+006

where:

Vs,jacket = Vs,j1 + Vs,j2 = 942477.796

Vs,j1 = 589048.623 is calculated for section web jacket, with:

d = 600.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.16666667

Vs,j2 = 353429.174 is calculated for section flange jacket, with:

d = 360.00

Av = 157079.633

fy = 625.00

$s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 699281.943$
 $bw = 450.00$

 Calculation of Shear Strength at edge 2, $V_{r2} = 1.0879E+006$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$
 $V_{Col0} = 1.0879E+006$
 $knl = 1$ (zero step-static loading)

 NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)
 Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 15.20$, but $f'_c^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $M_u = 4.5550E+008$
 $V_u = 1.7986448E-005$
 $d = 0.8 * h = 600.00$
 $N_u = 5.0813E+006$
 $Ag = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0354E+006$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 942477.796$
 $V_{s,j1} = 589048.623$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$

Av = 100530.965
fy = 525.00
s = 250.00
Vs,c2 is multiplied by Col,c2 = 0.00
s/d = 1.25
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 699281.943
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 0.80
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Primary Member: Concrete Strength, fc = fcm = 18.00
New material of Primary Member: Steel Strength, fs = fsm = 625.00
Concrete Elasticity, Ec = 19940.411
Steel Elasticity, Es = 200000.00
Existing Column
Existing material of Primary Member: Concrete Strength, fc = fcm = 12.00
Existing material of Primary Member: Steel Strength, fs = fsm = 525.00
Concrete Elasticity, Ec = 16281.278
Steel Elasticity, Es = 200000.00

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength, fs = 1.25*fsm = 781.25
Existing Column
Existing material: Steel Strength, fs = 1.25*fsm = 656.25

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.42131
Element Length, L = 3000.00
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lo/lou,min>=1)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -5.5168185E-006

EDGE -B-

Shear Force, $V_b = 5.5168185E-006$

BOTH EDGES

Axial Force, $F = -5.0813E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 314.1593$

-Compression: $A_{sc} = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{s,ten} = 1539.38$

-Compression: $A_{s,com} = 1539.38$

-Middle: $A_{s,mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.44711$

Member Controlled by Shear ($V_e/V_r > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 1.9243E+006$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 2.8865E+009$

$Mu_{1+} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 2.8865E+009$

$Mu_{2+} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 9.9083764E-006$

$M_u = 2.8865E+009$

with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.69163741$

$N = 5.0813E+006$

$f_c = 18.00$

$\alpha_{co} (5A.5, TBDY) = 0.002$

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.01486841$

$\omega_e (5.4c) = 0.08077545$

$\alpha_{se} ((5.4d), TBDY) = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.53375773$

$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$\alpha_{se2} (> \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)
"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and
is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and
is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length
equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{,min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$

$psh1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2 (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$

$psh1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2 ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou_{,min} = lb/d = 1.00$

$su1 = 0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 756.25$

with $Es1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 907.50$

$fy2 = 756.25$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou_{,min} = lb/lb_{,min} = 1.00$

$su2 = 0.4 * esu2_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 756.25$

with $Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 899.1522$
 $fy_v = 749.2935$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 1.00$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 749.2935$
 with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.15845977$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.15845977$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.36847443$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.18909264$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.18909264$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.43970658$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s_{y1}$ - LHS eq.(4.7) is not satisfied
 --->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.6344264$
 $MRC (4.17) = 2.3433E+009$
 --->
 New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
 In expressions below, the following modifications have been made
 - b, d, d' replaced by geometric parameters of the core: $bo, do, d'o$
 - $N, 1, 2, v$ normalised to $bo * do$, instead of $b * d$
 - - parameters of confined concrete, fcc, cc , used in lieu of fc, ecu
 --->
 Subcase: Rupture of tension steel
 --->
 $v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied
 --->
 $v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied
 --->
 Subcase rejected
 --->
 New Subcase: Failure of compression zone
 --->
 $v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied
 --->

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

---->

$$*cu(4.11) = 0.71499649$$

$$MRo(4.18) = 2.8865E+009$$

---->

$$u = cu(4.2) = 9.9083764E-006$$

$$Mu = MRo$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.9083764E-006$$

$$Mu = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$fc = 18.00$$

$$co(5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01486841$$

$$we(5.4c) = 0.08077545$$

$$ase((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of $AnoConf$, $Aconf,min$ and $Aconf,max$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$Aconf,max1 = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$Aconf,min1 = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $Aconf,max1$ by a length equal to half the clear spacing between external hoops.

$AnoConf1 = 173066.667$ is the unconfined external core area which is equal to $bi^2/6$ as defined at (A.2).

$$ase2 (\geq ase1) = \text{Max}(((Aconf,max2 - AnoConf2) / Aconf,max2) * (Aconf,min2 / Aconf,max2), 0) = 0.53375773$$

The definitions of $AnoConf$, $Aconf,min$ and $Aconf,max$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$Aconf,max2 = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$Aconf,min2 = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $Aconf,max2$ by a length equal to half the clear spacing between internal hoops.

$AnoConf2 = 110709.333$ is the unconfined internal core area which is equal to $bi^2/6$ as defined at (A.2).

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.724$$

$$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.724$$

$$psh1((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1(\text{Length of stirrups along } Y) = 2160.00$$

$$Astir1(\text{stirrups area}) = 78.53982$$

$$psh2(5.4d) = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.25416
psh₁ ((5.4d), TBDY) = Lstir₁*Astir₁/(Asec*s₁) = 0.00357443
Lstir₁ (Length of stirrups along X) = 2560.00
Astir₁ (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = Lstir₂*Astir₂/(Asec*s₂) = 0.00070345
Lstir₂ (Length of stirrups along X) = 1968.00
Astir₂ (stirrups area) = 50.26548

Asec = 562500.00
s₁ = 100.00
s₂ = 250.00

fywe₁ = 781.25
fywe₂ = 656.25
fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307
c = confinement factor = 1.42131

y₁ = 0.0025
sh₁ = 0.008
ft₁ = 907.50
fy₁ = 756.25
su₁ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 1.00

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*Asl_{ten,jacket} + fs_{core}*Asl_{ten,core})/Asl_{ten} = 756.25

with Es₁ = (Es_{jacket}*Asl_{ten,jacket} + Es_{core}*Asl_{ten,core})/Asl_{ten} = 200000.00

y₂ = 0.0025
sh₂ = 0.008
ft₂ = 907.50
fy₂ = 756.25
su₂ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 1.00

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*Asl_{com,jacket} + fs_{core}*Asl_{com,core})/Asl_{com} = 756.25

with Es₂ = (Es_{jacket}*Asl_{com,jacket} + Es_{core}*Asl_{com,core})/Asl_{com} = 200000.00

y_v = 0.0025
sh_v = 0.008
ft_v = 899.1522
fy_v = 749.2935
su_v = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 1.00

su_v = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_{nominal} = 0.08,

considering characteristic value fsy_v = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_{nominal} and y_v, sh_v,ft_v,fy_v, it is considered
characteristic value fsy_v = fsv/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fsv = (fs_{jacket}*Asl_{mid,jacket} + fs_{mid}*Asl_{mid,core})/Asl_{mid} = 749.2935

```

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977
2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977
v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443
and confined core properties:
b = 390.00
d = 877.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264
2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264
v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*s,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009
---->
u = cu (4.2) = 9.9083764E-006
Mu = MRo
-----

Calculation of ratio lb/d
-----
Adequate Lap Length: lb/d >= 1
-----
-----
-----
Calculation of Mu2+

```

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.9083764E-006$$

$$\mu = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.01486841$$

$$w_e(5.4c) = 0.08077545$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2}(5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2}((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$

$$c = \text{confinement factor} = 1.42131$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 907.50$$

$$fy_1 = 756.25$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu_{1, \text{nominal}}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{\text{jacket}} * Asl, \text{ten, jacket} + fs_{\text{core}} * Asl, \text{ten, core}) / Asl, \text{ten} = 756.25$$

$$\text{with } Es_1 = (Es_{\text{jacket}} * Asl, \text{ten, jacket} + Es_{\text{core}} * Asl, \text{ten, core}) / Asl, \text{ten} = 200000.00$$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 907.50$$

$$fy_2 = 756.25$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 1.00$$

$$su_2 = 0.4 * esu_{2, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{2, \text{nominal}} = 0.08$,

For calculation of $esu_{2, \text{nominal}}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{\text{jacket}} * Asl, \text{com, jacket} + fs_{\text{core}} * Asl, \text{com, core}) / Asl, \text{com} = 756.25$$

$$\text{with } Es_2 = (Es_{\text{jacket}} * Asl, \text{com, jacket} + Es_{\text{core}} * Asl, \text{com, core}) / Asl, \text{com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 899.1522$$

$$fy_v = 749.2935$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsy_v = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{\text{jacket}} * Asl, \text{mid, jacket} + fs_{\text{mid}} * Asl, \text{mid, core}) / Asl, \text{mid} = 749.2935$$

$$\text{with } Es_v = (Es_{\text{jacket}} * Asl, \text{mid, jacket} + Es_{\text{mid}} * Asl, \text{mid, core}) / Asl, \text{mid} = 200000.00$$

$$1 = Asl, \text{ten} / (b * d) * (fs_1 / fc) = 0.15845977$$

$$2 = Asl, \text{com} / (b * d) * (fs_2 / fc) = 0.15845977$$

$$v = Asl, \text{mid} / (b * d) * (fsv / fc) = 0.36847443$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{TBDY}) = 25.58352$$

$$cc (5A.5, \text{TBDY}) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = Asl, \text{ten} / (b * d) * (fs_1 / fc) = 0.18909264$$

$$2 = Asl, \text{com} / (b * d) * (fs_2 / fc) = 0.18909264$$

$$v = Asl, \text{mid} / (b * d) * (fsv / fc) = 0.43970658$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*s,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009
---->
u = cu (4.2) = 9.9083764E-006
Mu = MRo

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
u = 9.9083764E-006
Mu = 2.8865E+009

with full section properties:
b = 450.00
d = 907.00
d' = 43.00
v = 0.69163741
N = 5.0813E+006
fc = 18.00
co (5A.5, TBDY) = 0.002
Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00621307$

c = confinement factor = 1.42131

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * e_{su1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,

For calculation of $e_{su1,nominal}$ and $y1$, $sh1$, $ft1$, $fy1$, it is considered

characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 756.25$
 with $Es_1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou_{min} = lb/lb_{min} = 1.00$
 $su_2 = 0.4 \cdot esu_2_{nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu_2_{nominal} = 0.08$,
 For calculation of $esu_2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2 / 1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 756.25$
 with $Es_2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 899.1522$
 $fy_v = 749.2935$
 $su_v = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou_{min} = lb/d = 1.00$
 $su_v = 0.4 \cdot esuv_{nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsy_v = fs_v / 1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsy_v = fs_v / 1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 749.2935$
 with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.15845977$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.15845977$
 $v = Asl_{mid} / (b \cdot d) \cdot (fs_v / fc) = 0.36847443$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $f_{cc} (5A.2, \text{TBDY}) = 25.58352$
 $cc (5A.5, \text{TBDY}) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.18909264$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.18909264$
 $v = Asl_{mid} / (b \cdot d) \cdot (fs_v / fc) = 0.43970658$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y_2}$ - LHS eq.(4.5) is not satisfied
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s_{y_1}$ - LHS eq.(4.7) is not satisfied
 --->
 $v < v_{c,y_1}$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.6344264$
 $MRC (4.17) = 2.3433E+009$

--->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, ν_1 , ν_2 , ν normalised to b_o*d_o , instead of $b*d$
- ν_1 , ν_2 parameters of confined concrete, f_{cc} , ϵ_{cc} , used in lieu of f_c , ϵ_{cu}

--->

Subcase: Rupture of tension steel

--->

$v^* < v^*s_y2$ - LHS eq.(4.5) is not satisfied

--->

$v^* < v^*s_c$ - LHS eq.(4.5) is not satisfied

--->

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$v^* < v^*c_y2$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*c_y1$ - RHS eq.(4.6) is not satisfied

--->

ϵ_{cu} (4.11) = 0.71499649

M_{Ro} (4.18) = 2.8865E+009

--->

$u = \epsilon_{cu}$ (4.2) = 9.9083764E-006

$\mu_u = M_{Ro}$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.3298E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.3298E+006$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l^* V_{Col0}$

$V_{Col0} = 1.3298E+006$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f^* V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_c \text{ jacket} * \text{Area jacket} + f'_c \text{ core} * \text{Area core}) / \text{Area section} = 15.20$, but $f_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1.7267E+008$

$V_u = 5.5168185E-006$

$d = 0.8 * h = 760.00$

$N_u = 5.0813E+006$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 1.2262E+006$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 1.0996E+006$

$V_{sj1} = 353429.174$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

V_{sj1} is multiplied by $Col_{j1} = 1.00$

$s/d = 0.27777778$

$V_{sj2} = 746128.255$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.13157895$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 0.00$
 $s/d = 1.25$
 $V_{s,c2} = 126669.016$ is calculated for section flange core, with:
 $d = 600.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 1.00$
 $s/d = 0.41666667$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 885757.128$
 $bw = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.3298E+006$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$
 $V_{Col0} = 1.3298E+006$
 $knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)
 Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$, but $f_c'^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 1.6609E+008$
 $V_u = 5.5168185E-006$
 $d = 0.8 * h = 760.00$
 $N_u = 5.0813E+006$
 $Ag = 427500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.2262E+006$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 1.0996E+006$
 $V_{s,j1} = 353429.174$ is calculated for section web jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.27777778$
 $V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:
 $d = 760.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.13157895$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 0.00$
 $s/d = 1.25$
 $V_{s,c2} = 126669.016$ is calculated for section flange core, with:

d = 600.00
Av = 100530.965
fy = 525.00
s = 250.00
Vs,c2 is multiplied by Col,c2 = 1.00
s/d = 0.41666667
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 885757.128
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (b)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, γ = 0.80
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
Concrete Elasticity, $E_c = 19940.411$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
Concrete Elasticity, $E_c = 16281.278$
Steel Elasticity, $E_s = 200000.00$
Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$
Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $E_{cc} = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/l_d >= 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -3.5795E+008$
Shear Force, $V_2 = 716139.537$
Shear Force, $V_3 = -3.11526$
Axial Force, $F = -5.0716E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl} = 314.1593$
-Compression: $A_{slc} = 6377.433$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 1539.38$
-Compression: $A_{sl,com} = 1539.38$

-Middle: $Asl_{mid} = 3612.832$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl_{ten,jacket} = 1231.504$

-Compression: $Asl_{com,jacket} = 1231.504$

-Middle: $Asl_{mid,jacket} = 2689.203$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl_{ten,core} = 307.8761$

-Compression: $Asl_{com,core} = 307.8761$

-Middle: $Asl_{mid,core} = 923.6282$

Mean Diameter of Tension Reinforcement, $DbL = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_R = \alpha u = 0.00047556$
 $u = y + p = 0.00059446$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00059446$ ((4.29), Biskinis Phd)

$M_y = 1.6308E+009$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 499.8385

From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 4.5707E+014$

factor = 0.70

$A_g = 562500.00$

Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 15.20$

$N = 5.0716E+006$

$E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 6.5295E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 6.3767581E-006$

with $f_y = 601.9953$

$d = 907.00$

$y = 0.47957772$

$A = 0.0370359$

$B = 0.02922707$

with $pt = 0.0037716$

$pc = 0.0037716$

$pv = 0.00885172$

$N = 5.0716E+006$

$b = 450.00$

$" = 0.04740904$

$y_{comp} = 2.6024973E-006$

with $fc = 18.00$

$E_c = 19940.411$

$y = 0.68835635$

$A = -0.02184193$

$B = 0.0085861$

with $E_s = 200000.00$

Calculation of ratio l_b / l_d

Adequate Lap Length: $l_b / l_d \geq 1$

- Calculation of p -

From table 10-8: $p = 0.00$



with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$
shear control ratio $V_y E / V_{CoI OE} = 1.44711$
 $d = d_{external} = 907.00$
 $s = s_{external} = 100.00$
- $t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00427788$
jacket: $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00357443$
 $A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction
 $L_{stir1} = 2560.00$, is the total Length of all stirrups parallel to loading (shear) direction
 $s_1 = 100.00$
core: $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00070345$
 $A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction
 $L_{stir2} = 1968.00$, is the total Length of all stirrups parallel to loading (shear) direction
 $s_2 = 250.00$
The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution
where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength
All these variables have already been given in Shear control ratio calculation.
For the normalisation f_s of jacket is used.
 $NUD = 5.0716E+006$
 $A_g = 562500.00$
 $f_{cE} = (f_{c,jacket} * Area_{jacket} + f_{c,core} * Area_{core}) / section_area = 15.20$
 $f_{yIE} = (f_{y,ext_Long_Reinf} * Area_{ext_Long_Reinf} + f_{y,int_Long_Reinf} * Area_{int_Long_Reinf}) / Area_{Tot_Long_Rein} =$
 601.9953
 $f_{yIE} = (f_{y,ext_Trans_Reinf} * s_1 + f_{y,int_Trans_Reinf} * s_2) / (s_1 + s_2) = 608.5561$
 $p_l = Area_{Tot_Long_Rein} / (b * d) = 0.01639493$
 $b = 450.00$
 $d = 907.00$
 $f_{cE} = 15.20$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (b)

Calculation No. 9

column C1, Floor 1
Limit State: Life Safety (data interpolation between analysis steps 50 and 51)
Analysis: Uniform +X
Check: Shear capacity V_{Rd}
Edge: Start
Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjctcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 12.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 8.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 18.00$

New material: Steel Strength, $f_s = f_{sm} = 625.00$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material: Steel Strength, $f_s = f_{sm} = 525.00$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -1.8918E+009$
 Shear Force, $V_a = -638013.908$
 EDGE -B-
 Bending Moment, $M_b = -3.3682E+008$
 Shear Force, $V_b = 638013.908$
 BOTH EDGES
 Axial Force, $F = -5.0666E+006$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 3345.796$
 -Compression: $A_{sc} = 3345.796$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 1539.38$
 -Compression: $A_{sl,com} = 1539.38$
 -Middle: $A_{sl,mid} = 3612.832$
 Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 639759.811$
 V_n ((10.3), ASCE 41-17) = $k_n I V_{CoI0} = 799699.764$
 $V_{CoI} = 1.1287E+006$
 $k_n I = 0.70851738$
 displacement_ductility_demand = 5.88643

NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + \phi V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 10.13333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/d = 3.90154$
 $\mu_u = 1.8918E+009$
 $V_u = 638013.908$
 $d = 0.8 \cdot h = 760.00$
 $N_u = 5.0666E+006$
 $A_g = 427500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 980981.156$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 879645.943$
 $V_{s,j1} = 282743.339$ is calculated for section web jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$
 $s/d = 0.27777778$
 $V_{s,j2} = 596902.604$ is calculated for section flange jacket, with:
 $d = 760.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col_{j2} = 1.00$
 $s/d = 0.13157895$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 101335.213$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col_{c1} = 0.00$
 $s/d = 1.25$
 $V_{s,c2} = 101335.213$ is calculated for section flange core, with:
 $d = 600.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$

$V_{s,c2}$ is multiplied by $Col_{c2} = 1.00$
 $s/d = 0.41666667$
 $V_f((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 723217.666$
 $bw = 450.00$

displacement ductility demand is calculated as ϕ / y

- Calculation of ϕ / y for END A -
for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 0.02075981$
 $y = (M_y * L_s / 3) / E_{eff} = 0.00352672$ ((4.29), Biskinis Phd))
 $M_y = 1.6309E+009$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 2965.168
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 4.5707E+014$
factor = 0.70
 $A_g = 562500.00$
Mean concrete strength: $f'_c = (f'_{jacket} * Area_{jacket} + f'_{core} * Area_{core}) / Area_{section} = 15.20$
 $N = 5.0666E+006$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 6.5295E+014$

Calculation of Yielding Moment M_y

Calculation of ϕ and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 6.3752290E-006$
with $f_y = 601.9953$
 $d = 907.00$
 $y = 0.4794529$
 $A = 0.03701556$
 $B = 0.02920673$
with $pt = 0.0037716$
 $pc = 0.0037716$
 $pv = 0.00885172$
 $N = 5.0666E+006$
 $b = 450.00$
 $\rho = 0.04740904$
 $y_{comp} = 2.6045948E-006$
with $f_c = 18.00$
 $E_c = 19940.411$
 $y = 0.687802$
 $A = -0.02180425$
 $B = 0.0085861$
with $E_s = 200000.00$

Calculation of ratio l_b / d

Adequate Lap Length: $l_b / d \geq 1$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (a)

Calculation No. 10

column C1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.42131
Element Length, $L = 3000.00$
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou}, \min > = 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = -1.7986448E-005$
EDGE -B-
Shear Force, $V_b = 1.7986448E-005$
BOTH EDGES
Axial Force, $F = -5.0813E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 314.1593$
-Compression: $As_c = 6377.433$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1539.38$
-Compression: $As_{c,com} = 2475.575$
-Middle: $As_{mid} = 2676.637$

Calculation of Shear Capacity ratio , $V_e/V_r = 1.92314$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 2.0922E+006$
with
 $M_{pr1} = \text{Max}(Mu_{1+} , Mu_{1-}) = 3.1383E+009$
 $Mu_{1+} = 3.1383E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 1.6290E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+} , Mu_{2-}) = 3.1383E+009$
 $Mu_{2+} = 3.1383E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 1.6290E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.9524665E-005$
 $M_u = 3.1383E+009$

with full section properties:

$b = 950.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.420296$
 $N = 5.0813E+006$
 $f_c = 18.00$
 ϕ_o (5A.5, TBDY) = 0.002
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00621307$

c = confinement factor = 1.42131

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * e_{su1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,

For calculation of $e_{su1,nominal}$ and $y1$, $sh1$, $ft1$, $fy1$, it is considered

characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 756.25$
 with $Es_1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 900.1904$
 $fy_2 = 750.1586$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou_{min} = lb/lb_{min} = 1.00$
 $su_2 = 0.4 \cdot esu_2_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_2_{nominal} = 0.08$,
 For calculation of $esu_2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2 / 1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 750.1586$
 with $Es_2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 902.993$
 $fy_v = 752.4941$
 $su_v = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou_{min} = lb/ld = 1.00$
 $su_v = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsy_v = fs_v / 1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsy_v = fs_v / 1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 752.4941$
 with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.09629324$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.15360794$
 $v = Asl_{mid} / (b \cdot d) \cdot (fs_v / fc) = 0.16660079$
 and confined core properties:
 $b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.10733965$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.17122928$
 $v = Asl_{mid} / (b \cdot d) \cdot (fs_v / fc) = 0.18571261$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y_2}$ - LHS eq.(4.5) is not satisfied
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s_{y_1}$ - LHS eq.(4.7) is not satisfied
 --->
 $v < v_{c,y_1}$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.42075151$
 $MRC (4.17) = 2.3432E+009$

--->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, ν , ν normalised to $b_o \cdot d_o$, instead of $b \cdot d$
- parameters of confined concrete, f_{cc} , ϵ_{cc} , used in lieu of f_c , ϵ_{cu}

--->

Subcase: Rupture of tension steel

--->

$\nu^* < \nu^* s_y^2$ - LHS eq.(4.5) is not satisfied

--->

$\nu^* < \nu^* s_c$ - LHS eq.(4.5) is not satisfied

--->

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$\nu^* < \nu^* c_y^2$ - LHS eq.(4.6) is not satisfied

--->

$\nu^* < \nu^* c_y^1$ - RHS eq.(4.6) is not satisfied

--->

$\epsilon_{cu} (4.11) = 0.47003883$

$M_{Ro} (4.18) = 3.1383E+009$

--->

$u = \epsilon_{cu} (4.2) = 1.9524665E-005$

$\mu_u = M_{Ro}$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u1} -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.0952761E-005$

$\mu_u = 1.6290E+009$

with full section properties:

$b = 450.00$

$d = 707.00$

$d' = 43.00$

$\nu = 0.88729156$

$N = 5.0813E+006$

$f_c = 18.00$

$\omega (5A.5, TBDY) = 0.002$

Final value of ϵ_{cu} : $\epsilon_{cu}^* = \text{shear_factor} * \text{Max}(\epsilon_{cu}, \epsilon_{cc}) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\epsilon_{cu} = 0.01486841$

$\omega_e (5.4c) = 0.08077545$

$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

$$AnoConf2 = 110709.333 \text{ is the unconfined internal core area which is equal to } bi^2/6 \text{ as defined at (A.2).}$$

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.724$$

$$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.724$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1 \text{ (Length of stirrups along Y)} = 2160.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

$$Lstir2 \text{ (Length of stirrups along Y)} = 1568.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.25416$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

$$Lstir1 \text{ (Length of stirrups along X)} = 2560.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

$$Lstir2 \text{ (Length of stirrups along X)} = 1968.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 781.25$$

$$fywe2 = 656.25$$

$$fce = 18.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 900.1904$$

$$fy1 = 750.1586$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 1.00$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_nominal = 0.08,$$

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 750.1586$$

$$\text{with } Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 907.50$$

$$fy2 = 756.25$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4 * esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_nominal = 0.08,$$

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 756.25$
 with $Es2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$
 $yv = 0.0025$
 $shv = 0.008$
 $ftv = 902.993$
 $fyv = 752.4941$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 1.00$
 $suv = 0.4 \cdot esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} \cdot A_{sl,mid,jacket} + fs_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 752.4941$
 with $Esv = (Es_{jacket} \cdot A_{sl,mid,jacket} + Es_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$
 $1 = A_{sl,ten} / (b \cdot d) \cdot (fs1 / fc) = 0.32428344$
 $2 = A_{sl,com} / (b \cdot d) \cdot (fs2 / fc) = 0.20328574$
 $v = A_{sl,mid} / (b \cdot d) \cdot (fsv / fc) = 0.35171278$
 and confined core properties:
 $b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{sl,ten} / (b \cdot d) \cdot (fs1 / fc) = 0.39075399$
 $2 = A_{sl,com} / (b \cdot d) \cdot (fs2 / fc) = 0.24495458$
 $v = A_{sl,mid} / (b \cdot d) \cdot (fsv / fc) = 0.42380571$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is not satisfied
 --->
 $v < vs,c$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s,y1$ - LHS eq.(4.7) is not satisfied
 --->
 $v < vc,y1$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.82478813$
 $MRC (4.17) = 1.5333E+009$
 --->
 New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
 In expressions below, the following modifications have been made
 - b, d, d' replaced by geometric parameters of the core: $bo, do, d'o$
 - $N, 1, 2, v$ normalised to $bo \cdot do$, instead of $b \cdot d$
 - f, cc parameters of confined concrete, fcc, cc , used in lieu of fc, ecu
 --->
 Subcase: Rupture of tension steel
 --->
 $v^* < v^*s,y2$ - LHS eq.(4.5) is not satisfied
 --->
 $v^* < v^*s,c$ - LHS eq.(4.5) is not satisfied
 --->
 Subcase rejected
 --->
 New Subcase: Failure of compression zone

--->
 $v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied
 --->
 $v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied
 --->
 $*cu$ (4.11) = 0.83790293
 M_{Ro} (4.18) = 1.6290E+009
 --->
 $u = cu$ (4.2) = 1.0952761E-005
 $\mu = M_{Ro}$

 Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

 Calculation of μ_{2+}

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
 $u = 1.9524665E-005$
 $\mu = 3.1383E+009$

with full section properties:

$b = 950.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.420296$
 $N = 5.0813E+006$

$f_c = 18.00$
 α (5A.5, TBDY) = 0.002
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.01486841$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.01486841$

w_e (5.4c) = 0.08077545

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = Max(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (>= ase1) = Max(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{,min} * F_{ywe} = Min(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
psh2 (5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.25416
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00357443
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00070345
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 907.50

fy1 = 756.25

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 900.1904

fy2 = 750.1586

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 750.1586

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 902.993

fyv = 752.4941

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 752.4941$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

1 = $A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.09629324$

2 = $A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.15360794$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.16660079$

and confined core properties:

$b = 890.00$

$d = 677.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

1 = $A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.10733965$

2 = $A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.17122928$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.18571261$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < v_{s,y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

c_u (4.10) = 0.42075151

M_{Rc} (4.17) = 2.3432E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b , d , d' replaced by geometric parameters of the core: b_o , d_o , d'_o

- N , 1 , 2 , v normalised to $b_o \cdot d_o$, instead of $b \cdot d$

- f_{cc} , cc , used in lieu of f_c , e_{cu}

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$*c_u$ (4.11) = 0.47003883

M_{Ro} (4.18) = 3.1383E+009

---->

$u = c_u$ (4.2) = 1.9524665E-005

$\mu = M_{Ro}$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu2-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0952761E-005$$

$$\mu = 1.6290E+009$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.88729156$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01486841$$

$$w_e \text{ (5.4c)} = 0.08077545$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$s_2 = 250.00$
 $fy_{we1} = 781.25$
 $fy_{we2} = 656.25$
 $f_{ce} = 18.00$
 From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $y_1 = 0.0025$
 $sh_1 = 0.008$
 $ft_1 = 900.1904$
 $fy_1 = 750.1586$
 $su_1 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou, min = lb/d = 1.00$
 $su_1 = 0.4 * esu_1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_1_nominal = 0.08$,
 For calculation of $esu_1_nominal$ and y_1, sh_1, ft_1, fy_1 , it is considered
 characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_1 = (fs_{jacket} * A_{sl, ten, jacket} + fs_{core} * A_{sl, ten, core}) / A_{sl, ten} = 750.1586$
 with $Es_1 = (Es_{jacket} * A_{sl, ten, jacket} + Es_{core} * A_{sl, ten, core}) / A_{sl, ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou, min = lb/lb, min = 1.00$
 $su_2 = 0.4 * esu_2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_2_nominal = 0.08$,
 For calculation of $esu_2_nominal$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} * A_{sl, com, jacket} + fs_{core} * A_{sl, com, core}) / A_{sl, com} = 756.25$
 with $Es_2 = (Es_{jacket} * A_{sl, com, jacket} + Es_{core} * A_{sl, com, core}) / A_{sl, com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 902.993$
 $fy_v = 752.4941$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou, min = lb/d = 1.00$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} * A_{sl, mid, jacket} + fs_{mid} * A_{sl, mid, core}) / A_{sl, mid} = 752.4941$
 with $Es_v = (Es_{jacket} * A_{sl, mid, jacket} + Es_{mid} * A_{sl, mid, core}) / A_{sl, mid} = 200000.00$
 $1 = A_{sl, ten} / (b * d) * (fs_1 / f_c) = 0.32428344$
 $2 = A_{sl, com} / (b * d) * (fs_2 / f_c) = 0.20328574$
 $v = A_{sl, mid} / (b * d) * (fsv / f_c) = 0.35171278$
 and confined core properties:
 $b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{sl, ten} / (b * d) * (fs_1 / f_c) = 0.39075399$
 $2 = A_{sl, com} / (b * d) * (fs_2 / f_c) = 0.24495458$

```

v = Asl,mid/(b*d)*(fsv/fc) = 0.42380571
Case/Assumption: Unconfined full section - Steel rupture
'satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
'satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.82478813
MRc (4.17) = 1.5333E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*s,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.83790293
MRo (4.18) = 1.6290E+009
---->
u = cu (4.2) = 1.0952761E-005
Mu = MRo
-----

Calculation of ratio lb/d
-----
Adequate Lap Length: lb/d >= 1
-----
-----
-----
-----
Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 1.0879E+006
-----
Calculation of Shear Strength at edge 1, Vr1 = 1.0879E+006
Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 1.0879E+006
knl = 1 (zero step-static loading)
-----
NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).
-----
= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 15.20, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

```

$M/Vd = 4.00$
 $\mu_u = 4.8236E+008$
 $\nu_u = 1.7986448E-005$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0813E+006$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 1.0354E+006$
 where:
 $V_{sjacket} = V_{sj1} + V_{sj2} = 942477.796$
 $V_{sj1} = 589048.623$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 V_{sj1} is multiplied by $Col_{j1} = 1.00$
 $s/d = 0.16666667$
 $V_{sj2} = 353429.174$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 V_{sj2} is multiplied by $Col_{j2} = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col_{c1} = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col_{c2} = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 699281.943$
 $bw = 450.00$

 Calculation of Shear Strength at edge 2, $V_{r2} = 1.0879E+006$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl \cdot V_{Col0}$
 $V_{Col0} = 1.0879E+006$
 $knl = 1$ (zero step-static loading)

 NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)
 Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 15.20$, but $f_c'^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 4.5550E+008$
 $\nu_u = 1.7986448E-005$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0813E+006$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 1.0354E+006$
 where:
 $V_{sjacket} = V_{sj1} + V_{sj2} = 942477.796$
 $V_{sj1} = 589048.623$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 625.00$

$s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 699281.943$
 $bw = 450.00$

 End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rcjtcs

Constant Properties

 Knowledge Factor, $\phi = 0.80$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
 Concrete Elasticity, $E_c = 19940.411$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
 Concrete Elasticity, $E_c = 16281.278$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 Jacket
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$
 Existing Column
 Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$
 #####
 Max Height, $H_{max} = 750.00$
 Min Height, $H_{min} = 450.00$
 Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$
Eccentricity, $Ecc = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.42131
Element Length, $L = 3000.00$
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{o,u,min} >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -5.5168185E-006$
EDGE -B-
Shear Force, $V_b = 5.5168185E-006$
BOTH EDGES
Axial Force, $F = -5.0813E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 314.1593$
-Compression: $As_c = 6377.433$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1539.38$
-Compression: $As_{c,com} = 1539.38$
-Middle: $As_{c,mid} = 3612.832$

Calculation of Shear Capacity ratio , $V_e/V_r = 1.44711$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 1.9243E+006$
with
 $M_{pr1} = \text{Max}(Mu_{1+} , Mu_{1-}) = 2.8865E+009$
 $Mu_{1+} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+} , Mu_{2-}) = 2.8865E+009$
 $Mu_{2+} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 9.9083764E-006$
 $M_u = 2.8865E+009$

with full section properties:

$b = 450.00$
 $d = 907.00$
 $d' = 43.00$
 $v = 0.69163741$
 $N = 5.0813E+006$
 $f_c = 18.00$
 ω (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01486841$

w_e (5.4c) = 0.08077545

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

c = confinement factor = 1.42131

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered

characteristic value $f_{s1} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s,jacket} \cdot A_{s,ten,jacket} + f_{s,core} \cdot A_{s,ten,core})/A_{s,ten} = 756.25$

with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core})/A_{s,ten} = 200000.00$

$y_2 = 0.0025$

$sh_2 = 0.008$

$ft_2 = 907.50$

$fy_2 = 756.25$

$su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$

$su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core})/A_{s,com} = 756.25$

with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core})/A_{s,com} = 200000.00$

$y_v = 0.0025$

$sh_v = 0.008$

$ft_v = 899.1522$

$fy_v = 749.2935$

$su_v = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 1.00$

$su_v = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $f_{sv} = f_s/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $f_{sv} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 749.2935$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 200000.00$

$1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15845977$

$2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15845977$

$v = A_{s,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.36847443$

and confined core properties:

$b = 390.00$

$d = 877.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.18909264$

$2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.18909264$

$v = A_{s,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

$cu (4.10) = 0.6344264$

MRC (4.17) = 2.3433E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ec

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*s,y2$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*s,c$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

---->

*cu (4.11) = 0.71499649

MRO (4.18) = 2.8865E+009

---->

u = cu (4.2) = 9.9083764E-006

Mu = MRO

Calculation of ratio lb/lc

Adequate Lap Length: lb/lc >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 9.9083764E-006

Mu = 2.8865E+009

with full section properties:

b = 450.00

d = 907.00

d' = 43.00

v = 0.69163741

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2}-AnoConf_2)/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$
 The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
 J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.
 $A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.
 $AnoConf_2 = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 2.724$

 $psh_x * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 2.724$
 psh_1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 psh_2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.25416$
 psh_1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 psh_2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$
 $s_1 = 100.00$
 $s_2 = 250.00$
 $fy_{we1} = 781.25$
 $fy_{we2} = 656.25$
 $f_{ce} = 18.00$
 From ((5.A5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$

$y_1 = 0.0025$
 $sh_1 = 0.008$
 $ft_1 = 907.50$
 $fy_1 = 756.25$
 $su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{min} = lb/ld = 1.00$

$su_1 = 0.4 * esu_{1_nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1_nominal} = 0.08$,

For calculation of $esu_{1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 756.25$

with $Es_1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 1.00$

$su_2 = 0.4 * esu_{2_nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,

For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core})/A_{s,com} = 756.25$
with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core})/A_{s,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 899.1522$
 $f_{y_v} = 749.2935$
 $s_{u_v} = 0.032$
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 1.00$
 $s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,
considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY
For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{s_v} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 749.2935$
with $E_{s_v} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 200000.00$
 $1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15845977$
 $2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15845977$
 $v = A_{s,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.36847443$
and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.18909264$
 $2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.18909264$
 $v = A_{s,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.43970658$
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
--->
Case/Assumption Rejected.
--->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
--->
 $v < s_{y1}$ - LHS eq.(4.7) is not satisfied
--->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
--->
 $cu (4.10) = 0.6344264$
 $M_{Rc} (4.17) = 2.3433E+009$
--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, 1, 2, v$ normalised to $b_o \cdot d_o$, instead of $b \cdot d$
- f_{cc}, cc parameters of confined concrete, f_{cc}, cc , used in lieu of f_c, e_{cu}
--->
Subcase: Rupture of tension steel
--->
 $v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied
--->
Subcase rejected
--->

New Subcase: Failure of compression zone

--->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

--->

*cu (4.11) = 0.71499649

M_{Ro} (4.18) = 2.8865E+009

--->

u = cu (4.2) = 9.9083764E-006

Mu = M_{Ro}

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2+

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 9.9083764E-006

Mu = 2.8865E+009

with full section properties:

b = 450.00

d = 907.00

d' = 43.00

v = 0.69163741

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to bi2/6 as defined at (A.2).

ase2 (>= ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to bi2/6 as defined at (A.2).

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 2.724

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.724

psh1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
psh2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.25416
psh1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 907.50

fy1 = 756.25

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = $0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 756.25$

with Es1 = $(Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = $0.4 * esu2_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = $(fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 756.25$

with Es2 = $(Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.0025

shv = 0.008

ftv = 899.1522

fyv = 749.2935

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = $0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and y_v , sh_v , ft_v , fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 749.2935$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.15845977$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.15845977$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.36847443$

and confined core properties:

$b = 390.00$

$d = 877.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.18909264$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.18909264$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

cu (4.10) = 0.6344264

M_{Rc} (4.17) = 2.3433E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b , d , d' replaced by geometric parameters of the core: b_o , d_o , d'_o

- N_1 , N_2 , v normalised to $b_o \cdot d_o$, instead of $b \cdot d$

- f_{cc} , cc , used in lieu of f_c , e_{cu}

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$*cu$ (4.11) = 0.71499649

M_{Ro} (4.18) = 2.8865E+009

---->

$u = cu$ (4.2) = 9.9083764E-006

$\mu = M_{Ro}$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu2-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 9.9083764E-006$$

$$\mu_2 = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$\epsilon_{cu} \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \epsilon_{cu}: \epsilon_{cu}^* = \text{shear_factor} * \text{Max}(\epsilon_{cu}, \epsilon_{cc}) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \epsilon_{cu} = 0.01486841$$

$$\epsilon_{we} \text{ (5.4c)} = 0.08077545$$

$$\text{ase} \text{ ((5.4d), TBDY)} = (\text{ase1} * \text{Aext} + \text{ase2} * \text{Aint}) / \text{Asec} = 0.53375773$$

$$\text{ase1} = \text{Max}(((\text{Aconf,max1} - \text{AnoConf1}) / \text{Aconf,max1}) * (\text{Aconf,min1} / \text{Aconf,max1}), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{ase2} (\geq \text{ase1}) = \text{Max}(((\text{Aconf,max2} - \text{AnoConf2}) / \text{Aconf,max2}) * (\text{Aconf,min2} / \text{Aconf,max2}), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{psh,min} * \text{Fywe} = \text{Min}(\text{psh,x} * \text{Fywe}, \text{psh,y} * \text{Fywe}) = 2.724$$

$$\text{psh}_x * \text{Fywe} = \text{psh1} * \text{Fywe1} + \text{ps2} * \text{Fywe2} = 2.724$$

$$\text{psh1} \text{ ((5.4d), TBDY)} = \text{Lstir1} * \text{Astir1} / (\text{Asec} * s1) = 0.00301593$$

$$\text{Lstir1 (Length of stirrups along Y)} = 2160.00$$

$$\text{Astir1 (stirrups area)} = 78.53982$$

$$\text{psh2 (5.4d)} = \text{Lstir2} * \text{Astir2} / (\text{Asec} * s2) = 0.00056047$$

$$\text{Lstir2 (Length of stirrups along Y)} = 1568.00$$

$$\text{Astir2 (stirrups area)} = 50.26548$$

$$\text{psh}_y * \text{Fywe} = \text{psh1} * \text{Fywe1} + \text{ps2} * \text{Fywe2} = 3.25416$$

$$\text{psh1} \text{ ((5.4d), TBDY)} = \text{Lstir1} * \text{Astir1} / (\text{Asec} * s1) = 0.00357443$$

$$\text{Lstir1 (Length of stirrups along X)} = 2560.00$$

$$\text{Astir1 (stirrups area)} = 78.53982$$

$$\text{psh2} \text{ ((5.4d), TBDY)} = \text{Lstir2} * \text{Astir2} / (\text{Asec} * s2) = 0.00070345$$

$$\text{Lstir2 (Length of stirrups along X)} = 1968.00$$

$$\text{Astir2 (stirrups area)} = 50.26548$$

$$\text{Asec} = 562500.00$$

$s_1 = 100.00$
 $s_2 = 250.00$
 $fy_{we1} = 781.25$
 $fy_{we2} = 656.25$
 $f_{ce} = 18.00$
 From ((5.A5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $y_1 = 0.0025$
 $sh_1 = 0.008$
 $ft_1 = 907.50$
 $fy_1 = 756.25$
 $su_1 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou, \min = lb/ld = 1.00$
 $su_1 = 0.4 * esu_{1_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{1_nominal} = 0.08$,
 For calculation of $esu_{1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
 characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_1 = (fs_{jacket} * Asl, \text{ten}, \text{jacket} + fs_{core} * Asl, \text{ten}, \text{core}) / Asl, \text{ten} = 756.25$
 with $Es_1 = (Es_{jacket} * Asl, \text{ten}, \text{jacket} + Es_{core} * Asl, \text{ten}, \text{core}) / Asl, \text{ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou, \min = lb/lb, \min = 1.00$
 $su_2 = 0.4 * esu_{2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,
 For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} * Asl, \text{com}, \text{jacket} + fs_{core} * Asl, \text{com}, \text{core}) / Asl, \text{com} = 756.25$
 with $Es_2 = (Es_{jacket} * Asl, \text{com}, \text{jacket} + Es_{core} * Asl, \text{com}, \text{core}) / Asl, \text{com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 899.1522$
 $fy_v = 749.2935$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou, \min = lb/ld = 1.00$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} * Asl, \text{mid}, \text{jacket} + fs_{mid} * Asl, \text{mid}, \text{core}) / Asl, \text{mid} = 749.2935$
 with $Es_v = (Es_{jacket} * Asl, \text{mid}, \text{jacket} + Es_{mid} * Asl, \text{mid}, \text{core}) / Asl, \text{mid} = 200000.00$
 $1 = Asl, \text{ten} / (b * d) * (fs_1 / f_c) = 0.15845977$
 $2 = Asl, \text{com} / (b * d) * (fs_2 / f_c) = 0.15845977$
 $v = Asl, \text{mid} / (b * d) * (fsv / f_c) = 0.36847443$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl, \text{ten} / (b * d) * (fs_1 / f_c) = 0.18909264$

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.18909264$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.43970658$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < v_{s,y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

$$c_u (4.10) = 0.6344264$$

$$M_{Rc} (4.17) = 2.3433E+009$$

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- N₁, N₂, v normalised to b_o*d_o, instead of b*d
- parameters of confined concrete, f_{cc}, c_{cc}, used in lieu of f_c, c_u

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$$^*c_u (4.11) = 0.71499649$$

$$M_{Ro} (4.18) = 2.8865E+009$$

---->

$$u = c_u (4.2) = 9.9083764E-006$$

$$\mu_u = M_{Ro}$$

Calculation of ratio l_b/l_d

Adequate Lap Length: l_b/l_d >= 1

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.3298E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.3298E+006$

$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = k_{nl} * V_{Co10}$

$$V_{Co10} = 1.3298E+006$$

k_{nl} = 1 (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} = f^* * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 15.20$, but $f'_c^{0.5} \leq 8.3$

MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu = 1.7267E+008$$

$$V_u = 5.5168185E-006$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 5.0813E+006$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.2262E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 1.0996E+006$$

$V_{s,j1} = 353429.174$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 126669.016$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 885757.128$$

$$b_w = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.3298E+006$

$$V_{r2} = V_{Col} \text{ ((10.3), ASCE 41-17)} = knl \cdot V_{Col0}$$

$$V_{Col0} = 1.3298E+006$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 15.20, \text{ but } f_c'^{0.5} \leq 8.3$$

MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu = 1.6609E+008$$

$$V_u = 5.5168185E-006$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 5.0813E+006$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.2262E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 1.0996E+006$$

$V_{s,j1} = 353429.174$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$s/d = 1.25$

$V_{s,c2} = 126669.016$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$s/d = 0.41666667$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 885757.128$

$bw = 450.00$

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 2

Integration Section: (a)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/l_d >= 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -6.3339E+008$
Shear Force, $V2 = -638013.908$
Shear Force, $V3 = 2.2058$
Axial Force, $F = -5.0666E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 3345.796$
-Compression: $As_c = 3345.796$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1539.38$
-Compression: $As_{c,com} = 2475.575$
-Middle: $As_{c,mid} = 2676.637$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten,jacket} = 1231.504$
-Compression: $As_{c,com,jacket} = 1859.823$
-Middle: $As_{c,mid,jacket} = 2060.885$
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten,core} = 307.8761$
-Compression: $As_{c,com,core} = 615.7522$
-Middle: $As_{c,mid,core} = 615.7522$
Mean Diameter of Tension Reinforcement, $Db_L = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \alpha \cdot u = 0.01920821$
 $u = y + p = 0.02401027$

- Calculation of y -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.01234946$ ((4.29), Biskinis Phd))
 $M_y = 1.8636E+009$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 6000.00
From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 3.0181E+014$
factor = 0.70
 $A_g = 562500.00$
Mean concrete strength: $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 15.20$
 $N = 5.0666E+006$
 $E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 4.3116E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:
flange width, $b = 950.00$
web width, $b_w = 450.00$
flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 7.1312074E-006$
with $f_y = 601.9953$
 $d = 707.00$
 $y = 0.40299134$
 $A = 0.02249371$

B = 0.01716068
 with pt = 0.00229194
 pc = 0.00368581
 pv = 0.00398517
 N = 5.0666E+006
 b = 950.00
 " = 0.06082037
 y_comp = 4.9385210E-006
 with fc = 18.00
 Ec = 19940.411
 y = 0.46536593
 A = -0.01325006
 B = 0.00462988
 with Es = 200000.00
 CONFIRMATION: $y = 0.46536593 < t/d$

 Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

- Calculation of p -

From table 10-8: $p = 0.01166081$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $lb/d \geq 1$

shear control ratio $VyE/VCoIE = 1.92314$

$d = d_{external} = 707.00$

$s = s_{external} = 100.00$

- $t = s1 + s2 + 2*tf/bw*(ffe/fs) = 0.0035764$

jacket: $s1 = Av1*Lstir1/(s1*Ag) = 0.00301593$

$Av1 = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$Lstir1 = 2160.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s1 = 100.00$

core: $s2 = Av2*Lstir2/(s2*Ag) = 0.00056047$

$Av2 = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$Lstir2 = 1568.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s2 = 250.00$

The term $2*tf/bw*(ffe/fs)$ is implemented to account for FRP contribution

where $f = 2*tf/bw$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and ffe/fs normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation fs of jacket is used.

$NUD = 5.0666E+006$

$Ag = 562500.00$

$f_{cE} = (fc_{jacket}*Area_{jacket} + fc_{core}*Area_{core})/section_area = 15.20$

$fy_{lE} = (fy_{ext_Long_Reinf}*Area_{ext_Long_Reinf} + fy_{int_Long_Reinf}*Area_{int_Long_Reinf})/Area_{Tot_Long_Rein} =$

601.9953

$fy_{tE} = (fy_{ext_Trans_Reinf}*s1 + fy_{int_Trans_Reinf}*s2)/(s1 + s2) = 609.3286$

$p_l = Area_{Tot_Long_Rein}/(b*d) = 0.00996292$

$b = 950.00$

$d = 707.00$

$f_{cE} = 15.20$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 11

column C1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 12.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 8.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 18.00$

New material: Steel Strength, $f_s = f_{sm} = 625.00$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material: Steel Strength, $f_s = f_{sm} = 525.00$

#####

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{o,u,min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, Ma = -6.3339E+008
Shear Force, Va = 2.2058
EDGE -B-
Bending Moment, Mb = 4.5511E+008
Shear Force, Vb = -2.2058
BOTH EDGES
Axial Force, F = -5.0666E+006
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 3345.796
-Compression: Asc = 3345.796
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1539.38
-Compression: Asl,com = 2475.575
-Middle: Asl,mid = 2676.637
Mean Diameter of Tension Reinforcement, DbL,ten = 16.57143

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity VR = $V_n = 734369.173$
 V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{CoI} = 917961.466$
 $V_{CoI} = 917961.466$
 $k_n = 1.00$
displacement_ductility_demand = 0.9445196

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 10.13333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/d = 4.00$
 $M_u = 6.3339E+008$
 $V_u = 2.2058$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0666E+006$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 828294.726$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 753982.237$
 $V_{s,j1} = 471238.898$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$

$V_{s,j2} = 282743.339$ is calculated for section flange jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.27777778$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 74312.489$$

$V_{s,c1} = 74312.489$ is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 420.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 420.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 0.00$

$$s/d = 1.25$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 570961.316$

$$b_w = 450.00$$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 0.0116643$

$$y = (M_y * L_s / 3) / E_{eff} = 0.01234946 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 1.8636E+009$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 6000.00$$

From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 3.0181E+014$

$$factor = 0.70$$

$$A_g = 562500.00$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$$

$$N = 5.0666E+006$$

$$E_c * I_g = E_c * I_{g,jacket} + E_c * I_{g,core} = 4.3116E+014$$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

$$\text{flange width, } b = 950.00$$

$$\text{web width, } b_w = 450.00$$

$$\text{flange thickness, } t = 450.00$$

$$y = \text{Min}(y_{ten}, y_{com})$$

$$y_{ten} = 7.1312074E-006$$

with $f_y = 601.9953$

$$d = 707.00$$

$$y = 0.40299134$$

$$A = 0.02249371$$

$$B = 0.01716068$$

$$\text{with } pt = 0.00229194$$

$$pc = 0.00368581$$

$$pv = 0.00398517$$

$$N = 5.0666E+006$$

$$b = 950.00$$

" = 0.06082037
y_comp = 4.9385210E-006
with fc = 18.00
Ec = 19940.411
y = 0.46536593
A = -0.01325006
B = 0.00462988
with Es = 200000.00
CONFIRMATION: y = 0.46536593 < t/d


Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 12

column C1, Floor 1
Limit State: Life Safety (data interpolation between analysis steps 50 and 51)
Analysis: Uniform +X
Check: Chord rotation capacity (u)
Edge: Start
Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At Shear local axis: 3
(Bending local axis: 2)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 0.80
Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.42131

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.7986448E-005$

EDGE -B-

Shear Force, $V_b = 1.7986448E-005$

BOTH EDGES

Axial Force, $F = -5.0813E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 314.1593$

-Compression: $A_{sl,c} = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 2475.575$

-Middle: $A_{sl,mid} = 2676.637$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.92314$

Member Controlled by Shear ($V_e/V_r > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 2.0922E+006$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 3.1383E+009$

$M_{u1+} = 3.1383E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.6290E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 3.1383E+009$

$\mu_{2+} = 3.1383E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{2-} = 1.6290E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.9524665E-005$$

$$\mu = 3.1383E+009$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.420296$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01486841$$

$$\mu_{cc} \text{ (5.4c)} = 0.08077545$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (\geq a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A.5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 907.50

fy1 = 756.25

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 900.1904

fy2 = 750.1586

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 750.1586

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 902.993

fyv = 752.4941

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09629324

2 = Asl,com/(b*d)*(fs2/fc) = 0.15360794

v = Asl,mid/(b*d)*(fsv/fc) = 0.16660079

and confined core properties:

b = 890.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

1 = Asl,ten/(b*d)*(fs1/fc) = 0.10733965

2 = Asl,com/(b*d)*(fs2/fc) = 0.17122928

v = Asl,mid/(b*d)*(fsv/fc) = 0.18571261

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->
v < vs,y2 - LHS eq.(4.5) is not satisfied

---->
v < vs,c - RHS eq.(4.5) is not satisfied

---->
Case/Assumption Rejected.

---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)

---->
v < s,y1 - LHS eq.(4.7) is not satisfied

---->
v < vc,y1 - RHS eq.(4.6) is satisfied

---->
cu (4.10) = 0.42075151

MRC (4.17) = 2.3432E+009

---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu

---->
Subcase: Rupture of tension steel

---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied

---->
v* < v*s,c - LHS eq.(4.5) is not satisfied

---->
Subcase rejected

---->
New Subcase: Failure of compression zone

---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied

---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied

---->
*cu (4.11) = 0.47003883

MRO (4.18) = 3.1383E+009

---->
u = cu (4.2) = 1.9524665E-005
Mu = MRO

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
u = 1.0952761E-005

Mu = 1.6290E+009

with full section properties:
b = 450.00

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.88729156$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01486841$$

$$w_e (5.4c) = 0.08077545$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (> a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along } Y) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along } Y) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along } X) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along } X) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 900.1904$$

$$fy1 = 750.1586$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 750.1586

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 902.993

fyv = 752.4941

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.32428344

2 = Asl,com/(b*d)*(fs2/fc) = 0.20328574

v = Asl,mid/(b*d)*(fsv/fc) = 0.35171278

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

1 = Asl,ten/(b*d)*(fs1/fc) = 0.39075399

2 = Asl,com/(b*d)*(fs2/fc) = 0.24495458

v = Asl,mid/(b*d)*(fsv/fc) = 0.42380571

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is not satisfied

--->

v < vs,c - RHS eq.(4.5) is not satisfied

--->

Case/Assumption Rejected.

--->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

--->
 $v < s_y y_1$ - LHS eq.(4.7) is not satisfied
 --->
 $v < v_c y_1$ - RHS eq.(4.6) is satisfied
 --->
 μ_c (4.10) = 0.82478813
 $M R_c$ (4.17) = 1.5333E+009
 --->
 New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
 In expressions below, the following modifications have been made
 - b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
 - N, μ_1, μ_2, v normalised to $b_o d_o$, instead of $b d$
 - f_c, μ_c parameters of confined concrete, f_{cc}, μ_{cc} used in lieu of f_c, μ_c

--->
Subcase: Rupture of tension steel

--->
 $v^* < v^* s_y y_2$ - LHS eq.(4.5) is not satisfied

--->
 $v^* < v^* s_c$ - LHS eq.(4.5) is not satisfied

--->
Subcase rejected

--->
New Subcase: Failure of compression zone

--->
 $v^* < v^* c_y y_2$ - LHS eq.(4.6) is not satisfied

--->
 $v^* < v^* c_y y_1$ - RHS eq.(4.6) is not satisfied

--->
 $\mu^* \mu_c$ (4.11) = 0.83790293

$M R_o$ (4.18) = 1.6290E+009

--->
 $\mu = \mu_c$ (4.2) = 1.0952761E-005

$\mu_u = M R_o$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$\mu_u = 1.9524665E-005$

$\mu_u = 3.1383E+009$

with full section properties:

$b = 950.00$

$d = 707.00$

$d' = 43.00$

$v = 0.420296$

$N = 5.0813E+006$

$f_c = 18.00$

μ_c (5A.5, TBDY) = 0.002

Final value of μ_c : $\mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_c = 0.01486841$

μ_{cc} (5.4c) = 0.08077545

μ_{ase} ((5.4d), TBDY) = $(\mu_{ase1} * A_{ext} + \mu_{ase2} * A_{int}) / A_{sec} = 0.53375773$

$\mu_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase2 (>=ase1) = \text{Max}(((A_{conf,max2}-A_{noConf2})/A_{conf,max2})*(A_{conf,min2}/A_{conf,max2}),0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{min}*F_{ywe} = \text{Min}(psh_x*F_{ywe}, psh_y*F_{ywe}) = 2.724$

 $psh_x*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 2.724$

$psh1 ((5.4d), TBDY) = L_{stir1}*A_{stir1}/(A_{sec}*s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2 (5.4d) = L_{stir2}*A_{stir2}/(A_{sec}*s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $psh_y*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.25416$

$psh1 ((5.4d), TBDY) = L_{stir1}*A_{stir1}/(A_{sec}*s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2 ((5.4d), TBDY) = L_{stir2}*A_{stir2}/(A_{sec}*s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4*es_{u1,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{u1,nominal} = 0.08$,

For calculation of $es_{u1,nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fs_{y1} = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket}*A_{sl,ten,jacket} + f_{s,core}*A_{sl,ten,core})/A_{sl,ten} = 756.25$

with $Es1 = (E_{s,jacket}*A_{sl,ten,jacket} + E_{s,core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 900.1904$

$fy2 = 750.1586$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_{b,min} = 1.00$
 $s_u2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $esu2_nominal = 0.08$,
For calculation of $esu2_nominal$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $fs_2 = (fs_jacket * A_{s1,com,jacket} + fs_core * A_{s1,com,core}) / A_{s1,com} = 750.1586$
with $Es_2 = (Es_jacket * A_{s1,com,jacket} + Es_core * A_{s1,com,core}) / A_{s1,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 902.993$
 $fy_v = 752.4941$
 $s_{uv} = 0.032$
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 1.00$
 $s_{uv} = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fs_{uv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fs_{uv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 752.4941$
with $E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.09629324$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.15360794$
 $v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.16660079$
and confined core properties:
 $b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.10733965$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.17122928$
 $v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.18571261$
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
---->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
 $v < s_{y1}$ - LHS eq.(4.7) is not satisfied
---->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
---->
 $c_u (4.10) = 0.42075151$
 $M_{Rc} (4.17) = 2.3432E+009$
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, 1, 2, v$ normalised to $b_o * d_o$, instead of $b * d$
- parameters of confined concrete, f_{cc}, cc , used in lieu of f_c, e_{cu}
---->
Subcase: Rupture of tension steel
---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

--->

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

--->

*cu (4.11) = 0.47003883

MRO (4.18) = 3.1383E+009

--->

u = cu (4.2) = 1.9524665E-005

Mu = MRO

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0952761E-005

Mu = 1.6290E+009

with full section properties:

b = 450.00

d = 707.00

d' = 43.00

v = 0.88729156

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to bi²/6 as defined at (A.2).

ase2 (>=ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$
 $p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 $p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$
 $p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 $p_{sh2} ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 781.25$
 $f_{ywe2} = 656.25$
 $f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00621307$
 $c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 900.1904$
 $fy1 = 750.1586$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * esu1_{nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 750.1586$

with $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 907.50$
 $fy2 = 756.25$
 $su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$

$su2 = 0.4 * esu2_{nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 756.25$

with $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.0025$
 $shv = 0.008$
 $ftv = 902.993$
 $fyv = 752.4941$
 $suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 1.00$
 $s_{uv} = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,
considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{suv_nominal}$ and $\gamma_v, \delta_{vt}, \delta_{fv}$, it is considered
characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.
 $\gamma_1, \delta_{v1}, \delta_{f1}, \delta_{y1}$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 752.4941$
with $E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.32428344$
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.20328574$
 $v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.35171278$
and confined core properties:
 $b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.39075399$
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.24495458$
 $v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.42380571$
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
--->
Case/Assumption Rejected.
--->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
--->
 $v < s_{y1}$ - LHS eq.(4.7) is not satisfied
--->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
--->
 $c_u (4.10) = 0.82478813$
 $M_{Rc} (4.17) = 1.5333E+009$
--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, 1, 2, v$ normalised to $b_o * d_o$, instead of $b * d$
- - parameters of confined concrete, f_{cc}, cc , used in lieu of f_c, c_u
--->
Subcase: Rupture of tension steel
--->
 $v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied
--->
Subcase rejected
--->
New Subcase: Failure of compression zone
--->
 $v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied
--->
 $v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied
--->
 $*c_u (4.11) = 0.83790293$
 $M_{Ro} (4.18) = 1.6290E+009$
--->
 $u = c_u (4.2) = 1.0952761E-005$

Mu = MRo

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 1.0879E+006

Calculation of Shear Strength at edge 1, Vr1 = 1.0879E+006

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0

VCol0 = 1.0879E+006

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 15.20, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 4.8236E+008

Vu = 1.7986448E-005

d = 0.8*h = 600.00

Nu = 5.0813E+006

Ag = 337500.00

From (11.5.4.8), ACI 318-14: Vs = Vs_jacket + Vs_core = 1.0354E+006

where:

Vs_jacket = Vs_j1 + Vs_j2 = 942477.796

Vs_j1 = 589048.623 is calculated for section web jacket, with:

d = 600.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs_j1 is multiplied by Col_j1 = 1.00

s/d = 0.16666667

Vs_j2 = 353429.174 is calculated for section flange jacket, with:

d = 360.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs_j2 is multiplied by Col_j2 = 1.00

s/d = 0.27777778

Vs_core = Vs_c1 + Vs_c2 = 92890.612

Vs_c1 = 92890.612 is calculated for section web core, with:

d = 440.00

Av = 100530.965

fy = 525.00

s = 250.00

Vs_c1 is multiplied by Col_c1 = 1.00

s/d = 0.56818182

Vs_c2 = 0.00 is calculated for section flange core, with:

d = 200.00

Av = 100530.965

fy = 525.00

s = 250.00

Vs_c2 is multiplied by Col_c2 = 0.00

s/d = 1.25

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 699281.943

bw = 450.00

Calculation of Shear Strength at edge 2, Vr2 = 1.0879E+006

Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0

VCol0 = 1.0879E+006

kn1 = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 15.20, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 4.5550E+008

Vu = 1.7986448E-005

d = 0.8*h = 600.00

Nu = 5.0813E+006

Ag = 337500.00

From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 1.0354E+006

where:

Vs,jacket = Vs,j1 + Vs,j2 = 942477.796

Vs,j1 = 589048.623 is calculated for section web jacket, with:

d = 600.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.16666667

Vs,j2 = 353429.174 is calculated for section flange jacket, with:

d = 360.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.27777778

Vs,core = Vs,c1 + Vs,c2 = 92890.612

Vs,c1 = 92890.612 is calculated for section web core, with:

d = 440.00

Av = 100530.965

fy = 525.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 1.00

s/d = 0.56818182

Vs,c2 = 0.00 is calculated for section flange core, with:

d = 200.00

Av = 100530.965

fy = 525.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 0.00

s/d = 1.25

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 699281.943

bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 0.80

Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
Concrete Elasticity, $E_c = 19940.411$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
Concrete Elasticity, $E_c = 16281.278$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$
Existing Column
Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$

Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$
Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $E_{cc} = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.42131
Element Length, $L = 3000.00$
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -5.5168185E-006$
EDGE -B-
Shear Force, $V_b = 5.5168185E-006$
BOTH EDGES
Axial Force, $F = -5.0813E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl, t} = 314.1593$
-Compression: $A_{sl, c} = 6377.433$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl, ten} = 1539.38$
-Compression: $A_{sl, com} = 1539.38$
-Middle: $A_{sl, mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.44711$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 1.9243E+006$
with
 $M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 2.8865E+009$
 $M_{u1+} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u1-} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination

$$M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 2.8865E+009$$

$\mu_{2+} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination

$\mu_{2-} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 9.9083764E-006$$

$$M_u = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$\omega (5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \mu_c: \mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01486841$$

$$\omega_e (5.4c) = 0.08077545$$

$$\omega_{se} ((5.4d), \text{TBDY}) = (\omega_{se1} * A_{ext} + \omega_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$\omega_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\omega_{se2} (> = \omega_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00
s1 = 100.00
s2 = 250.00
fywe1 = 781.25
fywe2 = 656.25
fce = 18.00

From ((5.A.5), TBDY), TBDY: cc = 0.00621307
c = confinement factor = 1.42131

y1 = 0.0025
sh1 = 0.008
ft1 = 907.50
fy1 = 756.25
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 907.50
fy2 = 756.25
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 899.1522
fyv = 749.2935
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977

2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977

v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443

and confined core properties:

b = 390.00
d = 877.00
d' = 13.00

```

fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264
2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264
v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*s,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009
---->
u = cu (4.2) = 9.9083764E-006
Mu = MRo
-----

Calculation of ratio lb/d
-----
Adequate Lap Length: lb/d >= 1
-----
-----
Calculation of Mu1-
-----
-----

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
u = 9.9083764E-006
Mu = 2.8865E+009
-----

with full section properties:

```

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01486841$$

$$w_e (5.4c) = 0.08077545$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i d_i / 6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i d_i / 6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along } Y) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along } Y) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along } X) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along } X) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 18.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } c_c = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 907.50$$

$$fy1 = 756.25$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 899.1522

fyv = 749.2935

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977

2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977

v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443

and confined core properties:

b = 390.00

d = 877.00

d' = 13.00

fcc (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264

2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264

v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is not satisfied

--->

v < vs,c - RHS eq.(4.5) is not satisfied

--->

Case/Assumption Rejected.

--->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

satisfies Eq. (4.4)

---->

$v < s_y1$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

ϵ_{cu} (4.10) = 0.6344264

M_{Rc} (4.17) = 2.3433E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b , d , d' replaced by geometric parameters of the core: b_o , d_o , d'_o
- N , ϵ_1 , ϵ_2 , v normalised to b_o*d_o , instead of $b*d$
- ϵ_c , ϵ_{cc} - parameters of confined concrete, f_{cc} , ϵ_{cc} , used in lieu of f_c , ϵ_{cu}

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*s_y2$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*s_{c,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*c_{y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*c_{y1}$ - RHS eq.(4.6) is not satisfied

---->

ϵ^*_{cu} (4.11) = 0.71499649

M_{Ro} (4.18) = 2.8865E+009

---->

$\epsilon_u = \epsilon_{cu}$ (4.2) = 9.9083764E-006

$M_u = M_{Ro}$

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

Calculation of M_{u2+}

Calculation of ultimate curvature ϵ_u according to 4.1, Biskinis/Fardis 2013:

$\epsilon_u = 9.9083764E-006$

$M_u = 2.8865E+009$

with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.69163741$

$N = 5.0813E+006$

$f_c = 18.00$

ϵ_{co} (5A.5, TBDY) = 0.002

Final value of ϵ_{cu} : $\epsilon_{cu}^* = \text{shear_factor} * \text{Max}(\epsilon_{cu}, \epsilon_{cc}) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\epsilon_{cu} = 0.01486841$

ϵ_{we} (5.4c) = 0.08077545

ϵ_{ase} ((5.4d), TBDY) = $(\epsilon_{ase1} * A_{ext} + \epsilon_{ase2} * A_{int}) / A_{sec} = 0.53375773$

$\epsilon_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.
 $A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noconf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noconf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noconf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noconf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$

$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$

$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$p_{sh2} ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * e_{su1,nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,

For calculation of $e_{su1,nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 756.25$

with $E_{s1} = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 907.50$

$fy2 = 756.25$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_{b,min} = 1.00$
 $s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,
For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{s2} = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 756.25$
with $E_{s2} = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 899.1522$
 $fy_v = 749.2935$
 $s_{uv} = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 1.00$
 $s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,
considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{sv} = (f_{s,jacket} * A_{sl,mid,jacket} + f_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 749.2935$
with $E_{sv} = (E_{s,jacket} * A_{sl,mid,jacket} + E_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

$1 = A_{sl,ten} / (b * d) * (f_{s1} / f_c) = 0.15845977$
 $2 = A_{sl,com} / (b * d) * (f_{s2} / f_c) = 0.15845977$
 $v = A_{sl,mid} / (b * d) * (f_{sv} / f_c) = 0.36847443$

and confined core properties:

$b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{sl,ten} / (b * d) * (f_{s1} / f_c) = 0.18909264$
 $2 = A_{sl,com} / (b * d) * (f_{s2} / f_c) = 0.18909264$
 $v = A_{sl,mid} / (b * d) * (f_{sv} / f_c) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture
'satisfies Eq. (4.3)

---->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->
Case/Assumption Rejected.

---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
'satisfies Eq. (4.4)

---->
 $v < s_{y1}$ - LHS eq.(4.7) is not satisfied

---->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->
 $c_u (4.10) = 0.6344264$
 $M_{Rc} (4.17) = 2.3433E+009$

---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, 1, 2, v$ normalised to $b_o * d_o$, instead of $b * d$
- parameters of confined concrete, f_{cc}, cc , used in lieu of f_c, e_{cu}

---->
Subcase: Rupture of tension steel

--->
 $v^* < v^*s,y2$ - LHS eq.(4.5) is not satisfied

--->
 $v^* < v^*s,c$ - LHS eq.(4.5) is not satisfied

--->
Subcase rejected

--->
New Subcase: Failure of compression zone

--->
 $v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

--->
 $v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

--->
 $*c_u$ (4.11) = 0.71499649

MRO (4.18) = 2.8865E+009

--->
 $u = c_u$ (4.2) = 9.9083764E-006
Mu = MRO

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_2 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 9.9083764E-006$

Mu = 2.8865E+009

with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.69163741$

$N = 5.0813E+006$

$f_c = 18.00$

c_o (5A.5, TBDY) = 0.002

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (\geq ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $bi^2/6$ as defined at (A.2).
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 2.724

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.724
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00301593
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
psh2 (5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.25416
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00357443
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00070345
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00
s1 = 100.00
s2 = 250.00
fywe1 = 781.25
fywe2 = 656.25
fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307
c = confinement factor = 1.42131

y1 = 0.0025
sh1 = 0.008
ft1 = 907.50
fy1 = 756.25
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 907.50
fy2 = 756.25
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 899.1522
fyv = 749.2935
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_0/l_{0,min} = l_b/l_d = 1.00$

$s_{uv} = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and γ_v , sh_v, ft_v, f_{y_v} , it is considered
characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

$\gamma_1, sh_1, ft_1, f_{y_1}$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 749.2935$

with $E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.15845977$

$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.15845977$

$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.36847443$

and confined core properties:

$b = 390.00$

$d = 877.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.18909264$

$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.18909264$

$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

$c_u (4.10) = 0.6344264$

$M_{Rc} (4.17) = 2.3433E+009$

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_0, d_0, d'_0

- $N, 1, 2, v$ normalised to $b_0 * d_0$, instead of $b * d$

- parameters of confined concrete, f_{cc}, cc , used in lieu of f_c, e_{cu}

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$*c_u (4.11) = 0.71499649$

$M_{Ro} (4.18) = 2.8865E+009$

---->

$$u = cu(4.2) = 9.9083764E-006$$

$$\text{Mu} = \text{MRo}$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.3298E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.3298E+006$

$$V_{r1} = V_{Co10} \text{ ((10.3), ASCE 41-17)} = kn1 * V_{Co10}$$

$$V_{Co10} = 1.3298E+006$$

$kn1 = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} * \text{Area}_{\text{jacket}} + f_c'_{\text{core}} * \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\text{Mu} = 1.7267E+008$$

$$V_u = 5.5168185E-006$$

$$d = 0.8 * h = 760.00$$

$$N_u = 5.0813E+006$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.2262E+006$$

where:

$$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 1.0996E+006$$

$V_{s,j1} = 353429.174$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 126669.016$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 126669.016$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

From (11-11), ACI 440: $V_s + V_f \leq 885757.128$

$$bw = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.3298E+006$

$V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$

$V_{Col0} = 1.3298E+006$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$, but $f_c'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$M / Vd = 4.00$

$\mu_u = 1.6609E+008$

$V_u = 5.5168185E-006$

$d = 0.8 * h = 760.00$

$N_u = 5.0813E+006$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 1.2262E+006$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 1.0996E+006$

$V_{sj1} = 353429.174$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

V_{sj1} is multiplied by $Col_{j1} = 1.00$

$s/d = 0.27777778$

$V_{sj2} = 746128.255$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

V_{sj2} is multiplied by $Col_{j2} = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col_{c1} = 0.00$

$s/d = 1.25$

$V_{s,c2} = 126669.016$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col_{c2} = 1.00$

$s/d = 0.41666667$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 885757.128$

$bw = 450.00$

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\phi = 0.80$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/l_d >= 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -1.8918E+009$

Shear Force, $V_2 = -638013.908$

Shear Force, $V_3 = 2.2058$

Axial Force, $F = -5.0666E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 3345.796$

-Compression: $A_{sl,c} = 3345.796$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 1539.38$

-Middle: $A_{sl,mid} = 3612.832$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,jacket} = 1231.504$

-Compression: $A_{sl,com,jacket} = 1231.504$

-Middle: $A_{sl,mid,jacket} = 2689.203$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,core} = 307.8761$

-Compression: $A_{sl,com,core} = 307.8761$

-Middle: $A_{sl,mid,core} = 923.6282$

Mean Diameter of Tension Reinforcement, $Db_L = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = \phi * u = 0.01309245$

$u = y + p = 0.01636556$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00352672$ ((4.29), Biskinis Phd))

$M_y = 1.6309E+009$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 2965.168

From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 4.5707E+014$

factor = 0.70
 $A_g = 562500.00$
Mean concrete strength: $f_c' = (f_{c'}^{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_{c'}^{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 15.20$
 $N = 5.0666E+006$
 $E_c \cdot I_g = E_{c_{\text{jacket}}} \cdot I_{g_{\text{jacket}}} + E_{c_{\text{core}}} \cdot I_{g_{\text{core}}} = 6.5295E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

 $y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 6.3752290E-006$
with $f_y = 601.9953$
 $d = 907.00$
 $y = 0.4794529$
 $A = 0.03701556$
 $B = 0.02920673$
with $p_t = 0.0037716$
 $p_c = 0.0037716$
 $p_v = 0.00885172$
 $N = 5.0666E+006$
 $b = 450.00$
 $" = 0.04740904$
 $y_{\text{comp}} = 2.6045948E-006$
with $f_c = 18.00$
 $E_c = 19940.411$
 $y = 0.687802$
 $A = -0.02180425$
 $B = 0.0085861$
with $E_s = 200000.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of p -

From table 10-8: $p = 0.01283884$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/d \geq 1$
shear control ratio $V_y E / V_{col} O E = 1.44711$

$d = d_{\text{external}} = 907.00$

$s = s_{\text{external}} = 100.00$

- $t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00427788$

jacket: $s_1 = A_{v1} \cdot L_{\text{stir1}} / (s_1 \cdot A_g) = 0.00357443$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir1}} = 2560.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot L_{\text{stir2}} / (s_2 \cdot A_g) = 0.00070345$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir2}} = 1968.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5.0666E+006$

$A_g = 562500.00$

$f_{cE} = (f_{c'}^{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_{c'}^{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{section_area} = 15.20$

$f_{yIE} = (f_{y_{\text{ext_Long_Reinf}}} \cdot \text{Area}_{\text{ext_Long_Reinf}} + f_{y_{\text{int_Long_Reinf}}} \cdot \text{Area}_{\text{int_Long_Reinf}}) / \text{Area}_{\text{Tot_Long_Rein}} = 601.9953$

$f_{yTE} = (f_{y_{\text{ext_Trans_Reinf}}} \cdot s_1 + f_{y_{\text{int_Trans_Reinf}}} \cdot s_2) / (s_1 + s_2) = 608.5561$


$p_l = \text{Area}_{\text{Tot_Long_Rein}} / (b \cdot d) = 0.01639493$

b = 450.00
d = 907.00
f_{cE} = 15.20

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 13

column C1, Floor 1
Limit State: Life Safety (data interpolation between analysis steps 50 and 51)
Analysis: Uniform +X
Check: Shear capacity VR_d
Edge: End
Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (b)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$
Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.
Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 12.00$
New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$
Concrete Elasticity, $E_c = 19940.411$
Steel Elasticity, $E_s = 200000.00$
Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 8.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 18.00$

New material: Steel Strength, $f_s = f_{sm} = 625.00$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material: Steel Strength, $f_s = f_{sm} = 525.00$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} = l_b/d >= 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -1.8918E+009$

Shear Force, $V_a = -638013.908$

EDGE -B-

Bending Moment, $M_b = -3.3682E+008$

Shear Force, $V_b = 638013.908$

BOTH EDGES

Axial Force, $F = -5.0666E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 314.1593$

-Compression: $A_{sl,c} = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 1539.38$

-Middle: $A_{sl,mid} = 3612.832$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 1.2114E+006$

V_n ((10.3), ASCE 41-17) = $k_n l V_{CoI} = 1.5142E+006$

$V_{CoI} = 1.5142E+006$

$k_n = 1.00$

displacement_ductility_demand = 1.40424

NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + \phi V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_c_jacket * Area_jacket + f'_c_core * Area_core) / Area_section = 10.13333$, but $f'_c^{0.5} < = 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu = 3.3682E+008$
 $V_u = 638013.908$
 $d = 0.8 \cdot h = 760.00$
 $N_u = 5.0666E+006$
 $A_g = 427500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 980981.156$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 879645.943$

$V_{s,j1} = 282743.339$ is calculated for section web jacket, with:

$d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 596902.604$ is calculated for section flange jacket, with:

$d = 760.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 101335.213$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$s/d = 1.25$

$V_{s,c2} = 101335.213$ is calculated for section flange core, with:

$d = 600.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$s/d = 0.41666667$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 723217.666$

$b_w = 450.00$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END B -
for rotation axis 3 and integ. section (b)

From analysis, chord rotation = 0.00088171

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.0006279$ ((4.29), Biskinis Phd))

$M_y = 1.6309E+009$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 527.9175

From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 4.5707E+014$

factor = 0.70

$A_g = 562500.00$

Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 15.20$

$N = 5.0666E+006$

$E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 6.5295E+014$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

$y = \min(y_{ten}, y_{com})$

$y_{ten} = 6.3752290E-006$

with $f_y = 601.9953$
 $d = 907.00$
 $y = 0.4794529$
 $A = 0.03701556$
 $B = 0.02920673$
with $p_t = 0.0037716$
 $p_c = 0.0037716$
 $p_v = 0.00885172$
 $N = 5.0666E+006$
 $b = 450.00$
 $" = 0.04740904$
 $y_{comp} = 2.6045948E-006$
with $f_c = 18.00$
 $E_c = 19940.411$
 $y = 0.687802$
 $A = -0.02180425$
 $B = 0.0085861$
with $E_s = 200000.00$

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 14

column C1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3
(Bending local axis: 2)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
Concrete Elasticity, $E_c = 19940.411$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
Concrete Elasticity, $E_c = 16281.278$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket
New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$
Existing Column
Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$
#####

Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$
Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $Ecc = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.42131
Element Length, $L = 3000.00$
Primary Member
Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = -1.7986448E-005$
EDGE -B-
Shear Force, $V_b = 1.7986448E-005$
BOTH EDGES
Axial Force, $F = -5.0813E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 314.1593$
-Compression: $As_c = 6377.433$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1539.38$
-Compression: $As_{l,com} = 2475.575$
-Middle: $As_{l,mid} = 2676.637$

Calculation of Shear Capacity ratio , $V_e/V_r = 1.92314$

Member Controlled by Shear ($V_e/V_r > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 2.0922E+006$
with

$M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 3.1383E+009$

$\mu_{1+} = 3.1383E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$\mu_{1-} = 1.6290E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 3.1383E+009$

$\mu_{2+} = 3.1383E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{2-} = 1.6290E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.9524665E-005$

$\mu_u = 3.1383E+009$

with full section properties:

$b = 950.00$

$d = 707.00$

$d' = 43.00$

$\nu = 0.420296$

$N = 5.0813E+006$

$f_c = 18.00$

α_c (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.01486841$

ω_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b^2/6$ as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.25416
psh₁ ((5.4d), TBDY) = Lstir₁*Astir₁/(Asec*s₁) = 0.00357443
Lstir₁ (Length of stirrups along X) = 2560.00
Astir₁ (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = Lstir₂*Astir₂/(Asec*s₂) = 0.00070345
Lstir₂ (Length of stirrups along X) = 1968.00
Astir₂ (stirrups area) = 50.26548

Asec = 562500.00
s₁ = 100.00
s₂ = 250.00

fywe₁ = 781.25
fywe₂ = 656.25
fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307
c = confinement factor = 1.42131

y₁ = 0.0025
sh₁ = 0.008
ft₁ = 907.50
fy₁ = 756.25
su₁ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*Asl_{ten,jacket} + fs_{core}*Asl_{ten,core})/Asl_{ten} = 756.25

with Es₁ = (Es_{jacket}*Asl_{ten,jacket} + Es_{core}*Asl_{ten,core})/Asl_{ten} = 200000.00

y₂ = 0.0025
sh₂ = 0.008

ft₂ = 900.1904
fy₂ = 750.1586

su₂ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*Asl_{com,jacket} + fs_{core}*Asl_{com,core})/Asl_{com} = 750.1586

with Es₂ = (Es_{jacket}*Asl_{com,jacket} + Es_{core}*Asl_{com,core})/Asl_{com} = 200000.00

y_v = 0.0025
sh_v = 0.008

ft_v = 902.993
fy_v = 752.4941

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_{nominal} = 0.08,

considering characteristic value fsy_v = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_{nominal} and y_v, sh_v,ft_v,fy_v, it is considered
characteristic value fsy_v = fsv/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fsv = (fs_{jacket}*Asl_{mid,jacket} + fs_{mid}*Asl_{mid,core})/Asl_{mid} = 752.4941

```

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.09629324
2 = Asl,com/(b*d)*(fs2/fc) = 0.15360794
v = Asl,mid/(b*d)*(fsv/fc) = 0.16660079
and confined core properties:
b = 890.00
d = 677.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.10733965
2 = Asl,com/(b*d)*(fs2/fc) = 0.17122928
v = Asl,mid/(b*d)*(fsv/fc) = 0.18571261
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
--->
v < vs,y2 - LHS eq.(4.5) is not satisfied
--->
v < vs,c - RHS eq.(4.5) is not satisfied
--->
Case/Assumption Rejected.
--->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
--->
v < s,y1 - LHS eq.(4.7) is not satisfied
--->
v < vc,y1 - RHS eq.(4.6) is satisfied
--->
cu (4.10) = 0.42075151
MRc (4.17) = 2.3432E+009
--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
--->
Subcase: Rupture of tension steel
--->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
--->
v* < v*s,c - LHS eq.(4.5) is not satisfied
--->
Subcase rejected
--->
New Subcase: Failure of compression zone
--->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
--->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
--->
*cu (4.11) = 0.47003883
MRo (4.18) = 3.1383E+009
--->
u = cu (4.2) = 1.9524665E-005
Mu = MRo
-----

Calculation of ratio lb/d
-----
Adequate Lap Length: lb/d >= 1
-----
-----
-----
Calculation of Mu1-

```

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0952761E-005$$

$$\mu_u = 1.6290E+009$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.88729156$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu_u: \mu_u^* = \text{shear_factor} * \text{Max}(\mu_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_u = 0.01486841$$

$$w_e(5.4c) = 0.08077545$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2}((5.4d)) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2}((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$f_{ce} = 18.00$
 From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $y_1 = 0.0025$
 $sh_1 = 0.008$
 $ft_1 = 900.1904$
 $fy_1 = 750.1586$
 $su_1 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou, \min = lb/ld = 1.00$
 $su_1 = 0.4 * esu_1 \text{ nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu_1 \text{ nominal} = 0.08$,
 For calculation of $esu_1 \text{ nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
 characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_1 = (fs_{\text{jacket}} * A_{sl, \text{ten, jacket}} + fs_{\text{core}} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 750.1586$
 with $Es_1 = (Es_{\text{jacket}} * A_{sl, \text{ten, jacket}} + Es_{\text{core}} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou, \min = lb/lb, \min = 1.00$
 $su_2 = 0.4 * esu_2 \text{ nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu_2 \text{ nominal} = 0.08$,
 For calculation of $esu_2 \text{ nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{\text{jacket}} * A_{sl, \text{com, jacket}} + fs_{\text{core}} * A_{sl, \text{com, core}}) / A_{sl, \text{com}} = 756.25$
 with $Es_2 = (Es_{\text{jacket}} * A_{sl, \text{com, jacket}} + Es_{\text{core}} * A_{sl, \text{com, core}}) / A_{sl, \text{com}} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 902.993$
 $fy_v = 752.4941$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou, \min = lb/ld = 1.00$
 $suv = 0.4 * esuv \text{ nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esuv \text{ nominal} = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv \text{ nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{\text{jacket}} * A_{sl, \text{mid, jacket}} + fs_{\text{mid}} * A_{sl, \text{mid, core}}) / A_{sl, \text{mid}} = 752.4941$
 with $Es_v = (Es_{\text{jacket}} * A_{sl, \text{mid, jacket}} + Es_{\text{mid}} * A_{sl, \text{mid, core}}) / A_{sl, \text{mid}} = 200000.00$
 $1 = A_{sl, \text{ten}} / (b * d) * (fs_1 / f_c) = 0.32428344$
 $2 = A_{sl, \text{com}} / (b * d) * (fs_2 / f_c) = 0.20328574$
 $v = A_{sl, \text{mid}} / (b * d) * (fsv / f_c) = 0.35171278$
 and confined core properties:
 $b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, \text{TBDY}) = 25.58352$
 $cc (5A.5, \text{TBDY}) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{sl, \text{ten}} / (b * d) * (fs_1 / f_c) = 0.39075399$
 $2 = A_{sl, \text{com}} / (b * d) * (fs_2 / f_c) = 0.24495458$
 $v = A_{sl, \text{mid}} / (b * d) * (fsv / f_c) = 0.42380571$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

v < vs,y2 - LHS eq.(4.5) is not satisfied

v < vs,c - RHS eq.(4.5) is not satisfied

Case/Assumption Rejected.

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

v < vs,y1 - LHS eq.(4.7) is not satisfied

v < vc,y1 - RHS eq.(4.6) is satisfied

cu (4.10) = 0.82478813

MRC (4.17) = 1.5333E+009

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o

- N, ν_1 , ν_2 , ν normalised to bo*do, instead of b*d

- parameters of confined concrete, fcc, cc, used in lieu of fc, ecu

Subcase: Rupture of tension steel

v* < v*s,y2 - LHS eq.(4.5) is not satisfied

v* < v*s,c - LHS eq.(4.5) is not satisfied

Subcase rejected

New Subcase: Failure of compression zone

v* < v*c,y2 - LHS eq.(4.6) is not satisfied

v* < v*c,y1 - RHS eq.(4.6) is not satisfied

*cu (4.11) = 0.83790293

MRO (4.18) = 1.6290E+009

u = cu (4.2) = 1.0952761E-005

Mu = MRO

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2+

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

u = 1.9524665E-005

Mu = 3.1383E+009

with full section properties:

b = 950.00

d = 707.00

d' = 43.00

v = 0.420296

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.724$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.25416$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00621307$

c = confinement factor = 1.42131

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * e_{su1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,

For calculation of $e_{su1,nominal}$ and $y1$, $sh1$, $ft1$, $fy1$, it is considered

characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 756.25$
 with $Es_1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 900.1904$
 $fy_2 = 750.1586$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{ou,min} = lb/lb_{,min} = 1.00$
 $su_2 = 0.4 \cdot esu_2_{nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu_2_{nominal} = 0.08$,
 For calculation of $esu_2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2 / 1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 750.1586$
 with $Es_2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 902.993$
 $fy_v = 752.4941$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{ou,min} = lb/ld = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsyv = fsv / 1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsyv = fsv / 1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 752.4941$
 with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.09629324$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.15360794$
 $v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.16660079$
 and confined core properties:
 $b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $fcc (5A.2, \text{TBDY}) = 25.58352$
 $cc (5A.5, \text{TBDY}) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.10733965$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.17122928$
 $v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.18571261$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y_2}$ - LHS eq.(4.5) is not satisfied
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s_{y_1}$ - LHS eq.(4.7) is not satisfied
 --->
 $v < v_{c,y_1}$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.42075151$
 $MRC (4.17) = 2.3432E+009$

--->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, ν , ν normalised to $b_o \cdot d_o$, instead of $b \cdot d$
- parameters of confined concrete, f_{cc} , ϵ_{cc} , used in lieu of f_c , ϵ_{cu}

--->

Subcase: Rupture of tension steel

--->

$\nu^* < \nu^* s_y^2$ - LHS eq.(4.5) is not satisfied

--->

$\nu^* < \nu^* s_c$ - LHS eq.(4.5) is not satisfied

--->

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$\nu^* < \nu^* c_y^2$ - LHS eq.(4.6) is not satisfied

--->

$\nu^* < \nu^* c_y^1$ - RHS eq.(4.6) is not satisfied

--->

$\epsilon_{cu} (4.11) = 0.47003883$

$M_{Ro} (4.18) = 3.1383E+009$

--->

$u = \epsilon_{cu} (4.2) = 1.9524665E-005$

$\mu_u = M_{Ro}$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_u

Calculation of ultimate curvature ϵ_{cu} according to 4.1, Biskinis/Fardis 2013:

$u = 1.0952761E-005$

$\mu_u = 1.6290E+009$

with full section properties:

$b = 450.00$

$d = 707.00$

$d' = 43.00$

$\nu = 0.88729156$

$N = 5.0813E+006$

$f_c = 18.00$

$\epsilon_{co} (5A.5, TBDY) = 0.002$

Final value of ϵ_{cu} : $\epsilon_{cu}^* = \text{shear_factor} * \text{Max}(\epsilon_{cu}, \epsilon_{cc}) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\epsilon_{cu} = 0.01486841$

$\epsilon_{we} (5.4c) = 0.08077545$

$\epsilon_{ase} ((5.4d), TBDY) = (\epsilon_{ase1} * A_{ext} + \epsilon_{ase2} * A_{int}) / A_{sec} = 0.53375773$

$\epsilon_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

$$AnoConf2 = 110709.333 \text{ is the unconfined internal core area which is equal to } bi^2/6 \text{ as defined at (A.2).}$$

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.724$$

$$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.724$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1 \text{ (Length of stirrups along Y)} = 2160.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

$$Lstir2 \text{ (Length of stirrups along Y)} = 1568.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.25416$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

$$Lstir1 \text{ (Length of stirrups along X)} = 2560.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

$$Lstir2 \text{ (Length of stirrups along X)} = 1968.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 781.25$$

$$fywe2 = 656.25$$

$$fce = 18.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 900.1904$$

$$fy1 = 750.1586$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 1.00$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_nominal = 0.08,$$

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 750.1586$$

$$\text{with } Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 907.50$$

$$fy2 = 756.25$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4 * esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_nominal = 0.08,$$

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 756.25$
 with $Es2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$
 $yv = 0.0025$
 $shv = 0.008$
 $ftv = 902.993$
 $fyv = 752.4941$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 1.00$
 $suv = 0.4 \cdot esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} \cdot A_{sl,mid,jacket} + fs_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 752.4941$
 with $Esv = (Es_{jacket} \cdot A_{sl,mid,jacket} + Es_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$
 $1 = A_{sl,ten} / (b \cdot d) \cdot (fs1 / fc) = 0.32428344$
 $2 = A_{sl,com} / (b \cdot d) \cdot (fs2 / fc) = 0.20328574$
 $v = A_{sl,mid} / (b \cdot d) \cdot (fsv / fc) = 0.35171278$
 and confined core properties:
 $b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{sl,ten} / (b \cdot d) \cdot (fs1 / fc) = 0.39075399$
 $2 = A_{sl,com} / (b \cdot d) \cdot (fs2 / fc) = 0.24495458$
 $v = A_{sl,mid} / (b \cdot d) \cdot (fsv / fc) = 0.42380571$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is not satisfied
 --->
 $v < vs,c$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s,y1$ - LHS eq.(4.7) is not satisfied
 --->
 $v < vc,y1$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.82478813$
 $MRC (4.17) = 1.5333E+009$
 --->
 New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
 In expressions below, the following modifications have been made
 - b, d, d' replaced by geometric parameters of the core: $bo, do, d'o$
 - $N, 1, 2, v$ normalised to $bo \cdot do$, instead of $b \cdot d$
 - f, c parameters of confined concrete, fcc, cc , used in lieu of fc, ecu
 --->
 Subcase: Rupture of tension steel
 --->
 $v^* < v^*s,y2$ - LHS eq.(4.5) is not satisfied
 --->
 $v^* < v^*s,c$ - LHS eq.(4.5) is not satisfied
 --->
 Subcase rejected
 --->
 New Subcase: Failure of compression zone

--->
 $v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

--->
 $v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

--->
 $*c_u$ (4.11) = 0.83790293
MRo (4.18) = 1.6290E+009

--->
 $u = c_u$ (4.2) = 1.0952761E-005
Mu = MRo

Calculation of ratio lb/d

Adequate Lap Length: lb/d \geq 1

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0879E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0879E+006$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} * V_{ColO}$

$V_{ColO} = 1.0879E+006$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} = f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$, but $f_c'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 4.8236E+008$

$V_u = 1.7986448E-005$

$d = 0.8 * h = 600.00$

$N_u = 5.0813E+006$

$A_g = 337500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 1.0354E+006$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 942477.796$

$V_{sj1} = 589048.623$ is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

V_{sj1} is multiplied by $Col,j1 = 1.00$

$s/d = 0.16666667$

$V_{sj2} = 353429.174$ is calculated for section flange jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

V_{sj2} is multiplied by $Col,j2 = 1.00$

$s/d = 0.27777778$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$

$V_{s,c1} = 92890.612$ is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 525.00$

s = 250.00
Vs,c2 is multiplied by Col,c2 = 0.00
s/d = 1.25
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 699281.943
bw = 450.00

Calculation of Shear Strength at edge 2, Vr2 = 1.0879E+006
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 1.0879E+006
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*VF'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 15.20, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/d = 4.00
Mu = 4.5550E+008
Vu = 1.7986448E-005
d = 0.8*h = 600.00
Nu = 5.0813E+006
Ag = 337500.00
From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 1.0354E+006

where:

Vs,jacket = Vs,j1 + Vs,j2 = 942477.796
Vs,j1 = 589048.623 is calculated for section web jacket, with:

d = 600.00
Av = 157079.633
fy = 625.00
s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00
s/d = 0.16666667

Vs,j2 = 353429.174 is calculated for section flange jacket, with:

d = 360.00
Av = 157079.633
fy = 625.00
s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00
s/d = 0.27777778

Vs,core = Vs,c1 + Vs,c2 = 92890.612

Vs,c1 = 92890.612 is calculated for section web core, with:

d = 440.00
Av = 100530.965
fy = 525.00
s = 250.00

Vs,c1 is multiplied by Col,c1 = 1.00
s/d = 0.56818182

Vs,c2 = 0.00 is calculated for section flange core, with:

d = 200.00
Av = 100530.965
fy = 525.00
s = 250.00

Vs,c2 is multiplied by Col,c2 = 0.00
s/d = 1.25

Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 699281.943
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjctc

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.42131

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -5.5168185E-006$

EDGE -B-

Shear Force, $V_b = 5.5168185E-006$

BOTH EDGES

Axial Force, $F = -5.0813E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 314.1593$

-Compression: $A_{sl,c} = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 1539.38$

-Middle: $A_{sl,mid} = 3612.832$

Calculation of Shear Capacity ratio , $V_e/V_r = 1.44711$

Member Controlled by Shear ($V_e/V_r > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 1.9243E+006$

with
 $M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 2.8865E+009$
 $M_{u1+} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $M_{u1-} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 2.8865E+009$
 $M_{u2+} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $M_{u2-} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 9.9083764E-006$

$M_u = 2.8865E+009$

with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.69163741$

$N = 5.0813E+006$

$f_c = 18.00$

α (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.01486841$

we (5.4c) = 0.08077545

α_{se} ((5.4d), TBDY) = $(\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.53375773$

$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$\alpha_{se2} (> \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

psh2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.25416
psh1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A.5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 907.50

fy1 = 756.25

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = $0.4 * esu1_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_jacket * A_{sl,ten,jacket} + fs_core * A_{sl,ten,core}) / A_{sl,ten} = 756.25$

with Es1 = $(Es_jacket * A_{sl,ten,jacket} + Es_core * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.0025

sh2 = 0.008

ft2 = 907.50

fy2 = 756.25

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = $0.4 * esu2_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = $(fs_jacket * A_{sl,com,jacket} + fs_core * A_{sl,com,core}) / A_{sl,com} = 756.25$

with Es2 = $(Es_jacket * A_{sl,com,jacket} + Es_core * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.0025

shv = 0.008

ftv = 899.1522

fyv = 749.2935

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = $0.4 * esuv_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv, ftv, fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

```

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935
with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977
2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977
v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443
and confined core properties:
b = 390.00
d = 877.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264
2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264
v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
--->
v < vs,y2 - LHS eq.(4.5) is not satisfied
--->
v < vs,c - RHS eq.(4.5) is not satisfied
--->
Case/Assumption Rejected.
--->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
--->
v < sy1 - LHS eq.(4.7) is not satisfied
--->
v < vc,y1 - RHS eq.(4.6) is satisfied
--->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
--->
Subcase: Rupture of tension steel
--->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
--->
v* < v*s,c - LHS eq.(4.5) is not satisfied
--->
Subcase rejected
--->
New Subcase: Failure of compression zone
--->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
--->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
--->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009
--->
u = cu (4.2) = 9.9083764E-006
Mu = MRo

```

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 9.9083764E-006$$

$$Mu = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01486841$$

$$we (5.4c) = 0.08077545$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{,min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$$

$$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$$

$$psh1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$psh2 (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$$

$$psh1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$psh2 ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 781.25$$

$$fy_{w2} = 656.25$$

$$f_{ce} = 18.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$

$$c = \text{confinement factor} = 1.42131$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 907.50$$

$$fy_1 = 756.25$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu_{1, \text{nominal}}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{\text{jacket}} * A_{sl, \text{ten, jacket}} + fs_{\text{core}} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 756.25$$

$$\text{with } Es_1 = (Es_{\text{jacket}} * A_{sl, \text{ten, jacket}} + Es_{\text{core}} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 200000.00$$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 907.50$$

$$fy_2 = 756.25$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 1.00$$

$$su_2 = 0.4 * esu_{2, \text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{2, \text{nominal}} = 0.08$,

For calculation of $esu_{2, \text{nominal}}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{\text{jacket}} * A_{sl, \text{com, jacket}} + fs_{\text{core}} * A_{sl, \text{com, core}}) / A_{sl, \text{com}} = 756.25$$

$$\text{with } Es_2 = (Es_{\text{jacket}} * A_{sl, \text{com, jacket}} + Es_{\text{core}} * A_{sl, \text{com, core}}) / A_{sl, \text{com}} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 899.1522$$

$$fy_v = 749.2935$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{\text{jacket}} * A_{sl, \text{mid, jacket}} + fs_{\text{mid}} * A_{sl, \text{mid, core}}) / A_{sl, \text{mid}} = 749.2935$$

$$\text{with } Es_v = (Es_{\text{jacket}} * A_{sl, \text{mid, jacket}} + Es_{\text{mid}} * A_{sl, \text{mid, core}}) / A_{sl, \text{mid}} = 200000.00$$

$$1 = A_{sl, \text{ten}} / (b * d) * (fs_1 / f_c) = 0.15845977$$

$$2 = A_{sl, \text{com}} / (b * d) * (fs_2 / f_c) = 0.15845977$$

$$v = A_{sl, \text{mid}} / (b * d) * (fsv / f_c) = 0.36847443$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{TBDY}) = 25.58352$$

$$cc (5A.5, \text{TBDY}) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = A_{sl, \text{ten}} / (b * d) * (fs_1 / f_c) = 0.18909264$$

$$2 = A_{sl, \text{com}} / (b * d) * (fs_2 / f_c) = 0.18909264$$

$$v = A_{sl, \text{mid}} / (b * d) * (fsv / f_c) = 0.43970658$$

Case/Assumption: Unconfined full section - Steel rupture

```

' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < vs,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N1, N2, v normalised to bo*do, instead of b*d
- parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*s,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009
---->
u = cu (4.2) = 9.9083764E-006
Mu = MRo
-----

Calculation of ratio lb/d
-----
Adequate Lap Length: lb/d >= 1
-----
-----
-----

Calculation of Mu2+
-----
-----
-----

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
u = 9.9083764E-006
Mu = 2.8865E+009
-----

with full section properties:
b = 450.00
d = 907.00
d' = 43.00
v = 0.69163741
N = 5.0813E+006
fc = 18.00
co (5A.5, TBDY) = 0.002

```

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01486841$

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

c = confinement factor = 1.42131

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered

characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 756.25$

with $Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 907.50$

$fy2 = 756.25$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lo_{min} = lb/lb_{min} = 1.00$

$su2 = 0.4 \cdot esu2_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered

characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 756.25$

with $Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 899.1522$

$fyv = 749.2935$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lo_{min} = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 749.2935$

with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.15845977$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.15845977$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.36847443$

and confined core properties:

$b = 390.00$

$d = 877.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 25.58352$

$cc (5A.5, TBDY) = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.18909264$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.18909264$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.43970658$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is not satisfied

---->

$v < vs,c$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s,y1$ - LHS eq.(4.7) is not satisfied

---->

$v < vc,y1$ - RHS eq.(4.6) is satisfied

---->

$cu (4.10) = 0.6344264$

MRC (4.17) = 2.3433E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ec

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*s,y2$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*s,c$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

---->

*cu (4.11) = 0.71499649

MRO (4.18) = 2.8865E+009

---->

u = cu (4.2) = 9.9083764E-006

Mu = MRO

Calculation of ratio lb/ld

Adequate Lap Length: lb/ld >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 9.9083764E-006

Mu = 2.8865E+009

with full section properties:

b = 450.00

d = 907.00

d' = 43.00

v = 0.69163741

N = 5.0813E+006

fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - \text{AnoConf}_2)/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$
 The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
 J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.
 $A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.
 $\text{AnoConf}_2 = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 2.724$
 $psh_1 ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 $psh_2 (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.25416$
 $psh_1 ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 $psh_2 ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$
 $s_1 = 100.00$
 $s_2 = 250.00$
 $f_{ywe1} = 781.25$
 $f_{ywe2} = 656.25$
 $f_{ce} = 18.00$
 From ((5.A5), TBDY), TBDY: $cc = 0.00621307$
 $c = \text{confinement factor} = 1.42131$

$y_1 = 0.0025$
 $sh_1 = 0.008$
 $ft_1 = 907.50$
 $fy_1 = 756.25$
 $su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su_1 = 0.4 * esu_{1,nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 756.25$

with $Es_1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

$y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 907.50$
 $fy_2 = 756.25$
 $su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$

$su_2 = 0.4 * esu_{2,nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 756.25$
with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 899.1522$
 $f_{y_v} = 749.2935$
 $s_{u_v} = 0.032$
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 1.00$
 $s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,
considering characteristic value $f_{s_{y_v}} = f_{s_{y_v}}/1.2$, from table 5.1, TBDY
For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
characteristic value $f_{s_{y_v}} = f_{s_{y_v}}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $f_{s_v} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 749.2935$
with $E_{s_v} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.15845977$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.15845977$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{s_v} / f_c) = 0.36847443$
and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.18909264$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.18909264$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{s_v} / f_c) = 0.43970658$
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v < v_{s,c}$ - RHS eq.(4.5) is not satisfied
--->
Case/Assumption Rejected.
--->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
--->
 $v < s_{y1}$ - LHS eq.(4.7) is not satisfied
--->
 $v < v_{c,y1}$ - RHS eq.(4.6) is satisfied
--->
 $cu (4.10) = 0.6344264$
 $M_{Rc} (4.17) = 2.3433E+009$
--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, 1, 2, v$ normalised to $b_o \cdot d_o$, instead of $b \cdot d$
- f_{cc}, cc parameters of confined concrete, f_{cc}, cc , used in lieu of f_c, e_{cu}
--->
Subcase: Rupture of tension steel
--->
 $v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied
--->
Subcase rejected
--->

New Subcase: Failure of compression zone

--->

$v^* < v^*c,y2$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*c,y1$ - RHS eq.(4.6) is not satisfied

--->

*cu (4.11) = 0.71499649

MRO (4.18) = 2.8865E+009

--->

u = cu (4.2) = 9.9083764E-006

Mu = MRO

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.3298E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.3298E+006$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = knl* V_{Col0}

$V_{Col0} = 1.3298E+006$

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * \text{Area}_{jacket} + f_c'_{core} * \text{Area}_{core}) / \text{Area}_{section} = 15.20$, but $f_c'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1.7267E+008$

$V_u = 5.5168185E-006$

$d = 0.8 * h = 760.00$

$N_u = 5.0813E+006$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 1.2262E+006$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 1.0996E+006$

$V_{sj1} = 353429.174$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

V_{sj1} is multiplied by $Col,j1 = 1.00$

$s/d = 0.27777778$

$V_{sj2} = 746128.255$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

V_{sj2} is multiplied by $Col,j2 = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$s/d = 1.25$

$V_{s,c2} = 126669.016$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

fy = 525.00
s = 250.00
Vs,c2 is multiplied by Col,c2 = 1.00
s/d = 0.41666667
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 885757.128
bw = 450.00

Calculation of Shear Strength at edge 2, Vr2 = 1.3298E+006
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 1.3298E+006
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*VF'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 15.20, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00
Mu = 1.6609E+008
Vu = 5.5168185E-006
d = 0.8*h = 760.00
Nu = 5.0813E+006
Ag = 427500.00
From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 1.2262E+006
where:

Vs,jacket = Vs,j1 + Vs,j2 = 1.0996E+006
Vs,j1 = 353429.174 is calculated for section web jacket, with:
d = 360.00
Av = 157079.633
fy = 625.00
s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00
s/d = 0.27777778
Vs,j2 = 746128.255 is calculated for section flange jacket, with:
d = 760.00
Av = 157079.633
fy = 625.00
s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00
s/d = 0.13157895
Vs,core = Vs,c1 + Vs,c2 = 126669.016
Vs,c1 = 0.00 is calculated for section web core, with:
d = 200.00
Av = 100530.965
fy = 525.00
s = 250.00

Vs,c1 is multiplied by Col,c1 = 0.00
s/d = 1.25
Vs,c2 = 126669.016 is calculated for section flange core, with:
d = 600.00
Av = 100530.965
fy = 525.00
s = 250.00

Vs,c2 is multiplied by Col,c2 = 1.00
s/d = 0.41666667
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 885757.128
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/l_d > 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 4.5511E+008$

Shear Force, $V_2 = 638013.908$

Shear Force, $V_3 = -2.2058$

Axial Force, $F = -5.0666E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 314.1593$

-Compression: $A_{sl,c} = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 2475.575$

-Middle: $A_{sl,mid} = 2676.637$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,jacket} = 1231.504$

-Compression: $A_{sl,com,jacket} = 1859.823$

-Middle: $A_{sl,mid,jacket} = 2060.885$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,core} = 307.8761$

-Compression: $A_{sl,com,core} = 615.7522$

-Middle: $A_{sl,mid,core} = 615.7522$

Mean Diameter of Tension Reinforcement, $DbL = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $\phi_{u,R} = \phi_u = 0.01920821$

$$u = y + p = 0.02401027$$

- Calculation of y -

$$y = (M_y * L_s / 3) / E_{eff} = 0.01234946 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 1.8636E+009$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 6000.00$$

$$\text{From table 10.5, ASCE 41_17: } E_{eff} = \text{factor} * E_c * I_g = 3.0181E+014$$

$$\text{factor} = 0.70$$

$$A_g = 562500.00$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{\text{jacket}} * A_{\text{jacket}} + f_c'_{\text{core}} * A_{\text{core}}) / A_{\text{section}} = 15.20$$

$$N = 5.0666E+006$$

$$E_c * I_g = E_{c_{\text{jacket}}} * I_{g_{\text{jacket}}} + E_{c_{\text{core}}} * I_{g_{\text{core}}} = 4.3116E+014$$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

$$\text{flange width, } b = 950.00$$

$$\text{web width, } b_w = 450.00$$

$$\text{flange thickness, } t = 450.00$$

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 7.1312074E-006$$

$$\text{with } f_y = 601.9953$$

$$d = 707.00$$

$$y = 0.40299134$$

$$A = 0.02249371$$

$$B = 0.01716068$$

$$\text{with } p_t = 0.00229194$$

$$p_c = 0.00368581$$

$$p_v = 0.00398517$$

$$N = 5.0666E+006$$

$$b = 950.00$$

$$" = 0.06082037$$

$$y_{\text{comp}} = 4.9385210E-006$$

$$\text{with } f_c = 18.00$$

$$E_c = 19940.411$$

$$y = 0.46536593$$

$$A = -0.01325006$$

$$B = 0.00462988$$

$$\text{with } E_s = 200000.00$$

CONFIRMATION: $y = 0.46536593 < t/d$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of p -

From table 10-8: $p = 0.01166081$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/d \geq 1$

$$\text{shear control ratio } V_y E / V_{CoI} E = 1.92314$$

$$d = d_{\text{external}} = 707.00$$

$$s = s_{\text{external}} = 100.00$$

$$- t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.0035764$$

$$\text{jacket: } s_1 = A_{v1} * L_{\text{stir1}} / (s_1 * A_g) = 0.00301593$$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir1}} = 2160.00$, is the total length of all stirrups parallel to loading (shear) direction

$$s_1 = 100.00$$

core: $s_2 = A_{v2} \cdot L_{stir2} / (s_2 \cdot A_g) = 0.00056047$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1568.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5.0666E+006$

$A_g = 562500.00$

$f_{cE} = (f_{c,jacket} \cdot Area_{jacket} + f_{c,core} \cdot Area_{core}) / section_area = 15.20$

$f_{yIE} = (f_{y,ext_Long_Reinf} \cdot Area_{ext_Long_Reinf} + f_{y,int_Long_Reinf} \cdot Area_{int_Long_Reinf}) / Area_{Tot_Long_Rein} = 601.9953$

$f_{yIE} = (f_{y,ext_Trans_Reinf} \cdot s_1 + f_{y,int_Trans_Reinf} \cdot s_2) / (s_1 + s_2) = 609.3286$

$\rho_l = Area_{Tot_Long_Rein} / (b \cdot d) = 0.00996292$

$b = 950.00$

$d = 707.00$

$f_{cE} = 15.20$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 15

column C1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 12.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 8.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 18.00$

New material: Steel Strength, $f_s = f_{sm} = 625.00$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material: Steel Strength, $f_s = f_{sm} = 525.00$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -6.3339E+008$

Shear Force, $V_a = 2.2058$

EDGE -B-

Bending Moment, $M_b = 4.5511E+008$

Shear Force, $V_b = -2.2058$

BOTH EDGES

Axial Force, $F = -5.0666E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 314.1593$

-Compression: $A_{sl,c} = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 2475.575$

-Middle: $A_{sl,mid} = 2676.637$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 734369.173$
 V_n ((10.3), ASCE 41-17) = $k_n V_{Col} = 917961.466$
 $V_{Col} = 917961.466$
 $k_n = 1.00$
 $displacement_ductility_demand = 0.15701928$

NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + \phi V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{jacket} Area_{jacket} + f_c'_{core} Area_{core}) / Area_{section} = 10.13333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 4.5511E+008$
 $V_u = 2.2058$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 5.0666E+006$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 828294.726$
where:
 $V_{sjacket} = V_{sj1} + V_{sj2} = 753982.237$
 $V_{sj1} = 471238.898$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{sj1} is multiplied by $Col_{j1} = 1.00$
 $s/d = 0.16666667$
 $V_{sj2} = 282743.339$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{sj2} is multiplied by $Col_{j2} = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 74312.489$
 $V_{s,c1} = 74312.489$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col_{c1} = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col_{c2} = 0.00$
 $s/d = 1.25$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 570961.316$
 $bw = 450.00$

$displacement_ductility_demand$ is calculated as ϕ / y

- Calculation of ϕ / y for END B -
for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 0.0019391$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.01234946$ ((4.29), Biskinis Phd))
 $M_y = 1.8636E+009$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 6000.00

From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} * E_c * I_g = 3.0181E+014$

factor = 0.70

$A_g = 562500.00$

Mean concrete strength: $f_c' = (f_c'_{jacket} * \text{Area}_{jacket} + f_c'_{core} * \text{Area}_{core}) / \text{Area}_{section} = 15.20$

$N = 5.0666E+006$

$E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 4.3116E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, $b = 950.00$

web width, $b_w = 450.00$

flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 7.1312074E-006$

with $f_y = 601.9953$

$d = 707.00$

$y = 0.40299134$

$A = 0.02249371$

$B = 0.01716068$

with $p_t = 0.00229194$

$p_c = 0.00368581$

$p_v = 0.00398517$

$N = 5.0666E+006$

$b = 950.00$

" = 0.06082037

$y_{comp} = 4.9385210E-006$

with $f_c = 18.00$

$E_c = 19940.411$

$y = 0.46536593$

$A = -0.01325006$

$B = 0.00462988$

with $E_s = 200000.00$

CONFIRMATION: $y = 0.46536593 < t/d$

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 16

column C1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.42131

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, \min} >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = -1.7986448E-005$
EDGE -B-
Shear Force, $V_b = 1.7986448E-005$
BOTH EDGES
Axial Force, $F = -5.0813E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 314.1593$
-Compression: $A_{sc} = 6377.433$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st, \text{ten}} = 1539.38$
-Compression: $A_{sc, \text{com}} = 2475.575$
-Middle: $A_{sc, \text{mid}} = 2676.637$

Calculation of Shear Capacity ratio , $V_e/V_r = 1.92314$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 2.0922E+006$
with
 $M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 3.1383E+009$
 $M_{u1+} = 3.1383E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u1-} = 1.6290E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 3.1383E+009$
 $M_{u2+} = 3.1383E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $M_{u2-} = 1.6290E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.9524665E-005$
 $M_u = 3.1383E+009$

with full section properties:

$b = 950.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.420296$
 $N = 5.0813E+006$
 $f_c = 18.00$
 $\alpha_1 (5A.5, \text{TBDY}) = 0.002$
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.01486841$
 $\omega_e (5.4c) = 0.08077545$
 $\alpha_{se} ((5.4d), \text{TBDY}) = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.53375773$
 $\alpha_{se1} = \text{Max}(((A_{conf, \text{max}1} - A_{noConf1}) / A_{conf, \text{max}1}) * (A_{conf, \text{min}1} / A_{conf, \text{max}1}), 0) = 0.53375773$
The definitions of A_{noConf} , $A_{conf, \text{min}}$ and $A_{conf, \text{max}}$ are derived from generalization
of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)
"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and
is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and
is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length
equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization
of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)
"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and
is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and
is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length
equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$
and also multiplied by the $shear_factor$ according to 15.7.1.4, with
 $Shear_factor = 1.00$

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 756.25$

with $Es1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 900.1904$

$fy2 = 750.1586$

```

su2 = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/lb,min = 1.00
su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esu2_nominal = 0.08,
For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^ 2/3), from 10.3.5, ASCE 41-17.
with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 750.1586
with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00
yv = 0.0025
shv = 0.008
ftv = 902.993
fyv = 752.4941
suv = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/ld = 1.00
suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esuv_nominal = 0.08,
considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^ 2/3), from 10.3.5, ASCE 41-17.
with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941
with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.09629324
2 = Asl,com/(b*d)*(fs2/fc) = 0.15360794
v = Asl,mid/(b*d)*(fsv/fc) = 0.16660079
and confined core properties:
b = 890.00
d = 677.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.10733965
2 = Asl,com/(b*d)*(fs2/fc) = 0.17122928
v = Asl,mid/(b*d)*(fsv/fc) = 0.18571261
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.42075151
MRc (4.17) = 2.3432E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->

```

Subcase: Rupture of tension steel

--->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

--->

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

--->

*cu (4.11) = 0.47003883

M_{Ro} (4.18) = 3.1383E+009

--->

u = cu (4.2) = 1.9524665E-005

Mu = M_{Ro}

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0952761E-005

Mu = 1.6290E+009

with full section properties:

b = 450.00

d = 707.00

d' = 43.00

v = 0.88729156

N = 5.0813E+006

f_c = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length

equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to bi²/6 as defined at (A.2).

ase2 (>=ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{,min} * F_{ywe} = \text{Min}(psh_{,x} * F_{ywe}, psh_{,y} * F_{ywe}) = 2.724$

 $psh_{,x} * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$
 $psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 $psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $psh_{,y} * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$
 $psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 $psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A.5), TBDY), TBDY: $cc = 0.00621307$

$c = \text{confinement factor} = 1.42131$

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 900.1904$

$fy1 = 750.1586$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{,min} = lb/ld = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 750.1586$

with $Es1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 907.50$

$fy2 = 756.25$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou_{,min} = lb/lb_{,min} = 1.00$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 756.25$

with $Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 902.993$

$fyv = 752.4941$

$suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 1.00$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941$
 with $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.32428344$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.20328574$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.35171278$
 and confined core properties:
 $b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.39075399$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.24495458$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.42380571$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is not satisfied
 --->
 $v < vs,c$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s,y1$ - LHS eq.(4.7) is not satisfied
 --->
 $v < vc,y1$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.82478813$
 $MRC (4.17) = 1.5333E+009$
 --->
 New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
 In expressions below, the following modifications have been made
 - b, d, d' replaced by geometric parameters of the core: $bo, do, d'o$
 - $N, 1, 2, v$ normalised to $bo*do$, instead of $b*d$
 - - parameters of confined concrete, fcc, cc , used in lieu of fc, ecu
 --->
 Subcase: Rupture of tension steel
 --->
 $v^* < v^*,y2$ - LHS eq.(4.5) is not satisfied
 --->
 $v^* < v^*,c$ - LHS eq.(4.5) is not satisfied
 --->
 Subcase rejected
 --->
 New Subcase: Failure of compression zone
 --->
 $v^* < v^*,y2$ - LHS eq.(4.6) is not satisfied
 --->
 $v^* < v^*,y1$ - RHS eq.(4.6) is not satisfied
 --->
 $*cu (4.11) = 0.83790293$
 $MRO (4.18) = 1.6290E+009$

--->

$$u = cu(4.2) = 1.0952761E-005$$

$$\mu = M_{Ro}$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 1.9524665E-005$$

$$\mu = 3.1383E+009$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.420296$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01486841$$

$$w_e(5.4c) = 0.08077545$$

$$ase((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1}(\text{Length of stirrups along } Y) = 2160.00$$

$$A_{stir1}(\text{stirrups area}) = 78.53982$$

$$p_{sh2}(5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2}(\text{Length of stirrups along } Y) = 1568.00$$

$$A_{stir2}(\text{stirrups area}) = 50.26548$$

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.25416$

psh1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A.5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

sh1 = 0.008

ft1 = 907.50

fy1 = 756.25

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su1 = $0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_jacket * A_{sl,ten,jacket} + fs_core * A_{sl,ten,core}) / A_{sl,ten} = 756.25$

with Es1 = $(Es_jacket * A_{sl,ten,jacket} + Es_core * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.0025

sh2 = 0.008

ft2 = 900.1904

fy2 = 750.1586

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = $0.4 * esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = $(fs_jacket * A_{sl,com,jacket} + fs_core * A_{sl,com,core}) / A_{sl,com} = 750.1586$

with Es2 = $(Es_jacket * A_{sl,com,jacket} + Es_core * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.0025

shv = 0.008

ftv = 902.993

fyv = 752.4941

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

suv = $0.4 * esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = $(fs_jacket * A_{sl,mid,jacket} + fs_mid * A_{sl,mid,core}) / A_{sl,mid} = 752.4941$

with Esv = $(Es_jacket * A_{sl,mid,jacket} + Es_mid * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

1 = $A_{sl,ten} / (b * d) * (fs1 / fc) = 0.09629324$

2 = $A_{sl,com} / (b * d) * (fs2 / fc) = 0.15360794$

v = $A_{sl,mid} / (b * d) * (fsv / fc) = 0.16660079$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 25.58352$$

$$cc (5A.5, TBDY) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = A_{sl,ten}/(b*d)^*(f_{s1}/f_c) = 0.10733965$$

$$2 = A_{sl,com}/(b*d)^*(f_{s2}/f_c) = 0.17122928$$

$$v = A_{sl,mid}/(b*d)^*(f_{sv}/f_c) = 0.18571261$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

---->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

---->

$$c_u (4.10) = 0.42075151$$

$$MR_c (4.17) = 2.3432E+009$$

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o , d_o , d'_o

- N , 1 , 2 , v normalised to b_o*d_o , instead of $b*d$

- f_{cc} , c_c parameters of confined concrete, f_{cc} , c_c , used in lieu of f_c , c_u

---->

Subcase: Rupture of tension steel

---->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

---->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

---->

$$*c_u (4.11) = 0.47003883$$

$$MR_o (4.18) = 3.1383E+009$$

---->

$$u = c_u (4.2) = 1.9524665E-005$$

$$\mu_u = MR_o$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_{u2}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

u = 1.0952761E-005
Mu = 1.6290E+009

with full section properties:

b = 450.00
d = 707.00
d' = 43.00
v = 0.88729156
N = 5.0813E+006
fc = 18.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01486841

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01486841

we (5.4c) = 0.08077545

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to bi2/6 as defined at (A.2).

ase2 (>=ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.53375773

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to bi2/6 as defined at (A.2).

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 2.724

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.724

psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00301593

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.25416

psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00357443

Lstir1 (Length of stirrups along X) = 2560.00

Astir1 (stirrups area) = 78.53982

psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00070345

Lstir2 (Length of stirrups along X) = 1968.00

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 656.25

fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y1 = 0.0025

$$sh1 = 0.008$$

$$ft1 = 900.1904$$

$$fy1 = 750.1586$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 750.1586$$

$$\text{with } Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 907.50$$

$$fy2 = 756.25$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 902.993$$

$$fyv = 752.4941$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 752.4941$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.32428344$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.20328574$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.35171278$$

and confined core properties:

$$b = 390.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 25.58352$$

$$cc (5A.5, TBDY) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.39075399$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.24495458$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.42380571$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is not satisfied

---->

v < vs,c - RHS eq.(4.5) is not satisfied

```

--->
Case/Assumption Rejected.
--->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
'satisfies Eq. (4.4)
--->
 $v < s_y1$  - LHS eq.(4.7) is not satisfied
--->
 $v < v_c y1$  - RHS eq.(4.6) is satisfied
--->
 $c_u$  (4.10) = 0.82478813
 $M_{Rc}$  (4.17) = 1.5333E+009
--->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core:  $b_o$ ,  $d_o$ ,  $d'_o$ 
-  $N_1$ ,  $N_2$ ,  $v$  normalised to  $b_o d_o$ , instead of  $b d$ 
-  $f_{cc}$ ,  $f_{cc}$  parameters of confined concrete,  $f_{cc}$ ,  $f_{cc}$  used in lieu of  $f_c$ ,  $e_{cu}$ 
--->
Subcase: Rupture of tension steel
--->
 $v^* < v^* s_y2$  - LHS eq.(4.5) is not satisfied
--->
 $v^* < v^* s_c$  - LHS eq.(4.5) is not satisfied
--->
Subcase rejected
--->
New Subcase: Failure of compression zone
--->
 $v^* < v^* c_y2$  - LHS eq.(4.6) is not satisfied
--->
 $v^* < v^* c_y1$  - RHS eq.(4.6) is not satisfied
--->
 $c_u$  (4.11) = 0.83790293
 $M_{Ro}$  (4.18) = 1.6290E+009
--->
 $u = c_u$  (4.2) = 1.0952761E-005
 $\mu = M_{Ro}$ 
-----

Calculation of ratio  $l_b/d$ 
-----
Adequate Lap Length:  $l_b/d \geq 1$ 
-----
-----
-----
-----
Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0879E+006$ 
-----
Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0879E+006$ 
 $V_{r1} = V_{Co1}$  ((10.3), ASCE 41-17) =  $k_n l V_{Co10}$ 
 $V_{Co10} = 1.0879E+006$ 
 $k_n l = 1$  (zero step-static loading)
-----
NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + f^* V_f$ '
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).
-----
= 1 (normal-weight concrete)
Mean concrete strength:  $f'_c = (f'_{c\_jacket} \text{Area}_{jacket} + f'_{c\_core} \text{Area}_{core}) / \text{Area}_{section} = 15.20$ , but  $f_c^{0.5} \leq 8.3$ 
MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$ 
 $\mu = 4.8236E+008$ 
 $V_u = 1.7986448E-005$ 
 $d = 0.8 h = 600.00$ 
 $N_u = 5.0813E+006$ 
 $A_g = 337500.00$ 
From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0354E+006$ 

```

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 942477.796$$

$V_{s,j1} = 589048.623$ is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.27777778$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$$

$V_{s,c1} = 92890.612$ is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 0.00$

$$s/d = 1.25$$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 699281.943$

$$bw = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0879E+006$

$V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$

$$V_{Col0} = 1.0879E+006$$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 15.20$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$M_u = 4.5550E+008$$

$$V_u = 1.7986448E-005$$

$$d = 0.8 * h = 600.00$$

$$N_u = 5.0813E+006$$

$$A_g = 337500.00$$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0354E+006$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 942477.796$$

$V_{s,j1} = 589048.623$ is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 353429.174$ is calculated for section flange jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 92890.612$
 $V_{s,c1} = 92890.612$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 699281.943$
 $bw = 450.00$

 End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rcjtcs

Constant Properties

 Knowledge Factor, $\phi = 0.80$
 Mean strength values are used for both shear and moment calculations.
 Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
 Concrete Elasticity, $E_c = 19940.411$
 Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
 Concrete Elasticity, $E_c = 16281.278$
 Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.42131

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou}, \min >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -5.5168185E-006$
EDGE -B-
Shear Force, $V_b = 5.5168185E-006$
BOTH EDGES
Axial Force, $F = -5.0813E+006$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 314.1593$
-Compression: $A_{sc} = 6377.433$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 1539.38$
-Compression: $A_{sl,com} = 1539.38$
-Middle: $A_{sl,mid} = 3612.832$

Calculation of Shear Capacity ratio , $V_e/V_r = 1.44711$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 1.9243E+006$
with
 $M_{pr1} = \text{Max}(Mu_{1+} , Mu_{1-}) = 2.8865E+009$
 $Mu_{1+} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 2.8865E+009$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+} , Mu_{2-}) = 2.8865E+009$
 $Mu_{2+} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 2.8865E+009$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 9.9083764E-006$
 $M_u = 2.8865E+009$

with full section properties:

$b = 450.00$
 $d = 907.00$
 $d' = 43.00$
 $v = 0.69163741$
 $N = 5.0813E+006$
 $f_c = 18.00$
 $c_o (5A.5, TBDY) = 0.002$
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.01486841$
 $\phi_{we} (5.4c) = 0.08077545$
 $\phi_{ase} ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$
 $ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.724$

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.724$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.25416$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 18.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00621307$

$c =$ confinement factor = 1.42131

$y1 = 0.0025$

$sh1 = 0.008$

$ft1 = 907.50$

$fy1 = 756.25$

$su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered

characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 756.25$

with $Es1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 907.50$

$fy_2 = 756.25$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/lb,min = 1.00$
 $su_2 = 0.4*esu_2,nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_2,nominal = 0.08$,
 For calculation of $esu_2,nominal$ and y_2, sh_2,ft_2,fy_2 , it is considered
 characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1,ft_1,fy_1 , are also multiplied by $Min(1,1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25$
 with $Es_2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.0025$
 $shv = 0.008$
 $ftv = 899.1522$
 $fyv = 749.2935$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/d = 1.00$
 $suv = 0.4*esuv,nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv,nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv,nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1,ft_1,fy_1 , are also multiplied by $Min(1,1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs_1/fc) = 0.15845977$
 $2 = Asl,com/(b*d)*(fs_2/fc) = 0.15845977$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 25.58352$
 $cc (5A.5, TBDY) = 0.00621307$
 $c = \text{confinement factor} = 1.42131$
 $1 = Asl,ten/(b*d)*(fs_1/fc) = 0.18909264$
 $2 = Asl,com/(b*d)*(fs_2/fc) = 0.18909264$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y_2$ - LHS eq.(4.5) is not satisfied
 --->
 $v < vs,c$ - RHS eq.(4.5) is not satisfied
 --->
 Case/Assumption Rejected.
 --->
 New Case/Assumption: Unconfined full section - Spalling of concrete cover
 ' satisfies Eq. (4.4)
 --->
 $v < s,y_1$ - LHS eq.(4.7) is not satisfied
 --->
 $v < vc,y_1$ - RHS eq.(4.6) is satisfied
 --->
 $cu (4.10) = 0.6344264$
 $MRc (4.17) = 2.3433E+009$
 --->
 New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
 In expressions below, the following modifications have been made
 - b, d, d' replaced by geometric parameters of the core: $bo, do, d'o$
 - $N, 1, 2, v$ normalised to $bo*do$, instead of $b*d$
 - fcc, cc used in lieu of fc, ecu

--->
Subcase: Rupture of tension steel
--->
 $v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied
--->
 $v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied
--->
Subcase rejected

--->
New Subcase: Failure of compression zone
--->
 $v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied
--->
 $v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied
--->
 $*c_u$ (4.11) = 0.71499649
MRo (4.18) = 2.8865E+009

--->
 $u = c_u$ (4.2) = 9.9083764E-006
Mu = MRo

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$u = 9.9083764E-006$
Mu = 2.8865E+009

with full section properties:

b = 450.00
d = 907.00
d' = 43.00
v = 0.69163741
N = 5.0813E+006
fc = 18.00
co (5A.5, TBDY) = 0.002

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $c_u = 0.01486841$

w_e (5.4c) = 0.08077545

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 2.724$

$psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.724$
 $psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00301593$
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
 $psh2 (5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047$
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

$psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 3.25416$
 $psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
 $psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00
s1 = 100.00
s2 = 250.00
fywe1 = 781.25
fywe2 = 656.25
fce = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307
c = confinement factor = 1.42131

y1 = 0.0025
sh1 = 0.008
ft1 = 907.50
fy1 = 756.25
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 907.50
fy2 = 756.25
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 899.1522

```

fyv = 749.2935
suv = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/ld = 1.00
suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esuv_nominal = 0.08,
considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^ 2/3), from 10.3.5, ASCE 41-17.
with fsv = (fsjacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935
with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977
2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977
v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443
and confined core properties:
b = 390.00
d = 877.00
d' = 13.00
fcc (5A.2, TBDY) = 25.58352
cc (5A.5, TBDY) = 0.00621307
c = confinement factor = 1.42131
1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264
2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264
v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658
Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)
---->
v < vs,y2 - LHS eq.(4.5) is not satisfied
---->
v < vs,c - RHS eq.(4.5) is not satisfied
---->
Case/Assumption Rejected.
---->
New Case/Assumption: Unconfined full section - Spalling of concrete cover
' satisfies Eq. (4.4)
---->
v < s,y1 - LHS eq.(4.7) is not satisfied
---->
v < vc,y1 - RHS eq.(4.6) is satisfied
---->
cu (4.10) = 0.6344264
MRc (4.17) = 2.3433E+009
---->
New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover
In expressions below, the following modifications have been made
- b, d, d' replaced by geometric parameters of the core: bo, do, d'o
- N, 1, 2, v normalised to bo*do, instead of b*d
- - parameters of confined concrete, fcc, cc, used in lieu of fc, ecu
---->
Subcase: Rupture of tension steel
---->
v* < v*s,y2 - LHS eq.(4.5) is not satisfied
---->
v* < v*s,c - LHS eq.(4.5) is not satisfied
---->
Subcase rejected
---->
New Subcase: Failure of compression zone
---->
v* < v*c,y2 - LHS eq.(4.6) is not satisfied
---->
v* < v*c,y1 - RHS eq.(4.6) is not satisfied
---->
*cu (4.11) = 0.71499649

```

$$M_{Ro} (4.18) = 2.8865E+009$$

--->

$$u = c_u (4.2) = 9.9083764E-006$$

$$\mu = M_{Ro}$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 9.9083764E-006$$

$$\mu = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01486841$$

$$w_e (5.4c) = 0.08077545$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (\geq a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.724$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.724$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along } Y) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along } Y) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

psh_y*F_{ywe} = psh₁*F_{ywe1}+ps₂*F_{ywe2} = 3.25416
psh₁ ((5.4d), TBDY) = L_{stir1}*A_{stir1}/(A_{sec}*s₁) = 0.00357443
L_{stir1} (Length of stirrups along X) = 2560.00
A_{stir1} (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = L_{stir2}*A_{stir2}/(A_{sec}*s₂) = 0.00070345
L_{stir2} (Length of stirrups along X) = 1968.00
A_{stir2} (stirrups area) = 50.26548

A_{sec} = 562500.00

s₁ = 100.00

s₂ = 250.00

f_{ywe1} = 781.25

f_{ywe2} = 656.25

f_{ce} = 18.00

From ((5.A5), TBDY), TBDY: cc = 0.00621307

c = confinement factor = 1.42131

y₁ = 0.0025

sh₁ = 0.008

ft₁ = 907.50

fy₁ = 756.25

su₁ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fs_{y1} = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*A_{sl,ten,jacket} + fs_{core}*A_{sl,ten,core})/A_{sl,ten} = 756.25

with Es₁ = (Es_{jacket}*A_{sl,ten,jacket} + Es_{core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00

y₂ = 0.0025

sh₂ = 0.008

ft₂ = 907.50

fy₂ = 756.25

su₂ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fs_{y2} = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*A_{sl,com,jacket} + fs_{core}*A_{sl,com,core})/A_{sl,com} = 756.25

with Es₂ = (Es_{jacket}*A_{sl,com,jacket} + Es_{core}*A_{sl,com,core})/A_{sl,com} = 200000.00

y_v = 0.0025

sh_v = 0.008

ft_v = 899.1522

fy_v = 749.2935

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_{nominal} = 0.08,

considering characteristic value fs_{yv} = fs_v/1.2, from table 5.1, TBDY

For calculation of esuv_{nominal} and y_v, sh_v,ft_v,fy_v, it is considered
characteristic value fs_{yv} = fs_v/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs_v = (fs_{jacket}*A_{sl,mid,jacket} + fs_{mid}*A_{sl,mid,core})/A_{sl,mid} = 749.2935

with Es_v = (Es_{jacket}*A_{sl,mid,jacket} + Es_{mid}*A_{sl,mid,core})/A_{sl,mid} = 200000.00

1 = A_{sl,ten}/(b*d)*(fs₁/f_c) = 0.15845977

2 = A_{sl,com}/(b*d)*(fs₂/f_c) = 0.15845977

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.36847443$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 25.58352$$

$$c_c (5A.5, TBDY) = 0.00621307$$

$$c = \text{confinement factor} = 1.42131$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.18909264$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.18909264$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.43970658$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is not satisfied

--->

Case/Assumption Rejected.

--->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

--->

$v < s_{y1}$ - LHS eq.(4.7) is not satisfied

--->

$v < v_{c,y1}$ - RHS eq.(4.6) is satisfied

--->

$$c_u (4.10) = 0.6344264$$

$$M_{Rc} (4.17) = 2.3433E+009$$

--->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- $N, 1, 2, v$ normalised to b_o*d_o , instead of $b*d$
- - parameters of confined concrete, f_{cc}, c_c , used in lieu of f_c, c_u

--->

Subcase: Rupture of tension steel

--->

$v^* < v^*_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v^* < v^*_{s,c}$ - LHS eq.(4.5) is not satisfied

--->

Subcase rejected

--->

New Subcase: Failure of compression zone

--->

$v^* < v^*_{c,y2}$ - LHS eq.(4.6) is not satisfied

--->

$v^* < v^*_{c,y1}$ - RHS eq.(4.6) is not satisfied

--->

$$*c_u (4.11) = 0.71499649$$

$$M_{Ro} (4.18) = 2.8865E+009$$

--->

$$u = c_u (4.2) = 9.9083764E-006$$

$$M_u = M_{Ro}$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u2} -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.9083764E-006$$

$$\mu = 2.8865E+009$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.69163741$$

$$N = 5.0813E+006$$

$$f_c = 18.00$$

$$\omega (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01486841$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.01486841$$

$$\phi_{we} (5.4c) = 0.08077545$$

$$\phi_{ase} ((5.4d), TBDY) = (\phi_{ase1} * A_{ext} + \phi_{ase2} * A_{int}) / A_{sec} = 0.53375773$$

$$\phi_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\phi_{ase2} (> \phi_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\phi_{psh,min} * \phi_{fywe} = \text{Min}(\phi_{psh,x} * \phi_{fywe}, \phi_{psh,y} * \phi_{fywe}) = 2.724$$

$$\phi_{psh,x} * \phi_{fywe} = \phi_{psh1} * \phi_{fywe1} + \phi_{ps2} * \phi_{fywe2} = 2.724$$

$$\phi_{psh1} ((5.4d), TBDY) = \phi_{Lstir1} * \phi_{Astir1} / (A_{sec} * s1) = 0.00301593$$

$$\phi_{Lstir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$\phi_{Astir1} (\text{stirrups area}) = 78.53982$$

$$\phi_{ps2} (5.4d) = \phi_{Lstir2} * \phi_{Astir2} / (A_{sec} * s2) = 0.00056047$$

$$\phi_{Lstir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$\phi_{Astir2} (\text{stirrups area}) = 50.26548$$

$$\phi_{psh,y} * \phi_{fywe} = \phi_{psh1} * \phi_{fywe1} + \phi_{ps2} * \phi_{fywe2} = 3.25416$$

$$\phi_{psh1} ((5.4d), TBDY) = \phi_{Lstir1} * \phi_{Astir1} / (A_{sec} * s1) = 0.00357443$$

$$\phi_{Lstir1} (\text{Length of stirrups along X}) = 2560.00$$

$$\phi_{Astir1} (\text{stirrups area}) = 78.53982$$

$$\phi_{ps2} ((5.4d), TBDY) = \phi_{Lstir2} * \phi_{Astir2} / (A_{sec} * s2) = 0.00070345$$

$$\phi_{Lstir2} (\text{Length of stirrups along X}) = 1968.00$$

$$\phi_{Astir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$\phi_{fywe1} = 781.25$$

$$\phi_{fywe2} = 656.25$$

$$\phi_{fce} = 18.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.00621307$$

$$\phi_c = \text{confinement factor} = 1.42131$$

y1 = 0.0025
sh1 = 0.008
ft1 = 907.50
fy1 = 756.25
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 756.25

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 907.50
fy2 = 756.25
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 756.25

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 899.1522
fyv = 749.2935
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 749.2935

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15845977

2 = Asl,com/(b*d)*(fs2/fc) = 0.15845977

v = Asl,mid/(b*d)*(fsv/fc) = 0.36847443

and confined core properties:

b = 390.00

d = 877.00

d' = 13.00

fcc (5A.2, TBDY) = 25.58352

cc (5A.5, TBDY) = 0.00621307

c = confinement factor = 1.42131

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18909264

2 = Asl,com/(b*d)*(fs2/fc) = 0.18909264

v = Asl,mid/(b*d)*(fsv/fc) = 0.43970658

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is not satisfied

---->

v < v_{s,c} - RHS eq.(4.5) is not satisfied

---->

Case/Assumption Rejected.

---->

New Case/Assumption: Unconfined full section - Spalling of concrete cover

' satisfies Eq. (4.4)

---->

v < s_{y1} - LHS eq.(4.7) is not satisfied

---->

v < v_{c,y1} - RHS eq.(4.6) is satisfied

---->

cu (4.10) = 0.6344264

M_{Rc} (4.17) = 2.3433E+009

---->

New Case/Assumption: Ultimate curvature of confined core after spalling of concrete cover

In expressions below, the following modifications have been made

- b, d, d' replaced by geometric parameters of the core: b_o, d_o, d'_o
- N₁, N₂, v normalised to b_o*d_o, instead of b*d
- parameters of confined concrete, f_{cc}, c_c, used in lieu of f_c, e_{cu}

---->

Subcase: Rupture of tension steel

---->

v* < v*s_{y2} - LHS eq.(4.5) is not satisfied

---->

v* < v*s_c - LHS eq.(4.5) is not satisfied

---->

Subcase rejected

---->

New Subcase: Failure of compression zone

---->

v* < v*c_{y2} - LHS eq.(4.6) is not satisfied

---->

v* < v*c_{y1} - RHS eq.(4.6) is not satisfied

---->

*cu (4.11) = 0.71499649

M_{Ro} (4.18) = 2.8865E+009

---->

u = cu (4.2) = 9.9083764E-006

Mu = M_{Ro}

Calculation of ratio l_b/l_d

Adequate Lap Length: l_b/l_d >= 1

Calculation of Shear Strength V_r = Min(V_{r1},V_{r2}) = 1.3298E+006

Calculation of Shear Strength at edge 1, V_{r1} = 1.3298E+006

V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = knl*V_{Co1o}

V_{Co1o} = 1.3298E+006

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'V_s = A_v*f_y*d/s' is replaced by 'V_s+ f*V_f'
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: f_c' = (f_c'_{jacket}*Area_{jacket} + f_c'_{core}*Area_{core})/Area_{section} = 15.20, but f_c'^{0.5} <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/V_d = 4.00

Mu = 1.7267E+008

Vu = 5.5168185E-006

d = 0.8*h = 760.00

Nu = 5.0813E+006

Ag = 427500.00

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.2262E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 1.0996E+006$

$V_{s,j1} = 353429.174$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 126669.016$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$s/d = 1.25$

$V_{s,c2} = 126669.016$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$s/d = 0.41666667$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 885757.128$

$bw = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.3298E+006$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} * V_{Col0}$

$V_{Col0} = 1.3298E+006$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 15.20$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1.6609E+008$

$V_u = 5.5168185E-006$

$d = 0.8 * h = 760.00$

$N_u = 5.0813E+006$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.2262E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 1.0996E+006$

$V_{s,j1} = 353429.174$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 746128.255$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

fy = 625.00

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.13157895

Vs,core = Vs,c1 + Vs,c2 = 126669.016

Vs,c1 = 0.00 is calculated for section web core, with:

d = 200.00

Av = 100530.965

fy = 525.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 0.00

s/d = 1.25

Vs,c2 = 126669.016 is calculated for section flange core, with:

d = 600.00

Av = 100530.965

fy = 525.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 1.00

s/d = 0.41666667

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 885757.128

bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 0.80$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 18.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 19940.411$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 12.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 16281.278$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Ribbed Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -3.3682E+008$

Shear Force, $V2 = 638013.908$

Shear Force, $V3 = -2.2058$

Axial Force, $F = -5.0666E+006$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 314.1593$

-Compression: $As_c = 6377.433$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1539.38$

-Compression: $As_{l,com} = 1539.38$

-Middle: $As_{l,mid} = 3612.832$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{l,ten,jacket} = 1231.504$

-Compression: $As_{l,com,jacket} = 1231.504$

-Middle: $As_{l,mid,jacket} = 2689.203$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{l,ten,core} = 307.8761$

-Compression: $As_{l,com,core} = 307.8761$

-Middle: $As_{l,mid,core} = 923.6282$

Mean Diameter of Tension Reinforcement, $Db_L = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = u = 0.01077339$

$u = y + p = 0.01346674$

- Calculation of y -

$y = (My * Ls / 3) / E_{eff} = 0.0006279$ ((4.29), Biskinis Phd))

$My = 1.6309E+009$

$Ls = M / V$ (with $Ls > 0.1 * L$ and $Ls < 2 * L$) = 527.9175

From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 4.5707E+014$

factor = 0.70

$A_g = 562500.00$

Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 15.20$

$N = 5.0666E+006$

$E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 6.5295E+014$

Calculation of Yielding Moment My

Calculation of y and My according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 6.3752290E-006$

with $f_y = 601.9953$

$d = 907.00$

$y = 0.4794529$

$A = 0.03701556$

$B = 0.02920673$

with $pt = 0.0037716$

$pc = 0.0037716$

$pv = 0.00885172$

$N = 5.0666E+006$

$b = 450.00$

" = 0.04740904

$y_{comp} = 2.6045948E-006$

with $fc = 18.00$

$E_c = 19940.411$

$y = 0.687802$

$A = -0.02180425$

B = 0.0085861
with Es = 200000.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of p -

From table 10-8: p = 0.01283884

with:

- Columns not controlled by inadequate development or splicing along the clear height because lb/d >= 1

shear control ratio $V_y E / V_{CoI} O E = 1.44711$

d = d_external = 907.00

s = s_external = 100.00

- $t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00427788$

jacket: $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00357443$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2560.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00070345$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1968.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5.0666E+006$

$A_g = 562500.00$

$f_{cE} = (f_{c_jacket} * Area_jacket + f_{c_core} * Area_core) / section_area = 15.20$

$f_{yIE} = (f_{y_ext_Long_Reinf} * Area_ext_Long_Reinf + f_{y_int_Long_Reinf} * Area_int_Long_Reinf) / Area_Tot_Long_Rein = 601.9953$

$f_{ytE} = (f_{y_ext_Trans_Reinf} * s_1 + f_{y_int_Trans_Reinf} * s_2) / (s_1 + s_2) = 608.5561$

$p_l = Area_Tot_Long_Rein / (b * d) = 0.01639493$

b = 450.00

d = 907.00

$f_{cE} = 15.20$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)