

Detailed Member Calculations

Units: N&mm

Regulation: ASCE 41-17

Calculation No. 1

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity VR_d

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 10.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

New material: Concrete Strength, $f_c = f_{cm} = 15.00$

New material: Steel Strength, $f_s = f_{sm} = 420.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -1.0607E+008$

Shear Force, $V_a = 19652.798$

EDGE -B-

Bending Moment, $M_b = 3.8888E+006$

Shear Force, $V_b = -19652.798$

BOTH EDGES

Axial Force, $F = -745272.03$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 763.407$

-Compression: $A_{sl,c} = 1272.345$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 678.584$

-Compression: $A_{sl,com} = 678.584$

-Middle: $A_{sl,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 18.00$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 116441.787$

V_n ((10.3), ASCE 41-17) = $k_n l \cdot V_{CoIO} = 116441.787$

$V_{CoI} = 116441.787$

$k_n l = 1.00$

displacement_ductility_demand = 1.12653

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f' \cdot V_f$ ' where V_f is the contribution of FRPs ((11.3), ACI 440).

= 1 (normal-weight concrete)

$f'_c = 10.00$, but $f_c^{0.5} \leq 8.3$ MPa ((22.5.3.1), ACI 318-14)

$M / Vd = 4.00$

$M_u = 1.0607E+008$

$V_u = 19652.798$

$d = 0.8 \cdot D = 200.00$

$N_u = 745272.03$

$A_g = 49087.385$

From ((11.5.4.8), ACI 318-14: $V_s = 98696.044$

$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$

$f_y = 400.00$

$s = 100.00$

V_s is multiplied by $CoI = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From ((11-11), ACI 440: $V_s + V_f \leq 65995.85$

$$b_w*d = \frac{I_d}{4} = 31415.927$$

displacement_ductility_demand is calculated as $\frac{M}{y}$

- Calculation of $\frac{M}{y}$ for END A -
for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 0.07206292$
 $y = \frac{M_y * L_s / 3}{E_{eff}} = 0.06396885$ ((4.29), Biskinis Phd)
 $M_y = 8.6873E+007$
 $L_s = M/V$ (with $L_s > 0.1*L$ and $L_s < 2*L$) = 5397.284
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 2.4433E+012$
factor = 0.70
Ag = 49087.385
fc' = 15.00
N = 745272.03
 $E_c * I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of $\frac{M}{y}$ and M_y according to (7) - (8) in Biskinis and Fardis

$M_y = \text{Min}(M_{y_ten}, M_{y_com}) = 8.6873E+007$
 y ((10a) or (10b)) = $2.2945961E-005$
 M_{y_ten} (8a) = $9.3578E+007$
 $\frac{M}{y}$ (7a) = 89.00
error of function (7a) = -1.20629
 M_{y_com} (8b) = $8.6873E+007$
 $\frac{M}{y}$ (7b) = 92.63285
error of function (7b) = -0.01829496
with $e_y = 0.0021$
eco = 0.002
apl = 0.35 ((9a) in Biskinis and Fardis for no FRP Wrap)
d1 = 44.00
R = 125.00
v = 1.01217
N = 745272.03
Ac = 49087.385
= 1.16122
with fc = 15.00

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

End Of Calculation of Shear Capacity for element: column CC1 of floor 1
At local axis: 2
Integration Section: (a)

Calculation No. 2

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (ϕ)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 525.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.7465

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} \geq 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.5879607E-028$

EDGE -B-

Shear Force, $V_b = 1.5879607E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 678.584$

-Compression: $As_{c,com} = 678.584$

-Middle: $As_{mid} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 8.3720E+007$

$Mu_{1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 8.3720E+007$

$Mu_{2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

$Mu = 8.3720E+007$

$\lambda = 1.55334$

$\lambda' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of $f_y: f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \lambda \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu_{1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

$Mu = 8.3720E+007$

$\lambda = 1.55334$

$\lambda' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ

$\mu = 8.3720E+007$

$= 1.55334$

$' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ

$\mu = 8.3720E+007$

$= 1.55334$

$' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= *Min(1, 1.25*(l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l * V_{Col0}$

$V_{Col0} = 193699.191$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.5352144E-009$

$\nu_u = 1.5879607E-028$

$d = 0.8 * D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} * A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $\text{Col} = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$b_w * d = \sqrt{d} * d / 4 = 31415.927$

Calculation of Shear Strength at edge 2, $V_{r2} = 193699.191$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l * V_{Col0}$

$V_{Col0} = 193699.191$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.5352144E-009$

$\nu_u = 1.5879607E-028$

$d = 0.8 * D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} * A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $\text{Col} = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$b_w * d = \sqrt{d} * d / 4 = 31415.927$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$
Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$
Concrete Elasticity, $E_c = 18203.022$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25 * f_{sm} = 525.00$

Diameter, $D = 250.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.7465
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -6.8157582E-028$
EDGE -B-
Shear Force, $V_b = 6.8157582E-028$
BOTH EDGES
Axial Force, $F = -745904.162$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 2035.752$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st, ten} = 678.584$
-Compression: $A_{sl, com} = 678.584$
-Middle: $A_{sl, mid} = 678.584$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.28814544$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$
with
 $M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 8.3720E+007$
 $M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment

direction which is defined for the static loading combination

$$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u
 $M_u = 8.3720E+007$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$$f_c = 15.00$$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u
 $M_u = 8.3720E+007$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$$f_c = 15.00$$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u2+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$$f_c = 15.00$$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$$f_c = 15.00$$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Co1}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Co10}$

$$V_{Co10} = 193699.191$$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_{s+} = f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
fc' = 15.00, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
M/Vd = 2.00
Mu = 3.6227516E-010
Vu = 6.8157582E-028
d = 0.8*D = 200.00
Nu = 745904.162
Ag = 49087.385
From (11.5.4.8), ACI 318-14: Vs = 103630.846
Av = $\frac{1}{2} * A_{stirrup} = 123370.055$
fy = 420.00
s = 100.00
Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 80828.079
bw*d = $\frac{1}{4} * d^2 = 31415.927$

Calculation of Shear Strength at edge 2, Vr2 = 193699.191
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 193699.191
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*VF'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
fc' = 15.00, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
M/Vd = 2.00
Mu = 3.6227516E-010
Vu = 6.8157582E-028
d = 0.8*D = 200.00
Nu = 745904.162
Ag = 49087.385
From (11.5.4.8), ACI 318-14: Vs = 103630.846
Av = $\frac{1}{2} * A_{stirrup} = 123370.055$
fy = 420.00
s = 100.00
Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 80828.079
bw*d = $\frac{1}{4} * d^2 = 31415.927$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1
At local axis: 2
Integration Section: (a)
Section Type: rccs

Constant Properties

Knowledge Factor, = 1.00
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
New material of Primary Member: Concrete Strength, fc = fcm = 15.00
New material of Primary Member: Steel Strength, fs = fsm = 420.00
Concrete Elasticity, Ec = 18203.022

Steel Elasticity, $E_s = 200000.00$
Diameter, $D = 250.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/d >= 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 0.05842278$
Shear Force, $V_2 = 19652.798$
Shear Force, $V_3 = 3.7545092E-010$
Axial Force, $F = -745272.03$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 763.407$
-Compression: $A_{sc} = 1272.345$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 678.584$
-Compression: $A_{sc,com} = 678.584$
-Middle: $A_{st,mid} = 678.584$
Mean Diameter of Tension Reinforcement, $D_bL = 18.00$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^* u = 0.01777807$
 $u = y + p = 0.01777807$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.01777807$ ((4.29), Biskinis Phd)
 $M_y = 8.6873E+007$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1500.00
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 2.4433E+012$
factor = 0.70
Ag = 49087.385
fc' = 15.00
N = 745272.03
 $E_c * I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to (7) - (8) in Biskinis and Fardis

$M_y = \text{Min}(M_{y_ten}, M_{y_com}) = 8.6873E+007$
 y ((10a) or (10b)) = 2.2945961E-005
 M_{y_ten} (8a) = 9.3578E+007
 y_{ten} (7a) = 89.00
error of function (7a) = -1.20629
 M_{y_com} (8b) = 8.6873E+007
 y_{com} (7b) = 92.63285
error of function (7b) = -0.01829496
with $e_y = 0.0021$
eco = 0.002
apl = 0.35 ((9a) in Biskinis and Fardis for no FRP Wrap)
d1 = 44.00
R = 125.00
v = 1.01217

N = 745272.03
Ac = 49087.385
= 1.16122

with fc = 15.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of p -

From table 10-9: p = 0.00

with:

- Columns not controlled by inadequate development or splicing along the clear height because lb/d >= 1
shear control ratio $V_{yE}/V_{CoIE} = 0.28814544$

d = 209.00

s = 150.00

$t = 2 \cdot A_v / (d_c \cdot s) + 4 \cdot t_f / D \cdot (f_{fe} / f_s) = 0.00826735$

$A_v = 78.53982$, is the area of the circular stirrup

$d_c = D - 2 \cdot \text{cover} - \text{Hoop Diameter} = 190.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

NUD = 745272.03

Ag = 49087.385

f_{cE} = 15.00

f_{ytE} = f_{ylE} = 420.00

pl = Area_Tot_Long_Rein/(Ag) = 0.041472

f_{cE} = 15.00

End Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 3

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 10.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

New material: Concrete Strength, $f_c = f_{cm} = 15.00$

New material: Steel Strength, $f_s = f_{sm} = 420.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 0.05842278$

Shear Force, $V_a = 3.7545092E-010$

EDGE -B-

Bending Moment, $M_b = -0.00070098$

Shear Force, $V_b = -3.7545092E-010$

BOTH EDGES

Axial Force, $F = -745272.03$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 763.407$

-Compression: $A_{sl,c} = 1272.345$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 678.584$

-Compression: $A_{sl,com} = 678.584$

-Middle: $A_{sl,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.00$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 166887.723$
 V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{CoI} = 166887.723$
 $V_{CoI} = 166887.723$
 $k_n = 1.00$
 $displacement_ductility_demand = 1.4523071E-009$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 $f_c' = 10.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.00$
 $\mu_u = 0.05842278$
 $V_u = 3.7545092E-010$
 $d = 0.8 \cdot D = 200.00$
 $N_u = 745272.03$
 $A_g = 49087.385$
From (11.5.4.8), ACI 318-14: $V_s = 98696.044$
 $A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$
 $f_y = 400.00$
 $s = 100.00$
 V_s is multiplied by $CoI = 1.00$
 $s/d = 0.50$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 65995.85$
 $b_w \cdot d = \sqrt{N_u} \cdot d / 4 = 31415.927$

 $displacement_ductility_demand$ is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 2.5819210E-011$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.01777807$ ((4.29), Biskinis Phd))
 $M_y = 8.6873E+007$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00
From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.4433E+012$
 $factor = 0.70$
 $A_g = 49087.385$
 $f_c' = 15.00$
 $N = 745272.03$
 $E_c \cdot I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to (7) - (8) in Biskinis and Fardis

 $M_y = \min(M_{y_ten}, M_{y_com}) = 8.6873E+007$
 y ((10a) or (10b)) = $2.2945961E-005$
 M_{y_ten} (8a) = $9.3578E+007$
 y_{ten} (7a) = 89.00
error of function (7a) = -1.20629
 M_{y_com} (8b) = $8.6873E+007$
 y_{com} (7b) = 92.63285
error of function (7b) = -0.01829496
with $e_y = 0.0021$
 $e_{co} = 0.002$
 $a_{pl} = 0.35$ ((9a) in Biskinis and Fardis for no FRP Wrap)
 $d_1 = 44.00$

R = 125.00
v = 1.01217
N = 745272.03
Ac = 49087.385
= 1.16122

with $f_c = 15.00$

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

End Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 4

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 525.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.7465

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.5879607E-028$

EDGE -B-

Shear Force, $V_b = 1.5879607E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st, \text{ten}} = 678.584$

-Compression: $A_{sl, \text{com}} = 678.584$

-Middle: $A_{sl, \text{mid}} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

fc = 15.00

From 10.3.5, ASCE 41-17, Final value of fy: $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

lb/d = 1.00

d1 = 44.00

R = 125.00

v = 1.01248

N = 745904.162

Ac = 49087.385

= $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu1-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

Mu = $8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor c = 1.7465

fc = 15.00

From 10.3.5, ASCE 41-17, Final value of fy: $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

lb/d = 1.00

d1 = 44.00

R = 125.00

v = 1.01248

N = 745904.162

Ac = 49087.385

= $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

Mu = $8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor c = 1.7465

fc = 15.00

From 10.3.5, ASCE 41-17, Final value of fy: $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

lb/d = 1.00

d1 = 44.00

R = 125.00

v = 1.01248

N = 745904.162

Ac = 49087.385

= $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ
 $\mu = 8.3720E+007$

$$= 1.55334$$

$$\mu = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$V_{Col0} = 193699.191$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

$\mu = 1$ (normal-weight concrete)

$f_c' = 15.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/d = 2.00$

$$\mu = 1.5352144E-009$$

$$V_u = 1.5879607E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $\text{Col} = 1.00$

$$s/d = 0.50$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$$b_w \cdot d = \frac{N_u \cdot d}{4} = 31415.927$$

Calculation of Shear Strength at edge 2, $Vr2 = 193699.191$

$Vr2 = VCol$ ((10.3), ASCE 41-17) = $knl * VColO$

$VColO = 193699.191$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $Vs = Av * fy * d / s$ ' is replaced by ' $Vs + f * Vf$ ' where Vf is the contribution of FRPs (11.3), ACI 440).

$\lambda = 1$ (normal-weight concrete)

$fc' = 15.00$, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$Mu = 1.5352144E-009$

$Vu = 1.5879607E-028$

$d = 0.8 * D = 200.00$

$Nu = 745904.162$

$Ag = 49087.385$

From (11.5.4.8), ACI 318-14: $Vs = 103630.846$

$Av = \lambda / 2 * A_{stirrup} = 123370.055$

$fy = 420.00$

$s = 100.00$

Vs is multiplied by $Col = 1.00$

$s/d = 0.50$

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $Vs + Vf \leq 80828.079$

$bw * d = \lambda * d * d / 4 = 31415.927$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rccs

Constant Properties

Knowledge Factor, $\lambda = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, $fc = fcm = 15.00$

New material of Primary Member: Steel Strength, $fs = fsm = 420.00$

Concrete Elasticity, $Ec = 18203.022$

Steel Elasticity, $Es = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $fs = 1.25 * fsm = 525.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.7465

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($lo/lo_u, \min > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -6.8157582E-028$

EDGE -B-

Shear Force, $V_b = 6.8157582E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 678.584$

-Compression: $A_{sc,com} = 678.584$

-Middle: $A_{st,mid} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\phi = 1.55334$

$\phi' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3}) = 525.00$

$l_b/l_d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$\phi = \phi' \cdot \text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3}) = 1.16122$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$
conf. factor $c = 1.7465$
 $f_c = 15.00$
From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$
 $l_b/d = 1.00$
 $d_1 = 44.00$
 $R = 125.00$
 $v = 1.01248$
 $N = 745904.162$
 $Ac = 49087.385$
 $= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$
conf. factor $c = 1.7465$
 $f_c = 15.00$
From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$
 $l_b/d = 1.00$
 $d_1 = 44.00$
 $R = 125.00$
 $v = 1.01248$
 $N = 745904.162$
 $Ac = 49087.385$
 $= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$
conf. factor $c = 1.7465$
 $f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 193699.191$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 15.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 2.00$$

$$\mu_u = 3.6227516E-010$$

$$V_u = 6.8157582E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{\text{stirrup}} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $\text{Col} = 1.00$

$$s/d = 0.50$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$$b_w \cdot d = \text{Min}(V_s, V_f) \cdot d / 4 = 31415.927$$

Calculation of Shear Strength at edge 2, $V_{r2} = 193699.191$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 193699.191$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 15.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 2.00$$

$$\mu_u = 3.6227516E-010$$

$$V_u = 6.8157582E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{\text{stirrup}} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $\text{Col} = 1.00$

$$s/d = 0.50$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 80828.079$$

$$b_w * d = *d*d/4 = 31415.927$$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1
At local axis: 3
Integration Section: (a)
Section Type: rccs

Constant Properties

$$\text{Knowledge Factor, } = 1.00$$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

$$\text{New material of Primary Member: Concrete Strength, } f_c = f_{cm} = 15.00$$

$$\text{New material of Primary Member: Steel Strength, } f_s = f_{sm} = 420.00$$

$$\text{Concrete Elasticity, } E_c = 18203.022$$

$$\text{Steel Elasticity, } E_s = 200000.00$$

$$\text{Diameter, } D = 250.00$$

$$\text{Cover Thickness, } c = 25.00$$

$$\text{Element Length, } L = 3000.00$$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

$$\text{Bending Moment, } M = -1.0607E+008$$

$$\text{Shear Force, } V_2 = 19652.798$$

$$\text{Shear Force, } V_3 = 3.7545092E-010$$

$$\text{Axial Force, } F = -745272.03$$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

$$\text{-Tension: } A_{st} = 763.407$$

$$\text{-Compression: } A_{sc} = 1272.345$$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

$$\text{-Tension: } A_{st,ten} = 678.584$$

$$\text{-Compression: } A_{st,com} = 678.584$$

$$\text{-Middle: } A_{st,mid} = 678.584$$

$$\text{Mean Diameter of Tension Reinforcement, } D_bL = 18.00$$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_R = 1.0^*$ $u = 0.06396885$

$$u = y + p = 0.06396885$$

- Calculation of y -

$$y = (M_y * L_s / 3) / E_{eff} = 0.06396885 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 8.6873E+007$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 5397.284$$

$$\text{From table 10.5, ASCE 41_17: } E_{eff} = \text{factor} * E_c * I_g = 2.4433E+012$$

factor = 0.70
Ag = 49087.385
fc' = 15.00
N = 745272.03
Ec*Ig = 3.4904E+012

Calculation of Yielding Moment My

Calculation of ρ_y and My according to (7) - (8) in Biskinis and Fardis

My = Min(My_ten, My_com) = 8.6873E+007
 ρ_y ((10a) or (10b)) = 2.2945961E-005
My_ten (8a) = 9.3578E+007
 ρ_{y_ten} (7a) = 89.00
error of function (7a) = -1.20629
My_com (8b) = 8.6873E+007
 ρ_{y_com} (7b) = 92.63285
error of function (7b) = -0.01829496
with $e_y = 0.0021$
 $e_{co} = 0.002$
apl = 0.35 ((9a) in Biskinis and Fardis for no FRP Wrap)
d1 = 44.00
R = 125.00
v = 1.01217
N = 745272.03
Ac = 49087.385
= 1.16122
with fc = 15.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of ρ_p -

From table 10-9: $\rho_p = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because lb/d >= 1

shear control ratio $V_y E / C_o I_o E = 0.28814544$

d = 209.00

s = 150.00

$t = 2 * A_v / (d_c * s) + 4 * t_f / D * (f_{fe} / f_s) = 0.00826735$

$A_v = 78.53982$, is the area of the circular stirrup

$d_c = D - 2 * cover - Hoop Diameter = 190.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

NUD = 745272.03

Ag = 49087.385

f'cE = 15.00

fytE = fylE = 420.00

$\rho_l = Area_Tot_Long_Rein / (Ag) = 0.041472$

f'cE = 15.00

End Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 5

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 10.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

New material: Concrete Strength, $f_c = f_{cm} = 15.00$

New material: Steel Strength, $f_s = f_{sm} = 420.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -1.0607E+008$

Shear Force, $V_a = 19652.798$

EDGE -B-

Bending Moment, $M_b = 3.8888E+006$

Shear Force, $V_b = -19652.798$

BOTH EDGES

Axial Force, $F = -745272.03$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 678.584$

-Compression: $As_{c,com} = 678.584$

-Middle: $As_{c,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.00$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 135713.639$

V_n ((10.3), ASCE 41-17) = $kn_l \cdot V_{CoI} = 135713.639$

$V_{CoI} = 166887.723$

$kn_l = 0.81320325$

displacement_ductility_demand = 4.49062

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 10.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$M_u = 3.8888E+006$

$V_u = 19652.798$

$d = 0.8 \cdot D = 200.00$

$N_u = 745272.03$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 98696.044$

$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$

$f_y = 400.00$

$s = 100.00$

V_s is multiplied by $Col = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 65995.85$

$bw \cdot d = \sqrt{N_u} \cdot d / 4 = 31415.927$

displacement_ductility_demand is calculated as ϕ / y

- Calculation of ϕ / y for END B -

for rotation axis 3 and integ. section (b)

From analysis, chord rotation = 0.01596692

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.00355561$ ((4.29), Biskinis Phd)

$M_y = 8.6873E+007$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 300.00

From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.4433E+012$

factor = 0.70

$A_g = 49087.385$

$f_c' = 15.00$

$N = 745272.03$

$$E_c \cdot I_g = 3.4904E+012$$

Calculation of Yielding Moment M_y

Calculation of ρ_y and M_y according to (7) - (8) in Biskinis and Fardis

$$M_y = \min(M_{y_ten}, M_{y_com}) = 8.6873E+007$$

$$\rho_y \text{ ((10a) or (10b))} = 2.2945961E-005$$

$$M_{y_ten} \text{ (8a)} = 9.3578E+007$$

$$\rho_{y_ten} \text{ (7a)} = 89.00$$

$$\text{error of function (7a)} = -1.20629$$

$$M_{y_com} \text{ (8b)} = 8.6873E+007$$

$$\rho_{y_com} \text{ (7b)} = 92.63285$$

$$\text{error of function (7b)} = -0.01829496$$

$$\text{with } e_y = 0.0021$$

$$e_{co} = 0.002$$

$$a_{pl} = 0.35 \text{ ((9a) in Biskinis and Fardis for no FRP Wrap)}$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01217$$

$$N = 745272.03$$

$$A_c = 49087.385$$

$$= 1.16122$$

$$\text{with } f_c = 15.00$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

End Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 6

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rccs

Constant Properties

 Knowledge Factor, $\gamma = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$
 Concrete Elasticity, $E_c = 18203.022$
 Steel Elasticity, $E_s = 200000.00$

 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 525.00$

 Diameter, $D = 250.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.7465
 Element Length, $L = 3000.00$
 Primary Member
 Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_o/l_{ou,min} >= 1$)
 No FRP Wrapping

 Stepwise Properties

 At local axis: 3
 EDGE -A-
 Shear Force, $V_a = -1.5879607E-028$
 EDGE -B-
 Shear Force, $V_b = 1.5879607E-028$
 BOTH EDGES
 Axial Force, $F = -745904.162$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 0.00$
 -Compression: $A_{sc} = 2035.752$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 678.584$
 -Compression: $A_{sc,com} = 678.584$
 -Middle: $A_{sc,mid} = 678.584$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\phi = 1.55334$

$\lambda = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot \lambda = 26.19746$

conf. factor $\lambda = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \phi \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\phi = 1.55334$

$\lambda = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot \lambda = 26.19746$

conf. factor $\lambda = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \phi \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ
 $\mu = 8.3720E+007$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 525.00$

$lb/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of μ_{2-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ
 $\mu = 8.3720E+007$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 525.00$

$lb/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, Vr1 = 193699.191

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VColO

VColO = 193699.191

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

fc' = 15.00, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00

Mu = 1.5352144E-009

Vu = 1.5879607E-028

d = 0.8*D = 200.00

Nu = 745904.162

Ag = 49087.385

From (11.5.4.8), ACI 318-14: Vs = 103630.846

Av = /2*A_stirrup = 123370.055

fy = 420.00

s = 100.00

Vs is multiplied by Col = 1.00

s/d = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 80828.079

bw*d = *d*d/4 = 31415.927

Calculation of Shear Strength at edge 2, Vr2 = 193699.191

Vr2 = VCol ((10.3), ASCE 41-17) = knl*VColO

VColO = 193699.191

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

fc' = 15.00, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00

Mu = 1.5352144E-009

Vu = 1.5879607E-028

d = 0.8*D = 200.00

Nu = 745904.162

Ag = 49087.385

From (11.5.4.8), ACI 318-14: Vs = 103630.846

Av = /2*A_stirrup = 123370.055

fy = 420.00

s = 100.00

Vs is multiplied by Col = 1.00

s/d = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 80828.079

bw*d = *d*d/4 = 31415.927

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rccs

Constant Properties

Knowledge Factor, $\phi = 1.00$
Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$
Concrete Elasticity, $E_c = 18203.022$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 525.00$

Diameter, $D = 250.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.7465
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -6.8157582E-028$
EDGE -B-
Shear Force, $V_b = 6.8157582E-028$
BOTH EDGES
Axial Force, $F = -745904.162$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 2035.752$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st, ten} = 678.584$
-Compression: $A_{sc, com} = 678.584$
-Middle: $A_{sc, mid} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$
with
 $M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$
 $M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$
 $M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$$\text{Mu} = 8.3720\text{E}+007$$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu_1 -

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

$$\text{Mu} = 8.3720\text{E}+007$$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu_2 +

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

$$\text{Mu} = 8.3720\text{E}+007$$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

lb/d = 1.00
d1 = 44.00
R = 125.00
v = 1.01248
N = 745904.162
Ac = 49087.385
= *Min(1,1.25*(lb/d)^ 2/3) = 1.16122

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: fcc = fc* c = 26.19746
conf. factor c = 1.7465
fc = 15.00
From 10.3.5, ASCE 41-17, Final value of fy: fy*Min(1,1.25*(lb/d)^ 2/3) = 525.00
lb/d = 1.00
d1 = 44.00
R = 125.00
v = 1.01248
N = 745904.162
Ac = 49087.385
= *Min(1,1.25*(lb/d)^ 2/3) = 1.16122

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 193699.191

Calculation of Shear Strength at edge 1, Vr1 = 193699.191
Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 193699.191
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
fc' = 15.00, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)
M/Vd = 2.00
Mu = 3.6227516E-010
Vu = 6.8157582E-028
d = 0.8*D = 200.00
Nu = 745904.162
Ag = 49087.385
From (11.5.4.8), ACI 318-14: Vs = 103630.846
Av = /2*A_stirup = 123370.055
fy = 420.00
s = 100.00

Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 80828.079
bw*d = *d*d/4 = 31415.927

Calculation of Shear Strength at edge 2, Vr2 = 193699.191
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 193699.191
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
fc' = 15.00, but fc^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)
M/Vd = 2.00
Mu = 3.6227516E-010
Vu = 6.8157582E-028
d = 0.8*D = 200.00
Nu = 745904.162
Ag = 49087.385
From (11.5.4.8), ACI 318-14: Vs = 103630.846
Av = /2*A_stirrup = 123370.055
fy = 420.00
s = 100.00
Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 80828.079
bw*d = *d*d/4 = 31415.927

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1
At local axis: 2
Integration Section: (b)
Section Type: rccs

Constant Properties

Knowledge Factor, = 1.00
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
New material of Primary Member: Concrete Strength, fc = fcm = 15.00
New material of Primary Member: Steel Strength, fs = fsm = 420.00
Concrete Elasticity, Ec = 18203.022
Steel Elasticity, Es = 200000.00
Diameter, D = 250.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lb/d >= 1)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -0.00070098$
Shear Force, $V2 = -19652.798$
Shear Force, $V3 = -3.7545092E-010$
Axial Force, $F = -745272.03$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 2035.752$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{s,ten} = 678.584$
-Compression: $A_{s,com} = 678.584$
-Middle: $A_{s,mid} = 678.584$
Mean Diameter of Tension Reinforcement, $DbL = 18.00$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u,R = 1.0^*$ $u = 0.01777807$
 $u = y + p = 0.01777807$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.01777807$ ((4.29), Biskinis Phd))
 $M_y = 8.6873E+007$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1500.00
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 2.4433E+012$
factor = 0.70
 $A_g = 49087.385$
 $f_c' = 15.00$
 $N = 745272.03$
 $E_c * I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to (7) - (8) in Biskinis and Fardis

$M_y = \text{Min}(M_{y,ten}, M_{y,com}) = 8.6873E+007$
 y ((10a) or (10b)) = $2.2945961E-005$
 $M_{y,ten}$ (8a) = $9.3578E+007$
 y_{ten} (7a) = 89.00
error of function (7a) = -1.20629
 $M_{y,com}$ (8b) = $8.6873E+007$
 y_{com} (7b) = 92.63285
error of function (7b) = -0.01829496
with $e_y = 0.0021$
 $e_{co} = 0.002$
 $apl = 0.35$ ((9a) in Biskinis and Fardis for no FRP Wrap)
 $d1 = 44.00$
 $R = 125.00$
 $v = 1.01217$
 $N = 745272.03$
 $A_c = 49087.385$
= 1.16122
with $f_c = 15.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of p -

From table 10-9: $p = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$

shear control ratio $V_y E / V_{Co} I_{OE} = 0.28814544$

$d = 209.00$

$s = 150.00$

$t = 2 \cdot A_v / (d_c \cdot s) + 4 \cdot t_f / D \cdot (f_{fe} / f_s) = 0.00826735$

$A_v = 78.53982$, is the area of the circular stirrup

$d_c = D - 2 \cdot \text{cover} - \text{Hoop Diameter} = 190.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$NUD = 745272.03$

$Ag = 49087.385$

$f_{cE} = 15.00$

$f_{yE} = f_{yI} = 420.00$

$p_l = \text{Area_Tot_Long_Rein} / (Ag) = 0.041472$

$f_{cE} = 15.00$

End Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 7

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rccs

Constant Properties

Knowledge Factor, $\phi = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 10.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of μ_y for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

New material: Concrete Strength, $f_c = f_{cm} = 15.00$

New material: Steel Strength, $f_s = f_{sm} = 420.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 0.05842278$

Shear Force, $V_a = 3.7545092E-010$

EDGE -B-

Bending Moment, $M_b = -0.00070098$

Shear Force, $V_b = -3.7545092E-010$

BOTH EDGES

Axial Force, $F = -745272.03$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 0.00$

-Compression: $A_{sl,c} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 678.584$

-Compression: $A_{sl,com} = 678.584$

-Middle: $A_{sl,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 18.00$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 166887.723$

V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{CoI} = 166887.723$

$V_{CoI} = 166887.723$

$k_n = 1.00$

displacement_ductility_demand = $4.8322002E-010$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_{s+} + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$\phi = 1$ (normal-weight concrete)

$f_c' = 10.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.00070098$

$V_u = 3.7545092E-010$

$d = 0.8 \cdot D = 200.00$

$N_u = 745272.03$

$A_g = 49087.385$
From (11.5.4.8), ACI 318-14: $V_s = 98696.044$
 $A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$
 $f_y = 400.00$
 $s = 100.00$
 V_s is multiplied by $Col = 1.00$
 $s/d = 0.50$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 65995.85$
 $b_w \cdot d = \sqrt{d} \cdot d / 4 = 31415.927$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END B -
for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 8.5907194E-012$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.01777807$ ((4.29), Biskinis Phd)
 $M_y = 8.6873E+007$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00
From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.4433E+012$
 $factor = 0.70$
 $A_g = 49087.385$
 $f_c' = 15.00$
 $N = 745272.03$
 $E_c \cdot I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to (7) - (8) in Biskinis and Fardis

$M_y = \min(M_{y_ten}, M_{y_com}) = 8.6873E+007$
 $y ((10a) \text{ or } (10b)) = 2.2945961E-005$
 $M_{y_ten} (8a) = 9.3578E+007$
 $\delta_{ten} (7a) = 89.00$
error of function (7a) = -1.20629
 $M_{y_com} (8b) = 8.6873E+007$
 $\delta_{com} (7b) = 92.63285$
error of function (7b) = -0.01829496
with $e_y = 0.0021$
 $e_{co} = 0.002$
 $a_{pl} = 0.35$ ((9a) in Biskinis and Fardis for no FRP Wrap)
 $d_1 = 44.00$
 $R = 125.00$
 $v = 1.01217$
 $N = 745272.03$
 $A_c = 49087.385$
 $= 1.16122$
with $f_c = 15.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

End Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 8

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 525.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.7465

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} \geq 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.5879607E-028$

EDGE -B-

Shear Force, $V_b = 1.5879607E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 678.584$

-Compression: $A_{sc,com} = 678.584$

-Middle: $A_{sc,mid} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\lambda = 1.55334$

$\lambda' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \lambda \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$
conf. factor $c = 1.7465$
 $f_c = 15.00$
From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$
 $l_b/d = 1.00$
 $d_1 = 44.00$
 $R = 125.00$
 $v = 1.01248$
 $N = 745904.162$
 $Ac = 49087.385$
= $\cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$
conf. factor $c = 1.7465$
 $f_c = 15.00$
From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$
 $l_b/d = 1.00$
 $d_1 = 44.00$
 $R = 125.00$
 $v = 1.01248$
 $N = 745904.162$
 $Ac = 49087.385$
= $\cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l \cdot V_{ColO}$

$V_{ColO} = 193699.191$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/d = 2.00$

$\mu_u = 1.5352144E-009$

$\nu_u = 1.5879607E-028$

$d = 0.8 \cdot D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $Col = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$b_w \cdot d = \cdot d \cdot d/4 = 31415.927$

Calculation of Shear Strength at edge 2, $V_{r2} = 193699.191$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l \cdot V_{ColO}$

$V_{ColO} = 193699.191$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/d = 2.00$

$\mu_u = 1.5352144E-009$

$\nu_u = 1.5879607E-028$

$d = 0.8 \cdot D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$

$f_y = 420.00$

s = 100.00
Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 80828.079
bw*d = *d*d/4 = 31415.927

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rccs

Constant Properties

Knowledge Factor, = 1.00
Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Primary Member: Concrete Strength, fc = fcm = 15.00
New material of Primary Member: Steel Strength, fs = fsm = 420.00
Concrete Elasticity, Ec = 18203.022
Steel Elasticity, Es = 200000.00

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, fs = 1.25*fsm = 525.00

Diameter, D = 250.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.7465
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lo/lou,min>=1)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -6.8157582E-028
EDGE -B-
Shear Force, Vb = 6.8157582E-028
BOTH EDGES
Axial Force, F = -745904.162
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 0.00
-Compression: Aslc = 2035.752
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 678.584
-Compression: Asl,com = 678.584
-Middle: Asl,mid = 678.584

Calculation of Shear Capacity ratio , Ve/Vr = 0.28814544

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c^* \quad c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

= $\cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c^* \quad c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

= $\cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of fy: $f_y \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 525.00$

$$lb/d = 1.00$$

$$d1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$Ac = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 1.16122$$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of fy: $f_y \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 525.00$

$$lb/d = 1.00$$

$$d1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$Ac = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 1.16122$$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $Vr1 = 193699.191$

$Vr1 = V_{Col}$ ((10.3), ASCE 41-17) = $knl * V_{Col0}$

$V_{Col0} = 193699.191$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 3.6227516E-010$

$V_u = 6.8157582E-028$

$d = 0.8 * D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} * A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $Col = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$b_w * d = \sqrt{4} * d = 31415.927$

Calculation of Shear Strength at edge 2, $Vr2 = 193699.191$

$Vr2 = V_{Col}$ ((10.3), ASCE 41-17) = $knl * V_{Col0}$

$V_{Col0} = 193699.191$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 3.6227516E-010$

$V_u = 6.8157582E-028$

$d = 0.8 * D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} * A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $Col = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$b_w * d = \sqrt{4} * d = 31415.927$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rccs

Constant Properties

Knowledge Factor, $\phi = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/l_d > 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 3.8888E+006$

Shear Force, $V_2 = -19652.798$

Shear Force, $V_3 = -3.7545092E-010$

Axial Force, $F = -745272.03$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 678.584$

-Compression: $A_{st,com} = 678.584$

-Middle: $A_{st,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $D_bL = 18.00$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.00355561$

$u = y + p = 0.00355561$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00355561$ ((4.29), Biskinis Phd))

$M_y = 8.6873E+007$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 300.00

From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 2.4433E+012$

factor = 0.70

$A_g = 49087.385$

$f_c' = 15.00$

$N = 745272.03$

$E_c * I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to (7) - (8) in Biskinis and Fardis

$M_y = \text{Min}(M_{y_ten}, M_{y_com}) = 8.6873E+007$

y ((10a) or (10b)) = $2.2945961E-005$

M_{y_ten} (8a) = $9.3578E+007$

y_{ten} (7a) = 89.00

error of function (7a) = -1.20629

M_{y_com} (8b) = $8.6873E+007$

y_{com} (7b) = 92.63285

error of function (7b) = -0.01829496

with $\epsilon_y = 0.0021$

$\epsilon_{co} = 0.002$

$\alpha_{pl} = 0.35$ ((9a) in Biskinis and Fardis for no FRP Wrap)

$d_1 = 44.00$

$R = 125.00$

$\nu = 1.01217$

$N = 745272.03$

$A_c = 49087.385$

$= 1.16122$

with $f_c = 15.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ -

From table 10-9: $\rho = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/d \geq 1$

shear control ratio $V_y E / C_{ol} O E = 0.28814544$

$d = 209.00$

$s = 150.00$

$t = 2 \cdot A_v / (d_c \cdot s) + 4 \cdot t_f / D \cdot (f_{fe} / f_s) = 0.00826735$

$A_v = 78.53982$, is the area of the circular stirrup

$d_c = D - 2 \cdot \text{cover} - \text{Hoop Diameter} = 190.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$N_{UD} = 745272.03$

$A_g = 49087.385$

$f_{cE} = 15.00$

$f_{yE} = f_{yIE} = 420.00$

$\rho_l = \text{Area_Tot_Long_Rein} / (A_g) = 0.041472$

$f_{cE} = 15.00$

End Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 9

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 10.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

New material: Concrete Strength, $f_c = f_{cm} = 15.00$

New material: Steel Strength, $f_s = f_{sm} = 420.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -7.7473E+007$

Shear Force, $V_a = 8664.481$

EDGE -B-

Bending Moment, $M_b = 1.7029E+006$

Shear Force, $V_b = -8664.481$

BOTH EDGES

Axial Force, $F = -745499.012$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl} = 763.407$

-Compression: $A_{sc} = 1272.345$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 678.584$

-Compression: $A_{sl,com} = 678.584$

-Middle: $A_{sl,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.00$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 116448.746$
 V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{CoI} = 116448.746$
 $V_{CoI} = 116448.746$
 $k_n = 1.00$
 $displacement_ductility_demand = 0.64000462$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 $f_c' = 10.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $M_u = 7.7473E+007$
 $V_u = 8664.481$
 $d = 0.8 \cdot D = 200.00$
 $N_u = 745499.012$
 $A_g = 49087.385$
From (11.5.4.8), ACI 318-14: $V_s = 98696.044$
 $A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$
 $f_y = 400.00$
 $s = 100.00$
 V_s is multiplied by $Col = 1.00$
 $s/d = 0.50$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 65995.85$
 $b_w \cdot d = \sqrt{N_u} \cdot d / 4 = 31415.927$

 $displacement_ductility_demand$ is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 3 and integ. section (a)

From analysis, chord rotation = 0.04551179
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.07111166$ ((4.29), Biskinis Phd))
 $M_y = 8.6872E+007$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 6000.00
From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.4433E+012$
 $factor = 0.70$
 $A_g = 49087.385$
 $f_c' = 15.00$
 $N = 745499.012$
 $E_c \cdot I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to (7) - (8) in Biskinis and Fardis

 $M_y = \min(M_{y_ten}, M_{y_com}) = 8.6872E+007$
 y ((10a) or (10b)) = 2.2943480E-005
 M_{y_ten} (8a) = 9.3578E+007
 y_{ten} (7a) = 89.00
error of function (7a) = -1.2066
 M_{y_com} (8b) = 8.6872E+007
 y_{com} (7b) = 92.63934
error of function (7b) = -0.01830871
with $e_y = 0.0021$
 $e_{co} = 0.002$
 $apl = 0.35$ ((9a) in Biskinis and Fardis for no FRP Wrap)
 $d_1 = 44.00$

R = 125.00
v = 1.01248
N = 745499.012
Ac = 49087.385
= 1.16122

with $f_c = 15.00$

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

End Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 10

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25 * f_{sm} = 525.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.7465

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.5879607E-028$

EDGE -B-

Shear Force, $V_b = 1.5879607E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st, \text{ten}} = 678.584$

-Compression: $A_{sc, \text{com}} = 678.584$

-Middle: $A_{sc, \text{mid}} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c * c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ

$\mu = 8.3720E+007$

$\phi = 1.55334$

$\lambda = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ

$\mu = 8.3720E+007$

$\phi = 1.55334$

$\lambda = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ
 $\mu = 8.3720E+007$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 193699.191$$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 15.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/d = 2.00$$

$$\mu = 1.5352144E-009$$

$$V_u = 1.5879607E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $Col = 1.00$

$$s/d = 0.50$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$$b_w \cdot d = \cdot d \cdot d/4 = 31415.927$$

Calculation of Shear Strength at edge 2, $Vr2 = 193699.191$

$Vr2 = V_{Col}$ ((10.3), ASCE 41-17) = $knl * V_{Col0}$

$V_{Col0} = 193699.191$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 15.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.5352144E-009$

$V_u = 1.5879607E-028$

$d = 0.8 * D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} * A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $Col = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$b_w * d = \mu_u * d / 4 = 31415.927$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rccs

Constant Properties

Knowledge Factor, $\phi = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 * f_{sm} = 525.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.7465

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o / l_{ou, min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -6.8157582E-028$

EDGE -B-

Shear Force, $V_b = 6.8157582E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 678.584$

-Compression: $A_{sc,com} = 678.584$

-Middle: $A_{st,mid} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\phi = 1.55334$

$\phi' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3}) = 525.00$

$l_b/l_d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$\phi = \phi' \cdot \text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3}) = 1.16122$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: fcc = fc* c = 26.19746
conf. factor c = 1.7465
fc = 15.00
From 10.3.5, ASCE 41-17, Final value of fy: fy*Min(1,1.25*(lb/d)^ 2/3) = 525.00
lb/d = 1.00
d1 = 44.00
R = 125.00
v = 1.01248
N = 745904.162
Ac = 49087.385
= *Min(1,1.25*(lb/d)^ 2/3) = 1.16122

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: fcc = fc* c = 26.19746
conf. factor c = 1.7465
fc = 15.00
From 10.3.5, ASCE 41-17, Final value of fy: fy*Min(1,1.25*(lb/d)^ 2/3) = 525.00
lb/d = 1.00
d1 = 44.00
R = 125.00
v = 1.01248
N = 745904.162
Ac = 49087.385
= *Min(1,1.25*(lb/d)^ 2/3) = 1.16122

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: fcc = fc* c = 26.19746
conf. factor c = 1.7465
fc = 15.00

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 193699.191$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 15.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 2.00$$

$$\mu_u = 3.6227516E-010$$

$$V_u = 6.8157582E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{\text{stirrup}} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $\text{Col} = 1.00$

$$s/d = 0.50$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$$b_w \cdot d = \cdot d \cdot d/4 = 31415.927$$

Calculation of Shear Strength at edge 2, $V_{r2} = 193699.191$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 193699.191$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 15.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 2.00$$

$$\mu_u = 3.6227516E-010$$

$$V_u = 6.8157582E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{\text{stirrup}} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $\text{Col} = 1.00$

$$s/d = 0.50$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 80828.079$$

$$b_w * d = *d*d/4 = 31415.927$$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1
At local axis: 2
Integration Section: (a)
Section Type: rccs

Constant Properties

$$\text{Knowledge Factor, } = 1.00$$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

$$\text{New material of Primary Member: Concrete Strength, } f_c = f_{cm} = 15.00$$

$$\text{New material of Primary Member: Steel Strength, } f_s = f_{sm} = 420.00$$

$$\text{Concrete Elasticity, } E_c = 18203.022$$

$$\text{Steel Elasticity, } E_s = 200000.00$$

$$\text{Diameter, } D = 250.00$$

$$\text{Cover Thickness, } c = 25.00$$

$$\text{Element Length, } L = 3000.00$$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

$$\text{Bending Moment, } M = 0.03180461$$

$$\text{Shear Force, } V_2 = 8664.481$$

$$\text{Shear Force, } V_3 = 1.9291987E-010$$

$$\text{Axial Force, } F = -745499.012$$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

$$\text{-Tension: } A_{s,t} = 763.407$$

$$\text{-Compression: } A_{s,c} = 1272.345$$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

$$\text{-Tension: } A_{s,ten} = 678.584$$

$$\text{-Compression: } A_{s,com} = 678.584$$

$$\text{-Middle: } A_{s,mid} = 678.584$$

$$\text{Mean Diameter of Tension Reinforcement, } D_bL = 18.00$$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.01777791$

$$u = y + p = 0.01777791$$

- Calculation of y -

$$y = (M_y * L_s / 3) / E_{eff} = 0.01777791 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 8.6872E+007$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 1500.00$$

$$\text{From table 10.5, ASCE 41_17: } E_{eff} = \text{factor} * E_c * I_g = 2.4433E+012$$

factor = 0.70
Ag = 49087.385
fc' = 15.00
N = 745499.012
Ec*Ig = 3.4904E+012

Calculation of Yielding Moment My

Calculation of ρ_y and My according to (7) - (8) in Biskinis and Fardis

My = Min(My_ten, My_com) = 8.6872E+007
 ρ_y ((10a) or (10b)) = 2.2943480E-005
My_ten (8a) = 9.3578E+007
 ρ_{y_ten} (7a) = 89.00
error of function (7a) = -1.2066
My_com (8b) = 8.6872E+007
 ρ_{y_com} (7b) = 92.63934
error of function (7b) = -0.01830871
with $e_y = 0.0021$
eco = 0.002
apl = 0.35 ((9a) in Biskinis and Fardis for no FRP Wrap)
d1 = 44.00
R = 125.00
v = 1.01248
N = 745499.012
Ac = 49087.385
= 1.16122
with fc = 15.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of ρ_p -

From table 10-9: $\rho_p = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because lb/d >= 1

shear control ratio $V_y E / V_{CoI} E = 0.28814544$

d = 209.00

s = 150.00

$t = 2 * A_v / (d_c * s) + 4 * t_f / D * (f_{fe} / f_s) = 0.00826735$

$A_v = 78.53982$, is the area of the circular stirrup

$d_c = D - 2 * cover - Hoop Diameter = 190.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

NUD = 745499.012

Ag = 49087.385

f'cE = 15.00

fytE = fylE = 420.00

$\rho_l = Area_Tot_Long_Rein / (Ag) = 0.041472$

f'cE = 15.00

End Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 11

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 10.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

New material: Concrete Strength, $f_c = f_{cm} = 15.00$

New material: Steel Strength, $f_s = f_{sm} = 420.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 0.03180461$

Shear Force, $V_a = 1.9291987E-010$

EDGE -B-

Bending Moment, $M_b = -0.00066078$

Shear Force, $V_b = -1.9291987E-010$

BOTH EDGES

Axial Force, $F = -745499.012$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 763.407$

-Compression: $A_{sc} = 1272.345$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 678.584$

-Compression: $A_{sc,com} = 678.584$

-Middle: $A_{st,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 18.00$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 166901.642$

V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{Col} = 166901.642$

$V_{Col} = 166901.642$

$k_n = 1.00$

displacement_ductility_demand = $7.8359452E-010$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 10.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M / Vd = 2.00$

$M_u = 0.03180461$

$V_u = 1.9291987E-010$

$d = 0.8 \cdot D = 200.00$

$N_u = 745499.012$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 98696.044$

$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$

$f_y = 400.00$

$s = 100.00$

V_s is multiplied by $\phi_{Col} = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 65995.85$

$b_w \cdot d = \sqrt{N_u} \cdot d / 4 = 31415.927$

displacement_ductility_demand is calculated as ϕ / y

- Calculation of ϕ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation = $1.3930676E-011$

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.01777791$ ((4.29), Biskinis Phd)

$M_y = 8.6872E+007$

$L_s = M / V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00

From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.4433E+012$

factor = 0.70

$A_g = 49087.385$

$f_c' = 15.00$

$N = 745499.012$

$$E_c \cdot I_g = 3.4904E+012$$

Calculation of Yielding Moment M_y

Calculation of ρ_y and M_y according to (7) - (8) in Biskinis and Fardis

$$M_y = \min(M_{y_ten}, M_{y_com}) = 8.6872E+007$$

$$\rho_y \text{ ((10a) or (10b))} = 2.2943480E-005$$

$$M_{y_ten} \text{ (8a)} = 9.3578E+007$$

$$\rho_{y_ten} \text{ (7a)} = 89.00$$

$$\text{error of function (7a)} = -1.2066$$

$$M_{y_com} \text{ (8b)} = 8.6872E+007$$

$$\rho_{y_com} \text{ (7b)} = 92.63934$$

$$\text{error of function (7b)} = -0.01830871$$

$$\text{with } e_y = 0.0021$$

$$e_{co} = 0.002$$

$$a_{pl} = 0.35 \text{ ((9a) in Biskinis and Fardis for no FRP Wrap)}$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745499.012$$

$$A_c = 49087.385$$

$$= 1.16122$$

$$\text{with } f_c = 15.00$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

End Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 12

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rccs

Constant Properties

 Knowledge Factor, $\gamma = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$
 Concrete Elasticity, $E_c = 18203.022$
 Steel Elasticity, $E_s = 200000.00$

 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 525.00$
 #####

Diameter, $D = 250.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.7465
 Element Length, $L = 3000.00$
 Primary Member
 Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_o/l_{ou,min} >= 1$)
 No FRP Wrapping

 Stepwise Properties

 At local axis: 3
 EDGE -A-
 Shear Force, $V_a = -1.5879607E-028$
 EDGE -B-
 Shear Force, $V_b = 1.5879607E-028$
 BOTH EDGES
 Axial Force, $F = -745904.162$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 0.00$
 -Compression: $A_{sc} = 2035.752$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 678.584$
 -Compression: $A_{sc,com} = 678.584$
 -Middle: $A_{sc,mid} = 678.584$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\phi = 1.55334$

$\lambda = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot \lambda = 26.19746$

conf. factor $\lambda = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \phi \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\phi = 1.55334$

$\lambda = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot \lambda = 26.19746$

conf. factor $\lambda = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \phi \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ
 $\mu = 8.3720E+007$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ
 $\mu = 8.3720E+007$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, Vr1 = 193699.191

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VColO

VColO = 193699.191

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

fc' = 15.00, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00

Mu = 1.5352144E-009

Vu = 1.5879607E-028

d = 0.8*D = 200.00

Nu = 745904.162

Ag = 49087.385

From (11.5.4.8), ACI 318-14: Vs = 103630.846

Av = /2*A_stirrup = 123370.055

fy = 420.00

s = 100.00

Vs is multiplied by Col = 1.00

s/d = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 80828.079

bw*d = *d*d/4 = 31415.927

Calculation of Shear Strength at edge 2, Vr2 = 193699.191

Vr2 = VCol ((10.3), ASCE 41-17) = knl*VColO

VColO = 193699.191

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

fc' = 15.00, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00

Mu = 1.5352144E-009

Vu = 1.5879607E-028

d = 0.8*D = 200.00

Nu = 745904.162

Ag = 49087.385

From (11.5.4.8), ACI 318-14: Vs = 103630.846

Av = /2*A_stirrup = 123370.055

fy = 420.00

s = 100.00

Vs is multiplied by Col = 1.00

s/d = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 80828.079

bw*d = *d*d/4 = 31415.927

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rccs

Constant Properties

Knowledge Factor, $\phi = 1.00$
Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$
Concrete Elasticity, $E_c = 18203.022$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 525.00$

Diameter, $D = 250.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.7465
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -6.8157582E-028$
EDGE -B-
Shear Force, $V_b = 6.8157582E-028$
BOTH EDGES
Axial Force, $F = -745904.162$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 2035.752$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 678.584$
-Compression: $A_{sl,com} = 678.584$
-Middle: $A_{sl,mid} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$
with
 $M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$
 $M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$
 $M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$$\text{Mu} = 8.3720\text{E}+007$$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu_1 -

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

$$\text{Mu} = 8.3720\text{E}+007$$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu_2 +

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

$$\text{Mu} = 8.3720\text{E}+007$$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

lb/d = 1.00
d1 = 44.00
R = 125.00
v = 1.01248
N = 745904.162
Ac = 49087.385
= *Min(1,1.25*(lb/d)^ 2/3) = 1.16122

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: fcc = fc* c = 26.19746
conf. factor c = 1.7465
fc = 15.00
From 10.3.5, ASCE 41-17, Final value of fy: fy*Min(1,1.25*(lb/d)^ 2/3) = 525.00
lb/d = 1.00
d1 = 44.00
R = 125.00
v = 1.01248
N = 745904.162
Ac = 49087.385
= *Min(1,1.25*(lb/d)^ 2/3) = 1.16122

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 193699.191

Calculation of Shear Strength at edge 1, Vr1 = 193699.191
Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 193699.191
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
fc' = 15.00, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)
M/Vd = 2.00
Mu = 3.6227516E-010
Vu = 6.8157582E-028
d = 0.8*D = 200.00
Nu = 745904.162
Ag = 49087.385
From (11.5.4.8), ACI 318-14: Vs = 103630.846
Av = /2*A_stirup = 123370.055
fy = 420.00
s = 100.00

Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 80828.079
bw*d = *d*d/4 = 31415.927

Calculation of Shear Strength at edge 2, Vr2 = 193699.191
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 193699.191
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
fc' = 15.00, but fc^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)
M/Vd = 2.00
Mu = 3.6227516E-010
Vu = 6.8157582E-028
d = 0.8*D = 200.00
Nu = 745904.162
Ag = 49087.385
From (11.5.4.8), ACI 318-14: Vs = 103630.846
Av = /2*A_stirrup = 123370.055
fy = 420.00
s = 100.00
Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 80828.079
bw*d = *d*d/4 = 31415.927

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1
At local axis: 3
Integration Section: (a)
Section Type: rccs

Constant Properties

Knowledge Factor, = 1.00
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
New material of Primary Member: Concrete Strength, fc = fcm = 15.00
New material of Primary Member: Steel Strength, fs = fsm = 420.00
Concrete Elasticity, Ec = 18203.022
Steel Elasticity, Es = 200000.00
Diameter, D = 250.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lb/d >= 1)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -7.7473E+007$
Shear Force, $V2 = 8664.481$
Shear Force, $V3 = 1.9291987E-010$
Axial Force, $F = -745499.012$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 763.407$
-Compression: $As_c = 1272.345$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{,ten} = 678.584$
-Compression: $As_{,com} = 678.584$
-Middle: $As_{,mid} = 678.584$
Mean Diameter of Tension Reinforcement, $Db_L = 18.00$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.07111166$
 $u = y + p = 0.07111166$

- Calculation of y -

$y = (My * Ls / 3) / Eleff = 0.07111166$ ((4.29), Biskinis Phd))
 $My = 8.6872E+007$
 $Ls = M/V$ (with $Ls > 0.1 * L$ and $Ls < 2 * L$) = 6000.00
From table 10.5, ASCE 41_17: $Eleff = factor * Ec * I_g = 2.4433E+012$
 $factor = 0.70$
 $Ag = 49087.385$
 $fc' = 15.00$
 $N = 745499.012$
 $Ec * I_g = 3.4904E+012$

Calculation of Yielding Moment My

Calculation of y and My according to (7) - (8) in Biskinis and Fardis

$My = \text{Min}(My_{,ten}, My_{,com}) = 8.6872E+007$
 y ((10a) or (10b)) = $2.2943480E-005$
 $My_{,ten}$ (8a) = $9.3578E+007$
 $y_{,ten}$ (7a) = 89.00
error of function (7a) = -1.2066
 $My_{,com}$ (8b) = $8.6872E+007$
 $y_{,com}$ (7b) = 92.63934
error of function (7b) = -0.01830871
with $ey = 0.0021$
 $eco = 0.002$
 $apl = 0.35$ ((9a) in Biskinis and Fardis for no FRP Wrap)
 $d1 = 44.00$
 $R = 125.00$
 $v = 1.01248$
 $N = 745499.012$
 $Ac = 49087.385$
 $= 1.16122$
with $fc = 15.00$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

- Calculation of p -

From table 10-9: $\rho = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$

shear control ratio $V_y E / V_{Co} I_{OE} = 0.28814544$

$d = 209.00$

$s = 150.00$

$t = 2 \cdot A_v / (d_c \cdot s) + 4 \cdot t_f / D \cdot (f_{fe} / f_s) = 0.00826735$

$A_v = 78.53982$, is the area of the circular stirrup

$d_c = D - 2 \cdot \text{cover} - \text{Hoop Diameter} = 190.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $t_f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises t_f to steel strength

All these variables have already been given in Shear control ratio calculation.

$NUD = 745499.012$

$Ag = 49087.385$

$f_{cE} = 15.00$

$f_{yE} = f_{yI} = 420.00$

$\rho_l = \text{Area_Tot_Long_Rein} / (Ag) = 0.041472$

$f_{cE} = 15.00$

End Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 13

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 10.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

New material: Concrete Strength, $f_c = f_{cm} = 15.00$

New material: Steel Strength, $f_s = f_{sm} = 420.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -7.7473E+007$

Shear Force, $V_a = 8664.481$

EDGE -B-

Bending Moment, $M_b = 1.7029E+006$

Shear Force, $V_b = -8664.481$

BOTH EDGES

Axial Force, $F = -745499.012$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 678.584$

-Compression: $A_{st,com} = 678.584$

-Middle: $A_{st,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 18.00$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 151740.092$

V_n ((10.3), ASCE 41-17) = $k_n l \cdot V_{CoI} = 151740.092$

$V_{CoI} = 166901.642$

$k_n l = 0.90915877$

displacement_ductility_demand = 3.21122

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_{s+} = f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$\gamma = 1$ (normal-weight concrete)

$f_c' = 10.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$M_u = 1.7029E+006$

$V_u = 8664.481$

$d = 0.8 \cdot D = 200.00$

$N_u = 745499.012$

Ag = 49087.385
From (11.5.4.8), ACI 318-14: Vs = 98696.044
Av = $\sqrt{2} \cdot A_{stirrup} = 123370.055$
fy = 400.00
s = 100.00
Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 65995.85
bw*d = $\sqrt{2} \cdot d^2 / 4 = 31415.927$

displacement_ductility_demand is calculated as ϕ / y

- Calculation of ϕ / y for END B -
for rotation axis 3 and integ. section (b)

From analysis, chord rotation = 0.01141775
 $y = (My \cdot Ls / 3) / Eleff = 0.00355558$ ((4.29), Biskinis Phd)
My = 8.6872E+007
Ls = M/V (with Ls > 0.1*L and Ls < 2*L) = 300.00
From table 10.5, ASCE 41_17: Eleff = factor * Ec * Ig = 2.4433E+012
factor = 0.70
Ag = 49087.385
fc' = 15.00
N = 745499.012
Ec * Ig = 3.4904E+012

Calculation of Yielding Moment My

Calculation of ϕ / y and My according to (7) - (8) in Biskinis and Fardis

My = Min(My_ten, My_com) = 8.6872E+007
 y ((10a) or (10b)) = 2.2943480E-005
My_ten (8a) = 9.3578E+007
 ϕ_{ten} (7a) = 89.00
error of function (7a) = -1.2066
My_com (8b) = 8.6872E+007
 ϕ_{com} (7b) = 92.63934
error of function (7b) = -0.01830871
with ey = 0.0021
eco = 0.002
apl = 0.35 ((9a) in Biskinis and Fardis for no FRP Wrap)
d1 = 44.00
R = 125.00
v = 1.01248
N = 745499.012
Ac = 49087.385
= 1.16122
with fc = 15.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

End Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 14

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 525.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.7465

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} \geq 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.5879607E-028$

EDGE -B-

Shear Force, $V_b = 1.5879607E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 678.584$

-Compression: $A_{sc,com} = 678.584$

-Middle: $A_{st,mid} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\lambda = 1.55334$

$\lambda' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \lambda \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

= $\cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

= $\cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l \cdot V_{ColO}$

$V_{ColO} = 193699.191$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs ((11.3), ACI 440).

$= 1$ (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/d = 2.00$

$\mu_u = 1.5352144E-009$

$\nu_u = 1.5879607E-028$

$d = 0.8 \cdot D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $Col = 1.00$

$s/d = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$b_w \cdot d = \cdot d \cdot d/4 = 31415.927$

Calculation of Shear Strength at edge 2, $V_{r2} = 193699.191$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l \cdot V_{ColO}$

$V_{ColO} = 193699.191$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs ((11.3), ACI 440).

$= 1$ (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/d = 2.00$

$\mu_u = 1.5352144E-009$

$\nu_u = 1.5879607E-028$

$d = 0.8 \cdot D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$

$f_y = 420.00$

s = 100.00
Vs is multiplied by Col = 1.00
s/d = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 80828.079
bw*d = *d*d/4 = 31415.927

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rccs

Constant Properties

Knowledge Factor, = 1.00
Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Primary Member: Concrete Strength, fc = fcm = 15.00
New material of Primary Member: Steel Strength, fs = fsm = 420.00
Concrete Elasticity, Ec = 18203.022
Steel Elasticity, Es = 200000.00

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, fs = 1.25*fsm = 525.00

Diameter, D = 250.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.7465
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lo/lou,min>=1)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -6.8157582E-028
EDGE -B-
Shear Force, Vb = 6.8157582E-028
BOTH EDGES
Axial Force, F = -745904.162
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 0.00
-Compression: Aslc = 2035.752
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 678.584
-Compression: Asl,com = 678.584
-Middle: Asl,mid = 678.584

Calculation of Shear Capacity ratio , Ve/Vr = 0.28814544

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$
with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c^* \quad c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

= $\cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c^* \quad c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$l_b/d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

= $\cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 525.00$

$$lb/d = 1.00$$

$$d1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$Ac = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 1.16122$$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 525.00$

$$lb/d = 1.00$$

$$d1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$Ac = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (lb/d)^{2/3}) = 1.16122$$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $Vr1 = 193699.191$

$Vr1 = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$

$V_{Col0} = 193699.191$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 3.6227516E-010$

$V_u = 6.8157582E-028$

$d = 0.8 * D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = /2 * A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $Col = 1.00$

$s/d = 0.50$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$bw * d = *d * d / 4 = 31415.927$

Calculation of Shear Strength at edge 2, $Vr2 = 193699.191$

$Vr2 = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$

$V_{Col0} = 193699.191$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)

$f_c' = 15.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 3.6227516E-010$

$V_u = 6.8157582E-028$

$d = 0.8 * D = 200.00$

$N_u = 745904.162$

$A_g = 49087.385$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$A_v = /2 * A_{stirrup} = 123370.055$

$f_y = 420.00$

$s = 100.00$

V_s is multiplied by $Col = 1.00$

$s/d = 0.50$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$bw * d = *d * d / 4 = 31415.927$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rccs

Constant Properties

Knowledge Factor, $\phi = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/l_d >= 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -0.00066078$

Shear Force, $V_2 = -8664.481$

Shear Force, $V_3 = -1.9291987E-010$

Axial Force, $F = -745499.012$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 678.584$

-Compression: $A_{st,com} = 678.584$

-Middle: $A_{st,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $D_bL = 18.00$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.01777791$

$u = y + p = 0.01777791$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.01777791$ ((4.29), Biskinis Phd))

$M_y = 8.6872E+007$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1500.00

From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 2.4433E+012$

factor = 0.70

$A_g = 49087.385$

$f_c' = 15.00$

$N = 745499.012$

$E_c * I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to (7) - (8) in Biskinis and Fardis

$M_y = \text{Min}(M_{y_ten}, M_{y_com}) = 8.6872E+007$

y ((10a) or (10b)) = $2.2943480E-005$

M_{y_ten} (8a) = $9.3578E+007$

y_{ten} (7a) = 89.00

error of function (7a) = -1.2066

M_{y_com} (8b) = $8.6872E+007$

y_{com} (7b) = 92.63934

error of function (7b) = -0.01830871

with $\epsilon_y = 0.0021$

$\epsilon_{co} = 0.002$

$\alpha_{pl} = 0.35$ ((9a) in Biskinis and Fardis for no FRP Wrap)

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745499.012$

$A_c = 49087.385$

$= 1.16122$

with $f_c = 15.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ -

From table 10-9: $\rho = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/d \geq 1$

shear control ratio $V_y E / V_{co} I_{OE} = 0.28814544$

$d = 209.00$

$s = 150.00$

$t = 2 \cdot A_v / (d_c \cdot s) + 4 \cdot t_f / D \cdot (f_{fe} / f_s) = 0.00826735$

$A_v = 78.53982$, is the area of the circular stirrup

$d_c = D - 2 \cdot \text{cover} - \text{Hoop Diameter} = 190.00$

The term $2 \cdot t_f / bw \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / bw$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$N_{UD} = 745499.012$

$A_g = 49087.385$

$f_{cE} = 15.00$

$f_{yE} = f_{yIE} = 420.00$

$\rho_l = \text{Area_Tot_Long_Rein} / (A_g) = 0.041472$

$f_{cE} = 15.00$

End Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 15

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 10.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

New material: Concrete Strength, $f_c = f_{cm} = 15.00$

New material: Steel Strength, $f_s = f_{sm} = 420.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 0.03180461$

Shear Force, $V_a = 1.9291987E-010$

EDGE -B-

Bending Moment, $M_b = -0.00066078$

Shear Force, $V_b = -1.9291987E-010$

BOTH EDGES

Axial Force, $F = -745499.012$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 678.584$

-Compression: $A_{sl,com} = 678.584$

-Middle: $A_{sl,mid} = 678.584$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.00$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 166901.642$
 V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{Col} = 166901.642$
 $V_{Col} = 166901.642$
 $k_n = 1.00$
 $displacement_ductility_demand = 2.6661473E-010$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 $f_c' = 10.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.00$
 $\mu_u = 0.00066078$
 $V_u = 1.9291987E-010$
 $d = 0.8 \cdot D = 200.00$
 $N_u = 745499.012$
 $A_g = 49087.385$
From (11.5.4.8), ACI 318-14: $V_s = 98696.044$
 $A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$
 $f_y = 400.00$
 $s = 100.00$
 V_s is multiplied by $Col = 1.00$
 $s/d = 0.50$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 65995.85$
 $b_w \cdot d = \sqrt{2} \cdot d^2 / 4 = 31415.927$

 $displacement_ductility_demand$ is calculated as ϕ / y

- Calculation of ϕ / y for END B -
for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\phi = 4.7398535E-012$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.01777791$ ((4.29), Biskinis Phd))
 $M_y = 8.6872E+007$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00
From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.4433E+012$
 $factor = 0.70$
 $A_g = 49087.385$
 $f_c' = 15.00$
 $N = 745499.012$
 $E_c \cdot I_g = 3.4904E+012$

Calculation of Yielding Moment M_y

Calculation of ϕ / y and M_y according to (7) - (8) in Biskinis and Fardis

 $M_y = \text{Min}(M_{y_ten}, M_{y_com}) = 8.6872E+007$
 y ((10a) or (10b)) = 2.2943480E-005
 M_{y_ten} (8a) = 9.3578E+007
 y_{ten} (7a) = 89.00
error of function (7a) = -1.2066
 M_{y_com} (8b) = 8.6872E+007
 y_{com} (7b) = 92.63934
error of function (7b) = -0.01830871
with $e_y = 0.0021$
 $e_{co} = 0.002$
 $a_{pl} = 0.35$ ((9a) in Biskinis and Fardis for no FRP Wrap)
 $d_1 = 44.00$

R = 125.00
v = 1.01248
N = 745499.012
Ac = 49087.385
= 1.16122

with $f_c = 15.00$

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

End Of Calculation of Shear Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 16

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 50 and 51)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rccs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 15.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 420.00$

Concrete Elasticity, $E_c = 18203.022$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 525.00$

#####

Diameter, $D = 250.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.7465

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.5879607E-028$

EDGE -B-

Shear Force, $V_b = 1.5879607E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st, \text{ten}} = 678.584$

-Compression: $A_{sc, \text{com}} = 678.584$

-Middle: $A_{sc, \text{mid}} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

fc = 15.00

From 10.3.5, ASCE 41-17, Final value of fy: $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

lb/d = 1.00

d1 = 44.00

R = 125.00

v = 1.01248

N = 745904.162

Ac = 49087.385

= $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu1-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

Mu = $8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor c = 1.7465

fc = 15.00

From 10.3.5, ASCE 41-17, Final value of fy: $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

lb/d = 1.00

d1 = 44.00

R = 125.00

v = 1.01248

N = 745904.162

Ac = 49087.385

= $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu

Mu = $8.3720E+007$

= 1.55334

' = 1.35517

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor c = 1.7465

fc = 15.00

From 10.3.5, ASCE 41-17, Final value of fy: $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

lb/d = 1.00

d1 = 44.00

R = 125.00

v = 1.01248

N = 745904.162

Ac = 49087.385

= $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), μ
 $\mu = 8.3720E+007$

$$= 1.55334$$

$$' = 1.35517$$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 193699.191$$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)

$f_c' = 15.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/d = 2.00$$

$$\mu = 1.5352144E-009$$

$$V_u = 1.5879607E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{stirrup} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $Col = 1.00$

$$s/d = 0.50$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$$b_w \cdot d = \cdot d \cdot d/4 = 31415.927$$

Calculation of Shear Strength at edge 2, Vr2 = 193699.191

Vr2 = VCol ((10.3), ASCE 41-17) = knl*VColO

VColO = 193699.191

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

fc' = 15.00, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00

Mu = 1.5352144E-009

Vu = 1.5879607E-028

d = 0.8*D = 200.00

Nu = 745904.162

Ag = 49087.385

From (11.5.4.8), ACI 318-14: Vs = 103630.846

Av = /2*A_stirup = 123370.055

fy = 420.00

s = 100.00

Vs is multiplied by Col = 1.00

s/d = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 80828.079

bw*d = *d*d/4 = 31415.927

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rccs

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Primary Member: Concrete Strength, fc = fcm = 15.00

New material of Primary Member: Steel Strength, fs = fsm = 420.00

Concrete Elasticity, Ec = 18203.022

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths, the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, fs = 1.25*fsm = 525.00

#####

Diameter, D = 250.00

Cover Thickness, c = 25.00

Mean Confinement Factor overall section = 1.7465

Element Length, L = 3000.00

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length (lo/lou,min>= 1)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -6.8157582E-028$

EDGE -B-

Shear Force, $V_b = 6.8157582E-028$

BOTH EDGES

Axial Force, $F = -745904.162$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2035.752$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 678.584$

-Compression: $A_{sl,com} = 678.584$

-Middle: $A_{sl,mid} = 678.584$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.28814544$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 55813.539$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 8.3720E+007$

$M_{u1+} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 8.3720E+007$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 8.3720E+007$

$M_{u2+} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 8.3720E+007$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), M_u

$M_u = 8.3720E+007$

$\lambda = 1.55334$

$\lambda' = 1.35517$

error of function (3.68), Biskinis Phd = 335531.824

From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$

conf. factor $c = 1.7465$

$f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3}) = 525.00$

$l_b/l_d = 1.00$

$d_1 = 44.00$

$R = 125.00$

$v = 1.01248$

$N = 745904.162$

$A_c = 49087.385$

$= \lambda \cdot \text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3}) = 1.16122$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u1-}

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$
conf. factor $c = 1.7465$
 $f_c = 15.00$
From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$
 $l_b/d = 1.00$
 $d_1 = 44.00$
 $R = 125.00$
 $v = 1.01248$
 $N = 745904.162$
 $Ac = 49087.385$
 $= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2+

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$
conf. factor $c = 1.7465$
 $f_c = 15.00$
From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$
 $l_b/d = 1.00$
 $d_1 = 44.00$
 $R = 125.00$
 $v = 1.01248$
 $N = 745904.162$
 $Ac = 49087.385$
 $= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2-

Calculation of ultimate Moment Strength ((3.67), Biskinis Phd), Mu
Mu = 8.3720E+007

= 1.55334
' = 1.35517
error of function (3.68), Biskinis Phd = 335531.824
From 5A.2, TBDY: $f_{cc} = f_c \cdot c = 26.19746$
conf. factor $c = 1.7465$
 $f_c = 15.00$

From 10.3.5, ASCE 41-17, Final value of f_y : $f_y \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 525.00$

$$l_b/d = 1.00$$

$$d_1 = 44.00$$

$$R = 125.00$$

$$v = 1.01248$$

$$N = 745904.162$$

$$A_c = 49087.385$$

$$= \cdot \text{Min}(1, 1.25 \cdot (l_b/d)^{2/3}) = 1.16122$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 193699.191$

Calculation of Shear Strength at edge 1, $V_{r1} = 193699.191$

$V_{r1} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 193699.191$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 15.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 2.00$$

$$\mu_u = 3.6227516E-010$$

$$V_u = 6.8157582E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{\text{stirrup}} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $\text{Col} = 1.00$

$$s/d = 0.50$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 80828.079$

$$b_w \cdot d = \cdot d \cdot d/4 = 31415.927$$

Calculation of Shear Strength at edge 2, $V_{r2} = 193699.191$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 193699.191$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 15.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 2.00$$

$$\mu_u = 3.6227516E-010$$

$$V_u = 6.8157582E-028$$

$$d = 0.8 \cdot D = 200.00$$

$$N_u = 745904.162$$

$$A_g = 49087.385$$

From (11.5.4.8), ACI 318-14: $V_s = 103630.846$

$$A_v = \sqrt{2} \cdot A_{\text{stirrup}} = 123370.055$$

$$f_y = 420.00$$

$$s = 100.00$$

V_s is multiplied by $\text{Col} = 1.00$

$$s/d = 0.50$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 80828.079$$

$$b_w * d = *d*d/4 = 31415.927$$

End Of Calculation of Shear Capacity ratio for element: column CC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1
At local axis: 3
Integration Section: (b)
Section Type: rccs

Constant Properties

$$\text{Knowledge Factor, } = 1.00$$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

$$\text{New material of Primary Member: Concrete Strength, } f_c = f_{cm} = 15.00$$

$$\text{New material of Primary Member: Steel Strength, } f_s = f_{sm} = 420.00$$

$$\text{Concrete Elasticity, } E_c = 18203.022$$

$$\text{Steel Elasticity, } E_s = 200000.00$$

$$\text{Diameter, } D = 250.00$$

$$\text{Cover Thickness, } c = 25.00$$

$$\text{Element Length, } L = 3000.00$$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

$$\text{Bending Moment, } M = 1.7029E+006$$

$$\text{Shear Force, } V_2 = -8664.481$$

$$\text{Shear Force, } V_3 = -1.9291987E-010$$

$$\text{Axial Force, } F = -745499.012$$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

$$\text{-Tension: } A_{st} = 0.00$$

$$\text{-Compression: } A_{sc} = 2035.752$$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

$$\text{-Tension: } A_{st,ten} = 678.584$$

$$\text{-Compression: } A_{st,com} = 678.584$$

$$\text{-Middle: } A_{st,mid} = 678.584$$

$$\text{Mean Diameter of Tension Reinforcement, } D_bL = 18.00$$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_R = 1.0^*$ $u = 0.00355558$

$$u = y + p = 0.00355558$$

- Calculation of y -

$$y = (M_y * L_s / 3) / E_{eff} = 0.00355558 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 8.6872E+007$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 300.00$$

$$\text{From table 10.5, ASCE 41_17: } E_{eff} = \text{factor} * E_c * I_g = 2.4433E+012$$

factor = 0.70
Ag = 49087.385
fc' = 15.00
N = 745499.012
Ec*Ig = 3.4904E+012

Calculation of Yielding Moment My

Calculation of ρ_y and My according to (7) - (8) in Biskinis and Fardis

My = Min(My_ten, My_com) = 8.6872E+007
 ρ_y ((10a) or (10b)) = 2.2943480E-005
My_ten (8a) = 9.3578E+007
 ρ_{y_ten} (7a) = 89.00
error of function (7a) = -1.2066
My_com (8b) = 8.6872E+007
 ρ_{y_com} (7b) = 92.63934
error of function (7b) = -0.01830871
with e_y = 0.0021
eco = 0.002
apl = 0.35 ((9a) in Biskinis and Fardis for no FRP Wrap)
d1 = 44.00
R = 125.00
v = 1.01248
N = 745499.012
Ac = 49087.385
= 1.16122
with fc = 15.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of ρ_p -

From table 10-9: ρ_p = 0.00

with:

- Columns not controlled by inadequate development or splicing along the clear height because lb/d >= 1

shear control ratio $V_y E / C_o I_o E$ = 0.28814544

d = 209.00

s = 150.00

$t = 2 * A_v / (d_c * s) + 4 * t_f / D * (f_{fe} / f_s) = 0.00826735$

$A_v = 78.53982$, is the area of the circular stirrup

$d_c = D - 2 * \text{cover} - \text{Hoop Diameter} = 190.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

NUD = 745499.012

Ag = 49087.385

f'cE = 15.00

fytE = fylE = 420.00

$\rho_l = \text{Area_Tot_Long_Rein} / (A_g) = 0.041472$

f'cE = 15.00

End Of Calculation of Chord Rotation Capacity for element: column CC1 of floor 1

At local axis: 3

Integration Section: (b)