

Detailed Member Calculations

Units: N&mm

Regulation: ASCE 41-17

Calculation No. 1

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$
Section Height, $H = 400.00$
Section Width, $W = 300.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 1850.00$
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{o,u,min} = l_b/l_d >= 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -4.6301801E-012$
Shear Force, $V_a = -3.4466031E-014$
EDGE -B-
Bending Moment, $M_b = -5.9084780E-011$
Shear Force, $V_b = 3.4466031E-014$
BOTH EDGES
Axial Force, $F = -577.527$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{s,t} = 603.1858$
-Compression: $A_{s,c} = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{s,ten} = 508.938$
-Compression: $A_{s,com} = 508.938$
-Middle: $A_{s,mid} = 508.938$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 14.66667$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 102628.668$
 V_n ((22.5.1.1), ACI 318-14) = 136838.224

NOTE: In expression (22.5.1.1) 'V_w' is replaced by 'V_w + φV_f'
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 61440.00$
= 1 (normal-weight concrete)
 $f'_c = 16.00$, but $f'_c^{0.5} <= 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 4.6301801E-012$
 $V_u = 3.4466031E-014$
From (11.5.4.8), ACI 318-14: $V_s = 75398.224$
 $A_v = 157079.633$
 $f_y = 400.00$
 $s = 150.00$
 V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f <= 255092.67$

End Of Calculation of Shear Capacity for element: beam B1 of floor 1
At local axis: 2
Integration Section: (a)

Calculation No. 2

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_r)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Mean strength values are used for both shear and moment calculations.

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} \geq 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = 2740.264$

EDGE -B-

Shear Force, $V_b = 2740.264$

BOTH EDGES

Axial Force, $F = -224.0403$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 603.1858$

-Compression: $As_c = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 603.1858$

-Compression: $As_{l,com} = 615.7522$

-Middle: $As_{l,mid} = 307.8761$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77008272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 175486.019$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.5980E+008$

$Mu_{1+} = 1.5719E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.5980E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.5978E+008$

$Mu_{2+} = 1.5721E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.5978E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = 2740.264$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 2740.264$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010691$

$M_u = 1.5719E+008$

with full section properties:

$b = 300.00$

$d = 357.00$

$d' = 42.00$

$v = 0.00010459$

$N = 224.0403$

$f_c = 20.00$

$\phi_{co} (5A.5, TBDY) = 0.002$

Final value of ϕ_{cu} : $\phi_{cu}^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_{cu} = 0.00583896$

$\phi_{we} (5.4c) = 0.0034192$

$\phi_{ase} ((5.4d), TBDY) = 0.15672608$

$\phi_{bo} = 240.00$

$\phi_{ho} = 340.00$

$\phi_{bi2} = 346400.00$

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00261799$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x (5.4d) = 0.00349066$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 300.00$$

$$psh,y (5.4d) = 0.00261799$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 400.00$$

$$s = 150.00$$

$$fywe = 555.55$$

$$fce = 20.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00231479$$

$$sh1 = 0.008$$

$$ft1 = 666.66$$

$$fy1 = 555.55$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = fs = 555.55$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00231479$$

$$sh2 = 0.008$$

$$ft2 = 666.66$$

$$fy2 = 555.55$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = fs = 555.55$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

with $E_{sv} = E_s = 200000.00$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.15644251$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.15970173$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$f_{cc} (5A.2, TBDY) = 20.00$$

$$c_c (5A.5, TBDY) = 0.002$$

c = confinement factor = 1.00

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.2134938$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.21794159$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.16156243$$

$$M_u = M_{Rc} (4.14) = 1.5719E+008$$

$$u = s_u (4.1) = 0.00010691$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u1} -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010702$$

$$M_u = 1.5980E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.00583896$$

$$\phi_{we} (5.4c) = 0.0034192$$

$$\phi_{ase} ((5.4d), TBDY) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$\phi_{psh,min} = \text{Min}(\phi_{psh,x}, \phi_{psh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $\phi_{psh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$\phi_{psh,x} (5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$\phi_{psh,y} (5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.002$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_{b,min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsy_v = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Es_v = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.15925564$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.15600552$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.07962782$$

and confined core properties:

$$b = 240.00$$

$$d = 328.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.21727713$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.2128429$$

$$v = A_{sl, mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.10863856$$

Case/Assumption: Unconfined full section - Steel rupture
' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.1647931$$

$$\mu = M_{Rc}(4.14) = 1.5980E+008$$

$$u = s_u(4.1) = 0.00010702$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010682$$

$$\mu = 1.5721E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} \cdot \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}(5.4d), TBDY) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh, min} = \text{Min}(p_{sh, x}, p_{sh, y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh, min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh, x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} \cdot n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh, y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} \cdot n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15600552

2 = Asl,com/(b*d)*(fs2/fc) = 0.15925564

v = Asl,mid/(b*d)*(fsv/fc) = 0.07962782

and confined core properties:

b = 240.00

d = 328.00

d' = 13.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.2128429

2 = Asl,com/(b*d)*(fs2/fc) = 0.21727713

v = Asl,mid/(b*d)*(fsv/fc) = 0.10863856

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.16319614

Mu = MRc (4.14) = 1.5721E+008

u = su (4.1) = 0.00010682

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 0.00010711$$

$$\mu = 1.5978E+008$$

with full section properties:

$$b = 300.00$$

$$d = 357.00$$

$$d' = 42.00$$

$$v = 0.00010459$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1,nominal} = 0.08,$$

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/lb_{u,min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.15970173$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.15644251$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.21794159$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.2134938$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.16317177$$

$$\mu = MRc (4.14) = 1.5978E+008$$

$$u = su (4.1) = 0.00010711$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 227879.44$

Calculation of Shear Strength at edge 1, $V_{r1} = 227879.44$

$$V_{r1} = V_n ((22.5.1.1), ACI 318-14)$$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$
 = 1 (normal-weight concrete)
 $f'_c = 20.00$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 300.00$
 $d = 320.00$
 $V_u*d/M_u < 1 = 1.00$
 $M_u = 6710.981$
 $V_u = 2740.264$
 From (11.5.4.8), ACI 318-14: $V_s = 148933.273$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$
 V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
 From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

 Calculation of Shear Strength at edge 2, $V_{r2} = 227879.44$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

 NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
 where Vf is the contribution of FRPs (11.3), ACI 440).

 From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$
 = 1 (normal-weight concrete)
 $f'_c = 20.00$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 300.00$
 $d = 320.00$
 $V_u*d/M_u < 1 = 1.00$
 $M_u = 6710.981$
 $V_u = 2740.264$
 From (11.5.4.8), ACI 318-14: $V_s = 148933.273$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$
 V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
 From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

 End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
 At local axis: 3

 Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rcars

Constant Properties

 Knowledge Factor, $\phi = 0.75$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
 Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
 Concrete Elasticity, $E_c = 21019.039$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 Existing material: Steel Strength, $f_s = 1.25*f_{sm} = 555.55$
 #####

Section Height, H = 400.00
Section Width, W = 300.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.00
Element Length, L = 1850.00
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou}, \min >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -8.7724203E-020$
EDGE -B-
Shear Force, $V_b = 8.7724203E-020$
BOTH EDGES
Axial Force, $F = -224.0403$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 603.1858$
-Compression: $As_c = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 508.938$
-Compression: $As_{c,com} = 508.938$
-Middle: $As_{mid} = 508.938$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77093353$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 117541.903$
with
 $M_{pr1} = \max(\mu_{u1+}, \mu_{u1-}) = 1.0873E+008$
 $\mu_{u1+} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{u1-} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \max(\mu_{u2+}, \mu_{u2-}) = 1.0873E+008$
 $\mu_{u2+} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{u2-} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = -8.7724203E-020$, is the shear force acting at edge 1 for the static loading combination
 $V_2 = 8.7724203E-020$, is the shear force acting at edge 2 for the static loading combination

Calculation of μ_{u1+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:
 $\mu_u = 0.00015595$
 $\mu_u = 1.0873E+008$

with full section properties:
 $b = 400.00$
 $d = 258.00$
 $d' = 42.00$

v = 0.00010855

N = 224.0403

fc = 20.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

we (5.4c) = 0.0034192

ase ((5.4d), TBDY) = 0.15672608

bo = 240.00

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x, psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617

2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617

v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2046582

Mu = MRc (4.14) = 1.0873E+008

u = su (4.1) = 0.00015595

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 0.00015595

Mu = 1.0873E+008

with full section properties:

b = 400.00

d = 258.00

d' = 42.00

v = 0.00010855

N = 224.0403

fc = 20.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00583896

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00583896

we (5.4c) = 0.0034192

ase ((5.4d), TBDY) = 0.15672608

bo = 240.00

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066
Ash = Astir*ns = 78.53982
No stirups, ns = 2.00
bk = 300.00

psh,y (5.4d) = 0.00261799
Ash = Astir*ns = 78.53982
No stirups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479
shv = 0.008
ftv = 666.66
fyv = 555.55
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.13698668$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13698668$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$f_{cc} (5A.2, TBDY) = 20.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.18236617$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.18236617$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.2046582$$

$$\mu_u = M R_c (4.14) = 1.0873E+008$$

$$u = s_u (4.1) = 0.00015595$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$\mu_u = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e (5.4c) = 0.0034192$$

$$a_{se} ((5.4d), TBDY) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} (5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} (5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.002$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_{b,min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.13698668$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.13698668$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.18236617$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.18236617$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture
' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.2046582

$M_u = M_{Rc}$ (4.14) = 1.0873E+008

$u = \mu_u$ (4.1) = 0.00015595

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u2} -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00015595$

$M_u = 1.0873E+008$

with full section properties:

$b = 400.00$

$d = 258.00$

$d' = 42.00$

$v = 0.00010855$

$N = 224.0403$

$f_c = 20.00$

α (5A.5, TBDY) = 0.002

Final value of μ_{cu} : $\mu_{cu}^* = \text{shear_factor} * \text{Max}(\mu_{cu}, \mu_{cc}) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_{cu} = 0.00583896$

μ_{we} (5.4c) = 0.0034192

μ_{ase} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$b_{i2} = 346400.00$

$\mu_{psh,min} = \text{Min}(\mu_{psh,x}, \mu_{psh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $\mu_{psh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $\mu_{psh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} * n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

 $\mu_{psh,y}$ (5.4d) = 0.00261799

$A_{sh} = A_{stir} * n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 400.00$

 $s = 150.00$

$f_{ywe} = 555.55$

$f_{ce} = 20.00$

From ((5A5), TBDY), TBDY: $\mu_{cc} = 0.002$

$c = \text{confinement factor} = 1.00$

$y_1 = 0.00231479$

$sh_1 = 0.008$

$ft_1 = 666.66$

$fy_1 = 555.55$

$\mu_{su1} = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 1.00$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s1} = f_s = 555.55$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$s_u2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_s/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = f_s = 555.55$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$s_{u,v} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 1.00$$

$$s_{u,v} = 0.4 * e_{s_{u,v}_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_{u,v}_nominal} = 0.08$,

considering characteristic value $f_{s_{u,v}} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u,v}_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $f_{s_{u,v}} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = f_s = 555.55$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.13698668$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.13698668$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$f_{cc} (5A.2, TBDY) = 20.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.18236617$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.18236617$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$$s_u (4.9) = 0.2046582$$

$$M_u = M_{Rc} (4.14) = 1.0873E+008$$

$$u = s_u (4.1) = 0.00015595$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 152466.975$

Calculation of Shear Strength at edge 1, $V_{r1} = 152466.975$
 $V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u \cdot d / M_u < 1 = 0.00$
 $M_u = 1.8491887E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 152466.975$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u \cdot d / M_u < 1 = 0.00$
 $M_u = 1.8491916E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1
At local axis: 2
Integration Section: (a)
Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/l_d > 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 5.3884E+006$

Shear Force, $V_2 = -3.4466031E-014$

Shear Force, $V_3 = -3205.681$

Axial Force, $F = -577.527$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 603.1858$

-Compression: $A_{sc} = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 603.1858$

-Compression: $A_{sc,com} = 615.7522$

-Middle: $A_{st,mid} = 307.8761$

Mean Diameter of Tension Reinforcement, $D_bL = 16.00$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = \phi \cdot u = 0.00790463$

$u = \gamma + \rho = 0.01053951$

- Calculation of γ -

$\gamma = (M_y \cdot L_s / 3) / E_{eff} = 0.00553951$ ((4.29), Biskinis Phd))

$M_y = 9.9749E+007$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1680.883

From table 10.5, ASCE 41_17: $E_{eff} = 0.3 \cdot E_c \cdot I_g = 1.0089E+013$

Calculation of Yielding Moment M_y

Calculation of γ and M_y according to Annex 7 -

$\gamma = \text{Min}(\gamma_{ten}, \gamma_{com})$

$\gamma_{ten} = 8.5937621E-006$

with $f_y = 444.44$

$d = 357.00$

$\gamma = 0.27567813$

$A = 0.0142681$

$B = 0.00792694$

with $p_t = 0.00563199$

$p_c = 0.00574932$

pv = 0.00287466
N = 577.527
b = 300.00
" = 0.11764706
y_comp = 1.7409301E-005
with fc = 20.00
Ec = 21019.039
y = 0.27557517
A = 0.01424022
B = 0.00791481
with Es = 200000.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of p -

From table 10-7: p = 0.005

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.77008272$

- Transverse Reinforcement: NC

- Stirrup Spacing > d/3

- Low ductility demand, $\lambda / y < 2$ (table 10-6, ASCE 41-17)

= 6.3712927E-005

- Stirrup Spacing <= d/2

d = 357.00

s = 150.00

- Strength provided by hoops $V_s < 3/4$ *design Shear

$V_s = 148933.273$, already given in calculation of shear control ratio

design Shear = 3205.681

- (- ')/ bal = -0.160191

= $A_{st}/(b_w*d) = 0.00563199$

Tension Reinf Area: $A_{st} = 603.1858$

' = $A_{sc}/(b_w*d) = 0.00862398$

Compression Reinf Area: $A_{sc} = 923.6282$

From (B-1), ACI 318-11: bal = 0.01867766

fc = 20.00

fy = 444.44

From 10.2.7.3, ACI 318-11: $\lambda = 0.85$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000+fy) = c_b/d_t = 0.003/(0.003+ y) = 0.57447053$

y = 0.0022222

- $V/(b_w*d*fc^{0.5}) = 0.08060074$, NOTE: units in lb & in

$b_w = 300.00$

End Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 3

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 5.3884E+006$

Shear Force, $V_a = -3205.681$

EDGE -B-

Bending Moment, $M_b = 5.6116E+006$

Shear Force, $V_b = 8686.209$

BOTH EDGES

Axial Force, $F = -577.527$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 603.1858$

-Compression: $As_c = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 603.1858$

-Compression: $As_{l,com} = 615.7522$

-Middle: $As_{l,mid} = 307.8761$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.00$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 148075.075$
 $V_n ((22.5.1.1), ACI 318-14) = 197433.433$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f_v V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 63392.147$

= 1 (normal-weight concrete)

$f_c' = 16.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$\rho_w = As/(b_w \cdot d) = 0.00628319$

As (tension reinf.) = 603.1858

$b_w = 300.00$

$d = 320.00$

$V_u \cdot d / M_u < 1 = 0.19037609$

$M_u = 5.3884E+006$

$V_u = 3205.681$

From (11.5.4.8), ACI 318-14: $V_s = 134041.287$

$A_v = 157079.633$

$f_y = 400.00$

$s = 150.00$

V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17, 10.3.4)

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 255092.67$

End Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 4

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_r)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
 Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
 Concrete Elasticity, $E_c = 21019.039$
 Steel Elasticity, $E_s = 200000.00$

 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

 Section Height, $H = 400.00$
 Section Width, $W = 300.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.00
 Element Length, $L = 1850.00$
 Secondary Member
 Smooth Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_o/l_{ou, \min} >= 1$)
 No FRP Wrapping

Stepwise Properties

At local axis: 3
 EDGE -A-
 Shear Force, $V_a = 2740.264$
 EDGE -B-
 Shear Force, $V_b = 2740.264$
 BOTH EDGES
 Axial Force, $F = -224.0403$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{slt} = 603.1858$
 -Compression: $A_{slc} = 923.6282$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{sl, \text{ten}} = 603.1858$
 -Compression: $A_{sl, \text{com}} = 615.7522$
 -Middle: $A_{sl, \text{mid}} = 307.8761$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.77008272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 175486.019$
with

$M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 1.5980E+008$

$M_{u1+} = 1.5719E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.5980E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 1.5978E+008$

$M_{u2+} = 1.5721E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 1.5978E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = 2740.264$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 2740.264$, is the shear force acting at edge 2 for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010691$

$M_u = 1.5719E+008$

with full section properties:

$b = 300.00$

$d = 357.00$

$d' = 42.00$

$v = 0.00010459$

$N = 224.0403$

$f_c = 20.00$

ϕ_c (5A.5, TBDY) = 0.002

Final value of ϕ_{cu} : $\phi_{cu}^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_c) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_{cu} = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$b_{i2} = 346400.00$

$\phi_{sh,min} = \text{Min}(\phi_{sh,x}, \phi_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $\phi_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $\phi_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

 $\phi_{sh,y}$ (5.4d) = 0.00261799

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 400.00$

 $s = 150.00$

$f_{ywe} = 555.55$

$f_{ce} = 20.00$

From ((5.A5), TBDY), TBDY: $\phi_c = 0.002$

c = confinement factor = 1.00

$y_1 = 0.00231479$

$sh_1 = 0.008$

$$ft1 = 666.66$$

$$fy1 = 555.55$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/d = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = fs = 555.55$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00231479$$

$$sh2 = 0.008$$

$$ft2 = 666.66$$

$$fy2 = 555.55$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = fs = 555.55$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/d = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.15644251$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.15970173$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.2134938$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.21794159$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.16156243$$

$$Mu = MRc (4.14) = 1.5719E+008$$

$$u = s_u(4.1) = 0.00010691$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010702$$

$$\mu = 1.5980E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, \text{TB DY}) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TB DY: } c_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}((5.4d), \text{TB DY}) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_i^2 = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TB DY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TB DY), TB DY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu_1_{nominal}((5.5), \text{TB DY}) = 0.032$$

From table 5A.1, TB DY: $esu_1_{nominal} = 0.08$,

For calculation of $esu_1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TB DY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = fs = 555.55$$

with $E_{s1} = E_s = 200000.00$
 $y_2 = 0.00231479$
 $sh_2 = 0.008$
 $ft_2 = 666.66$
 $fy_2 = 555.55$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/lb_{min} = 1.00$
 $su_2 = 0.4 * esu_{2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,
 For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = fs = 555.55$
 with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00231479$
 $sh_v = 0.008$
 $ft_v = 666.66$
 $fy_v = 555.55$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 1.00$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = fs = 555.55$
 with $E_{sv} = E_s = 200000.00$
 $1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.15925564$
 $2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.15600552$
 $v = Asl_{mid}/(b*d) * (fs_v/fc) = 0.07962782$
 and confined core properties:
 $b = 240.00$
 $d = 328.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.21727713$
 $2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.2128429$
 $v = Asl_{mid}/(b*d) * (fs_v/fc) = 0.10863856$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.1647931$
 $Mu = MRc (4.14) = 1.5980E+008$
 $u = su (4.1) = 0.00010702$

 Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

 Calculation of Mu_{2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010682$$

$$\mu = 1.5721E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 1.00$$

$$su_1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_{nominal} = 0.08,$$

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$$

$$su_2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_{nominal} = 0.08,$$

For calculation of $esu2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s2} = f_s = 555.55$

with $E_{s2} = E_s = 200000.00$

$y_v = 0.00231479$

$sh_v = 0.008$

$ft_v = 666.66$

$f_{yv} = 555.55$

$s_{uv} = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/d = 1.00$

$s_{uv} = 0.4 \cdot e_{suv,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, f_{yv} , it is considered

characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

1 = $Asl_{ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15600552$

2 = $Asl_{com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15925564$

v = $Asl_{mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.07962782$

and confined core properties:

b = 240.00

d = 328.00

d' = 13.00

f_{cc} (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = $Asl_{ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.2128429$

2 = $Asl_{com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.21727713$

v = $Asl_{mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.10863856$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < v_{s,c} - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.16319614

Mu = MRc (4.14) = 1.5721E+008

u = su (4.1) = 0.00010682

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu2-

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

u = 0.00010711

Mu = 1.5978E+008

with full section properties:

b = 300.00

d = 357.00

d' = 42.00

v = 0.00010459

N = 224.0403

f_c = 20.00

co (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$b_{i2} = 346400.00$

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} * n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

$p_{sh,y}$ (5.4d) = 0.00261799

$A_{sh} = A_{stir} * n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 400.00$

$s = 150.00$

$f_{ywe} = 555.55$

$f_{ce} = 20.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

$c = \text{confinement factor} = 1.00$

$y_1 = 0.00231479$

$sh_1 = 0.008$

$ft_1 = 666.66$

$fy_1 = 555.55$

$su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su_1 = 0.4 * esu_{1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = fs = 555.55$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00231479$

$sh_2 = 0.008$

$ft_2 = 666.66$

$fy_2 = 555.55$

$su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$

$su_2 = 0.4 * esu_{2,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = fs = 555.55$

with $Es_2 = Es = 200000.00$

$y_v = 0.00231479$

$sh_v = 0.008$

$ft_v = 666.66$

$fy_v = 555.55$

$su_v = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = fs = 555.55$

with $Esv = Es = 200000.00$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.15970173$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.15644251$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$c =$ confinement factor = 1.00

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.21794159$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.2134938$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < vs,c$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.16317177$$

$$Mu = MRc (4.14) = 1.5978E+008$$

$$u = su (4.1) = 0.00010711$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 227879.44$

Calculation of Shear Strength at edge 1, $Vr1 = 227879.44$

$Vr1 = Vn$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' Vw ' is replaced by ' $Vw + f * Vf$ ' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $Vc = 78946.167$

= 1 (normal-weight concrete)

$fc' = 20.00$, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$pw = As / (bw * d) = 0.00628319$$

$$As \text{ (tension reinf.)} = 603.1858$$

$$bw = 300.00$$

$$d = 320.00$$

$$Vu * d / Mu < 1 = 1.00$$

$$Mu = 6710.981$$

$$Vu = 2740.264$$

From (11.5.4.8), ACI 318-14: $Vs = 148933.273$

$$Av = 157079.633$$

$$fy = 444.44$$

$$s = 150.00$$

Vs has been multiplied by 1 ($s < d/2$, according to ASCE 41-17, 10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $Vs + Vf \leq 285202.276$

Calculation of Shear Strength at edge 2, $Vr2 = 227879.44$

$Vr2 = Vn$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
As (tension reinf.) = 603.1858
bw = 300.00
d = 320.00
 $V_u*d/M_u < 1 = 1.00$
Mu = 6710.981
Vu = 2740.264

From (11.5.4.8), ACI 318-14: $V_s = 148933.273$
Av = 157079.633
fy = 444.44
s = 150.00

Vs has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcars

Constant Properties

Knowledge Factor, = 0.75

Mean strength values are used for both shear and moment calculations.

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25*f_{sm} = 555.55$

#####

Section Height, H = 400.00

Section Width, W = 300.00

Cover Thickness, c = 25.00

Mean Confinement Factor overall section = 1.00

Element Length, L = 1850.00

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, Va = -8.7724203E-020

EDGE -B-

Shear Force, Vb = 8.7724203E-020

BOTH EDGES

Axial Force, $F = -224.0403$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 603.1858$

-Compression: $As_c = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{,ten} = 508.938$

-Compression: $As_{,com} = 508.938$

-Middle: $As_{,mid} = 508.938$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77093353$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 117541.903$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.0873E+008$

$Mu_{1+} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.0873E+008$

$Mu_{2+} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -8.7724203E-020$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 8.7724203E-020$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00015595$

$M_u = 1.0873E+008$

with full section properties:

$b = 400.00$

$d = 258.00$

$d' = 42.00$

$v = 0.00010855$

$N = 224.0403$

$f_c = 20.00$

ϕ_c (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$bi_2 = 346400.00$

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

psh,y (5.4d) = 0.00261799
Ash = Astir*ns = 78.53982
No stirups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00
From ((5.A.5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479
shv = 0.008
ftv = 666.66
fyv = 555.55
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

$$cc \text{ (5A.5, TBDY)} = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture
' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$su \text{ (4.9)} = 0.2046582$$

$$Mu = MRc \text{ (4.14)} = 1.0873E+008$$

$$u = su \text{ (4.1)} = 0.00015595$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$Mu = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$fc = 20.00$$

$$co \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00583896$$

$$we \text{ (5.4c)} = 0.0034192$$

$$ase \text{ ((5.4d), TBDY)} = 0.15672608$$

$$bo = 240.00$$

$$ho = 340.00$$

$$bi2 = 346400.00$$

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00261799$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x \text{ (5.4d)} = 0.00349066$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 300.00$$

$$psh,y \text{ (5.4d)} = 0.00261799$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 400.00$$

$$s = 150.00$$

$$fywe = 555.55$$

$$fce = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00231479$$

$$sh1 = 0.008$$

$$ft1 = 666.66$$

$f_{y1} = 555.55$
 $s_{u1} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 1.00$
 $s_{u1} = 0.4 * e_{su1,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,
 For calculation of $e_{su1,nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = f_s = 555.55$
 with $E_{s1} = E_s = 200000.00$
 $y_2 = 0.00231479$
 $sh_2 = 0.008$
 $ft_2 = 666.66$
 $f_{y2} = 555.55$
 $s_{u2} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$
 $s_{u2} = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,
 For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_2, sh_2, ft_2, f_{y2} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = f_s = 555.55$
 with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00231479$
 $sh_v = 0.008$
 $ft_v = 666.66$
 $f_{yv} = 555.55$
 $s_{uv} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 1.00$
 $s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,
 considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, f_{yv} , it is considered
 characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = f_s = 555.55$
 with $E_{sv} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.13698668$
 $2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.13698668$
 $v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.13698668$
 and confined core properties:
 $b = 340.00$
 $d = 228.00$
 $d' = 12.00$
 $f_{cc} (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.18236617$
 $2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.18236617$
 $v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.18236617$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.2046582$
 $M_u = M_{Rc} (4.14) = 1.0873E+008$
 $u = s_u (4.1) = 0.00015595$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$\mu = 0.00015595$
 $\mu = 1.0873E+008$

with full section properties:

$b = 400.00$
 $d = 258.00$
 $d' = 42.00$
 $v = 0.00010855$
 $N = 224.0403$
 $f_c = 20.00$
 $\rho (5A.5, \text{TB DY}) = 0.002$
Final value of μ : $\mu^* = \text{shear_factor} * \text{Max}(\mu, \rho) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TB DY: $\mu = 0.00583896$
 $\mu (5.4c) = 0.0034192$
 $\mu (5.4d), \text{TB DY} = 0.15672608$
 $b_o = 240.00$
 $h_o = 340.00$
 $b_i^2 = 346400.00$
 $\mu_{\text{sh,min}} = \text{Min}(\mu_{\text{sh,x}}, \mu_{\text{sh,y}}) = 0.00261799$

Expression ((5.4d), TB DY) for $\mu_{\text{sh,min}}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$\mu_{\text{sh,x}} (5.4d) = 0.00349066$
 $A_{\text{sh}} = A_{\text{stir}} * n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 300.00$

$\mu_{\text{sh,y}} (5.4d) = 0.00261799$
 $A_{\text{sh}} = A_{\text{stir}} * n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 400.00$

$s = 150.00$
 $f_{ywe} = 555.55$
 $f_{ce} = 20.00$
From ((5.A5), TB DY), TB DY: $\rho = 0.002$
 $c = \text{confinement factor} = 1.00$
 $y_1 = 0.00231479$
 $sh_1 = 0.008$
 $ft_1 = 666.66$
 $fy_1 = 555.55$
 $su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,\text{min}} = l_b/d = 1.00$
 $su_1 = 0.4 * \text{esu1_nominal} ((5.5), \text{TB DY}) = 0.032$

From table 5A.1, TB DY: $\text{esu1_nominal} = 0.08$,
For calculation of esu1_nominal and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TB DY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = fs = 555.55$
with $E_s = E_s = 200000.00$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{min} = lb/lb_{min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$su_v = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{min} = lb/ld = 1.00$$

$$su_v = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Es_v = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.13698668$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.13698668$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.18236617$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.18236617$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.2046582$$

$$Mu = MRc (4.14) = 1.0873E+008$$

$$u = su (4.1) = 0.00015595$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu_2 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 0.00015595
Mu = 1.0873E+008

with full section properties:

b = 400.00
d = 258.00
d' = 42.00
v = 0.00010855
N = 224.0403
fc = 20.00
co (5A.5, TBDY) = 0.002
Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $cu = 0.00583896$
we (5.4c) = 0.0034192
ase ((5.4d), TBDY) = 0.15672608
bo = 240.00
ho = 340.00
bi2 = 346400.00
psh,min = $\text{Min}(psh,x, psh,y) = 0.00261799$
Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066
Ash = $\text{Astir} * ns = 78.53982$
No stirrups, ns = 2.00
bk = 300.00

psh,y (5.4d) = 0.00261799
Ash = $\text{Astir} * ns = 78.53982$
No stirrups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00
From ((5.A5), TBDY), TBDY: $cc = 0.002$
c = confinement factor = 1.00
y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $lo/lou,min = lb/d = 1.00$
 $su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $esu1_nominal = 0.08$,
For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $fs1 = fs = 555.55$
with $Es1 = Es = 200000.00$

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $lo/lou,min = lb/lb,min = 1.00$
 $su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $esu2_nominal = 0.08$,
For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = fs = 555.55$

with $Es_2 = Es = 200000.00$

$y_v = 0.00231479$

$sh_v = 0.008$

$ft_v = 666.66$

$fy_v = 555.55$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lou, \min = lb/d = 1.00$

$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = fs = 555.55$

with $Es_v = Es = 200000.00$

1 = $Asl, \text{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.13698668$

2 = $Asl, \text{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.13698668$

v = $Asl, \text{mid} / (b \cdot d) \cdot (fsv / fc) = 0.13698668$

and confined core properties:

$b = 340.00$

$d = 228.00$

$d' = 12.00$

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = $Asl, \text{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.18236617$

2 = $Asl, \text{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.18236617$

v = $Asl, \text{mid} / (b \cdot d) \cdot (fsv / fc) = 0.18236617$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2046582

$Mu = MRc$ (4.14) = 1.0873E+008

$u = su$ (4.1) = 0.00015595

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 152466.975$

Calculation of Shear Strength at edge 1, $V_{r1} = 152466.975$

$V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$

= 1 (normal-weight concrete)

$fc' = 20.00$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$pw = As / (bw \cdot d) = 0.00628319$

As (tension reinf.) = 603.1858

$bw = 400.00$

$d = 240.00$

$V_u \cdot d / Mu < 1 = 0.00$

$Mu = 1.8491887E-012$

$$V_u = 8.7724203E-020$$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$

$$A_v = 157079.633$$

$$f_y = 444.44$$

$$s = 150.00$$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$$2(1-s/d) = 0.75$$

$$V_f ((11-3)-(11.4), ACI 440) = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 285202.276$$

Calculation of Shear Strength at edge 2, $V_{r2} = 152466.975$

$$V_{r2} = V_n ((22.5.1.1), ACI 318-14)$$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$

= 1 (normal-weight concrete)

$$f_c' = 20.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$p_w = A_s / (b_w \cdot d) = 0.00628319$$

$$A_s (\text{tension reinf.}) = 603.1858$$

$$b_w = 400.00$$

$$d = 240.00$$

$$V_u \cdot d / M_u < 1 = 0.00$$

$$M_u = 1.8491916E-012$$

$$V_u = 8.7724203E-020$$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$

$$A_v = 157079.633$$

$$f_y = 444.44$$

$$s = 150.00$$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$$2(1-s/d) = 0.75$$

$$V_f ((11-3)-(11.4), ACI 440) = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 285202.276$$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcars

Constant Properties

Knowledge Factor, = 0.75

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -4.6301801E-012$

Shear Force, $V2 = -3.4466031E-014$

Shear Force, $V3 = -3205.681$

Axial Force, $F = -577.527$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 603.1858$

-Compression: $As_c = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 508.938$

-Compression: $As_{c,com} = 508.938$

-Middle: $As_{c,mid} = 508.938$

Mean Diameter of Tension Reinforcement, $Db_L = 14.66667$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \alpha u = 0.00654577$
 $u = \gamma + \rho = 0.0087277$

- Calculation of γ -

$\gamma = (M_y * L_s / 3) / E_{eff} = 0.0037277$ ((4.29), Biskinis Phd))

$M_y = 6.8611E+007$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 925.00

From table 10.5, ASCE 41_17: $E_{eff} = 0.3 * E_c * I_g = 5.6751E+012$

Calculation of Yielding Moment M_y

Calculation of γ and M_y according to Annex 7 -

$\gamma = \text{Min}(\gamma_{ten}, \gamma_{com})$

$\gamma_{ten} = 1.2093827E-005$

with $f_y = 444.44$

$d = 258.00$

$\gamma = 0.28780375$

$A = 0.0148073$

$B = 0.00861417$

with $p_t = 0.00493157$

$p_c = 0.00493157$

$p_v = 0.00493157$

$N = 577.527$

$b = 400.00$

" = 0.1627907

$\gamma_{comp} = 2.3073660E-005$

with $f_c = 20.00$

$E_c = 21019.039$

$\gamma = 0.287709$

$A = 0.01477837$

$B = 0.00860158$

with $E_s = 200000.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ -

From table 10-7: $\rho = 0.005$

with:

- Condition i occurred
- Beam controlled by flexure: $V_p/V_o \leq 1$
- shear control ratio $V_p/V_o = 0.77093353$
- Transverse Reinforcement: NC
- Stirrup Spacing $> d/3$
- Low ductility demand, $\lambda / \gamma < 2$ (table 10-6, ASCE 41-17)
 $= -2.8762001E-022$
- Stirrup Spacing $> d/2$
 $d = 258.00$
 $s = 150.00$
- Strength provided by hoops $V_s < 3/4 \cdot \text{design Shear}$
 $V_s = 111699.955$, already given in calculation of shear control ratio
- design Shear = $3.4466031E-014$
- $(\lambda - \gamma) / \text{bal} = -0.16624473$
 $= A_{st}/(b_w \cdot d) = 0.00584482$
- Tension Reinf Area: $A_{st} = 603.1858$
- $\lambda = A_{sc}/(b_w \cdot d) = 0.00894989$
- Compression Reinf Area: $A_{sc} = 923.6282$
- From (B-1), ACI 318-11: $\text{bal} = 0.01867766$
- $f_c = 20.00$
- $f_y = 444.44$
- From 10.2.7.3, ACI 318-11: $\lambda = 0.85$
- From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + \lambda) = 0.57447053$
 $\gamma = 0.0022222$
- $V/(b_w \cdot d \cdot f_c^{0.5}) = 8.9933150E-019$, NOTE: units in lb & in
 $b_w = 400.00$

End Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 5

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -4.6301801E-012$

Shear Force, $V_a = -3.4466031E-014$

EDGE -B-

Bending Moment, $M_b = -5.9084780E-011$

Shear Force, $V_b = 3.4466031E-014$

BOTH EDGES

Axial Force, $F = -577.527$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,ten} = 615.7522$

-Compression: $A_{sl,com} = 911.0619$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 508.938$

-Compression: $A_{sl,com} = 508.938$

-Middle: $A_{sl,mid} = 508.938$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 14.66667$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $VR = *V_n = 102628.668$

$V_n ((22.5.1.1), ACI 318-14) = 136838.224$

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 61440.00$
= 1 (normal-weight concrete)
 $f'_c = 16.00$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00641409$
 A_s (tension reinf.) = 615.7522
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 5.9084780E-011$
 $V_u = 3.4466031E-014$

From (11.5.4.8), ACI 318-14: $V_s = 75398.224$
 $A_v = 157079.633$
 $f_y = 400.00$
 $s = 150.00$
 V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 255092.67$

End Of Calculation of Shear Capacity for element: beam B1 of floor 1
At local axis: 2
Integration Section: (b)

Calculation No. 6

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 3

(Bending local axis: 2)
Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Mean strength values are used for both shear and moment calculations.

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou}, \min > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = 2740.264$

EDGE -B-

Shear Force, $V_b = 2740.264$

BOTH EDGES

Axial Force, $F = -224.0403$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 603.1858$

-Compression: $A_{sl,c} = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 603.1858$

-Compression: $A_{sl,com} = 615.7522$

-Middle: $A_{sl,mid} = 307.8761$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77008272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 175486.019$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 1.5980E+008$

$M_{u1+} = 1.5719E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.5980E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 1.5978E+008$

$M_{u2+} = 1.5721E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 1.5978E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

V1 = 2740.264, is the shear force acting at edge 1 for the the static loading combination

V2 = 2740.264, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu1+

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$\mu = 0.00010691$

$Mu = 1.5719E+008$

with full section properties:

$b = 300.00$

$d = 357.00$

$d' = 42.00$

$v = 0.00010459$

$N = 224.0403$

$f_c = 20.00$

μ_c (5A.5, TBDY) = 0.002

Final value of μ_c : $\mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_c) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_c = 0.00583896$

μ_w (5.4c) = 0.0034192

μ_{ase} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$b_{i2} = 346400.00$

$\mu_{psh,min} = \text{Min}(\mu_{psh,x}, \mu_{psh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $\mu_{psh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $\mu_{psh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} * n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

$\mu_{psh,y}$ (5.4d) = 0.00261799

$A_{sh} = A_{stir} * n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 400.00$

$s = 150.00$

$f_{ywe} = 555.55$

$f_{ce} = 20.00$

From ((5.A5), TBDY), TBDY: $\mu_{cc} = 0.002$

$c = \text{confinement factor} = 1.00$

$\mu_{y1} = 0.00231479$

$sh_1 = 0.008$

$ft_1 = 666.66$

$fy_1 = 555.55$

$su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$\mu_{su1} = 0.4 * \mu_{su1_nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $\mu_{su1_nominal} = 0.08$,

For calculation of $\mu_{su1_nominal}$ and $\mu_{y1}, sh_1, ft_1, fy_1$, it is considered characteristic value $\mu_{fsy1} = fs_1/1.2$, from table 5.1, TBDY.

$\mu_{y1}, sh_1, ft_1, fy_1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = fs = 555.55$

with $Es_1 = Es = 200000.00$

$\mu_{y2} = 0.00231479$

$sh_2 = 0.008$

$ft_2 = 666.66$

$$f_y2 = 555.55$$

$$s_u2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,

For calculation of $e_{su2,nominal}$ and y_2 , sh_2, ft_2, f_y2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, f_y1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = f_s = 555.55$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$f_{y_v} = 555.55$$

$$s_{u_v} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_d = 1.00$$

$$s_{u_v} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and y_v , sh_v, ft_v, f_{y_v} , it is considered
characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = f_s = 555.55$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.15644251$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.15970173$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$f_{cc} (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.2134938$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.21794159$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.16156243$$

$$M_u = M_{Rc} (4.14) = 1.5719E+008$$

$$u = s_u (4.1) = 0.00010691$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u1} -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010702$$

$$M_u = 1.5980E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_i^2 = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_{nominal} = 0.08,$$

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$$

$$su_2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_{nominal} = 0.08,$$

For calculation of $esu2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$su_v = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 1.00$$

$$su_v = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fs_y = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fs_y = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = fs = 555.55$

with $Esv = Es = 200000.00$

$$1 = A_{sl,ten}/(b*d) * (fs_1/fc) = 0.15925564$$

$$2 = A_{sl,com}/(b*d) * (fs_2/fc) = 0.15600552$$

$$v = A_{sl,mid}/(b*d) * (fsv/fc) = 0.07962782$$

and confined core properties:

$$b = 240.00$$

$$d = 328.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$c =$ confinement factor = 1.00

$$1 = A_{sl,ten}/(b*d) * (fs_1/fc) = 0.21727713$$

$$2 = A_{sl,com}/(b*d) * (fs_2/fc) = 0.2128429$$

$$v = A_{sl,mid}/(b*d) * (fsv/fc) = 0.10863856$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.1647931$$

$$Mu = MRc (4.14) = 1.5980E+008$$

$$u = su (4.1) = 0.00010702$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010682$$

$$Mu = 1.5721E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$fc = 20.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, co) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

$$we (5.4c) = 0.0034192$$

$$ase ((5.4d), TBDY) = 0.15672608$$

bo = 240.00
ho = 340.00
bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066
Ash = Astir*ns = 78.53982
No stirrups, ns = 2.00
bk = 300.00

psh,y (5.4d) = 0.00261799
Ash = Astir*ns = 78.53982
No stirrups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

1 = $A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15600552$

2 = $A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15925564$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.07962782$

and confined core properties:

$b = 240.00$

$d = 328.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = $A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.2128429$

2 = $A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.21727713$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.10863856$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.16319614

$M_u = M_{Rc}$ (4.14) = 1.5721E+008

$u = \mu_u$ (4.1) = 0.00010682

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_u

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010711$

$M_u = 1.5978E+008$

with full section properties:

$b = 300.00$

$d = 357.00$

$d' = 42.00$

$v = 0.00010459$

$N = 224.0403$

$f_c = 20.00$

cc (5A.5, TBDY) = 0.002

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$b_{i2} = 346400.00$

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

 $p_{sh,y}$ (5.4d) = 0.00261799

$$\text{Ash} = \text{Astir} * \text{ns} = 78.53982$$

$$\text{No stirups, ns} = 2.00$$

$$\text{bk} = 400.00$$

$$s = 150.00$$

$$\text{fywe} = 555.55$$

$$\text{fce} = 20.00$$

$$\text{From ((5.A.5), TBDY), TBDY: cc} = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00231479$$

$$\text{sh1} = 0.008$$

$$\text{ft1} = 666.66$$

$$\text{fy1} = 555.55$$

$$\text{su1} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/lb} = 1.00$$

$$\text{su1} = 0.4 * \text{esu1_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with fs1} = \text{fs} = 555.55$$

$$\text{with Es1} = \text{Es} = 200000.00$$

$$y2 = 0.00231479$$

$$\text{sh2} = 0.008$$

$$\text{ft2} = 666.66$$

$$\text{fy2} = 555.55$$

$$\text{su2} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb}/\text{lb,min} = 1.00$$

$$\text{su2} = 0.4 * \text{esu2_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with fs2} = \text{fs} = 555.55$$

$$\text{with Es2} = \text{Es} = 200000.00$$

$$yv = 0.00231479$$

$$\text{shv} = 0.008$$

$$\text{ftv} = 666.66$$

$$\text{fyv} = 555.55$$

$$\text{svv} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb}/\text{ld} = 1.00$$

$$\text{svv} = 0.4 * \text{esuv_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with fsv} = \text{fs} = 555.55$$

$$\text{with Esv} = \text{Es} = 200000.00$$

$$1 = \text{Asl,ten}/(\text{b} * \text{d}) * (\text{fs1}/\text{fc}) = 0.15970173$$

$$2 = \text{Asl,com}/(\text{b} * \text{d}) * (\text{fs2}/\text{fc}) = 0.15644251$$

$$v = \text{Asl,mid}/(\text{b} * \text{d}) * (\text{fsv}/\text{fc}) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$\text{fcc (5A.2, TBDY)} = 20.00$$

$$\text{cc (5A.5, TBDY)} = 0.002$$

c = confinement factor = 1.00

1 = $As_{l,ten}/(b*d)*(fs1/fc) = 0.21794159$

2 = $As_{l,com}/(b*d)*(fs2/fc) = 0.2134938$

v = $As_{l,mid}/(b*d)*(fsv/fc) = 0.10897079$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

v < $v_{s,c}$ - RHS eq.(4.5) is satisfied

su (4.9) = 0.16317177

Mu = MRc (4.14) = 1.5978E+008

u = su (4.1) = 0.00010711

Calculation of ratio lb/l_d

Adequate Lap Length: lb/l_d >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 227879.44

Calculation of Shear Strength at edge 1, Vr1 = 227879.44

Vr1 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 78946.167

= 1 (normal-weight concrete)

fc' = 20.00, but $fc'^{0.5} <= 8.3$ MPa (22.5.3.1, ACI 318-14)

pw = $As/(bw*d) = 0.00628319$

As (tension reinf.) = 603.1858

bw = 300.00

d = 320.00

$Vu*d/Mu < 1 = 1.00$

Mu = 6710.981

Vu = 2740.264

From (11.5.4.8), ACI 318-14: Vs = 148933.273

Av = 157079.633

fy = 444.44

s = 150.00

Vs has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $Vs + Vf <= 285202.276$

Calculation of Shear Strength at edge 2, Vr2 = 227879.44

Vr2 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 78946.167

= 1 (normal-weight concrete)

fc' = 20.00, but $fc'^{0.5} <= 8.3$ MPa (22.5.3.1, ACI 318-14)

pw = $As/(bw*d) = 0.00628319$

As (tension reinf.) = 603.1858

bw = 300.00

d = 320.00

$Vu*d/Mu < 1 = 1.00$

Mu = 6710.981

Vu = 2740.264

From (11.5.4.8), ACI 318-14: Vs = 148933.273

Av = 157079.633

fy = 444.44

s = 150.00

Vs has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$
Mean strength values are used for both shear and moment calculations.
Consequently:
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.55$

Section Height, $H = 400.00$
Section Width, $W = 300.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.00
Element Length, $L = 1850.00$
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -8.7724203E-020$
EDGE -B-
Shear Force, $V_b = 8.7724203E-020$
BOTH EDGES
Axial Force, $F = -224.0403$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 603.1858$
-Compression: $A_{sc} = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st, ten} = 508.938$
-Compression: $A_{sc, com} = 508.938$
-Middle: $A_{sc, mid} = 508.938$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.77093353$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u * l_n / 2 = 117541.903$
with

$$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 1.0873E+008$$

$M_{u1+} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 1.0873E+008$$

$M_{u2+} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination

$M_{u2-} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination

and

$$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$$

with

$V_1 = -8.7724203E-020$, is the shear force acting at edge 1 for the static loading combination

$V_2 = 8.7724203E-020$, is the shear force acting at edge 2 for the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$M_u = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$\omega (5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.00583896$$

$$\omega_e (5.4c) = 0.0034192$$

$$a_{se} ((5.4d), \text{TBDY}) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$\phi_{psh,min} = \text{Min}(\phi_{psh,x}, \phi_{psh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $\phi_{psh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$\phi_{psh,x} (5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$\phi_{psh,y} (5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_{cc} = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$f_{t1} = 666.66$$

$$f_{y1} = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617

2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617

v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

v < vs,c - RHS eq.(4.5) is satisfied

su (4.9) = 0.2046582

Mu = MRc (4.14) = 1.0873E+008

u = su (4.1) = 0.00015595

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$\mu = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1,nominal} = 0.08,$$

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_v = fs = 555.55$$

$$\text{with } Es_v = Es = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (fs_1/f_c) = 0.13698668$$

$$2 = A_{sl,com}/(b*d) * (fs_2/f_c) = 0.13698668$$

$$v = A_{sl,mid}/(b*d) * (fs_v/f_c) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d) * (fs_1/f_c) = 0.18236617$$

$$2 = A_{sl,com}/(b*d) * (fs_2/f_c) = 0.18236617$$

$$v = A_{sl,mid}/(b*d) * (fs_v/f_c) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.2046582$$

$$\mu_u = MR_c (4.14) = 1.0873E+008$$

$$u = su (4.1) = 0.00015595$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$\mu_u = 1.0873E+008$$

with full section properties:

b = 400.00

d = 258.00

d' = 42.00

v = 0.00010855

N = 224.0403

fc = 20.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

we (5.4c) = 0.0034192

ase ((5.4d), TBDY) = 0.15672608

bo = 240.00

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: $cc = 0.002$

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = $0.4 * \text{esu1_nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $\text{esu1_nominal} = 0.08$,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value $\text{fsy1} = \text{fs1}/1.2$, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with $\text{fs1} = \text{fs} = 555.55$

with $\text{Es1} = \text{Es} = 200000.00$

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = $0.4 * \text{esu2_nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $\text{esu2_nominal} = 0.08$,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value $\text{fsy2} = \text{fs2}/1.2$, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with $\text{fs2} = \text{fs} = 555.55$

with $\text{Es2} = \text{Es} = 200000.00$

yv = 0.00231479

$shv = 0.008$
 $ftv = 666.66$
 $fyv = 555.55$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 1.00$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = fs = 555.55$
 with $Esv = Es = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668$
 and confined core properties:
 $b = 340.00$
 $d = 228.00$
 $d' = 12.00$
 $fcc (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < vs,c$ - RHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.2046582$
 $Mu = MRc (4.14) = 1.0873E+008$
 $u = su (4.1) = 0.00015595$

 Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

 Calculation of $Mu2$ -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00015595$
 $Mu = 1.0873E+008$

 with full section properties:

$b = 400.00$
 $d = 258.00$
 $d' = 42.00$
 $v = 0.00010855$
 $N = 224.0403$
 $fc = 20.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00583896$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00583896$
 $we (5.4c) = 0.0034192$
 $ase ((5.4d), TBDY) = 0.15672608$
 $bo = 240.00$

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y2, sh2,ft2,fy2, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.13698668$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.13698668$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.13698668$

and confined core properties:

$b = 340.00$

$d = 228.00$

$d' = 12.00$

$f_{cc} \text{ (5A.2, TBDY)} = 20.00$

$cc \text{ (5A.5, TBDY)} = 0.002$

$c = \text{confinement factor} = 1.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.18236617$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.18236617$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.18236617$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$su \text{ (4.9)} = 0.2046582$

$\mu_u = MR_c \text{ (4.14)} = 1.0873E+008$

$u = su \text{ (4.1)} = 0.00015595$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 152466.975$

Calculation of Shear Strength at edge 1, $V_{r1} = 152466.975$

$V_{r1} = V_n \text{ ((22.5.1.1), ACI 318-14)}$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$

= 1 (normal-weight concrete)

$f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3 \text{ MPa}$ (22.5.3.1, ACI 318-14)

$\rho_w = A_s/(b_w \cdot d) = 0.00628319$

$A_s \text{ (tension reinf.)} = 603.1858$

$b_w = 400.00$

$d = 240.00$

$V_u \cdot d / \mu_u < 1 = 0.00$

$\mu_u = 1.8491887E-012$

$V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$

$A_v = 157079.633$

$f_y = 444.44$

$s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17, 10.3.4)

$2(1-s/d) = 0.75$

$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 152466.975$

$V_{r2} = V_n \text{ ((22.5.1.1), ACI 318-14)}$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$

= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/\mu_u < 1 = 0.00$
 $\mu_u = 1.8491916E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$
 V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1
At local axis: 2
Integration Section: (b)
Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$
Section Height, $H = 400.00$
Section Width, $W = 300.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 1850.00$
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/l_d > 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 5.6116E+006$
Shear Force, $V_2 = 3.4466031E-014$
Shear Force, $V_3 = 8686.209$
Axial Force, $F = -577.527$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{s,t} = 615.7522$
-Compression: $A_{s,c} = 911.0619$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{s,ten} = 615.7522$
-Compression: $A_{s,com} = 603.1858$
-Middle: $A_{s,mid} = 307.8761$
Mean Diameter of Tension Reinforcement, $D_bL = 14.00$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_R = \phi u = 0.00537844$
 $u = y + p = 0.00717126$

- Calculation of y -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.00217126$ ((4.29), Biskinis Phd)
 $M_y = 1.0173E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 646.037
From table 10.5, ASCE 41_17: $E_{eff} = 0.3 \cdot E_c \cdot I_g = 1.0089E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 8.5997478E-006$
with $f_y = 444.44$
 $d = 358.00$
 $y = 0.27820412$
 $A = 0.01422824$
 $B = 0.00802541$
with $p_t = 0.00573326$
 $p_c = 0.00561626$
 $p_v = 0.00286663$
 $N = 577.527$
 $b = 300.00$
 $\rho = 0.12011173$
 $y_{comp} = 1.7202834E-005$
with $f_c = 20.00$
 $E_c = 21019.039$
 $y = 0.2781036$
 $A = 0.01420045$
 $B = 0.00801331$
with $E_s = 200000.00$

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

- Calculation of p -

From table 10-7: $p = 0.005$
with:
- Condition i occurred
Beam controlled by flexure: $V_p/V_o \leq 1$
shear control ratio $V_p/V_o = 0.77008272$
- Transverse Reinforcement: NC
- Stirrup Spacing $> d/3$
- Low ductility demand, $\rho / y < 2$ (table 10-6, ASCE 41-17)
 $\rho = 2.4995476E-005$
- Stirrup Spacing $\leq d/2$
 $d = 358.00$
 $s = 150.00$
- Strength provided by hoops $V_s < 3/4 \cdot \text{design Shear}$
 $V_s = 148933.273$, already given in calculation of shear control ratio
design Shear = 8686.209
- $(\rho - \rho') / \rho_{bal} = -0.14721463$
 $\rho = A_{st} / (b_w \cdot d) = 0.00573326$
Tension Reinf Area: $A_{st} = 615.7522$

$$\rho = A_{sc}/(b_w*d) = 0.00848289$$

Compression Reinf Area: $A_{sc} = 911.0619$

From (B-1), ACI 318-11: $\rho_{bal} = 0.01867766$

$f_c = 20.00$

$f_y = 444.44$

From 10.2.7.3, ACI 318-11: $\beta_1 = 0.85$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000+f_y) = c_b/d_t = 0.003/(0.003+ y) = 0.57447053$

$$y = 0.0022222$$

$- V/(b_w*d*f_c^{0.5}) = 0.21778815$, NOTE: units in lb & in

$b_w = 300.00$

End Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 7

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$
Section Height, $H = 400.00$
Section Width, $W = 300.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 1850.00$
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = 5.3884E+006$
Shear Force, $V_a = -3205.681$
EDGE -B-
Bending Moment, $M_b = 5.6116E+006$
Shear Force, $V_b = 8686.209$
BOTH EDGES
Axial Force, $F = -577.527$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 615.7522$
-Compression: $A_{sl,c} = 911.0619$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 615.7522$
-Compression: $A_{sl,com} = 603.1858$
-Middle: $A_{sl,mid} = 307.8761$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 14.00$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 150499.703$
 V_n ((22.5.1.1), ACI 318-14) = 200666.271

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + \phi V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 66624.984$
= 1 (normal-weight concrete)
 $f_c' = 16.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00641409$
 A_s (tension reinf.) = 615.7522
 $b_w = 300.00$
 $d = 320.00$
 $V_u*d/M_u < 1 = 0.49532763$
 $M_u = 5.6116E+006$
 $V_u = 8686.209$
From (11.5.4.8), ACI 318-14: $V_s = 134041.287$
 $A_v = 157079.633$
 $f_y = 400.00$
 $s = 150.00$
 V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 255092.67$

End Of Calculation of Shear Capacity for element: beam B1 of floor 1
At local axis: 3
Integration Section: (b)

Calculation No. 8

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Mean strength values are used for both shear and moment calculations.

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou}, \min \geq 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = 2740.264$
EDGE -B-
Shear Force, $V_b = 2740.264$
BOTH EDGES
Axial Force, $F = -224.0403$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 603.1858$
-Compression: $As_c = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 603.1858$
-Compression: $As_{c,com} = 615.7522$
-Middle: $As_{c,mid} = 307.8761$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.77008272$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 175486.019$
with
 $M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 1.5980E+008$
 $\mu_{1+} = 1.5719E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{1-} = 1.5980E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 1.5978E+008$
 $\mu_{2+} = 1.5721E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $\mu_{2-} = 1.5978E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = 2740.264$, is the shear force acting at edge 1 for the the static loading combination
 $V_2 = 2740.264$, is the shear force acting at edge 2 for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:
 $\mu = 0.00010691$
 $\mu_u = 1.5719E+008$

with full section properties:

$b = 300.00$
 $d = 357.00$
 $d' = 42.00$
 $v = 0.00010459$
 $N = 224.0403$
 $f_c = 20.00$
 $\omega (5A.5, \text{TBDY}) = 0.002$
Final value of μ_c : $\mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \omega_c) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\mu_c = 0.00583896$
 $\omega_e (5.4c) = 0.0034192$
 $\omega_{se} ((5.4d), \text{TBDY}) = 0.15672608$
 $b_o = 240.00$

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y2, sh2,ft2,fy2, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15644251$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15970173$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.07985087$

and confined core properties:

$b = 240.00$

$d = 327.00$

$d' = 12.00$

$f_{cc} \text{ (5A.2, TBDY)} = 20.00$

$cc \text{ (5A.5, TBDY)} = 0.002$

$c = \text{confinement factor} = 1.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.2134938$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.21794159$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.10897079$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$su \text{ (4.9)} = 0.16156243$

$Mu = MR_c \text{ (4.14)} = 1.5719E+008$

$u = su \text{ (4.1)} = 0.00010691$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010702$

$Mu = 1.5980E+008$

with full section properties:

$b = 300.00$

$d = 358.00$

$d' = 43.00$

$v = 0.0001043$

$N = 224.0403$

$f_c = 20.00$

$co \text{ (5A.5, TBDY)} = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

$w_e \text{ (5.4c)} = 0.0034192$

$ase \text{ ((5.4d), TBDY)} = 0.15672608$

$bo = 240.00$

$ho = 340.00$

$bi_2 = 346400.00$

$psh_{,min} = \text{Min}(psh_x, psh_y) = 0.00261799$

Expression ((5.4d), TBDY) for $psh_{,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $psh_x \text{ (5.4d)} = 0.00349066$

$A_{sh} = A_{stir} \cdot ns = 78.53982$

No stirrups, $ns = 2.00$

$bk = 300.00$

 $psh_y \text{ (5.4d)} = 0.00261799$

$A_{sh} = A_{stir} \cdot ns = 78.53982$

No stirrups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00

From ((5.A.5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479
shv = 0.008
ftv = 666.66
fyv = 555.55
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15925564

2 = Asl,com/(b*d)*(fs2/fc) = 0.15600552

v = Asl,mid/(b*d)*(fsv/fc) = 0.07962782

and confined core properties:

b = 240.00
d = 328.00
d' = 13.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.21727713$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.2128429$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10863856$$

Case/Assumption: Unconfined full section - Steel rupture
' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$s_u(4.9) = 0.1647931$$

$$M_u = M_{Rc}(4.14) = 1.5980E+008$$

$$u = s_u(4.1) = 0.00010702$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010682$$

$$M_u = 1.5721E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}((5.4d), TBDY) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$f_{t1} = 666.66$$

$$f_{y1} = 555.55$$

$$s_{u1} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15600552

2 = Asl,com/(b*d)*(fs2/fc) = 0.15925564

v = Asl,mid/(b*d)*(fsv/fc) = 0.07962782

and confined core properties:

b = 240.00

d = 328.00

d' = 13.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.2128429

2 = Asl,com/(b*d)*(fs2/fc) = 0.21727713

v = Asl,mid/(b*d)*(fsv/fc) = 0.10863856

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.16319614

Mu = MRc (4.14) = 1.5721E+008

u = su (4.1) = 0.00010682

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 0.00010711$$

$$\mu = 1.5978E+008$$

with full section properties:

$$b = 300.00$$

$$d = 357.00$$

$$d' = 42.00$$

$$v = 0.00010459$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1,nominal} = 0.08,$$

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft2 = 666.66$$

$$fy2 = 555.55$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = fs = 555.55$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.15970173$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.15644251$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.21794159$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.2134938$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < vs,c$ - RHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.16317177$$

$$Mu = MRc (4.14) = 1.5978E+008$$

$$u = su (4.1) = 0.00010711$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 227879.44$

Calculation of Shear Strength at edge 1, $Vr1 = 227879.44$

$$Vr1 = Vn ((22.5.1.1), ACI 318-14)$$

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'

where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 300.00$
 $d = 320.00$
 $V_u*d/\mu_u < 1 = 1.00$
 $\mu_u = 6710.981$
 $V_u = 2740.264$

From (11.5.4.8), ACI 318-14: $V_s = 148933.273$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 227879.44$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f*V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 300.00$
 $d = 320.00$
 $V_u*d/\mu_u < 1 = 1.00$
 $\mu_u = 6710.981$
 $V_u = 2740.264$

From (11.5.4.8), ACI 318-14: $V_s = 148933.273$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$
Mean strength values are used for both shear and moment calculations.
Consequently:
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} >= 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -8.7724203E-020$

EDGE -B-

Shear Force, $V_b = 8.7724203E-020$

BOTH EDGES

Axial Force, $F = -224.0403$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 603.1858$

-Compression: $A_{sc} = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st, \text{ten}} = 508.938$

-Compression: $A_{sl, \text{com}} = 508.938$

-Middle: $A_{sl, \text{mid}} = 508.938$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77093353$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 117541.903$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 1.0873E+008$

$M_{u1+} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 1.0873E+008$

$M_{u2+} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -8.7724203E-020$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 8.7724203E-020$, is the shear force acting at edge 2 for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00015595$

$M_u = 1.0873E+008$

with full section properties:

$b = 400.00$

d = 258.00

d' = 42.00

v = 0.00010855

N = 224.0403

fc = 20.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

we (5.4c) = 0.0034192

ase ((5.4d), TBDY) = 0.15672608

bo = 240.00

ho = 340.00

bi2 = 346400.00

psh,min = $\text{Min}(psh,x, psh,y) = 0.00261799$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = $\text{Astir} * ns = 78.53982$

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = $\text{Astir} * ns = 78.53982$

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: $cc = 0.002$

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = $0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and y1, sh1,ft1,fy1, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = fs = 555.55$

with $Es1 = Es = 200000.00$

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = $0.4 * esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and y2, sh2,ft2,fy2, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = fs = 555.55$

with $Es2 = Es = 200000.00$

yv = 0.00231479

shv = 0.008

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv , shv , ftv , fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1$, $sh1$, $ft1$, $fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d)*(fs1/fc) = 0.13698668$$

$$2 = Asl_{com}/(b*d)*(fs2/fc) = 0.13698668$$

$$v = Asl_{mid}/(b*d)*(fsv/fc) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl_{ten}/(b*d)*(fs1/fc) = 0.18236617$$

$$2 = Asl_{com}/(b*d)*(fs2/fc) = 0.18236617$$

$$v = Asl_{mid}/(b*d)*(fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$$su (4.9) = 0.2046582$$

$$Mu = MRc (4.14) = 1.0873E+008$$

$$u = su (4.1) = 0.00015595$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$Mu = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$fc = 20.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00583896$$

$$we (5.4c) = 0.0034192$$

$$ase ((5.4d), TBDY) = 0.15672608$$

$$bo = 240.00$$

$$ho = 340.00$$

$$bi2 = 346400.00$$

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00261799$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x (5.4d) = 0.00349066$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 300.00$$

$$psh,y (5.4d) = 0.00261799$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 400.00$$

$$s = 150.00$$

$$fywe = 555.55$$

$$fce = 20.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00231479$$

$$sh1 = 0.008$$

$$ft1 = 666.66$$

$$fy1 = 555.55$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_d = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = fs = 555.55$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00231479$$

$$sh2 = 0.008$$

$$ft2 = 666.66$$

$$fy2 = 555.55$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_b,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = fs = 555.55$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_d = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$
with $E_{sv} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.13698668$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13698668$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.13698668$

and confined core properties:

$b = 340.00$
 $d = 228.00$
 $d' = 12.00$
 $f_{cc} (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.18236617$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.18236617$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.18236617$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$\mu_u (4.9) = 0.2046582$
 $\mu_u = M_{Rc} (4.14) = 1.0873E+008$
 $u = \mu_u (4.1) = 0.00015595$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00015595$
 $\mu_u = 1.0873E+008$

with full section properties:

$b = 400.00$
 $d = 258.00$
 $d' = 42.00$
 $v = 0.00010855$
 $N = 224.0403$
 $f_c = 20.00$
 $cc (5A.5, TBDY) = 0.002$
Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, cc) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $c_u = 0.00583896$
 $w_e (5.4c) = 0.0034192$
 $a_{se} ((5.4d), TBDY) = 0.15672608$
 $b_o = 240.00$
 $h_o = 340.00$
 $b_{i2} = 346400.00$
 $p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} (5.4d) = 0.00349066$
 $A_{sh} = A_{stir}*n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 300.00$

 $p_{sh,y} (5.4d) = 0.00261799$
 $A_{sh} = A_{stir}*n_s = 78.53982$
No stirrups, $n_s = 2.00$

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A.5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.18236617$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$s_u(4.9) = 0.2046582$$

$$M_u = M_{Rc}(4.14) = 1.0873E+008$$

$$u = s_u(4.1) = 0.00015595$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u2} -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$M_u = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}((5.4d), TBDY) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$f_{t1} = 666.66$$

$$f_{y1} = 555.55$$

$$s_{u1} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617

2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617

v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

v < vs,c - RHS eq.(4.5) is satisfied

su (4.9) = 0.2046582

Mu = MRc (4.14) = 1.0873E+008

u = su (4.1) = 0.00015595

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 152466.975$

Calculation of Shear Strength at edge 1, $V_{r1} = 152466.975$
 $V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw + f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 1.8491887E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 152466.975$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw + f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 1.8491916E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1
At local axis: 3
Integration Section: (b)

Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -5.9084780E-011$

Shear Force, $V_2 = 3.4466031E-014$

Shear Force, $V_3 = 8686.209$

Axial Force, $F = -577.527$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 615.7522$

-Compression: $A_{sc} = 911.0619$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 508.938$

-Compression: $A_{st,com} = 508.938$

-Middle: $A_{st,mid} = 508.938$

Mean Diameter of Tension Reinforcement, $D_bL = 14.66667$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = \phi \cdot u = 0.00654577$

$u = y + p = 0.0087277$

- Calculation of y -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.0037277$ ((4.29), Biskinis Phd)

$M_y = 6.8611E+007$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 925.00

From table 10.5, ASCE 41_17: $E_{eff} = 0.3 \cdot E_c \cdot I_g = 5.6751E+012$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 1.2093827E-005$

with $f_y = 444.44$

$d = 258.00$

$y = 0.28780375$

$A = 0.0148073$

$B = 0.00861417$

with $p_t = 0.00493157$
 $p_c = 0.00493157$
 $p_v = 0.00493157$
 $N = 577.527$
 $b = 400.00$
 $" = 0.1627907$
 $y_{comp} = 2.3073660E-005$
with $f_c = 20.00$
 $E_c = 21019.039$
 $y = 0.287709$
 $A = 0.01477837$
 $B = 0.00860158$
with $E_s = 200000.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of p -

From table 10-7: $p = 0.005$

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.77093353$

- Transverse Reinforcement: NC

- Stirrup Spacing $> d/3$

- Low ductility demand, $\lambda < 2$ (table 10-6, ASCE 41-17)

$= -8.8463222E-022$

- Stirrup Spacing $> d/2$

$d = 258.00$

$s = 150.00$

- Strength provided by hoops $V_s < 3/4$ *design Shear

$V_s = 111699.955$, already given in calculation of shear control ratio

design Shear = $3.4466031E-014$

- ($\lambda - 1$)/ λ bal = -0.15320593

$= A_{st}/(b_w*d) = 0.00596659$

Tension Reinf Area: $A_{st} = 615.7522$

$\lambda = A_{sc}/(b_w*d) = 0.00882812$

Compression Reinf Area: $A_{sc} = 911.0619$

From (B-1), ACI 318-11: λ bal = 0.01867766

$f_c = 20.00$

$f_y = 444.44$

From 10.2.7.3, ACI 318-11: λ = 0.85

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000+f_y) = c_b/d_t = 0.003/(0.003+ y) = 0.57447053$

$y = 0.0022222$

- $V/(b_w*d*f_c^{0.5}) = 8.9933150E-019$, NOTE: units in lb & in

$b_w = 400.00$

End Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 9

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -8.0944479E-012$

Shear Force, $V_a = -5.2893637E-014$
EDGE -B-
Bending Moment, $M_b = -8.9686435E-011$
Shear Force, $V_b = 5.2893637E-014$
BOTH EDGES
Axial Force, $F = -766.5227$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 603.1858$
-Compression: $A_{sc} = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 508.938$
-Compression: $A_{sc,com} = 508.938$
-Middle: $A_{st,mid} = 508.938$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 14.66667$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 102628.668$
 V_n ((22.5.1.1), ACI 318-14) = 136838.224

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + \phi V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 61440.00$
= 1 (normal-weight concrete)
 $f_c' = 16.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u \cdot d / M_u < 1 = 0.00$
 $M_u = 8.0944479E-012$
 $V_u = 5.2893637E-014$

From (11.5.4.8), ACI 318-14: $V_s = 75398.224$
 $A_v = 157079.633$
 $f_y = 400.00$
 $s = 150.00$
 V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17, 10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 255092.67$

End Of Calculation of Shear Capacity for element: beam B1 of floor 1
At local axis: 2
Integration Section: (a)

Calculation No. 10

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Mean strength values are used for both shear and moment calculations.

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, min} \geq 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = 2740.264$

EDGE -B-

Shear Force, $V_b = 2740.264$
BOTH EDGES
Axial Force, $F = -224.0403$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 603.1858$
-Compression: $As_c = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{ten} = 603.1858$
-Compression: $As_{com} = 615.7522$
-Middle: $As_{mid} = 307.8761$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77008272$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 175486.019$
with
 $M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.5980E+008$
 $Mu_{1+} = 1.5719E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 1.5980E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.5978E+008$
 $Mu_{2+} = 1.5721E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 1.5978E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = 2740.264$, is the shear force acting at edge 1 for the the static loading combination
 $V_2 = 2740.264$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 0.00010691$
 $M_u = 1.5719E+008$

with full section properties:

$b = 300.00$
 $d = 357.00$
 $d' = 42.00$
 $v = 0.00010459$
 $N = 224.0403$
 $f_c = 20.00$
 ϕ_c (5A.5, TBDY) = 0.002
Final value of ϕ_c : $\phi_c^* = \text{shear_factor} \cdot \text{Max}(\phi_c, \phi_{cc}) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_{cu} = 0.00583896$
 ϕ_{we} (5.4c) = 0.0034192
 ϕ_{ase} ((5.4d), TBDY) = 0.15672608
 $b_o = 240.00$
 $h_o = 340.00$
 $b_{i2} = 346400.00$
 $\phi_{psh,min} = \text{Min}(\phi_{psh,x}, \phi_{psh,y}) = 0.00261799$
Expression ((5.4d), TBDY) for $\phi_{psh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without
earthquake detailing (90° closed stirrups)

 $\phi_{psh,x}$ (5.4d) = 0.00349066
 $A_{sh} = A_{stir} \cdot n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 300.00$

psh,y (5.4d) = 0.00261799
Ash = Astir*ns = 78.53982
No stirups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479
shv = 0.008
ftv = 666.66
fyv = 555.55
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15644251

2 = Asl,com/(b*d)*(fs2/fc) = 0.15970173

v = Asl,mid/(b*d)*(fsv/fc) = 0.07985087

and confined core properties:

b = 240.00
d = 327.00
d' = 12.00

$$f_{cc} (5A.2, TBDY) = 20.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.2134938$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.21794159$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture
' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$s_u (4.9) = 0.16156243$$

$$M_u = M_{Rc} (4.14) = 1.5719E+008$$

$$u = s_u (4.1) = 0.00010691$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u1} -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010702$$

$$M_u = 1.5980E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e (5.4c) = 0.0034192$$

$$a_{se} ((5.4d), TBDY) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} (5.4d) = 0.00349066$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

 $p_{sh,y} (5.4d) = 0.00261799$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

 $s = 150.00$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft1 = 666.66$$

$$fy1 = 555.55$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = fs = 555.55$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00231479$$

$$sh2 = 0.008$$

$$ft2 = 666.66$$

$$fy2 = 555.55$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = fs = 555.55$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.15925564$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.15600552$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.07962782$$

and confined core properties:

$$b = 240.00$$

$$d = 328.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.21727713$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.2128429$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.10863856$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.1647931$$

$$Mu = MRc (4.14) = 1.5980E+008$$

$$u = s_u(4.1) = 0.00010702$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010682$$

$$\mu = 1.5721E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, \text{TB DY}) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TB DY: } c_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}((5.4d), \text{TB DY}) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_i^2 = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TB DY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TB DY), TB DY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu_1_{nominal}((5.5), \text{TB DY}) = 0.032$$

From table 5A.1, TB DY: $esu_1_{nominal} = 0.08$,

For calculation of $esu_1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TB DY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = fs = 555.55$$

with $E_{s1} = E_s = 200000.00$
 $y_2 = 0.00231479$
 $sh_2 = 0.008$
 $ft_2 = 666.66$
 $fy_2 = 555.55$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$
 $su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = fs = 555.55$
 with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00231479$
 $sh_v = 0.008$
 $ft_v = 666.66$
 $fy_v = 555.55$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 1.00$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = fs = 555.55$
 with $E_{sv} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d) * (fs_1/f_c) = 0.15600552$
 $2 = A_{sl,com}/(b*d) * (fs_2/f_c) = 0.15925564$
 $v = A_{sl,mid}/(b*d) * (fs_v/f_c) = 0.07962782$
 and confined core properties:
 $b = 240.00$
 $d = 328.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{sl,ten}/(b*d) * (fs_1/f_c) = 0.2128429$
 $2 = A_{sl,com}/(b*d) * (fs_2/f_c) = 0.21727713$
 $v = A_{sl,mid}/(b*d) * (fs_v/f_c) = 0.10863856$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.16319614$
 $Mu = MR_c (4.14) = 1.5721E+008$
 $u = su (4.1) = 0.00010682$

 Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_2 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010711$$

$$\mu = 1.5978E+008$$

with full section properties:

$$b = 300.00$$

$$d = 357.00$$

$$d' = 42.00$$

$$v = 0.00010459$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}((5.4d), \text{TBDY}) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal}((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1,nominal} = 0.08,$$

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal}((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{2,nominal} = 0.08,$$

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s2} = f_s = 555.55$

with $E_{s2} = E_s = 200000.00$

$y_v = 0.00231479$

$sh_v = 0.008$

$ft_v = 666.66$

$f_{yv} = 555.55$

$s_{uv} = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/d = 1.00$

$s_{uv} = 0.4 \cdot e_{suv,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, f_{yv} , it is considered

characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15970173$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15644251$

v = $As_{l,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.07985087$

and confined core properties:

b = 240.00

d = 327.00

d' = 12.00

f_{cc} (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.21794159$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.2134938$

v = $As_{l,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.10897079$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.16317177

$\mu_u = M_{Rc}$ (4.14) = 1.5978E+008

u = μ_u (4.1) = 0.00010711

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 227879.44$

Calculation of Shear Strength at edge 1, $V_{r1} = 227879.44$

$V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$

= 1 (normal-weight concrete)

$f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$\rho_w = A_s/(b_w \cdot d) = 0.00628319$

A_s (tension reinf.) = 603.1858

$b_w = 300.00$

d = 320.00

$V_u \cdot d / \mu_u < 1 = 1.00$

Mu = 6710.981

Vu = 2740.264

From (11.5.4.8), ACI 318-14: Vs = 148933.273

Av = 157079.633

fy = 444.44

s = 150.00

Vs has been multiplied by 1 (s<d/2, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 285202.276

Calculation of Shear Strength at edge 2, Vr2 = 227879.44

Vr2 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 78946.167

= 1 (normal-weight concrete)

fc' = 20.00, but fc^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

pw = As/(bw*d) = 0.00628319

As (tension reinf.) = 603.1858

bw = 300.00

d = 320.00

Vu*d/Mu < 1 = 1.00

Mu = 6710.981

Vu = 2740.264

From (11.5.4.8), ACI 318-14: Vs = 148933.273

Av = 157079.633

fy = 444.44

s = 150.00

Vs has been multiplied by 1 (s<d/2, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 285202.276

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcars

Constant Properties

Knowledge Factor, = 0.75

Mean strength values are used for both shear and moment calculations.

Consequently:

Existing material of Secondary Member: Concrete Strength, fc = fcm = 20.00

Existing material of Secondary Member: Steel Strength, fs = fsm = 444.44

Concrete Elasticity, Ec = 21019.039

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths, the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, fs = 1.25*fsm = 555.55

#####

Section Height, H = 400.00

Section Width, W = 300.00

Cover Thickness, c = 25.00

Mean Confinement Factor overall section = 1.00

Element Length, L = 1850.00

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou}, \min \geq 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -8.7724203E-020$
EDGE -B-
Shear Force, $V_b = 8.7724203E-020$
BOTH EDGES
Axial Force, $F = -224.0403$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 603.1858$
-Compression: $As_c = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 508.938$
-Compression: $As_{c,com} = 508.938$
-Middle: $As_{c,mid} = 508.938$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.77093353$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 117541.903$
with
 $M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 1.0873E+008$
 $\mu_{1+} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{1-} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 1.0873E+008$
 $\mu_{2+} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $\mu_{2-} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = -8.7724203E-020$, is the shear force acting at edge 1 for the the static loading combination
 $V_2 = 8.7724203E-020$, is the shear force acting at edge 2 for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:
 $\mu = 0.00015595$
 $M_u = 1.0873E+008$

with full section properties:

$b = 400.00$
 $d = 258.00$
 $d' = 42.00$
 $v = 0.00010855$
 $N = 224.0403$
 $f_c = 20.00$
 ω (5A.5, TBDY) = 0.002
Final value of μ_c : $\mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \omega) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\mu_c = 0.00583896$
 ω_e (5.4c) = 0.0034192

ase ((5.4d), TBDY) = 0.15672608

bo = 240.00

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of $e_{sv_nominal}$ and y_v , sh_v , ft_v , fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

1 = $A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.13698668$

2 = $A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.13698668$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.13698668$

and confined core properties:

$b = 340.00$

$d = 228.00$

$d' = 12.00$

f_{cc} (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = $A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.18236617$

2 = $A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.18236617$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.18236617$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2046582

$Mu = MR_c$ (4.14) = 1.0873E+008

$u = su$ (4.1) = 0.00015595

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00015595$

$Mu = 1.0873E+008$

with full section properties:

$b = 400.00$

$d = 258.00$

$d' = 42.00$

$v = 0.00010855$

$N = 224.0403$

$f_c = 20.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$bo = 240.00$

$ho = 340.00$

$bi_2 = 346400.00$

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$bk = 300.00$

psh,y (5.4d) = 0.00261799
Ash = Astir*ns = 78.53982
No stirups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00
From ((5.A.5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479
shv = 0.008
ftv = 666.66
fyv = 555.55
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

$$cc \text{ (5A.5, TBDY)} = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture
' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$su \text{ (4.9)} = 0.2046582$$

$$Mu = MRc \text{ (4.14)} = 1.0873E+008$$

$$u = su \text{ (4.1)} = 0.00015595$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$Mu = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$fc = 20.00$$

$$co \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00583896$$

$$we \text{ (5.4c)} = 0.0034192$$

$$ase \text{ ((5.4d), TBDY)} = 0.15672608$$

$$bo = 240.00$$

$$ho = 340.00$$

$$bi2 = 346400.00$$

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00261799$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x \text{ (5.4d)} = 0.00349066$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirups, } ns = 2.00$$

$$bk = 300.00$$

$$psh,y \text{ (5.4d)} = 0.00261799$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirups, } ns = 2.00$$

$$bk = 400.00$$

$$s = 150.00$$

$$fywe = 555.55$$

$$fce = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00231479$$

$$sh1 = 0.008$$

$$ft1 = 666.66$$

$f_{y1} = 555.55$
 $s_{u1} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 1.00$
 $s_{u1} = 0.4 * e_{su1,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,
 For calculation of $e_{su1,nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = f_s = 555.55$
 with $E_{s1} = E_s = 200000.00$
 $y_2 = 0.00231479$
 $sh_2 = 0.008$
 $ft_2 = 666.66$
 $f_{y2} = 555.55$
 $s_{u2} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$
 $s_{u2} = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,
 For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = f_s = 555.55$
 with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00231479$
 $sh_v = 0.008$
 $ft_v = 666.66$
 $f_{y_v} = 555.55$
 $s_{u_v} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 1.00$
 $s_{u_v} = 0.4 * e_{su_v,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su_v,nominal} = 0.08$,
 considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY
 For calculation of $e_{su_v,nominal}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_v} = f_s = 555.55$
 with $E_{s_v} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.13698668$
 $2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.13698668$
 $v = A_{sl,mid}/(b*d) * (f_{s_v}/f_c) = 0.13698668$
 and confined core properties:
 $b = 340.00$
 $d = 228.00$
 $d' = 12.00$
 $f_{cc} (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.18236617$
 $2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.18236617$
 $v = A_{sl,mid}/(b*d) * (f_{s_v}/f_c) = 0.18236617$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.2046582$
 $M_u = M_{Rc} (4.14) = 1.0873E+008$
 $u = s_u (4.1) = 0.00015595$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$\mu = 0.00015595$
 $\mu_2 = 1.0873E+008$

with full section properties:

$b = 400.00$
 $d = 258.00$
 $d' = 42.00$
 $v = 0.00010855$
 $N = 224.0403$
 $f_c = 20.00$
 $\rho (5A.5, \text{TB DY}) = 0.002$
Final value of μ_2 : $\mu_2^* = \text{shear_factor} * \text{Max}(\mu_2, \rho) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TB DY: $\mu_2 = 0.00583896$
 $\mu_2 (5.4c) = 0.0034192$
 $\mu_2 (5.4d), \text{TB DY} = 0.15672608$
 $b_o = 240.00$
 $h_o = 340.00$
 $b_i^2 = 346400.00$
 $\mu_{sh,min} = \text{Min}(\mu_{sh,x}, \mu_{sh,y}) = 0.00261799$

Expression ((5.4d), TB DY) for $\mu_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$\mu_{sh,x} (5.4d) = 0.00349066$
 $A_{sh} = A_{stir} * n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 300.00$

$\mu_{sh,y} (5.4d) = 0.00261799$
 $A_{sh} = A_{stir} * n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 400.00$

$s = 150.00$
 $f_{ywe} = 555.55$
 $f_{ce} = 20.00$
From ((5.A5), TB DY), TB DY: $\rho = 0.002$
 $c = \text{confinement factor} = 1.00$
 $y_1 = 0.00231479$
 $sh_1 = 0.008$
 $ft_1 = 666.66$
 $fy_1 = 555.55$
 $su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/d = 1.00$
 $su_1 = 0.4 * \text{esu1_nominal} ((5.5), \text{TB DY}) = 0.032$

From table 5A.1, TB DY: $\text{esu1_nominal} = 0.08$,
For calculation of esu1_nominal and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TB DY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = fs = 555.55$
with $E_s = E_s = 200000.00$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{min} = lb/lb_{min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$su_v = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{min} = lb/ld = 1.00$$

$$su_v = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Es_v = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.13698668$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.13698668$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.18236617$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.18236617$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.2046582$$

$$Mu = MRc (4.14) = 1.0873E+008$$

$$u = su (4.1) = 0.00015595$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 152466.975$

Calculation of Shear Strength at edge 1, $V_{r1} = 152466.975$

$V_{r1} = V_n ((22.5.1.1), ACI 318-14)$

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 1.8491887E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$
 V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 152466.975$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 1.8491916E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$
 V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1
At local axis: 2
Integration Section: (a)
Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$
Section Height, $H = 400.00$
Section Width, $W = 300.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 1850.00$
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/d \geq 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 8.2657E+006$
Shear Force, $V_2 = -5.2893637E-014$
Shear Force, $V_3 = -6384.747$
Axial Force, $F = -766.5227$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 603.1858$
-Compression: $A_{sc} = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 603.1858$
-Compression: $A_{sc,com} = 615.7522$
-Middle: $A_{st,mid} = 307.8761$
Mean Diameter of Tension Reinforcement, $D_bL = 16.00$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.01820078$
 $u = y + p = 0.02426771$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00426771$ ((4.29), Biskinis Phd)
 $M_y = 9.9777E+007$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1294.608
From table 10.5, ASCE 41_17: $E_{eff} = 0.3 * E_c * I_g = 1.0089E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 8.5945512E-006$
with $f_y = 444.44$
 $d = 357.00$
 $y = 0.27574463$
 $A = 0.01427207$
 $B = 0.00793091$
with $p_t = 0.00563199$
 $p_c = 0.00574932$
 $p_v = 0.00287466$
 $N = 766.5227$
 $b = 300.00$
 $" = 0.11764706$
 $y_{comp} = 1.7407225E-005$
with $f_c = 20.00$
 $E_c = 21019.039$
 $y = 0.27560804$

A = 0.01423507
B = 0.00791481
with Es = 200000.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of ρ -

From table 10-7: $\rho = 0.02$

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.77008272$

- Transverse Reinforcement: NC

- Stirrup Spacing > d/3

- Low ductility demand, $\lambda / y < 2$ (table 10-6, ASCE 41-17)

= 8.5758849E-005

- Stirrup Spacing $\leq d/2$

d = 357.00

s = 150.00

- Strength provided by hoops $V_s < 3/4$ *design Shear

$V_s = 148933.273$, already given in calculation of shear control ratio

design Shear = 6384.747

- (-)/ bal = -0.160191

= $A_{st}/(b_w*d) = 0.00563199$

Tension Reinf Area: $A_{st} = 603.1858$

' = $A_{sc}/(b_w*d) = 0.00862398$

Compression Reinf Area: $A_{sc} = 923.6282$

From (B-1), ACI 318-11: bal = 0.01867766

$f_c = 20.00$

$f_y = 444.44$

From 10.2.7.3, ACI 318-11: $\lambda = 0.85$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + \lambda) = 0.57447053$

$\lambda = 0.0022222$

- $V/(b_w*d*f_c^{0.5}) = 0.16053232$, NOTE: units in lb & in

$b_w = 300.00$

End Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 11

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 8.2657E+006$

Shear Force, $V_a = -6384.747$

EDGE -B-

Bending Moment, $M_b = 8.6155E+006$

Shear Force, $V_b = 11865.276$

BOTH EDGES

Axial Force, $F = -766.5227$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 603.1858$

-Compression: $As_c = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 603.1858$

-Compression: $As_{l,com} = 615.7522$

-Middle: $As_{l,mid} = 307.8761$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.00$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 148511.925$
 $V_n ((22.5.1.1), ACI 318-14) = 198015.901$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f_v V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 63974.614$

= 1 (normal-weight concrete)

$f_c' = 16.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$\rho_w = As/(b_w \cdot d) = 0.00628319$

As (tension reinf.) = 603.1858

$b_w = 300.00$

$d = 320.00$

$V_u \cdot d / M_u < 1 = 0.24717913$

$M_u = 8.2657E+006$

$V_u = 6384.747$

From (11.5.4.8), ACI 318-14: $V_s = 134041.287$

$A_v = 157079.633$

$f_y = 400.00$

$s = 150.00$

V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17, 10.3.4)

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 255092.67$

End Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 12

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_r)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
 Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
 Concrete Elasticity, $E_c = 21019.039$
 Steel Elasticity, $E_s = 200000.00$

 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

 Section Height, $H = 400.00$
 Section Width, $W = 300.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.00
 Element Length, $L = 1850.00$
 Secondary Member
 Smooth Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_o/l_{ou, \min} >= 1$)
 No FRP Wrapping

Stepwise Properties

At local axis: 3
 EDGE -A-
 Shear Force, $V_a = 2740.264$
 EDGE -B-
 Shear Force, $V_b = 2740.264$
 BOTH EDGES
 Axial Force, $F = -224.0403$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{slt} = 603.1858$
 -Compression: $A_{slc} = 923.6282$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{sl, \text{ten}} = 603.1858$
 -Compression: $A_{sl, \text{com}} = 615.7522$
 -Middle: $A_{sl, \text{mid}} = 307.8761$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.77008272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 175486.019$
with

$M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 1.5980E+008$

$M_{u1+} = 1.5719E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.5980E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 1.5978E+008$

$M_{u2+} = 1.5721E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 1.5978E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = 2740.264$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 2740.264$, is the shear force acting at edge 2 for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010691$

$M_u = 1.5719E+008$

with full section properties:

$b = 300.00$

$d = 357.00$

$d' = 42.00$

$v = 0.00010459$

$N = 224.0403$

$f_c = 20.00$

ϕ_c (5A.5, TBDY) = 0.002

Final value of ϕ_{cu} : $\phi_{cu}^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_c) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_{cu} = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$b_{i2} = 346400.00$

$\phi_{sh,min} = \text{Min}(\phi_{sh,x} , \phi_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $\phi_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $\phi_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

 $\phi_{sh,y}$ (5.4d) = 0.00261799

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 400.00$

 $s = 150.00$

$f_{ywe} = 555.55$

$f_{ce} = 20.00$

From ((5.A5), TBDY), TBDY: $\phi_c = 0.002$

c = confinement factor = 1.00

$y_1 = 0.00231479$

$sh_1 = 0.008$

$$ft1 = 666.66$$

$$fy1 = 555.55$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/d = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = fs = 555.55$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00231479$$

$$sh2 = 0.008$$

$$ft2 = 666.66$$

$$fy2 = 555.55$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = fs = 555.55$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/d = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.15644251$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.15970173$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.2134938$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.21794159$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.16156243$$

$$Mu = MRc (4.14) = 1.5719E+008$$

$$u = s_u(4.1) = 0.00010691$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010702$$

$$\mu = 1.5980E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, \text{TB DY}) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TB DY: } c_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}((5.4d), \text{TB DY}) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_i^2 = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TB DY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TB DY), TB DY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu_1_{nominal}((5.5), \text{TB DY}) = 0.032$$

$$\text{From table 5A.1, TB DY: } esu_1_{nominal} = 0.08,$$

For calculation of $esu_1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TB DY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = fs = 555.55$$

with $E_{s1} = E_s = 200000.00$
 $y_2 = 0.00231479$
 $sh_2 = 0.008$
 $ft_2 = 666.66$
 $fy_2 = 555.55$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/lb_{min} = 1.00$
 $su_2 = 0.4 * esu_{2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,
 For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = fs = 555.55$
 with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00231479$
 $sh_v = 0.008$
 $ft_v = 666.66$
 $fy_v = 555.55$
 $su_v = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 1.00$
 $su_v = 0.4 * esu_{v_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{v_nominal} = 0.08$,
 considering characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY
 For calculation of $esu_{v_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = fs = 555.55$
 with $E_{sv} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d) * (fs_1/fc) = 0.15925564$
 $2 = A_{sl,com}/(b*d) * (fs_2/fc) = 0.15600552$
 $v = A_{sl,mid}/(b*d) * (fs_v/fc) = 0.07962782$
 and confined core properties:
 $b = 240.00$
 $d = 328.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{sl,ten}/(b*d) * (fs_1/fc) = 0.21727713$
 $2 = A_{sl,com}/(b*d) * (fs_2/fc) = 0.2128429$
 $v = A_{sl,mid}/(b*d) * (fs_v/fc) = 0.10863856$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.1647931$
 $M_u = MR_c (4.14) = 1.5980E+008$
 $u = su (4.1) = 0.00010702$

 Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

 Calculation of M_{u2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010682$$

$$\mu = 1.5721E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1,nominal} = 0.08,$$

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{2,nominal} = 0.08,$$

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s2} = f_s = 555.55$

with $E_{s2} = E_s = 200000.00$

$y_v = 0.00231479$

$sh_v = 0.008$

$ft_v = 666.66$

$f_{y_v} = 555.55$

$s_{u_v} = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/d = 1.00$

$s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,

considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered

characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s_v} = f_s = 555.55$

with $E_{s_v} = E_s = 200000.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15600552$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15925564$

$v = As_{l,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.07962782$

and confined core properties:

$b = 240.00$

$d = 328.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 20.00$

$cc (5A.5, TBDY) = 0.002$

$c = \text{confinement factor} = 1.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.2128429$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.21727713$

$v = As_{l,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.10863856$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$s_u (4.9) = 0.16319614$

$M_u = MR_c (4.14) = 1.5721E+008$

$u = s_u (4.1) = 0.00010682$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of M_{u2} -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010711$

$M_u = 1.5978E+008$

with full section properties:

$b = 300.00$

$d = 357.00$

$d' = 42.00$

$v = 0.00010459$

$N = 224.0403$

$f_c = 20.00$

$cc (5A.5, TBDY) = 0.002$

Final value of c_u : $c_u^* = \text{shear_factor} \cdot \text{Max}(c_u, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$b_{i2} = 346400.00$

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} * n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

 $p_{sh,y}$ (5.4d) = 0.00261799

$A_{sh} = A_{stir} * n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 400.00$

 $s = 150.00$

$f_{ywe} = 555.55$

$f_{ce} = 20.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

$c = \text{confinement factor} = 1.00$

$y_1 = 0.00231479$

$sh_1 = 0.008$

$ft_1 = 666.66$

$fy_1 = 555.55$

$su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$su_1 = 0.4 * esu_{1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = fs = 555.55$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00231479$

$sh_2 = 0.008$

$ft_2 = 666.66$

$fy_2 = 555.55$

$su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$

$su_2 = 0.4 * esu_{2,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = fs = 555.55$

with $Es_2 = Es = 200000.00$

$y_v = 0.00231479$

$sh_v = 0.008$

$ft_v = 666.66$

$fy_v = 555.55$

$su_v = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 1.00$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = fs = 555.55$

with $Esv = Es = 200000.00$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.15970173$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.15644251$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$c =$ confinement factor = 1.00

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.21794159$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.2134938$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < vs,c$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.16317177$$

$$Mu = MRc (4.14) = 1.5978E+008$$

$$u = su (4.1) = 0.00010711$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 227879.44$

Calculation of Shear Strength at edge 1, $Vr1 = 227879.44$

$Vr1 = Vn$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' Vw ' is replaced by ' $Vw + f * Vf$ ' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $Vc = 78946.167$

= 1 (normal-weight concrete)

$fc' = 20.00$, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$pw = As / (bw * d) = 0.00628319$$

As (tension reinf.) = 603.1858

$bw = 300.00$

$d = 320.00$

$$Vu * d / Mu < 1 = 1.00$$

$Mu = 6710.981$

$Vu = 2740.264$

From (11.5.4.8), ACI 318-14: $Vs = 148933.273$

$Av = 157079.633$

$fy = 444.44$

$s = 150.00$

Vs has been multiplied by 1 ($s < d/2$, according to ASCE 41-17, 10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $Vs + Vf \leq 285202.276$

Calculation of Shear Strength at edge 2, $Vr2 = 227879.44$

$Vr2 = Vn$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
As (tension reinf.) = 603.1858
bw = 300.00
d = 320.00
 $V_u*d/\mu_u < 1 = 1.00$
 $\mu_u = 6710.981$
 $V_u = 2740.264$

From (11.5.4.8), ACI 318-14: $V_s = 148933.273$
 $A_v = 157079.633$
 $f_y = 444.44$
s = 150.00

V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$
Mean strength values are used for both shear and moment calculations.
Consequently:
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Existing material: Steel Strength, $f_s = 1.25*f_{sm} = 555.55$

Section Height, H = 400.00
Section Width, W = 300.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.00
Element Length, L = 1850.00
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, \min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -8.7724203E-020$
EDGE -B-
Shear Force, $V_b = 8.7724203E-020$

BOTH EDGES

Axial Force, $F = -224.0403$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 603.1858$

-Compression: $As_c = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{ten} = 508.938$

-Compression: $As_{com} = 508.938$

-Middle: $As_{mid} = 508.938$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77093353$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 117541.903$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.0873E+008$

$Mu_{1+} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.0873E+008$

$Mu_{2+} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -8.7724203E-020$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 8.7724203E-020$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00015595$

$M_u = 1.0873E+008$

with full section properties:

$b = 400.00$

$d = 258.00$

$d' = 42.00$

$v = 0.00010855$

$N = 224.0403$

$f_c = 20.00$

ϕ_c (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$bi_2 = 346400.00$

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

psh,y (5.4d) = 0.00261799
Ash = Astir*ns = 78.53982
No stirups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00
From ((5.A.5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479
shv = 0.008
ftv = 666.66
fyv = 555.55
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

$$cc \text{ (5A.5, TBDY)} = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture
' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$$su \text{ (4.9)} = 0.2046582$$

$$Mu = MRc \text{ (4.14)} = 1.0873E+008$$

$$u = su \text{ (4.1)} = 0.00015595$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$Mu = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$fc = 20.00$$

$$co \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00583896$$

$$we \text{ (5.4c)} = 0.0034192$$

$$ase \text{ ((5.4d), TBDY)} = 0.15672608$$

$$bo = 240.00$$

$$ho = 340.00$$

$$bi2 = 346400.00$$

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00261799$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x \text{ (5.4d)} = 0.00349066$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 300.00$$

$$psh,y \text{ (5.4d)} = 0.00261799$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 400.00$$

$$s = 150.00$$

$$fywe = 555.55$$

$$fce = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00231479$$

$$sh1 = 0.008$$

$$ft1 = 666.66$$

$f_{y1} = 555.55$
 $s_{u1} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 1.00$
 $s_{u1} = 0.4 * e_{su1,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,
 For calculation of $e_{su1,nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = f_s = 555.55$
 with $E_{s1} = E_s = 200000.00$
 $y_2 = 0.00231479$
 $sh_2 = 0.008$
 $ft_2 = 666.66$
 $f_{y2} = 555.55$
 $s_{u2} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 1.00$
 $s_{u2} = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,
 For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_2, sh_2, ft_2, f_{y2} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = f_s = 555.55$
 with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00231479$
 $sh_v = 0.008$
 $ft_v = 666.66$
 $f_{y_v} = 555.55$
 $s_{u_v} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 1.00$
 $s_{u_v} = 0.4 * e_{su_v,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su_v,nominal} = 0.08$,
 considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY
 For calculation of $e_{su_v,nominal}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_v} = f_s = 555.55$
 with $E_{s_v} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.13698668$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13698668$
 $v = A_{sl,mid}/(b*d)*(f_{s_v}/f_c) = 0.13698668$
 and confined core properties:
 $b = 340.00$
 $d = 228.00$
 $d' = 12.00$
 $f_{cc} (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.18236617$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.18236617$
 $v = A_{sl,mid}/(b*d)*(f_{s_v}/f_c) = 0.18236617$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.2046582$
 $M_u = M_{Rc} (4.14) = 1.0873E+008$
 $u = s_u (4.1) = 0.00015595$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$\mu = 0.00015595$
 $\mu_{2+} = 1.0873E+008$

with full section properties:

$b = 400.00$
 $d = 258.00$
 $d' = 42.00$
 $v = 0.00010855$
 $N = 224.0403$
 $f_c = 20.00$
 $\alpha (5A.5, TBDY) = 0.002$
Final value of μ_{cu} : $\mu_{cu}^* = \text{shear_factor} * \text{Max}(\mu_{cu}, \mu_{cc}) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\mu_{cu} = 0.00583896$
 $\mu_{we} (5.4c) = 0.0034192$
 $\mu_{ase} ((5.4d), TBDY) = 0.15672608$
 $b_o = 240.00$
 $h_o = 340.00$
 $b_{i2} = 346400.00$
 $\mu_{psh,min} = \text{Min}(\mu_{psh,x}, \mu_{psh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $\mu_{psh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$\mu_{psh,x} (5.4d) = 0.00349066$
 $A_{sh} = A_{stir} * n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 300.00$

$\mu_{psh,y} (5.4d) = 0.00261799$
 $A_{sh} = A_{stir} * n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 400.00$

$s = 150.00$
 $f_{ywe} = 555.55$
 $f_{ce} = 20.00$
From ((5.A.5), TBDY), TBDY: $\mu_{cc} = 0.002$
 $c = \text{confinement factor} = 1.00$
 $y_1 = 0.00231479$
 $sh_1 = 0.008$
 $ft_1 = 666.66$
 $fy_1 = 555.55$
 $su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/d = 1.00$
 $\mu_{su_1} = 0.4 * \mu_{su_1,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $\mu_{su_1,nominal} = 0.08$,

For calculation of $\mu_{su_1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy_1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = f_s = 555.55$
with $E_{s1} = E_s = 200000.00$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{min} = lb/lb_{min} = 1.00$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$su_v = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{min} = lb/ld = 1.00$$

$$su_v = 0.4 * esu_{v,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{v,nominal} = 0.08$,

considering characteristic value $fsy_v = fsv/1.2$, from table 5.1, TBDY

For calculation of $esu_{v,nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsy_v = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Es_v = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.13698668$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.13698668$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.18236617$$

$$2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.18236617$$

$$v = Asl_{mid}/(b*d) * (fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$$su (4.9) = 0.2046582$$

$$Mu = MRc (4.14) = 1.0873E+008$$

$$u = su (4.1) = 0.00015595$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu_2 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 0.00015595
Mu = 1.0873E+008

with full section properties:

b = 400.00
d = 258.00
d' = 42.00
v = 0.00010855
N = 224.0403
fc = 20.00
co (5A.5, TBDY) = 0.002
Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00583896
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: cu = 0.00583896
we (5.4c) = 0.0034192
ase ((5.4d), TBDY) = 0.15672608
bo = 240.00
ho = 340.00
bi2 = 346400.00
psh,min = Min(psh,x , psh,y) = 0.00261799
Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066
Ash = Astir*ns = 78.53982
No stirrups, ns = 2.00
bk = 300.00

psh,y (5.4d) = 0.00261799
Ash = Astir*ns = 78.53982
No stirrups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00
From ((5.A5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00
y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/d = 1.00
su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esu1_nominal = 0.08,
For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.
with fs1 = fs = 555.55
with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/lb,min = 1.00
su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esu2_nominal = 0.08,
For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = fs = 555.55$

with $Es_2 = Es = 200000.00$

$yv = 0.00231479$

$shv = 0.008$

$ftv = 666.66$

$fyv = 555.55$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lou, \min = lb/d = 1.00$

$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and yv, shv, ftv, fyv , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = fs = 555.55$

with $Es_v = Es = 200000.00$

1 = $Asl, \text{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.13698668$

2 = $Asl, \text{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.13698668$

v = $Asl, \text{mid} / (b \cdot d) \cdot (fsv / fc) = 0.13698668$

and confined core properties:

$b = 340.00$

$d = 228.00$

$d' = 12.00$

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = $Asl, \text{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.18236617$

2 = $Asl, \text{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.18236617$

v = $Asl, \text{mid} / (b \cdot d) \cdot (fsv / fc) = 0.18236617$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < vs, c$ - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2046582

$Mu = MRc$ (4.14) = 1.0873E+008

$u = su$ (4.1) = 0.00015595

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Shear Strength $Vr = \text{Min}(Vr_1, Vr_2) = 152466.975$

Calculation of Shear Strength at edge 1, $Vr_1 = 152466.975$

$Vr_1 = Vn$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' Vw ' is replaced by ' $Vw + f \cdot Vf$ '

where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $Vc = 68692.008$

= 1 (normal-weight concrete)

$fc' = 20.00$, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$pw = As / (bw \cdot d) = 0.00628319$

As (tension reinf.) = 603.1858

$bw = 400.00$

$d = 240.00$

$Vu \cdot d / Mu < 1 = 0.00$

$Mu = 1.8491887E-012$

$$V_u = 8.7724203E-020$$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$

$$A_v = 157079.633$$

$$f_y = 444.44$$

$$s = 150.00$$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$$2(1-s/d) = 0.75$$

$$V_f ((11-3)-(11.4), ACI 440) = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 285202.276$$

Calculation of Shear Strength at edge 2, $V_{r2} = 152466.975$

$$V_{r2} = V_n ((22.5.1.1), ACI 318-14)$$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$

= 1 (normal-weight concrete)

$$f_c' = 20.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$p_w = A_s / (b_w \cdot d) = 0.00628319$$

$$A_s (\text{tension reinf.}) = 603.1858$$

$$b_w = 400.00$$

$$d = 240.00$$

$$V_u \cdot d / M_u < 1 = 0.00$$

$$M_u = 1.8491916E-012$$

$$V_u = 8.7724203E-020$$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$

$$A_v = 157079.633$$

$$f_y = 444.44$$

$$s = 150.00$$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$$2(1-s/d) = 0.75$$

$$V_f ((11-3)-(11.4), ACI 440) = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 285202.276$$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -8.0944479E-012$

Shear Force, $V2 = -5.2893637E-014$

Shear Force, $V3 = -6384.747$

Axial Force, $F = -766.5227$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 603.1858$

-Compression: $As_c = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 508.938$

-Compression: $As_{c,com} = 508.938$

-Middle: $As_{mid} = 508.938$

Mean Diameter of Tension Reinforcement, $Db_L = 14.66667$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \alpha u = 0.01779661$
 $u = \gamma + \rho = 0.02372882$

- Calculation of γ -

$\gamma = (M \cdot L_s / 3) / E_{eff} = 0.00372882$ ((4.29), Biskinis Phd))

$M_y = 6.8632E+007$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 925.00

From table 10.5, ASCE 41_17: $E_{eff} = 0.3 \cdot E_c \cdot I_g = 5.6751E+012$

Calculation of Yielding Moment M_y

Calculation of γ and M_y according to Annex 7 -

$\gamma = \text{Min}(\gamma_{ten}, \gamma_{com})$

$\gamma_{ten} = 1.2094933E-005$

with $f_y = 444.44$

$d = 258.00$

$\gamma = 0.28786888$

$A = 0.01481142$

$B = 0.00861829$

with $p_t = 0.00493157$

$p_c = 0.00493157$

$p_v = 0.00493157$

$N = 766.5227$

$b = 400.00$

" = 0.1627907

$\gamma_{comp} = 2.3070920E-005$

with $f_c = 20.00$

$E_c = 21019.039$

$\gamma = 0.28774317$

$A = 0.01477303$

$B = 0.00860158$

with $E_s = 200000.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ -

From table 10-7: $\rho = 0.02$

with:

- Condition i occurred
Beam controlled by flexure: $V_p/V_o \leq 1$
shear control ratio $V_p/V_o = 0.77093353$
- Transverse Reinforcement: NC
- Stirrup Spacing $> d/3$
- Low ductility demand, $\lambda / \gamma < 2$ (table 10-6, ASCE 41-17)
 $= -5.3657545E-022$
- Stirrup Spacing $> d/2$
 $d = 258.00$
 $s = 150.00$
- Strength provided by hoops $V_s < 3/4 * \text{design Shear}$
 $V_s = 111699.955$, already given in calculation of shear control ratio
design Shear = $5.2893637E-014$
- ($\lambda - \lambda')$ / bal = -0.16624473
 $= A_{st}/(b_w * d) = 0.00584482$
Tension Reinf Area: $A_{st} = 603.1858$
 $\lambda' = A_{sc}/(b_w * d) = 0.00894989$
Compression Reinf Area: $A_{sc} = 923.6282$
From (B-1), ACI 318-11: bal = 0.01867766
 $f_c = 20.00$
 $f_y = 444.44$
From 10.2.7.3, ACI 318-11: $\lambda = 0.85$
From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + \lambda) = 0.57447053$
 $\gamma = 0.0022222$
- $V/(b_w * d * f_c^{0.5}) = 1.3801680E-018$, NOTE: units in lb & in
 $b_w = 400.00$

End Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 13

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcars

Constant Properties

Knowledge Factor, $\gamma = 0.75$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,min} = l_b/l_d \geq 1$)

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -8.0944479E-012$

Shear Force, $V_a = -5.2893637E-014$

EDGE -B-

Bending Moment, $M_b = -8.9686435E-011$

Shear Force, $V_b = 5.2893637E-014$

BOTH EDGES

Axial Force, $F = -766.5227$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{s,t} = 615.7522$

-Compression: $A_{s,c} = 911.0619$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{s,ten} = 508.938$

-Compression: $A_{s,com} = 508.938$

-Middle: $A_{s,mid} = 508.938$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 14.66667$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $VR = *V_n = 102628.668$

$V_n ((22.5.1.1), ACI 318-14) = 136838.224$

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 61440.00$
= 1 (normal-weight concrete)
 $f'_c = 16.00$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00641409$
 A_s (tension reinf.) = 615.7522
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 8.9686435E-011$
 $V_u = 5.2893637E-014$
From (11.5.4.8), ACI 318-14: $V_s = 75398.224$
 $A_v = 157079.633$
 $f_y = 400.00$
 $s = 150.00$
 V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 255092.67$

End Of Calculation of Shear Capacity for element: beam B1 of floor 1
At local axis: 2
Integration Section: (b)

Calculation No. 14

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 3

(Bending local axis: 2)
Section Type: rcars

Constant Properties

Knowledge Factor, $k = 0.75$

Mean strength values are used for both shear and moment calculations.

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou}, \min > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = 2740.264$

EDGE -B-

Shear Force, $V_b = 2740.264$

BOTH EDGES

Axial Force, $F = -224.0403$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 603.1858$

-Compression: $A_{sc} = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 603.1858$

-Compression: $A_{sl,com} = 615.7522$

-Middle: $A_{sl,mid} = 307.8761$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77008272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 175486.019$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 1.5980E+008$

$M_{u1+} = 1.5719E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.5980E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 1.5978E+008$

$M_{u2+} = 1.5721E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 1.5978E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

V1 = 2740.264, is the shear force acting at edge 1 for the the static loading combination

V2 = 2740.264, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu1+

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$\mu = 0.00010691$

Mu = 1.5719E+008

with full section properties:

b = 300.00

d = 357.00

d' = 42.00

v = 0.00010459

N = 224.0403

fc = 20.00

co (5A.5, TBDY) = 0.002

Final value of μ : $\mu^* = \text{shear_factor} * \text{Max}(\mu, \mu_c) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_c = 0.00583896$

we (5.4c) = 0.0034192

ase ((5.4d), TBDY) = 0.15672608

bo = 240.00

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: $\mu_c = 0.002$

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

$$f_y2 = 555.55$$

$$s_u2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,

For calculation of $e_{su2,nominal}$ and y_2 , sh_2, ft_2, f_y2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, f_y1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = f_s = 555.55$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$f_{y_v} = 555.55$$

$$s_{u_v} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_d = 1.00$$

$$s_{u_v} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and y_v , sh_v, ft_v, f_{y_v} , it is considered
characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = f_s = 555.55$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.15644251$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.15970173$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$f_{cc} (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.2134938$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.21794159$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.16156243$$

$$M_u = M_{Rc} (4.14) = 1.5719E+008$$

$$u = s_u (4.1) = 0.00010691$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_u1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010702$$

$$M_u = 1.5980E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_i^2 = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_nominal = 0.08,$$

For calculation of $esu1_nominal$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$$

$$su_2 = 0.4 * esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_nominal = 0.08,$$

For calculation of $esu2_nominal$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

$$y_2, sh_2, ft_2, fy_2, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$su_v = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 1.00$$

$$su_v = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fs_v = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fs_v = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = fs = 555.55$

with $Esv = Es = 200000.00$

$$1 = A_{sl,ten}/(b*d) * (fs_1/fc) = 0.15925564$$

$$2 = A_{sl,com}/(b*d) * (fs_2/fc) = 0.15600552$$

$$v = A_{sl,mid}/(b*d) * (fsv/fc) = 0.07962782$$

and confined core properties:

$$b = 240.00$$

$$d = 328.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$c =$ confinement factor = 1.00

$$1 = A_{sl,ten}/(b*d) * (fs_1/fc) = 0.21727713$$

$$2 = A_{sl,com}/(b*d) * (fs_2/fc) = 0.2128429$$

$$v = A_{sl,mid}/(b*d) * (fsv/fc) = 0.10863856$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.1647931$$

$$Mu = MRc (4.14) = 1.5980E+008$$

$$u = su (4.1) = 0.00010702$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010682$$

$$Mu = 1.5721E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$fc = 20.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, co) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

$$we (5.4c) = 0.0034192$$

$$ase ((5.4d), TBDY) = 0.15672608$$

bo = 240.00
ho = 340.00
bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799
Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066
Ash = Astir*ns = 78.53982
No stirrups, ns = 2.00
bk = 300.00

psh,y (5.4d) = 0.00261799
Ash = Astir*ns = 78.53982
No stirrups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

1 = $A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15600552$

2 = $A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15925564$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.07962782$

and confined core properties:

$b = 240.00$

$d = 328.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = $A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.2128429$

2 = $A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.21727713$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.10863856$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.16319614

$M_u = M_{Rc}$ (4.14) = 1.5721E+008

$u = \mu_u$ (4.1) = 0.00010682

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_u

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010711$

$M_u = 1.5978E+008$

with full section properties:

$b = 300.00$

$d = 357.00$

$d' = 42.00$

$v = 0.00010459$

$N = 224.0403$

$f_c = 20.00$

cc (5A.5, TBDY) = 0.002

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.00583896$

w_e (5.4c) = 0.0034192

a_{se} ((5.4d), TBDY) = 0.15672608

$b_o = 240.00$

$h_o = 340.00$

$b_{i2} = 346400.00$

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x}$ (5.4d) = 0.00349066

$A_{sh} = A_{stir} \cdot n_s = 78.53982$

No stirrups, $n_s = 2.00$

$b_k = 300.00$

 $p_{sh,y}$ (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982
No stirrups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00

From ((5.A.5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479
shv = 0.008
ftv = 666.66
fyv = 555.55
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15970173

2 = Asl,com/(b*d)*(fs2/fc) = 0.15644251

v = Asl,mid/(b*d)*(fsv/fc) = 0.07985087

and confined core properties:

b = 240.00
d = 327.00
d' = 12.00

fcc (5A.2, TBDY) = 20.00
cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = $As_{l,ten}/(b*d)*(fs1/fc) = 0.21794159$

2 = $As_{l,com}/(b*d)*(fs2/fc) = 0.2134938$

v = $As_{l,mid}/(b*d)*(fsv/fc) = 0.10897079$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

v < $v_{s,c}$ - RHS eq.(4.5) is satisfied

su (4.9) = 0.16317177

Mu = MRc (4.14) = 1.5978E+008

u = su (4.1) = 0.00010711

Calculation of ratio lb/ld

Adequate Lap Length: lb/ld >= 1

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 227879.44$

Calculation of Shear Strength at edge 1, $V_{r1} = 227879.44$

$V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$

= 1 (normal-weight concrete)

$fc' = 20.00$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$pw = As/(bw*d) = 0.00628319$

As (tension reinf.) = 603.1858

$bw = 300.00$

$d = 320.00$

$V_u*d/Mu < 1 = 1.00$

$Mu = 6710.981$

$V_u = 2740.264$

From (11.5.4.8), ACI 318-14: $V_s = 148933.273$

$Av = 157079.633$

$fy = 444.44$

$s = 150.00$

V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 227879.44$

$V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$

= 1 (normal-weight concrete)

$fc' = 20.00$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$pw = As/(bw*d) = 0.00628319$

As (tension reinf.) = 603.1858

$bw = 300.00$

$d = 320.00$

$V_u*d/Mu < 1 = 1.00$

$Mu = 6710.981$

$V_u = 2740.264$

From (11.5.4.8), ACI 318-14: $V_s = 148933.273$

$Av = 157079.633$

$fy = 444.44$

$s = 150.00$

Vs has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$
Mean strength values are used for both shear and moment calculations.
Consequently:
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.55$

Section Height, $H = 400.00$
Section Width, $W = 300.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.00
Element Length, $L = 1850.00$
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, min} > 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -8.7724203E-020$
EDGE -B-
Shear Force, $V_b = 8.7724203E-020$
BOTH EDGES
Axial Force, $F = -224.0403$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 603.1858$
-Compression: $A_{sc} = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st, ten} = 508.938$
-Compression: $A_{sc, com} = 508.938$
-Middle: $A_{sc, mid} = 508.938$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77093353$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u * l_n / 2 = 117541.903$
with

$$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 1.0873E+008$$

$M_{u1+} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 1.0873E+008$$

$M_{u2+} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination

$M_{u2-} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination

and

$$\pm w_u \cdot l_n = (|V1| + |V2|)/2$$

with

$V1 = -8.7724203E-020$, is the shear force acting at edge 1 for the static loading combination

$V2 = 8.7724203E-020$, is the shear force acting at edge 2 for the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$M_u = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$\omega (5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00583896$$

$$w_e (5.4c) = 0.0034192$$

$$a_{se} ((5.4d), \text{TBDY}) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} (5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} \cdot n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} (5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} \cdot n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00231479$$

$$sh1 = 0.008$$

$$ft1 = 666.66$$

$$fy1 = 555.55$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617

2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617

v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

v < vs,c - RHS eq.(4.5) is satisfied

su (4.9) = 0.2046582

Mu = MRc (4.14) = 1.0873E+008

u = su (4.1) = 0.00015595

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 0.00015595$$

$$\mu_1 = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1,nominal} = 0.08,$$

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft_2 = 666.66$$

$$fy_2 = 555.55$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

$$\text{Shear_factor} = 1.00$$

$$l_o/l_{o,\min} = l_b/l_{b,\min} = 1.00$$

$$su_2 = 0.4 * esu_2\text{nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_2\text{nominal} = 0.08$,

For calculation of $esu_2\text{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = fs = 555.55$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00231479$$

$$sh_v = 0.008$$

$$ft_v = 666.66$$

$$fy_v = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

$$\text{Shear_factor} = 1.00$$

$$l_o/l_{o,\min} = l_b/l_d = 1.00$$

$$suv = 0.4 * esuv\text{nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esuv\text{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv\text{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (fs_1/fc) = 0.13698668$$

$$2 = A_{sl,com}/(b*d) * (fs_2/fc) = 0.13698668$$

$$v = A_{sl,mid}/(b*d) * (fsv/fc) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$fcc (5A.2, \text{TBDY}) = 20.00$$

$$cc (5A.5, \text{TBDY}) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d) * (fs_1/fc) = 0.18236617$$

$$2 = A_{sl,com}/(b*d) * (fs_2/fc) = 0.18236617$$

$$v = A_{sl,mid}/(b*d) * (fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.2046582$$

$$\mu_u = MR_c (4.14) = 1.0873E+008$$

$$u = su (4.1) = 0.00015595$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$\mu_u = 1.0873E+008$$

with full section properties:

b = 400.00
d = 258.00
d' = 42.00
v = 0.00010855
N = 224.0403
fc = 20.00
co (5A.5, TBDY) = 0.002
Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $cu = 0.00583896$
we (5.4c) = 0.0034192
ase ((5.4d), TBDY) = 0.15672608
bo = 240.00
ho = 340.00
bi2 = 346400.00
psh,min = $\text{Min}(psh,x, psh,y) = 0.00261799$
Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066
Ash = $\text{Astir} * ns = 78.53982$
No stirrups, ns = 2.00
bk = 300.00

psh,y (5.4d) = 0.00261799
Ash = $\text{Astir} * ns = 78.53982$
No stirrups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00
From ((5.A5), TBDY), TBDY: $cc = 0.002$
c = confinement factor = 1.00
y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $lo/lou,min = lb/d = 1.00$
 $su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $esu1_nominal = 0.08$,
For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $fs1 = fs = 555.55$
with $Es1 = Es = 200000.00$

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $lo/lou,min = lb/lb,min = 1.00$
 $su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$
From table 5A.1, TBDY: $esu2_nominal = 0.08$,
For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.
with $fs2 = fs = 555.55$
with $Es2 = Es = 200000.00$
yv = 0.00231479

$shv = 0.008$
 $ftv = 666.66$
 $fyv = 555.55$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lo_{min} = lb/ld = 1.00$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = fs = 555.55$
 with $Esv = Es = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668$
 and confined core properties:
 $b = 340.00$
 $d = 228.00$
 $d' = 12.00$
 $fcc (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < vs,c$ - RHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.2046582$
 $Mu = MRc (4.14) = 1.0873E+008$
 $u = su (4.1) = 0.00015595$

 Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

 Calculation of $Mu2$ -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00015595$
 $Mu = 1.0873E+008$

with full section properties:

$b = 400.00$
 $d = 258.00$
 $d' = 42.00$
 $v = 0.00010855$
 $N = 224.0403$
 $fc = 20.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00583896$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00583896$
 $we (5.4c) = 0.0034192$
 $ase ((5.4d), TBDY) = 0.15672608$
 $bo = 240.00$

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.13698668$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.13698668$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.13698668$

and confined core properties:

$b = 340.00$

$d = 228.00$

$d' = 12.00$

$f_{cc} \text{ (5A.2, TBDY)} = 20.00$

$cc \text{ (5A.5, TBDY)} = 0.002$

$c = \text{confinement factor} = 1.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.18236617$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.18236617$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.18236617$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$su \text{ (4.9)} = 0.2046582$

$\mu_u = MR_c \text{ (4.14)} = 1.0873E+008$

$u = su \text{ (4.1)} = 0.00015595$

Calculation of ratio lb/d

Adequate Lap Length: $lb/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 152466.975$

Calculation of Shear Strength at edge 1, $V_{r1} = 152466.975$

$V_{r1} = V_n \text{ ((22.5.1.1), ACI 318-14)}$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$

$= 1$ (normal-weight concrete)

$f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3 \text{ MPa}$ (22.5.3.1, ACI 318-14)

$\rho_w = A_s/(b_w \cdot d) = 0.00628319$

$A_s \text{ (tension reinf.)} = 603.1858$

$b_w = 400.00$

$d = 240.00$

$V_u \cdot d / \mu_u < 1 = 0.00$

$\mu_u = 1.8491887E-012$

$V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$

$A_v = 157079.633$

$f_y = 444.44$

$s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17, 10.3.4)

$2(1-s/d) = 0.75$

$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 152466.975$

$V_{r2} = V_n \text{ ((22.5.1.1), ACI 318-14)}$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$

= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u \cdot d / M_u < 1 = 0.00$
 $M_u = 1.8491916E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$

$A_v = 157079.633$

$f_y = 444.44$

$s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17, 10.3.4)

$2(1-s/d) = 0.75$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b / l_d > 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 8.6155E+006$

Shear Force, $V_2 = 5.2893637E-014$

Shear Force, $V_3 = 11865.276$

Axial Force, $F = -766.5227$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{s,t} = 615.7522$

-Compression: $A_{s,c} = 911.0619$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{s,ten} = 615.7522$

-Compression: $A_{s,com} = 603.1858$

-Middle: $A_{s,mid} = 307.8761$

Mean Diameter of Tension Reinforcement, $Db_L = 14.00$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_R = \phi u = 0.0168308$
 $u = y + p = 0.02244106$

- Calculation of y -

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00244106$ ((4.29), Biskinis Phd))
 $M_y = 1.0175E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 726.1115
From table 10.5, ASCE 41_17: $E_{\text{eff}} = 0.3 \cdot E_c \cdot I_g = 1.0089E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 8.6005312E-006$
with $f_y = 444.44$
 $d = 358.00$
 $y = 0.27826986$
 $A = 0.0142322$
 $B = 0.00802937$
with $p_t = 0.00573326$
 $p_c = 0.00561626$
 $p_v = 0.00286663$
 $N = 766.5227$
 $b = 300.00$
 $\rho = 0.12011173$
 $y_{\text{comp}} = 1.7200799E-005$
with $f_c = 20.00$
 $E_c = 21019.039$
 $y = 0.2781365$
 $A = 0.01419531$
 $B = 0.00801331$
with $E_s = 200000.00$

Calculation of ratio I_b/I_d

Adequate Lap Length: $I_b/I_d \geq 1$

- Calculation of p -

From table 10-7: $p = 0.02$

with:

- Condition i occurred
Beam controlled by flexure: $V_p/V_o \leq 1$
shear control ratio $V_p/V_o = 0.77008272$
- Transverse Reinforcement: NC
- Stirrup Spacing $> d/3$
- Low ductility demand, $\rho / y < 2$ (table 10-6, ASCE 41-17)
 $\rho = 5.0378505E-005$
- Stirrup Spacing $\leq d/2$
 $d = 358.00$
 $s = 150.00$
- Strength provided by hoops $V_s < 3/4 \cdot \text{design Shear}$
 $V_s = 148933.273$, already given in calculation of shear control ratio
design Shear = 11865.276
- $(\rho - \rho') / \rho_{\text{bal}} = -0.14721463$
 $\rho = A_s / (b_w \cdot d) = 0.00573326$
Tension Reinf Area: $A_s = 615.7522$

$$\rho = A_{sc}/(b_w*d) = 0.00848289$$

Compression Reinf Area: $A_{sc} = 911.0619$

From (B-1), ACI 318-11: $\rho_{bal} = 0.01867766$

$f_c = 20.00$

$f_y = 444.44$

From 10.2.7.3, ACI 318-11: $\beta_1 = 0.85$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000+f_y) = c_b/d_t = 0.003/(0.003+ y) = 0.57447053$

$$y = 0.0022222$$

- $V/(b_w*d*f_c^{0.5}) = 0.29749645$, NOTE: units in lb & in

$b_w = 300.00$

End Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 15

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$
Section Height, $H = 400.00$
Section Width, $W = 300.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 1850.00$
Secondary Member
Smooth Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} = l_b/d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = 8.2657E+006$
Shear Force, $V_a = -6384.747$
EDGE -B-
Bending Moment, $M_b = 8.6155E+006$
Shear Force, $V_b = 11865.276$
BOTH EDGES
Axial Force, $F = -766.5227$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 615.7522$
-Compression: $A_{sc} = 911.0619$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 615.7522$
-Compression: $A_{st,com} = 603.1858$
-Middle: $A_{st,mid} = 307.8761$
Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 14.00$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 150070.859$
 V_n ((22.5.1.1), ACI 318-14) = 200094.479

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + \phi V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 66053.192$
= 1 (normal-weight concrete)
 $f_c' = 16.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00641409$
 A_s (tension reinf.) = 615.7522
 $b_w = 300.00$
 $d = 320.00$
 $V_u*d/\mu_u < 1 = 0.44070366$
 $\mu_u = 8.6155E+006$
 $V_u = 11865.276$
From (11.5.4.8), ACI 318-14: $V_s = 134041.287$
 $A_v = 157079.633$
 $f_y = 400.00$
 $s = 150.00$
 V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 255092.67$

End Of Calculation of Shear Capacity for element: beam B1 of floor 1
At local axis: 3
Integration Section: (b)

Calculation No. 16

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$

Mean strength values are used for both shear and moment calculations.

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou}, \min \geq 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = 2740.264$
EDGE -B-
Shear Force, $V_b = 2740.264$
BOTH EDGES
Axial Force, $F = -224.0403$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 603.1858$
-Compression: $As_c = 923.6282$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 603.1858$
-Compression: $As_{c,com} = 615.7522$
-Middle: $As_{c,mid} = 307.8761$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77008272$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 175486.019$
with
 $M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 1.5980E+008$
 $\mu_{1+} = 1.5719E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $\mu_{1-} = 1.5980E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 1.5978E+008$
 $\mu_{2+} = 1.5721E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $\mu_{2-} = 1.5978E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = 2740.264$, is the shear force acting at edge 1 for the the static loading combination
 $V_2 = 2740.264$, is the shear force acting at edge 2 for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:
 $\mu = 0.00010691$
 $\mu_u = 1.5719E+008$

with full section properties:

$b = 300.00$
 $d = 357.00$
 $d' = 42.00$
 $v = 0.00010459$
 $N = 224.0403$
 $f_c = 20.00$
 ω (5A.5, TBDY) = 0.002
Final value of μ_c : $\mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \omega) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\mu_c = 0.00583896$
 ω_e (5.4c) = 0.0034192
 ω_{se} ((5.4d), TBDY) = 0.15672608
 $b_o = 240.00$

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$

with $E_{sv} = E_s = 200000.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.15644251$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.15970173$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.07985087$

and confined core properties:

$b = 240.00$

$d = 327.00$

$d' = 12.00$

$f_{cc} \text{ (5A.2, TBDY)} = 20.00$

$cc \text{ (5A.5, TBDY)} = 0.002$

$c = \text{confinement factor} = 1.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.2134938$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.21794159$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.10897079$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$su \text{ (4.9)} = 0.16156243$

$Mu = MR_c \text{ (4.14)} = 1.5719E+008$

$u = su \text{ (4.1)} = 0.00010691$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010702$

$Mu = 1.5980E+008$

with full section properties:

$b = 300.00$

$d = 358.00$

$d' = 43.00$

$v = 0.0001043$

$N = 224.0403$

$f_c = 20.00$

$co \text{ (5A.5, TBDY)} = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

$w_e \text{ (5.4c)} = 0.0034192$

$ase \text{ ((5.4d), TBDY)} = 0.15672608$

$bo = 240.00$

$ho = 340.00$

$bi_2 = 346400.00$

$psh_{,min} = \text{Min}(psh_x, psh_y) = 0.00261799$

Expression ((5.4d), TBDY) for $psh_{,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $psh_x \text{ (5.4d)} = 0.00349066$

$A_{sh} = A_{stir} \cdot ns = 78.53982$

No stirrups, $ns = 2.00$

$bk = 300.00$

 $psh_y \text{ (5.4d)} = 0.00261799$

$A_{sh} = A_{stir} \cdot ns = 78.53982$

No stirrups, ns = 2.00
bk = 400.00

s = 150.00
fywe = 555.55
fce = 20.00

From ((5.A.5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y1 = 0.00231479
sh1 = 0.008
ft1 = 666.66
fy1 = 555.55
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479
sh2 = 0.008
ft2 = 666.66
fy2 = 555.55
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479
shv = 0.008
ftv = 666.66
fyv = 555.55
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15925564

2 = Asl,com/(b*d)*(fs2/fc) = 0.15600552

v = Asl,mid/(b*d)*(fsv/fc) = 0.07962782

and confined core properties:

b = 240.00
d = 328.00
d' = 13.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.21727713$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.2128429$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10863856$$

Case/Assumption: Unconfined full section - Steel rupture
' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$s_u(4.9) = 0.1647931$$

$$M_u = M_{Rc}(4.14) = 1.5980E+008$$

$$u = s_u(4.1) = 0.00010702$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010682$$

$$M_u = 1.5721E+008$$

with full section properties:

$$b = 300.00$$

$$d = 358.00$$

$$d' = 43.00$$

$$v = 0.0001043$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}((5.4d), TBDY) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$f_{t1} = 666.66$$

$$f_{y1} = 555.55$$

$$s_{u1} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15600552

2 = Asl,com/(b*d)*(fs2/fc) = 0.15925564

v = Asl,mid/(b*d)*(fsv/fc) = 0.07962782

and confined core properties:

b = 240.00

d = 328.00

d' = 13.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.2128429

2 = Asl,com/(b*d)*(fs2/fc) = 0.21727713

v = Asl,mid/(b*d)*(fsv/fc) = 0.10863856

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.16319614

Mu = MRc (4.14) = 1.5721E+008

u = su (4.1) = 0.00010682

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 0.00010711$$

$$\mu_u = 1.5978E+008$$

with full section properties:

$$b = 300.00$$

$$d = 357.00$$

$$d' = 42.00$$

$$v = 0.00010459$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e \text{ (5.4c)} = 0.0034192$$

$$a_{se} \text{ ((5.4d), TBDY)} = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ (5.4d)} = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y} \text{ (5.4d)} = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$ft_1 = 666.66$$

$$fy_1 = 555.55$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 1.00$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1,nominal} = 0.08,$$

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = fs = 555.55$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00231479$$

$$sh_2 = 0.008$$

$$ft2 = 666.66$$

$$fy2 = 555.55$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = fs = 555.55$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.15970173$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.15644251$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.07985087$$

and confined core properties:

$$b = 240.00$$

$$d = 327.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.21794159$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.2134938$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.10897079$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < vs,c$ - RHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.16317177$$

$$Mu = MRc (4.14) = 1.5978E+008$$

$$u = su (4.1) = 0.00010711$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 227879.44$

Calculation of Shear Strength at edge 1, $Vr1 = 227879.44$

$$Vr1 = Vn ((22.5.1.1), ACI 318-14)$$

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'

where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 300.00$
 $d = 320.00$
 $V_u*d/\mu_u < 1 = 1.00$
 $\mu_u = 6710.981$
 $V_u = 2740.264$

From (11.5.4.8), ACI 318-14: $V_s = 148933.273$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 227879.44$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f*V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 78946.167$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 300.00$
 $d = 320.00$
 $V_u*d/\mu_u < 1 = 1.00$
 $\mu_u = 6710.981$
 $V_u = 2740.264$

From (11.5.4.8), ACI 318-14: $V_s = 148933.273$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$
Mean strength values are used for both shear and moment calculations.
Consequently:
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou}, \min > = 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -8.7724203E-020$

EDGE -B-

Shear Force, $V_b = 8.7724203E-020$

BOTH EDGES

Axial Force, $F = -224.0403$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 603.1858$

-Compression: $A_{sl,c} = 923.6282$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 508.938$

-Compression: $A_{sl,com} = 508.938$

-Middle: $A_{sl,mid} = 508.938$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.77093353$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 117541.903$

with
 $M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 1.0873E+008$
 $M_{u1+} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 1.0873E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 1.0873E+008$
 $M_{u2+} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 1.0873E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with
 $V_1 = -8.7724203E-020$, is the shear force acting at edge 1 for the the static loading combination
 $V_2 = 8.7724203E-020$, is the shear force acting at edge 2 for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00015595$

$M_u = 1.0873E+008$

with full section properties:

$b = 400.00$

d = 258.00

d' = 42.00

v = 0.00010855

N = 224.0403

fc = 20.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00583896$

we (5.4c) = 0.0034192

ase ((5.4d), TBDY) = 0.15672608

bo = 240.00

ho = 340.00

bi2 = 346400.00

psh,min = Min(psh,x , psh,y) = 0.00261799

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x (5.4d) = 0.00349066

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 300.00

psh,y (5.4d) = 0.00261799

Ash = Astir*ns = 78.53982

No stirrups, ns = 2.00

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A5), TBDY), TBDY: $cc = 0.002$

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = $0.4 * \text{esu1_nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $\text{esu1_nominal} = 0.08$,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value $\text{fsy1} = \text{fs1}/1.2$, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with $\text{fs1} = \text{fs} = 555.55$

with $\text{Es1} = \text{Es} = 200000.00$

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = $0.4 * \text{esu2_nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $\text{esu2_nominal} = 0.08$,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value $\text{fsy2} = \text{fs2}/1.2$, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with $\text{fs2} = \text{fs} = 555.55$

with $\text{Es2} = \text{Es} = 200000.00$

yv = 0.00231479

shv = 0.008

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv , shv , ftv , fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1$, $sh1$, $ft1$, $fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = fs = 555.55$$

$$\text{with } Es = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d)*(fs1/fc) = 0.13698668$$

$$2 = Asl_{com}/(b*d)*(fs2/fc) = 0.13698668$$

$$v = Asl_{mid}/(b*d)*(fsv/fc) = 0.13698668$$

and confined core properties:

$$b = 340.00$$

$$d = 228.00$$

$$d' = 12.00$$

$$fcc (5A.2, TBDY) = 20.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl_{ten}/(b*d)*(fs1/fc) = 0.18236617$$

$$2 = Asl_{com}/(b*d)*(fs2/fc) = 0.18236617$$

$$v = Asl_{mid}/(b*d)*(fsv/fc) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.2046582$$

$$Mu = MRc (4.14) = 1.0873E+008$$

$$u = su (4.1) = 0.00015595$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$Mu = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$fc = 20.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00583896$$

$$we (5.4c) = 0.0034192$$

$$ase ((5.4d), TBDY) = 0.15672608$$

$$bo = 240.00$$

$$ho = 340.00$$

$$bi2 = 346400.00$$

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00261799$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x (5.4d) = 0.00349066$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 300.00$$

$$psh,y (5.4d) = 0.00261799$$

$$Ash = Astir*ns = 78.53982$$

$$\text{No stirrups, } ns = 2.00$$

$$bk = 400.00$$

$$s = 150.00$$

$$fywe = 555.55$$

$$fce = 20.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00231479$$

$$sh1 = 0.008$$

$$ft1 = 666.66$$

$$fy1 = 555.55$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_d = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = fs = 555.55$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00231479$$

$$sh2 = 0.008$$

$$ft2 = 666.66$$

$$fy2 = 555.55$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_b,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = fs = 555.55$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00231479$$

$$shv = 0.008$$

$$ftv = 666.66$$

$$fyv = 555.55$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_d = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = f_s = 555.55$
with $E_{sv} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.13698668$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13698668$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.13698668$

and confined core properties:

$b = 340.00$
 $d = 228.00$
 $d' = 12.00$
 $f_{cc} (5A.2, TBDY) = 20.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.18236617$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.18236617$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.18236617$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$\mu_u (4.9) = 0.2046582$
 $\mu_u = M_{Rc} (4.14) = 1.0873E+008$
 $u = \mu_u (4.1) = 0.00015595$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00015595$
 $\mu_u = 1.0873E+008$

with full section properties:

$b = 400.00$
 $d = 258.00$
 $d' = 42.00$
 $v = 0.00010855$
 $N = 224.0403$
 $f_c = 20.00$
 $cc (5A.5, TBDY) = 0.002$
Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, cc) = 0.00583896$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $c_u = 0.00583896$
 $w_e (5.4c) = 0.0034192$
 $a_{se} ((5.4d), TBDY) = 0.15672608$
 $b_o = 240.00$
 $h_o = 340.00$
 $b_{i2} = 346400.00$
 $p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} (5.4d) = 0.00349066$
 $A_{sh} = A_{stir}*n_s = 78.53982$
No stirrups, $n_s = 2.00$
 $b_k = 300.00$

 $p_{sh,y} (5.4d) = 0.00261799$
 $A_{sh} = A_{stir}*n_s = 78.53982$
No stirrups, $n_s = 2.00$

bk = 400.00

s = 150.00

fywe = 555.55

fce = 20.00

From ((5.A.5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00231479

sh1 = 0.008

ft1 = 666.66

fy1 = 555.55

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.18236617$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.18236617$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$s_u(4.9) = 0.2046582$$

$$M_u = M_{Rc}(4.14) = 1.0873E+008$$

$$u = s_u(4.1) = 0.00015595$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u2} -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00015595$$

$$M_u = 1.0873E+008$$

with full section properties:

$$b = 400.00$$

$$d = 258.00$$

$$d' = 42.00$$

$$v = 0.00010855$$

$$N = 224.0403$$

$$f_c = 20.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00583896$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00583896$$

$$w_e(5.4c) = 0.0034192$$

$$a_{se}((5.4d), TBDY) = 0.15672608$$

$$b_o = 240.00$$

$$h_o = 340.00$$

$$b_{i2} = 346400.00$$

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00261799$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}(5.4d) = 0.00349066$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 300.00$$

$$p_{sh,y}(5.4d) = 0.00261799$$

$$A_{sh} = A_{stir} * n_s = 78.53982$$

$$\text{No stirrups, } n_s = 2.00$$

$$b_k = 400.00$$

$$s = 150.00$$

$$f_{ywe} = 555.55$$

$$f_{ce} = 20.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00231479$$

$$sh_1 = 0.008$$

$$f_{t1} = 666.66$$

$$f_{y1} = 555.55$$

$$s_{u1} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = fs = 555.55

with Es1 = Es = 200000.00

y2 = 0.00231479

sh2 = 0.008

ft2 = 666.66

fy2 = 555.55

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = fs = 555.55

with Es2 = Es = 200000.00

yv = 0.00231479

shv = 0.008

ftv = 666.66

fyv = 555.55

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = fs = 555.55

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.13698668

2 = Asl,com/(b*d)*(fs2/fc) = 0.13698668

v = Asl,mid/(b*d)*(fsv/fc) = 0.13698668

and confined core properties:

b = 340.00

d = 228.00

d' = 12.00

fcc (5A.2, TBDY) = 20.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.18236617

2 = Asl,com/(b*d)*(fs2/fc) = 0.18236617

v = Asl,mid/(b*d)*(fsv/fc) = 0.18236617

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2046582

Mu = MRc (4.14) = 1.0873E+008

u = su (4.1) = 0.00015595

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 152466.975$

Calculation of Shear Strength at edge 1, $V_{r1} = 152466.975$
 $V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw + f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 1.8491887E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

Calculation of Shear Strength at edge 2, $V_{r2} = 152466.975$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw + f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 68692.008$
= 1 (normal-weight concrete)
 $f_c' = 20.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s/(b_w*d) = 0.00628319$
 A_s (tension reinf.) = 603.1858
 $b_w = 400.00$
 $d = 240.00$
 $V_u*d/M_u < 1 = 0.00$
 $M_u = 1.8491916E-012$
 $V_u = 8.7724203E-020$

From (11.5.4.8), ACI 318-14: $V_s = 83774.966$
 $A_v = 157079.633$
 $f_y = 444.44$
 $s = 150.00$

V_s has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.75$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 285202.276$

End Of Calculation of Shear Capacity ratio for element: beam B1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1
At local axis: 3
Integration Section: (b)

Section Type: rcars

Constant Properties

Knowledge Factor, $\phi = 0.75$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Section Height, $H = 400.00$

Section Width, $W = 300.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 1850.00$

Secondary Member

Smooth Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -8.9686435E-011$

Shear Force, $V_2 = 5.2893637E-014$

Shear Force, $V_3 = 11865.276$

Axial Force, $F = -766.5227$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 615.7522$

-Compression: $A_{sc} = 911.0619$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 508.938$

-Compression: $A_{st,com} = 508.938$

-Middle: $A_{st,mid} = 508.938$

Mean Diameter of Tension Reinforcement, $D_bL = 14.66667$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = \phi \cdot u = 0.01779661$

$u = y + p = 0.02372882$

- Calculation of y -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.00372882$ ((4.29), Biskinis Phd))

$M_y = 6.8632E+007$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 925.00

From table 10.5, ASCE 41_17: $E_{eff} = 0.3 \cdot E_c \cdot I_g = 5.6751E+012$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 1.2094933E-005$

with $f_y = 444.44$

$d = 258.00$

$y = 0.28786888$

$A = 0.01481142$

$B = 0.00861829$

with $p_t = 0.00493157$
 $p_c = 0.00493157$
 $p_v = 0.00493157$
 $N = 766.5227$
 $b = 400.00$
 $" = 0.1627907$
 $y_{comp} = 2.3070920E-005$
with $f_c = 20.00$
 $E_c = 21019.039$
 $y = 0.28774317$
 $A = 0.01477303$
 $B = 0.00860158$
with $E_s = 200000.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of p -

From table 10-7: $p = 0.02$

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.77093353$

- Transverse Reinforcement: NC

- Stirrup Spacing $> d/3$

- Low ductility demand, $\lambda < 2$ (table 10-6, ASCE 41-17)

$= -1.2886169E-021$

- Stirrup Spacing $> d/2$

$d = 258.00$

$s = 150.00$

- Strength provided by hoops $V_s < 3/4$ *design Shear

$V_s = 111699.955$, already given in calculation of shear control ratio

design Shear = $5.2893637E-014$

- ($\lambda - 1$)/ λ bal = -0.15320593

$= A_{slt}/(b_w*d) = 0.00596659$

Tension Reinf Area: $A_{slt} = 615.7522$

$\lambda = A_{scl}/(b_w*d) = 0.00882812$

Compression Reinf Area: $A_{scl} = 911.0619$

From (B-1), ACI 318-11: λ bal = 0.01867766

$f_c = 20.00$

$f_y = 444.44$

From 10.2.7.3, ACI 318-11: $\lambda = 0.85$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + \lambda) = 0.57447053$

$\lambda = 0.0022222$

- $V/(b_w*d*f_c^{0.5}) = 1.3801680E-018$, NOTE: units in lb & in

$b_w = 400.00$

End Of Calculation of Chord Rotation Capacity for element: beam B1 of floor 1

At local axis: 3

Integration Section: (b)