

Detailed Member Calculations

Units: N&mm

Regulation: ASCE 41-17

Calculation No. 1

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of μ_y for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material: Steel Strength, $f_s = f_{sm} = 444.44$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -2.5637E+007$

Shear Force, $V_a = -8505.401$

EDGE -B-

Bending Moment, $M_b = 116066.848$

Shear Force, $V_b = 8505.401$

BOTH EDGES

Axial Force, $F = -21315.408$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 0.00$

-Compression: $A_{sl,c} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1693.318$

-Compression: $A_{sl,com} = 1693.318$

-Middle: $A_{sl,mid} = 3612.832$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.25$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 1.1749E+006$

V_n ((10.3), ASCE 41-17) = $k_n \phi V_{Col} = 1.1749E+006$

$V_{Col} = 1.1749E+006$

$k_n = 1.00$

$displacement_ductility_demand = 0.02317721$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d/s$ ' is replaced by ' $V_s + \phi \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

 $\phi = 1$ (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 20.80$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 3.96606$
 $\mu_u = 2.5637E+007$
 $V_u = 8505.401$
 $d = 0.8 \cdot h = 760.00$
 $N_u = 21315.408$
 $A_g = 427500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 976155.669$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 879645.943$
 $V_{s,j1} = 282743.339$ is calculated for section web jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.27777778$
 $V_{s,j2} = 596902.604$ is calculated for section flange jacket, with:
 $d = 760.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.13157895$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 96509.726$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 400.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 0.00$
 $s/d = 1.25$
 $V_{s,c2} = 96509.726$ is calculated for section flange core, with:
 $d = 600.00$
 $A_v = 100530.965$
 $f_y = 400.00$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 1.00$
 $s/d = 0.41666667$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 1.0362E+006$
 $bw = 450.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 5.9943546E-005$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.00258631$ ((4.29), Biskinis Phd)
 $M_y = 6.7546E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 3014.205
From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.6241E+014$
 $factor = 0.30$
 $A_g = 562500.00$
Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 26.93333$
 $N = 21315.408$
 $E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 8.7468E+014$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

y = Min(y_ten, y_com)
y_ten = 2.2011335E-006
with ((10.1), ASCE 41-17) fy = Min(fy, 1.25*fy*(lb/d)^ 2/3) = 294.7834
d = 907.00
y = 0.261723
A = 0.01732642
B = 0.0091583
with pt = 0.00414877
pc = 0.00414877
pv = 0.00885172
N = 21315.408
b = 450.00
" = 0.04740904
y_comp = 9.3360319E-006
with fc = 33.00
Ec = 26999.444
y = 0.25981367
A = 0.01703057
B = 0.00898114
with Es = 200000.00

Calculation of ratio lb/d

Inadequate Lap Length with lb/d = 0.30

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 2

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (u)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$

Existing Column
 Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
 Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
 Concrete Elasticity, $E_c = 21019.039$
 Steel Elasticity, $E_s = 200000.00$

 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.45$
 Existing Column
 Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.55$
 #####

Max Height, $H_{max} = 750.00$
 Min Height, $H_{min} = 450.00$
 Max Width, $W_{max} = 950.00$
 Min Width, $W_{min} = 450.00$
 Eccentricity, $Ecc = 250.00$
 Jacket Thickness, $t_j = 100.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.00
 Element Length, $L = 3000.00$

Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_o/l_{o,min} = 0.30$
 No FRP Wrapping

Stepwise Properties

At local axis: 3
 EDGE -A-
 Shear Force, $V_a = -0.0003102$
 EDGE -B-

Shear Force, $V_b = 0.0003102$
BOTH EDGES
Axial Force, $F = -20816.964$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1539.38$
-Compression: $As_{c,com} = 2475.575$
-Middle: $As_{c,mid} = 2984.513$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.5622163$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 614853.514$
with
 $M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 9.2228E+008$
 $Mu_{1+} = 6.6218E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu_{1-} = 9.2228E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 9.2228E+008$
 $Mu_{2+} = 6.6218E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu_{2-} = 9.2228E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 8.5401626E-006$
 $M_u = 6.6218E+008$

with full section properties:

$b = 950.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.00093921$
 $N = 20816.964$
 $f_c = 33.00$
 α_1 (5A.5, TBDY) = 0.002
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.00782179$
 ω_e (5.4c) = 0.01167368
 α_{se} ((5.4d), TBDY) = $(\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.53375773$
 $\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.
 $A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.
 $A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $\alpha_{se2} (\geq \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.
 $A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{s2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{s2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 448.1427$

$fy1 = 373.4523$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lou,min = lb/ld = 0.30$

$su1 = 0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs,jacket * A_{sl,ten,jacket} + fs,core * A_{sl,ten,core}) / A_{sl,ten} = 373.4523$

with $Es1 = (Es,jacket * A_{sl,ten,jacket} + Es,core * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 443.5927$

$fy2 = 369.6606$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lou,min = lb/lb,min = 0.30$

$su2 = 0.4 * esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs,jacket * A_{sl,com,jacket} + fs,core * A_{sl,com,core}) / A_{sl,com} = 369.6606$

with $E_s2 = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 437.9212$
 $fy_v = 364.9343$
 $su_v = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 0.30$
 $su_v = 0.4 \cdot esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fs_yv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_yv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 364.9343$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02593726$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04128785$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04913955$

and confined core properties:

$b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02891269$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04602424$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.05477666$

Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.15202235$
 $Mu = MRc (4.14) = 6.6218E+008$
 $u = su (4.1) = 8.5401626E-006$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 9.2295561E-006$
 $Mu = 9.2228E+008$

 with full section properties:

$b = 450.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.00198277$
 $N = 20816.964$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00782179$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00782179$
 $we (5.4c) = 0.01167368$

$$ase((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((Aconf,max2 - AnoConf2) / Aconf,max2) * (Aconf,min2 / Aconf,max2), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.40578$$

Expression (5.4d) for psh,min * Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.40578$$

$$psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

$$psh2 (5.4d) = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

$$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307$$

$$psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

Lstir1 (Length of stirrups along X) = 2560.00

Astir1 (stirrups area) = 78.53982

$$psh2 ((5.4d), TBDY) = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00

Astir2 (stirrups area) = 50.26548

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.45$$

$$fywe2 = 555.55$$

$$fce = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 443.5927$$

$$fy1 = 369.6606$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s,jacket} \cdot A_{s,ten,jacket} + f_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 369.6606$
 with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 448.1427$
 $fy_2 = 373.4523$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 373.4523$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 437.9212$
 $fy_v = 364.9343$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_d = 0.30$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 364.9343$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08716324$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.05475644$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.10373905$

and confined core properties:

$b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.10502967$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.06598023$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.12500314$

Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->

$su (4.9) = 0.21536129$
 $Mu = MRc (4.14) = 9.2228E+008$
 $u = su (4.1) = 9.2295561E-006$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_{2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 8.5401626E-006$$

$$Mu = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$co(5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$we(5.4c) = 0.01167368$$

$$ase((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$$

$$psh1((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2(5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$$

$$psh1((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.002$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 448.1427$$

$$fy_1 = 373.4523$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 373.4523$$

$$\text{with } Es_1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 443.5927$$

$$fy_2 = 369.6606$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (f_{s,jacket} * A_{s,com,jacket} + f_{s,core} * A_{s,com,core}) / A_{s,com} = 369.6606$$

$$\text{with } Es_2 = (E_{s,jacket} * A_{s,com,jacket} + E_{s,core} * A_{s,com,core}) / A_{s,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 437.9212$$

$$fy_v = 364.9343$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsyv = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 364.9343$$

$$\text{with } Es_v = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (fs_1 / fc) = 0.02593726$$

$$2 = A_{s,com} / (b * d) * (fs_2 / fc) = 0.04128785$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / fc) = 0.04913955$$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s,ten} / (b * d) * (fs_1 / fc) = 0.02891269$$

$$2 = A_{s,com} / (b * d) * (fs_2 / fc) = 0.04602424$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / fc) = 0.05477666$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$\mu_u(4.9) = 0.15202235$

$\mu_u = M/R_c(4.14) = 6.6218E+008$

$u = \mu_u(4.1) = 8.5401626E-006$

Calculation of ratio I_b/I_d

Inadequate Lap Length with $I_b/I_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$\mu_u = 9.2295561E-006$

$\mu_u = 9.2228E+008$

with full section properties:

$b = 450.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00198277$

$N = 20816.964$

$f_c = 33.00$

$\alpha(5A.5, TBDY) = 0.002$

Final value of μ_u : $\mu_u^* = \text{shear_factor} * \text{Max}(\mu_u, \alpha) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.00782179$

$w_e(5.4c) = 0.01167368$

$\alpha_{se}((5.4d), TBDY) = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.53375773$

$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$\alpha_{se2} (>= \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$$\begin{aligned} \text{psh}_2 (5.4d) &= \text{Lstir}_2 * \text{Astir}_2 / (\text{Asec} * s_2) = 0.00056047 \\ \text{Lstir}_2 (\text{Length of stirrups along Y}) &= 1568.00 \\ \text{Astir}_2 (\text{stirrups area}) &= 50.26548 \end{aligned}$$

$$\begin{aligned} \text{psh}_y * \text{Fywe} &= \text{psh}_1 * \text{Fywe}_1 + \text{ps}_2 * \text{Fywe}_2 = 2.87307 \\ \text{psh}_1 ((5.4d), \text{TBDY}) &= \text{Lstir}_1 * \text{Astir}_1 / (\text{Asec} * s_1) = 0.00357443 \\ \text{Lstir}_1 (\text{Length of stirrups along X}) &= 2560.00 \\ \text{Astir}_1 (\text{stirrups area}) &= 78.53982 \\ \text{psh}_2 ((5.4d), \text{TBDY}) &= \text{Lstir}_2 * \text{Astir}_2 / (\text{Asec} * s_2) = 0.00070345 \\ \text{Lstir}_2 (\text{Length of stirrups along X}) &= 1968.00 \\ \text{Astir}_2 (\text{stirrups area}) &= 50.26548 \end{aligned}$$

$$\text{Asec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$\text{fywe}_1 = 694.45$$

$$\text{fywe}_2 = 555.55$$

$$\text{fce} = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 443.5927$$

$$fy_1 = 369.6606$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lo_{\min} = lb/ld = 0.30$$

$$su_1 = 0.4 * esu_{1_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1_nominal} = 0.08$,

For calculation of $esu_{1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{\text{jacket}} * Asl_{\text{ten,jacket}} + fs_{\text{core}} * Asl_{\text{ten,core}}) / Asl_{\text{ten}} = 369.6606$$

$$\text{with } Es_1 = (Es_{\text{jacket}} * Asl_{\text{ten,jacket}} + Es_{\text{core}} * Asl_{\text{ten,core}}) / Asl_{\text{ten}} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 448.1427$$

$$fy_2 = 373.4523$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lo_{\min} = lb/lb_{\min} = 0.30$$

$$su_2 = 0.4 * esu_{2_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,

For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{\text{jacket}} * Asl_{\text{com,jacket}} + fs_{\text{core}} * Asl_{\text{com,core}}) / Asl_{\text{com}} = 373.4523$$

$$\text{with } Es_2 = (Es_{\text{jacket}} * Asl_{\text{com,jacket}} + Es_{\text{core}} * Asl_{\text{com,core}}) / Asl_{\text{com}} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 437.9212$$

$$fy_v = 364.9343$$

$$su_v = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lo_{\min} = lb/ld = 0.30$$

$$su_v = 0.4 * esu_{v_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{v_nominal} = 0.08$,

considering characteristic value $fsy_v = fs_v/1.2$, from table 5.1, TBDY

For calculation of $esu_{v_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $fsy_v = fs_v/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 364.9343$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08716324$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.05475644$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.10373905$

and confined core properties:

$b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.10502967$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.06598023$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.12500314$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$\mu (4.9) = 0.21536129$
 $\mu = M_{Rc} (4.14) = 9.2228E+008$
 $u = \mu (4.1) = 9.2295561E-006$

 Calculation of ratio l_b / l_d

 Inadequate Lap Length with $l_b / l_d = 0.30$

 Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0936E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0936E+006$

$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$

$V_{Col0} = 1.0936E+006$

$k_{nl} = 1$ (zero step-static loading)

 NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_{s+} = f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} < = 8.3$ MPa (22.5.3.1, ACI 318-14)

$M / Vd = 4.00$

$\mu_u = 867.5146$

$\nu_u = 0.0003102$

$d = 0.8 \cdot h = 600.00$

$N_u = 20816.964$

$A_g = 337500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 916401.511$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 837764.743$

$V_{s,j1} = 523602.964$ is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.27777778$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$$

$V_{s,c1} = 78636.768$ is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 0.00$

$$s/d = 1.25$$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 930841.148$

$$bw = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0936E+006$

$V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{ColO}$

$$V_{ColO} = 1.0936E+006$$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 26.93333$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 867.5146$$

$$V_u = 0.0003102$$

$$d = 0.8 * h = 600.00$$

$$N_u = 20816.964$$

$$A_g = 337500.00$$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 916401.511$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 837764.743$$

$V_{s,j1} = 523602.964$ is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.27777778$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$$

$V_{s,c1} = 78636.768$ is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

s = 250.00
Vs,c2 is multiplied by Col,c2 = 0.00
s/d = 1.25
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 930841.148
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 1.00
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Secondary Member: Concrete Strength, fc = fcm = 33.00
New material of Secondary Member: Steel Strength, fs = fsm = 555.56
Concrete Elasticity, Ec = 26999.444
Steel Elasticity, Es = 200000.00
Existing Column
Existing material of Secondary Member: Concrete Strength, fc = fcm = 20.00
Existing material of Secondary Member: Steel Strength, fs = fsm = 444.44
Concrete Elasticity, Ec = 21019.039
Steel Elasticity, Es = 200000.00

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket
New material: Steel Strength, fs = 1.25*fsm = 694.45
Existing Column
Existing material: Steel Strength, fs = 1.25*fsm = 555.55
#####

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.00
Element Length, L = 3000.00

Secondary Member

Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with lo/lo,min = 0.30
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -2.7331429E-008
EDGE -B-
Shear Force, Vb = 2.7331429E-008

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{s,ten} = 1693.318$

-Compression: $A_{s,com} = 1693.318$

-Middle: $A_{s,mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.42425297$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 650163.608$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 9.7525E+008$

$M_{u1+} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 9.7525E+008$

$M_{u2+} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 6.9050030E-006$

$M_u = 9.7525E+008$

with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.00154555$

$N = 20816.964$

$f_c = 33.00$

$\omega (5A.5, \text{TBDY}) = 0.002$

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00782179$

$\omega_e (5.4c) = 0.01167368$

$\omega_{ase} ((5.4d), \text{TBDY}) = (\omega_{ase1} * A_{ext} + \omega_{ase2} * A_{int}) / A_{sec} = 0.53375773$

$\omega_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$\omega_{ase2} (>= \omega_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 441.3522$

$fy1 = 367.7935$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.7935$

with $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 441.3522$

$fy2 = 367.7935$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 367.7935$

with $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00140044
shv = 0.0044814
ftv = 442.9465
fyv = 369.1221
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905

2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905

v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112

and confined core properties:

b = 390.00

d = 877.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782

2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782

v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.18247922

Mu = MRc (4.14) = 9.7525E+008

u = su (4.1) = 6.9050030E-006

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 6.9050030E-006

Mu = 9.7525E+008

with full section properties:

b = 450.00

d = 907.00

d' = 43.00

v = 0.00154555

N = 20816.964

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00782179

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00782179

we (5.4c) = 0.01167368

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1)/Aconf,max1) * (Aconf,min1/Aconf,max1), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 2.40578$$

Expression (5.4d) for psh,min*Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.40578$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1*Astir1/(Asec*s1) = 0.00301593$$

$$Lstir1 \text{ (Length of stirrups along Y)} = 2160.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = Lstir2*Astir2/(Asec*s2) = 0.00056047$$

$$Lstir2 \text{ (Length of stirrups along Y)} = 1568.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.87307$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1*Astir1/(Asec*s1) = 0.00357443$$

$$Lstir1 \text{ (Length of stirrups along X)} = 2560.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2*Astir2/(Asec*s2) = 0.00070345$$

$$Lstir2 \text{ (Length of stirrups along X)} = 1968.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.45$$

$$fywe2 = 555.55$$

$$fce = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4*esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935$$

with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.3522$
 $fy_2 = 367.7935$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} \cdot A_{s,com,jacket} + fs_{core} \cdot A_{s,com,core}) / A_{s,com} = 367.7935$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 442.9465$
 $fy_v = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_d = 0.30$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 369.1221$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / f_c) = 0.04623905$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / f_c) = 0.04623905$
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / f_c) = 0.09901112$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / f_c) = 0.05517782$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / f_c) = 0.05517782$
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / f_c) = 0.11815159$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_s, y_2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.18247922$
 $M_u = MR_c (4.14) = 9.7525E+008$
 $u = su (4.1) = 6.9050030E-006$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of M_u2+

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$\mu = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$\omega (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00782179$$

$$\omega_e (5.4c) = 0.01167368$$

$$\text{ase ((5.4d), TBDY) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.53375773$$

$$\text{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1})/A_{conf,max1}) * (A_{conf,min1}/A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{ase2} (>= \text{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{psh}_{min} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $\text{psh}_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.40578$$

$$\text{psh}_1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.87307$$

$$\text{psh}_1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.002$
 $c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_jacket * Asl,ten,jacket + fs_core * Asl,ten,core) / Asl,ten = 367.7935$$

$$\text{with } Es1 = (Es_jacket * Asl,ten,jacket + Es_core * Asl,ten,core) / Asl,ten = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 441.3522$$

$$fy2 = 367.7935$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_jacket * Asl,com,jacket + fs_core * Asl,com,core) / Asl,com = 367.7935$$

$$\text{with } Es2 = (Es_jacket * Asl,com,jacket + Es_core * Asl,com,core) / Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 442.9465$$

$$fyv = 369.1221$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_jacket * Asl,mid,jacket + fs_mid * Asl,mid,core) / Asl,mid = 369.1221$$

$$\text{with } Esv = (Es_jacket * Asl,mid,jacket + Es_mid * Asl,mid,core) / Asl,mid = 200000.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.04623905$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.04623905$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.05517782$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.05517782$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.18247922$$

$$\mu_u = MR_c(4.14) = 9.7525E+008$$

$$u = s_u(4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$\mu_u = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e(5.4c) = 0.01167368$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1}(\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1}(\text{stirrups area}) = 78.53982$$

$$p_{sh2}(5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 2.87307
psh₁ ((5.4d), TBDY) = Lstir₁*Astir₁/(Asec*s₁) = 0.00357443
Lstir₁ (Length of stirrups along X) = 2560.00
Astir₁ (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = Lstir₂*Astir₂/(Asec*s₂) = 0.00070345
Lstir₂ (Length of stirrups along X) = 1968.00
Astir₂ (stirrups area) = 50.26548

Asec = 562500.00
s₁ = 100.00
s₂ = 250.00

fywe₁ = 694.45
fywe₂ = 555.55
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.3522
fy₁ = 367.7935
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*Asl_{ten,jacket} + fs_{core}*Asl_{ten,core})/Asl_{ten} = 367.7935

with Es₁ = (Es_{jacket}*Asl_{ten,jacket} + Es_{core}*Asl_{ten,core})/Asl_{ten} = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814

ft₂ = 441.3522
fy₂ = 367.7935

su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 0.30

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*Asl_{com,jacket} + fs_{core}*Asl_{com,core})/Asl_{com} = 367.7935

with Es₂ = (Es_{jacket}*Asl_{com,jacket} + Es_{core}*Asl_{com,core})/Asl_{com} = 200000.00

y_v = 0.00140044
sh_v = 0.0044814

ft_v = 442.9465
fy_v = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_{nominal} = 0.08,

considering characteristic value fsy_v = fs_v/1.2, from table 5.1, TBDY
For calculation of esuv_{nominal} and y_v, sh_v,ft_v,fy_v, it is considered

characteristic value fsy_v = fs_v/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs_v = (fs_{jacket}*Asl_{mid,jacket} + fs_{mid}*Asl_{mid,core})/Asl_{mid} = 369.1221

$$\text{with } E_{sv} = (E_{s,jacket} \cdot A_{sl,mid,jacket} + E_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.04623905$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04623905$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.05517782$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.05517782$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$M_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.5325E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.5325E+006$

$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$

$$V_{Col0} = 1.5325E+006$$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_{s+} = f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_c \cdot A_{jacket} + f'_c \cdot A_{core}) / A_{section} = 26.93333$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$M_u = 0.70443303$$

$$V_u = 2.7331429E-008$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$

$$bw = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.5325E+006$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} * V_{Col0}$

$$V_{Col0} = 1.5325E+006$$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$\mu_u = 0.70507494$$

$$V_u = 2.7331429E-008$$

$$d = 0.8 * h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

V_{s,c2} is multiplied by Col,c2 = 1.00
s/d = 0.41666667
V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: V_s + V_f <= 1.1791E+006
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (a)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, γ = 1.00
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$
Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$
Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $E_{cc} = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 95856.98$
Shear Force, $V_2 = -8505.401$
Shear Force, $V_3 = -47.78617$
Axial Force, $F = -21315.408$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 0.00$
-Compression: $A_{sl,c} = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 1539.38$
-Compression: $A_{sl,com} = 2475.575$
-Middle: $A_{sl,mid} = 2984.513$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten,jacket} = 1231.504$
-Compression: $A_{sl,com,jacket} = 1859.823$

-Middle: $Asl, mid, jacket = 2060.885$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl, ten, core = 307.8761$

-Compression: $Asl, com, core = 615.7522$

-Middle: $Asl, mid, core = 923.6282$

Mean Diameter of Tension Reinforcement, $DbL = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u, R = * u = 0.00185794$

$u = y + p = 0.00185794$

- Calculation of y -

$y = (My * Ls / 3) / Eleff = 0.00185794$ ((4.29), Biskinis Phd))

$My = 4.8184E+008$

$Ls = M/V$ (with $Ls > 0.1 * L$ and $Ls < 2 * L$) = 2005.957

From table 10.5, ASCE 41_17: $Eleff = factor * Ec * Ig = 1.7341E+014$

factor = 0.30

$Ag = 562500.00$

Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 26.93333$

$N = 21315.408$

$Ec * Ig = Ec_{jacket} * Ig_{jacket} + Ec_{core} * Ig_{core} = 5.7803E+014$

Calculation of Yielding Moment My

Calculation of y and My according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, $b = 950.00$

web width, $bw = 450.00$

flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 2.6210819E-006$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (lb/d)^{2/3}) = 294.7834$

$d = 707.00$

$y = 0.20462306$

$A = 0.01052896$

$B = 0.00498068$

with $pt = 0.00229194$

$pc = 0.00368581$

$pv = 0.00444355$

$N = 21315.408$

$b = 950.00$

$" = 0.06082037$

$y_{comp} = 1.5347948E-005$

with $fc = 33.00$

$Ec = 26999.444$

$y = 0.20275047$

$A = 0.01034918$

$B = 0.00487302$

with $Es = 200000.00$

CONFIRMATION: $y = 0.20363296 < t/d$

Calculation of ratio lb/d

Inadequate Lap Length with $lb/d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_{yE}/V_{Col0E} = 0.5622163$

$d = d_{external} = 707.00$

$s = s_{external} = 0.00$

- $t = s_1 + s_2 + 2 \cdot t_f/bw \cdot (f_{fe}/f_s) = 0.0035764$

jacket: $s_1 = A_{v1} \cdot L_{stir1}/(s_1 \cdot A_g) = 0.00301593$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2160.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot L_{stir2}/(s_2 \cdot A_g) = 0.00056047$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1568.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 \cdot t_f/bw \cdot (f_{fe}/f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f/bw$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe}/f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 21315.408$

$A_g = 562500.00$

$f_{cE} = (f_{c,jacket} \cdot Area_{jacket} + f_{c,core} \cdot Area_{core})/section_area = 26.93333$

$f_{yE} = (f_{y,ext_Long_Reinf} \cdot Area_{ext_Long_Reinf} + f_{y,int_Long_Reinf} \cdot Area_{int_Long_Reinf})/Area_{Tot_Long_Rein} = 526.2339$

$f_{yE} = (f_{y,ext_Trans_Reinf} \cdot s_1 + f_{y,int_Trans_Reinf} \cdot s_2)/(s_1 + s_2) = 538.146$

$p_l = Area_{Tot_Long_Rein}/(b \cdot d) = 0.0104213$

$b = 950.00$

$d = 707.00$

$f_{cE} = 26.93333$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 3

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material: Steel Strength, $f_s = f_{sm} = 444.44$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 95856.98$
 Shear Force, $V_a = -47.78617$
 EDGE -B-
 Bending Moment, $M_b = 48364.752$
 Shear Force, $V_b = 47.78617$
 BOTH EDGES
 Axial Force, $F = -21315.408$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 0.00$
 -Compression: $A_{sc} = 6999.468$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 1539.38$
 -Compression: $A_{sc,com} = 2475.575$
 -Middle: $A_{st,mid} = 2984.513$
 Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 1.0047E+006$
 V_n ((10.3), ASCE 41-17) = $k_n I V_{CoI0} = 1.0047E+006$
 $V_{CoI} = 1.0047E+006$
 $k_n I = 1.00$
 displacement_ductility_demand = 0.00639268

NOTE: In expression (10-3) ' $V_s = A_v f_y d / s$ ' is replaced by ' $V_s + \phi V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$\phi = 1$ (normal-weight concrete)
 Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 20.80$, but $f'_c^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M / Vd = 3.34326$
 $M_u = 95856.98$
 $V_u = 47.78617$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 21315.408$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 824756.036$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 753982.237$
 $V_{s,j1} = 471238.898$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 282743.339$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 70773.799$
 $V_{s,c1} = 70773.799$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 400.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 400.00$
 $s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 818016.733$
 $bw = 450.00$

displacement ductility demand is calculated as ϕ / y

- Calculation of ϕ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 1.1877232E-005$
 $y = (M_y * L_s / 3) / E_{eff} = 0.00185794$ ((4.29), Biskinis Phd)
 $M_y = 4.8184E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 2005.957
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7341E+014$
 $factor = 0.30$
 $A_g = 562500.00$
Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333$
 $N = 21315.408$
 $E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 5.7803E+014$

Calculation of Yielding Moment M_y

Calculation of ϕ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:
flange width, $b = 950.00$
web width, $bw = 450.00$
flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 2.6210819E-006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 294.7834$
 $d = 707.00$
 $y = 0.20462306$
 $A = 0.01052896$
 $B = 0.00498068$
with $pt = 0.00229194$
 $pc = 0.00368581$
 $p_v = 0.00444355$
 $N = 21315.408$
 $b = 950.00$
 $" = 0.06082037$
 $y_{comp} = 1.5347948E-005$
with $f_c = 33.00$
 $E_c = 26999.444$
 $y = 0.20275047$
 $A = 0.01034918$
 $B = 0.00487302$
with $E_s = 200000.00$
CONFIRMATION: $y = 0.20363296 < t/d$

Calculation of ratio I_b / I_d

Inadequate Lap Length with $I_b / I_d = 0.30$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 4

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.00
Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, Va = -0.0003102
EDGE -B-
Shear Force, Vb = 0.0003102
BOTH EDGES
Axial Force, F = -20816.964
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 0.00
-Compression: Asc = 6999.468
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1539.38
-Compression: Asl,com = 2475.575
-Middle: Asl,mid = 2984.513

Calculation of Shear Capacity ratio , $V_e/V_r = 0.5622163$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 614853.514$
with
 $M_{pr1} = \text{Max}(Mu_{1+} , Mu_{1-}) = 9.2228E+008$
 $Mu_{1+} = 6.6218E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 9.2228E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+} , Mu_{2-}) = 9.2228E+008$
 $Mu_{2+} = 6.6218E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 9.2228E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 8.5401626E-006$
 $M_u = 6.6218E+008$

with full section properties:
 $b = 950.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.00093921$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of $A_{noConf1}$, $A_{conf,min1}$ and $A_{conf,max1}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.87307$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 448.1427$$

$$fy1 = 373.4523$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 373.4523

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 443.5927

fy2 = 369.6606

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 369.6606

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.02593726

2 = Asl,com/(b*d)*(fs2/fc) = 0.04128785

v = Asl,mid/(b*d)*(fsv/fc) = 0.04913955

and confined core properties:

b = 890.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.02891269

2 = Asl,com/(b*d)*(fs2/fc) = 0.04602424

v = Asl,mid/(b*d)*(fsv/fc) = 0.05477666

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.15202235

Mu = MRc (4.14) = 6.6218E+008

u = su (4.1) = 8.5401626E-006

Calculation of ratio lb/d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 9.2295561E-006$$

$$\mu_u = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (\geq a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 443.5927

fy1 = 369.6606

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 369.6606

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 448.1427

fy2 = 373.4523

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 373.4523

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08716324

2 = Asl,com/(b*d)*(fs2/fc) = 0.05475644

v = Asl,mid/(b*d)*(fsv/fc) = 0.10373905

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.10502967$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.06598023$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.12500314$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.21536129$$

$$Mu = MRc (4.14) = 9.2228E+008$$

$$u = su (4.1) = 9.2295561E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 8.5401626E-006$$

$$Mu = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$fc = 33.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min * F_{ywe} = \text{Min}(psh,x * F_{ywe}, psh,y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $psh_{min} \cdot F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x \cdot F_{ywe} = psh1 \cdot F_{ywe1} + ps2 \cdot F_{ywe2} = 2.40578$$
$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 \cdot Astir1 / (Asec \cdot s1) = 0.00301593$$

Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ (5.4d)} = Lstir2 \cdot Astir2 / (Asec \cdot s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

$$psh_y \cdot F_{ywe} = psh1 \cdot F_{ywe1} + ps2 \cdot F_{ywe2} = 2.87307$$
$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 \cdot Astir1 / (Asec \cdot s1) = 0.00357443$$

Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2 \cdot Astir2 / (Asec \cdot s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.45$$

$$fywe2 = 555.55$$

$$fce = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c =$ confinement factor = 1.00

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 448.1427$$

$$fy1 = 373.4523$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/ld = 0.30$$

$$su1 = 0.4 \cdot esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_{jacket} \cdot A_{sl,ten,jacket} + fs_{core} \cdot A_{sl,ten,core}) / A_{sl,ten} = 373.4523$$

$$\text{with } Es1 = (Es_{jacket} \cdot A_{sl,ten,jacket} + Es_{core} \cdot A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 443.5927$$

$$fy2 = 369.6606$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/lb_{min} = 0.30$$

$$su2 = 0.4 \cdot esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 369.6606$$

$$\text{with } Es2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 437.9212$$

$$fyv = 364.9343$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and γ_v , sh_v, ft_v, fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

$\gamma_1, sh_1, ft_1, fy_1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 364.9343$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.02593726$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04128785$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.04913955$$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

c = confinement factor = 1.00

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.02891269$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04602424$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.05477666$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.15202235$$

$$M_u = M_{Rc} (4.14) = 6.6218E+008$$

$$u = s_u (4.1) = 8.5401626E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_2 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 9.2295561E-006$$

$$M_u = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.00782179$$

$$\text{we (5.4c) } = 0.01167368$$

$$\text{ase ((5.4d), TBDY) } = (\text{ase}_1 * A_{ext} + \text{ase}_2 * A_{int}) / A_{sec} = 0.53375773$$

$$\text{ase}_1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $bi^2/6$ as defined at (A.2).
ase2 (\geq ase1) = $\text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $bi^2/6$ as defined at (A.2).
psh,min*Fywe = $\text{Min}(psh,x*Fywe, psh,y*Fywe) = 2.40578$

Expression (5.4d) for psh,min*Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.40578
psh1 ((5.4d), TBDY) = $Lstir1 * Astir1 / (Asec * s1) = 0.00301593$

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = $Lstir2 * Astir2 / (Asec * s2) = 0.00056047$

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.87307
psh1 ((5.4d), TBDY) = $Lstir1 * Astir1 / (Asec * s1) = 0.00357443$

Lstir1 (Length of stirrups along X) = 2560.00

Astir1 (stirrups area) = 78.53982

psh2 ((5.4d), TBDY) = $Lstir2 * Astir2 / (Asec * s2) = 0.00070345$

Lstir2 (Length of stirrups along X) = 1968.00

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 443.5927

fy1 = 369.6606

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su1 = $0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_jacket * Asl,ten,jacket + fs_core * Asl,ten,core) / Asl,ten = 369.6606$

with Es1 = $(Es_jacket * Asl,ten,jacket + Es_core * Asl,ten,core) / Asl,ten = 200000.00$

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 448.1427

fy2 = 373.4523

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 373.4523

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08716324

2 = Asl,com/(b*d)*(fs2/fc) = 0.05475644

v = Asl,mid/(b*d)*(fsv/fc) = 0.10373905

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.10502967

2 = Asl,com/(b*d)*(fs2/fc) = 0.06598023

v = Asl,mid/(b*d)*(fsv/fc) = 0.12500314

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.21536129

Mu = MRc (4.14) = 9.2228E+008

u = su (4.1) = 9.2295561E-006

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 1.0936E+006

Calculation of Shear Strength at edge 1, Vr1 = 1.0936E+006

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0

VCol0 = 1.0936E+006

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 867.5146$
 $\nu_u = 0.0003102$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 20816.964$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 916401.511$
where:
 $V_{sjacket} = V_{sj1} + V_{sj2} = 837764.743$
 $V_{sj1} = 523602.964$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{sj1} is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{sj2} = 314161.779$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{sj2} is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$
 $V_{s,c1} = 78636.768$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 930841.148$
 $bw = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0936E+006$

$V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl \cdot V_{Col0}$

$V_{Col0} = 1.0936E+006$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 867.5146$

$\nu_u = 0.0003102$

$d = 0.8 \cdot h = 600.00$

$N_u = 20816.964$

$A_g = 337500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 916401.511$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 837764.743$

$V_{sj1} = 523602.964$ is calculated for section web jacket, with:

$d = 600.00$

Av = 157079.633

fy = 555.56

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.16666667

Vs,j2 = 314161.779 is calculated for section flange jacket, with:

d = 360.00

Av = 157079.633

fy = 555.56

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.27777778

Vs,core = Vs,c1 + Vs,c2 = 78636.768

Vs,c1 = 78636.768 is calculated for section web core, with:

d = 440.00

Av = 100530.965

fy = 444.44

s = 250.00

Vs,c1 is multiplied by Col,c1 = 1.00

s/d = 0.56818182

Vs,c2 = 0.00 is calculated for section flange core, with:

d = 200.00

Av = 100530.965

fy = 444.44

s = 250.00

Vs,c2 is multiplied by Col,c2 = 0.00

s/d = 1.25

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 930841.148

bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, fc = fcm = 33.00

New material of Secondary Member: Steel Strength, fs = fsm = 555.56

Concrete Elasticity, Ec = 26999.444

Steel Elasticity, Es = 200000.00

Existing Column

Existing material of Secondary Member: Concrete Strength, fc = fcm = 20.00

Existing material of Secondary Member: Steel Strength, fs = fsm = 444.44

Concrete Elasticity, Ec = 21019.039

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, fs = 1.25*fsm = 694.45

Existing Column

Existing material: Steel Strength, fs = 1.25*fsm = 555.55

#####

Max Height, Hmax = 750.00

Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.00
Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min}$ = 0.30
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -2.7331429E-008
EDGE -B-
Shear Force, Vb = 2.7331429E-008
BOTH EDGES
Axial Force, F = -20816.964
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 0.00
-Compression: Aslc = 6999.468
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1693.318
-Compression: Asl,com = 1693.318
-Middle: Asl,mid = 3612.832

Calculation of Shear Capacity ratio , V_e/V_r = 0.42425297
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 650163.608$
with
 $M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 9.7525E+008$
 $\mu_{1+} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{1-} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 9.7525E+008$
 $\mu_{2+} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $\mu_{2-} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 6.9050030E-006$
 $M_u = 9.7525E+008$

with full section properties:

b = 450.00
d = 907.00
d' = 43.00
v = 0.00154555
N = 20816.964

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

$$\text{Shear_factor} = 1.00$$

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{s1_nominal} = 0.08,$$

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } f_{s1} = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 367.7935$$

$$\text{with } E_{s1} = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.3522$$

$$fy_2 = 367.7935$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{s2_nominal} = 0.08,$$

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

$$y_2, sh_2, ft_2, fy_2, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } f_{s2} = (f_{s,jacket} * A_{s,com,jacket} + f_{s,core} * A_{s,com,core}) / A_{s,com} = 367.7935$$

$$\text{with } E_{s2} = (E_{s,jacket} * A_{s,com,jacket} + E_{s,core} * A_{s,com,core}) / A_{s,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 442.9465$$

$$fy_v = 369.1221$$

$$s_{uv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{suv_nominal} = 0.08,$$

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY For calculation of $e_{suv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 369.1221$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.04623905$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04623905$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.05517782$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.05517782$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$\mu_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 6.9050030E-006$$

$$\text{Mu} = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_o) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.3522

fy1 = 367.7935

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fsjacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.3522

fy2 = 367.7935

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fsjacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 442.9465

fyv = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905

2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905

v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112

and confined core properties:

b = 390.00

d = 877.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05517782$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.05517782$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->
v < v_{s,y2} - LHS eq.(4.5) is satisfied

$$\text{su (4.9)} = 0.18247922$$

$$\text{Mu} = \text{MRc (4.14)} = 9.7525\text{E}+008$$

$$u = \text{su (4.1)} = 6.9050030\text{E}-006$$

Calculation of ratio lb/l_d

Inadequate Lap Length with lb/l_d = 0.30

Calculation of Mu₂₊

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030\text{E}-006$$

$$\text{Mu} = 9.7525\text{E}+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $cu = 0.00782179$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$ase \text{ ((5.4d), TBDY)} = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf}, A_{conf,min} and A_{conf,max} are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

A_{conf,max1} = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

A_{conf,min1} = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area A_{conf,max1} by a length equal to half the clear spacing between external hoops.

A_{noConf1} = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf}, A_{conf,min} and A_{conf,max} are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

A_{conf,max2} = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

A_{conf,min2} = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area A_{conf,max2} by a length equal to half the clear spacing between internal hoops.

A_{noConf2} = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without

earthquake detailing (90° closed stirrups)

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.40578
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00301593
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
psh2 (5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.87307
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00357443
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00070345
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.3522

fy1 = 367.7935

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.3522

fy2 = 367.7935

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 442.9465

fyv = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1,ft1,fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_jacket * Asl_mid_jacket + fs_mid * Asl_mid_core) / Asl_mid = 369.1221$$

$$\text{with } Esv = (Es_jacket * Asl_mid_jacket + Es_mid * Asl_mid_core) / Asl_mid = 200000.00$$

$$1 = Asl_ten / (b * d) * (fs1 / fc) = 0.04623905$$

$$2 = Asl_com / (b * d) * (fs2 / fc) = 0.04623905$$

$$v = Asl_mid / (b * d) * (fsv / fc) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$c =$ confinement factor = 1.00

$$1 = Asl_ten / (b * d) * (fs1 / fc) = 0.05517782$$

$$2 = Asl_com / (b * d) * (fs2 / fc) = 0.05517782$$

$$v = Asl_mid / (b * d) * (fsv / fc) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.18247922$$

$$Mu = MRc (4.14) = 9.7525E+008$$

$$u = su (4.1) = 6.9050030E-006$$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of $Mu2$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$Mu = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$fc = 33.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = shear_factor * Max(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$we (5.4c) = 0.01167368$$

$$ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = Max(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of $AnoConf$, $Aconf,min$ and $Aconf,max$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$Aconf,max1 = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$Aconf,min1 = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$
 p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.87307$
 p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.3522$

$fy_1 = 367.7935$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu_{1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 367.7935$

with $Es_1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 441.3522$

$fy_2 = 367.7935$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s_u2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_u2,nominal} = 0.08$,

For calculation of $e_{s_u2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{s_y2} = f_{s_2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s_2} = (f_{s,jacket} * A_{s_l,com,jacket} + f_{s,core} * A_{s_l,com,core}) / A_{s_l,com} = 367.7935$$

$$\text{with } E_{s_2} = (E_{s,jacket} * A_{s_l,com,jacket} + E_{s,core} * A_{s_l,com,core}) / A_{s_l,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 442.9465$$

$$fy_v = 369.1221$$

$$s_{u_v} = 0.00512$$

using (30) in Bisikinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_d = 0.30$$

$$s_{u_v} = 0.4 * e_{s_{u_v},nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_{u_v},nominal} = 0.08$,

considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u_v},nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s_v} = (f_{s,jacket} * A_{s_l,mid,jacket} + f_{s,mid} * A_{s_l,mid,core}) / A_{s_l,mid} = 369.1221$$

$$\text{with } E_{s_v} = (E_{s,jacket} * A_{s_l,mid,jacket} + E_{s,mid} * A_{s_l,mid,core}) / A_{s_l,mid} = 200000.00$$

$$1 = A_{s_l,ten} / (b * d) * (f_{s_1} / f_c) = 0.04623905$$

$$2 = A_{s_l,com} / (b * d) * (f_{s_2} / f_c) = 0.04623905$$

$$v = A_{s_l,mid} / (b * d) * (f_{s_v} / f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s_l,ten} / (b * d) * (f_{s_1} / f_c) = 0.05517782$$

$$2 = A_{s_l,com} / (b * d) * (f_{s_2} / f_c) = 0.05517782$$

$$v = A_{s_l,mid} / (b * d) * (f_{s_v} / f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y_2}$ - LHS eq.(4.5) is satisfied

---->

$$s_u (4.9) = 0.18247922$$

$$M_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.5325E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.5325E+006$

$$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = k_{nl} * V_{Co10}$$

$$V_{Co10} = 1.5325E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} = f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333, \text{ but } f_c'^{0.5} < =$$

8.3 MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$\mu_u = 0.70443303$$

$$V_u = 2.7331429E+008$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 1.1791E+006$$

$$bw = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.5325E+006$

$$V_{r2} = V_{Col} \text{ ((10.3), ASCE 41-17)} = knl \cdot V_{Col0}$$

$$V_{Col0} = 1.5325E+006$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333, \text{ but } f_c'^{0.5} \leq$$

8.3 MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$\mu_u = 0.70507494$$

$$V_u = 2.7331429E+008$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$f_y = 555.56$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$s/d = 1.25$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$s/d = 0.41666667$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$

$bw = 450.00$

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -2.5637E+007$
Shear Force, $V2 = -8505.401$
Shear Force, $V3 = -47.78617$
Axial Force, $F = -21315.408$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1693.318$
-Compression: $As_{c,com} = 1693.318$
-Middle: $As_{c,mid} = 3612.832$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten,jacket} = 1231.504$
-Compression: $As_{c,com,jacket} = 1231.504$
-Middle: $As_{c,mid,jacket} = 2689.203$
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten,core} = 461.8141$
-Compression: $As_{c,com,core} = 461.8141$
-Middle: $As_{c,mid,core} = 923.6282$
Mean Diameter of Tension Reinforcement, $Db_L = 16.25$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $\phi_{u,R} = \phi_u = 0.00258631$
 $\phi_u = \phi_y + \phi_p = 0.00258631$

- Calculation of ϕ_y -

$\phi_y = (M_y \cdot L_s / 3) / E_{eff} = 0.00258631$ ((4.29), Biskinis Phd)
 $M_y = 6.7546E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 3014.205
From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.6241E+014$
factor = 0.30
 $A_g = 562500.00$
Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 26.93333$
 $N = 21315.408$
 $E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 8.7468E+014$

Calculation of Yielding Moment M_y

Calculation of ϕ_y and M_y according to Annex 7 -

$\phi_y = \text{Min}(\phi_{y,ten}, \phi_{y,com})$
 $\phi_{y,ten} = 2.2011335E-006$
with ((10.1), ASCE 41-17) $\phi_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 294.7834$
 $d = 907.00$
 $\phi_y = 0.261723$
 $A = 0.01732642$
 $B = 0.0091583$
with $pt = 0.00414877$
 $pc = 0.00414877$
 $pv = 0.00885172$
 $N = 21315.408$

$b = 450.00$
 $\mu = 0.04740904$
 $y_{comp} = 9.3360319E-006$
 with $f_c = 33.00$
 $E_c = 26999.444$
 $y = 0.25981367$
 $A = 0.01703057$
 $B = 0.00898114$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of ρ -

From table 10-8: $\rho = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.42425297$

$d = d_{external} = 907.00$

$s = s_{external} = 0.00$

- $t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00427788$

jacket: $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00357443$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2560.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00070345$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1968.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 21315.408$

$A_g = 562500.00$

$f_{cE} = (f_{c,jacket} * Area_{jacket} + f_{c,core} * Area_{core}) / section_area = 26.93333$

$f_{yE} = (f_{y,ext_Long_Reinf} * Area_{ext_Long_Reinf} + f_{y,int_Long_Reinf} * Area_{int_Long_Reinf}) / Area_{Tot_Long_Rein} = 526.2339$

$f_{yE} = (f_{y,ext_Trans_Reinf} * s_1 + f_{y,int_Trans_Reinf} * s_2) / (s_1 + s_2) = 537.2876$

$\rho_l = Area_{Tot_Long_Rein} / (b * d) = 0.01714926$

$b = 450.00$

$d = 907.00$

$f_{cE} = 26.93333$

 End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 5

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material: Steel Strength, $f_s = f_{sm} = 444.44$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -2.5637E+007$
Shear Force, $V_a = -8505.401$
EDGE -B-
Bending Moment, $M_b = 116066.848$
Shear Force, $V_b = 8505.401$
BOTH EDGES
Axial Force, $F = -21315.408$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 0.00$
-Compression: $A_{sl,c} = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 1693.318$
-Compression: $A_{sl,com} = 1693.318$
-Middle: $A_{sl,mid} = 3612.832$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.25$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = *V_n = 1.3703E+006$
 V_n ((10.3), ASCE 41-17) = $knI*V_{CoI} = 1.3703E+006$
 $V_{CoI} = 1.3703E+006$
 $knI = 1.00$
 $displacement_ductility_demand = 0.05741624$

NOTE: In expression (10-3) ' $V_s = A_v*f_y*d/s$ ' is replaced by ' $V_s + f*V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_c_jacket*Area_jacket + f'_c_core*Area_core)/Area_section = 20.80$, but $f'_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.00$
 $M_u = 116066.848$
 $V_u = 8505.401$
 $d = 0.8*h = 760.00$
 $N_u = 21315.408$
 $A_g = 427500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 976155.669$
where:
 $V_{sjacket} = V_{sj1} + V_{sj2} = 879645.943$
 $V_{sj1} = 282743.339$ is calculated for section web jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{sj1} is multiplied by $Col,j1 = 1.00$
 $s/d = 0.27777778$
 $V_{sj2} = 596902.604$ is calculated for section flange jacket, with:
 $d = 760.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{sj2} is multiplied by $Col,j2 = 1.00$
 $s/d = 0.13157895$

$$V_{s,c1} + V_{s,c2} = 96509.726$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 400.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 96509.726$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 400.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 1.0362E+006$

$$bw = 450.00$$

displacement ductility demand is calculated as ϕ / y

- Calculation of ϕ / y for END B -
for rotation axis 3 and integ. section (b)

From analysis, chord rotation = $1.4779662E-005$

$$y = (M_y * L_s / 3) / E_{eff} = 0.00025741 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 6.7546E+008$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 300.00$$

From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} * E_c * I_g = 2.6241E+014$

$$\text{factor} = 0.30$$

$$A_g = 562500.00$$

$$\text{Mean concrete strength: } f'_c = (f'_{c,jacket} * \text{Area}_{jacket} + f'_{c,core} * \text{Area}_{core}) / \text{Area}_{section} = 26.93333$$

$$N = 21315.408$$

$$E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 8.7468E+014$$

Calculation of Yielding Moment M_y

Calculation of ϕ / y and M_y according to Annex 7 -

$$y = \text{Min}(y_{ten}, y_{com})$$

$$y_{ten} = 2.2011335E-006$$

$$\text{with ((10.1), ASCE 41-17) } f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 294.7834$$

$$d = 907.00$$

$$y = 0.261723$$

$$A = 0.01732642$$

$$B = 0.0091583$$

$$\text{with } p_t = 0.00414877$$

$$p_c = 0.00414877$$

$$p_v = 0.00885172$$

$$N = 21315.408$$

$$b = 450.00$$

$$" = 0.04740904$$

$$y_{comp} = 9.3360319E-006$$

with $f_c = 33.00$

$$E_c = 26999.444$$

$$y = 0.25981367$$

$$A = 0.01703057$$

$$B = 0.00898114$$

$$\text{with } E_s = 200000.00$$

Calculation of ratio I_b / I_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 6

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_r)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjtc

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -0.0003102$

EDGE -B-

Shear Force, $V_b = 0.0003102$

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1539.38$

-Compression: $As_{c,com} = 2475.575$

-Middle: $As_{l,mid} = 2984.513$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.5622163$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 614853.514$

with

$M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 9.2228E+008$

$M_{u1+} = 6.6218E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 9.2228E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 9.2228E+008$

$M_{u2+} = 6.6218E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 9.2228E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 8.5401626E-006$

$$\mu = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 448.1427
fy1 = 373.4523
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 373.4523

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814

ft2 = 443.5927

fy2 = 369.6606

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 369.6606

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044
shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.02593726

2 = Asl,com/(b*d)*(fs2/fc) = 0.04128785

v = Asl,mid/(b*d)*(fsv/fc) = 0.04913955

and confined core properties:

b = 890.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.02891269

2 = Asl,com/(b*d)*(fs2/fc) = 0.04602424

v = Asl,mid/(b*d)*(fsv/fc) = 0.05477666

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is satisfied

---->

$$\begin{aligned} su(4.9) &= 0.15202235 \\ \mu &= MRc(4.14) = 6.6218E+008 \\ u &= su(4.1) = 8.5401626E-006 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u1} -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 9.2295561E-006 \\ \mu &= 9.2228E+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 450.00 \\ d &= 707.00 \\ d' &= 43.00 \\ v &= 0.00198277 \\ N &= 20816.964 \\ f_c &= 33.00 \\ c_o(5A.5, TBDY) &= 0.002 \\ \text{Final value of } \mu_u &: \mu_u^* = \text{shear_factor} * \text{Max}(\mu_u, c_c) = 0.00782179 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \mu_u &= 0.00782179 \\ w_e(5.4c) &= 0.01167368 \end{aligned}$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (> a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1}(\text{Length of stirrups along } Y) = 2160.00$$

$$A_{stir1}(\text{stirrups area}) = 78.53982$$

$$p_{sh2}((5.4d)) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2}(\text{Length of stirrups along } Y) = 1568.00$$

$$A_{stir2}(\text{stirrups area}) = 50.26548$$

$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307$
 $psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$
 Lstir1 (Length of stirrups along X) = 2560.00
 Astir1 (stirrups area) = 78.53982
 $psh2 ((5.4d), TBDY) = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$
 Lstir2 (Length of stirrups along X) = 1968.00
 Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 443.5927

fy1 = 369.6606

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by Min(1, 1.25 * (lb/ld)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 369.6606

with Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 448.1427

fy2 = 373.4523

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by Min(1, 1.25 * (lb/ld)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 373.4523

with Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv, ftv, fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by Min(1, 1.25 * (lb/ld)^2/3), from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 364.9343

with Esv = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00

1 = Asl,ten / (b * d) * (fs1 / fc) = 0.08716324

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.05475644$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10373905$$

and confined core properties:

$$b = 390.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.10502967$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.06598023$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.12500314$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.21536129$$

$$M_u = M_{Rc} (4.14) = 9.2228E+008$$

$$u = s_u (4.1) = 9.2295561E-006$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

Calculation of M_{u2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 8.5401626E-006$$

$$M_u = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$$
$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

$$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$$
$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

c = confinement factor = 1.00

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 448.1427$$

$$fy1 = 373.4523$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 373.4523$$

$$\text{with } Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 443.5927$$

$$fy2 = 369.6606$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$su2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 369.6606$$

$$\text{with } Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$yv = 0.00140044$$

$shv = 0.0044814$
 $ftv = 437.9212$
 $fyv = 364.9343$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343$
 with $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.02593726$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04128785$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04913955$

and confined core properties:

$b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.02891269$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04602424$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.05477666$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs,y2$ - LHS eq.(4.5) is satisfied

$su (4.9) = 0.15202235$
 $Mu = MRc (4.14) = 6.6218E+008$
 $u = su (4.1) = 8.5401626E-006$

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of $Mu2$ -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 9.2295561E-006$
 $Mu = 9.2228E+008$

 with full section properties:

$b = 450.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.00198277$
 $N = 20816.964$
 $fc = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00782179$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00782179$
 $we (5.4c) = 0.01167368$
 $ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773$
 $ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
ase2 (\geq ase1) = $\text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
psh,min*Fywe = $\text{Min}(psh,x*Fywe, psh,y*Fywe) = 2.40578$

Expression (5.4d) for psh,min*Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.40578

psh1 ((5.4d), TBDY) = $Lstir1 * Astir1 / (Asec * s1) = 0.00301593$

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = $Lstir2 * Astir2 / (Asec * s2) = 0.00056047$

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.87307

psh1 ((5.4d), TBDY) = $Lstir1 * Astir1 / (Asec * s1) = 0.00357443$

Lstir1 (Length of stirrups along X) = 2560.00

Astir1 (stirrups area) = 78.53982

psh2 ((5.4d), TBDY) = $Lstir2 * Astir2 / (Asec * s2) = 0.00070345$

Lstir2 (Length of stirrups along X) = 1968.00

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 443.5927

fy1 = 369.6606

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = $0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_jacket * Asl_ten_jacket + fs_core * Asl_ten_core) / Asl_ten = 369.6606$

with Es1 = $(Es_jacket * Asl_ten_jacket + Es_core * Asl_ten_core) / Asl_ten = 200000.00$

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 448.1427
fy2 = 373.4523
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 373.4523

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08716324

2 = Asl,com/(b*d)*(fs2/fc) = 0.05475644

v = Asl,mid/(b*d)*(fsv/fc) = 0.10373905

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.10502967

2 = Asl,com/(b*d)*(fs2/fc) = 0.06598023

v = Asl,mid/(b*d)*(fsv/fc) = 0.12500314

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.21536129

Mu = MRc (4.14) = 9.2228E+008

u = su (4.1) = 9.2295561E-006

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 1.0936E+006

Calculation of Shear Strength at edge 1, Vr1 = 1.0936E+006

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VColO

VColO = 1.0936E+006
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
M/Vd = 4.00
Mu = 867.5146
Vu = 0.0003102
d = 0.8*h = 600.00
Nu = 20816.964
Ag = 337500.00
From (11.5.4.8), ACI 318-14: $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 916401.511$
where:
 $V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 837764.743$
 $V_{s,j1} = 523602.964$ is calculated for section web jacket, with:
d = 600.00
Av = 157079.633
fy = 555.56
s = 100.00
 $V_{s,j1}$ is multiplied by Col,j1 = 1.00
s/d = 0.16666667
 $V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:
d = 360.00
Av = 157079.633
fy = 555.56
s = 100.00
 $V_{s,j2}$ is multiplied by Col,j2 = 1.00
s/d = 0.27777778
 $V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 78636.768$
 $V_{s,c1} = 78636.768$ is calculated for section web core, with:
d = 440.00
Av = 100530.965
fy = 444.44
s = 250.00
 $V_{s,c1}$ is multiplied by Col,c1 = 1.00
s/d = 0.56818182
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
d = 200.00
Av = 100530.965
fy = 444.44
s = 250.00
 $V_{s,c2}$ is multiplied by Col,c2 = 0.00
s/d = 1.25
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 930841.148$
bw = 450.00

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0936E+006$
 $V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = \text{knl} \cdot V_{\text{ColO}}$
VColO = 1.0936E+006
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
M/Vd = 4.00
Mu = 867.5146
Vu = 0.0003102
d = 0.8*h = 600.00

$N_u = 20816.964$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 916401.511$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 837764.743$
 $V_{s,j1} = 523602.964$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$
 $V_{s,c1} = 78636.768$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 930841.148$
 $bw = 450.00$

 End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At local axis: 3

 Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rcjtcs

Constant Properties

 Knowledge Factor, $\phi = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
 Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
 Concrete Elasticity, $E_c = 21019.039$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -2.7331429E-008$

EDGE -B-

Shear Force, $V_b = 2.7331429E-008$

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 1693.318$

-Compression: $A_{st,com} = 1693.318$

-Middle: $A_{st,mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.42425297$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 650163.608$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 9.7525E+008$

$M_{u1+} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 9.7525E+008$

$M_{u2+} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 6.9050030E-006$

$M_u = 9.7525E+008$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00140044$$

$sh1 = 0.0044814$
 $ft1 = 441.3522$
 $fy1 = 367.7935$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.3522$
 $fy2 = 367.7935$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.18247922$

$$\begin{aligned} \mu &= MRC(4.14) = 9.7525E+008 \\ u &= su(4.1) = 6.9050030E-006 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 6.9050030E-006 \\ \mu &= 9.7525E+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 450.00 \\ d &= 907.00 \\ d' &= 43.00 \\ v &= 0.00154555 \\ N &= 20816.964 \\ f_c &= 33.00 \end{aligned}$$

Final value of μ_c : $\mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_c) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_c = 0.00782179$

we (5.4c) = 0.01167368

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

ase1 = $\text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

ase2 ($\geq ase1$) = $\text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$

psh1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

psh2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.87307
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00357443
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00070345
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.3522

fy1 = 367.7935

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.3522

fy2 = 367.7935

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 442.9465

fyv = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905

2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05517782$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.05517782$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$\mu_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$\mu_u = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

c = confinement factor = 1.00

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 441.3522$

$fy1 = 367.7935$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.7935$

with $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 441.3522$

$fy2 = 367.7935$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 367.7935$

with $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.00140044$

$shv = 0.0044814$

$$ftv = 442.9465$$

$$fyv = 369.1221$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/d = 0.30$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv , shv , ftv , fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1$, $sh1$, $ft1$, $fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 369.1221$$

$$\text{with } Es_v = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.04623905$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.04623905$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

c = confinement factor = 1.00

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.05517782$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.05517782$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.18247922$$

$$Mu = MRc (4.14) = 9.7525E+008$$

$$u = su (4.1) = 6.9050030E-006$$

Calculation of ratio lb/d

Inadequate Lap Length with $lb/d = 0.30$

Calculation of $Mu2$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$Mu = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$fc = 33.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$we (5.4c) = 0.01167368$$

$$ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of $AnoConf$, $Aconf,min$ and $Aconf,max$ are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 441.3522$

$fy1 = 367.7935$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lo_{u,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 367.7935$

with $Es1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.00140044$

$sh_2 = 0.0044814$
 $ft_2 = 441.3522$
 $fy_2 = 367.7935$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{u,min} = lb/lb_{u,min} = 0.30$
 $su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 367.7935$
 with $Es_2 = (Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{u,min} = lb/ld = 0.30$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and yv , shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 369.1221$
 with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.04623905$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.04623905$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.09901112$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.05517782$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.05517782$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.11815159$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.18247922$
 $Mu = MRc (4.14) = 9.7525E+008$
 $u = su (4.1) = 6.9050030E-006$

 Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of Shear Strength $V_r = Min(V_{r1}, V_{r2}) = 1.5325E+006$

 Calculation of Shear Strength at edge 1, $V_{r1} = 1.5325E+006$
 $V_{r1} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$
 $V_{Col0} = 1.5325E+006$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.70443303$

$V_u = 2.7331429E-008$

$d = 0.8 \cdot h = 760.00$

$N_u = 20816.964$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col_{j2} = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col_{c1} = 0.00$

$s/d = 1.25$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col_{c2} = 1.00$

$s/d = 0.41666667$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$

$b_w = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.5325E+006$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$V_{Col0} = 1.5325E+006$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.70507494$

$V_u = 2.7331429E-008$

$d = 0.8 \cdot h = 760.00$

$N_u = 20816.964$

Ag = 427500.00
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$
 $V_{s,j1} = 314161.779$ is calculated for section web jacket, with:
d = 360.00
Av = 157079.633
fy = 555.56
s = 100.00
 $V_{s,j1}$ is multiplied by Col,j1 = 1.00
s/d = 0.27777778
 $V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:
d = 760.00
Av = 157079.633
fy = 555.56
s = 100.00
 $V_{s,j2}$ is multiplied by Col,j2 = 1.00
s/d = 0.13157895
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
d = 200.00
Av = 100530.965
fy = 444.44
s = 250.00
 $V_{s,c1}$ is multiplied by Col,c1 = 0.00
s/d = 1.25
 $V_{s,c2} = 107231.957$ is calculated for section flange core, with:
d = 600.00
Av = 100530.965
fy = 444.44
s = 250.00
 $V_{s,c2}$ is multiplied by Col,c2 = 1.00
s/d = 0.41666667
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (b)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 1.00
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$
Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$
 Min Width, $W_{min} = 450.00$
 Eccentricity, $Ecc = 250.00$
 Jacket Thickness, $t_j = 100.00$
 Cover Thickness, $c = 25.00$
 Element Length, $L = 3000.00$
 Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 No FRP Wrapping

 Stepwise Properties

Bending Moment, $M = 48364.752$
 Shear Force, $V_2 = 8505.401$
 Shear Force, $V_3 = 47.78617$
 Axial Force, $F = -21315.408$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 0.00$
 -Compression: $A_{sc} = 6999.468$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 1539.38$
 -Compression: $A_{sc,com} = 2475.575$
 -Middle: $A_{sc,mid} = 2984.513$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten,jacket} = 1231.504$
 -Compression: $A_{sc,com,jacket} = 1859.823$
 -Middle: $A_{sc,mid,jacket} = 2060.885$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten,core} = 307.8761$
 -Compression: $A_{sc,com,core} = 615.7522$
 -Middle: $A_{sc,mid,core} = 923.6282$
 Mean Diameter of Tension Reinforcement, $DbL = 16.57143$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \rho \cdot u = 0.00093743$
 $u = \rho \cdot y + p = 0.00093743$

 - Calculation of ρ -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.00093743$ ((4.29), Biskinis Phd))
 $M_y = 4.8184E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1012.108
 From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 1.7341E+014$
 $factor = 0.30$
 $A_g = 562500.00$
 Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$
 $N = 21315.408$
 $E_c \cdot I_g = E_c \cdot I_{g,jacket} + E_c \cdot I_{g,core} = 5.7803E+014$

 Calculation of Yielding Moment M_y

Calculation of ρ and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:
 flange width, $b = 950.00$
 web width, $b_w = 450.00$
 flange thickness, $t = 450.00$

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 2.6210819\text{E}-006$
 with $((10.1), \text{ASCE } 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 294.7834$
 $d = 707.00$
 $y = 0.20462306$
 $A = 0.01052896$
 $B = 0.00498068$
 with $pt = 0.00229194$
 $pc = 0.00368581$
 $pv = 0.00444355$
 $N = 21315.408$
 $b = 950.00$
 $" = 0.06082037$
 $y_{\text{comp}} = 1.5347948\text{E}-005$
 with $fc = 33.00$
 $Ec = 26999.444$
 $y = 0.20275047$
 $A = 0.01034918$
 $B = 0.00487302$
 with $Es = 200000.00$
 CONFIRMATION: $y = 0.20363296 < t/d$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{CoI} E = 0.5622163$

$d = d_{\text{external}} = 707.00$

$s = s_{\text{external}} = 0.00$

- $t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.0035764$

jacket: $s_1 = A_{v1} \cdot L_{\text{stir}1} / (s_1 \cdot A_g) = 0.00301593$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir}1} = 2160.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot L_{\text{stir}2} / (s_2 \cdot A_g) = 0.00056047$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir}2} = 1568.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 21315.408$

$A_g = 562500.00$

$f_{cE} = (f_{c_{\text{jacket}}} \cdot \text{Area}_{\text{jacket}} + f_{c_{\text{core}}} \cdot \text{Area}_{\text{core}}) / \text{section_area} = 26.93333$

$f_{yE} = (f_{y_{\text{ext_Long_Reinf}}} \cdot \text{Area}_{\text{ext_Long_Reinf}} + f_{y_{\text{int_Long_Reinf}}} \cdot \text{Area}_{\text{int_Long_Reinf}}) / \text{Area}_{\text{Tot_Long_Rein}} =$

526.2339

$f_{yE} = (f_{y_{\text{ext_Trans_Reinf}}} \cdot s_1 + f_{y_{\text{int_Trans_Reinf}}} \cdot s_2) / (s_1 + s_2) = 538.146$

$\rho_l = \text{Area}_{\text{Tot_Long_Rein}} / (b \cdot d) = 0.0104213$

$b = 950.00$

$d = 707.00$

$f_{cE} = 26.93333$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 7

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand,

the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as

Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$
Existing Column
Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material: Steel Strength, $f_s = f_{sm} = 444.44$

Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$
Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $Ecc = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = 95856.98$
Shear Force, $V_a = -47.78617$
EDGE -B-
Bending Moment, $M_b = 48364.752$
Shear Force, $V_b = 47.78617$
BOTH EDGES
Axial Force, $F = -21315.408$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 1539.38$
-Compression: $A_{sc,com} = 2475.575$
-Middle: $A_{st,mid} = 2984.513$
Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 1.1301E+006$
 $V_n ((10.3), ASCE 41-17) = k_n \cdot V_{CoI} = 1.1301E+006$
 $V_{CoI} = 1.1301E+006$
 $k_n = 1.00$
displacement_ductility_demand = 1.5359108E-005

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 20.80$, but $f_c'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.00$
 $M_u = 48364.752$
 $V_u = 47.78617$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 21315.408$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 824756.036$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 753982.237$
 $V_{s,j1} = 471238.898$ is calculated for section web jacket, with:
 $d = 600.00$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 282743.339$ is calculated for section flange jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.27777778$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 70773.799$$

$V_{s,c1} = 70773.799$ is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 400.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 400.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 0.00$

$$s/d = 1.25$$

$$V_f((11-3)-(11.4), ACI 440) = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 818016.733$$

$$b_w = 450.00$$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END B -
for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 1.4398040E-008$

$$y = (M_y * L_s / 3) / E_{eff} = 0.00093743 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 4.8184E+008$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 1012.108$$

$$\text{From table 10.5, ASCE 41_17: } E_{eff} = \text{factor} * E_c * I_g = 1.7341E+014$$

$$\text{factor} = 0.30$$

$$A_g = 562500.00$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{jacket} * \text{Area}_{jacket} + f_c'_{core} * \text{Area}_{core}) / \text{Area}_{section} = 26.93333$$

$$N = 21315.408$$

$$E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 5.7803E+014$$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($\delta / y < t/d$, compression zone rectangular) with:

$$\text{flange width, } b = 950.00$$

$$\text{web width, } b_w = 450.00$$

$$\text{flange thickness, } t = 450.00$$

$$y = \text{Min}(y_{ten}, y_{com})$$

$$y_{ten} = 2.6210819E-006$$

$$\text{with ((10.1), ASCE 41-17) } f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 294.7834$$

$$d = 707.00$$

$$y = 0.20462306$$

$$A = 0.01052896$$

$$B = 0.00498068$$

with $p_t = 0.00229194$
 $p_c = 0.00368581$
 $p_v = 0.00444355$
 $N = 21315.408$
 $b = 950.00$
 $" = 0.06082037$
 $y_{comp} = 1.5347948E-005$
 with $f_c = 33.00$
 $E_c = 26999.444$
 $y = 0.20275047$
 $A = 0.01034918$
 $B = 0.00487302$
 with $E_s = 200000.00$
 CONFIRMATION: $y = 0.20363296 < t/d$

Calculation of ratio I_b/I_d

Inadequate Lap Length with $I_b/I_d = 0.30$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 8

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -0.0003102$

EDGE -B-

Shear Force, $V_b = 0.0003102$

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 0.00$

-Compression: $A_{sl,c} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 2475.575$

-Middle: $A_{sl,mid} = 2984.513$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.5622163$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 614853.514$

with

$$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 9.2228E+008$$

$M_{u1+} = 6.6218E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 9.2228E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 9.2228E+008$$

$M_{u2+} = 6.6218E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 9.2228E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$\phi_u = 8.5401626E-006$$

$$M_u = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00782179$$

$$\omega_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$\text{Astir2 (stirrups area)} = 50.26548$$

$$\text{psh}_y * \text{Fywe} = \text{psh}_1 * \text{Fywe}_1 + \text{ps}_2 * \text{Fywe}_2 = 2.87307$$

$$\text{psh}_1 ((5.4d), \text{TBDY}) = \text{Lstir}_1 * \text{Astir}_1 / (\text{Asec} * \text{s}_1) = 0.00357443$$

$$\text{Lstir}_1 (\text{Length of stirrups along X}) = 2560.00$$

$$\text{Astir}_1 (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 ((5.4d), \text{TBDY}) = \text{Lstir}_2 * \text{Astir}_2 / (\text{Asec} * \text{s}_2) = 0.00070345$$

$$\text{Lstir}_2 (\text{Length of stirrups along X}) = 1968.00$$

$$\text{Astir}_2 (\text{stirrups area}) = 50.26548$$

$$\text{Asec} = 562500.00$$

$$\text{s}_1 = 100.00$$

$$\text{s}_2 = 250.00$$

$$\text{fywe}_1 = 694.45$$

$$\text{fywe}_2 = 555.55$$

$$\text{fce} = 33.00$$

$$\text{From } ((5.A.5), \text{TBDY}), \text{TBDY: } \text{cc} = 0.002$$

$$\text{c} = \text{confinement factor} = 1.00$$

$$\text{y}_1 = 0.00140044$$

$$\text{sh}_1 = 0.0044814$$

$$\text{ft}_1 = 448.1427$$

$$\text{fy}_1 = 373.4523$$

$$\text{su}_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{su}_1 = 0.4 * \text{esu}_1 \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esu}_1 \text{ nominal} = 0.08,$$

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$\text{y}_1, \text{sh}_1, \text{ft}_1, \text{fy}_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_1 = (\text{fs,jacket} * \text{Asl,ten,jacket} + \text{fs,core} * \text{Asl,ten,core}) / \text{Asl,ten} = 373.4523$$

$$\text{with } \text{Es}_1 = (\text{Es,jacket} * \text{Asl,ten,jacket} + \text{Es,core} * \text{Asl,ten,core}) / \text{Asl,ten} = 200000.00$$

$$\text{y}_2 = 0.00140044$$

$$\text{sh}_2 = 0.0044814$$

$$\text{ft}_2 = 443.5927$$

$$\text{fy}_2 = 369.6606$$

$$\text{su}_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/lb,min} = 0.30$$

$$\text{su}_2 = 0.4 * \text{esu}_2 \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esu}_2 \text{ nominal} = 0.08,$$

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$$\text{y}_2, \text{sh}_2, \text{ft}_2, \text{fy}_2, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_2 = (\text{fs,jacket} * \text{Asl,com,jacket} + \text{fs,core} * \text{Asl,com,core}) / \text{Asl,com} = 369.6606$$

$$\text{with } \text{Es}_2 = (\text{Es,jacket} * \text{Asl,com,jacket} + \text{Es,core} * \text{Asl,com,core}) / \text{Asl,com} = 200000.00$$

$$\text{y}_v = 0.00140044$$

$$\text{sh}_v = 0.0044814$$

$$\text{ft}_v = 437.9212$$

$$\text{fy}_v = 364.9343$$

$$\text{suv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{suv} = 0.4 * \text{esuv}_v \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esuv}_v \text{ nominal} = 0.08,$$

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

$$\text{y}_v, \text{sh}_v, \text{ft}_v, \text{fy}_v, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_v = (\text{fs,jacket} * \text{Asl,mid,jacket} + \text{fs,mid} * \text{Asl,mid,core}) / \text{Asl,mid} = 364.9343$$

$$\text{with } \text{Es}_v = (\text{Es,jacket} * \text{Asl,mid,jacket} + \text{Es,mid} * \text{Asl,mid,core}) / \text{Asl,mid} = 200000.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.02593726$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04128785$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.04913955$$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.02891269$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04602424$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.05477666$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.15202235$$

$$\mu_u = M_{Rc} (4.14) = 6.6218E+008$$

$$u = s_u (4.1) = 8.5401626E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u1} -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.2295561E-006$$

$$\mu_u = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 443.5927$

$fy1 = 369.6606$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 369.6606$

with $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 448.1427$

$fy2 = 373.4523$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 373.4523$

with $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00140044
shv = 0.0044814
ftv = 437.9212
fyv = 364.9343
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08716324

2 = Asl,com/(b*d)*(fs2/fc) = 0.05475644

v = Asl,mid/(b*d)*(fsv/fc) = 0.10373905

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.10502967

2 = Asl,com/(b*d)*(fs2/fc) = 0.06598023

v = Asl,mid/(b*d)*(fsv/fc) = 0.12500314

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.21536129

Mu = MRc (4.14) = 9.2228E+008

u = su (4.1) = 9.2295561E-006

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2+

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 8.5401626E-006

Mu = 6.6218E+008

with full section properties:

b = 950.00

d = 707.00

d' = 43.00

v = 0.00093921

N = 20816.964

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00782179

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00782179

we (5.4c) = 0.01167368

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1)/Aconf,max1) * (Aconf,min1/Aconf,max1), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.40578$$

Expression (5.4d) for psh,min * Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.40578$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1 \text{ (Length of stirrups along Y)} = 2160.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

$$Lstir2 \text{ (Length of stirrups along Y)} = 1568.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$psh,y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

$$Lstir1 \text{ (Length of stirrups along X)} = 2560.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

$$Lstir2 \text{ (Length of stirrups along X)} = 1968.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.45$$

$$fywe2 = 555.55$$

$$fce = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 448.1427$$

$$fy1 = 373.4523$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 373.4523$$

with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 443.5927$
 $fy_2 = 369.6606$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} \cdot A_{s,com,jacket} + fs_{core} \cdot A_{s,com,core}) / A_{s,com} = 369.6606$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 437.9212$
 $fy_v = 364.9343$
 $su_v = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_d = 0.30$
 $su_v = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 364.9343$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.02593726$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.04128785$
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / fc) = 0.04913955$
 and confined core properties:
 $b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.02891269$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.04602424$
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / fc) = 0.05477666$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.15202235$
 $Mu = MRc (4.14) = 6.6218E+008$
 $u = su (4.1) = 8.5401626E-006$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_2 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$\mu = 9.2295561E-006$$

$$\mu = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$\omega (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00782179$$

$$\omega_e (5.4c) = 0.01167368$$

$$\text{ase ((5.4d), TBDY) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.53375773$$

$$\text{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1})/A_{conf,max1}) * (A_{conf,min1}/A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{ase2} (>= \text{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{psh}_{min} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $\text{psh}_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.40578$$

$$\text{psh}_1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.87307$$

$$\text{psh}_1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.002$
 $c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 443.5927$$

$$fy1 = 369.6606$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_jacket * Asl,ten,jacket + fs_core * Asl,ten,core) / Asl,ten = 369.6606$$

$$\text{with } Es1 = (Es_jacket * Asl,ten,jacket + Es_core * Asl,ten,core) / Asl,ten = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 448.1427$$

$$fy2 = 373.4523$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_jacket * Asl,com,jacket + fs_core * Asl,com,core) / Asl,com = 373.4523$$

$$\text{with } Es2 = (Es_jacket * Asl,com,jacket + Es_core * Asl,com,core) / Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 437.9212$$

$$fyv = 364.9343$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_jacket * Asl,mid,jacket + fs_mid * Asl,mid,core) / Asl,mid = 364.9343$$

$$\text{with } Esv = (Es_jacket * Asl,mid,jacket + Es_mid * Asl,mid,core) / Asl,mid = 200000.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.08716324$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.05475644$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.10373905$$

and confined core properties:

$$b = 390.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.10502967$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.06598023$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.12500314$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

---->

$$\mu (4.9) = 0.21536129$$

$$\mu = M_{Rc} (4.14) = 9.2228E+008$$

$$u = \mu (4.1) = 9.2295561E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0936E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0936E+006$

$$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} * V_{Col0}$$

$$V_{Col0} = 1.0936E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 26.93333$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 867.5146$$

$$V_u = 0.0003102$$

$$d = 0.8 * h = 600.00$$

$$N_u = 20816.964$$

$$A_g = 337500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 916401.511$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 837764.743$$

$V_{s,j1} = 523602.964$ is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col_{j2} = 1.00$

$$s/d = 0.27777778$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$$

$V_{s,c1} = 78636.768$ is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col_{c1} = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col_{c2} = 0.00$

$$s/d = 1.25$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 930841.148$

bw = 450.00

Calculation of Shear Strength at edge 2, Vr2 = 1.0936E+006

Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0

VCol0 = 1.0936E+006

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 867.5146

Vu = 0.0003102

d = 0.8*h = 600.00

Nu = 20816.964

Ag = 337500.00

From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 916401.511

where:

Vs,jacket = Vs,j1 + Vs,j2 = 837764.743

Vs,j1 = 523602.964 is calculated for section web jacket, with:

d = 600.00

Av = 157079.633

fy = 555.56

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.16666667

Vs,j2 = 314161.779 is calculated for section flange jacket, with:

d = 360.00

Av = 157079.633

fy = 555.56

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.27777778

Vs,core = Vs,c1 + Vs,c2 = 78636.768

Vs,c1 = 78636.768 is calculated for section web core, with:

d = 440.00

Av = 100530.965

fy = 444.44

s = 250.00

Vs,c1 is multiplied by Col,c1 = 1.00

s/d = 0.56818182

Vs,c2 = 0.00 is calculated for section flange core, with:

d = 200.00

Av = 100530.965

fy = 444.44

s = 250.00

Vs,c2 is multiplied by Col,c2 = 0.00

s/d = 1.25

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 930841.148

bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -2.7331429E-008$

EDGE -B-

Shear Force, $V_b = 2.7331429E-008$

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 1693.318$

-Compression: $A_{st,com} = 1693.318$

-Middle: $A_{st,mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.42425297$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 650163.608$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 9.7525E+008$

Mu1+ = 9.7525E+008, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

Mu1- = 9.7525E+008, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

Mpr2 = Max(Mu2+ , Mu2-) = 9.7525E+008

Mu2+ = 9.7525E+008, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

Mu2- = 9.7525E+008, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu1+

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 6.9050030E-006$

Mu = 9.7525E+008

with full section properties:

b = 450.00

d = 907.00

d' = 43.00

v = 0.00154555

N = 20816.964

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00782179$

we (5.4c) = 0.01167368

ase ((5.4d), TBDY) = $(\text{ase1} * \text{Aext} + \text{ase2} * \text{Aint}) / \text{Asec} = 0.53375773$

ase1 = $\text{Max}(((\text{Aconf,max1} - \text{AnoConf1}) / \text{Aconf,max1}) * (\text{Aconf,min1} / \text{Aconf,max1}), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

ase2 (\geq ase1) = $\text{Max}(((\text{Aconf,max2} - \text{AnoConf2}) / \text{Aconf,max2}) * (\text{Aconf,min2} / \text{Aconf,max2}), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

psh,min*Fywe = $\text{Min}(\text{psh,x}*Fywe, \text{psh,y}*Fywe) = 2.40578$

Expression (5.4d) for psh,min*Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.40578

psh1 ((5.4d), TBDY) = $\text{Lstir1} * \text{Astir1} / (\text{Asec} * s1) = 0.00301593$

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = $\text{Lstir2} * \text{Astir2} / (\text{Asec} * s2) = 0.00056047$

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307$
 $psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$
 Lstir1 (Length of stirrups along X) = 2560.00
 Astir1 (stirrups area) = 78.53982
 $psh2 ((5.4d), TBDY) = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$
 Lstir2 (Length of stirrups along X) = 1968.00
 Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.3522

fy1 = 367.7935

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.3522

fy2 = 367.7935

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 442.9465

fyv = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^2/3), from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.04623905$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05517782$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.05517782$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$M_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

Calculation of $Mu1$ -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$M_u = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$$
$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

$$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$$
$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

c = confinement factor = 1.00

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.7935$$

$$\text{with } Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 441.3522$$

$$fy2 = 367.7935$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$su2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 367.7935$$

$$\text{with } Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$yv = 0.00140044$$

$shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221$
 with $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112$

and confined core properties:

$b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs,y2$ - LHS eq.(4.5) is satisfied

$su (4.9) = 0.18247922$
 $Mu = MRc (4.14) = 9.7525E+008$
 $u = su (4.1) = 6.9050030E-006$

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of $Mu2+$

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 6.9050030E-006$
 $Mu = 9.7525E+008$

 with full section properties:

$b = 450.00$
 $d = 907.00$
 $d' = 43.00$
 $v = 0.00154555$
 $N = 20816.964$
 $fc = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00782179$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00782179$
 $we (5.4c) = 0.01167368$
 $ase ((5.4d), TBDY) = (ase1*Aext+ ase2*Aint)/Asec = 0.53375773$
 $ase1 = Max(((Aconf,max1 - AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
ase2 (\geq ase1) = $\text{Max}(((A_{\text{conf,max2}} - A_{\text{noConf2}})/A_{\text{conf,max2}}) * (A_{\text{conf,min2}}/A_{\text{conf,max2}}), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
psh,min*Fywe = $\text{Min}(psh_x * Fywe, psh_y * Fywe) = 2.40578$

Expression (5.4d) for psh,min*Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.40578

psh1 ((5.4d), TBDY) = $L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s_1) = 0.00301593$

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = $L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s_2) = 0.00056047$

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.87307

psh1 ((5.4d), TBDY) = $L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s_1) = 0.00357443$

Lstir1 (Length of stirrups along X) = 2560.00

Astir1 (stirrups area) = 78.53982

psh2 ((5.4d), TBDY) = $L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s_2) = 0.00070345$

Lstir2 (Length of stirrups along X) = 1968.00

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.3522

fy1 = 367.7935

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = $0.4 * esu1_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(f_s, \text{jacket} * A_{s, \text{ten, jacket}} + f_s, \text{core} * A_{s, \text{ten, core}}) / A_{s, \text{ten}} = 367.7935$

with Es1 = $(E_s, \text{jacket} * A_{s, \text{ten, jacket}} + E_s, \text{core} * A_{s, \text{ten, core}}) / A_{s, \text{ten}} = 200000.00$

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.3522
fy2 = 367.7935
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 442.9465

fyv = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905

2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905

v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112

and confined core properties:

b = 390.00

d = 877.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782

2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782

v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.18247922

Mu = MRc (4.14) = 9.7525E+008

u = su (4.1) = 6.9050030E-006

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 6.9050030E-006
Mu = 9.7525E+008

with full section properties:

b = 450.00
d = 907.00
d' = 43.00
v = 0.00154555
N = 20816.964
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00782179$

we (5.4c) = 0.01167368

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.3522$
 $fy1 = 367.7935$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4 * esu1_nominal ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 367.7935$
 with $Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.3522$
 $fy2 = 367.7935$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4 * esu2_nominal ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 367.7935$
 with $Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4 * esuv_nominal ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 369.1221$
 with $Esv = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.04623905$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.04623905$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.09901112$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, \text{TBDY}) = 33.00$
 $cc (5A.5, \text{TBDY}) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.05517782$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.05517782$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.11815159$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

--->

$$\mu (4.9) = 0.18247922$$

$$\mu = MRC (4.14) = 9.7525E+008$$

$$u = \mu (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.5325E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.5325E+006$

$$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} * V_{Col0}$$

$$V_{Col0} = 1.5325E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$\text{Mean concrete strength: } f'_c = (f'_{c,jacket} * \text{Area}_{jacket} + f'_{c,core} * \text{Area}_{core}) / \text{Area}_{section} = 26.93333, \text{ but } f'_c^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 2.00$$

$$\mu = 0.70443303$$

$$V_u = 2.7331429E-008$$

$$d = 0.8 * h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col_{j2} = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col_{c1} = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col_{c2} = 1.00$

$$s/d = 0.41666667$$

$$V_f ((11-3)-(11.4), ACI 440) = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 1.1791E+006$$

$$b_w = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.5325E+006$

$V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$

$V_{Col0} = 1.5325E+006$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.70507494$

$\nu_u = 2.7331429E-008$

$d = 0.8 * h = 760.00$

$N_u = 20816.964$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 1.0846E+006$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 977392.20$

$V_{sj1} = 314161.779$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{sj1} is multiplied by $Col_{j1} = 1.00$

$s/d = 0.27777778$

$V_{sj2} = 663230.422$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{sj2} is multiplied by $Col_{j2} = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col_{c1} = 0.00$

$s/d = 1.25$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col_{c2} = 1.00$

$s/d = 0.41666667$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$

$bw = 450.00$

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\phi = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_b/l_d = 0.30$

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 116066.848$

Shear Force, $V_2 = 8505.401$

Shear Force, $V_3 = 47.78617$

Axial Force, $F = -21315.408$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl} = 0.00$

-Compression: $A_{sl,c} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1693.318$

-Compression: $A_{sl,com} = 1693.318$

-Middle: $A_{sl,mid} = 3612.832$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,jacket} = 1231.504$

-Compression: $A_{sl,com,jacket} = 1231.504$

-Middle: $A_{sl,mid,jacket} = 2689.203$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,core} = 461.8141$

-Compression: $A_{sl,com,core} = 461.8141$

-Middle: $A_{sl,mid,core} = 923.6282$

Mean Diameter of Tension Reinforcement, $DbL = 16.25$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = \phi \cdot u = 0.00025741$

$u = y + p = 0.00025741$

- Calculation of y -

$y = (My * Ls / 3) / E_{eff} = 0.00025741$ ((4.29), Biskinis Phd))

$My = 6.7546E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 300.00

From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.6241E+014$

factor = 0.30

$A_g = 562500.00$

Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$

$N = 21315.408$

$E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 8.7468E+014$

Calculation of Yielding Moment M_y

Calculation of ρ_y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 2.2011335E-006$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (I_b/I_d)^{2/3}) = 294.7834$

$d = 907.00$

$y = 0.261723$

$A = 0.01732642$

$B = 0.0091583$

with $pt = 0.00414877$

$pc = 0.00414877$

$pv = 0.00885172$

$N = 21315.408$

$b = 450.00$

$\rho = 0.04740904$

$y_{comp} = 9.3360319E-006$

with $f_c = 33.00$

$E_c = 26999.444$

$y = 0.25981367$

$A = 0.01703057$

$B = 0.00898114$

with $E_s = 200000.00$

Calculation of ratio I_b/I_d

Inadequate Lap Length with $I_b/I_d = 0.30$

- Calculation of ρ_p -

From table 10-8: $\rho_p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because $I_b/I_d < 1$

shear control ratio $V_y/E/V_{CoI}E = 0.42425297$

$d = d_{external} = 907.00$

$s = s_{external} = 0.00$

- $t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00427788$

jacket: $s_1 = A_{v1} \cdot L_{stir1} / (s_1 \cdot A_g) = 0.00357443$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2560.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot L_{stir2} / (s_2 \cdot A_g) = 0.00070345$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1968.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 21315.408$

$A_g = 562500.00$

$f_c E = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / section_area = 26.93333$

$f_y I_E = (f_y'_{ext_Long_Reinf} \cdot Area_{ext_Long_Reinf} + f_y'_{int_Long_Reinf} \cdot Area_{int_Long_Reinf}) / Area_{Tot_Long_Rein} =$

526.2339

$$f_y E = (f_{y_ext_Trans_Reinf} \cdot s_1 + f_{y_int_Trans_Reinf} \cdot s_2) / (s_1 + s_2) = 537.2876$$

$$\rho_l = \text{Area_Tot_Long_Rein} / (b \cdot d) = 0.01714926$$

$$b = 450.00$$

$$d = 907.00$$

$$f_c E = 26.93333$$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 9

column C1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjctcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

```

Steel Elasticity, Es = 200000.00
Existing Column
Existing material of Secondary Member: Concrete Strength, fc = fc_lower_bound = 16.00
Existing material of Secondary Member: Steel Strength, fs = fs_lower_bound = 400.00
Concrete Elasticity, Ec = 21019.039
Steel Elasticity, Es = 200000.00
#####
Note: Especially for the calculation of  $\mu_y$  for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, fc = fcm = 33.00
New material: Steel Strength, fs = fsm = 555.56
Existing Column
Existing material: Concrete Strength, fc = fcm = 20.00
Existing material: Steel Strength, fs = fsm = 444.44
#####
Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with  $l_o/l_{o,min} = l_b/l_d = 0.30$ 
No FRP Wrapping
-----

Stepwise Properties
-----
EDGE -A-
Bending Moment, Ma = -2.1323E+007
Shear Force, Va = -7074.25
EDGE -B-
Bending Moment, Mb = 96537.118
Shear Force, Vb = 7074.25
BOTH EDGES
Axial Force, F = -21231.538
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Asl,t = 0.00
-Compression: Asl,c = 6999.468
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1693.318
-Compression: Asl,com = 1693.318
-Middle: Asl,mid = 3612.832
Mean Diameter of Tension Reinforcement, DbL,ten = 16.25
-----

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity  $V_R = \phi V_n = 1.1749E+006$ 
 $V_n$  ((10.3), ASCE 41-17) =  $k_n \phi V_{CoI} = 1.1749E+006$ 
 $V_{CoI} = 1.1749E+006$ 
 $k_n = 1.00$ 
displacement_ductility_demand = 0.01927815
-----
NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + \phi \cdot V_f$ '
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).
-----
= 1 (normal-weight concrete)
Mean concrete strength:  $f'_c = (f'_c\_jacket \cdot Area\_jacket + f'_c\_core \cdot Area\_core) / Area\_section = 20.80$ , but  $f'_c^{0.5} \leq 8.3$ 

```

MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 3.96606$$

$$\mu_u = 2.1323E+007$$

$$V_u = 7074.25$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 21231.538$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 976155.669$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 879645.943$$

$V_{s,j1} = 282743.339$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 596902.604$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 96509.726$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 400.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 96509.726$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 400.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 1.0362E+006$$

$$bw = 450.00$$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 4.9857215E-005$

$$y = (M_y \cdot L_s / 3) / E_{eff} = 0.0025862 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 6.7544E+008$$

$$L_s = M/V \text{ (with } L_s > 0.1 \cdot L \text{ and } L_s < 2 \cdot L) = 3014.205$$

$$\text{From table 10.5, ASCE 41_17: } E_{eff} = \text{factor} \cdot E_c \cdot I_g = 2.6241E+014$$

$$\text{factor} = 0.30$$

$$A_g = 562500.00$$

$$\text{Mean concrete strength: } f'_c = (f'_{c,jacket} \cdot \text{Area}_{jacket} + f'_{c,core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 26.93333$$

$$N = 21231.538$$

$$E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 8.7468E+014$$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

y = Min(y_ten, y_com)
y_ten = 2.2011043E-006
with ((10.1), ASCE 41-17) fy = Min(fy, 1.25*fy*(lb/d)^ 2/3) = 294.7834
d = 907.00
y = 0.26171323
A = 0.01732572
B = 0.00915761
with pt = 0.00414877
pc = 0.00414877
pv = 0.00885172
N = 21231.538
b = 450.00
" = 0.04740904
y_comp = 9.3361155E-006
with fc = 33.00
Ec = 26999.444
y = 0.25981135
A = 0.01703103
B = 0.00898114
with Es = 200000.00

Calculation of ratio lb/d

Inadequate Lap Length with lb/d = 0.30

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (a)

Calculation No. 10

column C1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (u)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rcjtcs

Constant Properties

 Knowledge Factor, $\gamma = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
 Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
 Concrete Elasticity, $E_c = 21019.039$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 Jacket
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.45$
 Existing Column
 Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.55$
 #####
 Max Height, $H_{max} = 750.00$
 Min Height, $H_{min} = 450.00$
 Max Width, $W_{max} = 950.00$
 Min Width, $W_{min} = 450.00$
 Eccentricity, $E_{cc} = 250.00$
 Jacket Thickness, $t_j = 100.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.00
 Element Length, $L = 3000.00$
 Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_o/l_{o,min} = 0.30$
 No FRP Wrapping

Stepwise Properties

 At local axis: 3
 EDGE -A-
 Shear Force, $V_a = -0.0003102$
 EDGE -B-

Shear Force, $V_b = 0.0003102$
BOTH EDGES
Axial Force, $F = -20816.964$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1539.38$
-Compression: $As_{c,com} = 2475.575$
-Middle: $As_{c,mid} = 2984.513$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.5622163$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 614853.514$
with
 $M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 9.2228E+008$
 $Mu_{1+} = 6.6218E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu_{1-} = 9.2228E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 9.2228E+008$
 $Mu_{2+} = 6.6218E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu_{2-} = 9.2228E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 8.5401626E-006$
 $M_u = 6.6218E+008$

with full section properties:

$b = 950.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.00093921$
 $N = 20816.964$
 $f_c = 33.00$
 α_1 (5A.5, TBDY) = 0.002
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.00782179$
 ω_e (5.4c) = 0.01167368
 α_{se} ((5.4d), TBDY) = $(\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.53375773$
 $\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.
 $A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.
 $A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $\alpha_{se2} (\geq \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.
 $A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 448.1427$

$fy1 = 373.4523$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 373.4523$

with $Es1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 443.5927$

$fy2 = 369.6606$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 369.6606$

with $E_s2 = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 437.9212$
 $fy_v = 364.9343$
 $su_v = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 0.30$
 $su_v = 0.4 \cdot esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fs_yv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_yv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 364.9343$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02593726$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04128785$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04913955$

and confined core properties:

$b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02891269$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04602424$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.05477666$

Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.15202235$
 $Mu = MRc (4.14) = 6.6218E+008$
 $u = su (4.1) = 8.5401626E-006$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 9.2295561E-006$
 $Mu = 9.2228E+008$

with full section properties:

$b = 450.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.00198277$
 $N = 20816.964$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00782179$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00782179$
 $we (5.4c) = 0.01167368$

$$ase((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((Aconf,max2 - AnoConf2) / Aconf,max2) * (Aconf,min2 / Aconf,max2), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.40578$$

Expression (5.4d) for psh,min * Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.40578$$

$$psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

$$psh2 (5.4d) = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

$$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307$$

$$psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

Lstir1 (Length of stirrups along X) = 2560.00

Astir1 (stirrups area) = 78.53982

$$psh2 ((5.4d), TBDY) = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00

Astir2 (stirrups area) = 50.26548

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.45$$

$$fywe2 = 555.55$$

$$fce = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c =$ confinement factor = 1.00

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 443.5927$$

$$fy1 = 369.6606$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s,jacket} \cdot A_{s,ten,jacket} + f_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 369.6606$
 with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 448.1427$
 $fy_2 = 373.4523$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_{b,min} = 0.30$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 373.4523$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 437.9212$
 $fy_v = 364.9343$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 0.30$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 364.9343$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08716324$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.05475644$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.10373905$

and confined core properties:

$b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.10502967$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.06598023$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.12500314$

Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.21536129$
 $Mu = MRc (4.14) = 9.2228E+008$
 $u = su (4.1) = 9.2295561E-006$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_{2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 8.5401626E-006$$

$$Mu = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$co(5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$we(5.4c) = 0.01167368$$

$$ase((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$$

$$psh1((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2(5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$$

$$psh1((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.002$

$$c = \text{confinement factor} = 1.00$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 448.1427$$

$$fy_1 = 373.4523$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 373.4523$$

$$\text{with } Es_1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 443.5927$$

$$fy_2 = 369.6606$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (f_{s,jacket} * A_{s,com,jacket} + f_{s,core} * A_{s,com,core}) / A_{s,com} = 369.6606$$

$$\text{with } Es_2 = (E_{s,jacket} * A_{s,com,jacket} + E_{s,core} * A_{s,com,core}) / A_{s,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 437.9212$$

$$fy_v = 364.9343$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsy_v = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 364.9343$$

$$\text{with } Es_v = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (fs_1 / f_c) = 0.02593726$$

$$2 = A_{s,com} / (b * d) * (fs_2 / f_c) = 0.04128785$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.04913955$$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s,ten} / (b * d) * (fs_1 / f_c) = 0.02891269$$

$$2 = A_{s,com} / (b * d) * (fs_2 / f_c) = 0.04602424$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.05477666$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.15202235$$

$$\mu_u = M_{Rc}(4.14) = 6.6218E+008$$

$$u = s_u(4.1) = 8.5401626E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.2295561E-006$$

$$\mu_u = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e(5.4c) = 0.01167368$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1}(\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1}(\text{stirrups area}) = 78.53982$$

psh2 (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307
psh1 ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 443.5927

fy1 = 369.6606

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su1 = $0.4 * esu1_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 369.6606$

with Es1 = $(Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 448.1427

fy2 = 373.4523

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = $0.4 * esu2_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = $(fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 373.4523$

with Es2 = $(Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = $0.4 * esuv_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv, ftv, fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 364.9343$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08716324$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.05475644$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.10373905$

and confined core properties:

$b = 390.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.10502967$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.06598023$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.12500314$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$\mu (4.9) = 0.21536129$
 $\mu = M_{Rc} (4.14) = 9.2228E+008$
 $u = \mu (4.1) = 9.2295561E-006$

 Calculation of ratio l_b/d

 Inadequate Lap Length with $l_b/d = 0.30$

 Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0936E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0936E+006$

$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$

$V_{Col0} = 1.0936E+006$

$k_{nl} = 1$ (zero step-static loading)

 NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_{s+} = f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 867.5146$

$\nu_u = 0.0003102$

$d = 0.8 \cdot h = 600.00$

$N_u = 20816.964$

$A_g = 337500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 916401.511$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 837764.743$

$V_{s,j1} = 523602.964$ is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$
 $V_{s,c1} = 78636.768$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 930841.148$
 $bw = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0936E+006$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$
 $V_{Col0} = 1.0936E+006$
 $knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)
 Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 26.93333$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $M_u = 867.5146$
 $V_u = 0.0003102$
 $d = 0.8 * h = 600.00$
 $N_u = 20816.964$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 916401.511$
 where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 837764.743$
 $V_{s,j1} = 523602.964$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$
 $V_{s,c1} = 78636.768$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 444.44$

s = 250.00
Vs,c2 is multiplied by Col,c2 = 0.00
s/d = 1.25
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 930841.148
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 1.00
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Secondary Member: Concrete Strength, fc = fcm = 33.00
New material of Secondary Member: Steel Strength, fs = fsm = 555.56
Concrete Elasticity, Ec = 26999.444
Steel Elasticity, Es = 200000.00
Existing Column
Existing material of Secondary Member: Concrete Strength, fc = fcm = 20.00
Existing material of Secondary Member: Steel Strength, fs = fsm = 444.44
Concrete Elasticity, Ec = 21019.039
Steel Elasticity, Es = 200000.00

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket
New material: Steel Strength, fs = 1.25*fsm = 694.45
Existing Column
Existing material: Steel Strength, fs = 1.25*fsm = 555.55
#####

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.00
Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with lo/lo,min = 0.30
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -2.7331429E-008
EDGE -B-
Shear Force, Vb = 2.7331429E-008

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{s,ten} = 1693.318$

-Compression: $A_{s,com} = 1693.318$

-Middle: $A_{s,mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.42425297$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 650163.608$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 9.7525E+008$

$M_{u1+} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 9.7525E+008$

$M_{u2+} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 6.9050030E-006$

$M_u = 9.7525E+008$

with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.00154555$

$N = 20816.964$

$f_c = 33.00$

$\omega (5A.5, \text{TBDY}) = 0.002$

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00782179$

$\omega_e (5.4c) = 0.01167368$

$\omega_{ase} ((5.4d), \text{TBDY}) = (\omega_{ase1} * A_{ext} + \omega_{ase2} * A_{int}) / A_{sec} = 0.53375773$

$\omega_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$\omega_{ase2} (>= \omega_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 441.3522$

$fy1 = 367.7935$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.7935$

with $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 441.3522$

$fy2 = 367.7935$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 367.7935$

with $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221$
 with $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112$

and confined core properties:

$b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs,y2$ - LHS eq.(4.5) is satisfied

$su (4.9) = 0.18247922$

$Mu = MRc (4.14) = 9.7525E+008$

$u = su (4.1) = 6.9050030E-006$

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of $Mu1$ -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 6.9050030E-006$

$Mu = 9.7525E+008$

 with full section properties:

$b = 450.00$

$d = 907.00$

$d' = 43.00$

$v = 0.00154555$

$N = 20816.964$

$fc = 33.00$

$co (5A.5, TBDY) = 0.002$

Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00782179$

$we (5.4c) = 0.01167368$

$ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773$

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1)/Aconf,max1) * (Aconf,min1/Aconf,max1), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.40578$$

Expression (5.4d) for psh,min * Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.40578$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1 \text{ (Length of stirrups along Y)} = 2160.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

$$Lstir2 \text{ (Length of stirrups along Y)} = 1568.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$psh,y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

$$Lstir1 \text{ (Length of stirrups along X)} = 2560.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

$$Lstir2 \text{ (Length of stirrups along X)} = 1968.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.45$$

$$fywe2 = 555.55$$

$$fce = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 367.7935$$

with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.3522$
 $fy_2 = 367.7935$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} \cdot A_{s,com,jacket} + fs_{core} \cdot A_{s,com,core}) / A_{s,com} = 367.7935$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 442.9465$
 $fy_v = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_d = 0.30$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 369.1221$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / f_c) = 0.04623905$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / f_c) = 0.04623905$
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / f_c) = 0.09901112$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / f_c) = 0.05517782$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / f_c) = 0.05517782$
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / f_c) = 0.11815159$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_s, y_2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.18247922$
 $M_u = MR_c (4.14) = 9.7525E+008$
 $u = su (4.1) = 6.9050030E-006$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of M_{u2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$\mu = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$\omega (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00782179$$

$$\omega_e (5.4c) = 0.01167368$$

$$\text{ase ((5.4d), TBDY) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.53375773$$

$$\text{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1})/A_{conf,max1}) * (A_{conf,min1}/A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{ase2} (>= \text{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{psh}_{min} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $\text{psh}_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.40578$$

$$\text{psh}_1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.87307$$

$$\text{psh}_1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.002$
 $c = \text{confinement factor} = 1.00$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.3522$
 $fy1 = 367.7935$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.3522$
 $fy2 = 367.7935$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.18247922$$

$$\mu_u = M_{Rc}(4.14) = 9.7525E+008$$

$$u = s_u(4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$\mu_u = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e(5.4c) = 0.01167368$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1}(\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1}(\text{stirrups area}) = 78.53982$$

$$p_{sh2}(5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 2.87307
psh₁ ((5.4d), TBDY) = Lstir₁*Astir₁/(Asec*s₁) = 0.00357443
Lstir₁ (Length of stirrups along X) = 2560.00
Astir₁ (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = Lstir₂*Astir₂/(Asec*s₂) = 0.00070345
Lstir₂ (Length of stirrups along X) = 1968.00
Astir₂ (stirrups area) = 50.26548

Asec = 562500.00
s₁ = 100.00
s₂ = 250.00

fywe₁ = 694.45
fywe₂ = 555.55
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002
c = confinement factor = 1.00

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.3522
fy₁ = 367.7935
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*Asl_{ten,jacket} + fs_{core}*Asl_{ten,core})/Asl_{ten} = 367.7935

with Es₁ = (Es_{jacket}*Asl_{ten,jacket} + Es_{core}*Asl_{ten,core})/Asl_{ten} = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814

ft₂ = 441.3522

fy₂ = 367.7935

su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 0.30

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*Asl_{com,jacket} + fs_{core}*Asl_{com,core})/Asl_{com} = 367.7935

with Es₂ = (Es_{jacket}*Asl_{com,jacket} + Es_{core}*Asl_{com,core})/Asl_{com} = 200000.00

y_v = 0.00140044
sh_v = 0.0044814

ft_v = 442.9465

fy_v = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_{nominal} = 0.08,

considering characteristic value fsy_v = fs_v/1.2, from table 5.1, TBDY
For calculation of esuv_{nominal} and y_v, sh_v,ft_v,fy_v, it is considered

characteristic value fsy_v = fs_v/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs_v = (fs_{jacket}*Asl_{mid,jacket} + fs_{mid}*Asl_{mid,core})/Asl_{mid} = 369.1221

$$\text{with } E_{sv} = (E_{s,jacket} \cdot A_{sl,mid,jacket} + E_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.04623905$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04623905$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.05517782$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.05517782$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$M_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.5325E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.5325E+006$

$$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$$

$$V_{Col0} = 1.5325E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_{s+} = f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

Mean concrete strength: $f'_c = (f'_c \cdot A_{jacket} + f'_c \cdot A_{core}) / A_{section} = 26.93333$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$M_u = 0.70443303$$

$$V_u = 2.7331429E-008$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$

$$bw = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.5325E+006$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} * V_{Col0}$

$$V_{Col0} = 1.5325E+006$$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$\mu_u = 0.70507494$$

$$V_u = 2.7331429E-008$$

$$d = 0.8 * h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

V_{s,c2} is multiplied by Col,c2 = 1.00
s/d = 0.41666667
V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: V_s + V_f <= 1.1791E+006
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (a)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$
Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$
Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $E_{cc} = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 79873.692$
Shear Force, $V_2 = -7074.25$
Shear Force, $V_3 = -39.74554$
Axial Force, $F = -21231.538$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 0.00$
-Compression: $A_{sl,c} = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 1539.38$
-Compression: $A_{sl,com} = 2475.575$
-Middle: $A_{sl,mid} = 2984.513$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten,jacket} = 1231.504$
-Compression: $A_{sl,com,jacket} = 1859.823$

-Middle: $Asl, mid, jacket = 2060.885$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl, ten, core = 307.8761$

-Compression: $Asl, com, core = 615.7522$

-Middle: $Asl, mid, core = 923.6282$

Mean Diameter of Tension Reinforcement, $DbL = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u, R = * u = 0.02506965$

$u = y + p = 0.02506965$

- Calculation of y -

$y = (My * Ls / 3) / Eleff = 0.00186125$ ((4.29), Biskinis Phd))

$My = 4.8181E+008$

$Ls = M/V$ (with $Ls > 0.1 * L$ and $Ls < 2 * L$) = 2009.627

From table 10.5, ASCE 41_17: $Eleff = factor * Ec * Ig = 1.7341E+014$

factor = 0.30

$Ag = 562500.00$

Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 26.93333$

$N = 21231.538$

$Ec * Ig = Ec_{jacket} * Ig_{jacket} + Ec_{core} * Ig_{core} = 5.7803E+014$

Calculation of Yielding Moment My

Calculation of y and My according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, $b = 950.00$

web width, $bw = 450.00$

flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 2.6210528E-006$

with ((10.1), ASCE 41-17) $fy = \text{Min}(fy, 1.25 * fy * (lb/d)^{2/3}) = 294.7834$

$d = 707.00$

$y = 0.20461423$

$A = 0.01052854$

$B = 0.00498025$

with $pt = 0.00229194$

$pc = 0.00368581$

$p_v = 0.00444355$

$N = 21231.538$

$b = 950.00$

$" = 0.06082037$

$y_{comp} = 1.5348064E-005$

with $fc = 33.00$

$Ec = 26999.444$

$y = 0.20274895$

$A = 0.01034946$

$B = 0.00487302$

with $Es = 200000.00$

CONFIRMATION: $y = 0.20362798 < t/d$

Calculation of ratio lb/d

Inadequate Lap Length with $lb/d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.0232084$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$
shear control ratio $V_{yE}/V_{Col0E} = 0.5622163$

$$d = d_{\text{external}} = 707.00$$

$$s = s_{\text{external}} = 0.00$$

- $t = s_1 + s_2 + 2 \cdot t_f/bw \cdot (f_{fe}/f_s) = 0.0035764$

$$\text{jacket: } s_1 = A_{v1} \cdot L_{\text{stir1}} / (s_1 \cdot A_g) = 0.00301593$$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir1}} = 2160.00$, is the total Length of all stirrups parallel to loading (shear) direction

$$s_1 = 100.00$$

$$\text{core: } s_2 = A_{v2} \cdot L_{\text{stir2}} / (s_2 \cdot A_g) = 0.00056047$$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir2}} = 1568.00$, is the total Length of all stirrups parallel to loading (shear) direction

$$s_2 = 250.00$$

The term $2 \cdot t_f/bw \cdot (f_{fe}/f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f/bw$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe}/f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$$N_{UD} = 21231.538$$

$$A_g = 562500.00$$

$$f_{cE} = (f_{c_{\text{jacket}}} \cdot \text{Area}_{\text{jacket}} + f_{c_{\text{core}}} \cdot \text{Area}_{\text{core}}) / \text{section_area} = 26.93333$$

$$f_{yE} = (f_{y_{\text{ext_Long_Reinf}}} \cdot \text{Area}_{\text{ext_Long_Reinf}} + f_{y_{\text{int_Long_Reinf}}} \cdot \text{Area}_{\text{int_Long_Reinf}}) / \text{Area}_{\text{Tot_Long_Rein}} = 526.2339$$

$$f_{yE} = (f_{y_{\text{ext_Trans_Reinf}}} \cdot s_1 + f_{y_{\text{int_Trans_Reinf}}} \cdot s_2) / (s_1 + s_2) = 538.146$$

$$p_l = \text{Area}_{\text{Tot_Long_Rein}} / (b \cdot d) = 0.0104213$$

$$b = 950.00$$

$$d = 707.00$$

$$f_{cE} = 26.93333$$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 11

column C1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material: Steel Strength, $f_s = f_{sm} = 444.44$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 79873.692$
 Shear Force, $V_a = -39.74554$
 EDGE -B-
 Bending Moment, $M_b = 40080.744$
 Shear Force, $V_b = 39.74554$
 BOTH EDGES
 Axial Force, $F = -21231.538$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 0.00$
 -Compression: $A_{sc} = 6999.468$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 1539.38$
 -Compression: $A_{sc,com} = 2475.575$
 -Middle: $A_{sc,mid} = 2984.513$
 Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 1.0044E+006$
 V_n ((10.3), ASCE 41-17) = $k_n I^* V_{CoI} = 1.0044E+006$
 $V_{CoI} = 1.0044E+006$
 $k_n = 1.00$
 displacement_ductility_demand = 0.00530624

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + \phi * V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$\phi = 1$ (normal-weight concrete)
 Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 20.80$, but $f_c'^{0.5} \leq 8.3$
 MPa (22.5.3.1, ACI 318-14)
 $M / Vd = 3.34938$
 $M_u = 79873.692$
 $V_u = 39.74554$
 $d = 0.8 * h = 600.00$
 $N_u = 21231.538$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 824756.036$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 753982.237$
 $V_{s,j1} = 471238.898$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 282743.339$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 70773.799$
 $V_{s,c1} = 70773.799$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 400.00$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 400.00$
 $s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 818016.733$
 $bw = 450.00$

displacement ductility demand is calculated as ϕ / y

- Calculation of ϕ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 9.8762167E-006$
 $y = (M_y * L_s / 3) / E_{eff} = 0.00186125$ ((4.29), Biskinis Phd))
 $M_y = 4.8181E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 2009.627
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7341E+014$
 $factor = 0.30$
 $A_g = 562500.00$
Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333$
 $N = 21231.538$
 $E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 5.7803E+014$

Calculation of Yielding Moment M_y

Calculation of ϕ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:
flange width, $b = 950.00$
web width, $bw = 450.00$
flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 2.6210528E-006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 294.7834$
 $d = 707.00$
 $y = 0.20461423$
 $A = 0.01052854$
 $B = 0.00498025$
with $pt = 0.00229194$
 $pc = 0.00368581$
 $pv = 0.00444355$
 $N = 21231.538$
 $b = 950.00$
 $" = 0.06082037$
 $y_{comp} = 1.5348064E-005$
with $f_c = 33.00$
 $E_c = 26999.444$
 $y = 0.20274895$
 $A = 0.01034946$
 $B = 0.00487302$
with $E_s = 200000.00$
CONFIRMATION: $y = 0.20362798 < t/d$

Calculation of ratio I_b / I_d

Inadequate Lap Length with $I_b / I_d = 0.30$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 12

column C1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, Hmax = 750.00
Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.00
Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, Va = -0.0003102
EDGE -B-
Shear Force, Vb = 0.0003102
BOTH EDGES
Axial Force, F = -20816.964
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 0.00
-Compression: Asc = 6999.468
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1539.38
-Compression: Asl,com = 2475.575
-Middle: Asl,mid = 2984.513

Calculation of Shear Capacity ratio , $V_e/V_r = 0.5622163$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 614853.514$
with
 $M_{pr1} = \text{Max}(Mu_{1+} , Mu_{1-}) = 9.2228E+008$
 $Mu_{1+} = 6.6218E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 9.2228E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+} , Mu_{2-}) = 9.2228E+008$
 $Mu_{2+} = 6.6218E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 9.2228E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 8.5401626E-006$
 $M_u = 6.6218E+008$

with full section properties:
 $b = 950.00$
 $d = 707.00$
 $d' = 43.00$
 $v = 0.00093921$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of $A_{noConf1}$, $A_{conf,min1}$ and $A_{conf,max1}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.87307$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 448.1427$$

$$fy1 = 373.4523$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 373.4523

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 443.5927

fy2 = 369.6606

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 369.6606

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.02593726

2 = Asl,com/(b*d)*(fs2/fc) = 0.04128785

v = Asl,mid/(b*d)*(fsv/fc) = 0.04913955

and confined core properties:

b = 890.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.02891269

2 = Asl,com/(b*d)*(fs2/fc) = 0.04602424

v = Asl,mid/(b*d)*(fsv/fc) = 0.05477666

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.15202235

Mu = MRc (4.14) = 6.6218E+008

u = su (4.1) = 8.5401626E-006

Calculation of ratio lb/d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 9.2295561E-006$$

$$\mu_u = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 443.5927

fy1 = 369.6606

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 369.6606

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 448.1427

fy2 = 373.4523

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 373.4523

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08716324

2 = Asl,com/(b*d)*(fs2/fc) = 0.05475644

v = Asl,mid/(b*d)*(fsv/fc) = 0.10373905

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.10502967$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.06598023$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.12500314$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.21536129$$

$$Mu = MRc (4.14) = 9.2228E+008$$

$$u = su (4.1) = 9.2295561E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 8.5401626E-006$$

$$Mu = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$fc = 33.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min * F_{ywe} = \text{Min}(psh,x * F_{ywe}, psh,y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $psh_{min} \cdot F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x \cdot F_{ywe} = psh1 \cdot F_{ywe1} + ps2 \cdot F_{ywe2} = 2.40578$$
$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 \cdot Astir1 / (Asec \cdot s1) = 0.00301593$$

Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ (5.4d)} = Lstir2 \cdot Astir2 / (Asec \cdot s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

$$psh_y \cdot F_{ywe} = psh1 \cdot F_{ywe1} + ps2 \cdot F_{ywe2} = 2.87307$$
$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 \cdot Astir1 / (Asec \cdot s1) = 0.00357443$$

Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2 \cdot Astir2 / (Asec \cdot s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.45$$

$$fywe2 = 555.55$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 448.1427$$

$$fy1 = 373.4523$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/ld = 0.30$$

$$su1 = 0.4 \cdot esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_{nominal} = 0.08,$$

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 373.4523$$

$$\text{with } Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 443.5927$$

$$fy2 = 369.6606$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/lb_{min} = 0.30$$

$$su2 = 0.4 \cdot esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_{nominal} = 0.08,$$

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 369.6606$$

$$\text{with } Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 437.9212$$

$$fyv = 364.9343$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and γ_v , sh_v, ft_v, fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

$$\gamma_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from } 10.3.5, \text{ ASCE } 41-17.$$

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 364.9343$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.02593726$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04128785$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.04913955$$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.02891269$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04602424$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.05477666$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.15202235$$

$$M_u = M_{Rc} (4.14) = 6.6218E+008$$

$$u = s_u (4.1) = 8.5401626E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of M_{u2}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.2295561E-006$$

$$M_u = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_c, \phi_{cc}) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_c = 0.00782179$$

$$\text{we (5.4c) } = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $bi^2/6$ as defined at (A.2).
ase2 (\geq ase1) = $\text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $bi^2/6$ as defined at (A.2).
psh,min*Fywe = $\text{Min}(psh,x*Fywe, psh,y*Fywe) = 2.40578$

Expression (5.4d) for psh,min*Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.40578
psh1 ((5.4d), TBDY) = $Lstir1 * Astir1 / (Asec * s1) = 0.00301593$

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = $Lstir2 * Astir2 / (Asec * s2) = 0.00056047$

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.87307
psh1 ((5.4d), TBDY) = $Lstir1 * Astir1 / (Asec * s1) = 0.00357443$

Lstir1 (Length of stirrups along X) = 2560.00

Astir1 (stirrups area) = 78.53982

psh2 ((5.4d), TBDY) = $Lstir2 * Astir2 / (Asec * s2) = 0.00070345$

Lstir2 (Length of stirrups along X) = 1968.00

Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 443.5927

fy1 = 369.6606

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su1 = $0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_jacket * Asl,ten,jacket + fs_core * Asl,ten,core) / Asl,ten = 369.6606$

with Es1 = $(Es_jacket * Asl,ten,jacket + Es_core * Asl,ten,core) / Asl,ten = 200000.00$

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 448.1427

fy2 = 373.4523

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with

$$\text{Shear_factor} = 1.00$$

$$l_0/l_{0u,\min} = l_b/l_{b,\min} = 0.30$$

$$s_u2 = 0.4 \cdot e_{su2_nominal} ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{su2_nominal} = 0.08,$$

For calculation of $e_{su2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } f_{s2} = (f_{s,jacket} \cdot A_{s1,com,jacket} + f_{s,core} \cdot A_{s1,com,core}) / A_{s1,com} = 373.4523$$

$$\text{with } E_{s2} = (E_{s,jacket} \cdot A_{s1,com,jacket} + E_{s,core} \cdot A_{s1,com,core}) / A_{s1,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 437.9212$$

$$fy_v = 364.9343$$

$$s_{uv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{0u,\min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 \cdot e_{suv_nominal} ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{suv_nominal} = 0.08,$$

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } f_{sv} = (f_{s,jacket} \cdot A_{s1,mid,jacket} + f_{s,mid} \cdot A_{s1,mid,core}) / A_{s1,mid} = 364.9343$$

$$\text{with } E_{sv} = (E_{s,jacket} \cdot A_{s1,mid,jacket} + E_{s,mid} \cdot A_{s1,mid,core}) / A_{s1,mid} = 200000.00$$

$$1 = A_{s1,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08716324$$

$$2 = A_{s1,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.05475644$$

$$v = A_{s1,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.10373905$$

and confined core properties:

$$b = 390.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, \text{TBDY}) = 33.00$$

$$c_c (5A.5, \text{TBDY}) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s1,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.10502967$$

$$2 = A_{s1,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.06598023$$

$$v = A_{s1,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.12500314$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.21536129$$

$$M_u = M_{Rc} (4.14) = 9.2228E+008$$

$$u = s_u (4.1) = 9.2295561E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0936E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0936E+006$

$$V_{r1} = V_{Co1} ((10.3), \text{ASCE 41-17}) = k_{nl} \cdot V_{Co10}$$

$$V_{Co10} = 1.0936E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

Mean concrete strength: $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 867.5146$
 $\nu_u = 0.0003102$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 20816.964$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 916401.511$
where:
 $V_{sjacket} = V_{sj1} + V_{sj2} = 837764.743$
 $V_{sj1} = 523602.964$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{sj1} is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{sj2} = 314161.779$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{sj2} is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$
 $V_{s,c1} = 78636.768$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
From (11-11), ACI 440: $V_s + V_f \leq 930841.148$
 $bw = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0936E+006$

$V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl \cdot V_{Col0}$

$V_{Col0} = 1.0936E+006$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 867.5146$
 $\nu_u = 0.0003102$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 20816.964$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 916401.511$
where:
 $V_{sjacket} = V_{sj1} + V_{sj2} = 837764.743$
 $V_{sj1} = 523602.964$ is calculated for section web jacket, with:
 $d = 600.00$

Av = 157079.633

fy = 555.56

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.16666667

Vs,j2 = 314161.779 is calculated for section flange jacket, with:

d = 360.00

Av = 157079.633

fy = 555.56

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.27777778

Vs,core = Vs,c1 + Vs,c2 = 78636.768

Vs,c1 = 78636.768 is calculated for section web core, with:

d = 440.00

Av = 100530.965

fy = 444.44

s = 250.00

Vs,c1 is multiplied by Col,c1 = 1.00

s/d = 0.56818182

Vs,c2 = 0.00 is calculated for section flange core, with:

d = 200.00

Av = 100530.965

fy = 444.44

s = 250.00

Vs,c2 is multiplied by Col,c2 = 0.00

s/d = 1.25

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 930841.148

bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, fc = fcm = 33.00

New material of Secondary Member: Steel Strength, fs = fsm = 555.56

Concrete Elasticity, Ec = 26999.444

Steel Elasticity, Es = 200000.00

Existing Column

Existing material of Secondary Member: Concrete Strength, fc = fcm = 20.00

Existing material of Secondary Member: Steel Strength, fs = fsm = 444.44

Concrete Elasticity, Ec = 21019.039

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, fs = 1.25*fsm = 694.45

Existing Column

Existing material: Steel Strength, fs = 1.25*fsm = 555.55

#####

Max Height, Hmax = 750.00

Min Height, Hmin = 450.00
Max Width, Wmax = 950.00
Min Width, Wmin = 450.00
Eccentricity, Ecc = 250.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.00
Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min}$ = 0.30
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -2.7331429E-008
EDGE -B-
Shear Force, Vb = 2.7331429E-008
BOTH EDGES
Axial Force, F = -20816.964
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 0.00
-Compression: Aslc = 6999.468
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1693.318
-Compression: Asl,com = 1693.318
-Middle: Asl,mid = 3612.832

Calculation of Shear Capacity ratio , V_e/V_r = 0.42425297
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 650163.608$
with
 $M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 9.7525E+008$
 $\mu_{1+} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{1-} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 9.7525E+008$
 $\mu_{2+} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $\mu_{2-} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 6.9050030E-006$
 $M_u = 9.7525E+008$

with full section properties:

b = 450.00
d = 907.00
d' = 43.00
v = 0.00154555
N = 20816.964

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

$$\text{Shear_factor} = 1.00$$

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{su1_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{su1_nominal} = 0.08,$$

For calculation of $e_{su1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s1} = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 367.7935$$

$$\text{with } E_{s1} = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.3522$$

$$fy_2 = 367.7935$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{su2_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{su2_nominal} = 0.08,$$

For calculation of $e_{su2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = (f_{s,jacket} * A_{s2,com,jacket} + f_{s,core} * A_{s2,com,core}) / A_{s2,com} = 367.7935$$

$$\text{with } E_{s2} = (E_{s,jacket} * A_{s2,com,jacket} + E_{s,core} * A_{s2,com,core}) / A_{s2,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 442.9465$$

$$fy_v = 369.1221$$

$$s_{uv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{suv_nominal} = 0.08,$$

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY For calculation of $e_{suv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 369.1221$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.04623905$$

$$2 = A_{s2,com} / (b * d) * (f_{s2} / f_c) = 0.04623905$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.05517782$$

$$2 = A_{s2,com} / (b * d) * (f_{s2} / f_c) = 0.05517782$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$\mu_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 6.9050030E-006$$

$$Mu = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_o) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.3522

fy1 = 367.7935

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fsjacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.3522

fy2 = 367.7935

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 442.9465

fyv = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905

2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905

v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112

and confined core properties:

b = 390.00

d = 877.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s1,ten}/(b*d)*(f_{s1}/f_c) = 0.05517782$$

$$2 = A_{s1,com}/(b*d)*(f_{s2}/f_c) = 0.05517782$$

$$v = A_{s1,mid}/(b*d)*(f_{sv}/f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

$$\text{su (4.9)} = 0.18247922$$

$$\text{Mu} = \text{MRc (4.14)} = 9.7525\text{E}+008$$

$$u = \text{su (4.1)} = 6.9050030\text{E}-006$$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_{2+}

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030\text{E}-006$$

$$\text{Mu} = 9.7525\text{E}+008$$

 with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$ase \text{ ((5.4d), TBDY)} = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without

earthquake detailing (90° closed stirrups)

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.40578
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00301593
Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982
psh2 (5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00056047
Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.87307
psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00357443
Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982
psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00070345
Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

Asec = 562500.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.45

fywe2 = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.3522

fy1 = 367.7935

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.3522

fy2 = 367.7935

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 442.9465

fyv = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1,ft1,fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_jacket * Asl_mid_jacket + fs_mid * Asl_mid_core) / Asl_mid = 369.1221$$

$$\text{with } Esv = (Es_jacket * Asl_mid_jacket + Es_mid * Asl_mid_core) / Asl_mid = 200000.00$$

$$1 = Asl_ten / (b * d) * (fs1 / fc) = 0.04623905$$

$$2 = Asl_com / (b * d) * (fs2 / fc) = 0.04623905$$

$$v = Asl_mid / (b * d) * (fsv / fc) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$c =$ confinement factor = 1.00

$$1 = Asl_ten / (b * d) * (fs1 / fc) = 0.05517782$$

$$2 = Asl_com / (b * d) * (fs2 / fc) = 0.05517782$$

$$v = Asl_mid / (b * d) * (fsv / fc) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.18247922$$

$$Mu = MRc (4.14) = 9.7525E+008$$

$$u = su (4.1) = 6.9050030E-006$$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of $Mu2$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$Mu = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$fc = 33.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = shear_factor * Max(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$\text{we (5.4c) } = 0.01167368$$

$$ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = Max(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of $AnoConf$, $Aconf,min$ and $Aconf,max$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$Aconf,max1 = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$Aconf,min1 = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$
 p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$
 L_{stir1} (Length of stirrups along Y) = 2160.00
 A_{stir1} (stirrups area) = 78.53982
 p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$
 L_{stir2} (Length of stirrups along Y) = 1568.00
 A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$
 p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$
 L_{stir1} (Length of stirrups along X) = 2560.00
 A_{stir1} (stirrups area) = 78.53982
 p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$
 L_{stir2} (Length of stirrups along X) = 1968.00
 A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.3522$

$fy_1 = 367.7935$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu_{1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 367.7935$

with $Es_1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 441.3522$

$fy_2 = 367.7935$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s_u2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_u2,nominal} = 0.08$,

For calculation of $e_{s_u2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{s_y2} = f_{s_2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s_2} = (f_{s,jacket} * A_{s_l,com,jacket} + f_{s,core} * A_{s_l,com,core}) / A_{s_l,com} = 367.7935$$

$$\text{with } E_{s_2} = (E_{s,jacket} * A_{s_l,com,jacket} + E_{s,core} * A_{s_l,com,core}) / A_{s_l,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 442.9465$$

$$fy_v = 369.1221$$

$$s_{u_v} = 0.00512$$

using (30) in Bisikinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_d = 0.30$$

$$s_{u_v} = 0.4 * e_{s_{u_v},nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_{u_v},nominal} = 0.08$,

considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u_v},nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s_v} = (f_{s,jacket} * A_{s_l,mid,jacket} + f_{s,mid} * A_{s_l,mid,core}) / A_{s_l,mid} = 369.1221$$

$$\text{with } E_{s_v} = (E_{s,jacket} * A_{s_l,mid,jacket} + E_{s,mid} * A_{s_l,mid,core}) / A_{s_l,mid} = 200000.00$$

$$1 = A_{s_l,ten} / (b * d) * (f_{s_1} / f_c) = 0.04623905$$

$$2 = A_{s_l,com} / (b * d) * (f_{s_2} / f_c) = 0.04623905$$

$$v = A_{s_l,mid} / (b * d) * (f_{s_v} / f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s_l,ten} / (b * d) * (f_{s_1} / f_c) = 0.05517782$$

$$2 = A_{s_l,com} / (b * d) * (f_{s_2} / f_c) = 0.05517782$$

$$v = A_{s_l,mid} / (b * d) * (f_{s_v} / f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y_2}$ - LHS eq.(4.5) is satisfied

---->

$$s_u (4.9) = 0.18247922$$

$$M_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.5325E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.5325E+006$

$$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = k_{nl} * V_{Co10}$$

$$V_{Co10} = 1.5325E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} = f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333, \text{ but } f_c'^{0.5} < =$$

8.3 MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$\mu_u = 0.70443303$$

$$V_u = 2.7331429E+008$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 1.1791E+006$$

$$bw = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.5325E+006$

$$V_{r2} = V_{Col} \text{ ((10.3), ASCE 41-17)} = knl \cdot V_{Col0}$$

$$V_{Col0} = 1.5325E+006$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333, \text{ but } f_c'^{0.5} \leq$$

8.3 MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$\mu_u = 0.70507494$$

$$V_u = 2.7331429E+008$$

$$d = 0.8 \cdot h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$f_y = 555.56$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$s/d = 1.25$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$s/d = 0.41666667$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$

$bw = 450.00$

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 3
Integration Section: (a)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -2.1323E+007$
Shear Force, $V2 = -7074.25$
Shear Force, $V3 = -39.74554$
Axial Force, $F = -21231.538$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 1693.318$
-Compression: $As_{c,com} = 1693.318$
-Middle: $As_{c,mid} = 3612.832$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten,jacket} = 1231.504$
-Compression: $As_{c,com,jacket} = 1231.504$
-Middle: $As_{c,mid,jacket} = 2689.203$
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten,core} = 461.8141$
-Compression: $As_{c,com,core} = 461.8141$
-Middle: $As_{c,mid,core} = 923.6282$
Mean Diameter of Tension Reinforcement, $Db_L = 16.25$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_R = \alpha \cdot u = 0.0300035$
 $u = y + p = 0.0300035$

- Calculation of y -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.0025862$ ((4.29), Biskinis Phd))
 $M_y = 6.7544E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 3014.205
From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} \cdot E_c \cdot I_g = 2.6241E+014$
factor = 0.30
 $A_g = 562500.00$
Mean concrete strength: $fc' = (fc'_{jacket} \cdot \text{Area}_{jacket} + fc'_{core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 26.93333$
 $N = 21231.538$
 $E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 8.7468E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 2.2011043E-006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 294.7834$
 $d = 907.00$
 $y = 0.26171323$
 $A = 0.01732572$
 $B = 0.00915761$
with $pt = 0.00414877$
 $pc = 0.00414877$
 $p_v = 0.00885172$
 $N = 21231.538$

$b = 450.00$
 $\mu = 0.04740904$
 $y_{comp} = 9.3361155E-006$
 with $f_c = 33.00$
 $E_c = 26999.444$
 $y = 0.25981135$
 $A = 0.01703103$
 $B = 0.00898114$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 - Calculation of ρ -

 From table 10-8: $\rho = 0.0274173$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.42425297$

$d = d_{external} = 907.00$

$s = s_{external} = 0.00$

- $t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00427788$

jacket: $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00357443$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2560.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00070345$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1968.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 21231.538$

$A_g = 562500.00$

$f_{cE} = (f_{c,jacket} * Area_{jacket} + f_{c,core} * Area_{core}) / section_area = 26.93333$

$f_{yE} = (f_{y,ext_Long_Reinf} * Area_{ext_Long_Reinf} + f_{y,int_Long_Reinf} * Area_{int_Long_Reinf}) / Area_{Tot_Long_Rein} = 526.2339$

$f_{yE} = (f_{y,ext_Trans_Reinf} * s_1 + f_{y,int_Trans_Reinf} * s_2) / (s_1 + s_2) = 537.2876$

$\rho_l = Area_{Tot_Long_Rein} / (b * d) = 0.01714926$

$b = 450.00$

$d = 907.00$

$f_{cE} = 26.93333$

 End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 13

column C1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

Existing Column

Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material: Steel Strength, $f_s = f_{sm} = 444.44$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -2.1323E+007$
Shear Force, $V_a = -7074.25$
EDGE -B-
Bending Moment, $M_b = 96537.118$
Shear Force, $V_b = 7074.25$
BOTH EDGES
Axial Force, $F = -21231.538$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 1693.318$
-Compression: $A_{st,com} = 1693.318$
-Middle: $A_{st,mid} = 3612.832$
Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 16.25$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = *V_n = 1.3703E+006$
 V_n ((10.3), ASCE 41-17) = $knI*V_{CoIO} = 1.3703E+006$
 $V_{CoI} = 1.3703E+006$
 $knI = 1.00$
 $displacement_ductility_demand = 0.0477572$

NOTE: In expression (10-3) ' $V_s = A_v*f_y*d/s$ ' is replaced by ' $V_s + f*V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{jacket}*Area_{jacket} + f_c'_{core}*Area_{core})/Area_{section} = 20.80$, but $f_c'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.00$
 $M_u = 96537.118$
 $V_u = 7074.25$
 $d = 0.8*h = 760.00$
 $N_u = 21231.538$
 $A_g = 427500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 976155.669$
where:
 $V_{sjacket} = V_{sj1} + V_{sj2} = 879645.943$
 $V_{sj1} = 282743.339$ is calculated for section web jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{sj1} is multiplied by $Col,j1 = 1.00$
 $s/d = 0.27777778$
 $V_{sj2} = 596902.604$ is calculated for section flange jacket, with:
 $d = 760.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{sj2} is multiplied by $Col,j2 = 1.00$
 $s/d = 0.13157895$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 96509.726$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 400.00$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col,c1 = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 96509.726$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 400.00$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col,c2 = 1.00$

$$s/d = 0.41666667$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 1.0362E+006$

$$bw = 450.00$$

displacement_ductility_demand is calculated as ϕ / y

- Calculation of ϕ / y for END B -
for rotation axis 3 and integ. section (b)

From analysis, chord rotation = $1.2292778E-005$

$$y = (M_y * L_s / 3) / E_{eff} = 0.0002574 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 6.7544E+008$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 300.00$$

From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} * E_c * I_g = 2.6241E+014$

$$\text{factor} = 0.30$$

$$A_g = 562500.00$$

$$\text{Mean concrete strength: } f'_c = (f'_{c,jacket} * \text{Area}_{jacket} + f'_{c,core} * \text{Area}_{core}) / \text{Area}_{section} = 26.93333$$

$$N = 21231.538$$

$$E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 8.7468E+014$$

Calculation of Yielding Moment M_y

Calculation of ϕ / y and M_y according to Annex 7 -

$$y = \text{Min}(y_{ten}, y_{com})$$

$$y_{ten} = 2.2011043E-006$$

$$\text{with ((10.1), ASCE 41-17) } f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 294.7834$$

$$d = 907.00$$

$$y = 0.26171323$$

$$A = 0.01732572$$

$$B = 0.00915761$$

$$\text{with } p_t = 0.00414877$$

$$p_c = 0.00414877$$

$$p_v = 0.00885172$$

$$N = 21231.538$$

$$b = 450.00$$

$$r = 0.04740904$$

$$y_{comp} = 9.3361155E-006$$

with $f_c = 33.00$

$$E_c = 26999.444$$

$$y = 0.25981135$$

$$A = 0.01703103$$

$$B = 0.00898114$$

$$\text{with } E_s = 200000.00$$

Calculation of ratio I_b / I_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (b)

Calculation No. 14

column C1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3
(Bending local axis: 2)

Section Type: rcjtc

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -0.0003102$

EDGE -B-

Shear Force, $V_b = 0.0003102$

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1539.38$

-Compression: $As_{c,com} = 2475.575$

-Middle: $As_{l,mid} = 2984.513$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.5622163$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 614853.514$

with

$M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 9.2228E+008$

$M_{u1+} = 6.6218E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 9.2228E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 9.2228E+008$

$M_{u2+} = 6.6218E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 9.2228E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 8.5401626E-006$

$$\mu = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 448.1427
fy1 = 373.4523
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 373.4523

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814

ft2 = 443.5927

fy2 = 369.6606

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 369.6606

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044
shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.02593726

2 = Asl,com/(b*d)*(fs2/fc) = 0.04128785

v = Asl,mid/(b*d)*(fsv/fc) = 0.04913955

and confined core properties:

b = 890.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.02891269

2 = Asl,com/(b*d)*(fs2/fc) = 0.04602424

v = Asl,mid/(b*d)*(fsv/fc) = 0.05477666

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is satisfied

---->

$$\begin{aligned} su(4.9) &= 0.15202235 \\ \mu &= MRc(4.14) = 6.6218E+008 \\ u &= su(4.1) = 8.5401626E-006 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u1} -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 9.2295561E-006 \\ \mu &= 9.2228E+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 450.00 \\ d &= 707.00 \\ d' &= 43.00 \\ v &= 0.00198277 \\ N &= 20816.964 \\ f_c &= 33.00 \\ c_o(5A.5, TBDY) &= 0.002 \\ \text{Final value of } \mu_u &: \mu_u^* = \text{shear_factor} * \text{Max}(\mu_u, c_c) = 0.00782179 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \mu_u &= 0.00782179 \\ w_e(5.4c) &= 0.01167368 \end{aligned}$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (> a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1}(\text{Length of stirrups along } Y) = 2160.00$$

$$A_{stir1}(\text{stirrups area}) = 78.53982$$

$$p_{sh2}((5.4d)) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2}(\text{Length of stirrups along } Y) = 1568.00$$

$$A_{stir2}(\text{stirrups area}) = 50.26548$$

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 2.87307
psh₁ ((5.4d), TBDY) = Lstir₁*Astir₁/(Asec*s₁) = 0.00357443
Lstir₁ (Length of stirrups along X) = 2560.00
Astir₁ (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = Lstir₂*Astir₂/(Asec*s₂) = 0.00070345
Lstir₂ (Length of stirrups along X) = 1968.00
Astir₂ (stirrups area) = 50.26548

Asec = 562500.00

s₁ = 100.00

s₂ = 250.00

fywe₁ = 694.45

fywe₂ = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y₁ = 0.00140044

sh₁ = 0.0044814

ft₁ = 443.5927

fy₁ = 369.6606

su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 369.6606

with Es₁ = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y₂ = 0.00140044

sh₂ = 0.0044814

ft₂ = 448.1427

fy₂ = 373.4523

su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 373.4523

with Es₂ = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

y_v = 0.00140044

sh_v = 0.0044814

ft_v = 437.9212

fy_v = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and y_v, sh_v,ft_v,fy_v, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs₁/fc) = 0.08716324

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.05475644$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10373905$$

and confined core properties:

$$b = 390.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.10502967$$

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.06598023$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.12500314$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.21536129$$

$$M_u = M_{Rc} (4.14) = 9.2228E+008$$

$$u = s_u (4.1) = 9.2295561E-006$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

Calculation of M_{u2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 8.5401626E-006$$

$$M_u = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{min} \cdot F_{ywe} = \text{Min}(psh_x \cdot F_{ywe}, psh_y \cdot F_{ywe}) = 2.40578$$

Expression (5.4d) for $psh_{min} \cdot F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x \cdot F_{ywe} = psh1 \cdot F_{ywe1} + ps2 \cdot F_{ywe2} = 2.40578$$
$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} \cdot A_{stir1} / (A_{sec} \cdot s1) = 0.00301593$$

Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ (5.4d)} = L_{stir2} \cdot A_{stir2} / (A_{sec} \cdot s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

$$psh_y \cdot F_{ywe} = psh1 \cdot F_{ywe1} + ps2 \cdot F_{ywe2} = 2.87307$$
$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} \cdot A_{stir1} / (A_{sec} \cdot s1) = 0.00357443$$

Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ ((5.4d), TBDY)} = L_{stir2} \cdot A_{stir2} / (A_{sec} \cdot s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fy_{we1} = 694.45$$

$$fy_{we2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 448.1427$$

$$fy1 = 373.4523$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$su1 = 0.4 \cdot esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (f_{s,jacket} \cdot A_{sl,ten,jacket} + f_{s,core} \cdot A_{sl,ten,core}) / A_{sl,ten} = 373.4523$$

$$\text{with } Es1 = (E_{s,jacket} \cdot A_{sl,ten,jacket} + E_{s,core} \cdot A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 443.5927$$

$$fy2 = 369.6606$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$su2 = 0.4 \cdot esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (f_{s,jacket} \cdot A_{sl,com,jacket} + f_{s,core} \cdot A_{sl,com,core}) / A_{sl,com} = 369.6606$$

$$\text{with } Es2 = (E_{s,jacket} \cdot A_{sl,com,jacket} + E_{s,core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 437.9212$$

$$fyv = 364.9343$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 364.9343$$

$$\text{with } Esv = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.02593726$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.04128785$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.04913955$$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

c = confinement factor = 1.00

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.02891269$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.04602424$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.05477666$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.15202235$$

$$Mu = MRc (4.14) = 6.6218E+008$$

$$u = su (4.1) = 8.5401626E-006$$

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.2295561E-006$$

$$Mu = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$fc = 33.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00782179$$

$$we (5.4c) = 0.01167368$$

$$ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.53375773$$

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase2 (>=ase1) = \text{Max}(((A_{conf,max2}-A_{noConf2})/A_{conf,max2})*(A_{conf,min2}/A_{conf,max2}),0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min}*F_{ywe} = \text{Min}(psh_x*F_{ywe}, psh_y*F_{ywe}) = 2.40578$

Expression (5.4d) for $psh_{min}*F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $psh_x*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 2.40578$

$psh1$ ((5.4d), TBDY) = $L_{stir1}*A_{stir1}/(A_{sec}*s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2}*A_{stir2}/(A_{sec}*s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $psh_y*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 2.87307$

$psh1$ ((5.4d), TBDY) = $L_{stir1}*A_{stir1}/(A_{sec}*s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2}*A_{stir2}/(A_{sec}*s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 443.5927$

$fy1 = 369.6606$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lou,min = lb/d = 0.30$

$su1 = 0.4*esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket}*A_{sl,ten,jacket} + fs_{core}*A_{sl,ten,core})/A_{sl,ten} = 369.6606$

with $Es1 = (Es_{jacket}*A_{sl,ten,jacket} + Es_{core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 448.1427
fy2 = 373.4523
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 373.4523

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 437.9212

fyv = 364.9343

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08716324

2 = Asl,com/(b*d)*(fs2/fc) = 0.05475644

v = Asl,mid/(b*d)*(fsv/fc) = 0.10373905

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.10502967

2 = Asl,com/(b*d)*(fs2/fc) = 0.06598023

v = Asl,mid/(b*d)*(fsv/fc) = 0.12500314

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.21536129

Mu = MRc (4.14) = 9.2228E+008

u = su (4.1) = 9.2295561E-006

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 1.0936E+006

Calculation of Shear Strength at edge 1, Vr1 = 1.0936E+006

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VColO

VColO = 1.0936E+006
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

$\mu_u = 867.5146$

$\nu_u = 0.0003102$

$d = 0.8 \cdot h = 600.00$

$N_u = 20816.964$

$A_g = 337500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 916401.511$

where:

$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 837764.743$

$V_{s,j1} = 523602.964$ is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j1}$ is multiplied by $\text{Col},j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j2}$ is multiplied by $\text{Col},j2 = 1.00$

$s/d = 0.27777778$

$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 78636.768$

$V_{s,c1} = 78636.768$ is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c1}$ is multiplied by $\text{Col},c1 = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c2}$ is multiplied by $\text{Col},c2 = 0.00$

$s/d = 1.25$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 930841.148$

$b_w = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.0936E+006$

$V_{r2} = V_{\text{Col}}$ ((10.3), ASCE 41-17) = $knl \cdot V_{\text{ColO}}$

$V_{\text{ColO}} = 1.0936E+006$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

$\mu_u = 867.5146$

$\nu_u = 0.0003102$

$d = 0.8 \cdot h = 600.00$

$N_u = 20816.964$
 $A_g = 337500.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 916401.511$
 where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 837764.743$
 $V_{s,j1} = 523602.964$ is calculated for section web jacket, with:
 $d = 600.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 $V_{s,j1}$ is multiplied by $Col,j1 = 1.00$
 $s/d = 0.16666667$
 $V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:
 $d = 360.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 $V_{s,j2}$ is multiplied by $Col,j2 = 1.00$
 $s/d = 0.27777778$
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$
 $V_{s,c1} = 78636.768$ is calculated for section web core, with:
 $d = 440.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c1}$ is multiplied by $Col,c1 = 1.00$
 $s/d = 0.56818182$
 $V_{s,c2} = 0.00$ is calculated for section flange core, with:
 $d = 200.00$
 $A_v = 100530.965$
 $f_y = 444.44$
 $s = 250.00$
 $V_{s,c2}$ is multiplied by $Col,c2 = 0.00$
 $s/d = 1.25$
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$
 From (11-11), ACI 440: $V_s + V_f \leq 930841.148$
 $bw = 450.00$

 End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At local axis: 3

 Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rcjtcs

Constant Properties

 Knowledge Factor, $\phi = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 Jacket
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
 Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
 Concrete Elasticity, $E_c = 21019.039$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $Ecc = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -2.7331429E-008$

EDGE -B-

Shear Force, $V_b = 2.7331429E-008$

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 1693.318$

-Compression: $A_{st,com} = 1693.318$

-Middle: $A_{st,mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.42425297$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 650163.608$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 9.7525E+008$

$M_{u1+} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 9.7525E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 9.7525E+008$

$M_{u2+} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 9.7525E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 6.9050030E-006$

$M_u = 9.7525E+008$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935$$

$$\text{with } Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 441.3522$$

$$fy2 = 367.7935$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 442.9465$$

$$fyv = 369.1221$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.18247922$$

$$\begin{aligned} \mu &= MRC(4.14) = 9.7525E+008 \\ u &= su(4.1) = 6.9050030E-006 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 6.9050030E-006 \\ \mu &= 9.7525E+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 450.00 \\ d &= 907.00 \\ d' &= 43.00 \\ v &= 0.00154555 \\ N &= 20816.964 \\ f_c &= 33.00 \end{aligned}$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e(5.4c) = 0.01167368$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1}((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1}(\text{Length of stirrups along } Y) = 2160.00$$

$$A_{stir1}(\text{stirrups area}) = 78.53982$$

$$p_{sh2}(5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2}(\text{Length of stirrups along } Y) = 1568.00$$

$$A_{stir2}(\text{stirrups area}) = 50.26548$$

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 2.87307
psh₁ ((5.4d), TBDY) = Lstir₁*Astir₁/(Asec*s₁) = 0.00357443
Lstir₁ (Length of stirrups along X) = 2560.00
Astir₁ (stirrups area) = 78.53982
psh₂ ((5.4d), TBDY) = Lstir₂*Astir₂/(Asec*s₂) = 0.00070345
Lstir₂ (Length of stirrups along X) = 1968.00
Astir₂ (stirrups area) = 50.26548

Asec = 562500.00

s₁ = 100.00

s₂ = 250.00

fywe₁ = 694.45

fywe₂ = 555.55

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002

c = confinement factor = 1.00

y₁ = 0.00140044

sh₁ = 0.0044814

ft₁ = 441.3522

fy₁ = 367.7935

su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.7935

with Es₁ = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y₂ = 0.00140044

sh₂ = 0.0044814

ft₂ = 441.3522

fy₂ = 367.7935

su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es₂ = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

y_v = 0.00140044

sh_v = 0.0044814

ft_v = 442.9465

fy_v = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and y_v, sh_v,ft_v,fy_v, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/d)^{2/3}), from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221

with Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs₁/fc) = 0.04623905

2 = Asl,com/(b*d)*(fs₂/fc) = 0.04623905

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05517782$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.05517782$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$\mu_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$\mu_u = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

c = confinement factor = 1.00

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.3522$

$fy_1 = 367.7935$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu_{1,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.7935$

with $Es_1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 441.3522$

$fy_2 = 367.7935$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu_{2,nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 367.7935$

with $Es_2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$$f_{tv} = 442.9465$$

$$f_{yv} = 369.1221$$

$$s_{uv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and γ_v , sh_v, f_{tv}, f_{yv} , it is considered
characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , sh_1, f_{t1}, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 369.1221$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.04623905$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04623905$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.05517782$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.05517782$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$M_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of M_u2 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$M_u = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.
 $A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.
 $A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 441.3522$

$fy1 = 367.7935$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lou_{min} = lb/ld = 0.30$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.7935$

with $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00140044$

$sh_2 = 0.0044814$
 $ft_2 = 441.3522$
 $fy_2 = 367.7935$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lo_{min} = lb/lb_{min} = 0.30$
 $su_2 = 0.4 * esu_{2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,
 For calculation of $esu_{2_nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 367.7935$
 with $Es_2 = (Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lo_{min} = lb/ld = 0.30$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and yv , shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 369.1221$
 with $Es_v = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.04623905$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.04623905$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.09901112$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.05517782$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.05517782$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.11815159$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.18247922$
 $Mu = MRc (4.14) = 9.7525E+008$
 $u = su (4.1) = 6.9050030E-006$

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of Shear Strength $Vr = Min(Vr1, Vr2) = 1.5325E+006$

Calculation of Shear Strength at edge 1, $Vr1 = 1.5325E+006$
 $Vr1 = VCol ((10.3), ASCE 41-17) = knl * VColO$
 $VColO = 1.5325E+006$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.70443303$

$V_u = 2.7331429E-008$

$d = 0.8 \cdot h = 760.00$

$N_u = 20816.964$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$

$s/d = 0.27777778$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col_{j2} = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col_{c1} = 0.00$

$s/d = 1.25$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col_{c2} = 1.00$

$s/d = 0.41666667$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$

$b_w = 450.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.5325E+006$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{ColO}$

$V_{ColO} = 1.5325E+006$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.70507494$

$V_u = 2.7331429E-008$

$d = 0.8 \cdot h = 760.00$

$N_u = 20816.964$

Ag = 427500.00
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$
 $V_{s,j1} = 314161.779$ is calculated for section web jacket, with:
d = 360.00
Av = 157079.633
fy = 555.56
s = 100.00
 $V_{s,j1}$ is multiplied by Col,j1 = 1.00
s/d = 0.27777778
 $V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:
d = 760.00
Av = 157079.633
fy = 555.56
s = 100.00
 $V_{s,j2}$ is multiplied by Col,j2 = 1.00
s/d = 0.13157895
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$
 $V_{s,c1} = 0.00$ is calculated for section web core, with:
d = 200.00
Av = 100530.965
fy = 444.44
s = 250.00
 $V_{s,c1}$ is multiplied by Col,c1 = 0.00
s/d = 1.25
 $V_{s,c2} = 107231.957$ is calculated for section flange core, with:
d = 600.00
Av = 100530.965
fy = 444.44
s = 250.00
 $V_{s,c2}$ is multiplied by Col,c2 = 1.00
s/d = 0.41666667
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$
bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1
At local axis: 2
Integration Section: (b)
Section Type: rcjtcs

Constant Properties

Knowledge Factor, = 1.00
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$
Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $Ecc = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 40080.744$
Shear Force, $V_2 = 7074.25$
Shear Force, $V_3 = 39.74554$
Axial Force, $F = -21231.538$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 1539.38$
-Compression: $A_{sc,com} = 2475.575$
-Middle: $A_{sc,mid} = 2984.513$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten,jacket} = 1231.504$
-Compression: $A_{sc,com,jacket} = 1859.823$
-Middle: $A_{sc,mid,jacket} = 2060.885$
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten,core} = 307.8761$
-Compression: $A_{sc,com,core} = 615.7522$
-Middle: $A_{sc,mid,core} = 923.6282$
Mean Diameter of Tension Reinforcement, $Db_L = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \rho \cdot u = 0.02414238$
 $u = \rho \cdot y + p = 0.02414238$

- Calculation of ρ -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.00093398$ ((4.29), Biskinis Phd))
 $M_y = 4.8181E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1008.434
From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 1.7341E+014$
factor = 0.30
 $A_g = 562500.00$
Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$
 $N = 21231.538$
 $E_c \cdot I_g = E_c \cdot I_{g,jacket} + E_c \cdot I_{g,core} = 5.7803E+014$

Calculation of Yielding Moment M_y

Calculation of ρ and M_y according to Annex 7 -

Assuming neutral axis within flange ($\rho < t/d$, compression zone rectangular) with:
flange width, $b = 950.00$
web width, $b_w = 450.00$
flange thickness, $t = 450.00$

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 2.6210528\text{E}-006$
 with $((10.1), \text{ASCE } 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 294.7834$
 $d = 707.00$
 $y = 0.20461423$
 $A = 0.01052854$
 $B = 0.00498025$
 with $p_t = 0.00229194$
 $p_c = 0.00368581$
 $p_v = 0.00444355$
 $N = 21231.538$
 $b = 950.00$
 $" = 0.06082037$
 $y_{\text{comp}} = 1.5348064\text{E}-005$
 with $f_c = 33.00$
 $E_c = 26999.444$
 $y = 0.20274895$
 $A = 0.01034946$
 $B = 0.00487302$
 with $E_s = 200000.00$
 CONFIRMATION: $y = 0.20362798 < t/d$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.0232084$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{CoI} E = 0.5622163$

$d = d_{\text{external}} = 707.00$

$s = s_{\text{external}} = 0.00$

- $t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.0035764$

jacket: $s_1 = A_{v1} \cdot L_{\text{stir}1} / (s_1 \cdot A_g) = 0.00301593$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir}1} = 2160.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot L_{\text{stir}2} / (s_2 \cdot A_g) = 0.00056047$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir}2} = 1568.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 21231.538$

$A_g = 562500.00$

$f_{cE} = (f_{c_jacket} \cdot \text{Area}_{\text{jacket}} + f_{c_core} \cdot \text{Area}_{\text{core}}) / \text{section_area} = 26.93333$

$f_{yE} = (f_{y_ext_Long_Reinf} \cdot \text{Area}_{\text{ext_Long_Reinf}} + f_{y_int_Long_Reinf} \cdot \text{Area}_{\text{int_Long_Reinf}}) / \text{Area}_{\text{Tot_Long_Rein}} =$

526.2339

$f_{yE} = (f_{y_ext_Trans_Reinf} \cdot s_1 + f_{y_int_Trans_Reinf} \cdot s_2) / (s_1 + s_2) = 538.146$

$\rho_l = \text{Area}_{\text{Tot_Long_Rein}} / (b \cdot d) = 0.0104213$

$b = 950.00$

$d = 707.00$

$f_{cE} = 26.93333$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 15

column C1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand,

the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as

Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$
Existing Column
Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material: Steel Strength, $f_s = f_{sm} = 444.44$

Max Height, $H_{max} = 750.00$
Min Height, $H_{min} = 450.00$
Max Width, $W_{max} = 950.00$
Min Width, $W_{min} = 450.00$
Eccentricity, $Ecc = 250.00$
Jacket Thickness, $t_j = 100.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = 79873.692$
Shear Force, $V_a = -39.74554$
EDGE -B-
Bending Moment, $M_b = 40080.744$
Shear Force, $V_b = 39.74554$
BOTH EDGES
Axial Force, $F = -21231.538$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 6999.468$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 1539.38$
-Compression: $A_{sc,com} = 2475.575$
-Middle: $A_{st,mid} = 2984.513$
Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 16.57143$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 1.1301E+006$
 $V_n ((10.3), ASCE 41-17) = k_n l V_{CoI} = 1.1301E+006$
 $V_{CoI} = 1.1301E+006$
 $k_n l = 1.00$
displacement_ductility_demand = 1.5506497E-005

NOTE: In expression (10-3) ' $V_s = A_v f_y d/s$ ' is replaced by ' $V_s + f V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{jacket} Area_{jacket} + f_c'_{core} Area_{core}) / Area_{section} = 20.80$, but $f_c'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.00$
 $M_u = 40080.744$
 $V_u = 39.74554$
 $d = 0.8 \cdot h = 600.00$
 $N_u = 21231.538$
 $A_g = 337500.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s,jacket} + V_{s,core} = 824756.036$
where:
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 753982.237$
 $V_{s,j1} = 471238.898$ is calculated for section web jacket, with:
 $d = 600.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

$V_{s,j1}$ is multiplied by $Col,j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 282743.339$ is calculated for section flange jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

$V_{s,j2}$ is multiplied by $Col,j2 = 1.00$

$s/d = 0.27777778$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 70773.799$

$V_{s,c1} = 70773.799$ is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col,c1 = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col,c2 = 0.00$

$s/d = 1.25$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 818016.733$

$bw = 450.00$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END B -
for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 1.4482696E-008$

$y = (M_y * L_s / 3) / E_{eff} = 0.00093398$ ((4.29), Biskinis Phd))

$M_y = 4.8181E+008$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1008.434

From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7341E+014$

factor = 0.30

$A_g = 562500.00$

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333$

$N = 21231.538$

$E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 5.7803E+014$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($\delta / y < t/d$, compression zone rectangular) with:

flange width, $b = 950.00$

web width, $bw = 450.00$

flange thickness, $t = 450.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 2.6210528E-006$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 294.7834$

$d = 707.00$

$y = 0.20461423$

$A = 0.01052854$

$B = 0.00498025$

with $p_t = 0.00229194$
 $p_c = 0.00368581$
 $p_v = 0.00444355$
 $N = 21231.538$
 $b = 950.00$
 $" = 0.06082037$
 $y_{comp} = 1.5348064E-005$
 with $f_c = 33.00$
 $E_c = 26999.444$
 $y = 0.20274895$
 $A = 0.01034946$
 $B = 0.00487302$
 with $E_s = 200000.00$
 CONFIRMATION: $y = 0.20362798 < t/d$

Calculation of ratio I_b/I_d

Inadequate Lap Length with $I_b/I_d = 0.30$

End Of Calculation of Shear Capacity for element: column JTC1 of floor 1
 At local axis: 3
 Integration Section: (b)

Calculation No. 16

column C1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $k = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -0.0003102$

EDGE -B-

Shear Force, $V_b = 0.0003102$

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 0.00$

-Compression: $A_{sl,c} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1539.38$

-Compression: $A_{sl,com} = 2475.575$

-Middle: $A_{sl,mid} = 2984.513$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.5622163$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 614853.514$

with

$$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 9.2228E+008$$

$M_{u1+} = 6.6218E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 9.2228E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 9.2228E+008$$

$M_{u2+} = 6.6218E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination

$M_{u2-} = 9.2228E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$\phi_u = 8.5401626E-006$$

$$M_u = 6.6218E+008$$

with full section properties:

$$b = 950.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00093921$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00782179$$

$$\omega_e \text{ (5.4c)} = 0.01167368$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.40578$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$\text{Astir2 (stirrups area)} = 50.26548$$

$$\text{psh}_y \cdot \text{Fywe} = \text{psh}_1 \cdot \text{Fywe}_1 + \text{ps}_2 \cdot \text{Fywe}_2 = 2.87307$$

$$\text{psh}_1 ((5.4d), \text{TBDY}) = \text{Lstir}_1 \cdot \text{Astir}_1 / (\text{Asec} \cdot \text{s}_1) = 0.00357443$$

$$\text{Lstir}_1 (\text{Length of stirrups along X}) = 2560.00$$

$$\text{Astir}_1 (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 ((5.4d), \text{TBDY}) = \text{Lstir}_2 \cdot \text{Astir}_2 / (\text{Asec} \cdot \text{s}_2) = 0.00070345$$

$$\text{Lstir}_2 (\text{Length of stirrups along X}) = 1968.00$$

$$\text{Astir}_2 (\text{stirrups area}) = 50.26548$$

$$\text{Asec} = 562500.00$$

$$\text{s}_1 = 100.00$$

$$\text{s}_2 = 250.00$$

$$\text{fywe}_1 = 694.45$$

$$\text{fywe}_2 = 555.55$$

$$\text{fce} = 33.00$$

$$\text{From } ((5.A.5), \text{TBDY}), \text{TBDY: } \text{cc} = 0.002$$

$$\text{c} = \text{confinement factor} = 1.00$$

$$\text{y}_1 = 0.00140044$$

$$\text{sh}_1 = 0.0044814$$

$$\text{ft}_1 = 448.1427$$

$$\text{fy}_1 = 373.4523$$

$$\text{su}_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{su}_1 = 0.4 \cdot \text{esu}_1 \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esu}_1 \text{ nominal} = 0.08,$$

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$\text{y}_1, \text{sh}_1, \text{ft}_1, \text{fy}_1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_1 = (\text{fs,jacket} \cdot \text{Asl,ten,jacket} + \text{fs,core} \cdot \text{Asl,ten,core}) / \text{Asl,ten} = 373.4523$$

$$\text{with } \text{Es}_1 = (\text{Es,jacket} \cdot \text{Asl,ten,jacket} + \text{Es,core} \cdot \text{Asl,ten,core}) / \text{Asl,ten} = 200000.00$$

$$\text{y}_2 = 0.00140044$$

$$\text{sh}_2 = 0.0044814$$

$$\text{ft}_2 = 443.5927$$

$$\text{fy}_2 = 369.6606$$

$$\text{su}_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/lb,min} = 0.30$$

$$\text{su}_2 = 0.4 \cdot \text{esu}_2 \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esu}_2 \text{ nominal} = 0.08,$$

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$$\text{y}_2, \text{sh}_2, \text{ft}_2, \text{fy}_2, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_2 = (\text{fs,jacket} \cdot \text{Asl,com,jacket} + \text{fs,core} \cdot \text{Asl,com,core}) / \text{Asl,com} = 369.6606$$

$$\text{with } \text{Es}_2 = (\text{Es,jacket} \cdot \text{Asl,com,jacket} + \text{Es,core} \cdot \text{Asl,com,core}) / \text{Asl,com} = 200000.00$$

$$\text{y}_v = 0.00140044$$

$$\text{sh}_v = 0.0044814$$

$$\text{ft}_v = 437.9212$$

$$\text{fy}_v = 364.9343$$

$$\text{suv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{suv} = 0.4 \cdot \text{esuv}_v \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esuv}_v \text{ nominal} = 0.08,$$

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

$$\text{y}_v, \text{sh}_v, \text{ft}_v, \text{fy}_v, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_v = (\text{fs,jacket} \cdot \text{Asl,mid,jacket} + \text{fs,mid} \cdot \text{Asl,mid,core}) / \text{Asl,mid} = 364.9343$$

$$\text{with } \text{Es}_v = (\text{Es,jacket} \cdot \text{Asl,mid,jacket} + \text{Es,mid} \cdot \text{Asl,mid,core}) / \text{Asl,mid} = 200000.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.02593726$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04128785$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.04913955$$

and confined core properties:

$$b = 890.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.02891269$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04602424$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.05477666$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.15202235$$

$$\mu_u = M_{Rc} (4.14) = 6.6218E+008$$

$$u = s_u (4.1) = 8.5401626E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u1} -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.2295561E-006$$

$$\mu_u = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, cc) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 2.40578$

Expression (5.4d) for $p_{sh,min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.40578$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.87307$

p_{sh1} ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

p_{sh2} ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

 $A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.002$

$c = \text{confinement factor} = 1.00$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 443.5927$

$fy1 = 369.6606$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 369.6606$

with $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 448.1427$

$fy2 = 373.4523$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 373.4523$

with $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00140044
shv = 0.0044814
ftv = 437.9212
fyv = 364.9343
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 364.9343

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08716324

2 = Asl,com/(b*d)*(fs2/fc) = 0.05475644

v = Asl,mid/(b*d)*(fsv/fc) = 0.10373905

and confined core properties:

b = 390.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.10502967

2 = Asl,com/(b*d)*(fs2/fc) = 0.06598023

v = Asl,mid/(b*d)*(fsv/fc) = 0.12500314

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.21536129

Mu = MRc (4.14) = 9.2228E+008

u = su (4.1) = 9.2295561E-006

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2+

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 8.5401626E-006

Mu = 6.6218E+008

with full section properties:

b = 950.00

d = 707.00

d' = 43.00

v = 0.00093921

N = 20816.964

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00782179

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00782179

we (5.4c) = 0.01167368

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.53375773

$$ase1 = \text{Max}(((Aconf,max1 - AnoConf1)/Aconf,max1) * (Aconf,min1/Aconf,max1), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$ase2 (\geq ase1) = \text{Max}(((Aconf,max2 - AnoConf2)/Aconf,max2) * (Aconf,min2/Aconf,max2), 0) = 0.53375773$$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min * Fywe = \text{Min}(psh,x * Fywe, psh,y * Fywe) = 2.40578$$

Expression (5.4d) for psh,min * Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.40578$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00301593$$

$$Lstir1 \text{ (Length of stirrups along Y)} = 2160.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = Lstir2 * Astir2 / (Asec * s2) = 0.00056047$$

$$Lstir2 \text{ (Length of stirrups along Y)} = 1568.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$psh,y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307$$

$$psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$$

$$Lstir1 \text{ (Length of stirrups along X)} = 2560.00$$

$$Astir1 \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$$

$$Lstir2 \text{ (Length of stirrups along X)} = 1968.00$$

$$Astir2 \text{ (stirrups area)} = 50.26548$$

$$Asec = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.45$$

$$fywe2 = 555.55$$

$$fce = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 448.1427$$

$$fy1 = 373.4523$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 373.4523$$

with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 443.5927$
 $fy_2 = 369.6606$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} \cdot A_{s,com,jacket} + fs_{core} \cdot A_{s,com,core}) / A_{s,com} = 369.6606$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 437.9212$
 $fy_v = 364.9343$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_d = 0.30$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 364.9343$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.02593726$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.04128785$
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / fc) = 0.04913955$

and confined core properties:

$b = 890.00$
 $d = 677.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.02891269$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.04602424$
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / fc) = 0.05477666$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_s, y_2$ - LHS eq.(4.5) is satisfied

---->

$su (4.9) = 0.15202235$
 $Mu = MRc (4.14) = 6.6218E+008$
 $u = su (4.1) = 8.5401626E-006$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_2 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 9.2295561E-006$$

$$\mu = 9.2228E+008$$

with full section properties:

$$b = 450.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00198277$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$\omega (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00782179$$

$$\omega_e (5.4c) = 0.01167368$$

$$\text{ase ((5.4d), TBDY) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.53375773$$

$$\text{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1})/A_{conf,max1}) * (A_{conf,min1}/A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{ase2} (>= \text{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$\text{psh}_{min} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 2.40578$$

Expression (5.4d) for $\text{psh}_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.40578$$

$$\text{psh}_1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00301593$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2160.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00056047$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1568.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.87307$$

$$\text{psh}_1 ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00357443$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2560.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00070345$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1968.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 562500.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.002$
 $c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 443.5927$$

$$fy1 = 369.6606$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_jacket * Asl,ten,jacket + fs_core * Asl,ten,core) / Asl,ten = 369.6606$$

$$\text{with } Es1 = (Es_jacket * Asl,ten,jacket + Es_core * Asl,ten,core) / Asl,ten = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 448.1427$$

$$fy2 = 373.4523$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_jacket * Asl,com,jacket + fs_core * Asl,com,core) / Asl,com = 373.4523$$

$$\text{with } Es2 = (Es_jacket * Asl,com,jacket + Es_core * Asl,com,core) / Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 437.9212$$

$$fyv = 364.9343$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_jacket * Asl,mid,jacket + fs_mid * Asl,mid,core) / Asl,mid = 364.9343$$

$$\text{with } Esv = (Es_jacket * Asl,mid,jacket + Es_mid * Asl,mid,core) / Asl,mid = 200000.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.08716324$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.05475644$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.10373905$$

and confined core properties:

$$b = 390.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 33.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.10502967$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.06598023$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.12500314$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

---->

$$\mu (4.9) = 0.21536129$$

$$\mu = M/R_c (4.14) = 9.2228E+008$$

$$u = \mu (4.1) = 9.2295561E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0936E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.0936E+006$

$$V_{r1} = V_{col} ((10.3), ASCE 41-17) = k_{nl} * V_{col0}$$

$$V_{col0} = 1.0936E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 26.93333$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 867.5146$$

$$V_u = 0.0003102$$

$$d = 0.8 * h = 600.00$$

$$N_u = 20816.964$$

$$A_g = 337500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 916401.511$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 837764.743$$

$V_{s,j1} = 523602.964$ is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 314161.779$ is calculated for section flange jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col_{j2} = 1.00$

$$s/d = 0.27777778$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 78636.768$$

$V_{s,c1} = 78636.768$ is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col_{c1} = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$ is calculated for section flange core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col_{c2} = 0.00$

$$s/d = 1.25$$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 930841.148$

bw = 450.00

Calculation of Shear Strength at edge 2, Vr2 = 1.0936E+006

Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0

VCol0 = 1.0936E+006

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 26.93333, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 867.5146

Vu = 0.0003102

d = 0.8*h = 600.00

Nu = 20816.964

Ag = 337500.00

From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 916401.511

where:

Vs,jacket = Vs,j1 + Vs,j2 = 837764.743

Vs,j1 = 523602.964 is calculated for section web jacket, with:

d = 600.00

Av = 157079.633

fy = 555.56

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.16666667

Vs,j2 = 314161.779 is calculated for section flange jacket, with:

d = 360.00

Av = 157079.633

fy = 555.56

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.27777778

Vs,core = Vs,c1 + Vs,c2 = 78636.768

Vs,c1 = 78636.768 is calculated for section web core, with:

d = 440.00

Av = 100530.965

fy = 444.44

s = 250.00

Vs,c1 is multiplied by Col,c1 = 1.00

s/d = 0.56818182

Vs,c2 = 0.00 is calculated for section flange core, with:

d = 200.00

Av = 100530.965

fy = 444.44

s = 250.00

Vs,c2 is multiplied by Col,c2 = 0.00

s/d = 1.25

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 930841.148

bw = 450.00

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.55$

#####

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.00

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -2.7331429E-008$

EDGE -B-

Shear Force, $V_b = 2.7331429E-008$

BOTH EDGES

Axial Force, $F = -20816.964$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 1693.318$

-Compression: $A_{st,com} = 1693.318$

-Middle: $A_{st,mid} = 3612.832$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.42425297$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 650163.608$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 9.7525E+008$

Mu1+ = 9.7525E+008, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

Mu1- = 9.7525E+008, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

Mpr2 = Max(Mu2+ , Mu2-) = 9.7525E+008

Mu2+ = 9.7525E+008, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

Mu2- = 9.7525E+008, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu1+

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 6.9050030E-006$

Mu = 9.7525E+008

with full section properties:

b = 450.00

d = 907.00

d' = 43.00

v = 0.00154555

N = 20816.964

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00782179$

we (5.4c) = 0.01167368

ase ((5.4d), TBDY) = $(\text{ase1} * \text{Aext} + \text{ase2} * \text{Aint}) / \text{Asec} = 0.53375773$

ase1 = $\text{Max}(((\text{Aconf,max1} - \text{AnoConf1}) / \text{Aconf,max1}) * (\text{Aconf,min1} / \text{Aconf,max1}), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 464100.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 395025.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 173066.667 is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

ase2 (\geq ase1) = $\text{Max}(((\text{Aconf,max2} - \text{AnoConf2}) / \text{Aconf,max2}) * (\text{Aconf,min2} / \text{Aconf,max2}), 0) = 0.53375773$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

psh,min*Fywe = $\text{Min}(\text{psh,x}*Fywe, \text{psh,y}*Fywe) = 2.40578$

Expression (5.4d) for psh,min*Fywe has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.40578

psh1 ((5.4d), TBDY) = $\text{Lstir1} * \text{Astir1} / (\text{Asec} * s1) = 0.00301593$

Lstir1 (Length of stirrups along Y) = 2160.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = $\text{Lstir2} * \text{Astir2} / (\text{Asec} * s2) = 0.00056047$

Lstir2 (Length of stirrups along Y) = 1568.00

Astir2 (stirrups area) = 50.26548

$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.87307$
 $psh1 ((5.4d), TBDY) = Lstir1 * Astir1 / (Asec * s1) = 0.00357443$
 Lstir1 (Length of stirrups along X) = 2560.00
 Astir1 (stirrups area) = 78.53982
 $psh2 ((5.4d), TBDY) = Lstir2 * Astir2 / (Asec * s2) = 0.00070345$
 Lstir2 (Length of stirrups along X) = 1968.00
 Astir2 (stirrups area) = 50.26548

Asec = 562500.00
 s1 = 100.00
 s2 = 250.00

fywe1 = 694.45
 fywe2 = 555.55
 fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.002
 c = confinement factor = 1.00

y1 = 0.00140044
 sh1 = 0.0044814
 ft1 = 441.3522
 fy1 = 367.7935
 su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00

$lo/lou, min = lb/ld = 0.30$

$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
 characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = $(fs_jacket * Asl, ten, jacket + fs_core * Asl, ten, core) / Asl, ten = 367.7935$

with Es1 = $(Es_jacket * Asl, ten, jacket + Es_core * Asl, ten, core) / Asl, ten = 200000.00$

y2 = 0.00140044
 sh2 = 0.0044814
 ft2 = 441.3522
 fy2 = 367.7935
 su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00

$lo/lou, min = lb/lb, min = 0.30$

$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
 characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = $(fs_jacket * Asl, com, jacket + fs_core * Asl, com, core) / Asl, com = 367.7935$

with Es2 = $(Es_jacket * Asl, com, jacket + Es_core * Asl, com, core) / Asl, com = 200000.00$

yv = 0.00140044
 shv = 0.0044814
 ftv = 442.9465
 fyv = 369.1221
 suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00

$lo/lou, min = lb/ld = 0.30$

$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv, ftv, fyv, it is considered
 characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = $(fs_jacket * Asl, mid, jacket + fs_mid * Asl, mid, core) / Asl, mid = 369.1221$

with Esv = $(Es_jacket * Asl, mid, jacket + Es_mid * Asl, mid, core) / Asl, mid = 200000.00$

$1 = Asl, ten / (b * d) * (fs1 / fc) = 0.04623905$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04623905$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.09901112$$

and confined core properties:

$$b = 390.00$$

$$d = 877.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05517782$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.05517782$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.11815159$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18247922$$

$$M_u = M_{Rc} (4.14) = 9.7525E+008$$

$$u = s_u (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of M_u1 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.9050030E-006$$

$$M_u = 9.7525E+008$$

with full section properties:

$$b = 450.00$$

$$d = 907.00$$

$$d' = 43.00$$

$$v = 0.00154555$$

$$N = 20816.964$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00782179$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00782179$$

$$w_e (5.4c) = 0.01167368$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.53375773$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 252164.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 111441.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 110709.333 is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{min} \cdot F_{ywe} = \text{Min}(psh_x \cdot F_{ywe}, psh_y \cdot F_{ywe}) = 2.40578$$

Expression (5.4d) for $psh_{min} \cdot F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x \cdot F_{ywe} = psh1 \cdot F_{ywe1} + ps2 \cdot F_{ywe2} = 2.40578$$
$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} \cdot A_{stir1} / (A_{sec} \cdot s1) = 0.00301593$$

Lstir1 (Length of stirrups along Y) = 2160.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ (5.4d)} = L_{stir2} \cdot A_{stir2} / (A_{sec} \cdot s2) = 0.00056047$$

Lstir2 (Length of stirrups along Y) = 1568.00
Astir2 (stirrups area) = 50.26548

$$psh_y \cdot F_{ywe} = psh1 \cdot F_{ywe1} + ps2 \cdot F_{ywe2} = 2.87307$$
$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} \cdot A_{stir1} / (A_{sec} \cdot s1) = 0.00357443$$

Lstir1 (Length of stirrups along X) = 2560.00
Astir1 (stirrups area) = 78.53982

$$psh2 \text{ ((5.4d), TBDY)} = L_{stir2} \cdot A_{stir2} / (A_{sec} \cdot s2) = 0.00070345$$

Lstir2 (Length of stirrups along X) = 1968.00
Astir2 (stirrups area) = 50.26548

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fy_{we1} = 694.45$$

$$fy_{we2} = 555.55$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$su1 = 0.4 \cdot esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (f_{s,jacket} \cdot A_{s1,ten,jacket} + f_{s,core} \cdot A_{s1,ten,core}) / A_{s1,ten} = 367.7935$$

$$\text{with } Es1 = (E_{s,jacket} \cdot A_{s1,ten,jacket} + E_{s,core} \cdot A_{s1,ten,core}) / A_{s1,ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 441.3522$$

$$fy2 = 367.7935$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$su2 = 0.4 \cdot esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (f_{s,jacket} \cdot A_{s2,com,jacket} + f_{s,core} \cdot A_{s2,com,core}) / A_{s2,com} = 367.7935$$

$$\text{with } Es2 = (E_{s,jacket} \cdot A_{s2,com,jacket} + E_{s,core} \cdot A_{s2,com,core}) / A_{s2,com} = 200000.00$$

$$yv = 0.00140044$$

$shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221$
 with $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112$

and confined core properties:

$b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs,y2$ - LHS eq.(4.5) is satisfied

$su (4.9) = 0.18247922$
 $Mu = MRc (4.14) = 9.7525E+008$
 $u = su (4.1) = 6.9050030E-006$

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of $Mu2+$

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 6.9050030E-006$
 $Mu = 9.7525E+008$

 with full section properties:

$b = 450.00$
 $d = 907.00$
 $d' = 43.00$
 $v = 0.00154555$
 $N = 20816.964$
 $fc = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00782179$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00782179$
 $we (5.4c) = 0.01167368$
 $ase ((5.4d), TBDY) = (ase1*Aext+ ase2*Aint)/Asec = 0.53375773$
 $ase1 = Max(((Aconf,max1 - AnoConf1)/Aconf,max1)*(Aconf,min1/Aconf,max1),0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).
 $ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$$

$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2160.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1568.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$$

$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2560.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1968.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 562500.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 694.45$$

$$f_{ywe2} = 555.55$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.002$$

$$c = \text{confinement factor} = 1.00$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.3522$$

$$fy1 = 367.7935$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1$, $sh1$, $ft1$, $fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.7935$$

$$\text{with } Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.3522
fy2 = 367.7935
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.7935

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 442.9465

fyv = 369.1221

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 369.1221

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04623905

2 = Asl,com/(b*d)*(fs2/fc) = 0.04623905

v = Asl,mid/(b*d)*(fsv/fc) = 0.09901112

and confined core properties:

b = 390.00

d = 877.00

d' = 13.00

fcc (5A.2, TBDY) = 33.00

cc (5A.5, TBDY) = 0.002

c = confinement factor = 1.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.05517782

2 = Asl,com/(b*d)*(fs2/fc) = 0.05517782

v = Asl,mid/(b*d)*(fsv/fc) = 0.11815159

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.18247922

Mu = MRc (4.14) = 9.7525E+008

u = su (4.1) = 6.9050030E-006

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 6.9050030E-006
Mu = 9.7525E+008

with full section properties:

b = 450.00
d = 907.00
d' = 43.00
v = 0.00154555
N = 20816.964
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00782179$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00782179$

we (5.4c) = 0.01167368

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.53375773$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 464100.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 395025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max1}$ by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 173066.667$ is the unconfined external core area which is equal to $b_i^2/6$ as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.53375773$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 252164.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 111441.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{conf,max2}$ by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 110709.333$ is the unconfined internal core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 2.40578$

Expression (5.4d) for $psh_{min} * F_{ywe}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.40578$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00301593$

L_{stir1} (Length of stirrups along Y) = 2160.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ (5.4d) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00056047$

L_{stir2} (Length of stirrups along Y) = 1568.00

A_{stir2} (stirrups area) = 50.26548

$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.87307$

$psh1$ ((5.4d), TBDY) = $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00357443$

L_{stir1} (Length of stirrups along X) = 2560.00

A_{stir1} (stirrups area) = 78.53982

$psh2$ ((5.4d), TBDY) = $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00070345$

L_{stir2} (Length of stirrups along X) = 1968.00

A_{stir2} (stirrups area) = 50.26548

$A_{sec} = 562500.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 694.45$

$f_{ywe2} = 555.55$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.002$

$c = \text{confinement factor} = 1.00$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.3522$
 $fy1 = 367.7935$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4 * esu1_nominal ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 367.7935$
 with $Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.3522$
 $fy2 = 367.7935$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4 * esu2_nominal ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 367.7935$
 with $Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 442.9465$
 $fyv = 369.1221$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4 * esuv_nominal ((5.5), \text{TBDY}) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 369.1221$
 with $Es_v = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.04623905$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.04623905$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.09901112$
 and confined core properties:
 $b = 390.00$
 $d = 877.00$
 $d' = 13.00$
 $fcc (5A.2, \text{TBDY}) = 33.00$
 $cc (5A.5, \text{TBDY}) = 0.002$
 $c = \text{confinement factor} = 1.00$
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.05517782$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.05517782$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.11815159$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied

--->

$$\mu (4.9) = 0.18247922$$

$$\mu = M_{Rc} (4.14) = 9.7525E+008$$

$$u = \mu (4.1) = 6.9050030E-006$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.5325E+006$

Calculation of Shear Strength at edge 1, $V_{r1} = 1.5325E+006$

$$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = k_{nl} * V_{Co10}$$

$$V_{Co10} = 1.5325E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$\text{Mean concrete strength: } f'_c = (f'_{c,jacket} * \text{Area}_{jacket} + f'_{c,core} * \text{Area}_{core}) / \text{Area}_{section} = 26.93333, \text{ but } f'_c^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 2.00$$

$$\mu = 0.70443303$$

$$V_u = 2.7331429E-008$$

$$d = 0.8 * h = 760.00$$

$$N_u = 20816.964$$

$$A_g = 427500.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0846E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 977392.20$$

$V_{s,j1} = 314161.779$ is calculated for section web jacket, with:

$$d = 360.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j1}$ is multiplied by $Col_{j1} = 1.00$

$$s/d = 0.27777778$$

$V_{s,j2} = 663230.422$ is calculated for section flange jacket, with:

$$d = 760.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

$V_{s,j2}$ is multiplied by $Col_{j2} = 1.00$

$$s/d = 0.13157895$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$$d = 200.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c1}$ is multiplied by $Col_{c1} = 0.00$

$$s/d = 1.25$$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$$d = 600.00$$

$$A_v = 100530.965$$

$$f_y = 444.44$$

$$s = 250.00$$

$V_{s,c2}$ is multiplied by $Col_{c2} = 1.00$

$$s/d = 0.41666667$$

$$V_f ((11-3)-(11.4), ACI 440) = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 1.1791E+006$$

$$b_w = 450.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 1.5325E+006$

$V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$

$V_{Col0} = 1.5325E+006$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 26.93333$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.70507494$

$V_u = 2.7331429E-008$

$d = 0.8 * h = 760.00$

$N_u = 20816.964$

$A_g = 427500.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{sjacket} + V_{s,core} = 1.0846E+006$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 977392.20$

$V_{sj1} = 314161.779$ is calculated for section web jacket, with:

$d = 360.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{sj1} is multiplied by $Col_{j1} = 1.00$

$s/d = 0.27777778$

$V_{sj2} = 663230.422$ is calculated for section flange jacket, with:

$d = 760.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{sj2} is multiplied by $Col_{j2} = 1.00$

$s/d = 0.13157895$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 107231.957$

$V_{s,c1} = 0.00$ is calculated for section web core, with:

$d = 200.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c1}$ is multiplied by $Col_{c1} = 0.00$

$s/d = 1.25$

$V_{s,c2} = 107231.957$ is calculated for section flange core, with:

$d = 600.00$

$A_v = 100530.965$

$f_y = 444.44$

$s = 250.00$

$V_{s,c2}$ is multiplied by $Col_{c2} = 1.00$

$s/d = 0.41666667$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440: $V_s + V_f \leq 1.1791E+006$

$bw = 450.00$

End Of Calculation of Shear Capacity ratio for element: column JTC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjtcs

Constant Properties

Knowledge Factor, $\phi = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Secondary Member: Steel Strength, $f_s = f_{sm} = 444.44$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 750.00$

Min Height, $H_{min} = 450.00$

Max Width, $W_{max} = 950.00$

Min Width, $W_{min} = 450.00$

Eccentricity, $E_{cc} = 250.00$

Jacket Thickness, $t_j = 100.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_b/l_d = 0.30$

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 96537.118$

Shear Force, $V_2 = 7074.25$

Shear Force, $V_3 = 39.74554$

Axial Force, $F = -21231.538$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl} = 0.00$

-Compression: $A_{slc} = 6999.468$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 1693.318$

-Compression: $A_{sl,com} = 1693.318$

-Middle: $A_{sl,mid} = 3612.832$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,jacket} = 1231.504$

-Compression: $A_{sl,com,jacket} = 1231.504$

-Middle: $A_{sl,mid,jacket} = 2689.203$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,core} = 461.8141$

-Compression: $A_{sl,com,core} = 461.8141$

-Middle: $A_{sl,mid,core} = 923.6282$

Mean Diameter of Tension Reinforcement, $DbL = 16.25$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = \phi \cdot u = 0.0276747$

$u = y + p = 0.0276747$

- Calculation of y -

$y = (My * Ls / 3) / E_{eff} = 0.0002574 ((4.29), Biskinis Phd)$

$My = 6.7544E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 300.00

From table 10.5, ASCE 41_17: $E_{eff} = factor \cdot E_c \cdot I_g = 2.6241E+014$

factor = 0.30

$A_g = 562500.00$

Mean concrete strength: $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 26.93333$

$N = 21231.538$

$E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 8.7468E+014$

Calculation of Yielding Moment M_y

Calculation of ρ_y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 2.2011043E-006$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 294.7834$

$d = 907.00$

$y = 0.26171323$

$A = 0.01732572$

$B = 0.00915761$

with $pt = 0.00414877$

$pc = 0.00414877$

$pv = 0.00885172$

$N = 21231.538$

$b = 450.00$

$\rho = 0.04740904$

$y_{comp} = 9.3361155E-006$

with $f_c = 33.00$

$E_c = 26999.444$

$y = 0.25981135$

$A = 0.01703103$

$B = 0.00898114$

with $E_s = 200000.00$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

- Calculation of ρ_p -

From table 10-8: $\rho_p = 0.0274173$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/d < 1$

shear control ratio $V_y/E/V_{CoI}E = 0.42425297$

$d = d_{external} = 907.00$

$s = s_{external} = 0.00$

- $t = s_1 + s_2 + 2 \cdot t_f/bw \cdot (f_{fe}/f_s) = 0.00427788$

jacket: $s_1 = A_{v1} \cdot L_{stir1} / (s_1 \cdot A_g) = 0.00357443$

$A_{v1} = 78.53982$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2560.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot L_{stir2} / (s_2 \cdot A_g) = 0.00070345$

$A_{v2} = 50.26548$, is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1968.00$, is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term $2 \cdot t_f/bw \cdot (f_{fe}/f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f/bw$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe}/f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 21231.538$

$A_g = 562500.00$

$f_cE = (f_c,jacket \cdot Area_{jacket} + f_c,core \cdot Area_{core}) / section_area = 26.93333$

$f_yE = (f_y,ext_Long_Reinf \cdot Area_{ext_Long_Reinf} + f_y,int_Long_Reinf \cdot Area_{int_Long_Reinf}) / Area_{Tot_Long_Rein} =$

526.2339

$$f_{tE} = (f_{y_ext_Trans_Reinf} \cdot s_1 + f_{y_int_Trans_Reinf} \cdot s_2) / (s_1 + s_2) = 537.2876$$

$$\rho_l = \text{Area_Tot_Long_Rein} / (b \cdot d) = 0.01714926$$

$$b = 450.00$$

$$d = 907.00$$

$$f_{cE} = 26.93333$$

End Of Calculation of Chord Rotation Capacity for element: column JTC1 of floor 1

At local axis: 3

Integration Section: (b)
