

# Detailed Member Calculations

**Units: N&mm**

**Regulation: ASCE 41-17**

## Calculation No. 1

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity  $V_{Rd}$

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

```

Concrete Elasticity, Ec = 25742.96
Steel Elasticity, Es = 200000.00
Existing Column
New material of Primary Member: Concrete Strength, fc = fc_lower_bound = 20.00
New material of Primary Member: Steel Strength, fs = fs_lower_bound = 500.00
Concrete Elasticity, Ec = 25742.96
Steel Elasticity, Es = 200000.00
#####
Note: Especially for the calculation of  $\gamma$  for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, fc = fcm = 30.00
New material: Steel Strength, fs = fsm = 625.00
Existing Column
New material: Concrete Strength, fc = fcm = 30.00
New material: Steel Strength, fs = fsm = 625.00
#####
Max Height, Hmax = 750.00
Min Height, Hmin = 400.00
Max Width, Wmax = 750.00
Min Width, Wmin = 400.00
Jacket Thickness, tj = 100.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Lap Length lo = lb = 300.00
No FRP Wrapping
-----

Stepwise Properties
-----
EDGE -A-
Bending Moment, Ma = -1.4730E+007
Shear Force, Va = -4846.489
EDGE -B-
Bending Moment, Mb = 186273.79
Shear Force, Vb = 4846.489
BOTH EDGES
Axial Force, F = -17232.621
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Asl,t = 0.00
-Compression: Asl,c = 5353.274
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 1137.257
-Compression: Asl,com = 2208.54
-Middle: Asl,mid = 2007.478
Mean Diameter of Tension Reinforcement, DbL,ten = 16.80
-----

New component: From table 7-7, ASCE 41-17: Final Shear Capacity VR = 1.0*Vn = 848882.103
Vn ((10.3), ASCE 41-17) = knl*VCol = 848882.103
VCol = 848882.103
knl = 1.00
displacement_ductility_demand = 0.02762218
-----
NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).
-----
= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 20.00, but fc'^0.5 <= 8.3

```

MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 1.4730E+007$$

$$V_u = 4846.489$$

$$d = 0.8 \cdot h = 600.00$$

$$N_u = 17232.621$$

$$A_g = 300000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 811033.559$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 722566.31$$

$V_{s,j1} = 251327.412$  is calculated for section web jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$$s/d = 0.3125$$

$V_{s,j2} = 471238.898$  is calculated for section flange jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

$V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$

$$s/d = 0.16666667$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 88467.249$$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 500.00$$

$$s = 250.00$$

$V_{s,c1}$  is multiplied by  $Col,c1 = 0.00$

$$s/d = 1.5625$$

$V_{s,c2} = 88467.249$  is calculated for section flange core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 500.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$

$$s/d = 0.56818182$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 713005.69$$

$$b_w = 400.00$$

displacement ductility demand is calculated as  $\delta / y$

- Calculation of  $\delta / y$  for END A -  
for rotation axis 3 and integ. section (a)

From analysis, chord rotation  $\theta = 5.5147643E-005$

$$y = (M_y \cdot L_s / 3) / E_{eff} = 0.0019965 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 2.8693E+008$$

$$L_s = M/V \text{ (with } L_s > 0.1 \cdot L \text{ and } L_s < 2 \cdot L) = 3039.252$$

$$\text{From table 10.5, ASCE 41_17: } E_{eff} = \text{factor} \cdot E_c \cdot I_g = 1.4560E+014$$

$$\text{factor} = 0.30$$

$$A_g = 440000.00$$

$$\text{Mean concrete strength: } f'_c = (f'_{c,jacket} \cdot \text{Area}_{jacket} + f'_{c,core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 30.00$$

$$N = 17232.621$$

$$E_c \cdot I_g = E_{c,jacket} \cdot I_{g,jacket} + E_{c,core} \cdot I_{g,core} = 4.8532E+014$$

Calculation of Yielding Moment  $M_y$

Calculation of  $\delta / y$  and  $M_y$  according to Annex 7 -

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$

web width,  $b_w = 400.00$

flange thickness,  $t = 400.00$

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$

$y_{\text{ten}} = 2.1452649\text{E}-006$

with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 243.3535$

$d = 707.00$

$y = 0.1977546$

$A = 0.0102293$

$B = 0.00453971$

with  $p_t = 0.00214476$

$p_c = 0.00416509$

$p_v = 0.00378591$

$N = 17232.621$

$b = 750.00$

" = 0.06082037

$y_{\text{comp}} = 1.5203329\text{E}-005$

with  $f_c = 30.00$

$E_c = 25742.96$

$y = 0.19515388$

$A = 0.01001829$

$B = 0.00440616$

with  $E_s = 200000.00$

CONFIRMATION:  $y = 0.19591085 < t/d$

Calculation of ratio  $l_b/d$

Lap Length:  $l_d/d, \text{min} = 0.17384865$

$l_b = 300.00$

$l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \text{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

= 1

$d_b = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f'_c = (f'_{c\_jacket} \cdot \text{Area}_{jacket} + f'_{c\_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$c_b = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr\_x}, A_{tr\_y}) = 257.6106$

where  $A_{tr\_x}$ ,  $A_{tr\_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

End Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (a)

## Calculation No. 2

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (  $\theta$  )

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjlcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
Longitudinal Bars With Ends Lapped Starting at the End Sections  
Lap Length  $l_o = 300.00$   
No FRP Wrapping

-----  
Stepwise Properties  
-----

At local axis: 3  
EDGE -A-  
Shear Force,  $V_a = -0.00017144$   
EDGE -B-  
Shear Force,  $V_b = 0.00017144$   
BOTH EDGES  
Axial Force,  $F = -16273.608$   
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension:  $As_t = 0.00$   
-Compression:  $As_c = 5353.274$   
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension:  $As_{t,ten} = 1137.257$   
-Compression:  $As_{l,com} = 2208.54$   
-Middle:  $As_{l,mid} = 2007.478$   
-----  
-----

Calculation of Shear Capacity ratio ,  $V_e/V_r = 0.32266369$   
Member Controlled by Flexure ( $V_e/V_r < 1$ )  
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$   
with  
 $M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 5.0296E+008$   
 $\mu_{1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction  
which is defined for the static loading combination  
 $\mu_{1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment  
direction which is defined for the static loading combination  
 $M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 5.0296E+008$   
 $\mu_{2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction  
which is defined for the the static loading combination  
 $\mu_{2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment  
direction which is defined for the the static loading combination

-----  
Calculation of  $\mu_{1+}$   
-----

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$\mu = 4.8099118E-006$

$M_u = 2.3387E+008$   
-----

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\alpha (5A.5, TBDY) = 0.002$

Final value of  $\mu$ :  $\mu^* = \text{shear\_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\mu_c = 0.01260361$

$\mu_{cc} (5.4c) = 0.05179731$

$\alpha_{se} ((5.4d), TBDY) = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.45746528$

$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization  
of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.  
 $A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noconf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noconf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noconf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noconf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

-----  
 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.3968$

$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.3968$

$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2} ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.13907892$

$su1 = 0.4 * esu1_{nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$fy2 = 262.1446$

$su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.13907892$

$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY:  $esu_{2,nominal} = 0.08$ ,

For calculation of  $esu_{2,nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
characteristic value  $fsy_2 = fs_2/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $Min(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00083886$

$sh_v = 0.00268436$

$ft_v = 314.5735$

$fy_v = 262.1446$

$su_v = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.13907892$

$su_v = 0.4 * esu_{v,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY:  $esu_{v,nominal} = 0.08$ ,

considering characteristic value  $fsy_v = fs_v/1.2$ , from table 5.1, TBDY

For calculation of  $esu_{v,nominal}$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
characteristic value  $fsy_v = fs_v/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $Min(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_v = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$

with  $Es_v = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

$1 = A_{sl,ten} / (b * d) * (fs_1 / fc) = 0.0187412$

$2 = A_{sl,com} / (b * d) * (fs_2 / fc) = 0.03639521$

$v = A_{sl,mid} / (b * d) * (fs_v / fc) = 0.03308184$

and confined core properties:

$b = 690.00$

$d = 677.00$

$d' = 13.00$

$fcc (5A.2, TBDY) = 38.13135$

$cc (5A.5, TBDY) = 0.00471045$

$c =$  confinement factor  $= 1.27105$

$1 = A_{sl,ten} / (b * d) * (fs_1 / fc) = 0.02127357$

$2 = A_{sl,com} / (b * d) * (fs_2 / fc) = 0.04131304$

$v = A_{sl,mid} / (b * d) * (fs_v / fc) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.21062322$

$Mu = MRc (4.14) = 2.3387E+008$

$u = su (4.1) = 4.8099118E-006$

-----  
Calculation of ratio  $l_b/l_d$

-----  
Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} <= 8.3$   
MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $\mu_1$ -  
-----

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.1201636E-006$$

$$\mu = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$\omega (5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear\_factor} * \text{Max}(\mu, \omega) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu = 0.01260361$$

$$\omega (5.4c) = 0.05179731$$

$$\omega (5.4d, \text{TBDY}) = (\omega_1 * A_{\text{ext}} + \omega_2 * A_{\text{int}}) / A_{\text{sec}} = 0.45746528$$

$$\omega_1 = \text{Max}(((A_{\text{conf,max1}} - A_{\text{noConf1}}) / A_{\text{conf,max1}}) * (A_{\text{conf,min1}} / A_{\text{conf,max1}}), 0) = 0.45746528$$

The definitions of  $A_{\text{noConf}}$ ,  $A_{\text{conf,min}}$  and  $A_{\text{conf,max}}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max1}} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{\text{conf,min1}} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{\text{conf,max1}}$  by a length equal to half the clear spacing between external hoops.

$A_{\text{noConf1}} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\omega_2 (\geq \omega_1) = \text{Max}(((A_{\text{conf,max2}} - A_{\text{noConf2}}) / A_{\text{conf,max2}}) * (A_{\text{conf,min2}} / A_{\text{conf,max2}}), 0) = 0.45746528$$

The definitions of  $A_{\text{noConf}}$ ,  $A_{\text{conf,min}}$  and  $A_{\text{conf,max}}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max2}} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{\text{conf,min2}} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{\text{conf,max2}}$  by a length equal to half the clear spacing between internal hoops.

$A_{\text{noConf2}} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{\text{sec}} * s_1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{\text{sec}} * s_2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{\text{sec}} * s_1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

psh2 ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

su1 =  $0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with Es1 =  $(E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 =  $0.4 * esu2_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with Es2 =  $(E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

suv =  $0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY  
For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv =  $(f_{s,jacket} * A_{sl,mid,jacket} + f_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$

with Esv =  $(E_{s,jacket} * A_{sl,mid,jacket} + E_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

1 =  $A_{sl,ten} / (b * d) * (fs1 / fc) = 0.06824101$

2 =  $A_{sl,com} / (b * d) * (fs2 / fc) = 0.03513975$

v =  $A_{sl,mid} / (b * d) * (fsv / fc) = 0.06202846$

and confined core properties:

b = 340.00

d = 677.00

$d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.08384116$   
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04317283$   
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied  
 --->

$su (4.9) = 0.2584548$   
 $Mu = MRc (4.14) = 5.0296E+008$   
 $u = su (4.1) = 5.1201636E-006$

-----  
 Calculation of ratio  $l_b/l_d$   
 -----

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$

MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
 Calculation of  $Mu_{2+}$   
 -----

-----  
 Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$u = 4.8099118E-006$

$Mu = 2.3387E+008$

-----  
 with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$co (5A.5, TBDY) = 0.002$

Final value of  $cu$ :  $cu^* = \text{shear\_factor} * \text{Max}(cu, cc) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $cu = 0.01260361$

$we (5.4c) = 0.05179731$

$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$

$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase_2 (>=ase_1) = \text{Max}(((A_{conf,max2}-A_{noConf2})/A_{conf,max2})*(A_{conf,min2}/A_{conf,max2}),0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min}*F_{ywe} = \text{Min}(psh_x*F_{ywe}, psh_y*F_{ywe}) = 3.3968$

-----  
 $psh_x*F_{ywe} = psh_1*F_{ywe1} + ps_2*F_{ywe2} = 3.3968$

$psh_1$  ((5.4d), TBDY) =  $L_{stir1}*A_{stir1}/(A_{sec}*s_1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh_2$  (5.4d) =  $L_{stir2}*A_{stir2}/(A_{sec}*s_2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y*F_{ywe} = psh_1*F_{ywe1} + ps_2*F_{ywe2} = 3.3968$

$psh_1$  ((5.4d), TBDY) =  $L_{stir1}*A_{stir1}/(A_{sec}*s_1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh_2$  ((5.4d), TBDY) =  $L_{stir2}*A_{stir2}/(A_{sec}*s_2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c$  = confinement factor = 1.27105

$y_1 = 0.00083886$

$sh_1 = 0.00268436$

$ft_1 = 314.5735$

$fy_1 = 262.1446$

$su_1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_0/l_{ou,min} = l_b/l_d = 0.13907892$

$su_1 = 0.4*es_{u1\_nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $es_{u1\_nominal} = 0.08$ ,

For calculation of  $es_{u1\_nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered characteristic value  $fs_{y1} = fs_1/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25*(l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_1 = (f_{s,jacket}*A_{sl,ten,jacket} + f_{s,core}*A_{sl,ten,core})/A_{sl,ten} = 262.1446$

with  $Es_1 = (E_{s,jacket}*A_{sl,ten,jacket} + E_{s,core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

$y_2 = 0.00083886$

$sh_2 = 0.00268436$

$ft_2 = 314.5735$

$fy_2 = 262.1446$

$su_2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.0187412

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03639521

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03308184

and confined core properties:

b = 690.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.02127357

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.04131304

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03755196

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.21062322

Mu = MRc (4.14) = 2.3387E+008

u = su (4.1) = 4.8099118E-006

-----  
Calculation of ratio lb/ld

Lap Length: lb/ld = 0.13907892

lb = 300.00

ld = 2157.049

Calculation of lb,min according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

ld,min from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

db = 16.66667

Mean strength value of all re-bars: fy = 781.25

Mean concrete strength: fc' = (fc',jacket\*Area\_jacket + fc',core\*Area\_core)/Area\_section = 30.00, but  $fc'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

t = 1.00

s = 0.80

e = 1.00

cb = 25.00

Ktr = 1.7174

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

-----  
-----  
-----  
Calculation of  $\mu_2$ -  
-----

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.1201636E-006$$

$$\mu_2 = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_2: \mu_2^* = \text{shear\_factor} * \text{Max}(\mu_2, \mu_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_2 = 0.01260361$$

$$\mu_2 \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (\geq a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh_x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh_y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00  
s1 = 100.00  
s2 = 250.00  
fywe1 = 781.25  
fywe2 = 781.25  
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y1 = 0.00083886  
sh1 = 0.00268436  
ft1 = 314.5735  
fy1 = 262.1446  
su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lc = 0.13907892  
su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/lc)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886  
sh2 = 0.00268436  
ft2 = 314.5735  
fy2 = 262.1446  
su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892  
su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/lc)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886  
shv = 0.00268436  
ftv = 314.5735  
fyv = 262.1446  
suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lc = 0.13907892  
suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY  
For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/lc)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.06824101  
2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03513975  
v = Asl,mid/(b\*d)\*(fsv/fc) = 0.06202846

and confined core properties:

b = 340.00  
d = 677.00  
d' = 13.00

$f_{cc}$  (5A.2, TBDY) = 38.13135  
 $cc$  (5A.5, TBDY) = 0.00471045  
 $c$  = confinement factor = 1.27105  
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.08384116$   
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04317283$   
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.07620839$   
Case/Assumption: Unconfined full section - Steel rupture  
' satisfies Eq. (4.3)

--->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->  
 $\mu_u$  (4.9) = 0.2584548  
 $M_u = MR_c$  (4.14) = 5.0296E+008  
 $u = \mu_u$  (4.1) = 5.1201636E-006

-----  
Calculation of ratio  $l_b/l_d$

-----  
Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b, min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$d_b = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$c_b = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

-----  
Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$V_{r1} = V_{Col}$  ((10.3), ASCE 41-17) =  $k_{nl} * V_{Col0}$

$V_{Col0} = 1.0392E+006$

$k_{nl} = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$M_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 * h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{sjacket} + V_{s,core} = 1.0138E+006$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 903207.888$

$V_{sj1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$   
 $V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:  
 $d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 625.00$   
 $s = 100.00$   
 $V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$   
 $s/d = 0.3125$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$   
 $V_{s,c1} = 110584.061$  is calculated for section web core, with:  
 $d = 440.00$   
 $A_v = 100530.965$   
 $f_y = 625.00$   
 $s = 250.00$   
 $V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$   
 $s/d = 0.56818182$   
 $V_{s,c2} = 0.00$  is calculated for section flange core, with:  
 $d = 160.00$   
 $A_v = 100530.965$   
 $f_y = 625.00$   
 $s = 250.00$   
 $V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$   
 $s/d = 1.5625$   
 $V_f((11-3)-(11.4), ACI 440) = 0.00$   
 From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
 $bw = 400.00$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$   
 $V_{r2} = V_{Col}((10.3), ASCE 41-17) = knl * V_{Col0}$   
 $V_{Col0} = 1.0392E+006$   
 $kn1 = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

$= 1$  (normal-weight concrete)  
 Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)  
 $M/d = 4.00$   
 $M_u = 1308.016$   
 $V_u = 0.00017144$   
 $d = 0.8 * h = 600.00$   
 $N_u = 16273.608$   
 $A_g = 300000.00$   
 From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$   
 where:  
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$   
 $V_{s,j1} = 589048.623$  is calculated for section web jacket, with:  
 $d = 600.00$   
 $A_v = 157079.633$   
 $f_y = 625.00$   
 $s = 100.00$   
 $V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:  
 $d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 625.00$   
 $s = 100.00$   
 $V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$   
 $s/d = 0.3125$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$   
 $V_{s,c1} = 110584.061$  is calculated for section web core, with:  
 $d = 440.00$

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 1.00

s/d = 0.56818182

Vs,c2 = 0.00 is calculated for section flange core, with:

d = 160.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 873250.061

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At Shear local axis: 2  
(Bending local axis: 3)  
Section Type: rcjlc

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, fc = fcm = 30.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 25742.96

Steel Elasticity, Es = 200000.00

Existing Column

New material of Primary Member: Concrete Strength, fc = fcm = 30.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 25742.96

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths,  
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, fs = 1.25\*fsm = 781.25

Existing Column

New material: Steel Strength, fs = 1.25\*fsm = 781.25

#####

Max Height, Hmax = 750.00

Min Height, Hmin = 400.00

Max Width, Wmax = 750.00

Min Width, Wmin = 400.00

Jacket Thickness, tj = 100.00

Cover Thickness, c = 25.00

Mean Confinement Factor overall section = 1.27105

Element Length, L = 3000.00

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length lo = 300.00

No FRP Wrapping

## Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force,  $V_a = -0.0001715$

EDGE -B-

Shear Force,  $V_b = 0.0001715$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{sl,t} = 0.00$

-Compression:  $A_{sl,c} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten} = 1137.257$

-Compression:  $A_{sl,com} = 2208.54$

-Middle:  $A_{sl,mid} = 2007.478$

Calculation of Shear Capacity ratio,  $V_e/V_r = 0.32266369$

Member Controlled by Flexure ( $V_e/V_r < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 5.0296E+008$

$M_{u1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 5.0296E+008$

$M_{u2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of  $M_{u1+}$

Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 4.8099118E-006$

$M_u = 2.3387E+008$

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\alpha_1$  (5A.5, TBDY) = 0.002

Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\phi_{cu} = 0.01260361$

$\phi_{we}$  (5.4c) = 0.05179731

$\alpha_{se}$  ((5.4d), TBDY) =  $(\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.45746528$

$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$   
 $s1 = 100.00$   
 $s2 = 250.00$   
 $f_{ywe1} = 781.25$   
 $f_{ywe2} = 781.25$   
 $f_{ce} = 30.00$

From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$   
 $sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{s,t,jacket} + f_{s,core} * A_{s,t,core}) / A_{s,t} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{s,t,jacket} + E_{s,core} * A_{s,t,core}) / A_{s,t} = 200000.00$

$y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.13907892$

$su2 = 0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $es_{u2\_nominal} = 0.08$ ,

For calculation of  $es_{u2\_nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered characteristic value  $fs_{y2} = fs_2/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es_2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00083886$

$sh_v = 0.00268436$

$ft_v = 314.5735$

$fy_v = 262.1446$

$suv = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

$lo/lo_{u,min} = lb/d = 0.13907892$

$suv = 0.4 \cdot es_{uv\_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY:  $es_{uv\_nominal} = 0.08$ ,

considering characteristic value  $fs_{yv} = f_{sv}/1.2$ , from table 5.1, TBDY

For calculation of  $es_{uv\_nominal}$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered

characteristic value  $fs_{yv} = f_{sv}/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{sv} = (f_{s,jacket} \cdot A_{sl,mid,jacket} + f_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 262.1446$

with  $Es_v = (Es_{jacket} \cdot A_{sl,mid,jacket} + Es_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.0187412$

$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03639521$

$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03308184$

and confined core properties:

$b = 690.00$

$d = 677.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 38.13135$

$cc (5A.5, TBDY) = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02127357$

$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04131304$

$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.21062322$

$Mu = MRc (4.14) = 2.3387E+008$

$u = su (4.1) = 4.8099118E-006$

-----  
Calculation of ratio  $lb/d$

Lap Length:  $lb/d = 0.13907892$

$lb = 300.00$

$ld = 2157.049$

Calculation of  $lb_{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld_{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f'_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$

where  $A_{tr,x}, A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

Calculation of Mu1-

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.1201636E-006$$

$$Mu = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_o) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

s1 = 100.00  
s2 = 250.00  
fywe1 = 781.25  
fywe2 = 781.25  
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y1 = 0.00083886  
sh1 = 0.00268436  
ft1 = 314.5735  
fy1 = 262.1446  
su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886  
sh2 = 0.00268436  
ft2 = 314.5735  
fy2 = 262.1446  
su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886  
shv = 0.00268436  
ftv = 314.5735  
fyv = 262.1446  
suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.06824101

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03513975

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.06202846

and confined core properties:

b = 340.00  
d = 677.00  
d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.08384116

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.04317283$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.07620839$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---->

$$s_u(4.9) = 0.2584548$$

$$M_u = M_{Rc}(4.14) = 5.0296E+008$$

$$u = s_u(4.1) = 5.1201636E-006$$

-----  
Calculation of ratio  $l_b/l_d$

-----  
Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \min(A_{tr,x}, A_{tr,y}) = 257.6106$$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \max(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $M_u2+$

-----  
Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 4.8099118E-006$$

$$M_u = 2.3387E+008$$

-----  
with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

Final value of  $c_u$ :  $c_u^* = \text{shear\_factor} * \max(c_u, c_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e(5.4c) = 0.05179731$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \max(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

AnoConf1 = 158733.333 is the unconfined external core area which is equal to  $b_i/6$  as defined at (A.2).  
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - \text{AnoConf}_2)/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$\text{AnoConf}_2 = 106242.667$  is the unconfined internal core area which is equal to  $b_i/6$  as defined at (A.2).  
 $psh_{,min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.3968$   
 $psh_1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh_2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.3968$   
 $psh_1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh_2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c =$  confinement factor = 1.27105

$y_1 = 0.00083886$

$sh_1 = 0.00268436$

$ft_1 = 314.5735$

$fy_1 = 262.1446$

$su_1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.13907892$

$su_1 = 0.4 * esu_{1,nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu_{1,nominal} = 0.08$ ,

For calculation of  $esu_{1,nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered characteristic value  $fs_1 = fs_1/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 262.1446$

with  $Es_1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

$y_2 = 0.00083886$

$sh_2 = 0.00268436$

$ft_2 = 314.5735$

$fy_2 = 262.1446$

$su_2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.13907892$

$su_2 = 0.4 * esu_{2,nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu_{2,nominal} = 0.08$ ,

For calculation of  $es_{u2\_nominal}$  and  $y_2$ ,  $sh_2, ft_2, fy_2$ , it is considered characteristic value  $fs_{y2} = fs_2/1.2$ , from table 5.1, TBDY.

$y_1$ ,  $sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es_2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00083886$

$sh_v = 0.00268436$

$ft_v = 314.5735$

$fy_v = 262.1446$

$s_{uv} = 0.00268436$

using (30) in Bisquinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.13907892$

$s_{uv} = 0.4 \cdot es_{uv\_nominal} ((5,5), TBDY) = 0.032$

From table 5A.1, TBDY:  $es_{uv\_nominal} = 0.08$ ,

considering characteristic value  $fs_{yv} = f_{sv}/1.2$ , from table 5.1, TBDY

For calculation of  $es_{uv\_nominal}$  and  $y_v$ ,  $sh_v, ft_v, fy_v$ , it is considered characteristic value  $fs_{yv} = f_{sv}/1.2$ , from table 5.1, TBDY.

$y_1$ ,  $sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{sv} = (f_{s,jacket} \cdot A_{sl,mid,jacket} + f_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 262.1446$

with  $Es_v = (Es_{jacket} \cdot A_{sl,mid,jacket} + Es_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.0187412$

$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03639521$

$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03308184$

and confined core properties:

$b = 690.00$

$d = 677.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 38.13135$

$cc (5A.5, TBDY) = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02127357$

$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04131304$

$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.21062322$

$\mu_u = MR_c (4.14) = 2.3387E+008$

$u = su (4.1) = 4.8099118E-006$

-----  
Calculation of ratio  $lb/ld$

Lap Length:  $lb/ld = 0.13907892$

$lb = 300.00$

$ld = 2157.049$

Calculation of  $lb_{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld_{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

Calculation of Mu2-

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.1201636E-006$$

$$\mu = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$s_2 = 250.00$   
 $fy_{we1} = 781.25$   
 $fy_{we2} = 781.25$   
 $f_{ce} = 30.00$   
 From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $y_1 = 0.00083886$   
 $sh_1 = 0.00268436$   
 $ft_1 = 314.5735$   
 $fy_1 = 262.1446$   
 $su_1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/d = 0.13907892$   
 $su_1 = 0.4 * esu_1 \text{ nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_1 \text{ nominal} = 0.08$ ,  
 For calculation of  $esu_1 \text{ nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered  
 characteristic value  $fsy_1 = fs_1/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$   
 with  $Es_1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$   
 $y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/lb, \min = 0.13907892$   
 $su_2 = 0.4 * esu_2 \text{ nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_2 \text{ nominal} = 0.08$ ,  
 For calculation of  $esu_2 \text{ nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
 characteristic value  $fsy_2 = fs_2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$   
 with  $Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/d = 0.13907892$   
 $suv = 0.4 * esuv \text{ nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv \text{ nominal} = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv \text{ nominal}$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$   
 with  $Es_v = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$   
 $1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.06824101$   
 $2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.03513975$   
 $v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.06202846$   
 and confined core properties:  
 $b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.08384116$   
 $2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.04317283$

$$v = A_{sl, mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.07620839$$

Case/Assumption: Unconfined full section - Steel rupture  
' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.2584548$$

$$M_u = M_{Rc}(4.14) = 5.0296E+008$$

$$u = s_u(4.1) = 5.1201636E-006$$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

$$\text{Mean strength value of all re-bars: } f_y = 781.25$$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$$V_{r1} = V_{Col}((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$$

$$V_{Col0} = 1.0392E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$M_u = 1308.675$$

$$V_u = 0.0001715$$

$$d = 0.8 \cdot h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$$

$V_{s,j1} = 314159.265$  is calculated for section web jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$$s/d = 0.3125$$

$V_{s,j2} = 589048.623$  is calculated for section flange jacket, with:

$$d = 600.00$$

$A_v = 157079.633$   
 $f_y = 625.00$   
 $s = 100.00$   
 $V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$   
 $V_{s,c1} = 0.00$  is calculated for section web core, with:  
 $d = 160.00$   
 $A_v = 100530.965$   
 $f_y = 625.00$   
 $s = 250.00$   
 $V_{s,c1}$  is multiplied by  $Col,c1 = 0.00$   
 $s/d = 1.5625$   
 $V_{s,c2} = 110584.061$  is calculated for section flange core, with:  
 $d = 440.00$   
 $A_v = 100530.965$   
 $f_y = 625.00$   
 $s = 250.00$   
 $V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$   
 $s/d = 0.56818182$   
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$   
 From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
 $bw = 400.00$

-----  
 Calculation of Shear Strength at edge 2,  $V_r2 = 1.0392E+006$

$V_r2 = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$

$V_{Col0} = 1.0392E+006$

$knl = 1$  (zero step-static loading)

-----  
 NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
 where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.675$

$V_u = 0.0001715$

$d = 0.8 * h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 314159.265$  is calculated for section web jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$s/d = 0.3125$

$V_{s,j2} = 589048.623$  is calculated for section flange jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$

$s/d = 0.16666667$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col,c1 = 0.00$

$s/d = 1.5625$

$V_{s,c2} = 110584.061$  is calculated for section flange core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$

$s/d = 0.56818182$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$bw = 400.00$

-----  
End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 2

-----  
Start Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1  
At local axis: 2  
Integration Section: (a)  
Section Type: rcjics

Constant Properties

-----  
Knowledge Factor,  $= 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_b = 300.00$

No FRP Wrapping

-----  
Stepwise Properties

Bending Moment,  $M = -293351.828$

Shear Force,  $V_2 = -4846.489$

Shear Force,  $V_3 = 135.9404$

Axial Force,  $F = -17232.621$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $As_t = 0.00$

-Compression:  $As_c = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $As_{l,ten} = 1137.257$

-Compression:  $As_{l,com} = 2208.54$

-Middle:  $Asl, mid = 2007.478$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension:  $Asl, ten, jacket = 829.3805$

-Compression:  $Asl, com, jacket = 1746.726$

-Middle:  $Asl, mid, jacket = 1545.664$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $Asl, ten, core = 307.8761$

-Compression:  $Asl, com, core = 461.8141$

-Middle:  $Asl, mid, core = 461.8141$

Mean Diameter of Tension Reinforcement,  $DbL = 16.80$

New component: From table 7-7, ASCE 41\_17: Final chord rotation Capacity  $u, R = 1.0^*$   $u = 0.00141756$   
 $u = y + p = 0.00141756$

- Calculation of  $y$  -

$y = (My * Ls / 3) / Eleff = 0.00141756$  ((4.29), Biskinis Phd)

$My = 2.8693E+008$

$Ls = M/V$  (with  $Ls > 0.1 * L$  and  $Ls < 2 * L$ ) = 2157.945

From table 10.5, ASCE 41\_17:  $Eleff = factor * Ec * Ig = 1.4560E+014$

factor = 0.30

$Ag = 440000.00$

Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$

$N = 17232.621$

$Ec * Ig = Ec_{jacket} * Ig_{jacket} + Ec_{core} * Ig_{core} = 4.8532E+014$

Calculation of Yielding Moment  $My$

Calculation of  $y$  and  $My$  according to Annex 7 -

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$

web width,  $bw = 400.00$

flange thickness,  $t = 400.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 2.1452649E-006$

with ((10.1), ASCE 41-17)  $fy = \text{Min}(fy, 1.25 * fy * (lb/d)^{2/3}) = 243.3535$

$d = 707.00$

$y = 0.1977546$

$A = 0.0102293$

$B = 0.00453971$

with  $pt = 0.00434791$

$pc = 0.00416509$

$p_v = 0.00378591$

$N = 17232.621$

$b = 750.00$

" = 0.06082037

$y_{comp} = 1.5203329E-005$

with  $fc = 30.00$

$Ec = 25742.96$

$y = 0.19515388$

$A = 0.01001829$

$B = 0.00440616$

with  $Es = 200000.00$

CONFIRMATION:  $y = 0.19591085 < t/d$

Calculation of ratio  $lb/d$

Lap Length:  $l_d/l_{d,min} = 0.17384865$

$l_b = 300.00$

$l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

- Calculation of  $\rho$  -

From table 10-8:  $\rho = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because  $l_b/l_d < 1$

shear control ratio  $V_y E / V_{Col} O E = 0.32266369$

$d = d_{external} = 707.00$

$s = s_{external} = 0.00$

-  $t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00434791$

jacket:  $s_1 = A_{v1} \cdot L_{stir1} / (s_1 \cdot A_g) = 0.00367709$

$A_{v1} = 78.53982$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2060.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core:  $s_2 = A_{v2} \cdot L_{stir2} / (s_2 \cdot A_g) = 0.00067082$

$A_{v2} = 50.26548$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1468.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term  $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$  is implemented to account for FRP contribution

where  $f = 2 \cdot t_f / b_w$  is FRP ratio (EC8 - 3, A.4.4.3(6)) and  $f_{fe} / f_s$  normalises  $f$  to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation  $f_s$  of jacket is used.

$N_{UD} = 17232.621$

$A_g = 440000.00$

$f_{cE} = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / section\_area = 30.00$

$f_{yIE} = (f_{y\_ext\_Long\_Reinf} \cdot Area_{ext\_Long\_Reinf} + f_{y\_int\_Long\_Reinf} \cdot Area_{int\_Long\_Reinf}) / Area_{Tot\_Long\_Rein} = 625.00$

$f_{yTE} = (f_{y\_ext\_Trans\_Reinf} \cdot s_1 + f_{y\_int\_Trans\_Reinf} \cdot s_2) / (s_1 + s_2) = 625.00$

$\rho_l = Area_{Tot\_Long\_Rein} / (b \cdot d) = 0.01009575$

$b = 750.00$

$d = 707.00$

$f_{cE} = 30.00$

End Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (a)

## Calculation No. 3

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjlcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of  $\gamma$  for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

Existing Column

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

#####

Max Height, Hmax = 750.00  
Min Height, Hmin = 400.00  
Max Width, Wmax = 750.00  
Min Width, Wmin = 400.00  
Jacket Thickness, tj = 100.00  
Cover Thickness, c = 25.00  
Element Length, L = 3000.00  
Primary Member  
Smooth Bars  
Ductile Steel  
With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
Longitudinal Bars With Ends Lapped Starting at the End Sections  
Lap Length lo = lb = 300.00  
No FRP Wrapping

-----  
Stepwise Properties  
-----

EDGE -A-  
Bending Moment, Ma = -293351.828  
Shear Force, Va = 135.9404  
EDGE -B-  
Bending Moment, Mb = -112991.609  
Shear Force, Vb = -135.9404  
BOTH EDGES  
Axial Force, F = -17232.621  
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension: Aslt = 0.00  
-Compression: Aslc = 5353.274  
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension: Asl,ten = 1137.257  
-Compression: Asl,com = 2208.54  
-Middle: Asl,mid = 2007.478  
Mean Diameter of Tension Reinforcement, DbL,ten = 16.80

-----  
-----  
New component: From table 7-7, ASCE 41\_17: Final Shear Capacity VR = 1.0\*Vn = 864123.256  
Vn ((10.3), ASCE 41-17) = knl\*VCol0 = 864123.256  
VCol = 864123.256  
knl = 1.00  
displacement\_ductility\_demand = 0.01498415

-----  
NOTE: In expression (10-3) 'Vs = Av\*fy\*d/s' is replaced by 'Vs+ f\*Vf'  
where Vf is the contribution of FRPs (11.3), ACI 440).

-----  
= 1 (normal-weight concrete)  
Mean concrete strength: fc' = (fc'\_jacket\*Area\_jacket + fc'\_core\*Area\_core)/Area\_section = 20.00, but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)  
M/Vd = 3.59657  
Mu = 293351.828  
Vu = 135.9404  
d = 0.8\*h = 600.00  
Nu = 17232.621  
Ag = 300000.00  
From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 811033.559  
where:  
Vs,jacket = Vs,j1 + Vs,j2 = 722566.31  
Vs,j1 = 471238.898 is calculated for section web jacket, with:  
d = 600.00  
Av = 157079.633  
fy = 500.00  
s = 100.00  
Vs,j1 is multiplied by Col,j1 = 1.00  
s/d = 0.16666667  
Vs,j2 = 251327.412 is calculated for section flange jacket, with:

$d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$   
 $V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$   
 $s/d = 0.3125$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 88467.249$   
 $V_{s,c1} = 88467.249$  is calculated for section web core, with:  
 $d = 440.00$   
 $A_v = 100530.965$   
 $f_y = 500.00$   
 $s = 250.00$   
 $V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$   
 $s/d = 0.56818182$   
 $V_{s,c2} = 0.00$  is calculated for section flange core, with:  
 $d = 160.00$   
 $A_v = 100530.965$   
 $f_y = 500.00$   
 $s = 250.00$   
 $V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$   
 $s/d = 1.5625$   
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$   
 From (11-11), ACI 440:  $V_s + V_f \leq 713005.69$   
 $bw = 400.00$

-----  
 displacement ductility demand is calculated as  $\phi / y$

- Calculation of  $\phi / y$  for END A -  
 for rotation axis 2 and integ. section (a)

-----  
 From analysis, chord rotation  $\theta = 2.1240994E-005$   
 $y = (M_y * L_s / 3) / E_{eff} = 0.00141756 ((4.29), Biskinis Phd)$   
 $M_y = 2.8693E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 2157.945  
 From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
 $factor = 0.30$   
 $A_g = 440000.00$   
 Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17232.621$   
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 4.8532E+014$

-----  
 Calculation of Yielding Moment  $M_y$

-----  
 Calculation of  $\phi$  and  $M_y$  according to Annex 7 -

-----  
 Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:  
 flange width,  $b = 750.00$   
 web width,  $bw = 400.00$   
 flange thickness,  $t = 400.00$

-----  
 $y = \text{Min}(y_{ten}, y_{com})$   
 $y_{ten} = 2.1452649E-006$   
 with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 * f_y * (b/d)^{2/3}) = 243.3535$   
 $d = 707.00$   
 $y = 0.1977546$   
 $A = 0.0102293$   
 $B = 0.00453971$   
 with  $pt = 0.00214476$   
 $pc = 0.00416509$   
 $pv = 0.00378591$   
 $N = 17232.621$   
 $b = 750.00$   
 $\phi = 0.06082037$

y\_comp = 1.5203329E-005  
with fc = 30.00  
Ec = 25742.96  
y = 0.19515388  
A = 0.01001829  
B = 0.00440616  
with Es = 200000.00  
CONFIRMATION: y = 0.19591085 < t/d

-----  
-----  
Calculation of ratio lb/l<sub>d</sub>

-----  
Lap Length: l<sub>d</sub>/l<sub>d,min</sub> = 0.17384865  
lb = 300.00  
l<sub>d</sub> = 1725.639



Calculation of l according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
l<sub>d,min</sub> from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

= 1  
db = 16.66667  
Mean strength value of all re-bars: f<sub>y</sub> = 625.00  
Mean concrete strength: f<sub>c</sub>' = (f<sub>c</sub>'<sub>jacket</sub>\*Area<sub>jacket</sub> + f<sub>c</sub>'<sub>core</sub>\*Area<sub>core</sub>)/Area<sub>section</sub> = 30.00, but f<sub>c</sub>'<sup>0.5</sup> ≤ 8.3  
MPa (22.5.3.1, ACI 318-14)  
t = 1.00  
s = 0.80  
e = 1.00  
cb = 25.00  
K<sub>tr</sub> = 1.7174  
A<sub>tr</sub> = Min(A<sub>tr\_x</sub>, A<sub>tr\_y</sub>) = 257.6106  
where A<sub>tr\_x</sub>, A<sub>tr\_y</sub> are the sum of the area of all stirrup legs along X and Y local axis  
s = Max(s<sub>external</sub>, s<sub>internal</sub>) = 250.00  
n = 24.00

-----  
End Of Calculation of Shear Capacity for element: column JLC1 of floor 1  
At local axis: 3  
Integration Section: (a)

## Calculation No. 4

column C1, Floor 1  
Limit State: Operational Level (data interpolation between analysis steps 1 and 2)  
Analysis: Uniform +X  
Check: Chord rotation capacity ( u )  
Edge: Start  
Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At Shear local axis: 3  
 (Bending local axis: 2)  
 Section Type: rcjlcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$   
 Mean strength values are used for both shear and moment calculations.  
 Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,  
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = 300.00$

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force,  $V_a = -0.00017144$

EDGE -B-

Shear Force,  $V_b = 0.00017144$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $As_t = 0.00$

-Compression:  $As_c = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $As_{t,ten} = 1137.257$

-Compression:  $As_{c,com} = 2208.54$

-Middle:  $As_{c,mid} = 2007.478$

Calculation of Shear Capacity ratio,  $V_e/V_r = 0.32266369$

Member Controlled by Flexure ( $V_e/V_r < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 5.0296E+008$

$Mu_{1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 5.0296E+008$

$Mu_{2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination

Calculation of  $Mu_{1+}$

Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 4.8099118E-006$

$M_u = 2.3387E+008$

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\omega (5A.5, TBDY) = 0.002$

Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} * \text{Max}(\phi_u, \phi_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\phi_u = 0.01260361$

$\omega_e (5.4c) = 0.05179731$

$\omega_{ase} ((5.4d), TBDY) = (\omega_{ase1} * A_{ext} + \omega_{ase2} * A_{int}) / A_{sec} = 0.45746528$

$\omega_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\omega_{ase2} (>= \omega_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$   
 $s1 = 100.00$   
 $s2 = 250.00$

$f_{ywe1} = 781.25$   
 $f_{ywe2} = 781.25$   
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$   
 $sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/ld = 0.13907892$   
 $su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 0.13907892$   
 $su2 = 0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu2_{nominal} = 0.08$ ,

For calculation of  $esu2_{nominal}$  and  $y2, sh2, ft2, fy2$ , it is considered characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.00083886$   
 $shv = 0.00268436$

$$ftv = 314.5735$$

$$fyv = 262.1446$$

$$suv = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$lo/lo_{min} = lb/ld = 0.13907892$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $esuv_{nominal} = 0.08$ ,

considering characteristic value  $fsv = fsv/1.2$ , from table 5.1, TBDY

For calculation of  $esuv_{nominal}$  and  $yv$ ,  $shv$ ,  $ftv$ ,  $fyv$ , it is considered  
characteristic value  $fsv = fsv/1.2$ , from table 5.1, TBDY.

$y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 262.1446$$

$$\text{with } Es_v = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.0187412$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.03639521$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03308184$$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 38.13135$$

$$cc (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.02127357$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.04131304$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < vs_{y2}$  - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.21062322$$

$$Mu = MRc (4.14) = 2.3387E+008$$

$$u = su (4.1) = 4.8099118E-006$$

-----  
Calculation of ratio  $lb/ld$

-----  
Lap Length:  $lb/ld = 0.13907892$

$$lb = 300.00$$

$$ld = 2157.049$$

Calculation of  $lb_{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld_{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$db = 16.66667$$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$Ktr = 1.7174$$

$$Atr = \text{Min}(Atr_x, Atr_y) = 257.6106$$

where  $Atr_x$ ,  $Atr_y$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $Mu1$ -

-----  
Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

u = 5.1201636E-006  
Mu = 5.0296E+008

with full section properties:

b = 400.00  
d = 707.00  
d' = 43.00  
v = 0.00191815  
N = 16273.608

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu\* = shear\_factor \* Max( cu, cc) = 0.01260361

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01260361

we (5.4c) = 0.05179731

ase ((5.4d), TBDY) = (ase1\*Aext+ase2\*Aint)/Asec = 0.45746528

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)\*(Aconf,min1/Aconf,max1),0) = 0.45746528

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 353600.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 293525.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 158733.333 is the unconfined external core area which is equal to bi2/6 as defined at (A.2).

ase2 (>=ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)\*(Aconf,min2/Aconf,max2),0) = 0.45746528

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 171264.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 54741.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to bi2/6 as defined at (A.2).

psh,min\*Fywe = Min(psh,x\*Fywe , psh,y\*Fywe) = 3.3968

psh\_x\*Fywe = psh1\*Fywe1+ps2\*Fywe2 = 3.3968

psh1 ((5.4d), TBDY) = Lstir1\*Astir1/(Asec\*s1) = 0.00367709

Lstir1 (Length of stirrups along Y) = 2060.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = Lstir2\*Astir2/(Asec\*s2) = 0.00067082

Lstir2 (Length of stirrups along Y) = 1468.00

Astir2 (stirrups area) = 50.26548

psh\_y\*Fywe = psh1\*Fywe1+ps2\*Fywe2 = 3.3968

psh1 ((5.4d), TBDY) = Lstir1\*Astir1/(Asec\*s1) = 0.00367709

Lstir1 (Length of stirrups along X) = 2060.00

Astir1 (stirrups area) = 78.53982

psh2 ((5.4d), TBDY) = Lstir2\*Astir2/(Asec\*s2) = 0.00067082

Lstir2 (Length of stirrups along X) = 1468.00

Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

$sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou,min = lb/l_d = 0.13907892$   
 $su1 = 0.4*esu1\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,  
 For calculation of  $esu1\_nominal$  and  $y1, sh1, ft1, fy1$ , it is considered  
 characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 262.1446$   
 with  $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$   
 $y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou,min = lb/l_b,min = 0.13907892$   
 $su2 = 0.4*esu2\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu2\_nominal = 0.08$ ,  
 For calculation of  $esu2\_nominal$  and  $y2, sh2, ft2, fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 262.1446$   
 with  $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$   
 $yv = 0.00083886$   
 $shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou,min = lb/l_d = 0.13907892$   
 $suv = 0.4*esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv, shv, ftv, fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 262.1446$   
 with  $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.06824101$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.03513975$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.06202846$   
 and confined core properties:  
 $b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.08384116$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04317283$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)  
 --->  
 $v < vs,y2$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.2584548$

$$\begin{aligned} \mu &= M/R_c (4.14) = 5.0296E+008 \\ u &= s_u (4.1) = 5.1201636E-006 \end{aligned}$$

-----  
 Calculation of ratio  $l_b/l_d$   
 -----

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \min(A_{tr,x}, A_{tr,y}) = 257.6106$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \max(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
 Calculation of  $\mu_{2+}$   
 -----

-----  
 Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$u = 4.8099118E-006$

$\mu = 2.3387E+008$

-----  
 with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\alpha (5A.5, TBDY) = 0.002$

Final value of  $\mu$ :  $\mu^* = \text{shear\_factor} \cdot \max(\mu, \alpha) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\mu = 0.01260361$

we (5.4c)  $= 0.05179731$

ase ((5.4d), TBDY)  $= (ase1 \cdot A_{ext} + ase2 \cdot A_{int}) / A_{sec} = 0.45746528$

$ase1 = \max(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) \cdot (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$ase2 (\geq ase1) = \max(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) \cdot (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 171264.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 54741.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 3.3968$

---

$psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $Lstir1*Astir1/(Asec*s1) = 0.00367709$   
Lstir1 (Length of stirrups along Y) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2$  (5.4d) =  $Lstir2*Astir2/(Asec*s2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

---

$psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $Lstir1*Astir1/(Asec*s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2$  ((5.4d), TBDY) =  $Lstir2*Astir2/(Asec*s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

---

Asec = 440000.00  
s1 = 100.00  
s2 = 250.00  
fywe1 = 781.25  
fywe2 = 781.25  
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y1 = 0.00083886  
sh1 = 0.00268436  
ft1 = 314.5735  
fy1 = 262.1446  
su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/l\_d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 262.1446$

with Es1 =  $(Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$

y2 = 0.00083886  
sh2 = 0.00268436  
ft2 = 314.5735  
fy2 = 262.1446  
su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/l\_b,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 262.1446$

with Es2 =  $(Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$

yv = 0.00083886  
shv = 0.00268436  
ftv = 314.5735

$f_{yv} = 262.1446$   
 $s_{uv} = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{ou,min} = l_b/l_d = 0.13907892$   
 $s_{uv} = 0.4 * e_{suv\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $e_{suv\_nominal} = 0.08$ ,  
 considering characteristic value  $f_{sv} = f_{sv}/1.2$ , from table 5.1, TBDY  
 For calculation of  $e_{suv\_nominal}$  and  $\gamma_v$ ,  $sh_v, ft_v, f_{yv}$ , it is considered  
 characteristic value  $f_{sv} = f_{sv}/1.2$ , from table 5.1, TBDY.  
 $\gamma_1, sh_1, ft_1, f_{y1}$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 262.1446$   
 with  $E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$   
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.0187412$   
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.03639521$   
 $v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.03308184$

and confined core properties:

$b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.02127357$   
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04131304$   
 $v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---

$su (4.9) = 0.21062322$   
 $Mu = MRc (4.14) = 2.3387E+008$   
 $u = su (4.1) = 4.8099118E-006$

-----  
 Calculation of ratio  $l_b/l_d$   
 -----

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b,min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d,min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$

MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$

where  $A_{tr,x}, A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
 Calculation of  $Mu_2$ -  
 -----

-----  
 Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$u = 5.1201636E-006$

$$\mu = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$y1 = 0.00083886$$

$$sh1 = 0.00268436$$

$ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/ld = 0.13907892$   
 $su1 = 0.4*esu1\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,  
 For calculation of  $esu1\_nominal$  and  $y1, sh1,ft1,fy1$ , it is considered  
 characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.  
 $y1, sh1,ft1,fy1$ , are also multiplied by  $Min(1,1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 262.1446$   
 with  $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$   
 $y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/lb,min = 0.13907892$   
 $su2 = 0.4*esu2\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu2\_nominal = 0.08$ ,  
 For calculation of  $esu2\_nominal$  and  $y2, sh2,ft2,fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1,ft1,fy1$ , are also multiplied by  $Min(1,1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 262.1446$   
 with  $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$   
 $yv = 0.00083886$   
 $shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/ld = 0.13907892$   
 $suv = 0.4*esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv, shv,ftv,fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1,ft1,fy1$ , are also multiplied by  $Min(1,1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 262.1446$   
 with  $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.06824101$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.03513975$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.06202846$   
 and confined core properties:  
 $b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.08384116$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04317283$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)  
 --->  
 $v < vs,y2$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.2584548$   
 $Mu = MRc (4.14) = 5.0296E+008$

$$u = s_u(4.1) = 5.1201636E-006$$

Calculation of ratio  $l_b/d$

Lap Length:  $l_b/d = 0.13907892$

$$l_b = 300.00$$

$$d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_b, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$V_{r1} = V_{\text{Col}}((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col}0}$

$$V_{\text{Col}0} = 1.0392E+006$$

$k_{nl} = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

$= 1$  (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/d = 4.00$$

$$M_u = 1308.016$$

$$V_u = 0.00017144$$

$$d = 0.8 \cdot h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.0138E+006$

where:

$$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 903207.888$$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$  is multiplied by  $\text{Col},j1 = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j2}$  is multiplied by  $\text{Col},j2 = 1.00$

$$s/d = 0.3125$$

$$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 110584.061$$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$

$$s/d = 1.5625$$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$$bw = 400.00$$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$

$V_{r2} = V_{Col}$  ((10.3), ASCE 41-17) =  $k_{nl} * V_{Col0}$

$$V_{Col0} = 1.0392E+006$$

$k_{nl} = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f'_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 1308.016$$

$$V_u = 0.00017144$$

$$d = 0.8 * h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$

$$s/d = 0.3125$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$

$$s/d = 1.5625$$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
 $bw = 400.00$

-----  
-----  
End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 3

-----  
Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At Shear local axis: 2  
(Bending local axis: 3)  
Section Type: rcjcs

Constant Properties

-----  
Knowledge Factor,  $\gamma = 1.00$   
Mean strength values are used for both shear and moment calculations.  
Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,  
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 * f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 * f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = 300.00$

No FRP Wrapping

-----  
Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force,  $V_a = -0.0001715$

EDGE -B-

Shear Force,  $V_b = 0.0001715$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{st} = 0.00$

-Compression:  $A_{sc} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $Asl,ten = 1137.257$

-Compression:  $Asl,com = 2208.54$

-Middle:  $Asl,mid = 2007.478$

Calculation of Shear Capacity ratio ,  $Ve/Vr = 0.32266369$

Member Controlled by Flexure ( $Ve/Vr < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $Ve = (Mpr1 + Mpr2)/ln = 335307.657$

with

$Mpr1 = \text{Max}(Mu1+, Mu1-) = 5.0296E+008$

$Mu1+ = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu1- = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$Mpr2 = \text{Max}(Mu2+, Mu2-) = 5.0296E+008$

$Mu2+ = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu2- = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of  $Mu1+$

Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 4.8099118E-006$

$Mu = 2.3387E+008$

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\phi_c$  (5A.5, TBDY) = 0.002

Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} * \text{Max}(\phi_c, \phi_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\phi_u = 0.01260361$

$\phi_{we}$  (5.4c) = 0.05179731

$\phi_{ase}$  ((5.4d), TBDY) =  $(\phi_{ase1} * A_{ext} + \phi_{ase2} * A_{int}) / A_{sec} = 0.45746528$

$\phi_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\phi_{ase2} (>= \phi_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length

equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to  $bi^2/6$  as defined at (A.2).  
 $psh_{min} * Fywe = \text{Min}(psh_x * Fywe, psh_y * Fywe) = 3.3968$

$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $Lstir1 * Astir1 / (Asec * s1) = 0.00367709$   
Lstir1 (Length of stirrups along Y) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2$  (5.4d) =  $Lstir2 * Astir2 / (Asec * s2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $Lstir1 * Astir1 / (Asec * s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2$  ((5.4d), TBDY) =  $Lstir2 * Astir2 / (Asec * s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

su1 =  $0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1, ft1, fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(fs_{jacket} * Asl_{ten,jacket} + fs_{core} * Asl_{ten,core}) / Asl_{ten} = 262.1446$

with Es1 =  $(Es_{jacket} * Asl_{ten,jacket} + Es_{core} * Asl_{ten,core}) / Asl_{ten} = 200000.00$

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 =  $0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2, ft2, fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 262.1446$

with Es2 =  $(Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fsjacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.0187412

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03639521

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03308184

and confined core properties:

b = 690.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.02127357

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.04131304

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03755196

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

----

v < vs,y2 - LHS eq.(4.5) is satisfied

----

su (4.9) = 0.21062322

Mu = MRc (4.14) = 2.3387E+008

u = su (4.1) = 4.8099118E-006

-----  
Calculation of ratio lb/ld

-----  
Lap Length: lb/ld = 0.13907892

lb = 300.00

ld = 2157.049

Calculation of lb,min according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

ld,min from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

db = 16.66667

Mean strength value of all re-bars: fy = 781.25

Mean concrete strength: fc' = (fc'\_jacket\*Area\_jacket + fc'\_core\*Area\_core)/Area\_section = 30.00, but  $fc'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

t = 1.00

s = 0.80

e = 1.00

cb = 25.00

Ktr = 1.7174

Atr =  $\text{Min}(Atr_x, Atr_y)$  = 257.6106

where Atr\_x, Atr\_y are the sum of the area of all stirrup legs along X and Y local axis

s =  $\text{Max}(s_{\text{external}}, s_{\text{internal}})$  = 250.00

n = 24.00

-----  
Calculation of Mu1-

-----  
Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 5.1201636E-006

Mu = 5.0296E+008

-----  
with full section properties:

b = 400.00

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (> a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

---

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

---

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

---

$$A_{sec} = 440000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$y_1 = 0.00083886$$

$$sh_1 = 0.00268436$$

$$ft_1 = 314.5735$$

$$fy_1 = 262.1446$$

$$su_1 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.06824101

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03513975

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.06202846

and confined core properties:

b = 340.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.08384116

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.04317283

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.07620839

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2584548

Mu = MRc (4.14) = 5.0296E+008

u = su (4.1) = 5.1201636E-006

-----  
Calculation of ratio lb/d

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

Calculation of  $\mu_{2+}$

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$\mu = 4.8099118E-006$

$\mu_u = 2.3387E+008$

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$c_o$  (5A.5, TBDY) = 0.002

Final value of  $c_u$ :  $c_u^* = \text{shear\_factor} \cdot \text{Max}(c_u, c_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $c_u = 0.01260361$

$w_e$  (5.4c) = 0.05179731

$a_{se}$  ((5.4d), TBDY) =  $(a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.45746528$

$a_{se1} = \text{Max}(((A_{conf, \max 1} - A_{noConf1}) / A_{conf, \max 1}) \cdot (A_{conf, \min 1} / A_{conf, \max 1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf, \max 1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf, \min 1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf, \max 1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf, \max 2} - A_{noConf2}) / A_{conf, \max 2}) \cdot (A_{conf, \min 2} / A_{conf, \max 2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf, \max 2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf, \min 2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf, \max 2}$  by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * Fywe = \text{Min}(psh_x * Fywe, psh_y * Fywe) = 3.3968$

$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $Lstir1 * Astir1 / (Asec * s1) = 0.00367709$   
Lstir1 (Length of stirrups along Y) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2$  (5.4d) =  $Lstir2 * Astir2 / (Asec * s2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $Lstir1 * Astir1 / (Asec * s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2$  ((5.4d), TBDY) =  $Lstir2 * Astir2 / (Asec * s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00  
s1 = 100.00  
s2 = 250.00  
fywe1 = 781.25  
fywe2 = 781.25  
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y1 = 0.00083886  
sh1 = 0.00268436  
ft1 = 314.5735  
fy1 = 262.1446  
su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb = 0.13907892  
su1 =  $0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1, ft1, fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(fs_{jacket} * Asl_{ten,jacket} + fs_{core} * Asl_{ten,core}) / Asl_{ten} = 262.1446$

with Es1 =  $(Es_{jacket} * Asl_{ten,jacket} + Es_{core} * Asl_{ten,core}) / Asl_{ten} = 200000.00$

y2 = 0.00083886  
sh2 = 0.00268436  
ft2 = 314.5735  
fy2 = 262.1446  
su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892  
su2 =  $0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2, ft2, fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 262.1446$

with Es2 =  $(Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$

yv = 0.00083886  
shv = 0.00268436  
ftv = 314.5735  
fyv = 262.1446  
suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.13907892$$

$$s_{uv} = 0.4 * e_{suv\_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $e_{suv\_nominal} = 0.08$ ,

considering characteristic value  $f_{sv} = f_{sv}/1.2$ , from table 5.1, TBDY

For calculation of  $e_{suv\_nominal}$  and  $\gamma_v$ ,  $sh_v, ft_v, fy_v$ , it is considered

characteristic value  $f_{sv} = f_{sv}/1.2$ , from table 5.1, TBDY.

$$\gamma_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from } 10.3.5, \text{ ASCE } 41-17.$$

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 262.1446$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.0187412$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.03639521$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.03308184$$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 38.13135$$

$$c_c (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.02127357$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04131304$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.21062322$$

$$M_u = M_{Rc} (4.14) = 2.3387E+008$$

$$u = s_u (4.1) = 4.8099118E-006$$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b,min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d,min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

$$\text{Mean strength value of all re-bars: } f_y = 781.25$$

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of  $M_u$

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e (5.4c) = 0.05179731$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (> a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along } Y) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along } Y) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along } X) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along } X) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$y1 = 0.00083886$$

$$sh1 = 0.00268436$$

$$ft1 = 314.5735$$

$$fy1 = 262.1446$$

$$su1 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.06824101

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03513975

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.06202846

and confined core properties:

b = 340.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.08384116

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.04317283

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.07620839

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2584548

Mu = MRc (4.14) = 5.0296E+008

u = su (4.1) = 5.1201636E-006

-----  
Calculation of ratio lb/d  
-----

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b$ ,min according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d$ ,min from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

-----  
Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$

$V_{Col0} = 1.0392E+006$

$k_{nl} = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '

where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.675$

$V_u = 0.0001715$

$d = 0.8 \cdot h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 314159.265$  is calculated for section web jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col_{j1} = 1.00$

$s/d = 0.3125$

$V_{s,j2} = 589048.623$  is calculated for section flange jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $Col_{j2} = 1.00$

$s/d = 0.16666667$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col_{c1} = 0.00$

$s/d = 1.5625$

$V_{s,c2} = 110584.061$  is calculated for section flange core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$

$$s/d = 0.56818182$$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$$bw = 400.00$$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$

$V_{r2} = V_{Col}$  ((10.3), ASCE 41-17) =  $k_{nl} * V_{Col0}$

$$V_{Col0} = 1.0392E+006$$

$k_{nl} = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 1308.675$$

$$\nu_u = 0.0001715$$

$$d = 0.8 * h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

From (11.5.4.8), ACI 318-14:  $V_s = V_{sjacket} + V_{s,core} = 1.0138E+006$

where:

$$V_{sjacket} = V_{sj1} + V_{sj2} = 903207.888$$

$V_{sj1} = 314159.265$  is calculated for section web jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{sj1}$  is multiplied by  $Col,j1 = 1.00$

$$s/d = 0.3125$$

$V_{sj2} = 589048.623$  is calculated for section flange jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{sj2}$  is multiplied by  $Col,j2 = 1.00$

$$s/d = 0.16666667$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c1}$  is multiplied by  $Col,c1 = 0.00$

$$s/d = 1.5625$$

$V_{s,c2} = 110584.061$  is calculated for section flange core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$

$$s/d = 0.56818182$$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$$bw = 400.00$$

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At local axis: 2

---

Start Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjlc3

Constant Properties

---

Knowledge Factor,  $\gamma = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_b = 300.00$

No FRP Wrapping

---

Stepwise Properties

---

Bending Moment,  $M = -1.4730E+007$

Shear Force,  $V_2 = -4846.489$

Shear Force,  $V_3 = 135.9404$

Axial Force,  $F = -17232.621$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{sl,t} = 0.00$

-Compression:  $A_{sl,c} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten} = 1137.257$

-Compression:  $A_{sl,com} = 2208.54$

-Middle:  $A_{sl,mid} = 2007.478$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten,jacket} = 829.3805$

-Compression:  $A_{sl,com,jacket} = 1746.726$

-Middle:  $A_{sl,mid,jacket} = 1545.664$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten,core} = 307.8761$

-Compression:  $A_{sl,com,core} = 461.8141$

-Middle:  $A_{sl,mid,core} = 461.8141$

Mean Diameter of Tension Reinforcement,  $DbL = 16.80$

---

New component: From table 7-7, ASCE 41\_17: Final chord rotation Capacity  $u, R = 1.0^*$   $u = 0.0019965$   
 $u = y + p = 0.0019965$

-----  
- Calculation of  $y$  -  
-----

$y = (M_y * L_s / 3) / E_{eff} = 0.0019965$  ((4.29), Biskinis Phd))  
 $M_y = 2.8693E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 3039.252  
From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
 $factor = 0.30$   
 $A_g = 440000.00$   
Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17232.621$   
 $E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 4.8532E+014$   
-----  
-----

Calculation of Yielding Moment  $M_y$

-----  
Calculation of  $y$  and  $M_y$  according to Annex 7 -  
-----

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$   
web width,  $b_w = 400.00$   
flange thickness,  $t = 400.00$

-----  
 $y = \text{Min}(y_{ten}, y_{com})$   
 $y_{ten} = 2.1452649E-006$   
with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 * f_y * (l_b / l_d)^{2/3}) = 243.3535$   
 $d = 707.00$   
 $y = 0.1977546$   
 $A = 0.0102293$   
 $B = 0.00453971$   
with  $p_t = 0.00434791$   
 $p_c = 0.00416509$   
 $p_v = 0.00378591$   
 $N = 17232.621$   
 $b = 750.00$   
 $" = 0.06082037$   
 $y_{comp} = 1.5203329E-005$   
with  $f_c = 30.00$   
 $E_c = 25742.96$   
 $y = 0.19515388$   
 $A = 0.01001829$   
 $B = 0.00440616$   
with  $E_s = 200000.00$   
CONFIRMATION:  $y = 0.19591085 < t/d$   
-----  
-----

Calculation of ratio  $l_b / l_d$

-----  
Lap Length:  $l_d / l_{d,min} = 0.17384865$   
 $l_b = 300.00$   
 $l_d = 1725.639$   
Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)  
 $= 1$   
 $db = 16.66667$   
Mean strength value of all re-bars:  $f_y = 625.00$   
Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$   
 $e = 1.00$

$cb = 25.00$   
 $K_{tr} = 1.7174$   
 $A_{tr} = \text{Min}(A_{tr\_x}, A_{tr\_y}) = 257.6106$   
 where  $A_{tr\_x}$ ,  $A_{tr\_y}$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$   
 $n = 24.00$

-----  
 - Calculation of  $p$  -  
 -----

From table 10-8:  $p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because  $l_b/l_d < 1$

shear control ratio  $V_y E / V_{Co} I_{OE} = 0.32266369$

$d = d_{\text{external}} = 707.00$

$s = s_{\text{external}} = 0.00$

-  $t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00434791$

jacket:  $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00367709$

$A_{v1} = 78.53982$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2060.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core:  $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00067082$

$A_{v2} = 50.26548$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1468.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term  $2 * t_f / b_w * (f_{fe} / f_s)$  is implemented to account for FRP contribution

where  $f = 2 * t_f / b_w$  is FRP ratio (EC8 - 3, A.4.4.3(6)) and  $f_{fe} / f_s$  normalises  $f$  to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation  $f_s$  of jacket is used.

$N_{UD} = 17232.621$

$A_g = 440000.00$

$f_{cE} = (f_{c\_jacket} * \text{Area}_{\text{jacket}} + f_{c\_core} * \text{Area}_{\text{core}}) / \text{section\_area} = 30.00$

$f_{yE} = (f_{y\_ext\_Long\_Reinf} * \text{Area}_{\text{ext\_Long\_Reinf}} + f_{y\_int\_Long\_Reinf} * \text{Area}_{\text{int\_Long\_Reinf}}) / \text{Area}_{\text{Tot\_Long\_Rein}} = 625.00$

$f_{yE} = (f_{y\_ext\_Trans\_Reinf} * s_1 + f_{y\_int\_Trans\_Reinf} * s_2) / (s_1 + s_2) = 625.00$

$p_l = \text{Area}_{\text{Tot\_Long\_Rein}} / (b * d) = 0.01009575$

$b = 750.00$

$d = 707.00$

$f_{cE} = 30.00$

-----  
 End Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (a)  
 -----

## Calculation No. 5

column C1, Floor 1


Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjlcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of  $\gamma$  for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

Existing Column

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member  
Smooth Bars  
Ductile Steel  
With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
Longitudinal Bars With Ends Lapped Starting at the End Sections  
Lap Length  $l_o = l_b = 300.00$   
No FRP Wrapping

-----  
Stepwise Properties  
-----

EDGE -A-  
Bending Moment,  $M_a = -1.4730E+007$   
Shear Force,  $V_a = -4846.489$   
EDGE -B-  
Bending Moment,  $M_b = 186273.79$   
Shear Force,  $V_b = 4846.489$   
BOTH EDGES  
Axial Force,  $F = -17232.621$   
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension:  $A_{st} = 0.00$   
-Compression:  $A_{sc} = 5353.274$   
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension:  $A_{s,ten} = 1137.257$   
-Compression:  $A_{s,com} = 2208.54$   
-Middle:  $A_{s,mid} = 2007.478$   
Mean Diameter of Tension Reinforcement,  $D_{bL,ten} = 16.80$

-----  
New component: From table 7-7, ASCE 41\_17: Final Shear Capacity  $V_R = 1.0 \cdot V_n = 984758.516$   
 $V_n$  (10.3), ASCE 41-17) =  $k_n \cdot V_{CoI} = 984758.516$   
 $V_{CoI} = 984758.516$   
 $k_n = 1.00$   
displacement\_ductility\_demand = 0.07913193

-----  
NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
= 1 (normal-weight concrete)  
Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 20.00$ , but  $f_c'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)  
 $M / V_d = 2.00$   
 $M_u = 186273.79$   
 $V_u = 4846.489$   
 $d = 0.8 \cdot h = 600.00$   
 $N_u = 17232.621$   
 $A_g = 300000.00$   
From (11.5.4.8), ACI 318-14:  $V_s = V_{sjacket} + V_{s,core} = 811033.559$   
where:  
 $V_{sjacket} = V_{sj1} + V_{sj2} = 722566.31$   
 $V_{sj1} = 251327.412$  is calculated for section web jacket, with:  
 $d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$   
 $V_{sj1}$  is multiplied by  $Col_{j1} = 1.00$   
 $s/d = 0.3125$   
 $V_{sj2} = 471238.898$  is calculated for section flange jacket, with:  
 $d = 600.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$   
 $V_{sj2}$  is multiplied by  $Col_{j2} = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 88467.249$

$V_{s,c1}$  = 0.00 is calculated for section web core, with:

$d$  = 160.00  
 $A_v$  = 100530.965  
 $f_y$  = 500.00  
 $s$  = 250.00

$V_{s,c1}$  is multiplied by  $Col,c1$  = 0.00

$s/d$  = 1.5625

$V_{s,c2}$  = 88467.249 is calculated for section flange core, with:

$d$  = 440.00  
 $A_v$  = 100530.965  
 $f_y$  = 500.00  
 $s$  = 250.00

$V_{s,c2}$  is multiplied by  $Col,c2$  = 1.00

$s/d$  = 0.56818182

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 713005.69$

$b_w$  = 400.00

displacement\_ductility\_demand is calculated as  $\phi / y$

- Calculation of  $\phi / y$  for END B -  
for rotation axis 3 and integ. section (b)

From analysis, chord rotation = 1.5594637E-005

$y = (M_y * L_s / 3) / E_{eff} = 0.00019707$  ((4.29), Biskinis Phd)

$M_y = 2.8693E+008$

$L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 300.00

From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$

factor = 0.30

$A_g = 440000.00$

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$

$N = 17232.621$

$E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 4.8532E+014$

Calculation of Yielding Moment  $M_y$

Calculation of  $\phi / y$  and  $M_y$  according to Annex 7 -

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$

web width,  $b_w = 400.00$

flange thickness,  $t = 400.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 2.1452649E-006$

with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 243.3535$

$d = 707.00$

$y = 0.1977546$

$A = 0.0102293$

$B = 0.00453971$

with  $pt = 0.00214476$

$pc = 0.00416509$

$pv = 0.00378591$

$N = 17232.621$

$b = 750.00$

" = 0.06082037

$y_{comp} = 1.5203329E-005$

with  $f_c = 30.00$

$E_c = 25742.96$

$y = 0.19515388$

$A = 0.01001829$

$B = 0.00440616$

with  $E_s = 200000.00$

CONFIRMATION:  $y = 0.19591085 < t/d$

Calculation of ratio  $l_b/d$

Lap Length:  $l_d/d, \min = 0.17384865$

$l_b = 300.00$

$l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

End Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (b)

## Calculation No. 6

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity ( $\phi$ )

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjlc

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = 300.00$

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force,  $V_a = -0.00017144$

EDGE -B-

Shear Force,  $V_b = 0.00017144$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{sl} = 0.00$

-Compression:  $A_{slc} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten} = 1137.257$

-Compression:  $A_{sl,com} = 2208.54$

-Middle:  $A_{sl,mid} = 2007.478$

Calculation of Shear Capacity ratio ,  $V_e/V_r = 0.32266369$

Member Controlled by Flexure ( $V_e/V_r < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$

with

$M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 5.0296E+008$

$M_{u1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 5.0296E+008$

$M_{u2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

-----  
Calculation of  $M_{u1+}$   
-----

-----  
Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 4.8099118E-006$

$M_u = 2.3387E+008$   
-----

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\alpha_1$  (5A.5, TBDY) = 0.002

Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} * \text{Max}(\phi_u, \phi_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\phi_u = 0.01260361$

$\phi_c$  (5.4c) = 0.05179731

$\alpha_{se}$  ((5.4d), TBDY) =  $(\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.45746528$

$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\alpha_{se2} (> = \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\phi_{sh,min} * F_{ywe} = \text{Min}(\phi_{sh,x} * F_{ywe}, \phi_{sh,y} * F_{ywe}) = 3.3968$   
-----

$\phi_{sh,x} * F_{ywe} = \phi_{sh1} * F_{ywe1} + \phi_{sh2} * F_{ywe2} = 3.3968$

$\phi_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

psh2 (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

psh\_y \* Fywe = psh1 \* Fywe1 + ps2 \* Fywe2 = 3.3968  
psh1 ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
psh2 ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb = 0.13907892

su1 =  $0.4 * esu1\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1, ft1, fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $Min(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with Es1 =  $(Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 =  $0.4 * esu2\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2, ft2, fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $Min(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with Es2 =  $(Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb = 0.13907892

suv =  $0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY  
For calculation of esuv\_nominal and yv, shv, ftv, fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $Min(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 262.1446$   
with  $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$   
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.0187412$   
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03639521$   
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03308184$

and confined core properties:

$b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02127357$   
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04131304$   
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$\mu_u (4.9) = 0.21062322$   
 $M_u = M_{Rc} (4.14) = 2.3387E+008$   
 $u = \mu_u (4.1) = 4.8099118E-006$

-----  
Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$d_b = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
Calculation of  $\mu_{u1}$ -

-----  
Calculation of ultimate curvature  $\mu_u$  according to 4.1, Biskinis/Fardis 2013:

$u = 5.1201636E-006$

$M_u = 5.0296E+008$

-----  
with full section properties:

$b = 400.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00191815$

$N = 16273.608$

$f_c = 30.00$

$cc (5A.5, TBDY) = 0.002$

Final value of  $\mu_u$ :  $\mu_u^* = \text{shear\_factor} \cdot \text{Max}(\mu_u, cc) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $c_u = 0.01260361$

$w_e$  (5.4c) = 0.05179731

$a_{se}$  ((5.4d), TBDY) =  $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

-----  
 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $c_c = 0.00471045$

$c$  = confinement factor = 1.27105

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_{\text{jacket}} \cdot Asl_{\text{ten,jacket}} + fs_{\text{core}} \cdot Asl_{\text{ten,core}}) / Asl_{\text{ten}} = 262.1446$$

$$\text{with } Es1 = (Es_{\text{jacket}} \cdot Asl_{\text{ten,jacket}} + Es_{\text{core}} \cdot Asl_{\text{ten,core}}) / Asl_{\text{ten}} = 200000.00$$

$$y2 = 0.00083886$$

$$sh2 = 0.00268436$$

$$ft2 = 314.5735$$

$$fy2 = 262.1446$$

$$su2 = 0.00268436$$
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  

$$lo/lo_{\text{min}} = lb/lb_{\text{min}} = 0.13907892$$

$$su2 = 0.4 \cdot esu2_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$
 From table 5A.1, TBDY:  $esu2_{\text{nominal}} = 0.08$ ,  
 For calculation of  $esu2_{\text{nominal}}$  and  $y2, sh2, ft2, fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  

$$\text{with } fs2 = (fs_{\text{jacket}} \cdot Asl_{\text{com,jacket}} + fs_{\text{core}} \cdot Asl_{\text{com,core}}) / Asl_{\text{com}} = 262.1446$$

$$\text{with } Es2 = (Es_{\text{jacket}} \cdot Asl_{\text{com,jacket}} + Es_{\text{core}} \cdot Asl_{\text{com,core}}) / Asl_{\text{com}} = 200000.00$$

$$yv = 0.00083886$$

$$shv = 0.00268436$$

$$ftv = 314.5735$$

$$fyv = 262.1446$$

$$suv = 0.00268436$$
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  

$$lo/lo_{\text{min}} = lb/ld = 0.13907892$$

$$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$
 From table 5A.1, TBDY:  $esuv_{\text{nominal}} = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv_{\text{nominal}}$  and  $yv, shv, ftv, fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  

$$\text{with } fsv = (fs_{\text{jacket}} \cdot Asl_{\text{mid,jacket}} + fs_{\text{mid}} \cdot Asl_{\text{mid,core}}) / Asl_{\text{mid}} = 262.1446$$

$$\text{with } Esv = (Es_{\text{jacket}} \cdot Asl_{\text{mid,jacket}} + Es_{\text{mid}} \cdot Asl_{\text{mid,core}}) / Asl_{\text{mid}} = 200000.00$$

$$1 = Asl_{\text{ten}} / (b \cdot d) \cdot (fs1 / fc) = 0.06824101$$

$$2 = Asl_{\text{com}} / (b \cdot d) \cdot (fs2 / fc) = 0.03513975$$

$$v = Asl_{\text{mid}} / (b \cdot d) \cdot (fsv / fc) = 0.06202846$$

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, \text{TBDY}) = 38.13135$   
 $cc (5A.5, \text{TBDY}) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl_{\text{ten}} / (b \cdot d) \cdot (fs1 / fc) = 0.08384116$   
 $2 = Asl_{\text{com}} / (b \cdot d) \cdot (fs2 / fc) = 0.04317283$   
 $v = Asl_{\text{mid}} / (b \cdot d) \cdot (fsv / fc) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < vs, y2$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.2584548$   
 $Mu = MRc (4.14) = 5.0296E+008$   
 $u = su (4.1) = 5.1201636E-006$

-----  
 Calculation of ratio  $lb/ld$   
 -----

Lap Length:  $lb/ld = 0.13907892$   
 $lb = 300.00$   
 $ld = 2157.049$   
 Calculation of  $lb_{\text{min}}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $ld_{\text{min}}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$   
Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
-----  
-----  
Calculation of  $\mu_{2+}$   
-----

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 4.8099118E-006$$

$$\mu_u = 2.3387E+008$$

-----  
with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_u: \mu_u^* = \text{shear\_factor} \cdot \text{Max}(\mu_u, \mu_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_u = 0.01260361$$

$$\mu_w \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) \cdot (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (\geq a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) \cdot (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} \cdot F_{ywe} = \text{Min}(p_{sh,x} \cdot F_{ywe}, p_{sh,y} \cdot F_{ywe}) = 3.3968$$

$$p_{sh_x} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} \cdot A_{stir1} / (A_{sec} \cdot s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} \cdot A_{stir2} / (A_{sec} \cdot s2) = 0.00067082$$

Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

psh<sub>y</sub>\*Fywe = psh<sub>1</sub>\*Fywe<sub>1</sub>+ps<sub>2</sub>\*Fywe<sub>2</sub> = 3.3968  
psh<sub>1</sub> ((5.4d), TBDY) = Lstir<sub>1</sub>\*Astir<sub>1</sub>/(Asec\*s<sub>1</sub>) = 0.00367709  
Lstir<sub>1</sub> (Length of stirrups along X) = 2060.00  
Astir<sub>1</sub> (stirrups area) = 78.53982  
psh<sub>2</sub> ((5.4d), TBDY) = Lstir<sub>2</sub>\*Astir<sub>2</sub>/(Asec\*s<sub>2</sub>) = 0.00067082  
Lstir<sub>2</sub> (Length of stirrups along X) = 1468.00  
Astir<sub>2</sub> (stirrups area) = 50.26548

Asec = 440000.00  
s<sub>1</sub> = 100.00  
s<sub>2</sub> = 250.00

fywe<sub>1</sub> = 781.25  
fywe<sub>2</sub> = 781.25  
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y<sub>1</sub> = 0.00083886  
sh<sub>1</sub> = 0.00268436  
ft<sub>1</sub> = 314.5735  
fy<sub>1</sub> = 262.1446

su<sub>1</sub> = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>d</sub> = 0.13907892

su<sub>1</sub> = 0.4\*esu<sub>1\_nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu<sub>1\_nominal</sub> = 0.08,

For calculation of esu<sub>1\_nominal</sub> and y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, it is considered  
characteristic value fsy<sub>1</sub> = fs<sub>1</sub>/1.2, from table 5.1, TBDY.

y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>1</sub> = (fs<sub>jacket</sub>\*Asl<sub>ten,jacket</sub> + fs<sub>core</sub>\*Asl<sub>ten,core</sub>)/Asl<sub>ten</sub> = 262.1446

with Es<sub>1</sub> = (Es<sub>jacket</sub>\*Asl<sub>ten,jacket</sub> + Es<sub>core</sub>\*Asl<sub>ten,core</sub>)/Asl<sub>ten</sub> = 200000.00

y<sub>2</sub> = 0.00083886

sh<sub>2</sub> = 0.00268436

ft<sub>2</sub> = 314.5735

fy<sub>2</sub> = 262.1446

su<sub>2</sub> = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>b,min</sub> = 0.13907892

su<sub>2</sub> = 0.4\*esu<sub>2\_nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu<sub>2\_nominal</sub> = 0.08,

For calculation of esu<sub>2\_nominal</sub> and y<sub>2</sub>, sh<sub>2</sub>,ft<sub>2</sub>,fy<sub>2</sub>, it is considered  
characteristic value fsy<sub>2</sub> = fs<sub>2</sub>/1.2, from table 5.1, TBDY.

y<sub>2</sub>, sh<sub>2</sub>,ft<sub>2</sub>,fy<sub>2</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>2</sub> = (fs<sub>jacket</sub>\*Asl<sub>com,jacket</sub> + fs<sub>core</sub>\*Asl<sub>com,core</sub>)/Asl<sub>com</sub> = 262.1446

with Es<sub>2</sub> = (Es<sub>jacket</sub>\*Asl<sub>com,jacket</sub> + Es<sub>core</sub>\*Asl<sub>com,core</sub>)/Asl<sub>com</sub> = 200000.00

y<sub>v</sub> = 0.00083886

sh<sub>v</sub> = 0.00268436

ft<sub>v</sub> = 314.5735

fy<sub>v</sub> = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>d</sub> = 0.13907892

suv = 0.4\*esuv<sub>nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv<sub>nominal</sub> = 0.08,

considering characteristic value fsy<sub>v</sub> = fs<sub>v</sub>/1.2, from table 5.1, TBDY  
For calculation of esuv<sub>nominal</sub> and y<sub>v</sub>, sh<sub>v</sub>,ft<sub>v</sub>,fy<sub>v</sub>, it is considered

characteristic value fsy<sub>v</sub> = fs<sub>v</sub>/1.2, from table 5.1, TBDY.

y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>v</sub> = (fs<sub>jacket</sub>\*Asl<sub>mid,jacket</sub> + fs<sub>mid</sub>\*Asl<sub>mid,core</sub>)/Asl<sub>mid</sub> = 262.1446

$$\text{with } E_{sv} = (E_{s,jacket} \cdot A_{sl,mid,jacket} + E_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.0187412$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03639521$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03308184$$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 38.13135$$

$$c_c (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02127357$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04131304$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.21062322$$

$$M_u = M_{Rc} (4.14) = 2.3387E+008$$

$$u = s_u (4.1) = 4.8099118E-006$$

-----  
Calculation of ratio  $l_b/d$

-----  
Lap Length:  $l_b/d = 0.13907892$

$$l_b = 300.00$$

$$d = 2157.049$$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $M_{u2}$

-----  
Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} \cdot \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e (5.4c) = 0.05179731$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

From ((5.A.5), TBDY), TBDY:  $c_c = 0.00471045$

$c$  = confinement factor = 1.27105

$$y1 = 0.00083886$$

$$sh1 = 0.00268436$$

$$ft1 = 314.5735$$

$$fy1 = 262.1446$$

$$su1 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$$l_o / l_{ou,min} = l_b / l_d = 0.13907892$$

$$su1 = 0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , it is considered

characteristic value  $fsy1 = fs1 / 1.2$ , from table 5.1, TBDY.

$y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$$

with  $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$   
 $y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{o,min} = l_b/l_{b,min} = 0.13907892$   
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{2,nominal} = 0.08$ ,  
 For calculation of  $esu_{2,nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
 characteristic value  $fs_2 = fs_2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_2 = (fs_{jacket} \cdot A_{s,com,jacket} + fs_{core} \cdot A_{s,com,core}) / A_{s,com} = 262.1446$   
 with  $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{o,min} = l_b/l_d = 0.13907892$   
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv_{nominal} = 0.08$ ,  
 considering characteristic value  $fs_v = fs_v/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv_{nominal}$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fs_v = fs_v/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_v = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 262.1446$   
 with  $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$   
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / f_c) = 0.06824101$   
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / f_c) = 0.03513975$   
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / f_c) = 0.06202846$

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / f_c) = 0.08384116$   
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / f_c) = 0.04317283$   
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / f_c) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_s, y_2$  - LHS eq.(4.5) is satisfied

---->

$su (4.9) = 0.2584548$   
 $M_u = MR_c (4.14) = 5.0296E+008$   
 $u = su (4.1) = 5.1201636E-006$

-----  
 Calculation of ratio  $l_b/l_d$

-----  
 Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

-----  
Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

-----  
Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$V_{r1} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{ColO}}$

$V_{\text{ColO}} = 1.0392E+006$

$k_{nl} = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $f = 1$  (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M/d = 4.00$

$M_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 \cdot h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.0138E+006$

where:

$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$

$s/d = 0.3125$

$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$

$s/d = 1.5625$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
 $bw = 400.00$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$   
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$   
 $V_{Col0} = 1.0392E+006$   
 $knl = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

$= 1$  (normal-weight concrete)  
Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 * h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col_{j1} = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $Col_{j2} = 1.00$

$s/d = 0.3125$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col_{c1} = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $Col_{c2} = 0.00$

$s/d = 1.5625$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$bw = 400.00$

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjics

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = 300.00$

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force,  $V_a = -0.0001715$

EDGE -B-

Shear Force,  $V_b = 0.0001715$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{st} = 0.00$

-Compression:  $A_{sc} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{st,ten} = 1137.257$

-Compression:  $A_{sc,com} = 2208.54$

-Middle:  $A_{st,mid} = 2007.478$

Calculation of Shear Capacity ratio,  $V_e/V_r = 0.32266369$

Member Controlled by Flexure ( $V_e/V_r < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 5.0296E+008$

$\mu_{1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$\mu_{1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 5.0296E+008$

$\mu_{2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

-----  
Calculation of  $\mu_{1+}$   
-----

-----  
Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 4.8099118E-006$

$\mu_u = 2.3387E+008$   
-----

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\phi_{co} (5A.5, \text{TBDY}) = 0.002$

Final value of  $\phi_{cu}$ :  $\phi_{cu}^* = \text{shear\_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\phi_{cu} = 0.01260361$

$\omega_e (5.4c) = 0.05179731$

$\omega_{ase} ((5.4d), \text{TBDY}) = (\omega_{ase1} * A_{ext} + \omega_{ase2} * A_{int}) / A_{sec} = 0.45746528$

$\omega_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\omega_{ase2} (> \omega_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\phi_{psh,min} * F_{ywe} = \text{Min}(\phi_{psh,x} * F_{ywe}, \phi_{psh,y} * F_{ywe}) = 3.3968$   
-----

$\phi_{psh,x} * F_{ywe} = \phi_{psh1} * F_{ywe1} + \phi_{psh2} * F_{ywe2} = 3.3968$

$\phi_{psh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$\phi_{psh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548  
-----

$\phi_{psh,y} * F_{ywe} = \phi_{psh1} * F_{ywe1} + \phi_{psh2} * F_{ywe2} = 3.3968$

psh1 ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
psh2 ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

su1 =  $0.4 * esu1\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(fs\_jacket * A_{sl,ten,jacket} + fs\_core * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with Es1 =  $(Es\_jacket * A_{sl,ten,jacket} + Es\_core * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 =  $0.4 * esu2\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(fs\_jacket * A_{sl,com,jacket} + fs\_core * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with Es2 =  $(Es\_jacket * A_{sl,com,jacket} + Es\_core * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

suv =  $0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv =  $(fs\_jacket * A_{sl,mid,jacket} + fs\_mid * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$

with Esv =  $(Es\_jacket * A_{sl,mid,jacket} + Es\_mid * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

1 =  $A_{sl,ten} / (b * d) * (fs1 / fc) = 0.0187412$

2 =  $A_{sl,com} / (b * d) * (fs2 / fc) = 0.03639521$

v =  $A_{sl,mid} / (b * d) * (fsv / fc) = 0.03308184$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc \text{ (5A.2, TBDY)} = 38.13135$$

$$cc \text{ (5A.5, TBDY)} = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten}/(b*d)*(fs1/fc) = 0.02127357$$

$$2 = A_{sl,com}/(b*d)*(fs2/fc) = 0.04131304$$

$$v = A_{sl,mid}/(b*d)*(fsv/fc) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u \text{ (4.9)} = 0.21062322$$

$$M_u = MR_c \text{ (4.14)} = 2.3387E+008$$

$$u = s_u \text{ (4.1)} = 4.8099118E-006$$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of  $M_u1$ -

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

Final value of  $c_u$ :  $c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.  
 $A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.  
 $A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c =$  confinement factor = 1.27105

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$f_y2 = 262.1446$   
 $s_u2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{o,min} = l_b/l_{b,min} = 0.13907892$   
 $s_u2 = 0.4 * e_{su2\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $e_{su2\_nominal} = 0.08$ ,  
 For calculation of  $e_{su2\_nominal}$  and  $y_2, sh_2, ft_2, f_y2$ , it is considered  
 characteristic value  $f_{sy2} = f_s2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, f_y1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 262.1446$   
 with  $E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $f_yv = 262.1446$   
 $s_{uv} = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{o,min} = l_b/l_d = 0.13907892$   
 $s_{uv} = 0.4 * e_{suv\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $e_{suv\_nominal} = 0.08$ ,  
 considering characteristic value  $f_{syv} = f_{sv}/1.2$ , from table 5.1, TBDY  
 For calculation of  $e_{suv\_nominal}$  and  $y_v, sh_v, ft_v, f_yv$ , it is considered  
 characteristic value  $f_{syv} = f_{sv}/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, f_y1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $f_{sv} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 262.1446$   
 with  $E_{sv} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$   
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.06824101$   
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.03513975$   
 $v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.06202846$   
 and confined core properties:  
 $b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $c_c (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.08384116$   
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.04317283$   
 $v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)  
 --->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied  
 --->  
 $s_u (4.9) = 0.2584548$   
 $M_u = M_{Rc} (4.14) = 5.0296E+008$   
 $u = s_u (4.1) = 5.1201636E-006$

---

Calculation of ratio  $l_b/l_d$

---

Lap Length:  $l_b/l_d = 0.13907892$   
 $l_b = 300.00$   
 $l_d = 2157.049$   
 Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$   
 Mean strength value of all re-bars:  $f_y = 781.25$   
 Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$

$e = 1.00$   
 $cb = 25.00$   
 $Ktr = 1.7174$   
 $Atr = \text{Min}(Atr_x, Atr_y) = 257.6106$   
 where  $Atr_x, Atr_y$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$   
 $n = 24.00$

-----  
 Calculation of  $\mu_{2+}$   
 -----

-----  
 Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:  
 $\mu = 4.8099118E-006$   
 $\mu_{2+} = 2.3387E+008$   
 -----

with full section properties:

$b = 750.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00102301$   
 $N = 16273.608$

$f_c = 30.00$   
 $\alpha_{\text{co}} (5A.5, \text{TBDY}) = 0.002$   
 Final value of  $\mu_{cu}$ :  $\mu_{cu}^* = \text{shear\_factor} * \text{Max}(\mu_{cu}, \mu_{cc}) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\mu_{cu} = 0.01260361$

we (5.4c) = 0.05179731

$\alpha_{\text{se}} ((5.4d), \text{TBDY}) = (\alpha_{\text{se1}} * A_{\text{ext}} + \alpha_{\text{se2}} * A_{\text{int}}) / A_{\text{sec}} = 0.45746528$

$\alpha_{\text{se1}} = \text{Max}(((A_{\text{conf,max1}} - A_{\text{noConf1}}) / A_{\text{conf,max1}}) * (A_{\text{conf,min1}} / A_{\text{conf,max1}}), 0) = 0.45746528$

The definitions of  $A_{\text{noConf}}$ ,  $A_{\text{conf,min}}$  and  $A_{\text{conf,max}}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max1}} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{\text{conf,min1}} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{\text{conf,max1}}$  by a length equal to half the clear spacing between external hoops.

$A_{\text{noConf1}} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\alpha_{\text{se2}} (> \alpha_{\text{se1}}) = \text{Max}(((A_{\text{conf,max2}} - A_{\text{noConf2}}) / A_{\text{conf,max2}}) * (A_{\text{conf,min2}} / A_{\text{conf,max2}}), 0) = 0.45746528$

The definitions of  $A_{\text{noConf}}$ ,  $A_{\text{conf,min}}$  and  $A_{\text{conf,max}}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max2}} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{\text{conf,min2}} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{\text{conf,max2}}$  by a length equal to half the clear spacing between internal hoops.

$A_{\text{noConf2}} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\text{psh}_{\text{min}} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 3.3968$

-----  
 $\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 3.3968$

$\text{psh}_1 ((5.4d), \text{TBDY}) = L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s_1) = 0.00367709$

$L_{\text{stir1}}$  (Length of stirrups along Y) = 2060.00

$A_{\text{stir1}}$  (stirrups area) = 78.53982

$\text{psh}_2 (5.4d) = L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s_2) = 0.00067082$

$L_{\text{stir2}}$  (Length of stirrups along Y) = 1468.00

$A_{\text{stir2}}$  (stirrups area) = 50.26548

-----  
 $\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 3.3968$

$\text{psh}_1 ((5.4d), \text{TBDY}) = L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s_1) = 0.00367709$

Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
psh2 ((5.4d), TBDY) = Lstir2\*Astir2/(Asec\*s2) = 0.00067082  
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.0187412

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03639521

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03308184

and confined core properties:

$b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.02127357$   
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04131304$   
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.03755196$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.21062322$   
 $Mu = MRc (4.14) = 2.3387E+008$   
 $u = su (4.1) = 4.8099118E-006$

-----  
 Calculation of ratio  $l_b/l_d$

-----  
 Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$   
 $l_d = 2157.049$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$   
 $db = 16.66667$   
 Mean strength value of all re-bars:  $f_y = 781.25$   
 Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$   
 $e = 1.00$   
 $cb = 25.00$   
 $K_{tr} = 1.7174$   
 $A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$   
 where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{external}, s_{internal}) = 250.00$   
 $n = 24.00$

-----  
 Calculation of  $Mu_2$ -

-----  
 Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$u = 5.1201636E-006$   
 $Mu = 5.0296E+008$

-----  
 with full section properties:

$b = 400.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00191815$   
 $N = 16273.608$   
 $f_c = 30.00$   
 $co (5A.5, TBDY) = 0.002$   
 Final value of  $cu$ :  $cu^* = \text{shear\_factor} * \text{Max}(cu, cc) = 0.01260361$   
 The Shear\_factor is considered equal to 1 (pure moment strength)  
 From (5.4b), TBDY:  $cu = 0.01260361$   
 $we (5.4c) = 0.05179731$   
 $ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$   
 $ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$   
 The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

$A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$

$c$  = confinement factor = 1.27105

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$fy2 = 262.1446$

$$su_2 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_{b,min} = 0.13907892$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $esu_{2,nominal} = 0.08$ ,

For calculation of  $esu_{2,nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
characteristic value  $fs_2 = fs_2/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.00083886$$

$$sh_v = 0.00268436$$

$$ft_v = 314.5735$$

$$fy_v = 262.1446$$

$$suv = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_d = 0.13907892$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $esuv_{nominal} = 0.08$ ,

considering characteristic value  $fs_v = fs_v/1.2$ , from table 5.1, TBDY

For calculation of  $esuv_{nominal}$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
characteristic value  $fs_v = fs_v/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs_v = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$$

$$\text{with } Es_v = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / fc) = 0.06824101$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / fc) = 0.03513975$$

$$v = A_{sl,mid} / (b * d) * (fs_v / fc) = 0.06202846$$

and confined core properties:

$$b = 340.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 38.13135$$

$$cc (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / fc) = 0.08384116$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / fc) = 0.04317283$$

$$v = A_{sl,mid} / (b * d) * (fs_v / fc) = 0.07620839$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.2584548$$

$$\mu = MR_c (4.14) = 5.0296E+008$$

$$u = su (4.1) = 5.1201636E-006$$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$db = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

$$\text{Calculation of Shear Strength } V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$$

$$\text{Calculation of Shear Strength at edge 1, } V_{r1} = 1.0392E+006$$

$$V_{r1} = V_{Col} \text{ ((10.3), ASCE 41-17)} = k_{nl} * V_{Col0}$$

$$V_{Col0} = 1.0392E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{\text{jacket}} * \text{Area}_{\text{jacket}} + f_c'_{\text{core}} * \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 4.00$$

$$\mu_u = 1308.675$$

$$V_u = 0.0001715$$

$$d = 0.8 * h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.0138E+006$$

where:

$$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 903207.888$$

$V_{s,j1} = 314159.265$  is calculated for section web jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$$V_{s,j1} \text{ is multiplied by } Col_{j1} = 1.00$$

$$s/d = 0.3125$$

$V_{s,j2} = 589048.623$  is calculated for section flange jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$$V_{s,j2} \text{ is multiplied by } Col_{j2} = 1.00$$

$$s/d = 0.16666667$$

$$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 110584.061$$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$$V_{s,c1} \text{ is multiplied by } Col_{c1} = 0.00$$

$$s/d = 1.5625$$

$V_{s,c2} = 110584.061$  is calculated for section flange core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$$V_{s,c2} \text{ is multiplied by } Col_{c2} = 1.00$$

$$s/d = 0.56818182$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 873250.061$$

$$bw = 400.00$$

$$\text{Calculation of Shear Strength at edge 2, } V_{r2} = 1.0392E+006$$

Vr2 = VCol ((10.3), ASCE 41-17) = knl\*VCol0

VCol0 = 1.0392E+006

kn1 = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av\*fy\*d/s' is replaced by 'Vs+ f\*Vf'  
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'\_jacket\*Area\_jacket + fc'\_core\*Area\_core)/Area\_section = 30.00, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 1308.675

Vu = 0.0001715

d = 0.8\*h = 600.00

Nu = 16273.608

Ag = 300000.00

From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 1.0138E+006

where:

Vs,jacket = Vs,j1 + Vs,j2 = 903207.888

Vs,j1 = 314159.265 is calculated for section web jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.3125

Vs,j2 = 589048.623 is calculated for section flange jacket, with:

d = 600.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.16666667

Vs,core = Vs,c1 + Vs,c2 = 110584.061

Vs,c1 = 0.00 is calculated for section web core, with:

d = 160.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 0.00

s/d = 1.5625

Vs,c2 = 110584.061 is calculated for section flange core, with:

d = 440.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 1.00

s/d = 0.56818182

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 873250.061

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1  
At local axis: 2  
Integration Section: (b)  
Section Type: rcjlcs

Constant Properties

Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_b = 300.00$

No FRP Wrapping

-----  
Stepwise Properties

Bending Moment,  $M = -112991.609$

Shear Force,  $V_2 = 4846.489$

Shear Force,  $V_3 = -135.9404$

Axial Force,  $F = -17232.621$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $As_t = 0.00$

-Compression:  $As_c = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $As_{t,ten} = 1137.257$

-Compression:  $As_{l,com} = 2208.54$

-Middle:  $As_{l,mid} = 2007.478$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension:  $As_{l,ten,jacket} = 829.3805$

-Compression:  $As_{l,com,jacket} = 1746.726$

-Middle:  $As_{l,mid,jacket} = 1545.664$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $As_{l,ten,core} = 307.8761$

-Compression:  $As_{l,com,core} = 461.8141$

-Middle:  $As_{l,mid,core} = 461.8141$

Mean Diameter of Tension Reinforcement,  $Db_L = 16.80$

-----  
New component: From table 7-7, ASCE 41\_17: Final chord rotation Capacity  $u_R = 1.0^*$   $u = 0.00054601$

$u = y + p = 0.00054601$

-----  
- Calculation of  $y$  -

$y = (M_y * L_s / 3) / E_{eff} = 0.00054601$  ((4.29), Biskinis Phd))

$M_y = 2.8693E+008$

$L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 831.1851

From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$

factor = 0.30

$A_g = 440000.00$

Mean concrete strength:  $f'_c = (f'_{c\_jacket} \cdot Area\_jacket + f'_{c\_core} \cdot Area\_core) / Area\_section = 30.00$

$N = 17232.621$

$E_c \cdot I_g = E_{c\_jacket} \cdot I_{g\_jacket} + E_{c\_core} \cdot I_{g\_core} = 4.8532E+014$

Calculation of Yielding Moment  $M_y$

Calculation of  $y$  and  $M_y$  according to Annex 7 -

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$

web width,  $b_w = 400.00$

flange thickness,  $t = 400.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 2.1452649E-006$

with  $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 243.3535$

$d = 707.00$

$y = 0.1977546$

$A = 0.0102293$

$B = 0.00453971$

with  $pt = 0.00434791$

$pc = 0.00416509$

$pv = 0.00378591$

$N = 17232.621$

$b = 750.00$

$" = 0.06082037$

$y_{comp} = 1.5203329E-005$

with  $f_c = 30.00$

$E_c = 25742.96$

$y = 0.19515388$

$A = 0.01001829$

$B = 0.00440616$

with  $E_s = 200000.00$

CONFIRMATION:  $y = 0.19591085 < t/d$

Calculation of ratio  $l_b/d$

Lap Length:  $l_d/l_{d,min} = 0.17384865$

$l_b = 300.00$

$l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f'_c = (f'_{c\_jacket} \cdot Area\_jacket + f'_{c\_core} \cdot Area\_core) / Area\_section = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr\_x}, A_{tr\_y}) = 257.6106$

where  $A_{tr\_x}$ ,  $A_{tr\_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

- Calculation of  $\rho_p$  -

From table 10-8:  $\rho_p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because  $l_b/l_d < 1$

shear control ratio  $V_y E / V_{Co} I_{OE} = 0.32266369$

$d = d_{external} = 707.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00434791$

jacket:  $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00367709$

$A_{v1} = 78.53982$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2060.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core:  $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00067082$

$A_{v2} = 50.26548$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1468.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term  $2 * t_f / b_w * (f_{fe} / f_s)$  is implemented to account for FRP contribution

where  $f = 2 * t_f / b_w$  is FRP ratio (EC8 - 3, A.4.4.3(6)) and  $f_{fe} / f_s$  normalises  $f$  to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation  $f_s$  of jacket is used.

$N_{UD} = 17232.621$

$A_g = 440000.00$

$f_{cE} = (f_{c,jacket} * Area_{jacket} + f_{c,core} * Area_{core}) / section\_area = 30.00$

$f_{yIE} = (f_{y,ext\_Long\_Reinf} * Area_{ext\_Long\_Reinf} + f_{y,int\_Long\_Reinf} * Area_{int\_Long\_Reinf}) / Area_{Tot\_Long\_Rein} = 625.00$

$f_{yIE} = (f_{y,ext\_Trans\_Reinf} * s_1 + f_{y,int\_Trans\_Reinf} * s_2) / (s_1 + s_2) = 625.00$

$\rho_l = Area_{Tot\_Long\_Rein} / (b * d) = 0.01009575$

$b = 750.00$

$d = 707.00$

$f_{cE} = 30.00$

-----  
End Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (b)

-----

## Calculation No. 7

column C1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity  $V_{Rd}$

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjlcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of  $\gamma$  for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

Existing Column

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = l_b = 300.00$

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment,  $M_a = -293351.828$

Shear Force,  $V_a = 135.9404$   
 EDGE -B-  
 Bending Moment,  $M_b = -112991.609$   
 Shear Force,  $V_b = -135.9404$   
 BOTH EDGES  
 Axial Force,  $F = -17232.621$   
 Longitudinal Reinforcement Area Distribution (in 2 divisions)  
   -Tension:  $A_{st} = 0.00$   
   -Compression:  $A_{sc} = 5353.274$   
 Longitudinal Reinforcement Area Distribution (in 3 divisions)  
   -Tension:  $A_{st,ten} = 1137.257$   
   -Compression:  $A_{sc,com} = 2208.54$   
   -Middle:  $A_{st,mid} = 2007.478$   
 Mean Diameter of Tension Reinforcement,  $D_{bL,ten} = 16.80$

-----  
 -----  
 New component: From table 7-7, ASCE 41\_17: Final Shear Capacity  $V_R = 1.0 \cdot V_n = 984758.516$   
 $V_n$  ((10.3), ASCE 41-17) =  $k_n \cdot V_{CoI0} = 984758.516$   
 $V_{CoI} = 984758.516$   
 $k_n = 1.00$   
 $displacement\_ductility\_demand = 1.5776519E-005$

-----  
 NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '  
 where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)  
 Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 20.00$ , but  $f_c^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $M/d = 2.00$   
 $M_u = 112991.609$   
 $V_u = 135.9404$   
 $d = 0.8 \cdot h = 600.00$   
 $N_u = 17232.621$   
 $A_g = 300000.00$   
 From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 811033.559$   
 where:  
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 722566.31$   
 $V_{s,j1} = 471238.898$  is calculated for section web jacket, with:  
 $d = 600.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$   
 $V_{s,j1}$  is multiplied by  $Col_{j1} = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,j2} = 251327.412$  is calculated for section flange jacket, with:  
 $d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$   
 $V_{s,j2}$  is multiplied by  $Col_{j2} = 1.00$   
 $s/d = 0.3125$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 88467.249$   
 $V_{s,c1} = 88467.249$  is calculated for section web core, with:  
 $d = 440.00$   
 $A_v = 100530.965$   
 $f_y = 500.00$   
 $s = 250.00$   
 $V_{s,c1}$  is multiplied by  $Col_{c1} = 1.00$   
 $s/d = 0.56818182$   
 $V_{s,c2} = 0.00$  is calculated for section flange core, with:  
 $d = 160.00$   
 $A_v = 100530.965$   
 $f_y = 500.00$   
 $s = 250.00$   
 $V_{s,c2}$  is multiplied by  $Col_{c2} = 0.00$

$s/d = 1.5625$   
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$   
From (11-11), ACI 440:  $V_s + V_f \leq 713005.69$   
 $bw = 400.00$

-----  
displacement\_ductility\_demand is calculated as  $\delta / y$

- Calculation of  $\delta / y$  for END B -  
for rotation axis 2 and integ. section (b)

-----  
From analysis, chord rotation  $\theta = 8.6141257E-009$   
 $y = (M_y * L_s / 3) / E_{eff} = 0.00054601$  ((4.29), Biskinis Phd))  
 $M_y = 2.8693E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 831.1851  
From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
 $factor = 0.30$   
 $A_g = 440000.00$   
Mean concrete strength:  $f'_c = (f'_{c\_jacket} * Area_{jacket} + f'_{c\_core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17232.621$   
 $E_c * I_g = E_{c\_jacket} * I_{g\_jacket} + E_{c\_core} * I_{g\_core} = 4.8532E+014$

-----  
Calculation of Yielding Moment  $M_y$

-----  
Calculation of  $\delta / y$  and  $M_y$  according to Annex 7 -

-----  
Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:  
flange width,  $b = 750.00$   
web width,  $bw = 400.00$   
flange thickness,  $t = 400.00$

-----  
 $y = \text{Min}(y_{ten}, y_{com})$   
 $y_{ten} = 2.1452649E-006$   
with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 * f_y * (l_b / d)^{2/3}) = 243.3535$   
 $d = 707.00$   
 $y = 0.1977546$   
 $A = 0.0102293$   
 $B = 0.00453971$   
with  $pt = 0.00214476$   
 $pc = 0.00416509$   
 $pv = 0.00378591$   
 $N = 17232.621$   
 $b = 750.00$   
 $\lambda = 0.06082037$   
 $y_{comp} = 1.5203329E-005$   
with  $f_c = 30.00$   
 $E_c = 25742.96$   
 $y = 0.19515388$   
 $A = 0.01001829$   
 $B = 0.00440616$   
with  $E_s = 200000.00$   
CONFIRMATION:  $y = 0.19591085 < t/d$

-----  
Calculation of ratio  $l_b / d$


-----  
Lap Length:  $l_d / d, \text{min} = 0.17384865$   
 $l_b = 300.00$   
 $l_d = 1725.639$   
Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_d, \text{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)  
 $= 1$   
 $db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$   
 Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$   
 $e = 1.00$   
 $cb = 25.00$   
 $K_{tr} = 1.7174$   
 $A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$   
 where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$   
 $n = 24.00$

End Of Calculation of Shear Capacity for element: column JLC1 of floor 1  
 At local axis: 3  
 Integration Section: (b)

## Calculation No. 8

column C1, Floor 1  
 Limit State: Operational Level (data interpolation between analysis steps 1 and 2)  
 Analysis: Uniform +X  
 Check: Chord rotation capacity (  $\mu$  )  
 Edge: End  
 Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
 At Shear local axis: 3  
 (Bending local axis: 2)  
 Section Type: rcjlc

Constant Properties

Knowledge Factor,  $= 1.00$   
 Mean strength values are used for both shear and moment calculations.  
 Consequently:  
 Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$   
 Existing Column  
 New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$   
 #####  
 Note: Especially for the calculation of moment strengths,  
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14  
 Jacket  
 New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$   
 Existing Column  
 New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$   
 #####  
 Max Height,  $H_{max} = 750.00$   
 Min Height,  $H_{min} = 400.00$   
 Max Width,  $W_{max} = 750.00$   
 Min Width,  $W_{min} = 400.00$   
 Jacket Thickness,  $t_j = 100.00$   
 Cover Thickness,  $c = 25.00$   
 Mean Confinement Factor overall section = 1.27105  
 Element Length,  $L = 3000.00$   
 Primary Member  
 Smooth Bars  
 Ductile Steel  
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
 Longitudinal Bars With Ends Lapped Starting at the End Sections  
 Lap Length  $l_o = 300.00$   
 No FRP Wrapping

-----  
 Stepwise Properties  
 -----

At local axis: 3  
 EDGE -A-  
 Shear Force,  $V_a = -0.00017144$   
 EDGE -B-  
 Shear Force,  $V_b = 0.00017144$   
 BOTH EDGES  
 Axial Force,  $F = -16273.608$   
 Longitudinal Reinforcement Area Distribution (in 2 divisions)  
 -Tension:  $A_{sl,t} = 0.00$   
 -Compression:  $A_{sl,c} = 5353.274$   
 Longitudinal Reinforcement Area Distribution (in 3 divisions)  
 -Tension:  $A_{sl,ten} = 1137.257$   
 -Compression:  $A_{sl,com} = 2208.54$   
 -Middle:  $A_{sl,mid} = 2007.478$

-----  
 -----  
 Calculation of Shear Capacity ratio,  $V_e/V_r = 0.32266369$   
 Member Controlled by Flexure ( $V_e/V_r < 1$ )  
 Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$   
 with  
 $M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 5.0296E+008$   
 $M_{u1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction  
 which is defined for the static loading combination  
 $M_{u1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment  
 direction which is defined for the static loading combination  
 $M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 5.0296E+008$   
 $M_{u2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction  
 which is defined for the static loading combination  
 $M_{u2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment

direction which is defined for the the static loading combination

Calculation of  $\mu_{1+}$

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 4.8099118E-006$$

$$\mu_{1+} = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$\alpha (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu_{1+}: \mu_{1+} = \text{shear\_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01260361$$

$$\mu_{cc} (5.4c) = 0.05179731$$

$$\alpha_{se} ((5.4d), TBDY) = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\alpha_{se2} (> \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 440000.00$$

$s_1 = 100.00$   
 $s_2 = 250.00$   
 $fy_{we1} = 781.25$   
 $fy_{we2} = 781.25$   
 $f_{ce} = 30.00$   
 From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $y_1 = 0.00083886$   
 $sh_1 = 0.00268436$   
 $ft_1 = 314.5735$   
 $fy_1 = 262.1446$   
 $su_1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/ld = 0.13907892$   
 $su_1 = 0.4 * esu_{1\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{1\_nominal} = 0.08$ ,  
 For calculation of  $esu_{1\_nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered  
 characteristic value  $fsy_1 = fs_1/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_1 = (fs_{jacket} * Asl, \text{ten}, \text{jacket} + fs_{core} * Asl, \text{ten}, \text{core}) / Asl, \text{ten} = 262.1446$   
 with  $Es_1 = (Es_{jacket} * Asl, \text{ten}, \text{jacket} + Es_{core} * Asl, \text{ten}, \text{core}) / Asl, \text{ten} = 200000.00$   
 $y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/lb, \min = 0.13907892$   
 $su_2 = 0.4 * esu_{2\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{2\_nominal} = 0.08$ ,  
 For calculation of  $esu_{2\_nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
 characteristic value  $fsy_2 = fs_2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_2 = (fs_{jacket} * Asl, \text{com}, \text{jacket} + fs_{core} * Asl, \text{com}, \text{core}) / Asl, \text{com} = 262.1446$   
 with  $Es_2 = (Es_{jacket} * Asl, \text{com}, \text{jacket} + Es_{core} * Asl, \text{com}, \text{core}) / Asl, \text{com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/ld = 0.13907892$   
 $suv = 0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs_{jacket} * Asl, \text{mid}, \text{jacket} + fs_{mid} * Asl, \text{mid}, \text{core}) / Asl, \text{mid} = 262.1446$   
 with  $Es_v = (Es_{jacket} * Asl, \text{mid}, \text{jacket} + Es_{mid} * Asl, \text{mid}, \text{core}) / Asl, \text{mid} = 200000.00$   
 $1 = Asl, \text{ten} / (b * d) * (fs_1 / f_c) = 0.0187412$   
 $2 = Asl, \text{com} / (b * d) * (fs_2 / f_c) = 0.03639521$   
 $v = Asl, \text{mid} / (b * d) * (fsv / f_c) = 0.03308184$   
 and confined core properties:  
 $b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl, \text{ten} / (b * d) * (fs_1 / f_c) = 0.02127357$

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.04131304$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---->

$$s_u(4.9) = 0.21062322$$

$$M_u = M_{Rc}(4.14) = 2.3387E+008$$

$$u = s_u(4.1) = 4.8099118E-006$$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \min(A_{tr,x}, A_{tr,y}) = 257.6106$$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \max(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of  $M_u1$ -

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

Final value of  $c_u$ :  $c_u^* = \text{shear\_factor} * \max(c_u, c_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e(5.4c) = 0.05179731$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \max(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

AnoConf1 = 158733.333 is the unconfined external core area which is equal to  $b_i/6$  as defined at (A.2).  
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - \text{AnoConf}_2)/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$\text{AnoConf}_2 = 106242.667$  is the unconfined internal core area which is equal to  $b_i/6$  as defined at (A.2).  
 $psh_{,min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.3968$   
 $psh_1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh_2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.3968$   
 $psh_1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh_2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c =$  confinement factor = 1.27105

$y_1 = 0.00083886$

$sh_1 = 0.00268436$

$ft_1 = 314.5735$

$fy_1 = 262.1446$

$su_1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.13907892$

$su_1 = 0.4 * esu_{1,nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu_{1,nominal} = 0.08$ ,

For calculation of  $esu_{1,nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered characteristic value  $fs_1 = fs_1/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 262.1446$

with  $Es_1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y_2 = 0.00083886$

$sh_2 = 0.00268436$

$ft_2 = 314.5735$

$fy_2 = 262.1446$

$su_2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.13907892$

$su_2 = 0.4 * esu_{2,nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu_{2,nominal} = 0.08$ ,

For calculation of  $es_{u2\_nominal}$  and  $y_2$ ,  $sh_2, ft_2, fy_2$ , it is considered characteristic value  $fs_{y2} = fs_2/1.2$ , from table 5.1, TBDY.

$y_1$ ,  $sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es_2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00083886$

$sh_v = 0.00268436$

$ft_v = 314.5735$

$fy_v = 262.1446$

$s_{uv} = 0.00268436$

using (30) in Bisquinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.13907892$

$s_{uv} = 0.4 \cdot es_{uv\_nominal} ((5,5), TBDY) = 0.032$

From table 5A.1, TBDY:  $es_{uv\_nominal} = 0.08$ ,

considering characteristic value  $fs_{yv} = f_{sv}/1.2$ , from table 5.1, TBDY

For calculation of  $es_{uv\_nominal}$  and  $y_v$ ,  $sh_v, ft_v, fy_v$ , it is considered characteristic value  $fs_{yv} = f_{sv}/1.2$ , from table 5.1, TBDY.

$y_1$ ,  $sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{sv} = (f_{s,jacket} \cdot A_{sl,mid,jacket} + f_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 262.1446$

with  $Es_v = (Es_{jacket} \cdot A_{sl,mid,jacket} + Es_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.06824101$

$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03513975$

$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.06202846$

and confined core properties:

$b = 340.00$

$d = 677.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 38.13135$

$cc (5A.5, TBDY) = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08384116$

$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04317283$

$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.2584548$

$\mu_u = MR_c (4.14) = 5.0296E+008$

$u = su (4.1) = 5.1201636E-006$

-----  
Calculation of ratio  $lb/ld$

Lap Length:  $lb/ld = 0.13907892$

$lb = 300.00$

$ld = 2157.049$

Calculation of  $lb_{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld_{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y loxal axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

Calculation of Mu2+

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 4.8099118E-006$$

$$\mu = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s_1 = 100.00$$

$s_2 = 250.00$   
 $fy_{we1} = 781.25$   
 $fy_{we2} = 781.25$   
 $f_{ce} = 30.00$   
 From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $y_1 = 0.00083886$   
 $sh_1 = 0.00268436$   
 $ft_1 = 314.5735$   
 $fy_1 = 262.1446$   
 $su_1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/d = 0.13907892$   
 $su_1 = 0.4 * esu_{1\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{1\_nominal} = 0.08$ ,  
 For calculation of  $esu_{1\_nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered  
 characteristic value  $fsy_1 = fs_1/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$   
 with  $Es_1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$   
 $y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/lb, \min = 0.13907892$   
 $su_2 = 0.4 * esu_{2\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{2\_nominal} = 0.08$ ,  
 For calculation of  $esu_{2\_nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
 characteristic value  $fsy_2 = fs_2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$   
 with  $Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou, \min = lb/d = 0.13907892$   
 $suv = 0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$   
 with  $Es_v = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$   
 $1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.0187412$   
 $2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.03639521$   
 $v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.03308184$   
 and confined core properties:  
 $b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.02127357$   
 $2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.04131304$

$$v = A_{sl, mid} / (b * d) * (f_{sv} / f_c) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture  
' satisfies Eq. (4.3)

--->

$v < v_{s, y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.21062322$$

$$M_u = M_{Rc}(4.14) = 2.3387E+008$$

$$u = s_u(4.1) = 4.8099118E-006$$

-----  
Calculation of ratio  $l_b / l_d$

Lap Length:  $l_b / l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $M_u2$ -

-----  
Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e(5.4c) = 0.05179731$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf, max1} - A_{noConf1}) / A_{conf, max1}) * (A_{conf, min1} / A_{conf, max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf, min}$  and  $A_{conf, max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf, max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf, min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf, max1}$  by a length equal to half the clear spacing between external hoops.

AnoConf1 = 158733.333 is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - \text{AnoConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$   
 The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).  
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."  
 J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.  
 $A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.  
 $A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.  
 $\text{AnoConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

-----  
 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$   
 $p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $p_{sh2} ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$   
 $p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $p_{sh2} ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$   
 $s_1 = 100.00$   
 $s_2 = 250.00$   
 $f_{ywe1} = 781.25$   
 $f_{ywe2} = 781.25$   
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$

$y_1 = 0.00083886$   
 $sh_1 = 0.00268436$   
 $ft_1 = 314.5735$   
 $fy_1 = 262.1446$   
 $su_1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.13907892$

$su_1 = 0.4 * esu1_{nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered characteristic value  $fs_1 = fs_1/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with  $Es_1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.13907892$

$su_2 = 0.4 * esu2_{nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY:  $esu2_{nominal} = 0.08$ ,

For calculation of  $esu2_{nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered

characteristic value  $f_{s2} = f_{s2}/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, f_{y1}$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{s2} = (f_{s,jacket} \cdot A_{s1,com,jacket} + f_{s,core} \cdot A_{s1,com,core})/A_{s1,com} = 262.1446$

with  $E_{s2} = (E_{s,jacket} \cdot A_{s1,com,jacket} + E_{s,core} \cdot A_{s1,com,core})/A_{s1,com} = 200000.00$

$y_v = 0.00083886$

$sh_v = 0.00268436$

$ft_v = 314.5735$

$f_{y_v} = 262.1446$

$s_{u_v} = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.13907892$

$s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY:  $e_{s_{u_v,nominal}} = 0.08$ ,

considering characteristic value  $f_{s_{y_v}} = f_{s_{y_v}}/1.2$ , from table 5.1, TBDY

For calculation of  $e_{s_{u_v,nominal}}$  and  $y_v, sh_v, ft_v, f_{y_v}$ , it is considered

characteristic value  $f_{s_{y_v}} = f_{s_{y_v}}/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, f_{y1}$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{s_{y_v}} = (f_{s,jacket} \cdot A_{s1,mid,jacket} + f_{s,mid} \cdot A_{s1,mid,core})/A_{s1,mid} = 262.1446$

with  $E_{s_{y_v}} = (E_{s,jacket} \cdot A_{s1,mid,jacket} + E_{s,mid} \cdot A_{s1,mid,core})/A_{s1,mid} = 200000.00$

$1 = A_{s1,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.06824101$

$2 = A_{s1,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.03513975$

$v = A_{s1,mid}/(b \cdot d) \cdot (f_{s_{y_v}}/f_c) = 0.06202846$

and confined core properties:

$b = 340.00$

$d = 677.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 38.13135$

$cc (5A.5, TBDY) = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$1 = A_{s1,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.08384116$

$2 = A_{s1,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.04317283$

$v = A_{s1,mid}/(b \cdot d) \cdot (f_{s_{y_v}}/f_c) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$s_u (4.9) = 0.2584548$

$\mu_u = M_{Rc} (4.14) = 5.0296E+008$

$u = s_u (4.1) = 5.1201636E-006$

-----  
Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$d_b = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core})/Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y loxal axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392\text{E}+006$   
-----

Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392\text{E}+006$

$V_{r1} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{\text{Col}0}$

$V_{\text{Col}0} = 1.0392\text{E}+006$

$k_{nl} = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_{c\_jacket} * \text{Area}_{jacket} + f'_{c\_core} * \text{Area}_{core}) / \text{Area}_{section} = 30.00$ , but  $f'_c^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 * h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138\text{E}+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col_{j1} = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $Col_{j2} = 1.00$

$s/d = 0.3125$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col_{c1} = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $Col_{c2} = 0.00$

$s/d = 1.5625$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$bw = 400.00$   
-----

-----  
Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392\text{E}+006$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{\text{Col}0}$

$V_{\text{Col}0} = 1.0392\text{E}+006$

$k_{nl} = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 \cdot h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s\text{jacket}} + V_{s\text{core}} = 1.0138\text{E}+006$

where:

$V_{s\text{jacket}} = V_{s\text{j1}} + V_{s\text{j2}} = 903207.888$

$V_{s\text{j1}} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s\text{j1}}$  is multiplied by  $\text{Col,j1} = 1.00$

$s/d = 0.16666667$

$V_{s\text{j2}} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s\text{j2}}$  is multiplied by  $\text{Col,j2} = 1.00$

$s/d = 0.3125$

$V_{s\text{core}} = V_{s\text{c1}} + V_{s\text{c2}} = 110584.061$

$V_{s\text{c1}} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s\text{c1}}$  is multiplied by  $\text{Col,c1} = 1.00$

$s/d = 0.56818182$

$V_{s\text{c2}} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s\text{c2}}$  is multiplied by  $\text{Col,c2} = 0.00$

$s/d = 1.5625$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$bw = 400.00$

-----

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At local axis: 3

-----

Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjlc

Constant Properties

-----

Knowledge Factor,  $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

```

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$ 
New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$ 
Concrete Elasticity,  $E_c = 25742.96$ 
Steel Elasticity,  $E_s = 200000.00$ 
#####
Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$ 
Existing Column
New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$ 
#####
Max Height,  $H_{max} = 750.00$ 
Min Height,  $H_{min} = 400.00$ 
Max Width,  $W_{max} = 750.00$ 
Min Width,  $W_{min} = 400.00$ 
Jacket Thickness,  $t_j = 100.00$ 
Cover Thickness,  $c = 25.00$ 
Mean Confinement Factor overall section = 1.27105
Element Length,  $L = 3000.00$ 
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Lap Length  $l_o = 300.00$ 
No FRP Wrapping
-----

Stepwise Properties
-----
At local axis: 2
EDGE -A-
Shear Force,  $V_a = -0.0001715$ 
EDGE -B-
Shear Force,  $V_b = 0.0001715$ 
BOTH EDGES
Axial Force,  $F = -16273.608$ 
Longitudinal Reinforcement Area Distribution (in 2 divisions)
  -Tension:  $A_{sl,t} = 0.00$ 
  -Compression:  $A_{sl,c} = 5353.274$ 
Longitudinal Reinforcement Area Distribution (in 3 divisions)
  -Tension:  $A_{sl,ten} = 1137.257$ 
  -Compression:  $A_{sl,com} = 2208.54$ 
  -Middle:  $A_{sl,mid} = 2007.478$ 
-----
-----

Calculation of Shear Capacity ratio ,  $V_e/V_r = 0.32266369$ 
Member Controlled by Flexure ( $V_e/V_r < 1$ )
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$ 
with
 $M_{pr1} = \text{Max}(\mu_{u1+} , \mu_{u1-}) = 5.0296E+008$ 
 $\mu_{u1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{u1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{u2+} , \mu_{u2-}) = 5.0296E+008$ 
 $\mu_{u2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $\mu_{u2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination
-----

Calculation of  $\mu_{u1+}$ 
-----

```

Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 4.8099118E-006$$

$$\mu = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear\_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.01260361$$

$$\phi_{cc}(5.4c) = 0.05179731$$

$$\text{ase ((5.4d), TBDY) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.45746528}$$

$$\text{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1})/A_{conf,max1}) * (A_{conf,min1}/A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\text{ase2} (\geq \text{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\text{psh}_{min} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 3.3968$$

$$\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 3.3968$$

$$\text{psh}_1 \text{ ((5.4d), TBDY) = } L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y) = } 2060.00$$

$$A_{stir1} \text{ (stirrups area) = } 78.53982$$

$$\text{psh}_2 \text{ (5.4d) = } L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y) = } 1468.00$$

$$A_{stir2} \text{ (stirrups area) = } 50.26548$$

$$\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 3.3968$$

$$\text{psh}_1 \text{ ((5.4d), TBDY) = } L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X) = } 2060.00$$

$$A_{stir1} \text{ (stirrups area) = } 78.53982$$

$$\text{psh}_2 \text{ ((5.4d), TBDY) = } L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X) = } 1468.00$$

$$A_{stir2} \text{ (stirrups area) = } 50.26548$$

$$A_{sec} = 440000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $y1 = 0.00083886$   
 $sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/ld = 0.13907892$   
 $su1 = 0.4*esu1\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,  
 For calculation of  $esu1\_nominal$  and  $y1, sh1, ft1, fy1$ , it is considered  
 characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 262.1446$   
 with  $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$   
 $y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/lb,min = 0.13907892$   
 $su2 = 0.4*esu2\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu2\_nominal = 0.08$ ,  
 For calculation of  $esu2\_nominal$  and  $y2, sh2, ft2, fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 262.1446$   
 with  $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$   
 $yv = 0.00083886$   
 $shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/ld = 0.13907892$   
 $suv = 0.4*esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv, shv, ftv, fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 262.1446$   
 with  $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.0187412$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.03639521$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03308184$

and confined core properties:  
 $b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.02127357$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04131304$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_s, y_2$  - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.21062322$$

$$\mu = M_{Rc}(4.14) = 2.3387E+008$$

$$u = s_u(4.1) = 4.8099118E-006$$

-----  
Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \min(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \max(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $\mu_1$ -

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$\mu = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear\_factor} \cdot \max(\mu, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu = 0.01260361$$

$$\text{we (5.4c) } = 0.05179731$$

$$\text{ase ((5.4d), TBDY) } = (\text{ase1} \cdot A_{ext} + \text{ase2} \cdot A_{int}) / A_{sec} = 0.45746528$$

$$\text{ase1} = \max(((A_{conf, \max 1} - A_{noConf1}) / A_{conf, \max 1}) \cdot (A_{conf, \min 1} / A_{conf, \max 1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf, \max 1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf, \min 1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf, \max 1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\text{ase2 } (>= \text{ase1}) = \max(((A_{conf, \max 2} - A_{noConf2}) / A_{conf, \max 2}) \cdot (A_{conf, \min 2} / A_{conf, \max 2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/ld = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with  $Es1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$fy2 = 262.1446$

$su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 0.13907892$

$su2 = 0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu2_{nominal} = 0.08$ ,

For calculation of  $esu2_{nominal}$  and  $y2, sh2, ft2, fy2$ , it is considered characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $su_v = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lo_{min} = lb/ld = 0.13907892$   
 $su_v = 0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fs_v = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fs_v = fsv/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 262.1446$   
 with  $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$   
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.06824101$   
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.03513975$   
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.06202846$

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.08384116$   
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.04317283$   
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---

$su (4.9) = 0.2584548$

$Mu = MRc (4.14) = 5.0296E+008$

$u = su (4.1) = 5.1201636E-006$

Calculation of ratio  $lb/ld$

Lap Length:  $lb/ld = 0.13907892$

$lb = 300.00$

$ld = 2157.049$

Calculation of  $lb_{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld_{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$Ktr = 1.7174$

$Atr = Min(Atr_x, Atr_y) = 257.6106$

where  $Atr_x, Atr_y$  are the sum of the area of all stirrup legs along X and Y loxal axis

$s = Max(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

Calculation of  $Mu_{2+}$

Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 4.8099118E-006$$

$$Mu = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$co \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear\_factor} * \text{Max}(cu, cc) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01260361$$

$$we \text{ (5.4c)} = 0.05179731$$

$$ase \text{ ((5.4d), TBDY)} = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$ase2 (\geq ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$psh_{,min} * F_{ywe} = \text{Min}(psh_{,x} * F_{ywe}, psh_{,y} * F_{ywe}) = 3.3968$$

$$psh_{,x} * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$$

$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$psh_{,y} * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$$

$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00471045$$

$c = \text{confinement factor} = 1.27105$   
 $y1 = 0.00083886$   
 $sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou,min = lb/ld = 0.13907892$   
 $su1 = 0.4 * esu1\_nominal ((5.5), \text{TBDY}) = 0.032$   
 From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,  
 For calculation of  $esu1\_nominal$  and  $y1, sh1, ft1, fy1$ , it is considered  
 characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 262.1446$   
 with  $Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$   
 $y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou,min = lb/lb,min = 0.13907892$   
 $su2 = 0.4 * esu2\_nominal ((5.5), \text{TBDY}) = 0.032$   
 From table 5A.1, TBDY:  $esu2\_nominal = 0.08$ ,  
 For calculation of  $esu2\_nominal$  and  $y2, sh2, ft2, fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 262.1446$   
 with  $Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00$   
 $yv = 0.00083886$   
 $shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou,min = lb/ld = 0.13907892$   
 $suv = 0.4 * esuv\_nominal ((5.5), \text{TBDY}) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv, shv, ftv, fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 262.1446$   
 with  $Es_v = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$   
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.0187412$   
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.03639521$   
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.03308184$   
 and confined core properties:  
 $b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, \text{TBDY}) = 38.13135$   
 $cc (5A.5, \text{TBDY}) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.02127357$   
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.04131304$   
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.03755196$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < vs, y2$  - LHS eq.(4.5) is satisfied

--->  
 $s_u(4.9) = 0.21062322$   
 $\mu = MRc(4.14) = 2.3387E+008$   
 $u = s_u(4.1) = 4.8099118E-006$

---

Calculation of ratio  $l_b/l_d$

---

Lap Length:  $l_b/l_d = 0.13907892$   
 $l_b = 300.00$   
 $l_d = 2157.049$   
 Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$   
 Mean strength value of all re-bars:  $f_y = 781.25$   
 Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$   
 $e = 1.00$   
 $cb = 25.00$   
 $K_{tr} = 1.7174$   
 $A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$   
 where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{external}, s_{internal}) = 250.00$   
 $n = 24.00$

---

Calculation of  $\mu_2$

---

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:  
 $u = 5.1201636E-006$   
 $\mu = 5.0296E+008$

---

with full section properties:

$b = 400.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00191815$   
 $N = 16273.608$   
 $f_c = 30.00$   
 $co(5A.5, TBDY) = 0.002$   
 Final value of  $c_u$ :  $c_u = \text{shear\_factor} \cdot \text{Max}(c_u, c_c) = 0.01260361$   
 The Shear\_factor is considered equal to 1 (pure moment strength)  
 From (5.4b), TBDY:  $c_u = 0.01260361$   
 $w_e(5.4c) = 0.05179731$   
 $ase((5.4d), TBDY) = (ase1 \cdot A_{ext} + ase2 \cdot A_{int}) / A_{sec} = 0.45746528$   
 $ase1 = \text{Max}(((A_{conf, \max 1} - A_{noConf1}) / A_{conf, \max 1}) \cdot (A_{conf, \min 1} / A_{conf, \max 1}), 0) = 0.45746528$   
 The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).  
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."  
 J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.  
 $A_{conf, \max 1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.  
 $A_{conf, \min 1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf, \max 1}$  by a length equal to half the clear spacing between external hoops.  
 $A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase2 (\geq ase1) = \text{Max}(((A_{conf, \max 2} - A_{noConf2}) / A_{conf, \max 2}) \cdot (A_{conf, \min 2} / A_{conf, \max 2}), 0) = 0.45746528$   
 The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).  
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.  
 $A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$   
 $s1 = 100.00$   
 $s2 = 250.00$   
 $f_{ywe1} = 781.25$   
 $f_{ywe2} = 781.25$   
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$   
 $sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/ld = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 0.13907892$

$su2 = 0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu2_{nominal} = 0.08$ ,

For calculation of  $esu2_{nominal}$  and  $y2, sh2, ft2, fy2$ , it is considered characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.00083886$

$shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lo,min = lb/ld = 0.13907892$   
 $suv = 0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv$ ,  $shv,ftv,fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1,ft1,fy1$ , are also multiplied by  $Min(1,1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 262.1446$   
 with  $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.06824101$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.03513975$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.06202846$

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.08384116$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04317283$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---

$v < vs,y2$  - LHS eq.(4.5) is satisfied

---

$su (4.9) = 0.2584548$   
 $Mu = MRc (4.14) = 5.0296E+008$   
 $u = su (4.1) = 5.1201636E-006$

-----  
 Calculation of ratio  $lb/ld$   
 -----

Lap Length:  $lb/ld = 0.13907892$

$lb = 300.00$

$ld = 2157.049$

Calculation of  $lb,min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld,min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$   
 $db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $fc' = (fc'_jacket*Area\_jacket + fc'_core*Area\_core)/Area\_section = 30.00$ , but  $fc'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$Ktr = 1.7174$

$Atr = Min(Atr\_x,Atr\_y) = 257.6106$

where  $Atr\_x, Atr\_y$  are the sum of the area of all stirrup legs along X and Y local axis

$s = Max(s\_external,s\_internal) = 250.00$

$n = 24.00$   
 -----  
 -----  
 -----

Calculation of Shear Strength  $Vr = Min(Vr1,Vr2) = 1.0392E+006$   
 -----

Calculation of Shear Strength at edge 1,  $Vr1 = 1.0392E+006$

Vr1 = VCol ((10.3), ASCE 41-17) = knl\*VColO

VColO = 1.0392E+006

kn1 = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av\*fy\*d/s' is replaced by 'Vs+ f\*Vf'  
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 1308.675

Vu = 0.0001715

d = 0.8\*h = 600.00

Nu = 16273.608

Ag = 300000.00

From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 1.0138E+006

where:

Vs,jacket = Vs,j1 + Vs,j2 = 903207.888

Vs,j1 = 314159.265 is calculated for section web jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.3125

Vs,j2 = 589048.623 is calculated for section flange jacket, with:

d = 600.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.16666667

Vs,core = Vs,c1 + Vs,c2 = 110584.061

Vs,c1 = 0.00 is calculated for section web core, with:

d = 160.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 0.00

s/d = 1.5625

Vs,c2 = 110584.061 is calculated for section flange core, with:

d = 440.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 1.00

s/d = 0.56818182

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 873250.061

bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 1.0392E+006

Vr2 = VCol ((10.3), ASCE 41-17) = knl\*VColO

VColO = 1.0392E+006

kn1 = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av\*fy\*d/s' is replaced by 'Vs+ f\*Vf'  
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 1308.675

Vu = 0.0001715

d = 0.8\*h = 600.00  
Nu = 16273.608  
Ag = 300000.00  
From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$   
where:  
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$   
 $V_{s,j1} = 314159.265$  is calculated for section web jacket, with:  
d = 320.00  
Av = 157079.633  
fy = 625.00  
s = 100.00  
 $V_{s,j1}$  is multiplied by Col,j1 = 1.00  
s/d = 0.3125  
 $V_{s,j2} = 589048.623$  is calculated for section flange jacket, with:  
d = 600.00  
Av = 157079.633  
fy = 625.00  
s = 100.00  
 $V_{s,j2}$  is multiplied by Col,j2 = 1.00  
s/d = 0.16666667  
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$   
 $V_{s,c1} = 0.00$  is calculated for section web core, with:  
d = 160.00  
Av = 100530.965  
fy = 625.00  
s = 250.00  
 $V_{s,c1}$  is multiplied by Col,c1 = 0.00  
s/d = 1.5625  
 $V_{s,c2} = 110584.061$  is calculated for section flange core, with:  
d = 440.00  
Av = 100530.965  
fy = 625.00  
s = 250.00  
 $V_{s,c2}$  is multiplied by Col,c2 = 1.00  
s/d = 0.56818182  
Vf ((11-3)-(11.4), ACI 440) = 0.00  
From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
bw = 400.00

-----  
End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 2  
-----

Start Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1  
At local axis: 3  
Integration Section: (b)  
Section Type: rcjlcs

Constant Properties

-----  
Knowledge Factor, = 1.00  
Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.  
Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17  
Consequently:  
Jacket  
New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
Concrete Elasticity,  $E_c = 25742.96$   
Steel Elasticity,  $E_s = 200000.00$   
Existing Column  
New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
Concrete Elasticity,  $E_c = 25742.96$   
Steel Elasticity,  $E_s = 200000.00$

Max Height, Hmax = 750.00  
Min Height, Hmin = 400.00  
Max Width, Wmax = 750.00  
Min Width, Wmin = 400.00  
Jacket Thickness, tj = 100.00  
Cover Thickness, c = 25.00  
Element Length, L = 3000.00  
Primary Member  
Smooth Bars  
Ductile Steel  
With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
Longitudinal Bars With Ends Lapped Starting at the End Sections  
Lap Length lb = 300.00  
No FRP Wrapping

-----  
Stepwise Properties  
-----

Bending Moment, M = 186273.79  
Shear Force, V2 = 4846.489  
Shear Force, V3 = -135.9404  
Axial Force, F = -17232.621  
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension: Aslt = 0.00  
-Compression: Aslc = 5353.274  
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension: Asl,ten = 1137.257  
-Compression: Asl,com = 2208.54  
-Middle: Asl,mid = 2007.478  
Longitudinal External Reinforcement Area Distribution (in 3 divisions)  
-Tension: Asl,ten,jacket = 829.3805  
-Compression: Asl,com,jacket = 1746.726  
-Middle: Asl,mid,jacket = 1545.664  
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)  
-Tension: Asl,ten,core = 307.8761  
-Compression: Asl,com,core = 461.8141  
-Middle: Asl,mid,core = 461.8141  
Mean Diameter of Tension Reinforcement, DbL = 16.80  
-----  
-----

New component: From table 7-7, ASCE 41\_17: Final chord rotation Capacity  $u_{,R} = 1.0^*$   $u = 0.00019707$   
 $u = y + p = 0.00019707$

-----  
- Calculation of  $y$  -  
-----

$y = (M_y * L_s / 3) / E_{eff} = 0.00019707$  ((4.29), Biskinis Phd)  
 $M_y = 2.8693E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 300.00  
From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
factor = 0.30  
 $A_g = 440000.00$   
Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17232.621$   
 $E_c * I_g = E_c * I_{g,jacket} + E_c * I_{g,core} = 4.8532E+014$   
-----  
-----

Calculation of Yielding Moment  $M_y$   
-----

Calculation of  $y$  and  $M_y$  according to Annex 7 -  
-----

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:  
flange width, b = 750.00  
web width, bw = 400.00

flange thickness,  $t = 400.00$

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 2.1452649\text{E}-006$$

$$\text{with } ((10.1), \text{ASCE 41-17}) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 243.3535$$

$$d = 707.00$$

$$y = 0.1977546$$

$$A = 0.0102293$$

$$B = 0.00453971$$

$$\text{with } p_t = 0.00434791$$

$$p_c = 0.00416509$$

$$p_v = 0.00378591$$

$$N = 17232.621$$

$$b = 750.00$$

$$" = 0.06082037$$

$$y_{\text{comp}} = 1.5203329\text{E}-005$$

$$\text{with } f_c = 30.00$$

$$E_c = 25742.96$$

$$y = 0.19515388$$

$$A = 0.01001829$$

$$B = 0.00440616$$

$$\text{with } E_s = 200000.00$$

$$\text{CONFIRMATION: } y = 0.19591085 < t/d$$

Calculation of ratio  $l_b/l_d$

$$\text{Lap Length: } l_d/l_d, \text{min} = 0.17384865$$

$$l_b = 300.00$$

$$l_d = 1725.639$$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \text{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

$$= 1$$

$$d_b = 16.66667$$

$$\text{Mean strength value of all re-bars: } f_y = 625.00$$

$$\text{Mean concrete strength: } f'_c = (f'_c \cdot \text{jacket} \cdot \text{Area}_{\text{jacket}} + f'_c \cdot \text{core} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00, \text{ but } f'_c^{0.5} \leq 8.3$$

MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

- Calculation of  $p$  -

From table 10-8:  $p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because  $l_b/l_d < 1$

$$\text{shear control ratio } V_y E / V_{col} O E = 0.32266369$$

$$d = d_{\text{external}} = 707.00$$

$$s = s_{\text{external}} = 0.00$$

$$- t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00434791$$

$$\text{jacket: } s_1 = A_{v1} \cdot L_{\text{stir}1} / (s_1 \cdot A_g) = 0.00367709$$

$A_{v1} = 78.53982$ , is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir}1} = 2060.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$$s_1 = 100.00$$

$$\text{core: } s_2 = A_{v2} \cdot L_{\text{stir}2} / (s_2 \cdot A_g) = 0.00067082$$

$A_{v2} = 50.26548$ , is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir}2} = 1468.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$$s_2 = 250.00$$

The term  $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$  is implemented to account for FRP contribution

where  $f = 2 \cdot t_f / b_w$  is FRP ratio (EC8 - 3, A.4.4.3(6)) and  $f_{fe} / f_s$  normalises  $f$  to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation  $f_s$  of jacket is used.

$$N_{UD} = 17232.621$$

$$A_g = 440000.00$$

$$f_{cE} = (f_{c\_jacket} \cdot Area\_jacket + f_{c\_core} \cdot Area\_core) / section\_area = 30.00$$

$$f_{yE} = (f_{y\_ext\_Long\_Reinf} \cdot Area\_ext\_Long\_Reinf + f_{y\_int\_Long\_Reinf} \cdot Area\_int\_Long\_Reinf) / Area\_Tot\_Long\_Rein = 625.00$$

$$f_{yE} = (f_{y\_ext\_Trans\_Reinf} \cdot s_1 + f_{y\_int\_Trans\_Reinf} \cdot s_2) / (s_1 + s_2) = 625.00$$

$$p_l = Area\_Tot\_Long\_Rein / (b \cdot d) = 0.01009575$$

$$b = 750.00$$

$$d = 707.00$$

$$f_{cE} = 30.00$$

-----  
End Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (b)

-----

## Calculation No. 9

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity  $V_{Rd}$

Edge: Start

Local Axis: (2)



-----  
Start Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjlc

Constant Properties

-----

Knowledge Factor,  $\gamma = 1.00$   
Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.  
Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17  
Consequently:  
Jacket  
New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$   
New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$   
Concrete Elasticity,  $E_c = 25742.96$   
Steel Elasticity,  $E_s = 200000.00$   
Existing Column  
New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$   
New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$   
Concrete Elasticity,  $E_c = 25742.96$   
Steel Elasticity,  $E_s = 200000.00$   
#####  
Note: Especially for the calculation of  $\gamma$  for displacement ductility demand,  
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as  
Deformation-Controlled Action (Table C7-1, ASCE 41-17).  
Jacket  
New material: Concrete Strength,  $f_c = f_{cm} = 30.00$   
New material: Steel Strength,  $f_s = f_{sm} = 625.00$   
Existing Column  
New material: Concrete Strength,  $f_c = f_{cm} = 30.00$   
New material: Steel Strength,  $f_s = f_{sm} = 625.00$   
#####  
Max Height,  $H_{max} = 750.00$   
Min Height,  $H_{min} = 400.00$   
Max Width,  $W_{max} = 750.00$   
Min Width,  $W_{min} = 400.00$   
Jacket Thickness,  $t_j = 100.00$   
Cover Thickness,  $c = 25.00$   
Element Length,  $L = 3000.00$   
Primary Member  
Smooth Bars  
Ductile Steel  
With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
Longitudinal Bars With Ends Lapped Starting at the End Sections  
Lap Length  $l_o = l_b = 300.00$   
No FRP Wrapping

-----  
Stepwise Properties  
-----

EDGE -A-  
Bending Moment,  $M_a = -2.3128E+007$   
Shear Force,  $V_a = -7609.421$   
EDGE -B-  
Bending Moment,  $M_b = 293212.583$   
Shear Force,  $V_b = 7609.421$   
BOTH EDGES  
Axial Force,  $F = -17779.344$   
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension:  $A_{st} = 0.00$   
-Compression:  $A_{sc} = 5353.274$   
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension:  $A_{st,ten} = 1137.257$   
-Compression:  $A_{sc,com} = 2208.54$   
-Middle:  $A_{st,mid} = 2007.478$   
Mean Diameter of Tension Reinforcement,  $Db_{L,ten} = 16.80$   
-----  
-----

New component: From table 7-7, ASCE 41-17: Final Shear Capacity  $V_R = 1.0 * V_n = 848936.076$   
 $V_n$  ((10.3), ASCE 41-17) =  $k_n l * V_{CoIO} = 848936.076$   
 $V_{CoI} = 848936.076$   
 $k_n l = 1.00$

displacement\_ductility\_demand = 0.04334623

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 20.00$ , but  $f_c'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 2.3128E+007$

$V_u = 7609.421$

$d = 0.8 \cdot h = 600.00$

$N_u = 17779.344$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 811033.559$

where:

$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 722566.31$

$V_{s,j1} = 251327.412$  is calculated for section web jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $\text{Col},j1 = 1.00$

$s/d = 0.3125$

$V_{s,j2} = 471238.898$  is calculated for section flange jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $\text{Col},j2 = 1.00$

$s/d = 0.16666667$

$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 88467.249$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 500.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $\text{Col},c1 = 0.00$

$s/d = 1.5625$

$V_{s,c2} = 88467.249$  is calculated for section flange core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 500.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $\text{Col},c2 = 1.00$

$s/d = 0.56818182$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 713005.69$

$b_w = 400.00$

displacement\_ductility\_demand is calculated as  $\phi / y$

- Calculation of  $\phi / y$  for END A -  
for rotation axis 3 and integ. section (a)

From analysis, chord rotation  $\theta = 8.6592743E-005$

$y = (M_y \cdot L_s / 3) / \text{Eleff} = 0.0019977$  ((4.29), Biskinis Phd)

$M_y = 2.8709E+008$

$L_s = M/V$  (with  $L_s > 0.1 \cdot L$  and  $L_s < 2 \cdot L$ ) = 3039.351

From table 10.5, ASCE 41\_17:  $\text{Eleff} = \text{factor} \cdot E_c \cdot I_g = 1.4560E+014$

factor = 0.30

$A_g = 440000.00$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$

$N = 17779.344$

$E_c \cdot I_g = E_{c,\text{jacket}} \cdot I_{g,\text{jacket}} + E_{c,\text{core}} \cdot I_{g,\text{core}} = 4.8532E+014$

Calculation of Yielding Moment  $M_y$

Calculation of  $y$  and  $M_y$  according to Annex 7 -

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$

web width,  $b_w = 400.00$

flange thickness,  $t = 400.00$

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$

$y_{\text{ten}} = 2.1455196\text{E-}006$

with  $((10.1), \text{ASCE } 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 243.3535$

$d = 707.00$

$y = 0.19784983$

$A = 0.01023354$

$B = 0.00454395$

with  $p_t = 0.00214476$

$p_c = 0.00416509$

$p_v = 0.00378591$

$N = 17779.344$

$b = 750.00$

" = 0.06082037

$y_{\text{comp}} = 1.5202265\text{E-}005$

with  $f_c = 30.00$

$E_c = 25742.96$

$y = 0.19516753$

$A = 0.01001583$

$B = 0.00440616$

with  $E_s = 200000.00$

CONFIRMATION:  $y = 0.19594836 < t/d$

Calculation of ratio  $l_b/d$

Lap Length:  $l_d/l_{d,\text{min}} = 0.17384865$

$l_b = 300.00$

$l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,\text{min}}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f'_c = (f'_{c,\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f'_{c,\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c^{0.5} \leq 8.3$

MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

End Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (a)

## Calculation No. 10

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (  $\theta$  )

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjlcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$   
Cover Thickness,  $c = 25.00$   
Mean Confinement Factor overall section = 1.27105  
Element Length,  $L = 3000.00$   
Primary Member  
Smooth Bars  
Ductile Steel  
With Detailing for Earthquake Resistance (including stirrups closed at  $135^\circ$ )  
Longitudinal Bars With Ends Lapped Starting at the End Sections  
Lap Length  $l_o = 300.00$   
No FRP Wrapping

-----  
Stepwise Properties  
-----

At local axis: 3  
EDGE -A-  
Shear Force,  $V_a = -0.00017144$   
EDGE -B-  
Shear Force,  $V_b = 0.00017144$   
BOTH EDGES  
Axial Force,  $F = -16273.608$   
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension:  $As_t = 0.00$   
-Compression:  $As_c = 5353.274$   
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension:  $As_{t,ten} = 1137.257$   
-Compression:  $As_{c,com} = 2208.54$   
-Middle:  $As_{c,mid} = 2007.478$

-----  
-----  
Calculation of Shear Capacity ratio,  $V_e/V_r = 0.32266369$   
Member Controlled by Flexure ( $V_e/V_r < 1$ )  
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$   
with  
 $M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 5.0296E+008$   
 $Mu_{1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination  
 $Mu_{1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination  
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 5.0296E+008$   
 $Mu_{2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination  
 $Mu_{2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

-----  
Calculation of  $Mu_{1+}$   
-----

-----  
Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:  
 $\phi_u = 4.8099118E-006$   
 $Mu = 2.3387E+008$

-----  
with full section properties:

$b = 750.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00102301$   
 $N = 16273.608$   
 $f_c = 30.00$   
 $\omega (5A.5, TBDY) = 0.002$   
Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} * \text{Max}(\phi_u, \phi_c) = 0.01260361$   
The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $c_u = 0.01260361$

$w_e$  (5.4c) = 0.05179731

$a_{se}$  ((5.4d), TBDY) =  $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

-----  
 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $c_c = 0.00471045$

$c$  = confinement factor = 1.27105

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

$l_o / l_{ou,min} = l_b / l_d = 0.13907892$

$su1 = 0.4 * e_{su1,nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $e_{su1,nominal} = 0.08$ ,

For calculation of  $e_{su1,nominal}$  and  $y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , it is considered characteristic value  $f_{sy1} = f_{s1} / 1.2$ , from table 5.1, TBDY.

$y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 262.1446$   
 $with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$   
 $y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/lb,min = 0.13907892$   
 $su2 = 0.4*esu2,nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu2,nominal = 0.08$ ,  
 For calculation of  $esu2,nominal$  and  $y2, sh2,ft2,fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1,ft1,fy1$ , are also multiplied by  $Min(1,1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 $with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 262.1446$   
 $with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$   
 $yv = 0.00083886$   
 $shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/l_d = 0.13907892$   
 $suv = 0.4*esuv,nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv,nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv,nominal$  and  $yv, shv,ftv,fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1,ft1,fy1$ , are also multiplied by  $Min(1,1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 $with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 262.1446$   
 $with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.0187412$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.03639521$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03308184$

and confined core properties:

$b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.02127357$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04131304$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < vs,y2$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.21062322$   
 $Mu = MRc (4.14) = 2.3387E+008$   
 $u = su (4.1) = 4.8099118E-006$

-----  
 Calculation of ratio  $lb/l_d$   
 -----

Lap Length:  $lb/l_d = 0.13907892$   
 $lb = 300.00$   
 $l_d = 2157.049$   
 Calculation of  $lb,min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_d,min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$   
Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
-----  
-----  
Calculation of  $\mu_1$ -  
-----

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.1201636E-006$$

$$\mu_u = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$\alpha (5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \mu_u: \mu_u^* = \text{shear\_factor} \cdot \text{Max}(\mu_u, \mu_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_u = 0.01260361$$

$$\mu_c \text{ (5.4c)} = 0.05179731$$

$$\alpha_{se} \text{ ((5.4d), TBDY)} = (\alpha_{se1} \cdot A_{ext} + \alpha_{se2} \cdot A_{int}) / A_{sec} = 0.45746528$$

$$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) \cdot (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\alpha_{se2} (> \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) \cdot (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} \cdot F_{ywe} = \text{Min}(p_{sh,x} \cdot F_{ywe}, p_{sh,y} \cdot F_{ywe}) = 3.3968$$

$$p_{sh_x} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} \cdot A_{stir1} / (A_{sec} \cdot s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} \cdot A_{stir2} / (A_{sec} \cdot s2) = 0.00067082$$

Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

psh<sub>y</sub>\*Fywe = psh<sub>1</sub>\*Fywe<sub>1</sub>+ps<sub>2</sub>\*Fywe<sub>2</sub> = 3.3968  
psh<sub>1</sub> ((5.4d), TBDY) = Lstir<sub>1</sub>\*Astir<sub>1</sub>/(Asec\*s<sub>1</sub>) = 0.00367709  
Lstir<sub>1</sub> (Length of stirrups along X) = 2060.00  
Astir<sub>1</sub> (stirrups area) = 78.53982  
psh<sub>2</sub> ((5.4d), TBDY) = Lstir<sub>2</sub>\*Astir<sub>2</sub>/(Asec\*s<sub>2</sub>) = 0.00067082  
Lstir<sub>2</sub> (Length of stirrups along X) = 1468.00  
Astir<sub>2</sub> (stirrups area) = 50.26548

Asec = 440000.00  
s<sub>1</sub> = 100.00  
s<sub>2</sub> = 250.00

fywe<sub>1</sub> = 781.25  
fywe<sub>2</sub> = 781.25  
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y<sub>1</sub> = 0.00083886  
sh<sub>1</sub> = 0.00268436  
ft<sub>1</sub> = 314.5735  
fy<sub>1</sub> = 262.1446  
su<sub>1</sub> = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>d</sub> = 0.13907892

su<sub>1</sub> = 0.4\*esu<sub>1\_nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu<sub>1\_nominal</sub> = 0.08,

For calculation of esu<sub>1\_nominal</sub> and y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, it is considered  
characteristic value fsy<sub>1</sub> = fs<sub>1</sub>/1.2, from table 5.1, TBDY.

y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>1</sub> = (fs<sub>jacket</sub>\*Asl<sub>ten,jacket</sub> + fs<sub>core</sub>\*Asl<sub>ten,core</sub>)/Asl<sub>ten</sub> = 262.1446

with Es<sub>1</sub> = (Es<sub>jacket</sub>\*Asl<sub>ten,jacket</sub> + Es<sub>core</sub>\*Asl<sub>ten,core</sub>)/Asl<sub>ten</sub> = 200000.00

y<sub>2</sub> = 0.00083886  
sh<sub>2</sub> = 0.00268436

ft<sub>2</sub> = 314.5735  
fy<sub>2</sub> = 262.1446

su<sub>2</sub> = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>b,min</sub> = 0.13907892

su<sub>2</sub> = 0.4\*esu<sub>2\_nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu<sub>2\_nominal</sub> = 0.08,

For calculation of esu<sub>2\_nominal</sub> and y<sub>2</sub>, sh<sub>2</sub>,ft<sub>2</sub>,fy<sub>2</sub>, it is considered  
characteristic value fsy<sub>2</sub> = fs<sub>2</sub>/1.2, from table 5.1, TBDY.

y<sub>2</sub>, sh<sub>2</sub>,ft<sub>2</sub>,fy<sub>2</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>2</sub> = (fs<sub>jacket</sub>\*Asl<sub>com,jacket</sub> + fs<sub>core</sub>\*Asl<sub>com,core</sub>)/Asl<sub>com</sub> = 262.1446

with Es<sub>2</sub> = (Es<sub>jacket</sub>\*Asl<sub>com,jacket</sub> + Es<sub>core</sub>\*Asl<sub>com,core</sub>)/Asl<sub>com</sub> = 200000.00

y<sub>v</sub> = 0.00083886  
sh<sub>v</sub> = 0.00268436

ft<sub>v</sub> = 314.5735  
fy<sub>v</sub> = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>d</sub> = 0.13907892

suv = 0.4\*esuv<sub>nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv<sub>nominal</sub> = 0.08,

considering characteristic value fsy<sub>v</sub> = fs<sub>v</sub>/1.2, from table 5.1, TBDY  
For calculation of esuv<sub>nominal</sub> and y<sub>v</sub>, sh<sub>v</sub>,ft<sub>v</sub>,fy<sub>v</sub>, it is considered

characteristic value fsy<sub>v</sub> = fs<sub>v</sub>/1.2, from table 5.1, TBDY.

y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>v</sub> = (fs<sub>jacket</sub>\*Asl<sub>mid,jacket</sub> + fs<sub>mid</sub>\*Asl<sub>mid,core</sub>)/Asl<sub>mid</sub> = 262.1446

$$\text{with } E_{sv} = (E_{s,jacket} \cdot A_{sl,mid,jacket} + E_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.06824101$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03513975$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.06202846$$

and confined core properties:

$$b = 340.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 38.13135$$

$$c_c (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08384116$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04317283$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.07620839$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.2584548$$

$$\mu_u = M_{Rc} (4.14) = 5.0296E+008$$

$$u = s_u (4.1) = 5.1201636E-006$$

-----  
Calculation of ratio  $l_b/d$

-----  
Lap Length:  $l_b/d = 0.13907892$

$$l_b = 300.00$$

$$d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_b, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot \text{Area}_{jacket} + f_c'_{core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y loxal axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $\mu_{u2+}$

-----  
Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 4.8099118E-006$$

$$\mu_u = 2.3387E+008$$

-----  
with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} \cdot \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e (5.4c) = 0.05179731$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From } ((5.A.5), TBDY), TBDY: c_c = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$y1 = 0.00083886$$

$$sh1 = 0.00268436$$

$$ft1 = 314.5735$$

$$fy1 = 262.1446$$

$$su1 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$$l_o / l_{ou,min} = l_b / l_d = 0.13907892$$

$$su1 = 0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , it is considered

characteristic value  $fsy1 = fs1 / 1.2$ , from table 5.1, TBDY.

$y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$$

with  $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$   
 $y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_0/l_{ou,min} = l_b/l_{b,min} = 0.13907892$   
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{2,nominal} = 0.08$ ,  
 For calculation of  $esu_{2,nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
 characteristic value  $fs_2 = fs_2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_2 = (fs_{jacket} \cdot A_{s,com,jacket} + fs_{core} \cdot A_{s,com,core}) / A_{s,com} = 262.1446$   
 with  $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_0/l_{ou,min} = l_b/l_d = 0.13907892$   
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv_{nominal} = 0.08$ ,  
 considering characteristic value  $fs_v = fs_v/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv_{nominal}$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fs_v = fs_v/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_v = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 262.1446$   
 with  $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$   
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.0187412$   
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.03639521$   
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / fc) = 0.03308184$

and confined core properties:

$b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.02127357$   
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.04131304$   
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / fc) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_s, y_2$  - LHS eq.(4.5) is satisfied

---->

$su (4.9) = 0.21062322$   
 $M_u = MR_c (4.14) = 2.3387E+008$   
 $u = su (4.1) = 4.8099118E-006$

-----  
 Calculation of ratio  $l_b/l_d$

-----  
 Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $fc' = (fc'_{jacket} \cdot Area_{jacket} + fc'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
-----  
-----  
Calculation of  $\mu_2$ -  
-----

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.1201636E-006$$

$$\mu_2 = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$fc = 30.00$$

$$cc \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear\_factor} \cdot \text{Max}(\mu, cc) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu = 0.01260361$$

$$\text{we (5.4c)} = 0.05179731$$

$$\text{ase ((5.4d), TBDY)} = (\text{ase1} \cdot A_{ext} + \text{ase2} \cdot A_{int}) / A_{sec} = 0.45746528$$

$$\text{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) \cdot (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\text{ase2} (\geq \text{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) \cdot (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\text{psh,min} \cdot F_{ywe} = \text{Min}(\text{psh}_x \cdot F_{ywe}, \text{psh}_y \cdot F_{ywe}) = 3.3968$$

$$\text{psh}_x \cdot F_{ywe} = \text{psh}_1 \cdot F_{ywe1} + \text{ps}_2 \cdot F_{ywe2} = 3.3968$$

$$\text{psh}_1 \text{ ((5.4d), TBDY)} = L_{stir1} \cdot A_{stir1} / (A_{sec} \cdot s_1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$\text{psh}_2 \text{ (5.4d)} = L_{stir2} \cdot A_{stir2} / (A_{sec} \cdot s_2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$\text{Astir2 (stirrups area)} = 50.26548$$

$$\text{psh}_y * \text{Fywe} = \text{psh}_1 * \text{Fywe}_1 + \text{ps}_2 * \text{Fywe}_2 = 3.3968$$

$$\text{psh}_1 ((5.4d), \text{TBDY}) = \text{Lstir}_1 * \text{Astir}_1 / (\text{Asec} * \text{s}_1) = 0.00367709$$

$$\text{Lstir}_1 (\text{Length of stirrups along X}) = 2060.00$$

$$\text{Astir}_1 (\text{stirrups area}) = 78.53982$$

$$\text{psh}_2 ((5.4d), \text{TBDY}) = \text{Lstir}_2 * \text{Astir}_2 / (\text{Asec} * \text{s}_2) = 0.00067082$$

$$\text{Lstir}_2 (\text{Length of stirrups along X}) = 1468.00$$

$$\text{Astir}_2 (\text{stirrups area}) = 50.26548$$

$$\text{Asec} = 440000.00$$

$$\text{s}_1 = 100.00$$

$$\text{s}_2 = 250.00$$

$$\text{fywe}_1 = 781.25$$

$$\text{fywe}_2 = 781.25$$

$$\text{fce} = 30.00$$

$$\text{From } ((5.A5), \text{TBDY}), \text{TBDY: } \text{cc} = 0.00471045$$

$$\text{c} = \text{confinement factor} = 1.27105$$

$$\text{y}_1 = 0.00083886$$

$$\text{sh}_1 = 0.00268436$$

$$\text{ft}_1 = 314.5735$$

$$\text{fy}_1 = 262.1446$$

$$\text{su}_1 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$\text{lo/lo, min} = \text{lb/ld} = 0.13907892$$

$$\text{su}_1 = 0.4 * \text{esu}_1 \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esu}_1 \text{ nominal} = 0.08,$$

For calculation of esu1\_nominal and y1, sh1, ft1, fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$\text{y}_1, \text{sh}_1, \text{ft}_1, \text{fy}_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_1 = (\text{fs}_{\text{jacket}} * \text{Asl}_{\text{ten, jacket}} + \text{fs}_{\text{core}} * \text{Asl}_{\text{ten, core}}) / \text{Asl}_{\text{ten}} = 262.1446$$

$$\text{with } \text{Es}_1 = (\text{Es}_{\text{jacket}} * \text{Asl}_{\text{ten, jacket}} + \text{Es}_{\text{core}} * \text{Asl}_{\text{ten, core}}) / \text{Asl}_{\text{ten}} = 200000.00$$

$$\text{y}_2 = 0.00083886$$

$$\text{sh}_2 = 0.00268436$$

$$\text{ft}_2 = 314.5735$$

$$\text{fy}_2 = 262.1446$$

$$\text{su}_2 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$\text{lo/lo, min} = \text{lb/lb, min} = 0.13907892$$

$$\text{su}_2 = 0.4 * \text{esu}_2 \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esu}_2 \text{ nominal} = 0.08,$$

For calculation of esu2\_nominal and y2, sh2, ft2, fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$$\text{y}_2, \text{sh}_2, \text{ft}_2, \text{fy}_2, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_2 = (\text{fs}_{\text{jacket}} * \text{Asl}_{\text{com, jacket}} + \text{fs}_{\text{core}} * \text{Asl}_{\text{com, core}}) / \text{Asl}_{\text{com}} = 262.1446$$

$$\text{with } \text{Es}_2 = (\text{Es}_{\text{jacket}} * \text{Asl}_{\text{com, jacket}} + \text{Es}_{\text{core}} * \text{Asl}_{\text{com, core}}) / \text{Asl}_{\text{com}} = 200000.00$$

$$\text{y}_v = 0.00083886$$

$$\text{sh}_v = 0.00268436$$

$$\text{ft}_v = 314.5735$$

$$\text{fy}_v = 262.1446$$

$$\text{suv} = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$\text{lo/lo, min} = \text{lb/ld} = 0.13907892$$

$$\text{suv} = 0.4 * \text{esuv}_v \text{ nominal } ((5.5), \text{TBDY}) = 0.032$$

$$\text{From table 5A.1, TBDY: } \text{esuv}_v \text{ nominal} = 0.08,$$

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv, ftv, fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

$$\text{y}_v, \text{sh}_v, \text{ft}_v, \text{fy}_v, \text{ are also multiplied by } \text{Min}(1, 1.25 * (\text{lb/ld})^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } \text{fs}_v = (\text{fs}_{\text{jacket}} * \text{Asl}_{\text{mid, jacket}} + \text{fs}_{\text{mid}} * \text{Asl}_{\text{mid, core}}) / \text{Asl}_{\text{mid}} = 262.1446$$

$$\text{with } \text{Es}_v = (\text{Es}_{\text{jacket}} * \text{Asl}_{\text{mid, jacket}} + \text{Es}_{\text{mid}} * \text{Asl}_{\text{mid, core}}) / \text{Asl}_{\text{mid}} = 200000.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.06824101$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.03513975$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.06202846$$

and confined core properties:

$$b = 340.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 38.13135$$

$$c_c (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.08384116$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04317283$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.07620839$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.2584548$$

$$\mu_u = M R_c (4.14) = 5.0296E+008$$

$$u = s_u (4.1) = 5.1201636E-006$$

Calculation of ratio  $l_b/d$

Lap Length:  $l_b/d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y loxal axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} * V_{Col0}$$

$$V_{Col0} = 1.0392E+006$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '

where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 1308.016$$

$$V_u = 0.00017144$$

$$d = 0.8 * h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$

$s/d = 0.3125$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$

$s/d = 1.5625$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$bw = 400.00$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$

$V_{r2} = V_{Col}$  ((10.3), ASCE 41-17) =  $k_{nl} * V_{Col0}$

$V_{Col0} = 1.0392E+006$

$k_{nl} = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f'_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 * h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$   
 $s = 100.00$   
 $V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$   
 $s/d = 0.3125$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$   
 $V_{s,c1} = 110584.061$  is calculated for section web core, with:  
 $d = 440.00$   
 $A_v = 100530.965$   
 $f_y = 625.00$   
 $s = 250.00$   
 $V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$   
 $s/d = 0.56818182$   
 $V_{s,c2} = 0.00$  is calculated for section flange core, with:  
 $d = 160.00$   
 $A_v = 100530.965$   
 $f_y = 625.00$   
 $s = 250.00$   
 $V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$   
 $s/d = 1.5625$   
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$   
 From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
 $bw = 400.00$

-----  
 End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
 At local axis: 3  
 -----

Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
 At Shear local axis: 2  
 (Bending local axis: 3)  
 Section Type: rcjcs

Constant Properties

-----  
 Knowledge Factor,  $\gamma = 1.00$   
 Mean strength values are used for both shear and moment calculations.  
 Consequently:  
 Jacket  
 New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$

Existing Column  
 New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$

#####  
 Note: Especially for the calculation of moment strengths,  
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket  
 New material: Steel Strength,  $f_s = 1.25 * f_{sm} = 781.25$   
 Existing Column  
 New material: Steel Strength,  $f_s = 1.25 * f_{sm} = 781.25$   
 #####

Max Height,  $H_{max} = 750.00$   
 Min Height,  $H_{min} = 400.00$   
 Max Width,  $W_{max} = 750.00$   
 Min Width,  $W_{min} = 400.00$   
 Jacket Thickness,  $t_j = 100.00$   
 Cover Thickness,  $c = 25.00$   
 Mean Confinement Factor overall section = 1.27105  
 Element Length,  $L = 3000.00$   
 Primary Member

Smooth Bars  
Ductile Steel  
With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
Longitudinal Bars With Ends Lapped Starting at the End Sections  
Lap Length  $l_o = 300.00$   
No FRP Wrapping

-----  
Stepwise Properties  
-----

At local axis: 2  
EDGE -A-  
Shear Force,  $V_a = -0.0001715$   
EDGE -B-  
Shear Force,  $V_b = 0.0001715$   
BOTH EDGES  
Axial Force,  $F = -16273.608$   
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension:  $A_{sl,t} = 0.00$   
-Compression:  $A_{sl,c} = 5353.274$   
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension:  $A_{sl,ten} = 1137.257$   
-Compression:  $A_{sl,com} = 2208.54$   
-Middle:  $A_{sl,mid} = 2007.478$   
-----  
-----

Calculation of Shear Capacity ratio ,  $V_e/V_r = 0.32266369$   
Member Controlled by Flexure ( $V_e/V_r < 1$ )  
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$   
with

$M_{pr1} = \text{Max}(Mu_{1+} , Mu_{1-}) = 5.0296E+008$   
 $Mu_{1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination  
 $Mu_{1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination  
 $M_{pr2} = \text{Max}(Mu_{2+} , Mu_{2-}) = 5.0296E+008$   
 $Mu_{2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination  
 $Mu_{2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

-----  
Calculation of  $Mu_{1+}$   
-----

-----  
Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:  
 $\phi_u = 4.8099118E-006$   
 $Mu = 2.3387E+008$   
-----

with full section properties:

$b = 750.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00102301$   
 $N = 16273.608$   
 $f_c = 30.00$   
 $co (5A.5, TBDY) = 0.002$   
Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01260361$   
The Shear\_factor is considered equal to 1 (pure moment strength)  
From (5.4b), TBDY:  $\phi_{cu} = 0.01260361$   
 $\phi_{we} (5.4c) = 0.05179731$   
 $\phi_{ase} ((5.4d), TBDY) = (\text{ase1} * A_{ext} + \text{ase2} * A_{int}) / A_{sec} = 0.45746528$   
 $\text{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$   
The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

-----  
 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with  $shear\_factor$

and also multiplied by the  $shear\_factor$  according to 15.7.1.4, with

$Shear\_factor = 1.00$

$l_o/l_{ou,min} = l_b/l_d = 0.13907892$

$su1 = 0.4 * esu1\_nominal$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,

For calculation of  $esu1\_nominal$  and  $y1, sh1, ft1, fy1$ , it is considered

characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$f_y2 = 262.1446$   
 $s_u2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{o,min} = l_b/l_{b,min} = 0.13907892$   
 $s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $e_{su2,nominal} = 0.08$ ,  
 For calculation of  $e_{su2,nominal}$  and  $y_2, sh_2, ft_2, f_y2$ , it is considered  
 characteristic value  $f_{sy2} = f_s2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, f_y1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 262.1446$   
 with  $E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $f_yv = 262.1446$   
 $s_{uv} = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{o,min} = l_b/l_d = 0.13907892$   
 $s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $e_{suv,nominal} = 0.08$ ,  
 considering characteristic value  $f_{syv} = f_{sv}/1.2$ , from table 5.1, TBDY  
 For calculation of  $e_{suv,nominal}$  and  $y_v, sh_v, ft_v, f_yv$ , it is considered  
 characteristic value  $f_{syv} = f_{sv}/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, f_y1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $f_{sv} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 262.1446$   
 with  $E_{sv} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$   
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.0187412$   
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.03639521$   
 $v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.03308184$   
 and confined core properties:  
 $b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.02127357$   
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.04131304$   
 $v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.03755196$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)  
 --->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied  
 --->  
 $s_u (4.9) = 0.21062322$   
 $M_u = M_{Rc} (4.14) = 2.3387E+008$   
 $u = s_u (4.1) = 4.8099118E-006$

---

Calculation of ratio  $l_b/l_d$

---

Lap Length:  $l_b/l_d = 0.13907892$   
 $l_b = 300.00$   
 $l_d = 2157.049$   
 Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$   
 Mean strength value of all re-bars:  $f_y = 781.25$   
 Mean concrete strength:  $f_c' = (f_c',jacket * Area_{jacket} + f_c',core * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$

$e = 1.00$   
 $cb = 25.00$   
 $Ktr = 1.7174$   
 $Atr = \text{Min}(Atr_x, Atr_y) = 257.6106$   
 where  $Atr_x, Atr_y$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$   
 $n = 24.00$

-----  
 Calculation of  $\mu_1$ -  
 -----

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:  
 $u = 5.1201636E-006$   
 $\mu = 5.0296E+008$

-----  
 with full section properties:

$b = 400.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00191815$   
 $N = 16273.608$

$f_c = 30.00$   
 $co(5A.5, TBDY) = 0.002$

Final value of  $\mu$ :  $\mu^* = \text{shear\_factor} * \text{Max}(\mu, cc) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\mu = 0.01260361$

we (5.4c) = 0.05179731

ase ((5.4d), TBDY) =  $(ase1 * A_{\text{ext}} + ase2 * A_{\text{int}}) / A_{\text{sec}} = 0.45746528$

$ase1 = \text{Max}(((A_{\text{conf,max1}} - A_{\text{noConf1}}) / A_{\text{conf,max1}}) * (A_{\text{conf,min1}} / A_{\text{conf,max1}}), 0) = 0.45746528$

The definitions of  $A_{\text{noConf}}$ ,  $A_{\text{conf,min}}$  and  $A_{\text{conf,max}}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max1}} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{\text{conf,min1}} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{\text{conf,max1}}$  by a length equal to half the clear spacing between external hoops.

$A_{\text{noConf1}} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{\text{conf,max2}} - A_{\text{noConf2}}) / A_{\text{conf,max2}}) * (A_{\text{conf,min2}} / A_{\text{conf,max2}}), 0) = 0.45746528$

The definitions of  $A_{\text{noConf}}$ ,  $A_{\text{conf,min}}$  and  $A_{\text{conf,max}}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max2}} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{\text{conf,min2}} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{\text{conf,max2}}$  by a length equal to half the clear spacing between internal hoops.

$A_{\text{noConf2}} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$psh_{\text{min}} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s1) = 0.00367709$

$L_{\text{stir1}}$  (Length of stirrups along Y) = 2060.00

$A_{\text{stir1}}$  (stirrups area) = 78.53982

$psh2$  (5.4d) =  $L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s2) = 0.00067082$

$L_{\text{stir2}}$  (Length of stirrups along Y) = 1468.00

$A_{\text{stir2}}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s1) = 0.00367709$

Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
psh2 ((5.4d), TBDY) = Lstir2\*Astir2/(Asec\*s2) = 0.00067082  
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

-----  
Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.06824101

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03513975

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.06202846

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.08384116$   
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04317283$   
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.2584548$   
 $Mu = MRc (4.14) = 5.0296E+008$   
 $u = su (4.1) = 5.1201636E-006$

-----  
 Calculation of ratio  $l_b/l_d$

-----  
 Lap Length:  $l_b/l_d = 0.13907892$   
 $l_b = 300.00$   
 $l_d = 2157.049$   
 Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$   
 Mean strength value of all re-bars:  $f_y = 781.25$   
 Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$   
 $e = 1.00$   
 $cb = 25.00$   
 $K_{tr} = 1.7174$   
 $A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$   
 where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y loxal axis  
 $s = \text{Max}(s_{external}, s_{internal}) = 250.00$   
 $n = 24.00$

-----  
 Calculation of  $Mu_{2+}$

-----  
 Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:  
 $u = 4.8099118E-006$   
 $Mu = 2.3387E+008$

-----  
 with full section properties:

$b = 750.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00102301$   
 $N = 16273.608$   
 $f_c = 30.00$   
 $co (5A.5, TBDY) = 0.002$   
 Final value of  $cu$ :  $cu^* = \text{shear\_factor} * \text{Max}(cu, cc) = 0.01260361$   
 The Shear\_factor is considered equal to 1 (pure moment strength)  
 From (5.4b), TBDY:  $cu = 0.01260361$   
 $we (5.4c) = 0.05179731$   
 $ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$   
 $ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$   
 The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization  
 of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2})/A_{conf,max2}) * (A_{conf,min2}/A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

$A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$

$c$  = confinement factor = 1.27105

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$fy2 = 262.1446$

$$su_2 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.13907892$$

$$su_2 = 0.4 * esu_2,nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu\_2,nominal = 0.08,

For calculation of esu\_2,nominal and  $y_2$ , sh\_2,ft\_2,fy\_2, it is considered  
characteristic value fsy\_2 = fs\_2/1.2, from table 5.1, TBDY.

$y_1$ , sh\_1,ft\_1,fy\_1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$yv = 0.00083886$$

$$shv = 0.00268436$$

$$ftv = 314.5735$$

$$fyv = 262.1446$$

$$suv = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$lo/lou,min = lb/ld = 0.13907892$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and  $y_v$ , shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

$y_1$ , sh\_1,ft\_1,fy\_1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$$

$$\text{with } Esv = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / fc) = 0.0187412$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / fc) = 0.03639521$$

$$v = A_{sl,mid} / (b * d) * (fsv / fc) = 0.03308184$$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 38.13135$$

$$cc (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / fc) = 0.02127357$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / fc) = 0.04131304$$

$$v = A_{sl,mid} / (b * d) * (fsv / fc) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.21062322$$

$$\mu = MRc (4.14) = 2.3387E+008$$

$$u = su (4.1) = 4.8099118E-006$$

-----  
Calculation of ratio lb/ld

Lap Length: lb/ld = 0.13907892

$$lb = 300.00$$

$$ld = 2157.049$$

Calculation of lb,min according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

ld,min from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$db = 16.66667$$

Mean strength value of all re-bars: fy = 781.25

Mean concrete strength: fc' = (fc'\_jacket \* Area\_jacket + fc'\_core \* Area\_core) / Area\_section = 30.00, but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

-----  
-----  
-----  
Calculation of  $\mu_2$ -  
-----

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$\mu = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$co(5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear\_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01260361$$

$$\mu_{cc} \text{ (5.4c)} = 0.05179731$$

$$ase \text{ ((5.4d), TBDY)} = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$ase2 (\geq ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$$

$$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$$

$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$$

$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

Astir1 (stirrups area) = 78.53982  
psh2 ((5.4d), TBDY) = Lstir2\*Astir2/(Asec\*s2) = 0.00067082  
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

-----  
Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.06824101

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03513975

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.06202846

and confined core properties:

b = 340.00

$d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, \text{TBDY}) = 38.13135$   
 $cc (5A.5, \text{TBDY}) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.08384116$   
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04317283$   
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.2584548$   
 $Mu = MRc (4.14) = 5.0296E+008$   
 $u = su (4.1) = 5.1201636E-006$

-----  
 Calculation of ratio  $l_b/l_d$

-----  
 Lap Length:  $l_b/l_d = 0.13907892$   
 $l_b = 300.00$   
 $l_d = 2157.049$   
 Calculation of  $l_b, \text{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_d, \text{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$   
 Mean strength value of all re-bars:  $f_y = 781.25$   
 Mean concrete strength:  $f'_c = (f'_{c,jacket} * \text{Area}_{jacket} + f'_{c,core} * \text{Area}_{core}) / \text{Area}_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$   
 $e = 1.00$   
 $cb = 25.00$   
 $K_{tr} = 1.7174$   
 $A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$   
 where  $A_{tr,x}, A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{external}, s_{internal}) = 250.00$   
 $n = 24.00$

-----  
 Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

-----  
 Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$   
 $V_{r1} = V_{CoI} ((10.3), \text{ASCE } 41-17) = knl * V_{CoI0}$   
 $V_{CoI0} = 1.0392E+006$   
 $knl = 1$  (zero step-static loading)

-----  
 NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} + f * V_f$ '  
 where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)  
 Mean concrete strength:  $f'_c = (f'_{c,jacket} * \text{Area}_{jacket} + f'_{c,core} * \text{Area}_{core}) / \text{Area}_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $M/Vd = 4.00$   
 $Mu = 1308.675$   
 $Vu = 0.0001715$   
 $d = 0.8 * h = 600.00$   
 $Nu = 16273.608$   
 $Ag = 300000.00$   
 From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$   
 where:  
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$   
 $V_{s,j1} = 314159.265$  is calculated for section web jacket, with:  
 $d = 320.00$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

V<sub>s,j1</sub> is multiplied by Col<sub>j1</sub> = 1.00

$$s/d = 0.3125$$

V<sub>s,j2</sub> = 589048.623 is calculated for section flange jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

V<sub>s,j2</sub> is multiplied by Col<sub>j2</sub> = 1.00

$$s/d = 0.16666667$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$$

V<sub>s,c1</sub> = 0.00 is calculated for section web core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

V<sub>s,c1</sub> is multiplied by Col<sub>c1</sub> = 0.00

$$s/d = 1.5625$$

V<sub>s,c2</sub> = 110584.061 is calculated for section flange core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

V<sub>s,c2</sub> is multiplied by Col<sub>c2</sub> = 1.00

$$s/d = 0.56818182$$

$$V_f ((11-3)-(11.4), ACI 440) = 0.00$$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$$b_w = 400.00$$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$

$$V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$$

$$V_{Col0} = 1.0392E+006$$

knl = 1 (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f'_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/d = 4.00$$

$$M_u = 1308.675$$

$$V_u = 0.0001715$$

$$d = 0.8 * h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$$

V<sub>s,j1</sub> = 314159.265 is calculated for section web jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

V<sub>s,j1</sub> is multiplied by Col<sub>j1</sub> = 1.00

$$s/d = 0.3125$$

V<sub>s,j2</sub> = 589048.623 is calculated for section flange jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

V<sub>s,j2</sub> is multiplied by Col<sub>j2</sub> = 1.00

$$s/d = 0.16666667$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$$

Vs,c1 = 0.00 is calculated for section web core, with:

d = 160.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 0.00

s/d = 1.5625

Vs,c2 = 110584.061 is calculated for section flange core, with:

d = 440.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 1.00

s/d = 0.56818182

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 873250.061

bw = 400.00

-----  
End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At local axis: 2  
-----

Start Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjics

Constant Properties

-----  
Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, fc = fcm = 30.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 25742.96

Steel Elasticity, Es = 200000.00

Existing Column

New material of Primary Member: Concrete Strength, fc = fcm = 30.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 25742.96

Steel Elasticity, Es = 200000.00

Max Height, Hmax = 750.00

Min Height, Hmin = 400.00

Max Width, Wmax = 750.00

Min Width, Wmin = 400.00

Jacket Thickness, tj = 100.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length lb = 300.00

No FRP Wrapping  
-----

Stepwise Properties

-----  
Bending Moment, M = -459842.936

Shear Force, V2 = -7609.421

Shear Force, V3 = 213.4386

Axial Force,  $F = -17779.344$   
 Longitudinal Reinforcement Area Distribution (in 2 divisions)  
 -Tension:  $As_t = 0.00$   
 -Compression:  $As_c = 5353.274$   
 Longitudinal Reinforcement Area Distribution (in 3 divisions)  
 -Tension:  $As_{t,ten} = 1137.257$   
 -Compression:  $As_{c,com} = 2208.54$   
 -Middle:  $As_{c,mid} = 2007.478$   
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)  
 -Tension:  $As_{t,ten,jacket} = 829.3805$   
 -Compression:  $As_{c,com,jacket} = 1746.726$   
 -Middle:  $As_{c,mid,jacket} = 1545.664$   
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)  
 -Tension:  $As_{t,ten,core} = 307.8761$   
 -Compression:  $As_{c,com,core} = 461.8141$   
 -Middle:  $As_{c,mid,core} = 461.8141$   
 Mean Diameter of Tension Reinforcement,  $Db_L = 16.80$

-----  
 -----  
 New component: From table 7-7, ASCE 41\_17: Final chord rotation Capacity  $u_{,R} = 1.0^*$   $u = 0.04038849$   
 $u = y + p = 0.04038849$

-----  
 - Calculation of  $y$  -  
 -----

$y = (M_y * L_s / 3) / E_{eff} = 0.00141607$  ((4.29), Biskinis Phd)  
 $M_y = 2.8709E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 2154.45  
 From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
 $factor = 0.30$   
 $A_g = 440000.00$   
 Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17779.344$   
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 4.8532E+014$

-----  
 -----  
 Calculation of Yielding Moment  $M_y$   
 -----

Calculation of  $y$  and  $M_y$  according to Annex 7 -  
 -----

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:  
 flange width,  $b = 750.00$   
 web width,  $b_w = 400.00$   
 flange thickness,  $t = 400.00$

-----  
 -----  
 $y = \text{Min}(y_{ten}, y_{com})$   
 $y_{ten} = 2.1455196E-006$   
 with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 243.3535$   
 $d = 707.00$   
 $y = 0.19784983$   
 $A = 0.01023354$   
 $B = 0.00454395$   
 with  $pt = 0.00434791$   
 $pc = 0.00416509$   
 $pv = 0.00378591$   
 $N = 17779.344$   
 $b = 750.00$   
 $" = 0.06082037$   
 $y_{comp} = 1.5202265E-005$   
 with  $fc = 30.00$   
 $E_c = 25742.96$   
 $y = 0.19516753$   
 $A = 0.01001583$   
 $B = 0.00440616$

with  $E_s = 200000.00$

CONFIRMATION:  $y = 0.19594836 < t/d$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_d/l_{d,min} = 0.17384865$

$l_b = 300.00$

$l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f'_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

- Calculation of  $\rho$  -

From table 10-8:  $\rho = 0.03897242$

with:

- Columns controlled by inadequate development or splicing along the clear height because  $l_b/l_d < 1$

shear control ratio  $V_y E / V_{CoI} E = 0.32266369$

$d = d_{external} = 707.00$

$s = s_{external} = 0.00$

-  $t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00434791$

jacket:  $s_1 = A_{v1} \cdot L_{stir1} / (s_1 \cdot A_g) = 0.00367709$

$A_{v1} = 78.53982$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2060.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core:  $s_2 = A_{v2} \cdot L_{stir2} / (s_2 \cdot A_g) = 0.00067082$

$A_{v2} = 50.26548$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1468.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term  $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$  is implemented to account for FRP contribution

where  $f = 2 \cdot t_f / b_w$  is FRP ratio (EC8 - 3, A.4.4.3(6)) and  $f_{fe} / f_s$  normalises  $f$  to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation  $f_s$  of jacket is used.

$NUD = 17779.344$

$A_g = 440000.00$

$f_{cE} = (f_{c,jacket} \cdot Area_{jacket} + f_{c,core} \cdot Area_{core}) / section\_area = 30.00$

$f_{yE} = (f_{y,ext\_Long\_Reinf} \cdot Area_{ext\_Long\_Reinf} + f_{y,int\_Long\_Reinf} \cdot Area_{int\_Long\_Reinf}) / Area_{Tot\_Long\_Rein} = 625.00$

$f_{yE} = (f_{y,ext\_Trans\_Reinf} \cdot s_1 + f_{y,int\_Trans\_Reinf} \cdot s_2) / (s_1 + s_2) = 625.00$

$\rho_l = Area_{Tot\_Long\_Rein} / (b \cdot d) = 0.01009575$

$b = 750.00$

$d = 707.00$

$f_{cE} = 30.00$

End Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (a)

## Calculation No. 11

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjlc

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of  $\gamma$  for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

Existing Column

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = l_b = 300.00$

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment,  $M_a = -459842.936$

Shear Force,  $V_a = 213.4386$

EDGE -B-

Bending Moment,  $M_b = -178152.624$

Shear Force,  $V_b = -213.4386$

BOTH EDGES

Axial Force,  $F = -17779.344$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{slt} = 0.00$

-Compression:  $A_{slc} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten} = 1137.257$

-Compression:  $A_{sl,com} = 2208.54$

-Middle:  $A_{sl,mid} = 2007.478$

Mean Diameter of Tension Reinforcement,  $Db_{L,ten} = 16.80$

New component: From table 7-7, ASCE 41\_17: Final Shear Capacity  $V_R = 1.0 * V_n = 864428.503$

$V_n$  (10.3), ASCE 41-17) =  $k_n * V_{CoI0} = 864428.503$

$V_{CoI} = 864428.503$

$k_n = 1.00$

displacement\_ductility\_demand = 0.02355546

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_c_{jacket} * Area_{jacket} + f'_c_{core} * Area_{core}) / Area_{section} = 20.00$ , but  $f'_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M / Vd = 3.59075$

$M_u = 459842.936$

$V_u = 213.4386$

$d = 0.8 * h = 600.00$

$N_u = 17779.344$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{sjacket} + V_{s,core} = 811033.559$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 722566.31$

$V_{sj1} = 471238.898$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$   
 $V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,j2} = 251327.412$  is calculated for section flange jacket, with:  
 $d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$   
 $V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$   
 $s/d = 0.3125$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 88467.249$   
 $V_{s,c1} = 88467.249$  is calculated for section web core, with:  
 $d = 440.00$   
 $A_v = 100530.965$   
 $f_y = 500.00$   
 $s = 250.00$   
 $V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$   
 $s/d = 0.56818182$   
 $V_{s,c2} = 0.00$  is calculated for section flange core, with:  
 $d = 160.00$   
 $A_v = 100530.965$   
 $f_y = 500.00$   
 $s = 250.00$   
 $V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$   
 $s/d = 1.5625$   
 $V_f((11-3)-(11.4), ACI 440) = 0.00$   
 From (11-11), ACI 440:  $V_s + V_f \leq 713005.69$   
 $bw = 400.00$

displacement ductility demand is calculated as  $\delta / y$

- Calculation of  $\delta / y$  for END A -  
for rotation axis 2 and integ. section (a)

From analysis, chord rotation  $\theta = 3.3356266E-005$   
 $y = (M_y * L_s / 3) / E_{eff} = 0.00141607$  ((4.29), Biskinis Phd)  
 $M_y = 2.8709E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 2154.45  
 From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
 $factor = 0.30$   
 $A_g = 440000.00$   
 Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17779.344$   
 $E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 4.8532E+014$

Calculation of Yielding Moment  $M_y$

Calculation of  $\delta / y$  and  $M_y$  according to Annex 7 -

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$   
 web width,  $bw = 400.00$   
 flange thickness,  $t = 400.00$

$y = \text{Min}(y_{ten}, y_{com})$   
 $y_{ten} = 2.1455196E-006$   
 with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 243.3535$   
 $d = 707.00$   
 $y = 0.19784983$   
 $A = 0.01023354$   
 $B = 0.00454395$   
 with  $pt = 0.00214476$   
 $pc = 0.00416509$

pv = 0.00378591  
N = 17779.344  
b = 750.00  
" = 0.06082037  
y\_comp = 1.5202265E-005  
with fc = 30.00  
Ec = 25742.96  
y = 0.19516753  
A = 0.01001583  
B = 0.00440616  
with Es = 200000.00  
CONFIRMATION:  $y = 0.19594836 < t/d$



-----  
-----  
Calculation of ratio lb/l<sub>d</sub>

-----  
Lap Length:  $l_d/l_{d,min} = 0.17384865$   
lb = 300.00  
ld = 1725.639  
Calculation of l according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
ld,min from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)  
= 1  
db = 16.66667  
Mean strength value of all re-bars: fy = 625.00  
Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)  
t = 1.00  
s = 0.80  
e = 1.00  
cb = 25.00  
Ktr = 1.7174  
Atr =  $\text{Min}(Atr_x, Atr_y) = 257.6106$   
where Atr<sub>x</sub>, Atr<sub>y</sub> are the sum of the area of all stirrup legs along X and Y local axis  
s =  $\text{Max}(s_{external}, s_{internal}) = 250.00$   
n = 24.00

-----  
End Of Calculation of Shear Capacity for element: column JLC1 of floor 1  
At local axis: 3  
Integration Section: (a)

## Calculation No. 12

column C1, Floor 1  
Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)  
Analysis: Uniform +X  
Check: Chord rotation capacity (  $\theta$  )  
Edge: Start  
Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At Shear local axis: 3  
 (Bending local axis: 2)  
 Section Type: rcjlcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$   
 Mean strength values are used for both shear and moment calculations.  
 Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,  
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = 300.00$

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force,  $V_a = -0.00017144$

EDGE -B-

Shear Force,  $V_b = 0.00017144$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $As_t = 0.00$

-Compression:  $As_c = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $As_{t,ten} = 1137.257$

-Compression:  $As_{c,com} = 2208.54$

-Middle:  $As_{c,mid} = 2007.478$

Calculation of Shear Capacity ratio,  $V_e/V_r = 0.32266369$

Member Controlled by Flexure ( $V_e/V_r < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 5.0296E+008$

$Mu_{1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 5.0296E+008$

$Mu_{2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination

Calculation of  $Mu_{1+}$

Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 4.8099118E-006$

$M_u = 2.3387E+008$

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\omega (5A.5, TBDY) = 0.002$

Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} * \text{Max}(\phi_u, \phi_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\phi_u = 0.01260361$

$\omega_e (5.4c) = 0.05179731$

$\omega_{ase} ((5.4d), TBDY) = (\omega_{ase1} * A_{ext} + \omega_{ase2} * A_{int}) / A_{sec} = 0.45746528$

$\omega_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\omega_{ase2} (>= \omega_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

---

$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

---

$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

---

$A_{sec} = 440000.00$   
 $s1 = 100.00$   
 $s2 = 250.00$

$f_{ywe1} = 781.25$   
 $f_{ywe2} = 781.25$   
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$   
 $sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/ld = 0.13907892$   
 $su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 0.13907892$   
 $su2 = 0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu2_{nominal} = 0.08$ ,

For calculation of  $esu2_{nominal}$  and  $y2, sh2, ft2, fy2$ , it is considered characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.00083886$   
 $shv = 0.00268436$

$$ftv = 314.5735$$

$$fyv = 262.1446$$

$$suv = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$lo/lo_{min} = lb/ld = 0.13907892$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $esuv_{nominal} = 0.08$ ,

considering characteristic value  $fsv = fsv/1.2$ , from table 5.1, TBDY

For calculation of  $esuv_{nominal}$  and  $yv$ ,  $shv$ ,  $ftv$ ,  $fyv$ , it is considered  
characteristic value  $fsv = fsv/1.2$ , from table 5.1, TBDY.

$y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 262.1446$$

$$\text{with } Es_v = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.0187412$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.03639521$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03308184$$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 38.13135$$

$$cc (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.02127357$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.04131304$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < vs_{y2}$  - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.21062322$$

$$Mu = MRc (4.14) = 2.3387E+008$$

$$u = su (4.1) = 4.8099118E-006$$

-----  
Calculation of ratio  $lb/ld$

-----  
Lap Length:  $lb/ld = 0.13907892$

$$lb = 300.00$$

$$ld = 2157.049$$

Calculation of  $lb_{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld_{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$db = 16.66667$$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$Ktr = 1.7174$$

$$Atr = \text{Min}(Atr_x, Atr_y) = 257.6106$$

where  $Atr_x$ ,  $Atr_y$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $Mu1$ -

-----  
Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

u = 5.1201636E-006  
Mu = 5.0296E+008

with full section properties:

b = 400.00  
d = 707.00  
d' = 43.00  
v = 0.00191815  
N = 16273.608

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu\* = shear\_factor \* Max( cu, cc) = 0.01260361

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01260361

we (5.4c) = 0.05179731

ase ((5.4d), TBDY) = (ase1\*Aext+ase2\*Aint)/Asec = 0.45746528

ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)\*(Aconf,min1/Aconf,max1),0) = 0.45746528

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 353600.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 293525.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.

AnoConf1 = 158733.333 is the unconfined external core area which is equal to bi2/6 as defined at (A.2).

ase2 (>=ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)\*(Aconf,min2/Aconf,max2),0) = 0.45746528

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 171264.00 is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 54741.00 is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to bi2/6 as defined at (A.2).

psh,min\*Fywe = Min(psh,x\*Fywe , psh,y\*Fywe) = 3.3968

psh\_x\*Fywe = psh1\*Fywe1+ps2\*Fywe2 = 3.3968

psh1 ((5.4d), TBDY) = Lstir1\*Astir1/(Asec\*s1) = 0.00367709

Lstir1 (Length of stirrups along Y) = 2060.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) = Lstir2\*Astir2/(Asec\*s2) = 0.00067082

Lstir2 (Length of stirrups along Y) = 1468.00

Astir2 (stirrups area) = 50.26548

psh\_y\*Fywe = psh1\*Fywe1+ps2\*Fywe2 = 3.3968

psh1 ((5.4d), TBDY) = Lstir1\*Astir1/(Asec\*s1) = 0.00367709

Lstir1 (Length of stirrups along X) = 2060.00

Astir1 (stirrups area) = 78.53982

psh2 ((5.4d), TBDY) = Lstir2\*Astir2/(Asec\*s2) = 0.00067082

Lstir2 (Length of stirrups along X) = 1468.00

Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

$sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou,min = lb/ld = 0.13907892$   
 $su1 = 0.4*esu1\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,  
 For calculation of  $esu1\_nominal$  and  $y1, sh1, ft1, fy1$ , it is considered  
 characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 262.1446$   
 with  $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$   
 $y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou,min = lb/lb,min = 0.13907892$   
 $su2 = 0.4*esu2\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu2\_nominal = 0.08$ ,  
 For calculation of  $esu2\_nominal$  and  $y2, sh2, ft2, fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 262.1446$   
 with  $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$   
 $yv = 0.00083886$   
 $shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou,min = lb/ld = 0.13907892$   
 $suv = 0.4*esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv, shv, ftv, fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 262.1446$   
 with  $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.06824101$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.03513975$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.06202846$   
 and confined core properties:  
 $b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = confinement\ factor = 1.27105$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.08384116$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04317283$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)  
 --->  
 $v < vs,y2$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.2584548$

$$\begin{aligned} \mu &= M/R_c (4.14) = 5.0296E+008 \\ u &= s_u (4.1) = 5.1201636E-006 \end{aligned}$$

Calculation of ratio  $l_b/l_d$

$$\text{Lap Length: } l_b/l_d = 0.13907892$$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot \text{Area}_{jacket} + f'_{c,core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of  $\mu_{2+}$

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$u = 4.8099118E-006$$

$$\mu = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e (5.4c) = 0.05179731$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 171264.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 54741.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 3.3968$

-----  
 $psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 3.3968$   
 $psh1 \text{ ((5.4d), TBDY)} = Lstir1*Astir1/(Asec*s1) = 0.00367709$   
Lstir1 (Length of stirrups along Y) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2 \text{ (5.4d)} = Lstir2*Astir2/(Asec*s2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

-----  
 $psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 3.3968$   
 $psh1 \text{ ((5.4d), TBDY)} = Lstir1*Astir1/(Asec*s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2 \text{ ((5.4d), TBDY)} = Lstir2*Astir2/(Asec*s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

-----  
Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/l\_d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/l\_b,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

$f_{yv} = 262.1446$   
 $s_{uv} = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{ou,min} = l_b/l_d = 0.13907892$   
 $s_{uv} = 0.4 * e_{suv\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $e_{suv\_nominal} = 0.08$ ,  
 considering characteristic value  $f_{sv} = f_{sv}/1.2$ , from table 5.1, TBDY  
 For calculation of  $e_{suv\_nominal}$  and  $\gamma_v$ ,  $sh_v$ ,  $ft_v$ ,  $f_{yv}$ , it is considered  
 characteristic value  $f_{sv} = f_{sv}/1.2$ , from table 5.1, TBDY.  
 $\gamma_1$ ,  $sh_1$ ,  $ft_1$ ,  $f_{y1}$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 262.1446$   
 with  $E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$   
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.0187412$   
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.03639521$   
 $v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.03308184$

and confined core properties:

$b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.02127357$   
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04131304$   
 $v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---

$su (4.9) = 0.21062322$   
 $Mu = MRc (4.14) = 2.3387E+008$   
 $u = su (4.1) = 4.8099118E-006$

-----  
 Calculation of ratio  $l_b/l_d$   
 -----

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b,min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d,min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$

MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
 Calculation of  $Mu_2$ -  
 -----

-----  
 Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$u = 5.1201636E-006$

$$\mu = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$\alpha (5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \alpha: \alpha^* = \text{shear\_factor} * \text{Max}(\alpha, \alpha_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \alpha_c = 0.01260361$$

$$w_e (5.4c) = 0.05179731$$

$$a_{se} ((5.4d), \text{TBDY}) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along Y}) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along Y}) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along X}) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along X}) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \alpha_c = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$y1 = 0.00083886$$

$$sh1 = 0.00268436$$

$ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/ld = 0.13907892$   
 $su1 = 0.4*esu1\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,  
 For calculation of  $esu1\_nominal$  and  $y1, sh1, ft1, fy1$ , it is considered  
 characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 262.1446$   
 with  $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$   
 $y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/lb,min = 0.13907892$   
 $su2 = 0.4*esu2\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu2\_nominal = 0.08$ ,  
 For calculation of  $esu2\_nominal$  and  $y2, sh2, ft2, fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 262.1446$   
 with  $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$   
 $yv = 0.00083886$   
 $shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $lo/lou,min = lb/ld = 0.13907892$   
 $suv = 0.4*esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv, shv, ftv, fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 262.1446$   
 with  $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.06824101$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.03513975$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.06202846$   
 and confined core properties:  
 $b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.08384116$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04317283$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)  
 --->  
 $v < vs,y2$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.2584548$   
 $Mu = MRc (4.14) = 5.0296E+008$

$$u = s_u(4.1) = 5.1201636E-006$$

Calculation of ratio  $l_b/d$

Lap Length:  $l_b/d = 0.13907892$

$$l_b = 300.00$$

$$d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_b, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$V_{r1} = V_{\text{Col}}((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col}0}$

$$V_{\text{Col}0} = 1.0392E+006$$

$k_{nl} = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$M_u = 1308.016$$

$$V_u = 0.00017144$$

$$d = 0.8 \cdot h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.0138E+006$

where:

$$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 903207.888$$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$  is multiplied by  $\text{Col}_{j1} = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j2}$  is multiplied by  $\text{Col}_{j2} = 1.00$

$$s/d = 0.3125$$

$$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 110584.061$$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$

$$s/d = 1.5625$$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$$bw = 400.00$$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$

$V_{r2} = V_{Col}$  ((10.3), ASCE 41-17) =  $k_{nl} * V_{Col0}$

$$V_{Col0} = 1.0392E+006$$

$k_{nl} = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_c\_jacket * Area\_jacket + f'_c\_core * Area\_core) / Area\_section = 30.00$ , but  $f'_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 1308.016$$

$$V_u = 0.00017144$$

$$d = 0.8 * h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$$s/d = 0.16666667$$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$

$$s/d = 0.3125$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$

$$s/d = 0.56818182$$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$

$$s/d = 1.5625$$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
 $bw = 400.00$

-----  
-----  
End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 3

-----  
Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At Shear local axis: 2  
(Bending local axis: 3)  
Section Type: rcjcs

Constant Properties

-----  
Knowledge Factor,  $\gamma = 1.00$   
Mean strength values are used for both shear and moment calculations.  
Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,  
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 * f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 * f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = 300.00$

No FRP Wrapping

-----  
Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force,  $V_a = -0.0001715$

EDGE -B-

Shear Force,  $V_b = 0.0001715$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{st} = 0.00$

-Compression:  $A_{sc} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $Asl,ten = 1137.257$

-Compression:  $Asl,com = 2208.54$

-Middle:  $Asl,mid = 2007.478$

Calculation of Shear Capacity ratio ,  $Ve/Vr = 0.32266369$

Member Controlled by Flexure ( $Ve/Vr < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $Ve = (Mpr1 + Mpr2)/ln = 335307.657$

with

$Mpr1 = \text{Max}(Mu1+, Mu1-) = 5.0296E+008$

$Mu1+ = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu1- = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$Mpr2 = \text{Max}(Mu2+, Mu2-) = 5.0296E+008$

$Mu2+ = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu2- = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of  $Mu1+$

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$u = 4.8099118E-006$

$Mu = 2.3387E+008$

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$fc = 30.00$

$co$  (5A.5, TBDY) = 0.002

Final value of  $cu$ :  $cu^* = \text{shear\_factor} * \text{Max}(cu, cc) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $cu = 0.01260361$

$we$  (5.4c) = 0.05179731

$ase$  ((5.4d), TBDY) =  $(ase1 * Aext + ase2 * Aint) / Asec = 0.45746528$

$ase1 = \text{Max}(((Aconf,max1 - AnoConf1) / Aconf,max1) * (Aconf,min1 / Aconf,max1), 0) = 0.45746528$

The definitions of  $AnoConf$ ,  $Aconf,min$  and  $Aconf,max$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$Aconf,max1 = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$Aconf,min1 = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $Aconf,max1$  by a length equal to half the clear spacing between external hoops.

$AnoConf1 = 158733.333$  is the unconfined external core area which is equal to  $bi^2/6$  as defined at (A.2).

$ase2$  ( $\geq ase1$ ) =  $\text{Max}(((Aconf,max2 - AnoConf2) / Aconf,max2) * (Aconf,min2 / Aconf,max2), 0) = 0.45746528$

The definitions of  $AnoConf$ ,  $Aconf,min$  and  $Aconf,max$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$Aconf,max2 = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$Aconf,min2 = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $Aconf,max2$  by a length

equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to  $bi^2/6$  as defined at (A.2).  
 $psh_{min} * Fywe = \text{Min}(psh_x * Fywe, psh_y * Fywe) = 3.3968$

$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.3968$   
 $psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00367709$   
Lstir1 (Length of stirrups along Y) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2 \text{ (5.4d)} = Lstir2 * Astir2 / (Asec * s2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 3.3968$   
 $psh1 \text{ ((5.4d), TBDY)} = Lstir1 * Astir1 / (Asec * s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2 \text{ ((5.4d), TBDY)} = Lstir2 * Astir2 / (Asec * s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb = 0.13907892

su1 = 0.4 \* esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1, ft1, fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket \* Asl,ten,jacket + fs,core \* Asl,ten,core) / Asl,ten = 262.1446

with Es1 = (Es,jacket \* Asl,ten,jacket + Es,core \* Asl,ten,core) / Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4 \* esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2, ft2, fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket \* Asl,com,jacket + fs,core \* Asl,com,core) / Asl,com = 262.1446

with Es2 = (Es,jacket \* Asl,com,jacket + Es,core \* Asl,com,core) / Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fsjacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.0187412

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03639521

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03308184

and confined core properties:

b = 690.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.02127357

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.04131304

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03755196

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

----

v < vs,y2 - LHS eq.(4.5) is satisfied

----

su (4.9) = 0.21062322

Mu = MRc (4.14) = 2.3387E+008

u = su (4.1) = 4.8099118E-006

-----  
Calculation of ratio lb/ld

-----  
Lap Length: lb/ld = 0.13907892

lb = 300.00

ld = 2157.049

Calculation of lb,min according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

ld,min from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

db = 16.66667

Mean strength value of all re-bars: fy = 781.25

Mean concrete strength: fc' = (fc'\_jacket\*Area\_jacket + fc'\_core\*Area\_core)/Area\_section = 30.00, but  $fc'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

t = 1.00

s = 0.80

e = 1.00

cb = 25.00

Ktr = 1.7174

Atr =  $\text{Min}(Atr_x, Atr_y)$  = 257.6106

where Atr\_x, Atr\_y are the sum of the area of all stirrup legs along X and Y local axis

s =  $\text{Max}(s_{\text{external}}, s_{\text{internal}})$  = 250.00

n = 24.00

-----  
Calculation of Mu1-

-----  
Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 5.1201636E-006

Mu = 5.0296E+008

-----  
with full section properties:

b = 400.00

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (> a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$y1 = 0.00083886$$

$$sh1 = 0.00268436$$

$$ft1 = 314.5735$$

$$fy1 = 262.1446$$

$$su1 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.06824101

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03513975

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.06202846

and confined core properties:

b = 340.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.08384116

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.04317283

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.07620839

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2584548

Mu = MRc (4.14) = 5.0296E+008

u = su (4.1) = 5.1201636E-006

-----  
Calculation of ratio lb/d

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \min(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \max(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

Calculation of  $\mu_{2+}$

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$u = 4.8099118E-006$

$\mu = 2.3387E+008$

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$c_o$  (5A.5, TBDY) = 0.002

Final value of  $c_u$ :  $c_u^* = \text{shear\_factor} \cdot \max(c_u, c_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $c_u = 0.01260361$

$w_e$  (5.4c) = 0.05179731

$a_{se}$  ((5.4d), TBDY) =  $(a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.45746528$

$a_{se1} = \max(((A_{conf, \max 1} - A_{noConf1}) / A_{conf, \max 1}) \cdot (A_{conf, \min 1} / A_{conf, \max 1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf, \max 1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf, \min 1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf, \max 1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$a_{se2} (>= a_{se1}) = \max(((A_{conf, \max 2} - A_{noConf2}) / A_{conf, \max 2}) \cdot (A_{conf, \min 2} / A_{conf, \max 2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf, \max 2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf, \min 2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf, \max 2}$  by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.3968$

$psh_x * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.3968$   
 $psh_1$  ((5.4d), TBDY) =  $Lstir_1 * Astir_1 / (Asec * s_1) = 0.00367709$   
Lstir1 (Length of stirrups along Y) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh_2$  (5.4d) =  $Lstir_2 * Astir_2 / (Asec * s_2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.3968$   
 $psh_1$  ((5.4d), TBDY) =  $Lstir_1 * Astir_1 / (Asec * s_1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh_2$  ((5.4d), TBDY) =  $Lstir_2 * Astir_2 / (Asec * s_2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00  
s1 = 100.00  
s2 = 250.00  
fywe1 = 781.25  
fywe2 = 781.25  
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y1 = 0.00083886  
sh1 = 0.00268436  
ft1 = 314.5735  
fy1 = 262.1446  
su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l\_d = 0.13907892  
su1 =  $0.4 * esu_{1\_nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1, ft1, fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(fs_{jacket} * Asl_{ten,jacket} + fs_{core} * Asl_{ten,core}) / Asl_{ten} = 262.1446$

with Es1 =  $(Es_{jacket} * Asl_{ten,jacket} + Es_{core} * Asl_{ten,core}) / Asl_{ten} = 200000.00$

y2 = 0.00083886  
sh2 = 0.00268436  
ft2 = 314.5735  
fy2 = 262.1446  
su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892  
su2 =  $0.4 * esu_{2\_nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2, ft2, fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 262.1446$

with Es2 =  $(Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$

yv = 0.00083886  
shv = 0.00268436  
ftv = 314.5735  
fyv = 262.1446  
suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.13907892$$

$$s_{uv} = 0.4 * e_{suv\_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $e_{suv\_nominal} = 0.08$ ,

considering characteristic value  $f_{sv} = f_{sv}/1.2$ , from table 5.1, TBDY

For calculation of  $e_{suv\_nominal}$  and  $\gamma_v$ ,  $sh_v, ft_v, fy_v$ , it is considered

characteristic value  $f_{sv} = f_{sv}/1.2$ , from table 5.1, TBDY.

$$\gamma_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (l_b/l_d)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 262.1446$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.0187412$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.03639521$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.03308184$$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 38.13135$$

$$c_c (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.02127357$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.04131304$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.21062322$$

$$M_u = M_{Rc} (4.14) = 2.3387E+008$$

$$u = s_u (4.1) = 4.8099118E-006$$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b,min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d,min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

$$\text{Mean strength value of all re-bars: } f_y = 781.25$$

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of  $M_u$

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e (5.4c) = 0.05179731$$

$$a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (> a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

---

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along } Y) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along } Y) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

---

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$$

$$L_{stir1} (\text{Length of stirrups along } X) = 2060.00$$

$$A_{stir1} (\text{stirrups area}) = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$$

$$L_{stir2} (\text{Length of stirrups along } X) = 1468.00$$

$$A_{stir2} (\text{stirrups area}) = 50.26548$$

---

$$A_{sec} = 440000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$y_1 = 0.00083886$$

$$sh_1 = 0.00268436$$

$$ft_1 = 314.5735$$

$$fy_1 = 262.1446$$

$$su_1 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/d = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.06824101

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03513975

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.06202846

and confined core properties:

b = 340.00

d = 677.00

d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.08384116

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.04317283

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.07620839

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.2584548

Mu = MRc (4.14) = 5.0296E+008

u = su (4.1) = 5.1201636E-006

-----  
Calculation of ratio lb/d  
-----

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b$ ,min according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d$ ,min from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$   
-----

Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = knl \cdot V_{Col0}$

$V_{Col0} = 1.0392E+006$

$knl = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '

where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.675$

$V_u = 0.0001715$

$d = 0.8 \cdot h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 314159.265$  is calculated for section web jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col_{j1} = 1.00$

$s/d = 0.3125$

$V_{s,j2} = 589048.623$  is calculated for section flange jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $Col_{j2} = 1.00$

$s/d = 0.16666667$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col_{c1} = 0.00$

$s/d = 1.5625$

$V_{s,c2} = 110584.061$  is calculated for section flange core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$

$$s/d = 0.56818182$$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$$bw = 400.00$$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$

$V_{r2} = V_{Col}$  ((10.3), ASCE 41-17) =  $k_{nl} * V_{Col0}$

$$V_{Col0} = 1.0392E+006$$

$k_{nl} = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 4.00$$

$$\mu_u = 1308.675$$

$$\nu_u = 0.0001715$$

$$d = 0.8 * h = 600.00$$

$$N_u = 16273.608$$

$$A_g = 300000.00$$

From (11.5.4.8), ACI 318-14:  $V_s = V_{sjacket} + V_{s,core} = 1.0138E+006$

where:

$$V_{sjacket} = V_{sj1} + V_{sj2} = 903207.888$$

$V_{sj1} = 314159.265$  is calculated for section web jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{sj1}$  is multiplied by  $Col,j1 = 1.00$

$$s/d = 0.3125$$

$V_{sj2} = 589048.623$  is calculated for section flange jacket, with:

$$d = 600.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 100.00$$

$V_{sj2}$  is multiplied by  $Col,j2 = 1.00$

$$s/d = 0.16666667$$

$$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c1}$  is multiplied by  $Col,c1 = 0.00$

$$s/d = 1.5625$$

$V_{s,c2} = 110584.061$  is calculated for section flange core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 625.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$

$$s/d = 0.56818182$$

$V_f$  ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$$bw = 400.00$$

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At local axis: 2

---

Start Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjlc3

Constant Properties

---

Knowledge Factor,  $\gamma = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_b = 300.00$

No FRP Wrapping

---

Stepwise Properties

---

Bending Moment,  $M = -2.3128E+007$

Shear Force,  $V_2 = -7609.421$

Shear Force,  $V_3 = 213.4386$

Axial Force,  $F = -17779.344$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{sl,t} = 0.00$

-Compression:  $A_{sl,c} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten} = 1137.257$

-Compression:  $A_{sl,com} = 2208.54$

-Middle:  $A_{sl,mid} = 2007.478$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten,jacket} = 829.3805$

-Compression:  $A_{sl,com,jacket} = 1746.726$

-Middle:  $A_{sl,mid,jacket} = 1545.664$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten,core} = 307.8761$

-Compression:  $A_{sl,com,core} = 461.8141$

-Middle:  $A_{sl,mid,core} = 461.8141$

Mean Diameter of Tension Reinforcement,  $DbL = 16.80$

---

New component: From table 7-7, ASCE 41\_17: Final chord rotation Capacity  $u, R = 1.0^*$   $u = 0.04097012$   
 $u = y + p = 0.04097012$

-----  
- Calculation of  $y$  -  
-----

$y = (M_y * L_s / 3) / E_{eff} = 0.0019977$  ((4.29), Biskinis Phd))  
 $M_y = 2.8709E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 3039.351  
From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
 $factor = 0.30$   
 $A_g = 440000.00$   
Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17779.344$   
 $E_c * I_g = E_c_{jacket} * I_{g,jacket} + E_c_{core} * I_{g,core} = 4.8532E+014$   
-----  
-----

Calculation of Yielding Moment  $M_y$

-----  
Calculation of  $y$  and  $M_y$  according to Annex 7 -  
-----

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$   
web width,  $b_w = 400.00$   
flange thickness,  $t = 400.00$

-----  
 $y = \text{Min}(y_{ten}, y_{com})$   
 $y_{ten} = 2.1455196E-006$   
with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 * f_y * (l_b / l_d)^{2/3}) = 243.3535$   
 $d = 707.00$   
 $y = 0.19784983$   
 $A = 0.01023354$   
 $B = 0.00454395$   
with  $p_t = 0.00434791$   
 $p_c = 0.00416509$   
 $p_v = 0.00378591$   
 $N = 17779.344$   
 $b = 750.00$   
 $" = 0.06082037$   
 $y_{comp} = 1.5202265E-005$   
with  $f_c = 30.00$   
 $E_c = 25742.96$   
 $y = 0.19516753$   
 $A = 0.01001583$   
 $B = 0.00440616$   
with  $E_s = 200000.00$   
CONFIRMATION:  $y = 0.19594836 < t/d$   
-----  
-----

Calculation of ratio  $l_b / l_d$

-----  
Lap Length:  $l_d / l_{d,min} = 0.17384865$

$l_b = 300.00$   
 $l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

cb = 25.00  
Ktr = 1.7174  
Atr = Min(Atr\_x,Atr\_y) = 257.6106  
where Atr\_x, Atr\_y are the sum of the area of all stirrup legs along X and Y local axis  
s = Max(s\_external,s\_internal) = 250.00  
n = 24.00

-----  
- Calculation of  $\rho$  -  
-----

From table 10-8:  $\rho = 0.03897242$

with:

- Columns controlled by inadequate development or splicing along the clear height because  $l_b/l_d < 1$

shear control ratio  $V_y E / V_{Co} I_{OE} = 0.32266369$

d = d\_external = 707.00

s = s\_external = 0.00

-  $t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00434791$

jacket:  $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00367709$

A<sub>v1</sub> = 78.53982, is the area of every stirrup parallel to loading (shear) direction

L<sub>stir1</sub> = 2060.00, is the total Length of all stirrups parallel to loading (shear) direction

s<sub>1</sub> = 100.00

core:  $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00067082$

A<sub>v2</sub> = 50.26548, is the area of every stirrup parallel to loading (shear) direction

L<sub>stir2</sub> = 1468.00, is the total Length of all stirrups parallel to loading (shear) direction

s<sub>2</sub> = 250.00

The term  $2 * t_f / b_w * (f_{fe} / f_s)$  is implemented to account for FRP contribution

where  $f = 2 * t_f / b_w$  is FRP ratio (EC8 - 3, A.4.4.3(6)) and  $f_{fe} / f_s$  normalises  $f$  to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation  $f_s$  of jacket is used.

NUD = 17779.344

A<sub>g</sub> = 440000.00

f<sub>cE</sub> = (f<sub>c\_jacket</sub> \* Area<sub>jacket</sub> + f<sub>c\_core</sub> \* Area<sub>core</sub>) / section\_area = 30.00

f<sub>yE</sub> = (f<sub>y\_ext\_Long\_Reinf</sub> \* Area<sub>ext\_Long\_Reinf</sub> + f<sub>y\_int\_Long\_Reinf</sub> \* Area<sub>int\_Long\_Reinf</sub>) / Area<sub>Tot\_Long\_Rein</sub> = 625.00

f<sub>ytE</sub> = (f<sub>y\_ext\_Trans\_Reinf</sub> \* s<sub>1</sub> + f<sub>y\_int\_Trans\_Reinf</sub> \* s<sub>2</sub>) / (s<sub>1</sub> + s<sub>2</sub>) = 625.00

$\rho_l = \text{Area}_{\text{Tot\_Long\_Rein}} / (b * d) = 0.01009575$

b = 750.00

d = 707.00

f<sub>cE</sub> = 30.00

-----  
End Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (a)  
-----

**Calculation No. 13**

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjlcs

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of  $\gamma$  for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

Existing Column

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member  
Smooth Bars  
Ductile Steel  
With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
Longitudinal Bars With Ends Lapped Starting at the End Sections  
Lap Length  $l_o = l_b = 300.00$   
No FRP Wrapping

-----  
Stepwise Properties  
-----

EDGE -A-  
Bending Moment,  $M_a = -2.3128E+007$   
Shear Force,  $V_a = -7609.421$   
EDGE -B-  
Bending Moment,  $M_b = 293212.583$   
Shear Force,  $V_b = 7609.421$   
BOTH EDGES  
Axial Force,  $F = -17779.344$   
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension:  $A_{st} = 0.00$   
-Compression:  $A_{sc} = 5353.274$   
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension:  $A_{s,ten} = 1137.257$   
-Compression:  $A_{s,com} = 2208.54$   
-Middle:  $A_{s,mid} = 2007.478$   
Mean Diameter of Tension Reinforcement,  $Db_{L,ten} = 16.80$

-----  
New component: From table 7-7, ASCE 41\_17: Final Shear Capacity  $V_R = 1.0 * V_n = 984866.462$   
 $V_n$  ((10.3), ASCE 41-17) =  $k_n l * V_{CoI} = 984866.462$   
 $V_{CoI} = 984866.462$   
 $k_n = 1.00$   
 $displacement\_ductility\_demand = 0.12420401$

-----  
NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
= 1 (normal-weight concrete)  
Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 20.00$ , but  $f_c'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)  
 $M / V_d = 2.00$   
 $M_u = 293212.583$   
 $V_u = 7609.421$   
 $d = 0.8 * h = 600.00$   
 $N_u = 17779.344$   
 $A_g = 300000.00$   
From (11.5.4.8), ACI 318-14:  $V_s = V_{sjacket} + V_{s,core} = 811033.559$   
where:  
 $V_{sjacket} = V_{sj1} + V_{sj2} = 722566.31$   
 $V_{sj1} = 251327.412$  is calculated for section web jacket, with:  
 $d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$   
 $V_{sj1}$  is multiplied by  $Col_{j1} = 1.00$   
 $s/d = 0.3125$   
 $V_{sj2} = 471238.898$  is calculated for section flange jacket, with:  
 $d = 600.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$   
 $V_{sj2}$  is multiplied by  $Col_{j2} = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 88467.249$

$V_{s,c1} = 0.00$  is calculated for section web core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 500.00$$

$$s = 250.00$$

$V_{s,c1}$  is multiplied by  $Col,c1 = 0.00$

$$s/d = 1.5625$$

$V_{s,c2} = 88467.249$  is calculated for section flange core, with:

$$d = 440.00$$

$$A_v = 100530.965$$

$$f_y = 500.00$$

$$s = 250.00$$

$V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$

$$s/d = 0.56818182$$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 713005.69$

$$bw = 400.00$$

displacement ductility demand is calculated as  $\phi / y$

- Calculation of  $\phi / y$  for END B -

for rotation axis 3 and integ. section (b)

From analysis, chord rotation  $= 2.4490984E-005$

$$y = (M_y * L_s / 3) / E_{eff} = 0.00019718 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 2.8709E+008$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 300.00$$

$$\text{From table 10.5, ASCE 41_17: } E_{eff} = \text{factor} * E_c * I_g = 1.4560E+014$$

$$\text{factor} = 0.30$$

$$A_g = 440000.00$$

$$\text{Mean concrete strength: } f_c' = (f_c'_{\text{jacket}} * A_{\text{jacket}} + f_c'_{\text{core}} * A_{\text{core}}) / A_{\text{section}} = 30.00$$

$$N = 17779.344$$

$$E_c * I_g = E_c_{\text{jacket}} * I_{g_{\text{jacket}}} + E_c_{\text{core}} * I_{g_{\text{core}}} = 4.8532E+014$$

Calculation of Yielding Moment  $M_y$

Calculation of  $\phi / y$  and  $M_y$  according to Annex 7 -

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$

web width,  $bw = 400.00$

flange thickness,  $t = 400.00$

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 2.1455196E-006$$

$$\text{with ((10.1), ASCE 41-17) } f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 243.3535$$

$$d = 707.00$$

$$y = 0.19784983$$

$$A = 0.01023354$$

$$B = 0.00454395$$

$$\text{with } pt = 0.00214476$$

$$pc = 0.00416509$$

$$pv = 0.00378591$$

$$N = 17779.344$$

$$b = 750.00$$

$$" = 0.06082037$$

$$y_{\text{comp}} = 1.5202265E-005$$

with  $f_c = 30.00$

$$E_c = 25742.96$$

$$y = 0.19516753$$

$$A = 0.01001583$$

$$B = 0.00440616$$

$$\text{with } E_s = 200000.00$$

CONFIRMATION:  $y = 0.19594836 < t/d$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_d/l_{d,min} = 0.17384865$

$l_b = 300.00$

$l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

$= 1$

$d_b = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$c_b = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

End Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (b)

## Calculation No. 14

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity ( $\mu$ )

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1

At Shear local axis: 3  
(Bending local axis: 2)  
Section Type: rcjlc

Constant Properties

Knowledge Factor,  $\gamma = 1.00$   
Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,  
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = 300.00$

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force,  $V_a = -0.00017144$

EDGE -B-

Shear Force,  $V_b = 0.00017144$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{sl} = 0.00$

-Compression:  $A_{slc} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten} = 1137.257$

-Compression:  $A_{sl,com} = 2208.54$

-Middle:  $A_{sl,mid} = 2007.478$

Calculation of Shear Capacity ratio ,  $V_e/V_r = 0.32266369$

Member Controlled by Flexure ( $V_e/V_r < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$

with  
 $M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 5.0296E+008$   
 $M_{u1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination  
 $M_{u1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination  
 $M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 5.0296E+008$   
 $M_{u2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination  
 $M_{u2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

-----  
Calculation of  $M_{u1+}$   
-----

-----  
Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 4.8099118E-006$

$M_u = 2.3387E+008$   
-----

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\alpha_1$  (5A.5, TBDY) = 0.002

Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} * \text{Max}(\phi_u, \phi_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\phi_u = 0.01260361$

$\phi_w$  (5.4c) = 0.05179731

$\alpha_{se}$  ((5.4d), TBDY) =  $(\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.45746528$

$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\alpha_{se2} (> \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\phi_{sh,min} * F_{ywe} = \text{Min}(\phi_{sh,x} * F_{ywe}, \phi_{sh,y} * F_{ywe}) = 3.3968$   
-----

$\phi_{sh,x} * F_{ywe} = \phi_{sh1} * F_{ywe1} + \phi_{sh2} * F_{ywe2} = 3.3968$

$\phi_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

psh2 (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

psh\_y \* Fywe = psh1 \* Fywe1 + ps2 \* Fywe2 = 3.3968  
psh1 ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
psh2 ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb = 0.13907892

su1 =  $0.4 * esu1\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1, ft1, fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $Min(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with Es1 =  $(Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 =  $0.4 * esu2\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2, ft2, fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $Min(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with Es2 =  $(Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb = 0.13907892

suv =  $0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY  
For calculation of esuv\_nominal and yv, shv, ftv, fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $Min(1, 1.25 * (lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{sv} = (f_s \cdot j_{\text{jacket}} \cdot A_{sl, \text{mid, jacket}} + f_s \cdot \text{mid} \cdot A_{sl, \text{mid, core}}) / A_{sl, \text{mid}} = 262.1446$   
with  $E_{sv} = (E_s \cdot j_{\text{jacket}} \cdot A_{sl, \text{mid, jacket}} + E_s \cdot \text{mid} \cdot A_{sl, \text{mid, core}}) / A_{sl, \text{mid}} = 200000.00$   
 $1 = A_{sl, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.0187412$   
 $2 = A_{sl, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03639521$   
 $v = A_{sl, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03308184$

and confined core properties:

$b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, \text{TBDY}) = 38.13135$   
 $cc (5A.5, \text{TBDY}) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02127357$   
 $2 = A_{sl, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04131304$   
 $v = A_{sl, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.21062322$   
 $Mu = MRc (4.14) = 2.3387E+008$   
 $u = su (4.1) = 4.8099118E-006$

-----  
Calculation of ratio  $l_b / l_d$

Lap Length:  $l_b / l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_b, \text{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \text{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

-----  
Calculation of  $Mu_1$ -

-----  
Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$u = 5.1201636E-006$

$Mu = 5.0296E+008$

-----  
with full section properties:

$b = 400.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00191815$

$N = 16273.608$

$f_c = 30.00$

$cc (5A.5, \text{TBDY}) = 0.002$

Final value of  $\phi_u$ :  $\phi_u^* = \text{shear\_factor} \cdot \text{Max}(\phi_u, cc) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $c_u = 0.01260361$

$w_e$  (5.4c) = 0.05179731

$a_{se}$  ((5.4d), TBDY) =  $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$

$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

-----  
 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $c_c = 0.00471045$

$c$  = confinement factor = 1.27105

$y_1 = 0.00083886$

$sh_1 = 0.00268436$

$ft_1 = 314.5735$

$fy_1 = 262.1446$

$su_1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o / l_{ou,min} = l_b / l_d = 0.13907892$

$su_1 = 0.4 * esu_1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu_1_{nominal} = 0.08$ ,

For calculation of  $esu_1_{nominal}$  and  $y_1$ ,  $sh_1$ ,  $ft_1$ ,  $fy_1$ , it is considered characteristic value  $fsy_1 = fs_1 / 1.2$ , from table 5.1, TBDY.

$y_1$ ,  $sh_1$ ,  $ft_1$ ,  $fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_{\text{jacket}} \cdot Asl_{\text{ten,jacket}} + fs_{\text{core}} \cdot Asl_{\text{ten,core}}) / Asl_{\text{ten}} = 262.1446$$

$$\text{with } Es1 = (Es_{\text{jacket}} \cdot Asl_{\text{ten,jacket}} + Es_{\text{core}} \cdot Asl_{\text{ten,core}}) / Asl_{\text{ten}} = 200000.00$$

$$y2 = 0.00083886$$

$$sh2 = 0.00268436$$

$$ft2 = 314.5735$$

$$fy2 = 262.1446$$

$$su2 = 0.00268436$$
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  

$$lo/lo_{\text{min}} = lb/lb_{\text{min}} = 0.13907892$$

$$su2 = 0.4 \cdot esu2_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$
 From table 5A.1, TBDY:  $esu2_{\text{nominal}} = 0.08$ ,  
 For calculation of  $esu2_{\text{nominal}}$  and  $y2, sh2, ft2, fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  

$$\text{with } fs2 = (fs_{\text{jacket}} \cdot Asl_{\text{com,jacket}} + fs_{\text{core}} \cdot Asl_{\text{com,core}}) / Asl_{\text{com}} = 262.1446$$

$$\text{with } Es2 = (Es_{\text{jacket}} \cdot Asl_{\text{com,jacket}} + Es_{\text{core}} \cdot Asl_{\text{com,core}}) / Asl_{\text{com}} = 200000.00$$

$$yv = 0.00083886$$

$$shv = 0.00268436$$

$$ftv = 314.5735$$

$$fyv = 262.1446$$

$$suv = 0.00268436$$
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  

$$lo/lo_{\text{min}} = lb/ld = 0.13907892$$

$$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$
 From table 5A.1, TBDY:  $esuv_{\text{nominal}} = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv_{\text{nominal}}$  and  $yv, shv, ftv, fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  

$$\text{with } fsv = (fs_{\text{jacket}} \cdot Asl_{\text{mid,jacket}} + fs_{\text{mid}} \cdot Asl_{\text{mid,core}}) / Asl_{\text{mid}} = 262.1446$$

$$\text{with } Esv = (Es_{\text{jacket}} \cdot Asl_{\text{mid,jacket}} + Es_{\text{mid}} \cdot Asl_{\text{mid,core}}) / Asl_{\text{mid}} = 200000.00$$

$$1 = Asl_{\text{ten}} / (b \cdot d) \cdot (fs1 / fc) = 0.06824101$$

$$2 = Asl_{\text{com}} / (b \cdot d) \cdot (fs2 / fc) = 0.03513975$$

$$v = Asl_{\text{mid}} / (b \cdot d) \cdot (fsv / fc) = 0.06202846$$

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc$  (5A.2, TBDY) = 38.13135  
 $cc$  (5A.5, TBDY) = 0.00471045  
 $c$  = confinement factor = 1.27105  
 $1 = Asl_{\text{ten}} / (b \cdot d) \cdot (fs1 / fc) = 0.08384116$   
 $2 = Asl_{\text{com}} / (b \cdot d) \cdot (fs2 / fc) = 0.04317283$   
 $v = Asl_{\text{mid}} / (b \cdot d) \cdot (fsv / fc) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < vs, y2$  - LHS eq.(4.5) is satisfied  
 --->  
 $su$  (4.9) = 0.2584548  
 $Mu = MRc$  (4.14) = 5.0296E+008  
 $u = su$  (4.1) = 5.1201636E-006

-----  
 Calculation of ratio  $lb/ld$   
 -----

$Lap\ Length: lb/ld = 0.13907892$   
 $lb = 300.00$   
 $ld = 2157.049$   
 Calculation of  $lb_{\text{min}}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $ld_{\text{min}}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$   
Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
-----  
-----  
Calculation of  $\mu_{2+}$   
-----

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 4.8099118E-006$$

$$\mu_u = 2.3387E+008$$

-----  
with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_u: \mu_u^* = \text{shear\_factor} \cdot \text{Max}(\mu_u, \mu_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_u = 0.01260361$$

$$\mu_{ue} \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) \cdot (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) \cdot (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} \cdot F_{ywe} = \text{Min}(p_{sh,x} \cdot F_{ywe}, p_{sh,y} \cdot F_{ywe}) = 3.3968$$

$$p_{sh_x} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} \cdot A_{stir1} / (A_{sec} \cdot s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} \cdot A_{stir2} / (A_{sec} \cdot s2) = 0.00067082$$

Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

psh<sub>y</sub>\*Fywe = psh<sub>1</sub>\*Fywe<sub>1</sub>+ps<sub>2</sub>\*Fywe<sub>2</sub> = 3.3968  
psh<sub>1</sub> ((5.4d), TBDY) = Lstir<sub>1</sub>\*Astir<sub>1</sub>/(Asec\*s<sub>1</sub>) = 0.00367709  
Lstir<sub>1</sub> (Length of stirrups along X) = 2060.00  
Astir<sub>1</sub> (stirrups area) = 78.53982  
psh<sub>2</sub> ((5.4d), TBDY) = Lstir<sub>2</sub>\*Astir<sub>2</sub>/(Asec\*s<sub>2</sub>) = 0.00067082  
Lstir<sub>2</sub> (Length of stirrups along X) = 1468.00  
Astir<sub>2</sub> (stirrups area) = 50.26548

Asec = 440000.00  
s<sub>1</sub> = 100.00  
s<sub>2</sub> = 250.00

fywe<sub>1</sub> = 781.25  
fywe<sub>2</sub> = 781.25  
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y<sub>1</sub> = 0.00083886  
sh<sub>1</sub> = 0.00268436  
ft<sub>1</sub> = 314.5735  
fy<sub>1</sub> = 262.1446

su<sub>1</sub> = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>d</sub> = 0.13907892

su<sub>1</sub> = 0.4\*esu<sub>1\_nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu<sub>1\_nominal</sub> = 0.08,

For calculation of esu<sub>1\_nominal</sub> and y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, it is considered  
characteristic value fsy<sub>1</sub> = fs<sub>1</sub>/1.2, from table 5.1, TBDY.

y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>1</sub> = (fs<sub>jacket</sub>\*Asl<sub>ten,jacket</sub> + fs<sub>core</sub>\*Asl<sub>ten,core</sub>)/Asl<sub>ten</sub> = 262.1446

with Es<sub>1</sub> = (Es<sub>jacket</sub>\*Asl<sub>ten,jacket</sub> + Es<sub>core</sub>\*Asl<sub>ten,core</sub>)/Asl<sub>ten</sub> = 200000.00

y<sub>2</sub> = 0.00083886

sh<sub>2</sub> = 0.00268436

ft<sub>2</sub> = 314.5735

fy<sub>2</sub> = 262.1446

su<sub>2</sub> = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>b,min</sub> = 0.13907892

su<sub>2</sub> = 0.4\*esu<sub>2\_nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu<sub>2\_nominal</sub> = 0.08,

For calculation of esu<sub>2\_nominal</sub> and y<sub>2</sub>, sh<sub>2</sub>,ft<sub>2</sub>,fy<sub>2</sub>, it is considered  
characteristic value fsy<sub>2</sub> = fs<sub>2</sub>/1.2, from table 5.1, TBDY.

y<sub>2</sub>, sh<sub>2</sub>,ft<sub>2</sub>,fy<sub>2</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>2</sub> = (fs<sub>jacket</sub>\*Asl<sub>com,jacket</sub> + fs<sub>core</sub>\*Asl<sub>com,core</sub>)/Asl<sub>com</sub> = 262.1446

with Es<sub>2</sub> = (Es<sub>jacket</sub>\*Asl<sub>com,jacket</sub> + Es<sub>core</sub>\*Asl<sub>com,core</sub>)/Asl<sub>com</sub> = 200000.00

y<sub>v</sub> = 0.00083886

sh<sub>v</sub> = 0.00268436

ft<sub>v</sub> = 314.5735

fy<sub>v</sub> = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/l<sub>d</sub> = 0.13907892

suv = 0.4\*esuv<sub>nominal</sub> ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv<sub>nominal</sub> = 0.08,

considering characteristic value fsy<sub>v</sub> = fs<sub>v</sub>/1.2, from table 5.1, TBDY  
For calculation of esuv<sub>nominal</sub> and y<sub>v</sub>, sh<sub>v</sub>,ft<sub>v</sub>,fy<sub>v</sub>, it is considered

characteristic value fsy<sub>v</sub> = fs<sub>v</sub>/1.2, from table 5.1, TBDY.

y<sub>1</sub>, sh<sub>1</sub>,ft<sub>1</sub>,fy<sub>1</sub>, are also multiplied by Min(1,1.25\*(lb/l<sub>d</sub>)<sup>2/3</sup>), from 10.3.5, ASCE 41-17.

with fs<sub>v</sub> = (fs<sub>jacket</sub>\*Asl<sub>mid,jacket</sub> + fs<sub>mid</sub>\*Asl<sub>mid,core</sub>)/Asl<sub>mid</sub> = 262.1446

$$\text{with } E_{sv} = (E_{s,jacket} \cdot A_{sl,mid,jacket} + E_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.0187412$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03639521$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03308184$$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 38.13135$$

$$c_c (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.02127357$$

$$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04131304$$

$$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.21062322$$

$$\mu_u = M_{Rc} (4.14) = 2.3387E+008$$

$$u = s_u (4.1) = 4.8099118E-006$$

-----  
Calculation of ratio  $l_b/d$

-----  
Lap Length:  $l_b/d = 0.13907892$

$$l_b = 300.00$$

$$d = 2157.049$$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr,x}, A_{tr,y}) = 257.6106$$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $\mu_{u2}$ -

-----  
Calculation of ultimate curvature  $\mu_u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$\mu_u = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} \cdot \text{Max}(c_u, c_o) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e (5.4c) = 0.05179731$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From } ((5.A.5), TBDY), TBDY: c_c = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$y1 = 0.00083886$$

$$sh1 = 0.00268436$$

$$ft1 = 314.5735$$

$$fy1 = 262.1446$$

$$su1 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$$l_o / l_{ou,min} = l_b / l_d = 0.13907892$$

$$su1 = 0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , it is considered

characteristic value  $fsy1 = fs1 / 1.2$ , from table 5.1, TBDY.

$y1$ ,  $sh1$ ,  $ft1$ ,  $fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$$

with  $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$   
 $y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_0/l_{ou,min} = l_b/l_{b,min} = 0.13907892$   
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{2,nominal} = 0.08$ ,  
 For calculation of  $esu_{2,nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
 characteristic value  $fs_2 = fs_2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_2 = (fs_{jacket} \cdot A_{s,com,jacket} + fs_{core} \cdot A_{s,com,core}) / A_{s,com} = 262.1446$   
 with  $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $su_v = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_0/l_{ou,min} = l_b/l_d = 0.13907892$   
 $su_v = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv_{nominal} = 0.08$ ,  
 considering characteristic value  $fs_v = fs_v/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv_{nominal}$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fs_v = fs_v/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_v = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 262.1446$   
 with  $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$   
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.06824101$   
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.03513975$   
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / fc) = 0.06202846$

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.08384116$   
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.04317283$   
 $v = A_{s,mid} / (b \cdot d) \cdot (fs_v / fc) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_s, y_2$  - LHS eq.(4.5) is satisfied

---->

$su (4.9) = 0.2584548$   
 $M_u = MR_c (4.14) = 5.0296E+008$   
 $u = su (4.1) = 5.1201636E-006$

-----  
 Calculation of ratio  $l_b/l_d$

-----  
 Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

-----  
Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392E+006$

-----  
Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392E+006$

$V_{r1} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{ColO}}$

$V_{\text{ColO}} = 1.0392E+006$

$k_{nl} = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $f = 1$  (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M/d = 4.00$

$M_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 \cdot h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,\text{jacket}} + V_{s,\text{core}} = 1.0138E+006$

where:

$V_{s,\text{jacket}} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$

$s/d = 0.3125$

$V_{s,\text{core}} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$

$s/d = 1.5625$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
 $bw = 400.00$

Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392E+006$   
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$   
 $V_{Col0} = 1.0392E+006$   
 $knl = 1$  (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

$= 1$  (normal-weight concrete)  
Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$M / Vd = 4.00$

$\mu_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 * h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{sjacket} + V_{s,core} = 1.0138E+006$

where:

$V_{sjacket} = V_{sj1} + V_{sj2} = 903207.888$

$V_{sj1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{sj1}$  is multiplied by  $Col_{j1} = 1.00$

$s/d = 0.16666667$

$V_{sj2} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{sj2}$  is multiplied by  $Col_{j2} = 1.00$

$s/d = 0.3125$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $Col_{c1} = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $Col_{c2} = 0.00$

$s/d = 1.5625$

$V_f ((11-3)-(11.4), ACI 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$bw = 400.00$

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At Shear local axis: 2  
(Bending local axis: 3)

Section Type: rcjics

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Mean Confinement Factor overall section = 1.27105

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = 300.00$

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force,  $V_a = -0.0001715$

EDGE -B-

Shear Force,  $V_b = 0.0001715$

BOTH EDGES

Axial Force,  $F = -16273.608$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{st} = 0.00$

-Compression:  $A_{sc} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{st,ten} = 1137.257$

-Compression:  $A_{sc,com} = 2208.54$

-Middle:  $A_{st,mid} = 2007.478$

Calculation of Shear Capacity ratio,  $V_e/V_r = 0.32266369$

Member Controlled by Flexure ( $V_e/V_r < 1$ )

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 5.0296E+008$

$\mu_{1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$\mu_{1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 5.0296E+008$

$\mu_{2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

-----  
Calculation of  $\mu_{1+}$   
-----

-----  
Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 4.8099118E-006$

$M_u = 2.3387E+008$   
-----

with full section properties:

$b = 750.00$

$d = 707.00$

$d' = 43.00$

$v = 0.00102301$

$N = 16273.608$

$f_c = 30.00$

$\phi_{co} (5A.5, \text{TBDY}) = 0.002$

Final value of  $\phi_{cu}$ :  $\phi_{cu}^* = \text{shear\_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY:  $\phi_{cu} = 0.01260361$

$\omega_e (5.4c) = 0.05179731$

$\omega_{ase} ((5.4d), \text{TBDY}) = (\omega_{ase1} * A_{ext} + \omega_{ase2} * A_{int}) / A_{sec} = 0.45746528$

$\omega_{ase1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\omega_{ase2} (> \omega_{ase1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\phi_{psh,min} * F_{ywe} = \text{Min}(\phi_{psh,x} * F_{ywe}, \phi_{psh,y} * F_{ywe}) = 3.3968$   
-----

$\phi_{psh,x} * F_{ywe} = \phi_{psh1} * F_{ywe1} + \phi_{psh2} * F_{ywe2} = 3.3968$

$\phi_{psh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$\phi_{psh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548  
-----

$\phi_{psh,y} * F_{ywe} = \phi_{psh1} * F_{ywe1} + \phi_{psh2} * F_{ywe2} = 3.3968$

psh1 ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
psh2 ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

su1 =  $0.4 * esu1\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(fs\_jacket * A_{sl,ten,jacket} + fs\_core * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with Es1 =  $(Es\_jacket * A_{sl,ten,jacket} + Es\_core * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 =  $0.4 * esu2\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 =  $(fs\_jacket * A_{sl,com,jacket} + fs\_core * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with Es2 =  $(Es\_jacket * A_{sl,com,jacket} + Es\_core * A_{sl,com,core}) / A_{sl,com} = 200000.00$

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

suv =  $0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv =  $(fs\_jacket * A_{sl,mid,jacket} + fs\_mid * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$

with Esv =  $(Es\_jacket * A_{sl,mid,jacket} + Es\_mid * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

1 =  $A_{sl,ten} / (b * d) * (fs1 / fc) = 0.0187412$

2 =  $A_{sl,com} / (b * d) * (fs2 / fc) = 0.03639521$

v =  $A_{sl,mid} / (b * d) * (fsv / fc) = 0.03308184$

and confined core properties:

$$b = 690.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc \text{ (5A.2, TBDY)} = 38.13135$$

$$cc \text{ (5A.5, TBDY)} = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten}/(b*d)*(fs1/fc) = 0.02127357$$

$$2 = A_{sl,com}/(b*d)*(fs2/fc) = 0.04131304$$

$$v = A_{sl,mid}/(b*d)*(fsv/fc) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u \text{ (4.9)} = 0.21062322$$

$$M_u = MR_c \text{ (4.14)} = 2.3387E+008$$

$$u = s_u \text{ (4.1)} = 4.8099118E-006$$

Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of  $M_u1$ -

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

Final value of  $c_u$ :  $c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$ase2 (>= ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

-----  
 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.3968$

$p_{sh1}$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$p_{sh2}$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c =$  confinement factor = 1.27105

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

$l_o / l_{ou,min} = l_b / l_d = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered

characteristic value  $fsy1 = fs1 / 1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 262.1446$

with  $Es1 = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$f_y2 = 262.1446$   
 $s_u2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{o,min} = l_b/l_{b,min} = 0.13907892$   
 $s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $e_{su2,nominal} = 0.08$ ,  
 For calculation of  $e_{su2,nominal}$  and  $y_2, sh_2, ft_2, f_y2$ , it is considered  
 characteristic value  $f_{sy2} = f_s2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, f_y1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 262.1446$   
 with  $E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $f_{y_v} = 262.1446$   
 $s_{u_v} = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 Shear\_factor = 1.00  
 $l_o/l_{o,min} = l_b/l_d = 0.13907892$   
 $s_{u_v} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $e_{suv,nominal} = 0.08$ ,  
 considering characteristic value  $f_{syv} = f_{sv}/1.2$ , from table 5.1, TBDY  
 For calculation of  $e_{suv,nominal}$  and  $y_v, sh_v, ft_v, f_{y_v}$ , it is considered  
 characteristic value  $f_{syv} = f_{sv}/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, f_y1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $f_{sv} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 262.1446$   
 with  $E_{sv} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$   
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.06824101$   
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.03513975$   
 $v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.06202846$   
 and confined core properties:  
 $b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $c_c (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.08384116$   
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.04317283$   
 $v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.07620839$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)  
 --->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied  
 --->  
 $s_u (4.9) = 0.2584548$   
 $M_u = M_{Rc} (4.14) = 5.0296E+008$   
 $u = s_u (4.1) = 5.1201636E-006$

---

Calculation of ratio  $l_b/l_d$

---

Lap Length:  $l_b/l_d = 0.13907892$   
 $l_b = 300.00$   
 $l_d = 2157.049$   
 Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$   
 Mean strength value of all re-bars:  $f_y = 781.25$   
 Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$

$e = 1.00$   
 $cb = 25.00$   
 $Ktr = 1.7174$   
 $Atr = \text{Min}(Atr_x, Atr_y) = 257.6106$   
 where  $Atr_x, Atr_y$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$   
 $n = 24.00$

-----  
 Calculation of  $\mu_{2+}$   
 -----

-----  
 Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:  
 $\mu = 4.8099118E-006$   
 $\mu_{2+} = 2.3387E+008$   
 -----

with full section properties:

$b = 750.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00102301$   
 $N = 16273.608$   
 $f_c = 30.00$   
 $\alpha_{\text{co}} (5A.5, \text{TBDY}) = 0.002$

Final value of  $\mu_{cu}$ :  $\mu_{cu}^* = \text{shear\_factor} * \text{Max}(\mu_{cu}, \mu_{cc}) = 0.01260361$   
 The Shear\_factor is considered equal to 1 (pure moment strength)  
 From (5.4b), TBDY:  $\mu_{cu} = 0.01260361$

we (5.4c) = 0.05179731

$\alpha_{\text{se}} ((5.4d), \text{TBDY}) = (\alpha_{\text{se1}} * A_{\text{ext}} + \alpha_{\text{se2}} * A_{\text{int}}) / A_{\text{sec}} = 0.45746528$

$\alpha_{\text{se1}} = \text{Max}(((A_{\text{conf,max1}} - A_{\text{noConf1}}) / A_{\text{conf,max1}}) * (A_{\text{conf,min1}} / A_{\text{conf,max1}}), 0) = 0.45746528$

The definitions of  $A_{\text{noConf}}$ ,  $A_{\text{conf,min}}$  and  $A_{\text{conf,max}}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max1}} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{\text{conf,min1}} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{\text{conf,max1}}$  by a length equal to half the clear spacing between external hoops.

$A_{\text{noConf1}} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\alpha_{\text{se2}} (> \alpha_{\text{se1}}) = \text{Max}(((A_{\text{conf,max2}} - A_{\text{noConf2}}) / A_{\text{conf,max2}}) * (A_{\text{conf,min2}} / A_{\text{conf,max2}}), 0) = 0.45746528$

The definitions of  $A_{\text{noConf}}$ ,  $A_{\text{conf,min}}$  and  $A_{\text{conf,max}}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max2}} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{\text{conf,min2}} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{\text{conf,max2}}$  by a length equal to half the clear spacing between internal hoops.

$A_{\text{noConf2}} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$\text{psh}_{\text{min}} * F_{ywe} = \text{Min}(\text{psh}_x * F_{ywe}, \text{psh}_y * F_{ywe}) = 3.3968$

-----  
 $\text{psh}_x * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 3.3968$

$\text{psh}_1 ((5.4d), \text{TBDY}) = L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s_1) = 0.00367709$

$L_{\text{stir1}}$  (Length of stirrups along Y) = 2060.00

$A_{\text{stir1}}$  (stirrups area) = 78.53982

$\text{psh}_2 (5.4d) = L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s_2) = 0.00067082$

$L_{\text{stir2}}$  (Length of stirrups along Y) = 1468.00

$A_{\text{stir2}}$  (stirrups area) = 50.26548

-----  
 $\text{psh}_y * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 3.3968$

$\text{psh}_1 ((5.4d), \text{TBDY}) = L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s_1) = 0.00367709$

Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
psh2 ((5.4d), TBDY) = Lstir2\*Astir2/(Asec\*s2) = 0.00067082  
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

-----  
Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886

shv = 0.00268436

ftv = 314.5735

fyv = 262.1446

suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.0187412

2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03639521

v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03308184

and confined core properties:

$b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.02127357$   
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.04131304$   
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.03755196$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)

--->  
 $v < v_{s,y2}$  - LHS eq.(4.5) is satisfied  
 --->  
 $su (4.9) = 0.21062322$   
 $Mu = MRc (4.14) = 2.3387E+008$   
 $u = su (4.1) = 4.8099118E-006$

-----  
 Calculation of ratio  $l_b/l_d$

-----  
 Lap Length:  $l_b/l_d = 0.13907892$   
 $l_b = 300.00$   
 $l_d = 2157.049$   
 Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 $= 1$   
 $db = 16.66667$   
 Mean strength value of all re-bars:  $f_y = 781.25$   
 Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$   
 MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$   
 $e = 1.00$   
 $cb = 25.00$   
 $K_{tr} = 1.7174$   
 $A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$   
 where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{external}, s_{internal}) = 250.00$   
 $n = 24.00$

-----  
 Calculation of  $Mu_2$ -

-----  
 Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:  
 $u = 5.1201636E-006$   
 $Mu = 5.0296E+008$

-----  
 with full section properties:

$b = 400.00$   
 $d = 707.00$   
 $d' = 43.00$   
 $v = 0.00191815$   
 $N = 16273.608$   
 $f_c = 30.00$   
 $co (5A.5, TBDY) = 0.002$   
 Final value of  $cu$ :  $cu^* = \text{shear\_factor} * \text{Max}(cu, cc) = 0.01260361$   
 The Shear\_factor is considered equal to 1 (pure moment strength)  
 From (5.4b), TBDY:  $cu = 0.01260361$   
 $we (5.4c) = 0.05179731$   
 $ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$   
 $ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$   
 The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization  
 of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)  
"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max1 = 353600.00 is the confined core area at levels of member with hoops and  
is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

Aconf,min1 = 293525.00 is the confined core area at midway between the levels of hoops and  
is calculated by reducing all the dimensions of the area Aconf,max1 by a length  
equal to half the clear spacing between external hoops.

AnoConf1 = 158733.333 is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
ase2 ( $\geq$  ase1) =  $\text{Max}(((A_{\text{conf,max2}} - A_{\text{noConf2}})/A_{\text{conf,max2}}) * (A_{\text{conf,min2}}/A_{\text{conf,max2}}), 0) = 0.45746528$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization  
of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)  
"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 171264.00 is the confined core area at levels of member with hoops and  
is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 54741.00 is the confined core area at midway between the levels of hoops and  
is calculated by reducing all the dimensions of the area Aconf,max2 by a length  
equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
psh,min\*Fywe =  $\text{Min}(psh_x * Fywe, psh_y * Fywe) = 3.3968$

psh\_x\*Fywe = psh1\*Fywe1 + ps2\*Fywe2 = 3.3968

psh1 ((5.4d), TBDY) =  $L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s_1) = 0.00367709$

Lstir1 (Length of stirrups along Y) = 2060.00

Astir1 (stirrups area) = 78.53982

psh2 (5.4d) =  $L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s_2) = 0.00067082$

Lstir2 (Length of stirrups along Y) = 1468.00

Astir2 (stirrups area) = 50.26548

psh\_y\*Fywe = psh1\*Fywe1 + ps2\*Fywe2 = 3.3968

psh1 ((5.4d), TBDY) =  $L_{\text{stir1}} * A_{\text{stir1}} / (A_{\text{sec}} * s_1) = 0.00367709$

Lstir1 (Length of stirrups along X) = 2060.00

Astir1 (stirrups area) = 78.53982

psh2 ((5.4d), TBDY) =  $L_{\text{stir2}} * A_{\text{stir2}} / (A_{\text{sec}} * s_2) = 0.00067082$

Lstir2 (Length of stirrups along X) = 1468.00

Astir2 (stirrups area) = 50.26548

Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

su1 =  $0.4 * e_{s1\_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1, ft1, fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 =  $(f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 262.1446$

with Es1 =  $(E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

$$su_2 = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.13907892$$

$$su_2 = 0.4 * esu_2,nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu\_2,nominal = 0.08,

For calculation of esu\_2,nominal and  $y_2$ , sh\_2,ft\_2,fy\_2, it is considered  
characteristic value fsy\_2 = fs\_2/1.2, from table 5.1, TBDY.

$y_1$ , sh\_1,ft\_1,fy\_1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$yv = 0.00083886$$

$$shv = 0.00268436$$

$$ftv = 314.5735$$

$$fyv = 262.1446$$

$$suv = 0.00268436$$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$$lo/lou,min = lb/d = 0.13907892$$

$$suv = 0.4 * esuv,nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv,nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv,nominal and  $y_v$ , shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

$y_1$ , sh\_1,ft\_1,fy\_1, are also multiplied by  $\text{Min}(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 262.1446$$

$$\text{with } Esv = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / fc) = 0.06824101$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / fc) = 0.03513975$$

$$v = A_{sl,mid} / (b * d) * (fsv / fc) = 0.06202846$$

and confined core properties:

$$b = 340.00$$

$$d = 677.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 38.13135$$

$$cc (5A.5, TBDY) = 0.00471045$$

$$c = \text{confinement factor} = 1.27105$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / fc) = 0.08384116$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / fc) = 0.04317283$$

$$v = A_{sl,mid} / (b * d) * (fsv / fc) = 0.07620839$$

Case/Assumption: Unconfined full section - Steel rupture  
' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.2584548$$

$$\mu = MRc (4.14) = 5.0296E+008$$

$$u = su (4.1) = 5.1201636E-006$$

-----  
Calculation of ratio lb/d

Lap Length: lb/d = 0.13907892

$$lb = 300.00$$

$$ld = 2157.049$$

Calculation of lb,min according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

ld,min from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$db = 16.66667$$

Mean strength value of all re-bars: fy = 781.25

Mean concrete strength: fc' = (fc'\_jacket \* Area\_jacket + fc'\_core \* Area\_core) / Area\_section = 30.00, but  $fc'^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$cb = 25.00$$

$$Ktr = 1.7174$$

$$Atr = \text{Min}(Atr_x, Atr_y) = 257.6106$$

where  $Atr_x, Atr_y$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

$$\text{Calculation of Shear Strength } Vr = \text{Min}(Vr1, Vr2) = 1.0392E+006$$

$$\text{Calculation of Shear Strength at edge 1, } Vr1 = 1.0392E+006$$

$$Vr1 = VCol \text{ ((10.3), ASCE 41-17)} = knl * VCol0$$

$$VCol0 = 1.0392E+006$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $Vs = Av * fy * d / s$ ' is replaced by ' $Vs + f * Vf$ ' where  $Vf$  is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } fc' = (fc'_{\text{jacket}} * Area_{\text{jacket}} + fc'_{\text{core}} * Area_{\text{core}}) / Area_{\text{section}} = 30.00, \text{ but } fc'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 4.00$$

$$Mu = 1308.675$$

$$Vu = 0.0001715$$

$$d = 0.8 * h = 600.00$$

$$Nu = 16273.608$$

$$Ag = 300000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } Vs = Vs_{\text{jacket}} + Vs_{\text{core}} = 1.0138E+006$$

where:

$$Vs_{\text{jacket}} = Vs_{j1} + Vs_{j2} = 903207.888$$

$Vs_{j1} = 314159.265$  is calculated for section web jacket, with:

$$d = 320.00$$

$$Av = 157079.633$$

$$fy = 625.00$$

$$s = 100.00$$

$$Vs_{j1} \text{ is multiplied by } Col_{j1} = 1.00$$

$$s/d = 0.3125$$

$Vs_{j2} = 589048.623$  is calculated for section flange jacket, with:

$$d = 600.00$$

$$Av = 157079.633$$

$$fy = 625.00$$

$$s = 100.00$$

$$Vs_{j2} \text{ is multiplied by } Col_{j2} = 1.00$$

$$s/d = 0.16666667$$

$$Vs_{\text{core}} = Vs_{c1} + Vs_{c2} = 110584.061$$

$Vs_{c1} = 0.00$  is calculated for section web core, with:

$$d = 160.00$$

$$Av = 100530.965$$

$$fy = 625.00$$

$$s = 250.00$$

$$Vs_{c1} \text{ is multiplied by } Col_{c1} = 0.00$$

$$s/d = 1.5625$$

$Vs_{c2} = 110584.061$  is calculated for section flange core, with:

$$d = 440.00$$

$$Av = 100530.965$$

$$fy = 625.00$$

$$s = 250.00$$

$$Vs_{c2} \text{ is multiplied by } Col_{c2} = 1.00$$

$$s/d = 0.56818182$$

$$Vf \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } Vs + Vf \leq 873250.061$$

$$bw = 400.00$$

$$\text{Calculation of Shear Strength at edge 2, } Vr2 = 1.0392E+006$$

Vr2 = VCol ((10.3), ASCE 41-17) = knl\*VCol0

VCol0 = 1.0392E+006

kn1 = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av\*fy\*d/s' is replaced by 'Vs+ f\*Vf'  
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'\_jacket\*Area\_jacket + fc'\_core\*Area\_core)/Area\_section = 30.00, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 1308.675

Vu = 0.0001715

d = 0.8\*h = 600.00

Nu = 16273.608

Ag = 300000.00

From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 1.0138E+006

where:

Vs,jacket = Vs,j1 + Vs,j2 = 903207.888

Vs,j1 = 314159.265 is calculated for section web jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.3125

Vs,j2 = 589048.623 is calculated for section flange jacket, with:

d = 600.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.16666667

Vs,core = Vs,c1 + Vs,c2 = 110584.061

Vs,c1 = 0.00 is calculated for section web core, with:

d = 160.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 0.00

s/d = 1.5625

Vs,c2 = 110584.061 is calculated for section flange core, with:

d = 440.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 1.00

s/d = 0.56818182

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 873250.061

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1  
At local axis: 2  
Integration Section: (b)  
Section Type: rcjics

Constant Properties

Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_b = 300.00$

No FRP Wrapping

-----  
Stepwise Properties

Bending Moment,  $M = -178152.624$

Shear Force,  $V_2 = 7609.421$

Shear Force,  $V_3 = -213.4386$

Axial Force,  $F = -17779.344$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension:  $A_{st} = 0.00$

-Compression:  $A_{sc} = 5353.274$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{st,ten} = 1137.257$

-Compression:  $A_{sl,com} = 2208.54$

-Middle:  $A_{sl,mid} = 2007.478$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten,jacket} = 829.3805$

-Compression:  $A_{sl,com,jacket} = 1746.726$

-Middle:  $A_{sl,mid,jacket} = 1545.664$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension:  $A_{sl,ten,core} = 307.8761$

-Compression:  $A_{sl,com,core} = 461.8141$

-Middle:  $A_{sl,mid,core} = 461.8141$

Mean Diameter of Tension Reinforcement,  $DbL = 16.80$

-----  
New component: From table 7-7, ASCE 41\_17: Final chord rotation Capacity  $u_R = 1.0^*$   $u = 0.03952104$

$u = y + p = 0.03952104$

-----  
- Calculation of  $y$  -

$y = (M_y * L_s / 3) / E_{eff} = 0.00054862$  ((4.29), Biskinis Phd))

$M_y = 2.8709E+008$

$L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 834.6784

From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$

factor = 0.30

$A_g = 440000.00$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$

$N = 17779.344$

$E_c \cdot I_g = E_c_{\text{jacket}} \cdot I_{g_{\text{jacket}}} + E_c_{\text{core}} \cdot I_{g_{\text{core}}} = 4.8532E+014$

Calculation of Yielding Moment  $M_y$

Calculation of  $y$  and  $M_y$  according to Annex 7 -

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:

flange width,  $b = 750.00$

web width,  $b_w = 400.00$

flange thickness,  $t = 400.00$

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$

$y_{\text{ten}} = 2.1455196E-006$

with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 243.3535$

$d = 707.00$

$y = 0.19784983$

$A = 0.01023354$

$B = 0.00454395$

with  $pt = 0.00434791$

$pc = 0.00416509$

$pv = 0.00378591$

$N = 17779.344$

$b = 750.00$

$" = 0.06082037$

$y_{\text{comp}} = 1.5202265E-005$

with  $f_c = 30.00$

$E_c = 25742.96$

$y = 0.19516753$

$A = 0.01001583$

$B = 0.00440616$

with  $E_s = 200000.00$

CONFIRMATION:  $y = 0.19594836 < t/d$

Calculation of ratio  $l_b/d$

Lap Length:  $l_d/l_{d,\text{min}} = 0.17384865$

$l_b = 300.00$

$l_d = 1725.639$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,\text{min}}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$

$n = 24.00$

- Calculation of  $\rho$  -

From table 10-8:  $\rho = 0.03897242$

with:

- Columns controlled by inadequate development or splicing along the clear height because  $l_b/l_d < 1$

shear control ratio  $V_y E / V_{Co} I_{OE} = 0.32266369$

$d = d_{external} = 707.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00434791$

jacket:  $s_1 = A_{v1} * L_{stir1} / (s_1 * A_g) = 0.00367709$

$A_{v1} = 78.53982$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir1} = 2060.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_1 = 100.00$

core:  $s_2 = A_{v2} * L_{stir2} / (s_2 * A_g) = 0.00067082$

$A_{v2} = 50.26548$ , is the area of every stirrup parallel to loading (shear) direction

$L_{stir2} = 1468.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$s_2 = 250.00$

The term  $2 * t_f / b_w * (f_{fe} / f_s)$  is implemented to account for FRP contribution

where  $f = 2 * t_f / b_w$  is FRP ratio (EC8 - 3, A.4.4.3(6)) and  $f_{fe} / f_s$  normalises  $f$  to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation  $f_s$  of jacket is used.

$N_{UD} = 17779.344$

$A_g = 440000.00$

$f_{cE} = (f_{c,jacket} * Area_{jacket} + f_{c,core} * Area_{core}) / section\_area = 30.00$

$f_{yIE} = (f_{y,ext\_Long\_Reinf} * Area_{ext\_Long\_Reinf} + f_{y,int\_Long\_Reinf} * Area_{int\_Long\_Reinf}) / Area_{Tot\_Long\_Rein} = 625.00$

$f_{yIE} = (f_{y,ext\_Trans\_Reinf} * s_1 + f_{y,int\_Trans\_Reinf} * s_2) / (s_1 + s_2) = 625.00$

$\rho_l = Area_{Tot\_Long\_Rein} / (b * d) = 0.01009575$

$b = 750.00$

$d = 707.00$

$f_{cE} = 30.00$

-----  
End Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 2

Integration Section: (b)

-----

## Calculation No. 15

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity  $V_{Rd}$

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjics

Constant Properties

Knowledge Factor,  $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

New material of Primary Member: Concrete Strength,  $f_c = f_{c\_lower\_bound} = 20.00$

New material of Primary Member: Steel Strength,  $f_s = f_{s\_lower\_bound} = 500.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

#####

Note: Especially for the calculation of  $\gamma$  for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE 41-17).

Jacket

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

Existing Column

New material: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material: Steel Strength,  $f_s = f_{sm} = 625.00$

#####

Max Height,  $H_{max} = 750.00$

Min Height,  $H_{min} = 400.00$

Max Width,  $W_{max} = 750.00$

Min Width,  $W_{min} = 400.00$

Jacket Thickness,  $t_j = 100.00$

Cover Thickness,  $c = 25.00$

Element Length,  $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Lap Length  $l_o = l_b = 300.00$

No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment,  $M_a = -459842.936$

Shear Force,  $V_a = 213.4386$   
EDGE -B-  
Bending Moment,  $M_b = -178152.624$   
Shear Force,  $V_b = -213.4386$   
BOTH EDGES  
Axial Force,  $F = -17779.344$   
Longitudinal Reinforcement Area Distribution (in 2 divisions)  
-Tension:  $A_{st} = 0.00$   
-Compression:  $A_{sc} = 5353.274$   
Longitudinal Reinforcement Area Distribution (in 3 divisions)  
-Tension:  $A_{st,ten} = 1137.257$   
-Compression:  $A_{sc,com} = 2208.54$   
-Middle:  $A_{st,mid} = 2007.478$   
Mean Diameter of Tension Reinforcement,  $D_{bL,ten} = 16.80$

-----  
-----  
New component: From table 7-7, ASCE 41\_17: Final Shear Capacity  $V_R = 1.0 \cdot V_n = 984866.462$   
 $V_n$  ((10.3), ASCE 41-17) =  $k_n \cdot V_{CoI0} = 984866.462$   
 $V_{CoI} = 984866.462$   
 $k_n = 1.00$   
 $displacement\_ductility\_demand = 1.3707411E-005$

-----  
NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
= 1 (normal-weight concrete)  
Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 20.00$ , but  $f_c^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$M/d = 2.00$   
 $M_u = 178152.624$   
 $V_u = 213.4386$   
 $d = 0.8 \cdot h = 600.00$   
 $N_u = 17779.344$   
 $A_g = 300000.00$   
From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 811033.559$   
where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 722566.31$   
 $V_{s,j1} = 471238.898$  is calculated for section web jacket, with:  
 $d = 600.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$

$V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,j2} = 251327.412$  is calculated for section flange jacket, with:  
 $d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 500.00$   
 $s = 100.00$

$V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$   
 $s/d = 0.3125$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 88467.249$   
 $V_{s,c1} = 88467.249$  is calculated for section web core, with:  
 $d = 440.00$   
 $A_v = 100530.965$   
 $f_y = 500.00$   
 $s = 250.00$

$V_{s,c1}$  is multiplied by  $Col,c1 = 1.00$   
 $s/d = 0.56818182$   
 $V_{s,c2} = 0.00$  is calculated for section flange core, with:  
 $d = 160.00$   
 $A_v = 100530.965$   
 $f_y = 500.00$   
 $s = 250.00$   
 $V_{s,c2}$  is multiplied by  $Col,c2 = 0.00$

$s/d = 1.5625$   
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$   
From (11-11), ACI 440:  $V_s + V_f \leq 713005.69$   
 $b_w = 400.00$

-----  
displacement\_ductility\_demand is calculated as  $\phi / y$

- Calculation of  $\phi / y$  for END B -  
for rotation axis 2 and integ. section (b)

-----  
From analysis, chord rotation  $\theta = 7.5201070E-009$   
 $y = (M_y * L_s / 3) / E_{eff} = 0.00054862 ((4.29), Biskinis Phd)$   
 $M_y = 2.8709E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 834.6784  
From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
 $factor = 0.30$   
 $A_g = 440000.00$   
Mean concrete strength:  $f'_c = (f'_{c\_jacket} * Area_{jacket} + f'_{c\_core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17779.344$   
 $E_c * I_g = E_{c\_jacket} * I_{g\_jacket} + E_{c\_core} * I_{g\_core} = 4.8532E+014$

-----  
Calculation of Yielding Moment  $M_y$

-----  
Calculation of  $\phi / y$  and  $M_y$  according to Annex 7 -

-----  
Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:  
flange width,  $b = 750.00$   
web width,  $b_w = 400.00$   
flange thickness,  $t = 400.00$

-----  
 $y = \text{Min}(y_{ten}, y_{com})$   
 $y_{ten} = 2.1455196E-006$   
with ((10.1), ASCE 41-17)  $f_y = \text{Min}(f_y, 1.25 * f_y * (l_b / d)^{2/3}) = 243.3535$   
 $d = 707.00$   
 $y = 0.19784983$   
 $A = 0.01023354$   
 $B = 0.00454395$   
with  $pt = 0.00214476$   
 $pc = 0.00416509$   
 $pv = 0.00378591$   
 $N = 17779.344$   
 $b = 750.00$   
 $\lambda = 0.06082037$   
 $y_{comp} = 1.5202265E-005$   
with  $f_c = 30.00$   
 $E_c = 25742.96$   
 $y = 0.19516753$   
 $A = 0.01001583$   
 $B = 0.00440616$   
with  $E_s = 200000.00$   
CONFIRMATION:  $y = 0.19594836 < t/d$

-----  
Calculation of ratio  $l_b / d$


-----  
Lap Length:  $l_d / d, \text{min} = 0.17384865$   
 $l_b = 300.00$   
 $l_d = 1725.639$   
Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 $l_d, \text{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)  
 $= 1$   
 $db = 16.66667$

Mean strength value of all re-bars:  $f_y = 625.00$   
 Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)  
 $t = 1.00$   
 $s = 0.80$   
 $e = 1.00$   
 $cb = 25.00$   
 $K_{tr} = 1.7174$   
 $A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$   
 where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis  
 $s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$   
 $n = 24.00$

End Of Calculation of Shear Capacity for element: column JLC1 of floor 1  
 At local axis: 3  
 Integration Section: (b)

## Calculation No. 16

column C1, Floor 1  
 Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)  
 Analysis: Uniform +X  
 Check: Chord rotation capacity (  $\mu$  )  
 Edge: End  
 Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
 At Shear local axis: 3  
 (Bending local axis: 2)  
 Section Type: rcjlc

Constant Properties

Knowledge Factor,  $= 1.00$   
 Mean strength values are used for both shear and moment calculations.  
 Consequently:  
 Jacket

· New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 · New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 · Concrete Elasticity,  $E_c = 25742.96$   
 · Steel Elasticity,  $E_s = 200000.00$   
 · Existing Column  
 · New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 · New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 · Concrete Elasticity,  $E_c = 25742.96$   
 · Steel Elasticity,  $E_s = 200000.00$   
 · #####  
 · Note: Especially for the calculation of moment strengths,  
 · the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14  
 · Jacket  
 · New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$   
 · Existing Column  
 · New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$   
 · #####  
 · Max Height,  $H_{max} = 750.00$   
 · Min Height,  $H_{min} = 400.00$   
 · Max Width,  $W_{max} = 750.00$   
 · Min Width,  $W_{min} = 400.00$   
 · Jacket Thickness,  $t_j = 100.00$   
 · Cover Thickness,  $c = 25.00$   
 · Mean Confinement Factor overall section = 1.27105  
 · Element Length,  $L = 3000.00$   
 · Primary Member  
 · Smooth Bars  
 · Ductile Steel  
 · With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
 · Longitudinal Bars With Ends Lapped Starting at the End Sections  
 · Lap Length  $l_o = 300.00$   
 · No FRP Wrapping

-----  
 · Stepwise Properties  
 -----

· At local axis: 3  
 · EDGE -A-  
 · Shear Force,  $V_a = -0.00017144$   
 · EDGE -B-  
 · Shear Force,  $V_b = 0.00017144$   
 · BOTH EDGES  
 · Axial Force,  $F = -16273.608$   
 · Longitudinal Reinforcement Area Distribution (in 2 divisions)  
 · -Tension:  $A_{sl,t} = 0.00$   
 · -Compression:  $A_{sl,c} = 5353.274$   
 · Longitudinal Reinforcement Area Distribution (in 3 divisions)  
 · -Tension:  $A_{sl,ten} = 1137.257$   
 · -Compression:  $A_{sl,com} = 2208.54$   
 · -Middle:  $A_{sl,mid} = 2007.478$

· Calculation of Shear Capacity ratio,  $V_e/V_r = 0.32266369$   
 · Member Controlled by Flexure ( $V_e/V_r < 1$ )  
 · Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$   
 · with  
 ·  $M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 5.0296E+008$   
 ·  $M_{u1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction  
 · which is defined for the static loading combination  
 ·  $M_{u1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment  
 · direction which is defined for the static loading combination  
 ·  $M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 5.0296E+008$   
 ·  $M_{u2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction  
 · which is defined for the static loading combination  
 ·  $M_{u2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment

direction which is defined for the the static loading combination

Calculation of Mu1+

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 4.8099118E-006$$

$$Mu = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_o) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

s1 = 100.00  
s2 = 250.00  
fywe1 = 781.25  
fywe2 = 781.25  
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00471045  
c = confinement factor = 1.27105

y1 = 0.00083886  
sh1 = 0.00268436  
ft1 = 314.5735  
fy1 = 262.1446  
su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered  
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Es,jacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886  
sh2 = 0.00268436  
ft2 = 314.5735  
fy2 = 262.1446  
su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of esu2\_nominal and y2, sh2,ft2,fy2, it is considered  
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket\*Asl,com,jacket + fs,core\*Asl,com,core)/Asl,com = 262.1446

with Es2 = (Es,jacket\*Asl,com,jacket + Es,core\*Asl,com,core)/Asl,com = 200000.00

yv = 0.00083886  
shv = 0.00268436  
ftv = 314.5735  
fyv = 262.1446  
suv = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

lo/lou,min = lb/ld = 0.13907892

suv = 0.4\*esuv\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv\_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv\_nominal and yv, shv,ftv,fyv, it is considered  
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$ , from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket\*Asl,mid,jacket + fs,mid\*Asl,mid,core)/Asl,mid = 262.1446

with Esv = (Es,jacket\*Asl,mid,jacket + Es,mid\*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.0187412  
2 = Asl,com/(b\*d)\*(fs2/fc) = 0.03639521  
v = Asl,mid/(b\*d)\*(fsv/fc) = 0.03308184

and confined core properties:

b = 690.00  
d = 677.00  
d' = 13.00

fcc (5A.2, TBDY) = 38.13135

cc (5A.5, TBDY) = 0.00471045

c = confinement factor = 1.27105

1 = Asl,ten/(b\*d)\*(fs1/fc) = 0.02127357

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.04131304$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture  
' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---->

$$s_u(4.9) = 0.21062322$$

$$M_u = M_{Rc}(4.14) = 2.3387E+008$$

$$u = s_u(4.1) = 4.8099118E-006$$

-----  
Calculation of ratio  $l_b/l_d$

-----  
Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \min(A_{tr,x}, A_{tr,y}) = 257.6106$$

where  $A_{tr,x}$ ,  $A_{tr,y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \max(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $M_u1$ -

-----  
Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \max(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e(5.4c) = 0.05179731$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \max(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

AnoConf1 = 158733.333 is the unconfined external core area which is equal to  $b_i/6$  as defined at (A.2).  
 $ase2 (>=ase1) = \text{Max}(((Aconf,max2-AnoConf2)/Aconf,max2)*(Aconf,min2/Aconf,max2),0) = 0.45746528$

The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max2 = 171264.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

Aconf,min2 = 54741.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max2 by a length equal to half the clear spacing between internal hoops.

AnoConf2 = 106242.667 is the unconfined internal core area which is equal to  $b_i/6$  as defined at (A.2).  
 $psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 3.3968$

-----  
 $psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.3968$   
 $psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00367709$   
Lstir1 (Length of stirrups along Y) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2 (5.4d) = Lstir2*Astir2/(Asec*s2) = 0.00067082$   
Lstir2 (Length of stirrups along Y) = 1468.00  
Astir2 (stirrups area) = 50.26548

-----  
 $psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.3968$   
 $psh1 ((5.4d), TBDY) = Lstir1*Astir1/(Asec*s1) = 0.00367709$   
Lstir1 (Length of stirrups along X) = 2060.00  
Astir1 (stirrups area) = 78.53982  
 $psh2 ((5.4d), TBDY) = Lstir2*Astir2/(Asec*s2) = 0.00067082$   
Lstir2 (Length of stirrups along X) = 1468.00  
Astir2 (stirrups area) = 50.26548

-----  
Asec = 440000.00

s1 = 100.00

s2 = 250.00

fywe1 = 781.25

fywe2 = 781.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00471045

c = confinement factor = 1.27105

y1 = 0.00083886

sh1 = 0.00268436

ft1 = 314.5735

fy1 = 262.1446

su1 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/lb = 0.13907892

su1 = 0.4\*esu1\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1\_nominal = 0.08,

For calculation of esu1\_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by  $\text{Min}(1,1.25*(lb/lb)^{2/3})$ , from 10.3.5, ASCE 41-17.

with fs1 = (fsjacket\*Asl,ten,jacket + fs,core\*Asl,ten,core)/Asl,ten = 262.1446

with Es1 = (Esjacket\*Asl,ten,jacket + Es,core\*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00083886

sh2 = 0.00268436

ft2 = 314.5735

fy2 = 262.1446

su2 = 0.00268436

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

lo/lou,min = lb/lb,min = 0.13907892

su2 = 0.4\*esu2\_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2\_nominal = 0.08,

For calculation of  $es_{u2\_nominal}$  and  $y_2$ ,  $sh_2, ft_2, fy_2$ , it is considered characteristic value  $fs_{y2} = fs_2/1.2$ , from table 5.1, TBDY.

$y_1$ ,  $sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es_2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00083886$

$sh_v = 0.00268436$

$ft_v = 314.5735$

$fy_v = 262.1446$

$s_{uv} = 0.00268436$

using (30) in Bisquinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.13907892$

$s_{uv} = 0.4 \cdot es_{uv\_nominal} ((5,5), TBDY) = 0.032$

From table 5A.1, TBDY:  $es_{uv\_nominal} = 0.08$ ,

considering characteristic value  $fs_{yv} = f_{sv}/1.2$ , from table 5.1, TBDY

For calculation of  $es_{uv\_nominal}$  and  $y_v$ ,  $sh_v, ft_v, fy_v$ , it is considered characteristic value  $fs_{yv} = f_{sv}/1.2$ , from table 5.1, TBDY.

$y_1$ ,  $sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{sv} = (f_{s,jacket} \cdot A_{sl,mid,jacket} + f_{s,mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 262.1446$

with  $Es_v = (Es_{jacket} \cdot A_{sl,mid,jacket} + Es_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.06824101$

$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.03513975$

$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.06202846$

and confined core properties:

$b = 340.00$

$d = 677.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 38.13135$

$cc (5A.5, TBDY) = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$1 = A_{sl,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08384116$

$2 = A_{sl,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.04317283$

$v = A_{sl,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---

$su (4.9) = 0.2584548$

$\mu_u = MR_c (4.14) = 5.0296E+008$

$u = su (4.1) = 5.1201636E-006$

-----  
Calculation of ratio  $lb/ld$

Lap Length:  $lb/ld = 0.13907892$

$lb = 300.00$

$ld = 2157.049$

Calculation of  $lb_{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld_{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$db = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

Calculation of Mu2+

Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$\mu = 4.8099118E-006$$

$$\mu = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e \text{ (5.4c)} = 0.05179731$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$a_{se2} (>= a_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization

of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length

equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$$

$$p_{sh1} \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$p_{sh2} \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$s_2 = 250.00$   
 $fy_{we1} = 781.25$   
 $fy_{we2} = 781.25$   
 $f_{ce} = 30.00$   
 From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $y_1 = 0.00083886$   
 $sh_1 = 0.00268436$   
 $ft_1 = 314.5735$   
 $fy_1 = 262.1446$   
 $su_1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou, min = lb/d = 0.13907892$   
 $su_1 = 0.4 * esu_{1\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{1\_nominal} = 0.08$ ,  
 For calculation of  $esu_{1\_nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered  
 characteristic value  $fsy_1 = fs_1/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $Min(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_1 = (fs_{jacket} * A_{sl, ten, jacket} + fs_{core} * A_{sl, ten, core}) / A_{sl, ten} = 262.1446$   
 with  $Es_1 = (Es_{jacket} * A_{sl, ten, jacket} + Es_{core} * A_{sl, ten, core}) / A_{sl, ten} = 200000.00$   
 $y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou, min = lb/lb, min = 0.13907892$   
 $su_2 = 0.4 * esu_{2\_nominal} ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esu_{2\_nominal} = 0.08$ ,  
 For calculation of  $esu_{2\_nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered  
 characteristic value  $fsy_2 = fs_2/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $Min(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs_2 = (fs_{jacket} * A_{sl, com, jacket} + fs_{core} * A_{sl, com, core}) / A_{sl, com} = 262.1446$   
 with  $Es_2 = (Es_{jacket} * A_{sl, com, jacket} + Es_{core} * A_{sl, com, core}) / A_{sl, com} = 200000.00$   
 $y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou, min = lb/d = 0.13907892$   
 $suv = 0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $Min(1, 1.25 * (lb/d)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs_{jacket} * A_{sl, mid, jacket} + fs_{mid} * A_{sl, mid, core}) / A_{sl, mid} = 262.1446$   
 with  $Es_v = (Es_{jacket} * A_{sl, mid, jacket} + Es_{mid} * A_{sl, mid, core}) / A_{sl, mid} = 200000.00$   
 $1 = A_{sl, ten} / (b * d) * (fs_1 / f_c) = 0.0187412$   
 $2 = A_{sl, com} / (b * d) * (fs_2 / f_c) = 0.03639521$   
 $v = A_{sl, mid} / (b * d) * (fsv / f_c) = 0.03308184$   
 and confined core properties:  
 $b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $f_{cc} (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = A_{sl, ten} / (b * d) * (fs_1 / f_c) = 0.02127357$   
 $2 = A_{sl, com} / (b * d) * (fs_2 / f_c) = 0.04131304$

$$v = A_{sl, mid} / (b * d) * (f_{sv} / f_c) = 0.03755196$$

Case/Assumption: Unconfined full section - Steel rupture  
' satisfies Eq. (4.3)

--->

$v < v_{s, y2}$  - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.21062322$$

$$M_u = M_{Rc}(4.14) = 2.3387E+008$$

$$u = s_u(4.1) = 4.8099118E-006$$

Calculation of ratio  $l_b / l_d$

Lap Length:  $l_b / l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

Calculation of  $M_u$

Calculation of ultimate curvature  $u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$M_u = 5.0296E+008$$

with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear\_factor} * \text{Max}(c_u, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01260361$$

$$w_e(5.4c) = 0.05179731$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$a_{se1} = \text{Max}(((A_{conf, max1} - A_{noConf1}) / A_{conf, max1}) * (A_{conf, min1} / A_{conf, max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf, min}$  and  $A_{conf, max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf, max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf, min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf, max1}$  by a length equal to half the clear spacing between external hoops.

AnoConf1 = 158733.333 is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $ase_2 (>= ase_1) = \text{Max}(((A_{conf,max2} - \text{AnoConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$   
 The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).  
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."  
 J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.  
 $A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.  
 $A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.  
 $\text{AnoConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.3968$

-----  
 $p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$   
 $p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $p_{sh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.3968$   
 $p_{sh1} ((5.4d), \text{TBDY}) = L_{stir1} * A_{stir1} / (A_{sec} * s_1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $p_{sh2} ((5.4d), \text{TBDY}) = L_{stir2} * A_{stir2} / (A_{sec} * s_2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$   
 $s_1 = 100.00$   
 $s_2 = 250.00$   
 $f_{ywe1} = 781.25$   
 $f_{ywe2} = 781.25$   
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$

$y_1 = 0.00083886$   
 $sh_1 = 0.00268436$   
 $ft_1 = 314.5735$   
 $fy_1 = 262.1446$   
 $su_1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.13907892$

$su_1 = 0.4 * esu1_{nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y_1, sh_1, ft_1, fy_1$ , it is considered characteristic value  $fs_1 = fs_1/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs_1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with  $Es_1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y_2 = 0.00083886$   
 $sh_2 = 0.00268436$   
 $ft_2 = 314.5735$   
 $fy_2 = 262.1446$   
 $su_2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.13907892$

$su_2 = 0.4 * esu2_{nominal} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY:  $esu2_{nominal} = 0.08$ ,

For calculation of  $esu2_{nominal}$  and  $y_2, sh_2, ft_2, fy_2$ , it is considered

characteristic value  $f_{s2} = f_{s2}/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, f_{y1}$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{s2} = (f_{s,jacket} \cdot A_{s1,com,jacket} + f_{s,core} \cdot A_{s1,com,core})/A_{s1,com} = 262.1446$

with  $E_{s2} = (E_{s,jacket} \cdot A_{s1,com,jacket} + E_{s,core} \cdot A_{s1,com,core})/A_{s1,com} = 200000.00$

$y_v = 0.00083886$

$sh_v = 0.00268436$

$ft_v = 314.5735$

$f_{y_v} = 262.1446$

$s_{u_v} = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor

and also multiplied by the shear\_factor according to 15.7.1.4, with

Shear\_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.13907892$

$s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY:  $e_{s_{u_v,nominal}} = 0.08$ ,

considering characteristic value  $f_{s_{y_v}} = f_{s_{y_v}}/1.2$ , from table 5.1, TBDY

For calculation of  $e_{s_{u_v,nominal}}$  and  $y_v, sh_v, ft_v, f_{y_v}$ , it is considered

characteristic value  $f_{s_{y_v}} = f_{s_{y_v}}/1.2$ , from table 5.1, TBDY.

$y_1, sh_1, ft_1, f_{y1}$ , are also multiplied by  $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $f_{s_{y_v}} = (f_{s,jacket} \cdot A_{s1,mid,jacket} + f_{s,mid} \cdot A_{s1,mid,core})/A_{s1,mid} = 262.1446$

with  $E_{s_{y_v}} = (E_{s,jacket} \cdot A_{s1,mid,jacket} + E_{s,mid} \cdot A_{s1,mid,core})/A_{s1,mid} = 200000.00$

$1 = A_{s1,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.06824101$

$2 = A_{s1,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.03513975$

$v = A_{s1,mid}/(b \cdot d) \cdot (f_{s_{y_v}}/f_c) = 0.06202846$

and confined core properties:

$b = 340.00$

$d = 677.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 38.13135$

$cc (5A.5, TBDY) = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$1 = A_{s1,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.08384116$

$2 = A_{s1,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.04317283$

$v = A_{s1,mid}/(b \cdot d) \cdot (f_{s_{y_v}}/f_c) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---

$s_u (4.9) = 0.2584548$

$\mu = M_{Rc} (4.14) = 5.0296E+008$

$u = s_u (4.1) = 5.1201636E-006$

-----  
Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$l_b = 300.00$

$l_d = 2157.049$

Calculation of  $l_{b,min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_{d,min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

= 1

$d_b = 16.66667$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core})/Area_{section} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$K_{tr} = 1.7174$

$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y loxal axis

$s = \text{Max}(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

-----  
Calculation of Shear Strength  $V_r = \text{Min}(V_{r1}, V_{r2}) = 1.0392\text{E}+006$   
-----

Calculation of Shear Strength at edge 1,  $V_{r1} = 1.0392\text{E}+006$

$V_{r1} = V_{\text{Col}} \text{ ((10.3), ASCE 41-17)} = k_{nl} * V_{\text{ColO}}$

$V_{\text{ColO}} = 1.0392\text{E}+006$

$k_{nl} = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)

Mean concrete strength:  $f'_c = (f'_{c\_jacket} * \text{Area}_{jacket} + f'_{c\_core} * \text{Area}_{core}) / \text{Area}_{section} = 30.00$ , but  $f'_c^{0.5} \leq 8.3$   
MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 * h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138\text{E}+006$

where:

$V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$

$V_{s,j1} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j1}$  is multiplied by  $\text{Col},j1 = 1.00$

$s/d = 0.16666667$

$V_{s,j2} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s,j2}$  is multiplied by  $\text{Col},j2 = 1.00$

$s/d = 0.3125$

$V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$

$V_{s,c1} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c1}$  is multiplied by  $\text{Col},c1 = 1.00$

$s/d = 0.56818182$

$V_{s,c2} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s,c2}$  is multiplied by  $\text{Col},c2 = 0.00$

$s/d = 1.5625$

$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$b_w = 400.00$   
-----

-----  
Calculation of Shear Strength at edge 2,  $V_{r2} = 1.0392\text{E}+006$

$V_{r2} = V_{\text{Col}} \text{ ((10.3), ASCE 41-17)} = k_{nl} * V_{\text{ColO}}$

$V_{\text{ColO}} = 1.0392\text{E}+006$

$k_{nl} = 1$  (zero step-static loading)

-----  
NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '  
where  $V_f$  is the contribution of FRPs (11.3), ACI 440).

-----  
 $= 1$  (normal-weight concrete)

Mean concrete strength:  $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1308.016$

$V_u = 0.00017144$

$d = 0.8 \cdot h = 600.00$

$N_u = 16273.608$

$A_g = 300000.00$

From (11.5.4.8), ACI 318-14:  $V_s = V_{s\text{jacket}} + V_{s\text{core}} = 1.0138\text{E}+006$

where:

$V_{s\text{jacket}} = V_{s\text{j1}} + V_{s\text{j2}} = 903207.888$

$V_{s\text{j1}} = 589048.623$  is calculated for section web jacket, with:

$d = 600.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s\text{j1}}$  is multiplied by  $\text{Col,j1} = 1.00$

$s/d = 0.16666667$

$V_{s\text{j2}} = 314159.265$  is calculated for section flange jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 100.00$

$V_{s\text{j2}}$  is multiplied by  $\text{Col,j2} = 1.00$

$s/d = 0.3125$

$V_{s\text{core}} = V_{s\text{c1}} + V_{s\text{c2}} = 110584.061$

$V_{s\text{c1}} = 110584.061$  is calculated for section web core, with:

$d = 440.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s\text{c1}}$  is multiplied by  $\text{Col,c1} = 1.00$

$s/d = 0.56818182$

$V_{s\text{c2}} = 0.00$  is calculated for section flange core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 625.00$

$s = 250.00$

$V_{s\text{c2}}$  is multiplied by  $\text{Col,c2} = 0.00$

$s/d = 1.5625$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$

From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$

$bw = 400.00$

-----

End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At local axis: 3

-----

Start Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
At Shear local axis: 2  
(Bending local axis: 3)  
Section Type: rcjlc3

Constant Properties

-----

Knowledge Factor,  $\phi = 1.00$

Mean strength values are used for both shear and moment calculations.  
Consequently:

Jacket

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$

Concrete Elasticity,  $E_c = 25742.96$

Steel Elasticity,  $E_s = 200000.00$

Existing Column

```

New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$ 
New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$ 
Concrete Elasticity,  $E_c = 25742.96$ 
Steel Elasticity,  $E_s = 200000.00$ 
#####
Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$ 
Existing Column
New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 781.25$ 
#####
Max Height,  $H_{max} = 750.00$ 
Min Height,  $H_{min} = 400.00$ 
Max Width,  $W_{max} = 750.00$ 
Min Width,  $W_{min} = 400.00$ 
Jacket Thickness,  $t_j = 100.00$ 
Cover Thickness,  $c = 25.00$ 
Mean Confinement Factor overall section = 1.27105
Element Length,  $L = 3000.00$ 
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Lap Length  $l_o = 300.00$ 
No FRP Wrapping
-----

Stepwise Properties
-----
At local axis: 2
EDGE -A-
Shear Force,  $V_a = -0.0001715$ 
EDGE -B-
Shear Force,  $V_b = 0.0001715$ 
BOTH EDGES
Axial Force,  $F = -16273.608$ 
Longitudinal Reinforcement Area Distribution (in 2 divisions)
  -Tension:  $A_{sl,t} = 0.00$ 
  -Compression:  $A_{sl,c} = 5353.274$ 
Longitudinal Reinforcement Area Distribution (in 3 divisions)
  -Tension:  $A_{sl,ten} = 1137.257$ 
  -Compression:  $A_{sl,com} = 2208.54$ 
  -Middle:  $A_{sl,mid} = 2007.478$ 
-----
-----

Calculation of Shear Capacity ratio ,  $V_e/V_r = 0.32266369$ 
Member Controlled by Flexure ( $V_e/V_r < 1$ )
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 335307.657$ 
with
 $M_{pr1} = \text{Max}(\mu_{u1+} , \mu_{u1-}) = 5.0296E+008$ 
 $\mu_{u1+} = 2.3387E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{u1-} = 5.0296E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{u2+} , \mu_{u2-}) = 5.0296E+008$ 
 $\mu_{u2+} = 2.3387E+008$ , is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $\mu_{u2-} = 5.0296E+008$ , is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination
-----
Calculation of  $\mu_{u1+}$ 
-----

```

Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 4.8099118E-006$$

$$\mu = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$\alpha_{co} (5A.5, TBDY) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear\_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.01260361$$

$$\phi_{we} (5.4c) = 0.05179731$$

$$\alpha_{se} ((5.4d), TBDY) = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.45746528$$

$$\alpha_{se1} = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\alpha_{se2} (> \alpha_{se1}) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\phi_{psh,min} * F_{ywe} = \text{Min}(\phi_{psh,x} * F_{ywe}, \phi_{psh,y} * F_{ywe}) = 3.3968$$

$$\phi_{psh,x} * F_{ywe} = \phi_{psh1} * F_{ywe1} + \phi_{ps2} * F_{ywe2} = 3.3968$$

$$\phi_{psh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$\phi_{psh2} (5.4d) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$\phi_{psh,y} * F_{ywe} = \phi_{psh1} * F_{ywe1} + \phi_{ps2} * F_{ywe2} = 3.3968$$

$$\phi_{psh1} ((5.4d), TBDY) = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$\phi_{psh2} ((5.4d), TBDY) = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

From ((5.A.5), TBDY), TBDY:  $cc = 0.00471045$

$c =$  confinement factor  $= 1.27105$

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$lo/lou,min = lb/ld = 0.13907892$

$su1 = 0.4 * esu1\_nominal$  ((5.5), TBDY)  $= 0.032$

From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,

For calculation of  $esu1\_nominal$  and  $y1, sh1, ft1, fy1$ , it is considered  
characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 262.1446$

with  $Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$fy2 = 262.1446$

$su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$lo/lou,min = lb/lb,min = 0.13907892$

$su2 = 0.4 * esu2\_nominal$  ((5.5), TBDY)  $= 0.032$

From table 5A.1, TBDY:  $esu2\_nominal = 0.08$ ,

For calculation of  $esu2\_nominal$  and  $y2, sh2, ft2, fy2$ , it is considered  
characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 262.1446$

with  $Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00$

$yv = 0.00083886$

$shv = 0.00268436$

$ftv = 314.5735$

$fyv = 262.1446$

$suv = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
and also multiplied by the shear\_factor according to 15.7.1.4, with  
Shear\_factor = 1.00

$lo/lou,min = lb/ld = 0.13907892$

$suv = 0.4 * esuv\_nominal$  ((5.5), TBDY)  $= 0.032$

From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,

considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY

For calculation of  $esuv\_nominal$  and  $yv, shv, ftv, fyv$ , it is considered  
characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 262.1446$

with  $Esv = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$

$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.0187412$

$2 = Asl,com / (b * d) * (fs2 / fc) = 0.03639521$

$v = Asl,mid / (b * d) * (fsv / fc) = 0.03308184$

and confined core properties:

$b = 690.00$

$d = 677.00$

$d' = 13.00$

$fcc$  (5A.2, TBDY)  $= 38.13135$

$cc$  (5A.5, TBDY)  $= 0.00471045$

$c =$  confinement factor  $= 1.27105$

$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.02127357$

$2 = Asl,com / (b * d) * (fs2 / fc) = 0.04131304$

$v = Asl,mid / (b * d) * (fsv / fc) = 0.03755196$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_s, y_2$  - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.21062322$$

$$\mu = M_{Rc}(4.14) = 2.3387E+008$$

$$u = s_u(4.1) = 4.8099118E-006$$

-----  
Calculation of ratio  $l_b/l_d$

Lap Length:  $l_b/l_d = 0.13907892$

$$l_b = 300.00$$

$$l_d = 2157.049$$

Calculation of  $l_b, \min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 781.25$

Mean concrete strength:  $f_c' = (f_c'_{jacket} \cdot Area_{jacket} + f_c'_{core} \cdot Area_{core}) / Area_{section} = 30.00$ , but  $f_c'^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}, A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{external}, s_{internal}) = 250.00$$

$$n = 24.00$$

-----  
Calculation of  $\mu_1$ -

-----  
Calculation of ultimate curvature  $\mu$  according to 4.1, Biskinis/Fardis 2013:

$$u = 5.1201636E-006$$

$$\mu = 5.0296E+008$$

-----  
with full section properties:

$$b = 400.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00191815$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear\_factor} \cdot \text{Max}(\mu, c_c) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu = 0.01260361$$

$$\text{we (5.4c) } \mu = 0.05179731$$

$$\text{ase ((5.4d), TBDY) } = (\text{ase1} \cdot A_{ext} + \text{ase2} \cdot A_{int}) / A_{sec} = 0.45746528$$

$$\text{ase1} = \text{Max}(((A_{conf, \max 1} - A_{noConf1}) / A_{conf, \max 1}) \cdot (A_{conf, \min 1} / A_{conf, \max 1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf, \max 1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf, \min 1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf, \max 1}$  by a length

equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$\text{ase2} (\geq \text{ase1}) = \text{Max}(((A_{conf, \max 2} - A_{noConf2}) / A_{conf, \max 2}) \cdot (A_{conf, \min 2} / A_{conf, \max 2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf, \min}$  and  $A_{conf, \max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along Y) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along Y) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$

$psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$

$L_{stir1}$  (Length of stirrups along X) = 2060.00

$A_{stir1}$  (stirrups area) = 78.53982

$psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$

$L_{stir2}$  (Length of stirrups along X) = 1468.00

$A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$

$s1 = 100.00$

$s2 = 250.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 781.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$

$c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$

$sh1 = 0.00268436$

$ft1 = 314.5735$

$fy1 = 262.1446$

$su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/ld = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with  $Es1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00083886$

$sh2 = 0.00268436$

$ft2 = 314.5735$

$fy2 = 262.1446$

$su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor and also multiplied by the shear\_factor according to 15.7.1.4, with Shear\_factor = 1.00

$lo/lou_{min} = lb/lb_{min} = 0.13907892$

$su2 = 0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu2_{nominal} = 0.08$ ,

For calculation of  $esu2_{nominal}$  and  $y2, sh2, ft2, fy2$ , it is considered characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00083886$   
 $sh_v = 0.00268436$   
 $ft_v = 314.5735$   
 $fy_v = 262.1446$   
 $su_v = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lo_{min} = lb/ld = 0.13907892$   
 $su_v = 0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fs_v = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $y_v, sh_v, ft_v, fy_v$ , it is considered  
 characteristic value  $fs_v = fsv/1.2$ , from table 5.1, TBDY.  
 $y_1, sh_1, ft_1, fy_1$ , are also multiplied by  $Min(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 262.1446$   
 with  $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$   
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.06824101$   
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.03513975$   
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.06202846$

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.08384116$   
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.04317283$   
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---

$v < v_{s,y2}$  - LHS eq.(4.5) is satisfied

---

$su (4.9) = 0.2584548$

$Mu = MRc (4.14) = 5.0296E+008$

$u = su (4.1) = 5.1201636E-006$

Calculation of ratio  $lb/ld$

Lap Length:  $lb/ld = 0.13907892$

$lb = 300.00$

$ld = 2157.049$

Calculation of  $lb_{min}$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld_{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$ , but  $fc'^{0.5} \leq 8.3$

MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$Ktr = 1.7174$

$Atr = Min(Atr_x, Atr_y) = 257.6106$

where  $Atr_x, Atr_y$  are the sum of the area of all stirrup legs along X and Y loxal axis

$s = Max(s_{external}, s_{internal}) = 250.00$

$n = 24.00$

Calculation of  $Mu_{2+}$

Calculation of ultimate curvature  $\phi_u$  according to 4.1, Biskinis/Fardis 2013:

$$u = 4.8099118E-006$$

$$Mu = 2.3387E+008$$

with full section properties:

$$b = 750.00$$

$$d = 707.00$$

$$d' = 43.00$$

$$v = 0.00102301$$

$$N = 16273.608$$

$$f_c = 30.00$$

$$co \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear\_factor} * \text{Max}(cu, cc) = 0.01260361$$

The Shear\_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01260361$$

$$we \text{ (5.4c)} = 0.05179731$$

$$ase \text{ ((5.4d), TBDY)} = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.45746528$$

$$ase1 = \text{Max}(((A_{conf,max1} - A_{noConf1}) / A_{conf,max1}) * (A_{conf,min1} / A_{conf,max1}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max1} = 353600.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the external perimeter hoops.

$A_{conf,min1} = 293525.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max1}$  by a length equal to half the clear spacing between external hoops.

$A_{noConf1} = 158733.333$  is the unconfined external core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$ase2 (\geq ase1) = \text{Max}(((A_{conf,max2} - A_{noConf2}) / A_{conf,max2}) * (A_{conf,min2} / A_{conf,max2}), 0) = 0.45746528$$

The definitions of  $A_{noConf}$ ,  $A_{conf,min}$  and  $A_{conf,max}$  are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.

$A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).

$$psh_{,min} * F_{ywe} = \text{Min}(psh_{,x} * F_{ywe}, psh_{,y} * F_{ywe}) = 3.3968$$

$$psh_{,x} * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$$

$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along Y)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ (5.4d)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along Y)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$psh_{,y} * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$$

$$psh1 \text{ ((5.4d), TBDY)} = L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$$

$$L_{stir1} \text{ (Length of stirrups along X)} = 2060.00$$

$$A_{stir1} \text{ (stirrups area)} = 78.53982$$

$$psh2 \text{ ((5.4d), TBDY)} = L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$$

$$L_{stir2} \text{ (Length of stirrups along X)} = 1468.00$$

$$A_{stir2} \text{ (stirrups area)} = 50.26548$$

$$A_{sec} = 440000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 781.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00471045$$

$c = \text{confinement factor} = 1.27105$   
 $y1 = 0.00083886$   
 $sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou,min = lb/ld = 0.13907892$   
 $su1 = 0.4 * esu1\_nominal ((5.5), \text{TBDY}) = 0.032$   
 From table 5A.1, TBDY:  $esu1\_nominal = 0.08$ ,  
 For calculation of  $esu1\_nominal$  and  $y1, sh1, ft1, fy1$ , it is considered  
 characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 262.1446$   
 with  $Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$   
 $y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou,min = lb/lb,min = 0.13907892$   
 $su2 = 0.4 * esu2\_nominal ((5.5), \text{TBDY}) = 0.032$   
 From table 5A.1, TBDY:  $esu2\_nominal = 0.08$ ,  
 For calculation of  $esu2\_nominal$  and  $y2, sh2, ft2, fy2$ , it is considered  
 characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 262.1446$   
 with  $Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00$   
 $yv = 0.00083886$   
 $shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $\text{Shear\_factor} = 1.00$   
 $lo/lou,min = lb/ld = 0.13907892$   
 $suv = 0.4 * esuv\_nominal ((5.5), \text{TBDY}) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv, shv, ftv, fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 262.1446$   
 with  $Es_v = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$   
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.0187412$   
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.03639521$   
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.03308184$   
 and confined core properties:  
 $b = 690.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, \text{TBDY}) = 38.13135$   
 $cc (5A.5, \text{TBDY}) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.02127357$   
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.04131304$   
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.03755196$   
 Case/Assumption: Unconfined full section - Steel rupture  
 ' satisfies Eq. (4.3)  
 --->  
 $v < vs,y2$  - LHS eq.(4.5) is satisfied

--->  
 su (4.9) = 0.21062322  
 Mu = MRc (4.14) = 2.3387E+008  
 u = su (4.1) = 4.8099118E-006

---

Calculation of ratio lb/l<sub>d</sub>

---

Lap Length: lb/l<sub>d</sub> = 0.13907892  
 lb = 300.00  
 l<sub>d</sub> = 2157.049

Calculation of lb,min according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.  
 l<sub>d,min</sub> from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)  
 = 1  
 db = 16.66667  
 Mean strength value of all re-bars: f<sub>y</sub> = 781.25  
 Mean concrete strength: f<sub>c</sub>' = (f<sub>c</sub>'<sub>jacket</sub>\*Area<sub>jacket</sub> + f<sub>c</sub>'<sub>core</sub>\*Area<sub>core</sub>)/Area<sub>section</sub> = 30.00, but f<sub>c</sub>'<sup>0.5</sup> ≤ 8.3 MPa (22.5.3.1, ACI 318-14)  
 t = 1.00  
 s = 0.80  
 e = 1.00  
 cb = 25.00  
 K<sub>tr</sub> = 1.7174  
 A<sub>tr</sub> = Min(A<sub>tr\_x</sub>, A<sub>tr\_y</sub>) = 257.6106  
 where A<sub>tr\_x</sub>, A<sub>tr\_y</sub> are the sum of the area of all stirrup legs along X and Y loxal axis  
 s = Max(s<sub>external</sub>, s<sub>internal</sub>) = 250.00  
 n = 24.00

---



---

Calculation of Mu<sub>2</sub>

---



---

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:  
 u = 5.1201636E-006  
 Mu = 5.0296E+008

---

with full section properties:  
 b = 400.00  
 d = 707.00  
 d' = 43.00  
 v = 0.00191815  
 N = 16273.608  
 f<sub>c</sub> = 30.00  
 co (5A.5, TBDY) = 0.002  
 Final value of cu: cu\* = shear\_factor \* Max( cu, cc) = 0.01260361  
 The Shear\_factor is considered equal to 1 (pure moment strength)  
 From (5.4b), TBDY: cu = 0.01260361  
 we (5.4c) = 0.05179731  
 ase ((5.4d), TBDY) = (ase1\*Aext+ase2\*Aint)/Asec = 0.45746528  
 ase1 = Max(((Aconf,max1-AnoConf1)/Aconf,max1)\*(Aconf,min1/Aconf,max1),0) = 0.45746528  
 The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).  
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."  
 J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.  
 Aconf,max1 = 353600.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the external perimeter hoops.  
 Aconf,min1 = 293525.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max1 by a length equal to half the clear spacing between external hoops.  
 AnoConf1 = 158733.333 is the unconfined external core area which is equal to bi<sup>2</sup>/6 as defined at (A.2).  
 ase2 (≥ ase1) = Max(((Aconf,max2-AnoConf2)/Aconf,max2)\*(Aconf,min2/Aconf,max2),0) = 0.45746528  
 The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).  
 The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max2} = 171264.00$  is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the internal perimeter hoops.  
 $A_{conf,min2} = 54741.00$  is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area  $A_{conf,max2}$  by a length equal to half the clear spacing between internal hoops.

$A_{noConf2} = 106242.667$  is the unconfined internal core area which is equal to  $b_i^2/6$  as defined at (A.2).  
 $psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.3968$

-----  
 $psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along Y) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  (5.4d) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along Y) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 3.3968$   
 $psh1$  ((5.4d), TBDY) =  $L_{stir1} * A_{stir1} / (A_{sec} * s1) = 0.00367709$   
 $L_{stir1}$  (Length of stirrups along X) = 2060.00  
 $A_{stir1}$  (stirrups area) = 78.53982  
 $psh2$  ((5.4d), TBDY) =  $L_{stir2} * A_{stir2} / (A_{sec} * s2) = 0.00067082$   
 $L_{stir2}$  (Length of stirrups along X) = 1468.00  
 $A_{stir2}$  (stirrups area) = 50.26548

-----  
 $A_{sec} = 440000.00$   
 $s1 = 100.00$   
 $s2 = 250.00$   
 $f_{ywe1} = 781.25$   
 $f_{ywe2} = 781.25$   
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY:  $cc = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$

$y1 = 0.00083886$   
 $sh1 = 0.00268436$   
 $ft1 = 314.5735$   
 $fy1 = 262.1446$   
 $su1 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with  $shear\_factor$  and also multiplied by the  $shear\_factor$  according to 15.7.1.4, with  $Shear\_factor = 1.00$

$lo/lou_{min} = lb/ld = 0.13907892$

$su1 = 0.4 * esu1_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu1_{nominal} = 0.08$ ,

For calculation of  $esu1_{nominal}$  and  $y1, sh1, ft1, fy1$ , it is considered characteristic value  $fsy1 = fs1/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 262.1446$

with  $Es1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.00083886$   
 $sh2 = 0.00268436$   
 $ft2 = 314.5735$   
 $fy2 = 262.1446$   
 $su2 = 0.00268436$

using (30) in Biskinis/Fardis (2013) multiplied with  $shear\_factor$  and also multiplied by the  $shear\_factor$  according to 15.7.1.4, with  $Shear\_factor = 1.00$

$lo/lou_{min} = lb/lb_{min} = 0.13907892$

$su2 = 0.4 * esu2_{nominal}$  ((5.5), TBDY) = 0.032

From table 5A.1, TBDY:  $esu2_{nominal} = 0.08$ ,

For calculation of  $esu2_{nominal}$  and  $y2, sh2, ft2, fy2$ , it is considered characteristic value  $fsy2 = fs2/1.2$ , from table 5.1, TBDY.

$y1, sh1, ft1, fy1$ , are also multiplied by  $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.

with  $fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 262.1446$

with  $Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$

$yv = 0.00083886$

$shv = 0.00268436$   
 $ftv = 314.5735$   
 $fyv = 262.1446$   
 $suv = 0.00268436$   
 using (30) in Biskinis/Fardis (2013) multiplied with shear\_factor  
 and also multiplied by the shear\_factor according to 15.7.1.4, with  
 $Shear\_factor = 1.00$   
 $lo/lou,min = lb/ld = 0.13907892$   
 $suv = 0.4 * esuv\_nominal ((5.5), TBDY) = 0.032$   
 From table 5A.1, TBDY:  $esuv\_nominal = 0.08$ ,  
 considering characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY  
 For calculation of  $esuv\_nominal$  and  $yv$ ,  $shv,ftv,fyv$ , it is considered  
 characteristic value  $fsyv = fsv/1.2$ , from table 5.1, TBDY.  
 $y1, sh1,ft1,fy1$ , are also multiplied by  $Min(1,1.25*(lb/ld)^{2/3})$ , from 10.3.5, ASCE 41-17.  
 with  $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 262.1446$   
 with  $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.06824101$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.03513975$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.06202846$

and confined core properties:

$b = 340.00$   
 $d = 677.00$   
 $d' = 13.00$   
 $fcc (5A.2, TBDY) = 38.13135$   
 $cc (5A.5, TBDY) = 0.00471045$   
 $c = \text{confinement factor} = 1.27105$   
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.08384116$   
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.04317283$   
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.07620839$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---

$v < vs,y2$  - LHS eq.(4.5) is satisfied

---

$su (4.9) = 0.2584548$   
 $Mu = MRc (4.14) = 5.0296E+008$   
 $u = su (4.1) = 5.1201636E-006$

-----  
 Calculation of ratio  $lb/ld$   
 -----

Lap Length:  $lb/ld = 0.13907892$

$lb = 300.00$

$ld = 2157.049$

Calculation of  $lb,min$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$ld,min$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (9.1.2, TS500 - No provision in ACI 318)

$= 1$

$db = 16.66667$

Mean strength value of all re-bars:  $fy = 781.25$

Mean concrete strength:  $fc' = (fc'_jacket*Area\_jacket + fc'_core*Area\_core)/Area\_section = 30.00$ , but  $fc'^{0.5} \leq 8.3$

MPa (22.5.3.1, ACI 318-14)

$t = 1.00$

$s = 0.80$

$e = 1.00$

$cb = 25.00$

$Ktr = 1.7174$

$Atr = Min(Atr\_x,Atr\_y) = 257.6106$

where  $Atr\_x, Atr\_y$  are the sum of the area of all stirrup legs along X and Y local axis

$s = Max(s\_external,s\_internal) = 250.00$

$n = 24.00$

-----  
 Calculation of Shear Strength  $Vr = Min(Vr1,Vr2) = 1.0392E+006$   
 -----

Calculation of Shear Strength at edge 1,  $Vr1 = 1.0392E+006$

Vr1 = VCol ((10.3), ASCE 41-17) = knl\*VColO

VColO = 1.0392E+006

kn1 = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av\*fy\*d/s' is replaced by 'Vs+ f\*Vf'  
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'\_jacket\*Area\_jacket + fc'\_core\*Area\_core)/Area\_section = 30.00, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 1308.675

Vu = 0.0001715

d = 0.8\*h = 600.00

Nu = 16273.608

Ag = 300000.00

From (11.5.4.8), ACI 318-14: Vs = Vs,jacket + Vs,core = 1.0138E+006

where:

Vs,jacket = Vs,j1 + Vs,j2 = 903207.888

Vs,j1 = 314159.265 is calculated for section web jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j1 is multiplied by Col,j1 = 1.00

s/d = 0.3125

Vs,j2 = 589048.623 is calculated for section flange jacket, with:

d = 600.00

Av = 157079.633

fy = 625.00

s = 100.00

Vs,j2 is multiplied by Col,j2 = 1.00

s/d = 0.16666667

Vs,core = Vs,c1 + Vs,c2 = 110584.061

Vs,c1 = 0.00 is calculated for section web core, with:

d = 160.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c1 is multiplied by Col,c1 = 0.00

s/d = 1.5625

Vs,c2 = 110584.061 is calculated for section flange core, with:

d = 440.00

Av = 100530.965

fy = 625.00

s = 250.00

Vs,c2 is multiplied by Col,c2 = 1.00

s/d = 0.56818182

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 873250.061

bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 1.0392E+006

Vr2 = VCol ((10.3), ASCE 41-17) = knl\*VColO

VColO = 1.0392E+006

kn1 = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av\*fy\*d/s' is replaced by 'Vs+ f\*Vf'  
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'\_jacket\*Area\_jacket + fc'\_core\*Area\_core)/Area\_section = 30.00, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

Mu = 1308.675

Vu = 0.0001715

$d = 0.8 \cdot h = 600.00$   
 $Nu = 16273.608$   
 $Ag = 300000.00$   
 From (11.5.4.8), ACI 318-14:  $V_s = V_{s,jacket} + V_{s,core} = 1.0138E+006$   
 where:  
 $V_{s,jacket} = V_{s,j1} + V_{s,j2} = 903207.888$   
 $V_{s,j1} = 314159.265$  is calculated for section web jacket, with:  
 $d = 320.00$   
 $A_v = 157079.633$   
 $f_y = 625.00$   
 $s = 100.00$   
 $V_{s,j1}$  is multiplied by  $Col,j1 = 1.00$   
 $s/d = 0.3125$   
 $V_{s,j2} = 589048.623$  is calculated for section flange jacket, with:  
 $d = 600.00$   
 $A_v = 157079.633$   
 $f_y = 625.00$   
 $s = 100.00$   
 $V_{s,j2}$  is multiplied by  $Col,j2 = 1.00$   
 $s/d = 0.16666667$   
 $V_{s,core} = V_{s,c1} + V_{s,c2} = 110584.061$   
 $V_{s,c1} = 0.00$  is calculated for section web core, with:  
 $d = 160.00$   
 $A_v = 100530.965$   
 $f_y = 625.00$   
 $s = 250.00$   
 $V_{s,c1}$  is multiplied by  $Col,c1 = 0.00$   
 $s/d = 1.5625$   
 $V_{s,c2} = 110584.061$  is calculated for section flange core, with:  
 $d = 440.00$   
 $A_v = 100530.965$   
 $f_y = 625.00$   
 $s = 250.00$   
 $V_{s,c2}$  is multiplied by  $Col,c2 = 1.00$   
 $s/d = 0.56818182$   
 $V_f ((11-3)-(11.4), ACI 440) = 0.00$   
 From (11-11), ACI 440:  $V_s + V_f \leq 873250.061$   
 $bw = 400.00$

-----  
 End Of Calculation of Shear Capacity ratio for element: column JLC1 of floor 1  
 At local axis: 2  
 -----

Start Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1  
 At local axis: 3  
 Integration Section: (b)  
 Section Type: rcjlc

Constant Properties

-----  
 Knowledge Factor,  $\phi = 1.00$   
 Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.  
 Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17  
 Consequently:  
 Jacket  
 New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$   
 Existing Column  
 New material of Primary Member: Concrete Strength,  $f_c = f_{cm} = 30.00$   
 New material of Primary Member: Steel Strength,  $f_s = f_{sm} = 625.00$   
 Concrete Elasticity,  $E_c = 25742.96$   
 Steel Elasticity,  $E_s = 200000.00$

Max Height, Hmax = 750.00  
 Min Height, Hmin = 400.00  
 Max Width, Wmax = 750.00  
 Min Width, Wmin = 400.00  
 Jacket Thickness, tj = 100.00  
 Cover Thickness, c = 25.00  
 Element Length, L = 3000.00  
 Primary Member  
 Smooth Bars  
 Ductile Steel  
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)  
 Longitudinal Bars With Ends Lapped Starting at the End Sections  
 Lap Length lb = 300.00  
 No FRP Wrapping

-----  
 Stepwise Properties  
 -----

Bending Moment, M = 293212.583  
 Shear Force, V2 = 7609.421  
 Shear Force, V3 = -213.4386  
 Axial Force, F = -17779.344  
 Longitudinal Reinforcement Area Distribution (in 2 divisions)  
   -Tension: Asl,t = 0.00  
   -Compression: Asl,c = 5353.274  
 Longitudinal Reinforcement Area Distribution (in 3 divisions)  
   -Tension: Asl,ten = 1137.257  
   -Compression: Asl,com = 2208.54  
   -Middle: Asl,mid = 2007.478  
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)  
   -Tension: Asl,ten,jacket = 829.3805  
   -Compression: Asl,com,jacket = 1746.726  
   -Middle: Asl,mid,jacket = 1545.664  
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)  
   -Tension: Asl,ten,core = 307.8761  
   -Compression: Asl,com,core = 461.8141  
   -Middle: Asl,mid,core = 461.8141  
 Mean Diameter of Tension Reinforcement, DbL = 16.80

-----  
 New component: From table 7-7, ASCE 41\_17: Final chord rotation Capacity  $u_{,R} = 1.0^*$   $u = 0.0391696$   
 $u = y + p = 0.0391696$

-----  
 - Calculation of  $y$  -  
 -----

$y = (M_y * L_s / 3) / E_{eff} = 0.00019718$  ((4.29), Biskinis Phd)  
 $M_y = 2.8709E+008$   
 $L_s = M/V$  (with  $L_s > 0.1 * L$  and  $L_s < 2 * L$ ) = 300.00  
 From table 10.5, ASCE 41\_17:  $E_{eff} = factor * E_c * I_g = 1.4560E+014$   
 $factor = 0.30$   
 $A_g = 440000.00$   
 Mean concrete strength:  $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 30.00$   
 $N = 17779.344$   
 $E_c * I_g = E_c * I_{g,jacket} + E_c * I_{g,core} = 4.8532E+014$

-----  
 Calculation of Yielding Moment  $M_y$   
 -----

Calculation of  $y$  and  $M_y$  according to Annex 7 -  
 -----

Assuming neutral axis within flange ( $y < t/d$ , compression zone rectangular) with:  
 flange width, b = 750.00  
 web width, bw = 400.00

flange thickness,  $t = 400.00$

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 2.1455196\text{E}-006$$

$$\text{with } ((10.1), \text{ASCE 41-17}) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 243.3535$$

$$d = 707.00$$

$$y = 0.19784983$$

$$A = 0.01023354$$

$$B = 0.00454395$$

$$\text{with } p_t = 0.00434791$$

$$p_c = 0.00416509$$

$$p_v = 0.00378591$$

$$N = 17779.344$$

$$b = 750.00$$

$$" = 0.06082037$$

$$y_{\text{comp}} = 1.5202265\text{E}-005$$

$$\text{with } f_c = 30.00$$

$$E_c = 25742.96$$

$$y = 0.19516753$$

$$A = 0.01001583$$

$$B = 0.00440616$$

$$\text{with } E_s = 200000.00$$

CONFIRMATION:  $y = 0.19594836 < t/d$

Calculation of ratio  $l_b/l_d$

$$\text{Lap Length: } l_d/l_d, \text{min} = 0.17384865$$

$$l_b = 300.00$$

$$l_d = 1725.639$$

Calculation of  $l$  according to (25.4.3.2), ACI 318-14, using mean values for all the section re-bars.

$l_d, \text{min}$  from (25.4.3.2) is multiplied 2 times to account for smooth re-bars (10.3.5, ASCE 41-17)

$$= 1$$

$$d_b = 16.66667$$

Mean strength value of all re-bars:  $f_y = 625.00$

Mean concrete strength:  $f'_c = (f'_c \cdot \text{jacket} \cdot \text{Area}_{\text{jacket}} + f'_c \cdot \text{core} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 30.00$ , but  $f_c^{0.5} \leq 8.3$  MPa (22.5.3.1, ACI 318-14)

$$t = 1.00$$

$$s = 0.80$$

$$e = 1.00$$

$$c_b = 25.00$$

$$K_{tr} = 1.7174$$

$$A_{tr} = \text{Min}(A_{tr_x}, A_{tr_y}) = 257.6106$$

where  $A_{tr_x}$ ,  $A_{tr_y}$  are the sum of the area of all stirrup legs along X and Y local axis

$$s = \text{Max}(s_{\text{external}}, s_{\text{internal}}) = 250.00$$

$$n = 24.00$$

- Calculation of  $p$  -

From table 10-8:  $p = 0.03897242$

with:

- Columns controlled by inadequate development or splicing along the clear height because  $l_b/l_d < 1$

$$\text{shear control ratio } V_y E / V_{CoI} E = 0.32266369$$

$$d = d_{\text{external}} = 707.00$$

$$s = s_{\text{external}} = 0.00$$

$$- t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00434791$$

$$\text{jacket: } s_1 = A_{v1} \cdot L_{\text{stir1}} / (s_1 \cdot A_g) = 0.00367709$$

$A_{v1} = 78.53982$ , is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir1}} = 2060.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$$s_1 = 100.00$$

$$\text{core: } s_2 = A_{v2} \cdot L_{\text{stir2}} / (s_2 \cdot A_g) = 0.00067082$$

$A_{v2} = 50.26548$ , is the area of every stirrup parallel to loading (shear) direction

$L_{\text{stir2}} = 1468.00$ , is the total Length of all stirrups parallel to loading (shear) direction

$$s_2 = 250.00$$

The term  $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$  is implemented to account for FRP contribution

where  $\rho_f = 2 \cdot t_f / b_w$  is FRP ratio (EC8 - 3, A.4.4.3(6)) and  $f_{fe}/f_s$  normalises  $f$  to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation  $f_s$  of jacket is used.

$$N_{UD} = 17779.344$$

$$A_g = 440000.00$$

$$f_{cE} = (f_{c,jacket} \cdot Area_{jacket} + f_{c,core} \cdot Area_{core}) / section\_area = 30.00$$

$$f_{yIE} = (f_{y,ext\_Long\_Reinf} \cdot Area_{ext\_Long\_Reinf} + f_{y,int\_Long\_Reinf} \cdot Area_{int\_Long\_Reinf}) / Area_{Tot\_Long\_Rein} = 625.00$$

$$f_{yIE} = (f_{y,ext\_Trans\_Reinf} \cdot s_1 + f_{y,int\_Trans\_Reinf} \cdot s_2) / (s_1 + s_2) = 625.00$$

$$p_l = Area_{Tot\_Long\_Rein} / (b \cdot d) = 0.01009575$$

$$b = 750.00$$

$$d = 707.00$$

$$f_{cE} = 30.00$$

-----  
End Of Calculation of Chord Rotation Capacity for element: column JLC1 of floor 1

At local axis: 3

Integration Section: (b)

-----