

Detailed Member Calculations

Units: N&mm

Regulation: ASCE 41-17

Calculation No. 1

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of γ for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, $f_c = f_{cm} = 33.00$
New material: Steel Strength, $f_s = f_{sm} = 555.5556$
Existing Column
Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material: Steel Strength, $f_s = f_{sm} = 444.4444$

External Height, $H = 400.00$
External Width, $W = 400.00$
Internal Height, $H = 200.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -1.3686E+007$
Shear Force, $V_a = -4560.604$
EDGE -B-
Bending Moment, $M_b = 0.04224678$
Shear Force, $V_b = 4560.604$
BOTH EDGES
Axial Force, $F = -5974.983$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 1137.257$
-Compression: $As_c = 1539.38$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 1137.257$
-Compression: $As_{l,com} = 1137.257$
-Middle: $As_{l,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.80$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = *V_n = 409879.624$
 $V_n ((10.3), ASCE 41-17) = knl*V_{CoIo} = 482211.322$

VCol = 482211.322

knl = 1.00

displacement_ductility_demand = 0.03204207

NOTE: In expression (10-3) $V_s = A_v \cdot f_y \cdot d / s$ is replaced by $V_s + f \cdot V_f$
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 22.75$, but $f_c'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

M/Vd = 4.00

$\mu_u = 1.3686E+007$

$V_u = 4560.604$

$d = 0.8 \cdot h = 320.00$

$N_u = 5974.983$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 251327.412$

where:

$V_{s1} = 251327.412$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

V_{s2} is multiplied by $Col2 = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot_a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 405571.497$

$b_w = 400.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END A -

for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 0.0002277$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00710641$ ((4.29), Biskinis Phd)

$M_y = 1.2106E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 3000.891

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 1.7040E+013$

factor = 0.30

$A_g = 160000.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$

$N = 5974.983$

$E_c \cdot I_g = E_{c_{\text{jacket}}} \cdot I_{g_{\text{jacket}}} + E_{c_{\text{core}}} \cdot I_{g_{\text{core}}} = 5.6801E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 5.7839617\text{E-}006$$

$$\text{with } ((10.1), \text{ASCE 41-17}) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 296.8901$$

$$d = 357.00$$

$$y = 0.28109392$$

$$A = 0.01888489$$

$$B = 0.01064175$$

$$\text{with } p_t = 0.00796398$$

$$p_c = 0.00796398$$

$$p_v = 0.00281599$$

$$N = 5974.983$$

$$b = 400.00$$

$$" = 0.12044818$$

$$y_{\text{comp}} = 2.3130538\text{E-}005$$

$$\text{with } f_c^* (12.3, \text{ACI 440}) = 34.65043$$

$$f_l = 33.00$$

$$f_l = 0.93147527$$

$$b = 400.00$$

$$h = 400.00$$

$$A_g = 160000.00$$

$$\text{From } (12.9), \text{ACI 440: } k_a = 0.56518315$$

$$g = p_t + p_c + p_v = 0.01874396$$

$$r_c = 40.00$$

$$A_e/A_c = 0.56518315$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cdot \text{Cos}(b_1) = 1.016$$

$$\text{effective strain from } (12.5) \text{ and } (12.12), e_{fe} = 0.004$$

$$f_u = 0.01$$

$$E_f = 64828.00$$

$$E_c = 26999.444$$

$$y = 0.27975148$$

$$A = 0.01865339$$

$$B = 0.01050082$$

$$\text{with } E_s = 200000.00$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

End Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 2

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $bi: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.8468314E-031$

EDGE -B-

Shear Force, $V_b = 1.8468314E-031$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1137.257$

-Compression: $As_{c,com} = 1137.257$

-Middle: $As_{mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.18171192$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 115036.425$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.7255E+008$

$Mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.7255E+008$

$Mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

ϕ_0 (5A.5, TBDY) = 0.002

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase^* sh_{\min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_2_1 = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_2_2 = 147456.00$

$psh_{\min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

 $psh_x * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

$c =$ confinement factor = 1.13212

$y_1 = 0.00140044$

$sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.538$
 $fy2 = 367.9484$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$

$$\begin{aligned} \text{Mu} &= \text{MRc} (4.14) = 1.7255\text{E}+008 \\ u &= \text{su} (4.1) = 1.7890363\text{E}-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 1.7890363\text{E}-005 \\ \text{Mu} &= 1.7255\text{E}+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 400.00 \\ d &= 357.00 \\ d' &= 43.00 \\ v &= 0.00126831 \\ N &= 5976.808 \\ f_c &= 33.00 \\ c_o (5A.5, \text{TBDY}) &= 0.002 \\ \text{Final value of } \phi_u: \phi_u^* &= \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01608084 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \phi_u &= 0.01608084 \\ \phi_{we} ((5.4c), \text{TBDY}) &= a_{se} * \text{sh}_{, \text{min}} * f_{ywe} / f_{ce} + \text{Min}(\phi_x, \phi_y) = 0.09892348 \\ \text{where } \phi &= a_f * p_f * f_{fe} / f_{ce} \text{ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)} \end{aligned}$$

$$\begin{aligned} \phi_x &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} \phi_y &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} R &= 40.00 \\ \text{Effective FRP thickness, } t_f &= NL * t * \text{Cos}(b_1) = 1.016 \\ f_{u,f} &= 1055.00 \\ E_f &= 64828.00 \\ u_{,f} &= 0.015 \\ a_{se} ((5.4d), \text{TBDY}) &= (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288 \\ a_{se1} &= 0.24250288 \\ b_{o,1} &= 340.00 \\ h_{o,1} &= 340.00 \\ b_{i,1} &= 462400.00 \\ a_{se2} &= \text{Max}(a_{se1}, a_{se2}) = 0.24250288 \\ b_{o,2} &= 192.00 \\ h_{o,2} &= 192.00 \\ b_{i,2} &= 147456.00 \\ p_{sh, \text{min}} * F_{ywe} &= \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633 \end{aligned}$$

$$\begin{aligned} p_{sh,x} * F_{ywe} &= p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.00633 \\ p_{s1} (\text{external}) &= (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699 \\ A_{sh1} &= A_{stir_1} * n_{s_1} = 157.0796 \end{aligned}$$

No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.00633
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00392699
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 160000.00
s₁ = 100.00
s₂ = 250.00
fywe₁ = 694.4444
fywe₂ = 555.5556
fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.538
fy₁ = 367.9484
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*As_{l,ten,jacket} + fs_{core}*As_{l,ten,core})/As_{l,ten} = 367.9484

with Es₁ = (Es_{jacket}*As_{l,ten,jacket} + Es_{core}*As_{l,ten,core})/As_{l,ten} = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814
ft₂ = 441.538
fy₂ = 367.9484
su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 0.30

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*As_{l,com,jacket} + fs_{core}*As_{l,com,core})/As_{l,com} = 367.9484

with Es₂ = (Es_{jacket}*As_{l,com,jacket} + Es_{core}*As_{l,com,core})/As_{l,com} = 200000.00

y_v = 0.00140044
sh_v = 0.0044814
ft_v = 466.813
fy_v = 389.0108
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$

with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.088798$

$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.088798$

$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

$c =$ confinement factor = 1.13212

$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.11405247$

$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.11405247$

$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->

$v < vs_{y2}$ - LHS eq.(4.5) is satisfied

---->

su (4.9) = 0.19835408

$Mu = MRc$ (4.14) = 1.7255E+008

$u = su$ (4.1) = 1.7890363E-005

Calculation of ratio lb/l_d

Inadequate Lap Length with $lb/l_d = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

where ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + Min(fx, fy) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $ff_e = 870.5244$

$fy = 0.07683125$

af = 0.57333333
b = 400.00
h = 400.00
From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508
bw = 400.00
effective stress from (A.35), ff,e = 870.5244

R = 40.00
Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288
ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00
From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30
su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

$y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $fy_2 = 367.9484$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{u,min} = lb/lb_{u,min} = 0.30$
 $su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 367.9484$
 with $Es_2 = (Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$

$y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $fy_v = 389.0108$
 $su_v = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{u,min} = lb/ld = 0.30$
 $su_v = 0.4 * esu_{v,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{v,nominal} = 0.08$,
 considering characteristic value $fsy_v = fs_v/1.2$, from table 5.1, TBDY
 For calculation of $esu_{v,nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsy_v = fs_v/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_v = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$
 with $Es_v = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.088798$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.088798$
 $v = Asl_{mid} / (b * d) * (fs_v / fc) = 0.03319551$

and confined core properties:

$b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.11405247$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.11405247$
 $v = Asl_{mid} / (b * d) * (fs_v / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->
 $v < v_s, y_2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$
 $Mu = MRc (4.14) = 1.7255E+008$
 $u = su (4.1) = 1.7890363E-005$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu_2 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005
Mu = 1.7255E+008

with full section properties:

b = 400.00
d = 357.00
d' = 43.00
v = 0.00126831
N = 5976.808
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{\min} * fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.09892348$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

fy = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

R = 40.00

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288

bo_1 = 340.00

ho_1 = 340.00

bi2_1 = 462400.00

ase2 = $\text{Max}(ase1, ase2) = 0.24250288$

bo_2 = 192.00

ho_2 = 192.00

bi2_2 = 147456.00

$psh_{\min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

$psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

Asec = 160000.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.4444

fywe2 = 555.5556

fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119

c = confinement factor = 1.13212

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.538

fy1 = 367.9484

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.538

fy2 = 367.9484

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

$$cc(5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

$$su(4.9) = 0.19835408$$

$$Mu = MRc(4.14) = 1.7255E+008$$

$$u = su(4.1) = 1.7890363E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 633070.334$

Calculation of Shear Strength at edge 1, $V_{r1} = 633070.334$

$$V_{r1} = V_{CoI}((10.3), ASCE 41-17) = knl * V_{CoIO}$$

$$V_{CoIO} = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} = f * V_f$
where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 29.75$, but $fc'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$Mu = 8.4878329E-012$$

$$Vu = 1.8468314E-031$$

$$d = 0.8 * h = 320.00$$

$$Nu = 5976.808$$

$$Ag = 160000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 279252.68$$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.5556$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 0.00$ is calculated for core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 444.4444$$

$$s = 250.00$$

V_{s2} is multiplied by $Col2 = 0.00$

$$s/d = 1.5625$$

$$V_f((11-3)-(11.4), ACI 440) = 188111.148$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$$V_f = \text{Min}(|V_f(45, 1)|, |V_f(-45, a1)|), \text{ with:}$$

$$\text{total thickness per orientation, } tf1 = NL * t / NoDir = 1.016$$

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 633070.334
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 29.75, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00
Mu = 8.4878329E-012
Vu = 1.8468314E-031
d = 0.8*h = 320.00
Nu = 5976.808
Ag = 160000.00
From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68
where:

Vs1 = 279252.68 is calculated for jacket, with:
d = 320.00
Av = 157079.633
fy = 555.5556
s = 100.00

Vs1 is multiplied by Col1 = 1.00
s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:
d = 160.00
Av = 100530.965
fy = 444.4444
s = 250.00

Vs2 is multiplied by Col2 = 0.00
s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148
f = 0.95, for fully-wrapped sections
wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) sin + cos is replaced with (cot + cota)sina which is more a generalised expression,
where is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(,), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, = 45° and = -45° to take into consideration the cyclic seismic loading.

orientation 1: 1 = b1 + 90° = 90.00

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:
total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = 3.2548216E-032$

EDGE -B-

Shear Force, $V_b = -3.2548216E-032$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 1137.257$
-Compression: $Asl,com = 1137.257$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 0.18171192$

Member Controlled by Flexure ($Ve/Vr < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 115036.425$

with

$Mpr1 = \text{Max}(Mu1+, Mu1-) = 1.7255E+008$

$Mu1+ = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu1- = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$Mpr2 = \text{Max}(Mu2+, Mu2-) = 1.7255E+008$

$Mu2+ = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu2- = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$\phi_{co} (5A.5, TBDY) = 0.002$

Final value of ϕ_{cu} : $\phi_{cu}^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_{cu} = 0.01608084$

where $\phi_{we} ((5.4c), TBDY) = \phi_{ase} * \text{sh}_{,min} * f_{ywe} / f_{ce} + \text{Min}(\phi_{fx}, \phi_{fy}) = 0.09892348$

where $\phi_f = \phi_{af} * \phi_{pf} * \phi_{ffe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$\phi_{fx} = 0.07683125$

$\phi_{af} = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $\phi_{pf} = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $\phi_{ffe} = 870.5244$

$\phi_{fy} = 0.07683125$

$\phi_{af} = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $\phi_{pf} = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $\phi_{ffe} = 870.5244$

$R = 40.00$

Effective FRP thickness, $t_f = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$\phi_{ase} ((5.4d), TBDY) = (\phi_{ase1} * A_{ext} + \phi_{ase2} * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 367.9484$

with $Es_2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.813$

$fy_v = 389.0108$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot A_{sl,mid,jacket} + fs_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 389.0108$

with $Esv = (Es_{jacket} \cdot A_{sl,mid,jacket} + Es_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

$1 = A_{sl,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.088798$

$2 = A_{sl,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.088798$

$v = A_{sl,mid} / (b \cdot d) \cdot (fsv / fc) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

$1 = A_{sl,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.11405247$

$2 = A_{sl,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.11405247$

$v = A_{sl,mid} / (b \cdot d) \cdot (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

$Mu = MRc$ (4.14) = 1.7255E+008

$u = su$ (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_{2,1} = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_{2,2} = 147456.00$

$psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

c = confinement factor = 1.13212

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.538$

$f_{y1} = 367.9484$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{s_{u1,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u1,nominal}} = 0.08$,
 For calculation of $e_{s_{u1,nominal}}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{s_{y1}} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 367.9484$
 with $E_{s1} = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $f_{y2} = 367.9484$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{s_{u2,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u2,nominal}} = 0.08$,
 For calculation of $e_{s_{u2,nominal}}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{s_{y2}} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_2, sh_2, ft_2, f_{y2} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} * A_{s2,com,jacket} + f_{s,core} * A_{s2,com,core}) / A_{s2,com} = 367.9484$
 with $E_{s2} = (E_{s,jacket} * A_{s2,com,jacket} + E_{s,core} * A_{s2,com,core}) / A_{s2,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $f_{y_v} = 389.0108$
 $s_{u_v} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u_v} = 0.4 * e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,
 considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY
 For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_v} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 389.0108$
 with $E_{s_v} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.088798$
 $2 = A_{s2,com} / (b * d) * (f_{s2} / f_c) = 0.088798$
 $v = A_{s,mid} / (b * d) * (f_{s_v} / f_c) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.11405247$
 $2 = A_{s2,com} / (b * d) * (f_{s2} / f_c) = 0.11405247$
 $v = A_{s,mid} / (b * d) * (f_{s_v} / f_c) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.19835408$
 $M_u = M_{Rc} (4.14) = 1.7255E+008$
 $u = s_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$\mu_u = 1.7890363E-005$$

$$\mu_{2+} = 1.7255E+008$$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$\alpha_{co} \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_{cu}: \mu_{cu}^* = \text{shear_factor} * \text{Max}(\mu_{cu}, \mu_{cc}) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_{cu} = 0.01608084$$

$$\mu_{we} \text{ ((5.4c), TBDY)} = \alpha_{se} * \text{sh}_{,\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$$

where $f_x = \alpha_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.07683125$$

$$\alpha_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{fe} = 870.5244$$

$$f_y = 0.07683125$$

$$\alpha_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{fe} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = NL * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$\alpha_{se} \text{ ((5.4d), TBDY)} = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$\alpha_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,1} = 462400.00$$

$$\alpha_{se2} = \text{Max}(\alpha_{se1}, \alpha_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2} = 147456.00$$

$$p_{sh,\min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$ps_2 \text{ (internal)} = (Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$$

$$Ash_2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h_2 = 200.00$$

$$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$$

$$ps_1 \text{ (external)} = (Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$$

$$Ash_1 = Astir_1 * ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h_1 = 400.00$$

$$ps_2 \text{ (internal)} = (Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$$

$$Ash_2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 160000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$fy_{we1} = 694.4444$$

$$fy_{we2} = 555.5556$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 441.538$$

$$fy_1 = 367.9484$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 0.30$$

$$su_1 = 0.4 * esu_1 \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_1 \text{ nominal} = 0.08,$$

For calculation of $esu_1 \text{ nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1 / 1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = (fs_{jacket} * A_{sl, ten, jacket} + fs_{core} * A_{sl, ten, core}) / A_{sl, ten} = 367.9484$$

$$\text{with } Es_1 = (Es_{jacket} * A_{sl, ten, jacket} + Es_{core} * A_{sl, ten, core}) / A_{sl, ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.538$$

$$fy_2 = 367.9484$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 0.30$$

$$su_2 = 0.4 * esu_2 \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_2 \text{ nominal} = 0.08,$$

For calculation of $esu_2 \text{ nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2 / 1.2$, from table 5.1, TBDY.

$$y_2, sh_2, ft_2, fy_2, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_2 = (fs_{jacket} * A_{sl, com, jacket} + fs_{core} * A_{sl, com, core}) / A_{sl, com} = 367.9484$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl, com, jacket} + Es_{core} * A_{sl, com, core}) / A_{sl, com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.813$$

$$fy_v = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 0.30$$

$$suv = 0.4 * esuv \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esuv \text{ nominal} = 0.08,$$

considering characteristic value $fsyv = fsv / 1.2$, from table 5.1, TBDY

For calculation of $\epsilon_{sv_nominal}$ and γ_v , η_v , f_{tv} , f_{yv} , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , η_1 , f_{t1} , f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $\epsilon_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.19835408

$M_u = M_{Rc}$ (4.14) = 1.7255E+008

$u = \mu_u$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

cc (5A.5, TBDY) = 0.002

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.01608084$

η_v ((5.4c), TBDY) = $\eta_v \cdot \text{Min}(f_x, f_y) / f_{ce} = 0.09892348$

where $f = \eta_v \cdot \text{Min}(f_x, f_y) / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$\eta_v = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $\eta_v = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$f_y = 0.07683125$

$\eta_v = 0.57333333$

$b = 400.00$

h = 400.00
From EC8 A4.4.3(6), $pf = 2tf/bw = 0.00508$
bw = 400.00
effective stress from (A.35), $ff,e = 870.5244$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $ase((5.4d), \text{TBDY}) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.24250288$
 $ase1 = 0.24250288$
 $bo_1 = 340.00$
 $ho_1 = 340.00$
 $bi2_1 = 462400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.24250288$
 $bo_2 = 192.00$
 $ho_2 = 192.00$
 $bi2_2 = 147456.00$
 $psh_{,min}*F_{ywe} = \text{Min}(psh_{,x}*F_{ywe}, psh_{,y}*F_{ywe}) = 3.00633$

$psh_{,x}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$psh_{,y}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 160000.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 694.4444$
 $f_{ywe2} = 555.5556$
 $f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$
 $c = \text{confinement factor} = 1.13212$

$y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou_{,min} = lb/ld = 0.30$

$su1 = 0.4*esu1_{,nominal}((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu1_{,nominal} = 0.08$,

For calculation of $esu1_{,nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{,jacket}*A_{sl,ten,jacket} + fs_{,core}*A_{sl,ten,core})/A_{sl,ten} = 367.9484$

with $Es1 = (Es_{,jacket}*A_{sl,ten,jacket} + Es_{,core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 37.35991$$

$$cc (5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.19835408$$

$$Mu = MRc (4.14) = 1.7255E+008$$

$$u = su (4.1) = 1.7890363E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 633070.334$

Calculation of Shear Strength at edge 1, $Vr1 = 633070.334$

$$Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0$$

$$VCol0 = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$\nu_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.5556$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 444.4444$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \text{cota})\sin\alpha$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 463788.751$

$b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col0}}$

$V_{\text{Col0}} = 633070.334$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$\nu_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \cot \alpha) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, α)|), with:

total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 463788.751

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

External Height, H = 400.00

External Width, W = 400.00

Internal Height, H = 200.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $bi: 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

 Stepwise Properties

Bending Moment, $M = -1.6937287E-010$
 Shear Force, $V_2 = -4560.604$
 Shear Force, $V_3 = 9.4294951E-014$
 Axial Force, $F = -5974.983$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $As_{lt} = 1137.257$
 -Compression: $As_{lc} = 1539.38$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten} = 1137.257$
 -Compression: $As_{l,com} = 1137.257$
 -Middle: $As_{l,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,jacket} = 829.3805$
 -Compression: $As_{l,com,jacket} = 829.3805$
 -Middle: $As_{l,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,core} = 307.8761$
 -Compression: $As_{l,com,core} = 307.8761$
 -Middle: $As_{l,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 16.80$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.00301933$
 $u = y + p = 0.00355215$

 - Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00355215$ ((4.29), Biskinis Phd)
 $M_y = 1.2106E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1500.00
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7040E+013$
 $factor = 0.30$
 $A_g = 160000.00$
 Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 29.75$
 $N = 5974.983$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 5.6801E+013$

 Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.7839617E-006$
 with $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109392$
 $A = 0.01888489$
 $B = 0.01064175$
 with $pt = 0.00680079$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.983$
 $b = 400.00$
 $" = 0.12044818$

$y_{comp} = 2.3130538E-005$
 with $f_c^* (12.3, (ACI 440)) = 34.65043$
 $f_c = 33.00$
 $f_l = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $A_g = 160000.00$
 From (12.9), ACI 440: $k_a = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $A_e/A_c = 0.56518315$
 Effective FRP thickness, $t_f = NL \cdot t \cdot \text{Cos}(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975148$
 $A = 0.01865339$
 $B = 0.01050082$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.18171192$

$d = d_{external} = 357.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00680079$

jacket: $s_1 = A_{v1} \cdot h_1 / (s_1 \cdot A_g) = 0.00392699$

$A_{v1} = 157.0796$, is the total area of all stirrups parallel to loading (shear) direction

$h_1 = 400.00$

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot h_2 / (s_2 \cdot A_g) = 0.00050265$

$A_{v2} = 100.531$, is the total area of all stirrups parallel to loading (shear) direction

$h_2 = 200.00$

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$NUD = 5974.983$

$A_g = 160000.00$

$f_c E = (f_{c,jacket} \cdot \text{Area}_{jacket} + f_{c,core} \cdot \text{Area}_{core}) / \text{section_area} = 29.75$

$f_y E = (f_{y,ext_Long_Reinf} \cdot \text{Area}_{ext_Long_Reinf} + f_{y,int_Long_Reinf} \cdot \text{Area}_{int_Long_Reinf}) / \text{Area}_{Tot_Long_Rein} = 529.9948$

$f_y E = (f_{y,ext_Trans_Reinf} \cdot \text{Area}_{ext_Trans_Reinf} + f_{y,int_Trans_Reinf} \cdot \text{Area}_{int_Trans_Reinf}) / \text{Area}_{Tot_Trans_Rein} =$

542.9472

$pl = \text{Area_Tot_Long_Rein}/(b*d) = 0.01874396$

$b = 400.00$

$d = 357.00$

$f_{cE} = 29.75$

End Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 3

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of γ for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, $f_c = f_{cm} = 33.00$
New material: Steel Strength, $f_s = f_{sm} = 555.5556$
Existing Column
Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material: Steel Strength, $f_s = f_{sm} = 444.4444$

External Height, $H = 400.00$
External Width, $W = 400.00$
Internal Height, $H = 200.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -1.6937287E-010$
Shear Force, $V_a = 9.4294951E-014$
EDGE -B-
Bending Moment, $M_b = -1.1352078E-010$
Shear Force, $V_b = -9.4294951E-014$
BOTH EDGES
Axial Force, $F = -5974.983$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 1137.257$
-Compression: $As_c = 1539.38$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 1137.257$
-Compression: $As_{l,com} = 1137.257$
-Middle: $As_{l,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.80$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $VR = *V_n = 475023.475$
 $V_n ((10.3), ASCE 41-17) = knl * V_{ColO} = 558851.147$
 $V_{Col} = 558851.147$
 $knl = 1.00$

displacement_ductility_demand = 0.00

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 22.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.6937287E-010$

$\nu_u = 9.4294951E-014$

$d = 0.8 \cdot h = 320.00$

$N_u = 5974.983$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 251327.412$

where:

$V_{s1} = 251327.412$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \csc) \sin \alpha$ which is more a generalised expression, where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 405571.497$

$b_w = 400.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 5.1296730E-022$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00355215$ ((4.29), Biskinis Phd)

$M_y = 1.2106E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 1.7040E+013$

factor = 0.30

$A_g = 160000.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$

$N = 5974.983$

$E_c \cdot I_g = E_c \cdot I_{g_{\text{jacket}}} + E_c \cdot I_{g_{\text{core}}} = 5.6801E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 5.7839617\text{E-}006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109392$
 $A = 0.01888489$
 $B = 0.01064175$
with $pt = 0.00796398$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.983$
 $b = 400.00$
 $" = 0.12044818$
 $y_{\text{comp}} = 2.3130538\text{E-}005$
with $fc^* (12.3, (ACI 440)) = 34.65043$
 $fc = 33.00$
 $fl = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $Ag = 160000.00$
From (12.9), ACI 440: $ka = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $Ae/Ac = 0.56518315$
Effective FRP thickness, $tf = NL \cdot t \cdot \text{Cos}(\theta_1) = 1.016$
effective strain from (12.5) and (12.12), $e_{fe} = 0.004$
 $fu = 0.01$
 $Ef = 64828.00$
 $Ec = 26999.444$
 $y = 0.27975148$
 $A = 0.01865339$
 $B = 0.01050082$
with $Es = 200000.00$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

End Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 4

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (ϕ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $bi: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.8468314E-031$

EDGE -B-

Shear Force, $V_b = 1.8468314E-031$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1137.257$

-Compression: $As_{c,com} = 1137.257$

-Middle: $As_{mid} = 402.1239$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.18171192$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 115036.425$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.7255E+008$

$Mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.7255E+008$

$Mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$\alpha (\text{5A.5, TBDY}) = 0.002$

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase^* sh_{\min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_2_1 = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_2_2 = 147456.00$

$psh_{\min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

 $psh_x * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

$c =$ confinement factor = 1.13212

$y_1 = 0.00140044$

$sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.538$
 $fy2 = 367.9484$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$

$$\begin{aligned} \text{Mu} &= \text{MRc} (4.14) = 1.7255\text{E}+008 \\ u &= \text{su} (4.1) = 1.7890363\text{E}-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.7890363\text{E}-005$
 $\text{Mu} = 1.7255\text{E}+008$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$c_o (5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.01608084$$

$$\phi_{we} ((5.4c), \text{TBDY}) = a_{se} * \phi_{sh, \min} * f_{ywe} / f_{ce} + \text{Min}(\phi_{fx}, \phi_{fy}) = 0.09892348$$

where $\phi_{fx} = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$\phi_{fx} = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$\phi_{fy} = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} ((5.4d), \text{TBDY}) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$a_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,2,1} = 462400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2,2} = 147456.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.00633$$

$$p_{s1} (\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.00633
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00392699
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 160000.00
s₁ = 100.00
s₂ = 250.00
fywe₁ = 694.4444
fywe₂ = 555.5556
fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.538
fy₁ = 367.9484
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su₁ = 0.4*esu₁_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu₁_nominal = 0.08,

For calculation of esu₁_nominal and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es₁ = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814
ft₂ = 441.538
fy₂ = 367.9484
su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su₂ = 0.4*esu₂_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu₂_nominal = 0.08,

For calculation of esu₂_nominal and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es₂ = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

y_v = 0.00140044
sh_v = 0.0044814
ft_v = 466.813
fy_v = 389.0108
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,
considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{suv_nominal}$ and γ_v , sh_v, ft_v, fy_v , it is considered
characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

$\gamma_1, sh_1, ft_1, fy_1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

1 = $A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

2 = $A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = $A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

2 = $A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

---->

su (4.9) = 0.19835408

$Mu = MR_c$ (4.14) = 1.7255E+008

$u = su$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

where ((5.4c), TBDY) = $ase \cdot sh_{\min} \cdot fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.09892348$

where $f = af \cdot pf \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$fy = 0.07683125$

af = 0.57333333
b = 400.00
h = 400.00
From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508
bw = 400.00
effective stress from (A.35), ff,e = 870.5244

R = 40.00
Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288
ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00
From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30
su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247

2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247

v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005
Mu = 1.7255E+008

with full section properties:

b = 400.00
d = 357.00
d' = 43.00
v = 0.00126831
N = 5976.808
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.09892348$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

fy = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

R = 40.00

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288

bo_1 = 340.00

ho_1 = 340.00

bi2_1 = 462400.00

ase2 = $\text{Max}(ase1, ase2) = 0.24250288$

bo_2 = 192.00

ho_2 = 192.00

bi2_2 = 147456.00

$psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

$psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

Asec = 160000.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.4444

fywe2 = 555.5556

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119

c = confinement factor = 1.13212

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.538

fy1 = 367.9484

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.538

fy2 = 367.9484

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

$$cc(5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.11405247$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11405247$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.19835408$$

$$M_u = MR_c(4.14) = 1.7255E+008$$

$$u = s_u(4.1) = 1.7890363E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 633070.334$

Calculation of Shear Strength at edge 1, $V_{r1} = 633070.334$

$$V_{r1} = V_{CoI}((10.3), ASCE 41-17) = knl * V_{CoIO}$$

$$V_{CoIO} = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} = f * V_f$
where V_f is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 29.75$, but $f_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$M_u = 8.4878329E-012$$

$$V_u = 1.8468314E-031$$

$$d = 0.8 * h = 320.00$$

$$N_u = 5976.808$$

$$A_g = 160000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 279252.68$$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.5556$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 0.00$ is calculated for core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 444.4444$$

$$s = 250.00$$

V_{s2} is multiplied by $Col2 = 0.00$

$$s/d = 1.5625$$

$$V_f((11-3)-(11.4), ACI 440) = 188111.148$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$$V_f = \text{Min}(|V_f(45, 1)|, |V_f(-45, a1)|), \text{ with:}$$

$$\text{total thickness per orientation, } t_{f1} = NL * t / \text{NoDir} = 1.016$$

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 633070.334
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*VF'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 29.75, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00
Mu = 8.4878329E-012
Vu = 1.8468314E-031
d = 0.8*h = 320.00
Nu = 5976.808
Ag = 160000.00
From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68
where:

Vs1 = 279252.68 is calculated for jacket, with:
d = 320.00
Av = 157079.633
fy = 555.5556
s = 100.00

Vs1 is multiplied by Col1 = 1.00
s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:
d = 160.00
Av = 100530.965
fy = 444.4444
s = 250.00

Vs2 is multiplied by Col2 = 0.00
s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148
f = 0.95, for fully-wrapped sections
wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) sin + cos is replaced with (cot + cota)sina which is more a generalised expression,
where is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(,), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, = 45° and = -45° to take into consideration the cyclic seismic loading.

orientation 1: 1 = b1 + 90° = 90.00

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:
total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket
New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.4444$
Existing Column
Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.5556$
#####

External Height, $H = 400.00$
External Width, $W = 400.00$
Internal Height, $H = 200.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.13212
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $b_i = 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 3.2548216E-032$
EDGE -B-
Shear Force, $V_b = -3.2548216E-032$
BOTH EDGES
Axial Force, $F = -5976.808$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 2676.637$
Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 1137.257$
-Compression: $Asl,com = 1137.257$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 0.18171192$

Member Controlled by Flexure ($Ve/Vr < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 115036.425$

with
 $Mpr1 = \text{Max}(\mu_{1+}, \mu_{1-}) = 1.7255E+008$
 $\mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $\mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $Mpr2 = \text{Max}(\mu_{2+}, \mu_{2-}) = 1.7255E+008$
 $\mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $\mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$\mu = 1.7890363E-005$
 $\mu_u = 1.7255E+008$

with full section properties:

$b = 400.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.00126831$
 $N = 5976.808$
 $f_c = 33.00$
 $\alpha_1 (5A.5, TBDY) = 0.002$
Final value of α_1 : $\alpha_1 = \text{shear_factor} * \text{Max}(\alpha_c, \alpha_{cc}) = 0.01608084$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\alpha_1 = 0.01608084$
 $\alpha_{we} ((5.4c), TBDY) = \alpha_{se} * \text{sh}_{,min} * f_{ywe}/f_{ce} + \text{Min}(\alpha_{fx}, \alpha_{fy}) = 0.09892348$
where $\alpha_{fx} = \alpha_{pf} * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$\alpha_{fx} = 0.07683125$
 $\alpha_{pf} = 0.57333333$
 $b = 400.00$
 $h = 400.00$
From EC8 A.4.4.3(6), $\alpha_{pf} = 2t_f/bw = 0.00508$
 $bw = 400.00$
effective stress from (A.35), $f_{fe} = 870.5244$

$\alpha_{fy} = 0.07683125$
 $\alpha_{pf} = 0.57333333$
 $b = 400.00$
 $h = 400.00$
From EC8 A.4.4.3(6), $\alpha_{pf} = 2t_f/bw = 0.00508$
 $bw = 400.00$
effective stress from (A.35), $f_{fe} = 870.5244$

$R = 40.00$
Effective FRP thickness, $t_f = NL * t * \text{Cos}(b_1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $\alpha_{se} ((5.4d), TBDY) = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (f_s \cdot \text{jacket} \cdot A_{s1, \text{com, jacket}} + f_s \cdot \text{core} \cdot A_{s1, \text{com, core}}) / A_{s1, \text{com}} = 367.9484$

with $Es_2 = (E_s \cdot \text{jacket} \cdot A_{s1, \text{com, jacket}} + E_s \cdot \text{core} \cdot A_{s1, \text{com, core}}) / A_{s1, \text{com}} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.813$

$fy_v = 389.0108$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o, \text{min}} = l_b/l_d = 0.30$

$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fs_yv = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fs_yv = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_s \cdot \text{jacket} \cdot A_{s1, \text{mid, jacket}} + f_s \cdot \text{mid} \cdot A_{s1, \text{mid, core}}) / A_{s1, \text{mid}} = 389.0108$

with $E_{sv} = (E_s \cdot \text{jacket} \cdot A_{s1, \text{mid, jacket}} + E_s \cdot \text{mid} \cdot A_{s1, \text{mid, core}}) / A_{s1, \text{mid}} = 200000.00$

$1 = A_{s1, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$2 = A_{s1, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$v = A_{s1, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, \text{TBDY}) = 37.35991$

$cc (5A.5, \text{TBDY}) = 0.00332119$

$c = \text{confinement factor} = 1.13212$

$1 = A_{s1, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$2 = A_{s1, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$v = A_{s1, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s, y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.19835408$

$Mu = MRc (4.14) = 1.7255E+008$

$u = su (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$cc (5A.5, \text{TBDY}) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $a_{se} \cdot \text{sh}_{\min} \cdot f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = a_f \cdot p_f \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f / b_w = 0.00508$

$b_w = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$f_y = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f / b_w = 0.00508$

$b_w = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$R = 40.00$

Effective FRP thickness, $t_f = N_L \cdot t \cdot \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

a_{se} ((5.4d), TBDY) = $(a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.24250288$

$a_{se1} = 0.24250288$

$b_{o,1} = 340.00$

$h_{o,1} = 340.00$

$b_{i,2,1} = 462400.00$

$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.24250288$

$b_{o,2} = 192.00$

$h_{o,2} = 192.00$

$b_{i,2,2} = 147456.00$

$p_{sh,\min} \cdot F_{ywe} = \text{Min}(p_{sh,x} \cdot F_{ywe}, p_{sh,y} \cdot F_{ywe}) = 3.00633$

$p_{sh,x} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.00633$

p_{s1} (external) = $(A_{sh1} \cdot h_1 / s_1) / A_{sec} = 0.00392699$

$A_{sh1} = A_{stir,1} \cdot n_{s,1} = 157.0796$

No stirups, $n_{s,1} = 2.00$

$h_1 = 400.00$

p_{s2} (internal) = $(A_{sh2} \cdot h_2 / s_2) / A_{sec} = 0.00050265$

$A_{sh2} = A_{stir,2} \cdot n_{s,2} = 100.531$

No stirups, $n_{s,2} = 2.00$

$h_2 = 200.00$

$p_{sh,y} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.00633$

p_{s1} (external) = $(A_{sh1} \cdot h_1 / s_1) / A_{sec} = 0.00392699$

$A_{sh1} = A_{stir,1} \cdot n_{s,1} = 157.0796$

No stirups, $n_{s,1} = 2.00$

$h_1 = 400.00$

p_{s2} (internal) = $(A_{sh2} \cdot h_2 / s_2) / A_{sec} = 0.00050265$

$A_{sh2} = A_{stir,2} \cdot n_{s,2} = 100.531$

No stirups, $n_{s,2} = 2.00$

$h_2 = 200.00$

$A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 694.4444$

$f_{ywe2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00332119$

c = confinement factor = 1.13212

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.538$

$f_{y1} = 367.9484$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,
 For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{s1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 367.9484$
 with $E_{s1} = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $f_{y2} = 367.9484$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,
 For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_2, sh_2, ft_2, f_{y2} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 367.9484$
 with $E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $f_{y_v} = 389.0108$
 $s_{u_v} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u_v} = 0.4 * e_{s_{u_v}}_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u_v}}_nominal = 0.08$,
 considering characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY
 For calculation of $e_{s_{u_v}}_nominal$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_{u_v}} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 389.0108$
 with $E_{s_{u_v}} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.088798$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.088798$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.11405247$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.11405247$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.19835408$
 $M_u = M_{Rc} (4.14) = 1.7255E+008$
 $u = s_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7890363E-005$$

$$\mu = 1.7255E+008$$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01608084$$

$$\mu_e \text{ ((5.4c), TBDY)} = a_{se} * \text{sh}_{,min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$f_y = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$a_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,1} = 462400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2} = 147456.00$$

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$ps_2 \text{ (internal)} = (Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$$

$$Ash_2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h_2 = 200.00$$

$$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$$

$$ps_1 \text{ (external)} = (Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$$

$$Ash_1 = Astir_1 * ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h_1 = 400.00$$

$$ps_2 \text{ (internal)} = (Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$$

$$Ash_2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 160000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$fy_{we1} = 694.4444$$

$$fy_{we2} = 555.5556$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 441.538$$

$$fy_1 = 367.9484$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 0.30$$

$$su_1 = 0.4 * esu_1 \text{ nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_1 \text{ nominal} = 0.08$,

For calculation of $esu_1 \text{ nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1 / 1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{jacket} * A_{sl, \text{ten, jacket}} + fs_{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 367.9484$$

$$\text{with } Es_1 = (Es_{jacket} * A_{sl, \text{ten, jacket}} + Es_{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.538$$

$$fy_2 = 367.9484$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 0.30$$

$$su_2 = 0.4 * esu_2 \text{ nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_2 \text{ nominal} = 0.08$,

For calculation of $esu_2 \text{ nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2 / 1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{jacket} * A_{sl, \text{com, jacket}} + fs_{core} * A_{sl, \text{com, core}}) / A_{sl, \text{com}} = 367.9484$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl, \text{com, jacket}} + Es_{core} * A_{sl, \text{com, core}}) / A_{sl, \text{com}} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.813$$

$$fy_v = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 0.30$$

$$suv = 0.4 * esuv \text{ nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esuv \text{ nominal} = 0.08$,

considering characteristic value $fsyv = fsv / 1.2$, from table 5.1, TBDY

For calculation of $\epsilon_{sv_nominal}$ and γ_v , η_v , f_{tv} , f_{yv} , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , η_1 , f_{t1} , f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $\epsilon_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.19835408

$M_u = M_{Rc}$ (4.14) = 1.7255E+008

$u = \mu_u$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

cc (5A.5, TBDY) = 0.002

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.01608084$

η_v ((5.4c), TBDY) = $a_s \cdot \eta_{v,min} \cdot f_{ywe} / f_{ce} + \text{Min}(\gamma_x, \gamma_y) = 0.09892348$

where $f = a_s \cdot p_f \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$f_y = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

h = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.00508$
bw = 400.00
effective stress from (A.35), $ff,e = 870.5244$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $ase((5.4d), \text{TBDY}) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.24250288$
 $ase1 = 0.24250288$
 $bo_1 = 340.00$
 $ho_1 = 340.00$
 $bi2_1 = 462400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.24250288$
 $bo_2 = 192.00$
 $ho_2 = 192.00$
 $bi2_2 = 147456.00$
 $psh_{,min}*F_{ywe} = \text{Min}(psh_{,x}*F_{ywe}, psh_{,y}*F_{ywe}) = 3.00633$

$psh_{,x}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$psh_{,y}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 160000.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 694.4444$
 $f_{ywe2} = 555.5556$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$
 $su1 = 0.4*esu1_{nominal}((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket}*A_{sl,ten,jacket} + fs_{core}*A_{sl,ten,core})/A_{sl,ten} = 367.9484$

with $Es1 = (Es_{jacket}*A_{sl,ten,jacket} + Es_{core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and $y2$, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$y1$, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv , shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

$y1$, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 37.35991$$

$$cc (5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.19835408$$

$$Mu = MRc (4.14) = 1.7255E+008$$

$$u = su (4.1) = 1.7890363E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 633070.334$

Calculation of Shear Strength at edge 1, $Vr1 = 633070.334$

$$Vr1 = VCol ((10.3), ASCE 41-17) = knl*VColO$$

$$VColO = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.5556$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 444.4444$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \text{cota})\sin\alpha$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha_1 = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha_1)|, |V_f(-45, \alpha_1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / N_{\text{Dir}} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 463788.751$

$b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col}0}$

$V_{\text{Col}0} = 633070.334$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, θ)|), with:

total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 463788.751

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

External Height, H = 400.00

External Width, W = 400.00

Internal Height, H = 200.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $bi: 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

 Stepwise Properties

 Bending Moment, $M = -1.3686E+007$
 Shear Force, $V2 = -4560.604$
 Shear Force, $V3 = 9.4294951E-014$
 Axial Force, $F = -5974.983$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $As_{lt} = 1137.257$
 -Compression: $As_{lc} = 1539.38$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten} = 1137.257$
 -Compression: $As_{l,com} = 1137.257$
 -Middle: $As_{l,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,jacket} = 829.3805$
 -Compression: $As_{l,com,jacket} = 829.3805$
 -Middle: $As_{l,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,core} = 307.8761$
 -Compression: $As_{l,com,core} = 307.8761$
 -Middle: $As_{l,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 16.80$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.00604045$
 $u = y + p = 0.00710641$

 - Calculation of y -

 $y = (M_y * L_s / 3) / E_{eff} = 0.00710641$ ((4.29), Biskinis Phd)
 $M_y = 1.2106E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 3000.891
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7040E+013$
 $factor = 0.30$
 $A_g = 160000.00$
 Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 29.75$
 $N = 5974.983$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 5.6801E+013$

 Calculation of Yielding Moment M_y

 Calculation of y and M_y according to Annex 7 -

 $y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.7839617E-006$
 with $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 * f_y * (l_b / l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109392$
 $A = 0.01888489$
 $B = 0.01064175$
 with $pt = 0.00680079$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.983$
 $b = 400.00$
 $" = 0.12044818$

$y_{comp} = 2.3130538E-005$
 with $f_c^* (12.3, (ACI 440)) = 34.65043$
 $f_c = 33.00$
 $f_l = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $A_g = 160000.00$
 From (12.9), ACI 440: $k_a = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $A_e / A_c = 0.56518315$
 Effective FRP thickness, $t_f = NL * t * \text{Cos}(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975148$
 $A = 0.01865339$
 $B = 0.01050082$
 with $E_s = 200000.00$

 Calculation of ratio l_b / l_d

Inadequate Lap Length with $l_b / l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b / l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.18171192$

$d = d_{external} = 357.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00680079$

jacket: $s_1 = A_{v1} * h_1 / (s_1 * A_g) = 0.00392699$

$A_{v1} = 157.0796$, is the total area of all stirrups parallel to loading (shear) direction

$h_1 = 400.00$

$s_1 = 100.00$

core: $s_2 = A_{v2} * h_2 / (s_2 * A_g) = 0.00050265$

$A_{v2} = 100.531$, is the total area of all stirrups parallel to loading (shear) direction

$h_2 = 200.00$

$s_2 = 250.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5974.983$

$A_g = 160000.00$

$f_c E = (f_{c,jacket} * \text{Area}_{jacket} + f_{c,core} * \text{Area}_{core}) / \text{section_area} = 29.75$

$f_y E = (f_{y,ext_Long_Reinf} * \text{Area}_{ext_Long_Reinf} + f_{y,int_Long_Reinf} * \text{Area}_{int_Long_Reinf}) / \text{Area}_{Tot_Long_Rein} = 529.9948$

$f_y E = (f_{y,ext_Trans_Reinf} * \text{Area}_{ext_Trans_Reinf} + f_{y,int_Trans_Reinf} * \text{Area}_{int_Trans_Reinf}) / \text{Area}_{Tot_Trans_Rein} =$

542.9472

$pl = \text{Area_Tot_Long_Rein}/(b*d) = 0.01874396$

$b = 400.00$

$d = 357.00$

$f_{cE} = 29.75$

End Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 5

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of γ for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, $f_c = f_{cm} = 33.00$
New material: Steel Strength, $f_s = f_{sm} = 555.5556$
Existing Column
Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material: Steel Strength, $f_s = f_{sm} = 444.4444$

External Height, $H = 400.00$
External Width, $W = 400.00$
Internal Height, $H = 200.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $b_i: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -1.3686E+007$
Shear Force, $V_a = -4560.604$
EDGE -B-
Bending Moment, $M_b = 0.04224678$
Shear Force, $V_b = 4560.604$
BOTH EDGES
Axial Force, $F = -5974.983$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 2676.637$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 1137.257$
-Compression: $As_{l,com} = 1137.257$
-Middle: $As_{l,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.80$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $VR = *V_n = 475023.475$
 $V_n ((10.3), ASCE 41-17) = knl * V_{ColO} = 558851.147$
 $V_{Col} = 558851.147$
 $knl = 1.00$

displacement_ductility_demand = 0.16955779

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 22.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.04224678$

$V_u = 4560.604$

$d = 0.8 \cdot h = 320.00$

$N_u = 5974.983$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 251327.412$

where:

$V_{s1} = 251327.412$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot_a) \sin a$ which is more a generalised expression, where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 405571.497$

$b_w = 400.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END B -

for rotation axis 3 and integ. section (b)

From analysis, chord rotation $\theta = 0.00012046$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00071043$ ((4.29), Biskinis Phd)

$M_y = 1.2106 \text{E} + 008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 300.00

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 1.7040 \text{E} + 013$

factor = 0.30

$A_g = 160000.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$

$N = 5974.983$

$E_c \cdot I_g = E_c \cdot I_{g_{\text{jacket}}} + E_c \cdot I_{g_{\text{core}}} = 5.6801 \text{E} + 013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 5.7839617\text{E-}006$$

$$\text{with } ((10.1), \text{ASCE 41-17}) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$$

$$d = 357.00$$

$$y = 0.28109392$$

$$A = 0.01888489$$

$$B = 0.01064175$$

$$\text{with } p_t = 0.00796398$$

$$p_c = 0.00796398$$

$$p_v = 0.00281599$$

$$N = 5974.983$$

$$b = 400.00$$

$$" = 0.12044818$$

$$y_{\text{comp}} = 2.3130538\text{E-}005$$

$$\text{with } f_c^* (12.3, (\text{ACI 440})) = 34.65043$$

$$f_c = 33.00$$

$$f_l = 0.93147527$$

$$b = 400.00$$

$$h = 400.00$$

$$A_g = 160000.00$$

$$\text{From } (12.9), \text{ACI 440: } k_a = 0.56518315$$

$$g = p_t + p_c + p_v = 0.01874396$$

$$r_c = 40.00$$

$$A_e/A_c = 0.56518315$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cdot \text{Cos}(\theta_1) = 1.016$$

$$\text{effective strain from } (12.5) \text{ and } (12.12), e_{fe} = 0.004$$

$$f_u = 0.01$$

$$E_f = 64828.00$$

$$E_c = 26999.444$$

$$y = 0.27975148$$

$$A = 0.01865339$$

$$B = 0.01050082$$

$$\text{with } E_s = 200000.00$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 6

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.8468314E-031$

EDGE -B-

Shear Force, $V_b = 1.8468314E-031$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1137.257$

-Compression: $As_{c,com} = 1137.257$

-Middle: $As_{mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.18171192$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 115036.425$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.7255E+008$

$Mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.7255E+008$

$Mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$\alpha (\text{5A.5, TBDY}) = 0.002$

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase^* sh_{\min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

$ase1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi2_1 = 462400.00$

$ase2 = \text{Max}(ase1, ase2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi2_2 = 147456.00$

$psh_{\min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

 $psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$

$ps1$ (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

$Ash1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h1 = 400.00$

$ps2$ (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

$Ash2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h2 = 200.00$

 $psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$

$ps1$ (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

$Ash1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h1 = 400.00$

$ps2$ (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

$Ash2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h2 = 200.00$

 $A_{sec} = 160000.00$

$s1 = 100.00$

$s2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

$c =$ confinement factor = 1.13212

$y1 = 0.00140044$

$sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.538$
 $fy2 = 367.9484$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$

$$\begin{aligned} \text{Mu} &= \text{MRc} (4.14) = 1.7255\text{E}+008 \\ u &= \text{su} (4.1) = 1.7890363\text{E}-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 1.7890363\text{E}-005 \\ \text{Mu} &= 1.7255\text{E}+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 400.00 \\ d &= 357.00 \\ d' &= 43.00 \\ v &= 0.00126831 \\ N &= 5976.808 \\ f_c &= 33.00 \\ c_o (5A.5, \text{TBDY}) &= 0.002 \\ \text{Final value of } \phi_u: \phi_u^* &= \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01608084 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \phi_u &= 0.01608084 \\ \phi_{we} ((5.4c), \text{TBDY}) &= a_{se} * \text{sh}_{,min} * f_{ywe} / f_{ce} + \text{Min}(\phi_x, \phi_y) = 0.09892348 \\ \text{where } \phi &= a_f * p_f * f_{fe} / f_{ce} \text{ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)} \end{aligned}$$

$$\begin{aligned} \phi_x &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} \phi_y &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} R &= 40.00 \\ \text{Effective FRP thickness, } t_f &= N L * t * \text{Cos}(b_1) = 1.016 \\ f_{u,f} &= 1055.00 \\ E_f &= 64828.00 \\ u_{,f} &= 0.015 \\ a_{se} ((5.4d), \text{TBDY}) &= (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288 \\ a_{se1} &= 0.24250288 \\ b_{o,1} &= 340.00 \\ h_{o,1} &= 340.00 \\ b_{i,2,1} &= 462400.00 \\ a_{se2} &= \text{Max}(a_{se1}, a_{se2}) = 0.24250288 \\ b_{o,2} &= 192.00 \\ h_{o,2} &= 192.00 \\ b_{i,2,2} &= 147456.00 \\ p_{sh,min} * F_{ywe} &= \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633 \end{aligned}$$

$$\begin{aligned} p_{sh,x} * F_{ywe} &= p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.00633 \\ p_{s1} (\text{external}) &= (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699 \\ A_{sh1} &= A_{stir,1} * n_{s,1} = 157.0796 \end{aligned}$$

No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.00633
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00392699
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 160000.00
s₁ = 100.00
s₂ = 250.00
fywe₁ = 694.4444
fywe₂ = 555.5556
fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.538
fy₁ = 367.9484
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*Asl_{ten,jacket} + fs_{core}*Asl_{ten,core})/Asl_{ten} = 367.9484

with Es₁ = (Es_{jacket}*Asl_{ten,jacket} + Es_{core}*Asl_{ten,core})/Asl_{ten} = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814
ft₂ = 441.538
fy₂ = 367.9484
su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 0.30

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*Asl_{com,jacket} + fs_{core}*Asl_{com,core})/Asl_{com} = 367.9484

with Es₂ = (Es_{jacket}*Asl_{com,jacket} + Es_{core}*Asl_{com,core})/Asl_{com} = 200000.00

y_v = 0.00140044
sh_v = 0.0044814
ft_v = 466.813
fy_v = 389.0108
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$

with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.088798$

$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.088798$

$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

$c =$ confinement factor = 1.13212

$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.11405247$

$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.11405247$

$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < vs_{y2}$ - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

$Mu = MRc$ (4.14) = 1.7255E+008

$u = su$ (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

where ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + Min(fx, fy) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$fy = 0.07683125$

af = 0.57333333
b = 400.00
h = 400.00
From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508
bw = 400.00
effective stress from (A.35), ff,e = 870.5244

R = 40.00
Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288
ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00
From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

$y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $fy_2 = 367.9484$
 $su_2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/lb_{min} = 0.30$
 $su_2 = 0.4 * esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs_2 = (fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 367.9484$
 with $Es_2 = (Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 0.30$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$
 with $Es_v = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.088798$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.088798$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl_{ten} / (b * d) * (fs_1 / fc) = 0.11405247$
 $2 = Asl_{com} / (b * d) * (fs_2 / fc) = 0.11405247$
 $v = Asl_{mid} / (b * d) * (fsv / fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

---->
 $v < v_s, y_2$ - LHS eq.(4.5) is satisfied
 ---->
 $su (4.9) = 0.19835408$
 $Mu = MRc (4.14) = 1.7255E+008$
 $u = su (4.1) = 1.7890363E-005$

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of Mu_2 -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005
Mu = 1.7255E+008

with full section properties:

b = 400.00
d = 357.00
d' = 43.00
v = 0.00126831
N = 5976.808
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01608084

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01608084

we ((5.4c), TBDY) = ase* sh,min*fywe/fce+Min(fx, fy) = 0.09892348

where f = af*pf*ffe/fce is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508

bw = 400.00
effective stress from (A.35), ffe = 870.5244

fy = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508

bw = 400.00
effective stress from (A.35), ffe = 870.5244

R = 40.00

Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016

fu,f = 1055.00

Ef = 64828.00

u,f = 0.015

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288

ase1 = 0.24250288

bo_1 = 340.00

ho_1 = 340.00

bi2_1 = 462400.00

ase2 = Max(ase1,ase2) = 0.24250288

bo_2 = 192.00

ho_2 = 192.00

bi2_2 = 147456.00

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 400.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 400.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

$$h_2 = 200.00$$

$$A_{sec} = 160000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 694.4444$$

$$f_{ywe2} = 555.5556$$

$$f_{ce} = 33.00$$

$$\text{From } ((5.A.5), \text{ TBDY}), \text{ TBDY: } c_c = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 441.538$$

$$fy_1 = 367.9484$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_1_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_1_{nominal} = 0.08$,

For calculation of $esu_1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.9484$$

$$\text{with } Es_1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.538$$

$$fy_2 = 367.9484$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu_2_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_2_{nominal} = 0.08$,

For calculation of $esu_2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 367.9484$$

$$\text{with } Es_2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.813$$

$$fy_v = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$suv = 0.4 * esuv_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (f_{s,jacket} * A_{sl,mid,jacket} + f_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 389.0108$$

$$\text{with } Es_v = (E_{s,jacket} * A_{sl,mid,jacket} + E_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.088798$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.088798$$

$$v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{ TBDY}) = 37.35991$$

cc (5A.5, TBDY) = 0.00332119
c = confinement factor = 1.13212
1 = $Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
2 = $Asl,com/(b*d)*(fs2/fc) = 0.11405247$
v = $Asl,mid/(b*d)*(fsv/fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->
v < vs,y2 - LHS eq.(4.5) is satisfied

---->
su (4.9) = 0.19835408
Mu = MRc (4.14) = 1.7255E+008
u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/l_d

Inadequate Lap Length with lb/l_d = 0.30

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 633070.334

Calculation of Shear Strength at edge 1, Vr1 = 633070.334

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $fc' = (fc'_{jacket}*Area_{jacket} + fc'_{core}*Area_{core})/Area_{section} = 29.75$, but $fc'^{0.5} <= 8.3$
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00

Mu = 8.4878329E-012

Vu = 1.8468314E-031

d = 0.8*h = 320.00

Nu = 5976.808

Ag = 160000.00

From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a)\sin a$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(α), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:

total thickness per orientation, tf1 = NL*t/NoDir = 1.016

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00
 f_{fe} ((11-5), ACI 440) = 259.312
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
with $f_u = 0.01$
From (11-11), ACI 440: $V_s + V_f \leq 463788.751$
 $b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$
 $V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l * V_{Col0}$
 $V_{Col0} = 633070.334$
 $k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 29.75$, but $f_c'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$M / V d = 2.00$
 $\mu_u = 8.4878329E-012$
 $V_u = 1.8468314E-031$
 $d = 0.8 * h = 320.00$
 $N_u = 5976.808$
 $A_g = 160000.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$
where:

$V_{s1} = 279252.68$ is calculated for jacket, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.5556$
 $s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:
 $d = 160.00$
 $A_v = 100530.965$
 $f_y = 444.4444$
 $s = 250.00$

V_{s2} is multiplied by $Col2 = 0.00$
 $s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148
 $f = 0.95$, for fully-wrapped sections
 $w_f / s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 135^\circ$

$V_f = \text{Min}(|V_f(45, 1)|, |V_f(-45, a1)|)$, with:
total thickness per orientation, $t_{f1} = N_L * t / N_{oDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00
 f_{fe} ((11-5), ACI 440) = 259.312
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
with $f_u = 0.01$
From (11-11), ACI 440: $V_s + V_f \leq 463788.751$
 $b_w = 400.00$

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket
New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.4444$
Existing Column
Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.5556$
#####

External Height, $H = 400.00$
External Width, $W = 400.00$
Internal Height, $H = 200.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.13212
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $b_i = 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 3.2548216E-032$
EDGE -B-
Shear Force, $V_b = -3.2548216E-032$
BOTH EDGES
Axial Force, $F = -5976.808$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 2676.637$
Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 1137.257$
-Compression: $Asl,com = 1137.257$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 0.18171192$

Member Controlled by Flexure ($Ve/Vr < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 115036.425$

with

$Mpr1 = \text{Max}(Mu1+, Mu1-) = 1.7255E+008$

$Mu1+ = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu1- = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$Mpr2 = \text{Max}(Mu2+, Mu2-) = 1.7255E+008$

$Mu2+ = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu2- = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$\phi_{co} (5A.5, TBDY) = 0.002$

Final value of ϕ_{cu} : $\phi_{cu}^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_{cu} = 0.01608084$

$\phi_{we} ((5.4c), TBDY) = \phi_{cu} * \text{sh}_{,min} * f_{ywe}/f_{ce} + \text{Min}(\phi_{fx}, \phi_{fy}) = 0.09892348$

where $\phi_f = \phi_{af} * \phi_{pf} * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $\phi_{fx} = 0.07683125$

$\phi_{af} = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $\phi_{pf} = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

 $\phi_{fy} = 0.07683125$

$\phi_{af} = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $\phi_{pf} = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $t_f = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$\phi_{ase} ((5.4d), TBDY) = (\phi_{ase1} * A_{ext} + \phi_{ase2} * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (f_s \cdot \text{jacket} \cdot A_{s, \text{com, jacket}} + f_s \cdot \text{core} \cdot A_{s, \text{com, core}}) / A_{s, \text{com}} = 367.9484$

with $Es_2 = (E_s \cdot \text{jacket} \cdot A_{s, \text{com, jacket}} + E_s \cdot \text{core} \cdot A_{s, \text{com, core}}) / A_{s, \text{com}} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.813$

$fy_v = 389.0108$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o, \text{min}} = l_b/l_d = 0.30$

$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fs_yv = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fs_yv = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_s \cdot \text{jacket} \cdot A_{s, \text{mid, jacket}} + f_s \cdot \text{mid} \cdot A_{s, \text{mid, core}}) / A_{s, \text{mid}} = 389.0108$

with $E_{sv} = (E_s \cdot \text{jacket} \cdot A_{s, \text{mid, jacket}} + E_s \cdot \text{mid} \cdot A_{s, \text{mid, core}}) / A_{s, \text{mid}} = 200000.00$

$1 = A_{s, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$2 = A_{s, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$v = A_{s, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, \text{TBDY}) = 37.35991$

$cc (5A.5, \text{TBDY}) = 0.00332119$

$c = \text{confinement factor} = 1.13212$

$1 = A_{s, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$2 = A_{s, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$v = A_{s, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s, y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.19835408$

$Mu = MRc (4.14) = 1.7255E+008$

$u = su (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$cc (5A.5, \text{TBDY}) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_{2,1} = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_{2,2} = 147456.00$

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.00633$

$psh_x * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$psh_y * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

c = confinement factor = 1.13212

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.538$

$f_{y1} = 367.9484$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,
 For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{s1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 367.9484$
 with $E_{s1} = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $f_{y2} = 367.9484$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,
 For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 367.9484$
 with $E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $f_{y_v} = 389.0108$
 $s_{u_v} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u_v} = 0.4 * e_{s_{u_v}}_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u_v}}_nominal = 0.08$,
 considering characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY
 For calculation of $e_{s_{u_v}}_nominal$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_{u_v}} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 389.0108$
 with $E_{s_{u_v}} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.088798$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.088798$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.11405247$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.11405247$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.19835408$
 $M_u = M_{Rc} (4.14) = 1.7255E+008$
 $u = s_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7890363E-005$$

$$\mu = 1.7255E+008$$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01608084$$

$$\mu_e \text{ ((5.4c), TBDY)} = a_{se} * \text{sh}_{,min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$f_y = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$a_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,1} = 462400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2} = 147456.00$$

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$ps_2 \text{ (internal)} = (Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$$

$$Ash_2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h_2 = 200.00$$

$$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$$

$$ps_1 \text{ (external)} = (Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$$

$$Ash_1 = Astir_1 * ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h_1 = 400.00$$

$$ps_2 \text{ (internal)} = (Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$$

$$Ash_2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 160000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$fy_{we1} = 694.4444$$

$$fy_{we2} = 555.5556$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 441.538$$

$$fy_1 = 367.9484$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 0.30$$

$$su_1 = 0.4 * esu_1 \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_1 \text{ nominal} = 0.08,$$

For calculation of $esu_1 \text{ nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1 / 1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 367.9484$$

$$\text{with } Es_1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.538$$

$$fy_2 = 367.9484$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 0.30$$

$$su_2 = 0.4 * esu_2 \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_2 \text{ nominal} = 0.08,$$

For calculation of $esu_2 \text{ nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2 / 1.2$, from table 5.1, TBDY.

$$y_2, sh_2, ft_2, fy_2, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 367.9484$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.813$$

$$fy_v = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 0.30$$

$$suv = 0.4 * esuv \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esuv \text{ nominal} = 0.08,$$

considering characteristic value $fsyv = fsv / 1.2$, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and y_v , sh_v , ft_v , fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 37.35991$

$cc (5A.5, TBDY) = 0.00332119$

$c = \text{confinement factor} = 1.13212$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.19835408$

$Mu = MRc (4.14) = 1.7255E+008$

$u = su (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_2 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$co (5A.5, TBDY) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

we ((5.4c), TBDY) = $ase \cdot sh_{,min} \cdot fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.09892348$

where $f = af \cdot pf \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$fy = 0.07683125$

$af = 0.57333333$

$b = 400.00$

h = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.00508$
bw = 400.00
effective stress from (A.35), $ff,e = 870.5244$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $ase((5.4d), \text{TBDY}) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.24250288$
 $ase1 = 0.24250288$
 $bo_1 = 340.00$
 $ho_1 = 340.00$
 $bi2_1 = 462400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.24250288$
 $bo_2 = 192.00$
 $ho_2 = 192.00$
 $bi2_2 = 147456.00$
 $psh_{,min}*F_{ywe} = \text{Min}(psh_{,x}*F_{ywe}, psh_{,y}*F_{ywe}) = 3.00633$

$psh_{,x}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$psh_{,y}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 160000.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 694.4444$
 $f_{ywe2} = 555.5556$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou_{,min} = lb/ld = 0.30$
 $su1 = 0.4*esu1_{,nominal}((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu1_{,nominal} = 0.08$,

For calculation of $esu1_{,nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{,jacket}*A_{sl,ten,jacket} + fs_{,core}*A_{sl,ten,core})/A_{sl,ten} = 367.9484$

with $Es1 = (Es_{,jacket}*A_{sl,ten,jacket} + Es_{,core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_jacket * Asl,com,jacket + fs_core * Asl,com,core) / Asl,com = 367.9484$$

$$\text{with } Es2 = (Es_jacket * Asl,com,jacket + Es_core * Asl,com,core) / Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_jacket * Asl,mid,jacket + fs_mid * Asl,mid,core) / Asl,mid = 389.0108$$

$$\text{with } Esv = (Es_jacket * Asl,mid,jacket + Es_mid * Asl,mid,core) / Asl,mid = 200000.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.088798$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.088798$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 37.35991$$

$$cc (5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.11405247$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.11405247$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.19835408$$

$$Mu = MRc (4.14) = 1.7255E+008$$

$$u = su (4.1) = 1.7890363E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 633070.334$

Calculation of Shear Strength at edge 1, $Vr1 = 633070.334$

$$Vr1 = VCol ((10.3), ASCE 41-17) = knl * VColO$$

$$VColO = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$\nu_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.5556$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 444.4444$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \text{cota})\sin\alpha$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / N_{\text{Dir}} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 463788.751$

$b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col0}}$

$V_{\text{Col0}} = 633070.334$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$\nu_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta_1 = b_1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ_1)|, |Vf(-45, α_1)|), with:

total thickness per orientation, $tf_1 = NL * t / NoDir = 1.016$

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 463788.751

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

External Height, H = 400.00

External Width, W = 400.00

Internal Height, H = 200.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $bi = 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

 Stepwise Properties

Bending Moment, $M = -1.1352078E-010$
 Shear Force, $V_2 = 4560.604$
 Shear Force, $V_3 = -9.4294951E-014$
 Axial Force, $F = -5974.983$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $As_{lt} = 0.00$
 -Compression: $As_{lc} = 2676.637$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten} = 1137.257$
 -Compression: $As_{l,com} = 1137.257$
 -Middle: $As_{l,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,jacket} = 829.3805$
 -Compression: $As_{l,com,jacket} = 829.3805$
 -Middle: $As_{l,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,core} = 307.8761$
 -Compression: $As_{l,com,core} = 307.8761$
 -Middle: $As_{l,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 16.80$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.00301933$
 $u = y + p = 0.00355215$

 - Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00355215$ ((4.29), Biskinis Phd))
 $M_y = 1.2106E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1500.00
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7040E+013$
 $factor = 0.30$
 $A_g = 160000.00$
 Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 29.75$
 $N = 5974.983$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 5.6801E+013$

 Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.7839617E-006$
 with $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109392$
 $A = 0.01888489$
 $B = 0.01064175$
 with $pt = 0.00680079$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.983$
 $b = 400.00$
 $" = 0.12044818$

$y_{comp} = 2.3130538E-005$
 with $f_c^* (12.3, (ACI 440)) = 34.65043$
 $f_c = 33.00$
 $f_l = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $A_g = 160000.00$
 From (12.9), ACI 440: $k_a = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $A_e/A_c = 0.56518315$
 Effective FRP thickness, $t_f = NL \cdot t \cdot \text{Cos}(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975148$
 $A = 0.01865339$
 $B = 0.01050082$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.18171192$

$d = d_{external} = 357.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00680079$

jacket: $s_1 = A_{v1} \cdot h_1 / (s_1 \cdot A_g) = 0.00392699$

$A_{v1} = 157.0796$, is the total area of all stirrups parallel to loading (shear) direction

$h_1 = 400.00$

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot h_2 / (s_2 \cdot A_g) = 0.00050265$

$A_{v2} = 100.531$, is the total area of all stirrups parallel to loading (shear) direction

$h_2 = 200.00$

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$NUD = 5974.983$

$A_g = 160000.00$

$f_c E = (f_{c,jacket} \cdot \text{Area}_{jacket} + f_{c,core} \cdot \text{Area}_{core}) / \text{section_area} = 29.75$

$f_y E = (f_{y,ext_Long_Reinf} \cdot \text{Area}_{ext_Long_Reinf} + f_{y,int_Long_Reinf} \cdot \text{Area}_{int_Long_Reinf}) / \text{Area}_{Tot_Long_Rein} = 529.9948$

$f_y E = (f_{y,ext_Trans_Reinf} \cdot \text{Area}_{ext_Trans_Reinf} + f_{y,int_Trans_Reinf} \cdot \text{Area}_{int_Trans_Reinf}) / \text{Area}_{Tot_Trans_Rein} =$

542.9472

$pl = \text{Area_Tot_Long_Rein}/(b*d) = 0.01874396$

$b = 400.00$

$d = 357.00$

$f_{cE} = 29.75$

End Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 7

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

```

Existing Column
Existing material of Primary Member: Concrete Strength, fc = fc_lower_bound = 16.00
Existing material of Primary Member: Steel Strength, fs = fs_lower_bound = 400.00
Concrete Elasticity, Ec = 21019.039
Steel Elasticity, Es = 200000.00
#####
Note: Especially for the calculation of  $\gamma$  for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, fc = fcm = 33.00
New material: Steel Strength, fs = fsm = 555.5556
Existing Column
Existing material: Concrete Strength, fc = fcm = 20.00
Existing material: Steel Strength, fs = fsm = 444.4444
#####
External Height, H = 400.00
External Width, W = 400.00
Internal Height, H = 200.00
Internal Width, W = 200.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with  $l_o/l_{ou,min} = l_b/l_d = 0.30$ 
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, t = 1.016
Tensile Strength,  $f_{fu} = 1055.00$ 
Tensile Modulus,  $E_f = 64828.00$ 
Elongation,  $e_{fu} = 0.01$ 
Number of directions, NoDir = 1
Fiber orientations,  $b_i = 0.00^\circ$ 
Number of layers, NL = 1
Radius of rounding corners, R = 40.00
-----

Stepwise Properties
-----
EDGE -A-
Bending Moment,  $M_a = -1.6937287E-010$ 
Shear Force,  $V_a = 9.4294951E-014$ 
EDGE -B-
Bending Moment,  $M_b = -1.1352078E-010$ 
Shear Force,  $V_b = -9.4294951E-014$ 
BOTH EDGES
Axial Force, F = -5974.983
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension:  $A_{sl,t} = 0.00$ 
-Compression:  $A_{sl,c} = 2676.637$ 
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension:  $A_{sl,ten} = 1137.257$ 
-Compression:  $A_{sl,com} = 1137.257$ 
-Middle:  $A_{sl,mid} = 402.1239$ 
Mean Diameter of Tension Reinforcement,  $D_{bL,ten} = 16.80$ 
-----
-----

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity  $V_R = *V_n = 475023.475$ 
 $V_n ((10.3), ASCE 41-17) = knl*V_{CoIO} = 558851.147$ 
 $V_{CoI} = 558851.147$ 
 $knl = 1.00$ 

```

displacement_ductility_demand = 0.00

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 22.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.1352078E-010$

$\nu_u = 9.4294951E-014$

$d = 0.8 \cdot h = 320.00$

$N_u = 5974.983$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 251327.412$

where:

$V_{s1} = 251327.412$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot_a) \sin a$ which is more a generalised expression, where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a_i)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 405571.497$

$b_w = 400.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END B -

for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 1.0792184E-022$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00355215$ ((4.29), Biskinis Phd)

$M_y = 1.2106E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 1.7040E+013$

factor = 0.30

$A_g = 160000.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$

$N = 5974.983$

$E_c \cdot I_g = E_c \cdot I_{g_{\text{jacket}}} + E_c \cdot I_{g_{\text{core}}} = 5.6801E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 5.7839617\text{E-}006$$

$$\text{with } ((10.1), \text{ASCE 41-17}) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$$

$$d = 357.00$$

$$y = 0.28109392$$

$$A = 0.01888489$$

$$B = 0.01064175$$

$$\text{with } p_t = 0.00796398$$

$$p_c = 0.00796398$$

$$p_v = 0.00281599$$

$$N = 5974.983$$

$$b = 400.00$$

$$" = 0.12044818$$

$$y_{\text{comp}} = 2.3130538\text{E-}005$$

$$\text{with } f_c^* (12.3, (\text{ACI 440})) = 34.65043$$

$$f_c = 33.00$$

$$f_l = 0.93147527$$

$$b = 400.00$$

$$h = 400.00$$

$$A_g = 160000.00$$

$$\text{From } (12.9), \text{ACI 440: } k_a = 0.56518315$$

$$g = p_t + p_c + p_v = 0.01874396$$

$$r_c = 40.00$$

$$A_e/A_c = 0.56518315$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cdot \text{Cos}(\theta_1) = 1.016$$

$$\text{effective strain from } (12.5) \text{ and } (12.12), e_{fe} = 0.004$$

$$f_u = 0.01$$

$$E_f = 64828.00$$

$$E_c = 26999.444$$

$$y = 0.27975148$$

$$A = 0.01865339$$

$$B = 0.01050082$$

$$\text{with } E_s = 200000.00$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 8

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $bi: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.8468314E-031$

EDGE -B-

Shear Force, $V_b = 1.8468314E-031$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1137.257$

-Compression: $As_{c,com} = 1137.257$

-Middle: $As_{mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.18171192$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 115036.425$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.7255E+008$

$Mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.7255E+008$

$Mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$\alpha (\text{5A.5, TBDY}) = 0.002$

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase^* sh_{min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

$ase1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi2_1 = 462400.00$

$ase2 = \text{Max}(ase1, ase2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi2_2 = 147456.00$

$psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

 $psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$

$ps1$ (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

$Ash1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h1 = 400.00$

$ps2$ (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

$Ash2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h2 = 200.00$

 $psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$

$ps1$ (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

$Ash1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h1 = 400.00$

$ps2$ (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

$Ash2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h2 = 200.00$

 $A_{sec} = 160000.00$

$s1 = 100.00$

$s2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

$c =$ confinement factor = 1.13212

$y1 = 0.00140044$

$sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.538$
 $fy2 = 367.9484$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$

$$\begin{aligned} \text{Mu} &= \text{MRc} (4.14) = 1.7255\text{E}+008 \\ u &= \text{su} (4.1) = 1.7890363\text{E}-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature κ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 1.7890363\text{E}-005 \\ \text{Mu} &= 1.7255\text{E}+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 400.00 \\ d &= 357.00 \\ d' &= 43.00 \\ v &= 0.00126831 \\ N &= 5976.808 \\ f_c &= 33.00 \\ c_o (5A.5, \text{TBDY}) &= 0.002 \\ \text{Final value of } \kappa_u &: \kappa_u^* = \text{shear_factor} * \text{Max}(\kappa_u, \kappa_c) = 0.01608084 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \kappa_u &= 0.01608084 \\ \kappa_{ue} ((5.4c), \text{TBDY}) &= a_{se} * \text{sh}_{, \text{min}} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348 \\ \text{where } f &= a_f * p_f * f_{fe} / f_{ce} \text{ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)} \end{aligned}$$

$$\begin{aligned} f_x &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} f_y &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} R &= 40.00 \\ \text{Effective FRP thickness, } t_f &= NL * t * \text{Cos}(b_1) = 1.016 \\ f_{u,f} &= 1055.00 \\ E_f &= 64828.00 \\ u_{,f} &= 0.015 \\ a_{se} ((5.4d), \text{TBDY}) &= (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288 \\ a_{se1} &= 0.24250288 \\ b_{o,1} &= 340.00 \\ h_{o,1} &= 340.00 \\ b_{i,1} &= 462400.00 \\ a_{se2} &= \text{Max}(a_{se1}, a_{se2}) = 0.24250288 \\ b_{o,2} &= 192.00 \\ h_{o,2} &= 192.00 \\ b_{i,2} &= 147456.00 \\ p_{sh, \text{min}} * F_{ywe} &= \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633 \end{aligned}$$

$$\begin{aligned} p_{sh,x} * F_{ywe} &= p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633 \\ p_{s1} (\text{external}) &= (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699 \\ A_{sh1} &= A_{stir,1} * n_{s,1} = 157.0796 \end{aligned}$$

No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.00633
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00392699
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 160000.00
s₁ = 100.00
s₂ = 250.00
fywe₁ = 694.4444
fywe₂ = 555.5556
fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.538
fy₁ = 367.9484
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*Asl_{ten,jacket} + fs_{core}*Asl_{ten,core})/Asl_{ten} = 367.9484

with Es₁ = (Es_{jacket}*Asl_{ten,jacket} + Es_{core}*Asl_{ten,core})/Asl_{ten} = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814
ft₂ = 441.538
fy₂ = 367.9484
su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 0.30

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*Asl_{com,jacket} + fs_{core}*Asl_{com,core})/Asl_{com} = 367.9484

with Es₂ = (Es_{jacket}*Asl_{com,jacket} + Es_{core}*Asl_{com,core})/Asl_{com} = 200000.00

y_v = 0.00140044
sh_v = 0.0044814
ft_v = 466.813
fy_v = 389.0108
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$

with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$

1 = $Asl_{ten} / (b * d) * (fs1 / fc) = 0.088798$

2 = $Asl_{com} / (b * d) * (fs2 / fc) = 0.088798$

v = $Asl_{mid} / (b * d) * (fsv / fc) = 0.03319551$

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = $Asl_{ten} / (b * d) * (fs1 / fc) = 0.11405247$

2 = $Asl_{com} / (b * d) * (fs2 / fc) = 0.11405247$

v = $Asl_{mid} / (b * d) * (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->

v < vs_{y2} - LHS eq.(4.5) is satisfied

---->

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2+

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005

Mu = 1.7255E+008

with full section properties:

b = 400.00

d = 357.00

d' = 43.00

v = 0.00126831

N = 5976.808

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = shear_factor * Max(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

we ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + Min(fx, fy) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.07683125$

$af = 0.57333333$

b = 400.00

h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $f_{fe} = 870.5244$

 $fy = 0.07683125$

af = 0.57333333
b = 400.00
h = 400.00
From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508
bw = 400.00
effective stress from (A.35), ff,e = 870.5244

R = 40.00
Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288
ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00
From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247

2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247

v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005
Mu = 1.7255E+008

with full section properties:

b = 400.00
d = 357.00
d' = 43.00
v = 0.00126831
N = 5976.808
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01608084

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01608084

we ((5.4c), TBDY) = ase* sh,min*fywe/fce+Min(fx, fy) = 0.09892348

where f = af*pf*ffe/fce is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508

bw = 400.00

effective stress from (A.35), ffe = 870.5244

fy = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508

bw = 400.00

effective stress from (A.35), ffe = 870.5244

R = 40.00

Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016

fu,f = 1055.00

Ef = 64828.00

u,f = 0.015

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288

ase1 = 0.24250288

bo_1 = 340.00

ho_1 = 340.00

bi2_1 = 462400.00

ase2 = Max(ase1,ase2) = 0.24250288

bo_2 = 192.00

ho_2 = 192.00

bi2_2 = 147456.00

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 400.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 400.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 200.00

Asec = 160000.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.4444

fywe2 = 555.5556

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119

c = confinement factor = 1.13212

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.538

fy1 = 367.9484

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.538

fy2 = 367.9484

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

$$cc(5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.11405247$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11405247$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$su(4.9) = 0.19835408$$

$$Mu = MRc(4.14) = 1.7255E+008$$

$$u = su(4.1) = 1.7890363E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 633070.334$

Calculation of Shear Strength at edge 1, $V_{r1} = 633070.334$

$$V_{r1} = V_{CoI}((10.3), ASCE 41-17) = knl * V_{CoIO}$$

$$V_{CoIO} = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 29.75$, but $f_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$Mu = 8.4878329E-012$$

$$Vu = 1.8468314E-031$$

$$d = 0.8 * h = 320.00$$

$$Nu = 5976.808$$

$$Ag = 160000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 279252.68$$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.5556$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 0.00$ is calculated for core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 444.4444$$

$$s = 250.00$$

V_{s2} is multiplied by $Col2 = 0.00$

$$s/d = 1.5625$$

$$V_f((11-3)-(11.4), ACI 440) = 188111.148$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 90.00$

$$V_f = \text{Min}(|V_f(45, 1)|, |V_f(-45, a1)|), \text{ with:}$$

$$\text{total thickness per orientation, } t_{f1} = NL * t / \text{NoDir} = 1.016$$

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 633070.334
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 29.75, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00
Mu = 8.4878329E-012
Vu = 1.8468314E-031
d = 0.8*h = 320.00
Nu = 5976.808
Ag = 160000.00
From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68
where:

Vs1 = 279252.68 is calculated for jacket, with:
d = 320.00
Av = 157079.633
fy = 555.5556
s = 100.00

Vs1 is multiplied by Col1 = 1.00
s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:
d = 160.00
Av = 100530.965
fy = 444.4444
s = 250.00

Vs2 is multiplied by Col2 = 0.00
s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148
f = 0.95, for fully-wrapped sections
wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) sin + cos is replaced with (cot + cota)sin which is more a generalised expression,
where is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(,), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, = 45° and = -45° to take into consideration the cyclic seismic loading.

orientation 1: 1 = b1 + 90° = 90.00

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:
total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = 3.2548216E-032$

EDGE -B-

Shear Force, $V_b = -3.2548216E-032$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 1137.257$
-Compression: $Asl,com = 1137.257$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 0.18171192$

Member Controlled by Flexure ($Ve/Vr < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 115036.425$

with
 $Mpr1 = \text{Max}(Mu1+, Mu1-) = 1.7255E+008$
 $Mu1+ = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu1- = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $Mpr2 = \text{Max}(Mu2+, Mu2-) = 1.7255E+008$
 $Mu2+ = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu2- = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$
 $Mu = 1.7255E+008$

with full section properties:

$b = 400.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.00126831$
 $N = 5976.808$
 $fc = 33.00$
 $co (5A.5, TBDY) = 0.002$
Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $cu = 0.01608084$
 $w_e ((5.4c), TBDY) = ase * sh, \text{min}(fywe/fce + \text{Min}(fx, fy)) = 0.09892348$
where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.07683125$
 $af = 0.57333333$
 $b = 400.00$
 $h = 400.00$
From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$
 $bw = 400.00$
effective stress from (A.35), $ff,e = 870.5244$

 $fy = 0.07683125$
 $af = 0.57333333$
 $b = 400.00$
 $h = 400.00$
From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$
 $bw = 400.00$
effective stress from (A.35), $ff,e = 870.5244$

 $R = 40.00$
Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$
 $fu,f = 1055.00$
 $Ef = 64828.00$
 $u,f = 0.015$
 $ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.24250288$

ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (f_s \cdot \text{jacket} \cdot A_{s1, \text{com, jacket}} + f_s \cdot \text{core} \cdot A_{s1, \text{com, core}}) / A_{s1, \text{com}} = 367.9484$

with $Es_2 = (E_s \cdot \text{jacket} \cdot A_{s1, \text{com, jacket}} + E_s \cdot \text{core} \cdot A_{s1, \text{com, core}}) / A_{s1, \text{com}} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.813$

$fy_v = 389.0108$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o, \text{min}} = l_b/l_d = 0.30$

$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fsyv = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsyv = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_s \cdot \text{jacket} \cdot A_{s1, \text{mid, jacket}} + f_s \cdot \text{mid} \cdot A_{s1, \text{mid, core}}) / A_{s1, \text{mid}} = 389.0108$

with $E_{sv} = (E_s \cdot \text{jacket} \cdot A_{s1, \text{mid, jacket}} + E_s \cdot \text{mid} \cdot A_{s1, \text{mid, core}}) / A_{s1, \text{mid}} = 200000.00$

$1 = A_{s1, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$2 = A_{s1, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$v = A_{s1, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, \text{TBDY}) = 37.35991$

$cc (5A.5, \text{TBDY}) = 0.00332119$

$c = \text{confinement factor} = 1.13212$

$1 = A_{s1, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$2 = A_{s1, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$v = A_{s1, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s, y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.19835408$

$Mu = MRc (4.14) = 1.7255E+008$

$u = su (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$cc (5A.5, \text{TBDY}) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_{2,1} = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_{2,2} = 147456.00$

$psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

c = confinement factor = 1.13212

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.538$

$f_{y1} = 367.9484$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,
 For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{s1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 367.9484$
 with $E_{s1} = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $f_{y2} = 367.9484$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,
 For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 367.9484$
 with $E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $f_{y_v} = 389.0108$
 $s_{u_v} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u_v} = 0.4 * e_{s_{u_v}}_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u_v}}_nominal = 0.08$,
 considering characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY
 For calculation of $e_{s_{u_v}}_nominal$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_{u_v}} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 389.0108$
 with $E_{s_{u_v}} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.088798$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.088798$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.11405247$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.11405247$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.19835408$
 $M_u = M_{Rc} (4.14) = 1.7255E+008$
 $u = s_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7890363E-005$$

$$\mu = 1.7255E+008$$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$\alpha (5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01608084$$

$$\mu_{cc} \text{ ((5.4c), TBDY) = } \alpha_{se} * \text{sh}_{, \text{min}} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$$

where $f_x = \alpha_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.07683125$$

$$\alpha_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{fe} = 870.5244$$

$$f_y = 0.07683125$$

$$\alpha_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{fe} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$\mu_{,f} = 0.015$$

$$\alpha_{se} \text{ ((5.4d), TBDY) = } (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$\alpha_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,1} = 462400.00$$

$$\alpha_{se2} = \text{Max}(\alpha_{se1}, \alpha_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2} = 147456.00$$

$$p_{sh, \text{min}} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633$$

$$p_{s1} \text{ (external) = } (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 \cdot h2 / s2) / Asec = 0.00050265$$

$$Ash2 = Astir_2 \cdot ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$psh_y \cdot Fywe = psh1 \cdot Fywe1 + ps2 \cdot Fywe2 = 3.00633$$

$$ps1 \text{ (external)} = (Ash1 \cdot h1 / s1) / Asec = 0.00392699$$

$$Ash1 = Astir_1 \cdot ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 \cdot h2 / s2) / Asec = 0.00050265$$

$$Ash2 = Astir_2 \cdot ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$Asec = 160000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.4444$$

$$fywe2 = 555.5556$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.538$$

$$fy1 = 367.9484$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$su1 = 0.4 \cdot esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_nominal = 0.08,$$

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs_jacket \cdot Asl, \text{ten, jacket} + fs_core \cdot Asl, \text{ten, core}) / Asl, \text{ten} = 367.9484$$

$$\text{with } Es1 = (Es_jacket \cdot Asl, \text{ten, jacket} + Es_core \cdot Asl, \text{ten, core}) / Asl, \text{ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/lb, \text{min} = 0.30$$

$$su2 = 0.4 \cdot esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_nominal = 0.08,$$

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs2 = (fs_jacket \cdot Asl, \text{com, jacket} + fs_core \cdot Asl, \text{com, core}) / Asl, \text{com} = 367.9484$$

$$\text{with } Es2 = (Es_jacket \cdot Asl, \text{com, jacket} + Es_core \cdot Asl, \text{com, core}) / Asl, \text{com} = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$suv = 0.4 \cdot esuv_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esuv_nominal = 0.08,$$

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and γ_v , sh_v , ft_v , fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

$c = \text{confinement factor} = 1.13212$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.19835408

$M_u = M_{Rc}$ (4.14) = 1.7255E+008

$u = \mu_u$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

cc (5A.5, TBDY) = 0.002

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.01608084$

μ_{we} ((5.4c), TBDY) = $a_{se} \cdot sh_{,min} \cdot f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = a_{se} \cdot p_f \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$f_y = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

h = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.00508$
bw = 400.00
effective stress from (A.35), $ff,e = 870.5244$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $ase((5.4d), \text{TBDY}) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.24250288$
 $ase1 = 0.24250288$
 $bo_1 = 340.00$
 $ho_1 = 340.00$
 $bi2_1 = 462400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.24250288$
 $bo_2 = 192.00$
 $ho_2 = 192.00$
 $bi2_2 = 147456.00$
 $psh_{,min}*F_{ywe} = \text{Min}(psh_{,x}*F_{ywe}, psh_{,y}*F_{ywe}) = 3.00633$

$psh_{,x}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$psh_{,y}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 160000.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 694.4444$
 $f_{ywe2} = 555.5556$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $lo/lou_{,min} = lb/ld = 0.30$
 $su1 = 0.4*esu1_{nominal}((5.5), \text{TBDY}) = 0.032$
From table 5A.1, TBDY: $esu1_{nominal} = 0.08$
For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
with $fs1 = (fs_{jacket}*A_{sl,ten,jacket} + fs_{core}*A_{sl,ten,core})/A_{sl,ten} = 367.9484$
with $Es1 = (Es_{jacket}*A_{sl,ten,jacket} + Es_{core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_jacket * Asl,com,jacket + fs_core * Asl,com,core) / Asl,com = 367.9484$$

$$\text{with } Es2 = (Es_jacket * Asl,com,jacket + Es_core * Asl,com,core) / Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_jacket * Asl,mid,jacket + fs_mid * Asl,mid,core) / Asl,mid = 389.0108$$

$$\text{with } Esv = (Es_jacket * Asl,mid,jacket + Es_mid * Asl,mid,core) / Asl,mid = 200000.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.088798$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.088798$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 37.35991$$

$$cc (5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.11405247$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.11405247$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.19835408$$

$$Mu = MRc (4.14) = 1.7255E+008$$

$$u = su (4.1) = 1.7890363E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 633070.334$

Calculation of Shear Strength at edge 1, $Vr1 = 633070.334$

$$Vr1 = VCol ((10.3), ASCE 41-17) = knl * VColO$$

$$VColO = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$\nu_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.5556$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 444.4444$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \text{cota})\sin\alpha$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 463788.751$

$b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col0}}$

$V_{\text{Col0}} = 633070.334$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$\nu_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, α)|), with:

total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 463788.751

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

External Height, H = 400.00

External Width, W = 400.00

Internal Height, H = 200.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $b_i = 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

 Stepwise Properties

 Bending Moment, $M = 0.04224678$
 Shear Force, $V_2 = 4560.604$
 Shear Force, $V_3 = -9.4294951E-014$
 Axial Force, $F = -5974.983$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $As_{lt} = 0.00$
 -Compression: $As_{lc} = 2676.637$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten} = 1137.257$
 -Compression: $As_{l,com} = 1137.257$
 -Middle: $As_{l,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,jacket} = 829.3805$
 -Compression: $As_{l,com,jacket} = 829.3805$
 -Middle: $As_{l,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,core} = 307.8761$
 -Compression: $As_{l,com,core} = 307.8761$
 -Middle: $As_{l,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 16.80$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.00060387$
 $u = y + p = 0.00071043$

 - Calculation of y -

 $y = (M_y * L_s / 3) / E_{eff} = 0.00071043$ ((4.29), Biskinis Phd)
 $M_y = 1.2106E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 300.00
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7040E+013$
 $factor = 0.30$
 $A_g = 160000.00$
 Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 29.75$
 $N = 5974.983$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 5.6801E+013$

 Calculation of Yielding Moment M_y

 Calculation of y and M_y according to Annex 7 -

 $y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.7839617E-006$
 with $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109392$
 $A = 0.01888489$
 $B = 0.01064175$
 with $pt = 0.00680079$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.983$
 $b = 400.00$
 $" = 0.12044818$

$y_{comp} = 2.3130538E-005$
 with $f_c^* (12.3, (ACI 440)) = 34.65043$
 $f_c = 33.00$
 $f_l = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $A_g = 160000.00$
 From (12.9), ACI 440: $k_a = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $A_e/A_c = 0.56518315$
 Effective FRP thickness, $t_f = NL \cdot t \cdot \text{Cos}(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975148$
 $A = 0.01865339$
 $B = 0.01050082$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 - Calculation of p -

 From table 10-8: $p = 0.00$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{CoI} E = 0.18171192$

$d = d_{external} = 357.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00680079$

jacket: $s_1 = A_{v1} \cdot h_1 / (s_1 \cdot A_g) = 0.00392699$

$A_{v1} = 157.0796$, is the total area of all stirrups parallel to loading (shear) direction

$h_1 = 400.00$

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot h_2 / (s_2 \cdot A_g) = 0.00050265$

$A_{v2} = 100.531$, is the total area of all stirrups parallel to loading (shear) direction

$h_2 = 200.00$

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5974.983$

$A_g = 160000.00$

$f_c E = (f_{c,jacket} \cdot \text{Area}_{jacket} + f_{c,core} \cdot \text{Area}_{core}) / \text{section_area} = 29.75$

$f_y E = (f_{y,ext_Long_Reinf} \cdot \text{Area}_{ext_Long_Reinf} + f_{y,int_Long_Reinf} \cdot \text{Area}_{int_Long_Reinf}) / \text{Area}_{Tot_Long_Rein} = 529.9948$

$f_y E = (f_{y,ext_Trans_Reinf} \cdot \text{Area}_{ext_Trans_Reinf} + f_{y,int_Trans_Reinf} \cdot \text{Area}_{int_Trans_Reinf}) / \text{Area}_{Tot_Trans_Rein} =$

542.9472

$pl = \text{Area_Tot_Long_Rein}/(b*d) = 0.01874396$

$b = 400.00$

$d = 357.00$

$f_{cE} = 29.75$

End Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 9

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

```

Existing Column
Existing material of Primary Member: Concrete Strength, fc = fc_lower_bound = 16.00
Existing material of Primary Member: Steel Strength, fs = fs_lower_bound = 400.00
Concrete Elasticity, Ec = 21019.039
Steel Elasticity, Es = 200000.00
#####
Note: Especially for the calculation of  $\gamma$  for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, fc = fcm = 33.00
New material: Steel Strength, fs = fsm = 555.5556
Existing Column
Existing material: Concrete Strength, fc = fcm = 20.00
Existing material: Steel Strength, fs = fsm = 444.4444
#####
External Height, H = 400.00
External Width, W = 400.00
Internal Height, H = 200.00
Internal Width, W = 200.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with  $l_o/l_{ou,min} = l_b/l_d = 0.30$ 
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, t = 1.016
Tensile Strength,  $f_{fu} = 1055.00$ 
Tensile Modulus,  $E_f = 64828.00$ 
Elongation,  $e_{fu} = 0.01$ 
Number of directions, NoDir = 1
Fiber orientations,  $b_i = 0.00^\circ$ 
Number of layers, NL = 1
Radius of rounding corners, R = 40.00
-----

Stepwise Properties
-----
EDGE -A-
Bending Moment,  $M_a = -1.7103E+007$ 
Shear Force,  $V_a = -5699.261$ 
EDGE -B-
Bending Moment,  $M_b = 0.05279463$ 
Shear Force,  $V_b = 5699.261$ 
BOTH EDGES
Axial Force,  $F = -5974.527$ 
Longitudinal Reinforcement Area Distribution (in 2 divisions)
  -Tension:  $A_{sl,t} = 1137.257$ 
  -Compression:  $A_{sl,c} = 1539.38$ 
Longitudinal Reinforcement Area Distribution (in 3 divisions)
  -Tension:  $A_{sl,ten} = 1137.257$ 
  -Compression:  $A_{sl,com} = 1137.257$ 
  -Middle:  $A_{sl,mid} = 402.1239$ 
Mean Diameter of Tension Reinforcement,  $Db_{L,ten} = 16.80$ 
-----
-----

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity  $V_R = *V_n = 409879.585$ 
 $V_n ((10.3), ASCE 41-17) = knl * V_{ColO} = 482211.277$ 
   $V_{Col} = 482211.277$ 
   $knl = 1.00$ 

```

displacement_ductility_demand = 0.04004211

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 22.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1.7103E+007$

$V_u = 5699.261$

$d = 0.8 \cdot h = 320.00$

$N_u = 5974.527$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 251327.412$

where:

$V_{s1} = 251327.412$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot_a) \sin a$ which is more a generalised expression, where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / N_{\text{Dir}} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 405571.497$

$b_w = 400.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 0.00028456$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00710641$ ((4.29), Biskinis Phd)

$M_y = 1.2106E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 3000.891

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 1.7040E+013$

factor = 0.30

$A_g = 160000.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$

$N = 5974.527$

$E_c \cdot I_g = E_c \cdot I_{g_{\text{jacket}}} + E_c \cdot I_{g_{\text{core}}} = 5.6801E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 5.7839606\text{E-}006$$

$$\text{with } ((10.1), \text{ASCE 41-17}) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$$

$$d = 357.00$$

$$y = 0.28109378$$

$$A = 0.01888488$$

$$B = 0.01064174$$

$$\text{with } p_t = 0.00796398$$

$$p_c = 0.00796398$$

$$p_v = 0.00281599$$

$$N = 5974.527$$

$$b = 400.00$$

$$" = 0.12044818$$

$$y_{\text{comp}} = 2.3130541\text{E-}005$$

$$\text{with } f_c^* (12.3, (\text{ACI 440})) = 34.65043$$

$$f_c = 33.00$$

$$f_l = 0.93147527$$

$$b = 400.00$$

$$h = 400.00$$

$$A_g = 160000.00$$

$$\text{From } (12.9), \text{ACI 440: } k_a = 0.56518315$$

$$g = p_t + p_c + p_v = 0.01874396$$

$$r_c = 40.00$$

$$A_e/A_c = 0.56518315$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cdot \text{Cos}(\theta_1) = 1.016$$

$$\text{effective strain from } (12.5) \text{ and } (12.12), e_{fe} = 0.004$$

$$f_u = 0.01$$

$$E_f = 64828.00$$

$$E_c = 26999.444$$

$$y = 0.27975145$$

$$A = 0.0186534$$

$$B = 0.01050082$$

$$\text{with } E_s = 200000.00$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 10

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.8468314E-031$

EDGE -B-

Shear Force, $V_b = 1.8468314E-031$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1137.257$

-Compression: $As_{c,com} = 1137.257$

-Middle: $As_{mid} = 402.1239$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.18171192$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 115036.425$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.7255E+008$

$Mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.7255E+008$

$Mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

ϕ_o (5A.5, TBDY) = 0.002

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase^* sh_{\min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af^* pf^* f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL^*t^* \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1^* A_{ext} + ase_2^* A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_2_1 = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_2_2 = 147456.00$

$psh_{\min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 3.00633$

 $psh_x * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.00633$

ps_1 (external) = $(Ash_1^* h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1^* ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2^* h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2^* ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $psh_y * F_{ywe} = psh_1 * F_{ywe1} + ps_2 * F_{ywe2} = 3.00633$

ps_1 (external) = $(Ash_1^* h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1^* ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2^* h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2^* ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

$c =$ confinement factor = 1.13212

$y_1 = 0.00140044$

$sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.538$
 $fy2 = 367.9484$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = confinement\ factor = 1.13212$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$

$$\begin{aligned} \text{Mu} &= \text{MRc} (4.14) = 1.7255\text{E}+008 \\ u &= \text{su} (4.1) = 1.7890363\text{E}-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature κ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 1.7890363\text{E}-005 \\ \text{Mu} &= 1.7255\text{E}+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 400.00 \\ d &= 357.00 \\ d' &= 43.00 \\ v &= 0.00126831 \\ N &= 5976.808 \\ f_c &= 33.00 \\ c_o (5A.5, \text{TBDY}) &= 0.002 \\ \text{Final value of } \kappa_u: \kappa_u^* &= \text{shear_factor} * \text{Max}(\kappa_u, \kappa_c) = 0.01608084 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \kappa_u &= 0.01608084 \\ \kappa_{ue} ((5.4c), \text{TBDY}) &= a_{se} * \text{sh}_{, \text{min}} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348 \\ \text{where } f &= a_f * p_f * f_{fe} / f_{ce} \text{ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)} \end{aligned}$$

$$\begin{aligned} f_x &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} f_y &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} R &= 40.00 \\ \text{Effective FRP thickness, } t_f &= NL * t * \text{Cos}(b_1) = 1.016 \\ f_{u,f} &= 1055.00 \\ E_f &= 64828.00 \\ u_{,f} &= 0.015 \\ a_{se} ((5.4d), \text{TBDY}) &= (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288 \\ a_{se1} &= 0.24250288 \\ b_{o,1} &= 340.00 \\ h_{o,1} &= 340.00 \\ b_{i,2,1} &= 462400.00 \\ a_{se2} &= \text{Max}(a_{se1}, a_{se2}) = 0.24250288 \\ b_{o,2} &= 192.00 \\ h_{o,2} &= 192.00 \\ b_{i,2,2} &= 147456.00 \\ p_{sh, \text{min}} * F_{ywe} &= \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633 \end{aligned}$$

$$\begin{aligned} p_{sh,x} * F_{ywe} &= p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.00633 \\ p_{s1} (\text{external}) &= (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699 \\ A_{sh1} &= A_{stir,1} * n_{s,1} = 157.0796 \end{aligned}$$

No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.00633
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00392699
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 160000.00
s₁ = 100.00
s₂ = 250.00
fywe₁ = 694.4444
fywe₂ = 555.5556
fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.538
fy₁ = 367.9484
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su₁ = 0.4*esu₁_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu₁_nominal = 0.08,

For calculation of esu₁_nominal and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es₁ = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814
ft₂ = 441.538
fy₂ = 367.9484
su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su₂ = 0.4*esu₂_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu₂_nominal = 0.08,

For calculation of esu₂_nominal and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/ld)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es₂ = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

y_v = 0.00140044
sh_v = 0.0044814
ft_v = 466.813
fy_v = 389.0108
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$

with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.088798$

$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.088798$

$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

$c =$ confinement factor = 1.13212

$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.11405247$

$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.11405247$

$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < vs_{y2}$ - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

$Mu = MRc$ (4.14) = 1.7255E+008

$u = su$ (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

where ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + Min(fx, fy) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$fy = 0.07683125$

af = 0.57333333
b = 400.00
h = 400.00
From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508
bw = 400.00
effective stress from (A.35), ff,e = 870.5244

R = 40.00
Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288
ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00
From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247

2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247

v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005
Mu = 1.7255E+008

with full section properties:

b = 400.00
d = 357.00
d' = 43.00
v = 0.00126831
N = 5976.808
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{\min} * fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.09892348$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

fy = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

R = 40.00

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288

bo_1 = 340.00

ho_1 = 340.00

bi2_1 = 462400.00

ase2 = $\text{Max}(ase1, ase2) = 0.24250288$

bo_2 = 192.00

ho_2 = 192.00

bi2_2 = 147456.00

$psh_{\min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

$psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$$h_2 = 200.00$$

$$A_{sec} = 160000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 694.4444$$

$$f_{ywe2} = 555.5556$$

$$f_{ce} = 33.00$$

$$\text{From } ((5.A.5), \text{ TBDY}), \text{ TBDY: } c_c = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 441.538$$

$$fy_1 = 367.9484$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.9484$$

$$\text{with } Es_1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.538$$

$$fy_2 = 367.9484$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu_{2,nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 367.9484$$

$$\text{with } Es_2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.813$$

$$fy_v = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$suv = 0.4 * esuv_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (f_{s,jacket} * A_{sl,mid,jacket} + f_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 389.0108$$

$$\text{with } Es_v = (E_{s,jacket} * A_{sl,mid,jacket} + E_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.088798$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.088798$$

$$v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{ TBDY}) = 37.35991$$

cc (5A.5, TBDY) = 0.00332119
c = confinement factor = 1.13212
1 = $Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
2 = $Asl,com/(b*d)*(fs2/fc) = 0.11405247$
v = $Asl,mid/(b*d)*(fsv/fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->
v < vs,y2 - LHS eq.(4.5) is satisfied

---->
su (4.9) = 0.19835408
Mu = MRc (4.14) = 1.7255E+008
u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/l_d

Inadequate Lap Length with lb/l_d = 0.30

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 633070.334

Calculation of Shear Strength at edge 1, Vr1 = 633070.334

Vr1 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: $fc' = (fc'_{jacket}*Area_{jacket} + fc'_{core}*Area_{core})/Area_{section} = 29.75$, but $fc'^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00

Mu = 8.4878329E-012

Vu = 1.8468314E-031

d = 0.8*h = 320.00

Nu = 5976.808

Ag = 160000.00

From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \csc)\sin\alpha$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(α), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:

total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 633070.334
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 29.75, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00
Mu = 8.4878329E-012
Vu = 1.8468314E-031
d = 0.8*h = 320.00
Nu = 5976.808
Ag = 160000.00
From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68
where:

Vs1 = 279252.68 is calculated for jacket, with:
d = 320.00
Av = 157079.633
fy = 555.5556
s = 100.00

Vs1 is multiplied by Col1 = 1.00
s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:
d = 160.00
Av = 100530.965
fy = 444.4444
s = 250.00

Vs2 is multiplied by Col2 = 0.00
s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148
f = 0.95, for fully-wrapped sections
wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) sin + cos is replaced with (cot + cota)sin which is more a generalised expression,
where is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(,), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, = 45° and = -45° to take into consideration the cyclic seismic loading.

orientation 1: 1 = b1 + 90° = 90.00

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:
total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket
New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.4444$
Existing Column
Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.5556$
#####

External Height, $H = 400.00$
External Width, $W = 400.00$
Internal Height, $H = 200.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.13212
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $N_{oDir} = 1$
Fiber orientations, $b_i = 0.00^\circ$
Number of layers, $N_L = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 3.2548216E-032$
EDGE -B-
Shear Force, $V_b = -3.2548216E-032$
BOTH EDGES
Axial Force, $F = -5976.808$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 2676.637$
Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 1137.257$
-Compression: $Asl,com = 1137.257$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 0.18171192$

Member Controlled by Flexure ($Ve/Vr < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 115036.425$

with

$Mpr1 = \text{Max}(Mu1+, Mu1-) = 1.7255E+008$

$Mu1+ = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu1- = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$Mpr2 = \text{Max}(Mu2+, Mu2-) = 1.7255E+008$

$Mu2+ = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu2- = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh, \text{min}(fywe/fce + \text{Min}(fx, fy)) = 0.09892348$

where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $ffe = 870.5244$

$fy = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $ffe = 870.5244$

$R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$fu,f = 1055.00$

$Ef = 64828.00$

$u,f = 0.015$

ase ((5.4d), TBDY) = $(ase1 * Aext + ase2 * Aint) / Asec = 0.24250288$

ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (fs_{jacket} \cdot A_{s1,com,jacket} + fs_{core} \cdot A_{s1,com,core}) / A_{s1,com} = 367.9484$

with $Es_2 = (Es_{jacket} \cdot A_{s1,com,jacket} + Es_{core} \cdot A_{s1,com,core}) / A_{s1,com} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.813$

$fy_v = 389.0108$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $Esv = (Es_{jacket} \cdot A_{s,mid,jacket} + Es_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.088798$

$2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.088798$

$v = A_{s,mid} / (b \cdot d) \cdot (fsv / fc) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

$1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.11405247$

$2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.11405247$

$v = A_{s,mid} / (b \cdot d) \cdot (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

$Mu = MRc$ (4.14) = 1.7255E+008

$u = su$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_{2,1} = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_{2,2} = 147456.00$

$psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

c = confinement factor = 1.13212

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.538$

$f_{y1} = 367.9484$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,
 For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{s1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 367.9484$
 with $E_{s1} = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $f_{y2} = 367.9484$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,
 For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 367.9484$
 with $E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $f_{y_v} = 389.0108$
 $s_{u_v} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u_v} = 0.4 * e_{s_{u_v}}_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u_v}}_nominal = 0.08$,
 considering characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY
 For calculation of $e_{s_{u_v}}_nominal$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_{u_v}} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 389.0108$
 with $E_{s_{u_v}} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.088798$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.088798$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.11405247$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.11405247$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.19835408$
 $M_u = M_{Rc} (4.14) = 1.7255E+008$
 $u = s_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$\mu_u = 1.7890363E-005$$

$$\mu = 1.7255E+008$$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_u: \mu_u^* = \text{shear_factor} * \text{Max}(\mu_u, \mu_c) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_u = 0.01608084$$

$$\mu_{e \text{ (5.4c), TBDY}} = a_{se} * \text{sh}_{, \text{min}} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$f_y = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$a_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,1} = 462400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2} = 147456.00$$

$$p_{sh, \text{min}} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 \cdot h2 / s2) / Asec = 0.00050265$$

$$Ash2 = Astir_2 \cdot ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$psh_y \cdot Fywe = psh1 \cdot Fywe1 + ps2 \cdot Fywe2 = 3.00633$$

$$ps1 \text{ (external)} = (Ash1 \cdot h1 / s1) / Asec = 0.00392699$$

$$Ash1 = Astir_1 \cdot ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 \cdot h2 / s2) / Asec = 0.00050265$$

$$Ash2 = Astir_2 \cdot ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$Asec = 160000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.4444$$

$$fywe2 = 555.5556$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.538$$

$$fy1 = 367.9484$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$su1 = 0.4 \cdot esu1_{\text{nominal}} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{\text{nominal}} = 0.08$,

For calculation of $esu1_{\text{nominal}}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_{\text{jacket}} \cdot Asl, \text{ten, jacket} + fs_{\text{core}} \cdot Asl, \text{ten, core}) / Asl, \text{ten} = 367.9484$$

$$\text{with } Es1 = (Es_{\text{jacket}} \cdot Asl, \text{ten, jacket} + Es_{\text{core}} \cdot Asl, \text{ten, core}) / Asl, \text{ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/lb, \text{min} = 0.30$$

$$su2 = 0.4 \cdot esu2_{\text{nominal}} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu2_{\text{nominal}} = 0.08$,

For calculation of $esu2_{\text{nominal}}$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_{\text{jacket}} \cdot Asl, \text{com, jacket} + fs_{\text{core}} \cdot Asl, \text{com, core}) / Asl, \text{com} = 367.9484$$

$$\text{with } Es2 = (Es_{\text{jacket}} \cdot Asl, \text{com, jacket} + Es_{\text{core}} \cdot Asl, \text{com, core}) / Asl, \text{com} = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$suv = 0.4 \cdot esuv_{\text{nominal}} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $\epsilon_{sv_nominal}$ and γ_v , η_v , f_{tv} , f_{yv} , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , η_1 , f_{t1} , f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $\epsilon_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.19835408

$M_u = M_{Rc}$ (4.14) = 1.7255E+008

$u = \mu_u$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

cc (5A.5, TBDY) = 0.002

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.01608084$

η_{ve} ((5.4c), TBDY) = $\eta_{ve} \cdot \text{sh}_{,min} \cdot f_{ywe} / f_{ce} + \text{Min}(\eta_{fx}, \eta_{fy}) = 0.09892348$

where $\eta_{fx} = \eta_{fy} = \eta_{ve} \cdot \text{pf} \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $\eta_{fx} = 0.07683125$

$\eta_{fy} = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $\text{pf} = 2t_f/b_w = 0.00508$

$b_w = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$\eta_{fx} = 0.07683125$

$\eta_{fy} = 0.57333333$

$b = 400.00$

h = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.00508$
bw = 400.00
effective stress from (A.35), $ff,e = 870.5244$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $ase((5.4d), \text{TBDY}) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.24250288$
 $ase1 = 0.24250288$
 $bo_1 = 340.00$
 $ho_1 = 340.00$
 $bi2_1 = 462400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.24250288$
 $bo_2 = 192.00$
 $ho_2 = 192.00$
 $bi2_2 = 147456.00$
 $psh_{,min}*F_{ywe} = \text{Min}(psh_{,x}*F_{ywe}, psh_{,y}*F_{ywe}) = 3.00633$

$psh_{,x}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$psh_{,y}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 160000.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 694.4444$
 $f_{ywe2} = 555.5556$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $lo/lou_{,min} = lb/ld = 0.30$
 $su1 = 0.4*esu1_{nominal}((5.5), \text{TBDY}) = 0.032$
From table 5A.1, TBDY: $esu1_{nominal} = 0.08$
For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
with $fs1 = (fs_{jacket}*A_{sl,ten,jacket} + fs_{core}*A_{sl,ten,core})/A_{sl,ten} = 367.9484$
with $Es1 = (Es_{jacket}*A_{sl,ten,jacket} + Es_{core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 37.35991$$

$$cc (5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.19835408$$

$$Mu = MRc (4.14) = 1.7255E+008$$

$$u = su (4.1) = 1.7890363E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 633070.334$

Calculation of Shear Strength at edge 1, $Vr1 = 633070.334$

$$Vr1 = VCoI ((10.3), ASCE 41-17) = knl*VCoIo$$

$$VCoIo = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.5556$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 444.4444$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \text{cota})\sin\alpha$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha_1 = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha_1)|, |V_f(-45, \alpha_1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / N_{\text{Dir}} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 463788.751$

$b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col}0}$

$V_{\text{Col}0} = 633070.334$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, α)|), with:

total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 463788.751

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

External Height, H = 400.00

External Width, W = 400.00

Internal Height, H = 200.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $b_i = 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

 Stepwise Properties

Bending Moment, $M = -2.1377975E-010$
 Shear Force, $V_2 = -5699.261$
 Shear Force, $V_3 = 1.1783778E-013$
 Axial Force, $F = -5974.527$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $As_{lt} = 1137.257$
 -Compression: $As_{lc} = 1539.38$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten} = 1137.257$
 -Compression: $As_{l,com} = 1137.257$
 -Middle: $As_{l,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,jacket} = 829.3805$
 -Compression: $As_{l,com,jacket} = 829.3805$
 -Middle: $As_{l,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,core} = 307.8761$
 -Compression: $As_{l,com,core} = 307.8761$
 -Middle: $As_{l,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 16.80$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.03871933$
 $u = y + p = 0.04555215$

 - Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00355215$ ((4.29), Biskinis Phd)
 $M_y = 1.2106E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1500.00
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7040E+013$
 $factor = 0.30$
 $A_g = 160000.00$
 Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 29.75$
 $N = 5974.527$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 5.6801E+013$

 Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.7839606E-006$
 with $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109378$
 $A = 0.01888488$
 $B = 0.01064174$
 with $pt = 0.00680079$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.527$
 $b = 400.00$
 $" = 0.12044818$

$y_{comp} = 2.3130541E-005$
 with $f_c^* (12.3, (ACI 440)) = 34.65043$
 $f_c = 33.00$
 $f_l = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $A_g = 160000.00$
 From (12.9), ACI 440: $k_a = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $A_e/A_c = 0.56518315$
 Effective FRP thickness, $t_f = NL \cdot t \cdot \text{Cos}(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975145$
 $A = 0.0186534$
 $B = 0.01050082$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.042$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.18171192$

$d = d_{external} = 357.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00680079$

jacket: $s_1 = A_{v1} \cdot h_1 / (s_1 \cdot A_g) = 0.00392699$

$A_{v1} = 157.0796$, is the total area of all stirrups parallel to loading (shear) direction

$h_1 = 400.00$

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot h_2 / (s_2 \cdot A_g) = 0.00050265$

$A_{v2} = 100.531$, is the total area of all stirrups parallel to loading (shear) direction

$h_2 = 200.00$

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5974.527$

$A_g = 160000.00$

$f_c E = (f_{c,jacket} \cdot \text{Area}_{jacket} + f_{c,core} \cdot \text{Area}_{core}) / \text{section_area} = 29.75$

$f_y E = (f_{y,ext_Long_Reinf} \cdot \text{Area}_{ext_Long_Reinf} + f_{y,int_Long_Reinf} \cdot \text{Area}_{int_Long_Reinf}) / \text{Area}_{Tot_Long_Rein} = 529.9948$

$f_y E = (f_{y,ext_Trans_Reinf} \cdot \text{Area}_{ext_Trans_Reinf} + f_{y,int_Trans_Reinf} \cdot \text{Area}_{int_Trans_Reinf}) / \text{Area}_{Tot_Trans_Rein} =$

542.9472

$pl = \text{Area_Tot_Long_Rein}/(b*d) = 0.01874396$

$b = 400.00$

$d = 357.00$

$f_{cE} = 29.75$

End Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 11

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of γ for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, $f_c = f_{cm} = 33.00$
New material: Steel Strength, $f_s = f_{sm} = 555.5556$
Existing Column
Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material: Steel Strength, $f_s = f_{sm} = 444.4444$

External Height, $H = 400.00$
External Width, $W = 400.00$
Internal Height, $H = 200.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $b_i: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -2.1377975E-010$
Shear Force, $V_a = 1.1783778E-013$
EDGE -B-
Bending Moment, $M_b = -1.3974459E-010$
Shear Force, $V_b = -1.1783778E-013$
BOTH EDGES
Axial Force, $F = -5974.527$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 1137.257$
-Compression: $As_c = 1539.38$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 1137.257$
-Compression: $As_{l,com} = 1137.257$
-Middle: $As_{l,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.80$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $VR = *V_n = 475023.398$
 $V_n ((10.3), ASCE 41-17) = knl * V_{ColO} = 558851.057$
 $V_{Col} = 558851.057$
 $knl = 1.00$

displacement_ductility_demand = 0.00

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 22.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 2.1377975E-010$

$\nu_u = 1.1783778E-013$

$d = 0.8 \cdot h = 320.00$

$N_u = 5974.527$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 251327.412$

where:

$V_{s1} = 251327.412$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot_a) \sin a$ which is more a generalised expression, where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 405571.497$

$b_w = 400.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END A -

for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 6.4104099E-022$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00355215$ ((4.29), Biskinis Phd)

$M_y = 1.2106E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 1.7040E+013$

factor = 0.30

$A_g = 160000.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$

$N = 5974.527$

$E_c \cdot I_g = E_c \cdot I_{g_{\text{jacket}}} + E_c \cdot I_{g_{\text{core}}} = 5.6801E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 5.7839606\text{E-}006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109378$
 $A = 0.01888488$
 $B = 0.01064174$
with $pt = 0.00796398$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.527$
 $b = 400.00$
 $" = 0.12044818$
 $y_{\text{comp}} = 2.3130541\text{E-}005$
with fc^* (12.3, (ACI 440)) = 34.65043
 $fc = 33.00$
 $fl = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $Ag = 160000.00$
From (12.9), ACI 440: $ka = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $Ae/Ac = 0.56518315$
Effective FRP thickness, $tf = NL \cdot t \cdot \text{Cos}(\theta_1) = 1.016$
effective strain from (12.5) and (12.12), $e_{fe} = 0.004$
 $fu = 0.01$
 $Ef = 64828.00$
 $Ec = 26999.444$
 $y = 0.27975145$
 $A = 0.0186534$
 $B = 0.01050082$
with $Es = 200000.00$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 12

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $bi: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.8468314E-031$

EDGE -B-

Shear Force, $V_b = 1.8468314E-031$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1137.257$

-Compression: $As_{l,com} = 1137.257$

-Middle: $As_{l,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.18171192$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 115036.425$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.7255E+008$

$Mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.7255E+008$

$Mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

ϕ_0 (5A.5, TBDY) = 0.002

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase^* sh_{min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

$ase1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi2_1 = 462400.00$

$ase2 = \text{Max}(ase1, ase2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi2_2 = 147456.00$

$psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

 $psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$

$ps1$ (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

$Ash1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h1 = 400.00$

$ps2$ (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

$Ash2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h2 = 200.00$

 $psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$

$ps1$ (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

$Ash1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h1 = 400.00$

$ps2$ (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

$Ash2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h2 = 200.00$

 $A_{sec} = 160000.00$

$s1 = 100.00$

$s2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

$c =$ confinement factor = 1.13212

$y1 = 0.00140044$

$sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.538$
 $fy2 = 367.9484$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$

$$\begin{aligned} \text{Mu} &= \text{MRc} (4.14) = 1.7255\text{E}+008 \\ u &= \text{su} (4.1) = 1.7890363\text{E}-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 1.7890363\text{E}-005 \\ \text{Mu} &= 1.7255\text{E}+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 400.00 \\ d &= 357.00 \\ d' &= 43.00 \\ v &= 0.00126831 \\ N &= 5976.808 \\ f_c &= 33.00 \\ c_o (5A.5, \text{TBDY}) &= 0.002 \\ \text{Final value of } \phi_u: \phi_u^* &= \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01608084 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \phi_u &= 0.01608084 \\ \phi_{we} ((5.4c), \text{TBDY}) &= a_{se} * \text{sh}_{,min} * f_{ywe} / f_{ce} + \text{Min}(\phi_x, \phi_y) = 0.09892348 \\ \text{where } \phi &= a_f * p_f * f_{fe} / f_{ce} \text{ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)} \end{aligned}$$

$$\begin{aligned} \phi_x &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} \phi_y &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} R &= 40.00 \\ \text{Effective FRP thickness, } t_f &= N L * t * \text{Cos}(b_1) = 1.016 \\ f_{u,f} &= 1055.00 \\ E_f &= 64828.00 \\ u_{,f} &= 0.015 \\ a_{se} ((5.4d), \text{TBDY}) &= (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288 \\ a_{se1} &= 0.24250288 \\ b_{o,1} &= 340.00 \\ h_{o,1} &= 340.00 \\ b_{i,1} &= 462400.00 \\ a_{se2} &= \text{Max}(a_{se1}, a_{se2}) = 0.24250288 \\ b_{o,2} &= 192.00 \\ h_{o,2} &= 192.00 \\ b_{i,2} &= 147456.00 \\ p_{sh,min} * F_{ywe} &= \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633 \end{aligned}$$

$$\begin{aligned} p_{sh,x} * F_{ywe} &= p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.00633 \\ p_{s1} (\text{external}) &= (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699 \\ A_{sh1} &= A_{stir,1} * n_{s,1} = 157.0796 \end{aligned}$$

No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.00633
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00392699
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 160000.00
s₁ = 100.00
s₂ = 250.00
fywe₁ = 694.4444
fywe₂ = 555.5556
fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.538
fy₁ = 367.9484
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

su₁ = 0.4*esu₁_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu₁_nominal = 0.08,

For calculation of esu₁_nominal and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*As_{l,ten,jacket} + fs_{core}*As_{l,ten,core})/As_{l,ten} = 367.9484

with Es₁ = (Es_{jacket}*As_{l,ten,jacket} + Es_{core}*As_{l,ten,core})/As_{l,ten} = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814
ft₂ = 441.538
fy₂ = 367.9484
su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 0.30

su₂ = 0.4*esu₂_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu₂_nominal = 0.08,

For calculation of esu₂_nominal and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*As_{l,com,jacket} + fs_{core}*As_{l,com,core})/As_{l,com} = 367.9484

with Es₂ = (Es_{jacket}*As_{l,com,jacket} + Es_{core}*As_{l,com,core})/As_{l,com} = 200000.00

y_v = 0.00140044
sh_v = 0.0044814
ft_v = 466.813
fy_v = 389.0108
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$

with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$

1 = $Asl_{ten} / (b * d) * (fs1 / fc) = 0.088798$

2 = $Asl_{com} / (b * d) * (fs2 / fc) = 0.088798$

v = $Asl_{mid} / (b * d) * (fsv / fc) = 0.03319551$

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = $Asl_{ten} / (b * d) * (fs1 / fc) = 0.11405247$

2 = $Asl_{com} / (b * d) * (fs2 / fc) = 0.11405247$

v = $Asl_{mid} / (b * d) * (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->

v < vs_{y2} - LHS eq.(4.5) is satisfied

---->

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2+

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005

Mu = 1.7255E+008

with full section properties:

b = 400.00

d = 357.00

d' = 43.00

v = 0.00126831

N = 5976.808

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = shear_factor * Max(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

we ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + Min(fx, fy) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.07683125$

$af = 0.57333333$

b = 400.00

h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $f_{fe} = 870.5244$

 $fy = 0.07683125$

af = 0.57333333
b = 400.00
h = 400.00
From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508
bw = 400.00
effective stress from (A.35), ff,e = 870.5244

R = 40.00
Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288
ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00
From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247

2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247

v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005
Mu = 1.7255E+008

with full section properties:

b = 400.00
d = 357.00
d' = 43.00
v = 0.00126831
N = 5976.808
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{\min} * fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.09892348$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

fy = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

R = 40.00

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288

bo_1 = 340.00

ho_1 = 340.00

bi2_1 = 462400.00

ase2 = $\text{Max}(ase1, ase2) = 0.24250288$

bo_2 = 192.00

ho_2 = 192.00

bi2_2 = 147456.00

$psh_{\min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$
Ash1 = $A_{stir_1} * ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

$psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$
Ash1 = $A_{stir_1} * ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

Asec = 160000.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.4444

fywe2 = 555.5556

fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119

c = confinement factor = 1.13212

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.538

fy1 = 367.9484

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.538

fy2 = 367.9484

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

$$cc(5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.11405247$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11405247$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.19835408$$

$$M_u = MR_c(4.14) = 1.7255E+008$$

$$u = s_u(4.1) = 1.7890363E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 633070.334$

Calculation of Shear Strength at edge 1, $V_{r1} = 633070.334$

$$V_{r1} = V_{CoI}((10.3), ASCE 41-17) = k_{nl} * V_{CoIO}$$

$$V_{CoIO} = 633070.334$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_{s+} = f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 29.75$, but $f_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$M_u = 8.4878329E-012$$

$$V_u = 1.8468314E-031$$

$$d = 0.8 * h = 320.00$$

$$N_u = 5976.808$$

$$A_g = 160000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 279252.68$$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.5556$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 0.00$ is calculated for core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 444.4444$$

$$s = 250.00$$

V_{s2} is multiplied by $Col2 = 0.00$

$$s/d = 1.5625$$

$$V_f((11-3)-(11.4), ACI 440) = 188111.148$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 90.00$

$$V_f = \text{Min}(|V_f(45, 1)|, |V_f(-45, a1)|), \text{ with:}$$

$$\text{total thickness per orientation, } t_{f1} = NL * t / \text{NoDir} = 1.016$$

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 633070.334
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 29.75, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00
Mu = 8.4878329E-012
Vu = 1.8468314E-031
d = 0.8*h = 320.00
Nu = 5976.808
Ag = 160000.00
From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68
where:

Vs1 = 279252.68 is calculated for jacket, with:
d = 320.00
Av = 157079.633
fy = 555.5556
s = 100.00

Vs1 is multiplied by Col1 = 1.00
s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:
d = 160.00
Av = 100530.965
fy = 444.4444
s = 250.00

Vs2 is multiplied by Col2 = 0.00
s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148
f = 0.95, for fully-wrapped sections
wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) sin + cos is replaced with (cot + cota)sin which is more a generalised expression,
where is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(,), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, = 45° and = -45° to take into consideration the cyclic seismic loading.

orientation 1: 1 = b1 + 90° = 90.00

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:
total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = 3.2548216E-032$

EDGE -B-

Shear Force, $V_b = -3.2548216E-032$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 1137.257$
-Compression: $Asl,com = 1137.257$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 0.18171192$

Member Controlled by Flexure ($Ve/Vr < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 115036.425$

with
 $Mpr1 = \text{Max}(Mu1+, Mu1-) = 1.7255E+008$
 $Mu1+ = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu1- = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $Mpr2 = \text{Max}(Mu2+, Mu2-) = 1.7255E+008$
 $Mu2+ = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu2- = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$
 $Mu = 1.7255E+008$

with full section properties:

$b = 400.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.00126831$
 $N = 5976.808$
 $fc = 33.00$
 $co (5A.5, TBDY) = 0.002$
Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $cu = 0.01608084$
 $w_e ((5.4c), TBDY) = ase * sh, \text{min}(fywe/fce + \text{Min}(fx, fy)) = 0.09892348$
where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$fx = 0.07683125$
 $af = 0.57333333$
 $b = 400.00$
 $h = 400.00$
From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$
 $bw = 400.00$
effective stress from (A.35), $ff,e = 870.5244$

$fy = 0.07683125$
 $af = 0.57333333$
 $b = 400.00$
 $h = 400.00$
From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$
 $bw = 400.00$
effective stress from (A.35), $ff,e = 870.5244$

$R = 40.00$
Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$
 $fu,f = 1055.00$
 $Ef = 64828.00$
 $u,f = 0.015$
 $ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.24250288$

ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (f_s \cdot \text{jacket} \cdot A_{s, \text{com, jacket}} + f_s \cdot \text{core} \cdot A_{s, \text{com, core}}) / A_{s, \text{com}} = 367.9484$

with $Es_2 = (E_s \cdot \text{jacket} \cdot A_{s, \text{com, jacket}} + E_s \cdot \text{core} \cdot A_{s, \text{com, core}}) / A_{s, \text{com}} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.813$

$fy_v = 389.0108$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o, \text{min}} = l_b/l_d = 0.30$

$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fs_yv = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fs_yv = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_s \cdot \text{jacket} \cdot A_{s, \text{mid, jacket}} + f_s \cdot \text{mid} \cdot A_{s, \text{mid, core}}) / A_{s, \text{mid}} = 389.0108$

with $E_{sv} = (E_s \cdot \text{jacket} \cdot A_{s, \text{mid, jacket}} + E_s \cdot \text{mid} \cdot A_{s, \text{mid, core}}) / A_{s, \text{mid}} = 200000.00$

$1 = A_{s, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$2 = A_{s, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$v = A_{s, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, \text{TBDY}) = 37.35991$

$cc (5A.5, \text{TBDY}) = 0.00332119$

$c = \text{confinement factor} = 1.13212$

$1 = A_{s, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$2 = A_{s, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$v = A_{s, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s, y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.19835408$

$Mu = MRc (4.14) = 1.7255E+008$

$u = su (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$cc (5A.5, \text{TBDY}) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $a_{se} \cdot \text{sh}_{\min} \cdot f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = a_f \cdot p_f \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f / b_w = 0.00508$

$b_w = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$f_y = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f / b_w = 0.00508$

$b_w = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$R = 40.00$

Effective FRP thickness, $t_f = N_L \cdot t \cdot \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

a_{se} ((5.4d), TBDY) = $(a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.24250288$

$a_{se1} = 0.24250288$

$b_{o,1} = 340.00$

$h_{o,1} = 340.00$

$b_{i,2,1} = 462400.00$

$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.24250288$

$b_{o,2} = 192.00$

$h_{o,2} = 192.00$

$b_{i,2,2} = 147456.00$

$p_{sh,\min} \cdot F_{ywe} = \text{Min}(p_{sh,x} \cdot F_{ywe}, p_{sh,y} \cdot F_{ywe}) = 3.00633$

$p_{sh,x} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.00633$

p_{s1} (external) = $(A_{sh1} \cdot h_1 / s_1) / A_{sec} = 0.00392699$

$A_{sh1} = A_{stir,1} \cdot n_{s,1} = 157.0796$

No stirups, $n_{s,1} = 2.00$

$h_1 = 400.00$

p_{s2} (internal) = $(A_{sh2} \cdot h_2 / s_2) / A_{sec} = 0.00050265$

$A_{sh2} = A_{stir,2} \cdot n_{s,2} = 100.531$

No stirups, $n_{s,2} = 2.00$

$h_2 = 200.00$

$p_{sh,y} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.00633$

p_{s1} (external) = $(A_{sh1} \cdot h_1 / s_1) / A_{sec} = 0.00392699$

$A_{sh1} = A_{stir,1} \cdot n_{s,1} = 157.0796$

No stirups, $n_{s,1} = 2.00$

$h_1 = 400.00$

p_{s2} (internal) = $(A_{sh2} \cdot h_2 / s_2) / A_{sec} = 0.00050265$

$A_{sh2} = A_{stir,2} \cdot n_{s,2} = 100.531$

No stirups, $n_{s,2} = 2.00$

$h_2 = 200.00$

$A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 694.4444$

$f_{ywe2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00332119$

c = confinement factor = 1.13212

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.538$

$f_{y1} = 367.9484$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{s_{u1,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u1,nominal}} = 0.08$,
 For calculation of $e_{s_{u1,nominal}}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{s_{y1}} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 367.9484$
 with $E_{s1} = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $f_{y2} = 367.9484$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{s_{u2,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u2,nominal}} = 0.08$,
 For calculation of $e_{s_{u2,nominal}}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{s_{y2}} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} * A_{s,com,jacket} + f_{s,core} * A_{s,com,core}) / A_{s,com} = 367.9484$
 with $E_{s2} = (E_{s,jacket} * A_{s,com,jacket} + E_{s,core} * A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $f_{y_v} = 389.0108$
 $s_{u_v} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u_v} = 0.4 * e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,
 considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY
 For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_v} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 389.0108$
 with $E_{s_v} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.088798$
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.088798$
 $v = A_{s,mid} / (b * d) * (f_{s_v} / f_c) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.11405247$
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.11405247$
 $v = A_{s,mid} / (b * d) * (f_{s_v} / f_c) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.19835408$
 $M_u = M_{Rc} (4.14) = 1.7255E+008$
 $u = s_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7890363E-005$$

$$\mu = 1.7255E+008$$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01608084$$

$$\mu_e \text{ ((5.4c), TBDY)} = a_{se} * \text{sh}_{,min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$f_y = 0.07683125$$

$$a_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$a_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,1} = 462400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2} = 147456.00$$

$$p_{sh,min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 \cdot h2 / s2) / Asec = 0.00050265$$

$$Ash2 = Astir_2 \cdot ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$psh_y \cdot Fywe = psh1 \cdot Fywe1 + ps2 \cdot Fywe2 = 3.00633$$

$$ps1 \text{ (external)} = (Ash1 \cdot h1 / s1) / Asec = 0.00392699$$

$$Ash1 = Astir_1 \cdot ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 \cdot h2 / s2) / Asec = 0.00050265$$

$$Ash2 = Astir_2 \cdot ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$Asec = 160000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.4444$$

$$fywe2 = 555.5556$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.538$$

$$fy1 = 367.9484$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$su1 = 0.4 \cdot esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_nominal = 0.08,$$

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs_jacket \cdot Asl, \text{ten, jacket} + fs_core \cdot Asl, \text{ten, core}) / Asl, \text{ten} = 367.9484$$

$$\text{with } Es1 = (Es_jacket \cdot Asl, \text{ten, jacket} + Es_core \cdot Asl, \text{ten, core}) / Asl, \text{ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/lb, \text{min} = 0.30$$

$$su2 = 0.4 \cdot esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_nominal = 0.08,$$

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs2 = (fs_jacket \cdot Asl, \text{com, jacket} + fs_core \cdot Asl, \text{com, core}) / Asl, \text{com} = 367.9484$$

$$\text{with } Es2 = (Es_jacket \cdot Asl, \text{com, jacket} + Es_core \cdot Asl, \text{com, core}) / Asl, \text{com} = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$suv = 0.4 \cdot esuv_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esuv_nominal = 0.08,$$

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of $\epsilon_{sv_nominal}$ and γ_v , δ_v , f_{tv} , f_{yv} , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , δ_1 , f_{t1} , f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $\epsilon_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$\gamma_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$\gamma_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.19835408

$M_u = M_{Rc}$ (4.14) = 1.7255E+008

$u = \mu_u$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

cc (5A.5, TBDY) = 0.002

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.01608084$

μ_{we} ((5.4c), TBDY) = $a_s \cdot \delta_{h,min} \cdot f_{ywe} / f_{ce} + \text{Min}(\mu_{fx}, \mu_{fy}) = 0.09892348$

where $\mu_f = a_s \cdot p_f \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $\mu_{fx} = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$\mu_{fy} = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

h = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.00508$
bw = 400.00
effective stress from (A.35), $ff,e = 870.5244$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $ase((5.4d), \text{TBDY}) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.24250288$
 $ase1 = 0.24250288$
 $bo_1 = 340.00$
 $ho_1 = 340.00$
 $bi2_1 = 462400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.24250288$
 $bo_2 = 192.00$
 $ho_2 = 192.00$
 $bi2_2 = 147456.00$
 $psh_{,min}*F_{ywe} = \text{Min}(psh_{,x}*F_{ywe}, psh_{,y}*F_{ywe}) = 3.00633$

$psh_{,x}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$psh_{,y}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

Asec = 160000.00
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 694.4444$
 $f_{ywe2} = 555.5556$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$
 $su1 = 0.4*esu1_{nominal}((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket}*A_{sl,ten,jacket} + fs_{core}*A_{sl,ten,core})/A_{sl,ten} = 367.9484$

with $Es1 = (Es_{jacket}*A_{sl,ten,jacket} + Es_{core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/lb_{u,min} = 0.30$$

$$su2 = 0.4 * esu2_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2$, $sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1$, $sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 367.9484$$

$$\text{with } Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/ld = 0.30$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv , shv, ftv, fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1$, $sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 389.0108$$

$$\text{with } Esv = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs1 / fc) = 0.088798$$

$$2 = A_{sl,com} / (b * d) * (fs2 / fc) = 0.088798$$

$$v = A_{sl,mid} / (b * d) * (fsv / fc) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 37.35991$$

$$cc (5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = A_{sl,ten} / (b * d) * (fs1 / fc) = 0.11405247$$

$$2 = A_{sl,com} / (b * d) * (fs2 / fc) = 0.11405247$$

$$v = A_{sl,mid} / (b * d) * (fsv / fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs, y2$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.19835408$$

$$Mu = MRc (4.14) = 1.7255E+008$$

$$u = su (4.1) = 1.7890363E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 633070.334$

Calculation of Shear Strength at edge 1, $Vr1 = 633070.334$

$$Vr1 = V_{CoI} ((10.3), ASCE 41-17) = knl * V_{CoIO}$$

$$V_{CoIO} = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.5556$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 444.4444$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \text{cota})\sin\alpha$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 463788.751$

$b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col0}}$

$V_{\text{Col0}} = 633070.334$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, α)|), with:

total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 463788.751

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

External Height, H = 400.00

External Width, W = 400.00

Internal Height, H = 200.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $b_i = 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

 Stepwise Properties

 Bending Moment, $M = -1.7103E+007$
 Shear Force, $V_2 = -5699.261$
 Shear Force, $V_3 = 1.1783778E-013$
 Axial Force, $F = -5974.527$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $As_{lt} = 1137.257$
 -Compression: $As_{lc} = 1539.38$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten} = 1137.257$
 -Compression: $As_{l,com} = 1137.257$
 -Middle: $As_{l,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,jacket} = 829.3805$
 -Compression: $As_{l,com,jacket} = 829.3805$
 -Middle: $As_{l,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,core} = 307.8761$
 -Compression: $As_{l,com,core} = 307.8761$
 -Middle: $As_{l,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 16.80$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.04174045$
 $u = y + p = 0.04910641$

 - Calculation of y -

 $y = (M_y * L_s / 3) / E_{eff} = 0.00710641$ ((4.29), Biskinis Phd)
 $M_y = 1.2106E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 3000.891
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7040E+013$
 $factor = 0.30$
 $A_g = 160000.00$
 Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 29.75$
 $N = 5974.527$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 5.6801E+013$

 Calculation of Yielding Moment M_y

 Calculation of y and M_y according to Annex 7 -

 $y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.7839606E-006$
 with $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109378$
 $A = 0.01888488$
 $B = 0.01064174$
 with $pt = 0.00680079$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.527$
 $b = 400.00$
 $" = 0.12044818$

$y_{comp} = 2.3130541E-005$
 with $f_c^* (12.3, (ACI 440)) = 34.65043$
 $f_c = 33.00$
 $f_l = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $A_g = 160000.00$
 From (12.9), ACI 440: $k_a = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $A_e/A_c = 0.56518315$
 Effective FRP thickness, $t_f = NL \cdot t \cdot \text{Cos}(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975145$
 $A = 0.0186534$
 $B = 0.01050082$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.042$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.18171192$

$d = d_{external} = 357.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00680079$

jacket: $s_1 = A_{v1} \cdot h_1 / (s_1 \cdot A_g) = 0.00392699$

$A_{v1} = 157.0796$, is the total area of all stirrups parallel to loading (shear) direction

$h_1 = 400.00$

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot h_2 / (s_2 \cdot A_g) = 0.00050265$

$A_{v2} = 100.531$, is the total area of all stirrups parallel to loading (shear) direction

$h_2 = 200.00$

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$NUD = 5974.527$

$A_g = 160000.00$

$f_c E = (f_{c,jacket} \cdot \text{Area}_{jacket} + f_{c,core} \cdot \text{Area}_{core}) / \text{section_area} = 29.75$

$f_y E = (f_{y,ext_Long_Reinf} \cdot \text{Area}_{ext_Long_Reinf} + f_{y,int_Long_Reinf} \cdot \text{Area}_{int_Long_Reinf}) / \text{Area}_{Tot_Long_Rein} = 529.9948$

$f_y E = (f_{y,ext_Trans_Reinf} \cdot \text{Area}_{ext_Trans_Reinf} + f_{y,int_Trans_Reinf} \cdot \text{Area}_{int_Trans_Reinf}) / \text{Area}_{Tot_Trans_Rein} =$

542.9472

$pl = \text{Area_Tot_Long_Rein}/(b*d) = 0.01874396$

$b = 400.00$

$d = 357.00$

$f_{cE} = 29.75$

End Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 13

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

```

Existing Column
Existing material of Primary Member: Concrete Strength, fc = fc_lower_bound = 16.00
Existing material of Primary Member: Steel Strength, fs = fs_lower_bound = 400.00
Concrete Elasticity, Ec = 21019.039
Steel Elasticity, Es = 200000.00
#####
Note: Especially for the calculation of  $\gamma$  for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, fc = fcm = 33.00
New material: Steel Strength, fs = fsm = 555.5556
Existing Column
Existing material: Concrete Strength, fc = fcm = 20.00
Existing material: Steel Strength, fs = fsm = 444.4444
#####
External Height, H = 400.00
External Width, W = 400.00
Internal Height, H = 200.00
Internal Width, W = 200.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with  $l_o/l_{ou,min} = l_b/l_d = 0.30$ 
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, t = 1.016
Tensile Strength,  $f_{fu} = 1055.00$ 
Tensile Modulus,  $E_f = 64828.00$ 
Elongation,  $e_{fu} = 0.01$ 
Number of directions, NoDir = 1
Fiber orientations,  $b_i = 0.00^\circ$ 
Number of layers, NL = 1
Radius of rounding corners, R = 40.00
-----

Stepwise Properties
-----
EDGE -A-
Bending Moment,  $M_a = -1.7103E+007$ 
Shear Force,  $V_a = -5699.261$ 
EDGE -B-
Bending Moment,  $M_b = 0.05279463$ 
Shear Force,  $V_b = 5699.261$ 
BOTH EDGES
Axial Force,  $F = -5974.527$ 
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension:  $A_{sl,t} = 0.00$ 
-Compression:  $A_{sl,c} = 2676.637$ 
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension:  $A_{sl,ten} = 1137.257$ 
-Compression:  $A_{sl,com} = 1137.257$ 
-Middle:  $A_{sl,mid} = 402.1239$ 
Mean Diameter of Tension Reinforcement,  $D_{bL,ten} = 16.80$ 
-----
-----

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity  $V_R = *V_n = 475023.398$ 
 $V_n ((10.3), ASCE 41-17) = knl * V_{ColO} = 558851.057$ 
 $V_{Col} = 558851.057$ 
 $knl = 1.00$ 

```

displacement_ductility_demand = 0.21189178

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 22.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 0.05279463$

$V_u = 5699.261$

$d = 0.8 \cdot h = 320.00$

$N_u = 5974.527$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 251327.412$

where:

$V_{s1} = 251327.412$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \csc) \sin \alpha$ which is more a generalised expression, where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / N_{\text{Dir}} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 405571.497$

$b_w = 400.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END B -

for rotation axis 3 and integ. section (b)

From analysis, chord rotation $\theta = 0.00015053$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00071043$ ((4.29), Biskinis Phd)

$M_y = 1.2106 \text{E} + 008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 300.00

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 1.7040 \text{E} + 013$

factor = 0.30

$A_g = 160000.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$

$N = 5974.527$

$E_c \cdot I_g = E_c \cdot I_{g_{\text{jacket}}} + E_c \cdot I_{g_{\text{core}}} = 5.6801 \text{E} + 013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 5.7839606\text{E-}006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109378$
 $A = 0.01888488$
 $B = 0.01064174$
with $pt = 0.00796398$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.527$
 $b = 400.00$
 $" = 0.12044818$
 $y_{\text{comp}} = 2.3130541\text{E-}005$
with $fc^* (12.3, (ACI 440)) = 34.65043$
 $fc = 33.00$
 $fl = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $Ag = 160000.00$
From (12.9), ACI 440: $ka = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $Ae/Ac = 0.56518315$
Effective FRP thickness, $tf = NL \cdot t \cdot \text{Cos}(\theta_1) = 1.016$
effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975145$
 $A = 0.0186534$
 $B = 0.01050082$
with $E_s = 200000.00$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 14

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $bi: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.8468314E-031$

EDGE -B-

Shear Force, $V_b = 1.8468314E-031$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1137.257$

-Compression: $As_{c,com} = 1137.257$

-Middle: $As_{mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.18171192$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 115036.425$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.7255E+008$

$Mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.7255E+008$

$Mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

ϕ_0 (5A.5, TBDY) = 0.002

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase^* sh_{\min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af^* pf^* f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL^*t^* \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1^* A_{ext} + ase_2^* A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_2_1 = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_2_2 = 147456.00$

$psh_{\min} * Fy_{we} = \text{Min}(psh_x^* Fy_{we}, psh_y^* Fy_{we}) = 3.00633$

 $psh_x^* Fy_{we} = psh_1^* Fy_{we1} + ps_2^* Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1^* h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1^* ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2^* h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2^* ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $psh_y^* Fy_{we} = psh_1^* Fy_{we1} + ps_2^* Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1^* h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1^* ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2^* h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2^* ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

$c =$ confinement factor = 1.13212

$y_1 = 0.00140044$

$sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.538$
 $fy2 = 367.9484$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$

$$\begin{aligned} \text{Mu} &= \text{MRc} (4.14) = 1.7255\text{E}+008 \\ u &= \text{su} (4.1) = 1.7890363\text{E}-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 1.7890363\text{E}-005 \\ \text{Mu} &= 1.7255\text{E}+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 400.00 \\ d &= 357.00 \\ d' &= 43.00 \\ v &= 0.00126831 \\ N &= 5976.808 \\ f_c &= 33.00 \\ c_o (5A.5, \text{TBDY}) &= 0.002 \\ \text{Final value of } \phi_u: \phi_u^* &= \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01608084 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \phi_u &= 0.01608084 \\ \phi_{we} ((5.4c), \text{TBDY}) &= a_{se} * \text{sh}_{, \text{min}} * f_{ywe} / f_{ce} + \text{Min}(\phi_x, \phi_y) = 0.09892348 \\ \text{where } \phi &= a_f * p_f * f_{fe} / f_{ce} \text{ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)} \end{aligned}$$

$$\begin{aligned} \phi_x &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} \phi_y &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} R &= 40.00 \\ \text{Effective FRP thickness, } t_f &= N L * t * \text{Cos}(b_1) = 1.016 \\ f_{u,f} &= 1055.00 \\ E_f &= 64828.00 \\ u_{,f} &= 0.015 \\ a_{se} ((5.4d), \text{TBDY}) &= (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288 \\ a_{se1} &= 0.24250288 \\ b_{o,1} &= 340.00 \\ h_{o,1} &= 340.00 \\ b_{i2,1} &= 462400.00 \\ a_{se2} &= \text{Max}(a_{se1}, a_{se2}) = 0.24250288 \\ b_{o,2} &= 192.00 \\ h_{o,2} &= 192.00 \\ b_{i2,2} &= 147456.00 \\ p_{sh, \text{min}} * F_{ywe} &= \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633 \end{aligned}$$

$$\begin{aligned} p_{sh,x} * F_{ywe} &= p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 3.00633 \\ p_{s1} (\text{external}) &= (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699 \\ A_{sh1} &= A_{stir,1} * n_{s,1} = 157.0796 \end{aligned}$$

No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.00633
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00392699
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 160000.00
s₁ = 100.00
s₂ = 250.00
fywe₁ = 694.4444
fywe₂ = 555.5556
fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.538
fy₁ = 367.9484
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*As_{l,ten,jacket} + fs_{core}*As_{l,ten,core})/As_{l,ten} = 367.9484

with Es₁ = (Es_{jacket}*As_{l,ten,jacket} + Es_{core}*As_{l,ten,core})/As_{l,ten} = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814
ft₂ = 441.538
fy₂ = 367.9484
su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 0.30

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*As_{l,com,jacket} + fs_{core}*As_{l,com,core})/As_{l,com} = 367.9484

with Es₂ = (Es_{jacket}*As_{l,com,jacket} + Es_{core}*As_{l,com,core})/As_{l,com} = 200000.00

y_v = 0.00140044
sh_v = 0.0044814
ft_v = 466.813
fy_v = 389.0108
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

suv = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$

with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$

1 = $Asl_{ten} / (b * d) * (fs1 / fc) = 0.088798$

2 = $Asl_{com} / (b * d) * (fs2 / fc) = 0.088798$

v = $Asl_{mid} / (b * d) * (fsv / fc) = 0.03319551$

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = $Asl_{ten} / (b * d) * (fs1 / fc) = 0.11405247$

2 = $Asl_{com} / (b * d) * (fs2 / fc) = 0.11405247$

v = $Asl_{mid} / (b * d) * (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

---->

v < vs_{y2} - LHS eq.(4.5) is satisfied

---->

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2+

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005

Mu = 1.7255E+008

with full section properties:

b = 400.00

d = 357.00

d' = 43.00

v = 0.00126831

N = 5976.808

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = shear_factor * Max(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

we ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + Min(fx, fy) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125

af = 0.57333333

b = 400.00

h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_{e} = 870.5244$

fy = 0.07683125

af = 0.57333333
b = 400.00
h = 400.00
From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508
bw = 400.00
effective stress from (A.35), ff,e = 870.5244

R = 40.00
Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288
ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00
From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30
su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247

2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247

v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

v < vs,y2 - LHS eq.(4.5) is satisfied

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005
Mu = 1.7255E+008

with full section properties:

b = 400.00
d = 357.00
d' = 43.00
v = 0.00126831
N = 5976.808
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{\min} * fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.09892348$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00
effective stress from (A.35), $ff_e = 870.5244$

fy = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00
effective stress from (A.35), $ff_e = 870.5244$

R = 40.00

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288

bo_1 = 340.00

ho_1 = 340.00

bi2_1 = 462400.00

ase2 = $\text{Max}(ase1, ase2) = 0.24250288$

bo_2 = 192.00

ho_2 = 192.00

bi2_2 = 147456.00

$psh_{\min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

$psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

Asec = 160000.00

s1 = 100.00

s2 = 250.00

fywe1 = 694.4444

fywe2 = 555.5556

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119

c = confinement factor = 1.13212

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 441.538

fy1 = 367.9484

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 441.538

fy2 = 367.9484

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

$$cc(5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.11405247$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11405247$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

$$su(4.9) = 0.19835408$$

$$Mu = MRc(4.14) = 1.7255E+008$$

$$u = su(4.1) = 1.7890363E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 633070.334$

Calculation of Shear Strength at edge 1, $V_{r1} = 633070.334$

$$V_{r1} = V_{CoI}((10.3), ASCE 41-17) = knl * V_{CoIO}$$

$$V_{CoIO} = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 29.75$, but $f'_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$Mu = 8.4878329E-012$$

$$Vu = 1.8468314E-031$$

$$d = 0.8 * h = 320.00$$

$$Nu = 5976.808$$

$$Ag = 160000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 279252.68$$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.5556$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 0.00$ is calculated for core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 444.4444$$

$$s = 250.00$$

V_{s2} is multiplied by $Col2 = 0.00$

$$s/d = 1.5625$$

$$V_f((11-3)-(11.4), ACI 440) = 188111.148$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 90.00$

$$V_f = \text{Min}(|V_f(45, 1)|, |V_f(-45, a1)|), \text{ with:}$$

$$\text{total thickness per orientation, } tf1 = NL * t / NoDir = 1.016$$

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 633070.334
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 29.75, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00
Mu = 8.4878329E-012
Vu = 1.8468314E-031
d = 0.8*h = 320.00
Nu = 5976.808
Ag = 160000.00
From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68
where:

Vs1 = 279252.68 is calculated for jacket, with:
d = 320.00
Av = 157079.633
fy = 555.5556
s = 100.00

Vs1 is multiplied by Col1 = 1.00
s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:
d = 160.00
Av = 100530.965
fy = 444.4444
s = 250.00

Vs2 is multiplied by Col2 = 0.00
s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148
f = 0.95, for fully-wrapped sections
wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) sin + cos is replaced with (cot + cota)sin which is more a generalised expression,
where is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(,), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, = 45° and = -45° to take into consideration the cyclic seismic loading.

orientation 1: 1 = b1 + 90° = 90.00

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:
total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $\epsilon_{fu} = 0.01$

Number of directions, $N_{oDir} = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $N_L = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = 3.2548216E-032$

EDGE -B-

Shear Force, $V_b = -3.2548216E-032$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 1137.257$
-Compression: $Asl,com = 1137.257$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 0.18171192$

Member Controlled by Flexure ($Ve/Vr < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 115036.425$

with

$Mpr1 = \text{Max}(Mu1+, Mu1-) = 1.7255E+008$

$Mu1+ = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu1- = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$Mpr2 = \text{Max}(Mu2+, Mu2-) = 1.7255E+008$

$Mu2+ = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu2- = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

we ((5.4c), TBDY) = $ase * sh, \text{min}(fywe/fce + \text{Min}(fx, fy)) = 0.09892348$

where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $ffe = 870.5244$

 $fy = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $ffe = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$fu,f = 1055.00$

$Ef = 64828.00$

$u,f = 0.015$

ase ((5.4d), TBDY) = $(ase1 * Aext + ase2 * Aint) / Asec = 0.24250288$

ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (fs_{jacket} \cdot A_{s1,com,jacket} + fs_{core} \cdot A_{s1,com,core}) / A_{s1,com} = 367.9484$

with $Es_2 = (Es_{jacket} \cdot A_{s1,com,jacket} + Es_{core} \cdot A_{s1,com,core}) / A_{s1,com} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.813$

$fy_v = 389.0108$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot A_{s,mid,jacket} + fs_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $Es_v = (Es_{jacket} \cdot A_{s,mid,jacket} + Es_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.088798$

$2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.088798$

$v = A_{s,mid} / (b \cdot d) \cdot (fsv / fc) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

$1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.11405247$

$2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.11405247$

$v = A_{s,mid} / (b \cdot d) \cdot (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

$Mu = MRc$ (4.14) = 1.7255E+008

$u = su$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_{,1} = 340.00$

$ho_{,1} = 340.00$

$bi_{2,1} = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_{,2} = 192.00$

$ho_{,2} = 192.00$

$bi_{2,2} = 147456.00$

$psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1 * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2 * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

$A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

c = confinement factor = 1.13212

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.538$

$f_{y1} = 367.9484$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{s_{u1,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u1,nominal}} = 0.08$,
 For calculation of $e_{s_{u1,nominal}}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{s_{y1}} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 367.9484$
 with $E_{s1} = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $f_{y2} = 367.9484$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{s_{u2,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u2,nominal}} = 0.08$,
 For calculation of $e_{s_{u2,nominal}}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{s_{y2}} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} * A_{s,com,jacket} + f_{s,core} * A_{s,com,core}) / A_{s,com} = 367.9484$
 with $E_{s2} = (E_{s,jacket} * A_{s,com,jacket} + E_{s,core} * A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $f_{y_v} = 389.0108$
 $s_{u_v} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u_v} = 0.4 * e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,
 considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY
 For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_v} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 389.0108$
 with $E_{s_v} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.088798$
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.088798$
 $v = A_{s,mid} / (b * d) * (f_{s_v} / f_c) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.11405247$
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.11405247$
 $v = A_{s,mid} / (b * d) * (f_{s_v} / f_c) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.19835408$
 $M_u = M_{Rc} (4.14) = 1.7255E+008$
 $u = s_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7890363E-005$$

$$\mu_{2+} = 1.7255E+008$$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$\alpha_{co} \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_{cu}: \mu_{cu}^* = \text{shear_factor} * \text{Max}(\mu_{cu}, \mu_{cc}) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_{cu} = 0.01608084$$

$$\mu_{we} \text{ ((5.4c), TBDY)} = \alpha_{se} * \text{sh}_{,min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$$

where $f = \alpha_f * \rho_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.07683125$$

$$\alpha_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } \rho_f = 2t_f/bw = 0.00508$$

$$bw = 400.00$$

$$\text{effective stress from (A.35), } f_{fe} = 870.5244$$

$$f_y = 0.07683125$$

$$\alpha_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } \rho_f = 2t_f/bw = 0.00508$$

$$bw = 400.00$$

$$\text{effective stress from (A.35), } f_{fe} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = NL * t * \text{Cos}(b1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$\mu_{f} = 0.015$$

$$\alpha_{se} \text{ ((5.4d), TBDY)} = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$\alpha_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,1} = 462400.00$$

$$\alpha_{se2} = \text{Max}(\alpha_{se1}, \alpha_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2} = 147456.00$$

$$\text{psh}_{,min} * F_{ywe} = \text{Min}(\text{psh}_{,x} * F_{ywe}, \text{psh}_{,y} * F_{ywe}) = 3.00633$$

$$\text{psh}_{,x} * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{psh}_2 * F_{ywe2} = 3.00633$$

$$\text{ps}_1 \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 \cdot h2 / s2) / Asec = 0.00050265$$

$$Ash2 = Astir_2 \cdot ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$psh_y \cdot Fywe = psh1 \cdot Fywe1 + ps2 \cdot Fywe2 = 3.00633$$

$$ps1 \text{ (external)} = (Ash1 \cdot h1 / s1) / Asec = 0.00392699$$

$$Ash1 = Astir_1 \cdot ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 \cdot h2 / s2) / Asec = 0.00050265$$

$$Ash2 = Astir_2 \cdot ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$Asec = 160000.00$$

$$s1 = 100.00$$

$$s2 = 250.00$$

$$fywe1 = 694.4444$$

$$fywe2 = 555.5556$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 441.538$$

$$fy1 = 367.9484$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$su1 = 0.4 \cdot esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_nominal = 0.08,$$

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs_jacket \cdot Asl, \text{ten, jacket} + fs_core \cdot Asl, \text{ten, core}) / Asl, \text{ten} = 367.9484$$

$$\text{with } Es1 = (Es_jacket \cdot Asl, \text{ten, jacket} + Es_core \cdot Asl, \text{ten, core}) / Asl, \text{ten} = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/lb, \text{min} = 0.30$$

$$su2 = 0.4 \cdot esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu2_nominal = 0.08,$$

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 \cdot (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs2 = (fs_jacket \cdot Asl, \text{com, jacket} + fs_core \cdot Asl, \text{com, core}) / Asl, \text{com} = 367.9484$$

$$\text{with } Es2 = (Es_jacket \cdot Asl, \text{com, jacket} + Es_core \cdot Asl, \text{com, core}) / Asl, \text{com} = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$suv = 0.4 \cdot esuv_nominal \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esuv_nominal = 0.08,$$

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of $\epsilon_{sv_nominal}$ and γ_v , η_v , f_{tv} , f_{yv} , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , η_1 , f_{t1} , f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $\epsilon_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 37.35991$

$cc (5A.5, TBDY) = 0.00332119$

$c = \text{confinement factor} = 1.13212$

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$\mu_u (4.9) = 0.19835408$

$M_u = M_{Rc} (4.14) = 1.7255E+008$

$u = \mu_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$cc (5A.5, TBDY) = 0.002$

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.01608084$

where μ_u ((5.4c), TBDY) = $a_s \cdot \eta_v \cdot f_{ywe} / f_{ce} + \text{Min}(\mu_{fx}, \mu_{fy}) = 0.09892348$

where $\mu_{fx} = a_s \cdot \eta_v \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $\mu_{fx} = 0.07683125$

$\mu_{fy} = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $\mu_{fy} = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$\mu_{fy} = 0.07683125$

$\mu_{fx} = 0.57333333$

$b = 400.00$

h = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.00508$
bw = 400.00
effective stress from (A.35), $ff,e = 870.5244$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $ase((5.4d), \text{TBDY}) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.24250288$
 $ase1 = 0.24250288$
 $bo_1 = 340.00$
 $ho_1 = 340.00$
 $bi2_1 = 462400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.24250288$
 $bo_2 = 192.00$
 $ho_2 = 192.00$
 $bi2_2 = 147456.00$
 $psh_{,min}*F_{ywe} = \text{Min}(psh_{,x}*F_{ywe}, psh_{,y}*F_{ywe}) = 3.00633$

$psh_{,x}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$psh_{,y}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 160000.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 694.4444$
 $f_{ywe2} = 555.5556$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$
 $su1 = 0.4*esu1_{nominal}((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket}*A_{sl,ten,jacket} + fs_{core}*A_{sl,ten,core})/A_{sl,ten} = 367.9484$

with $Es1 = (Es_{jacket}*A_{sl,ten,jacket} + Es_{core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and $y2$, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

$y1$, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv , shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

$y1$, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 37.35991$$

$$cc (5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.19835408$$

$$Mu = MRc (4.14) = 1.7255E+008$$

$$u = su (4.1) = 1.7890363E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 633070.334$

Calculation of Shear Strength at edge 1, $Vr1 = 633070.334$

$$Vr1 = VCoI ((10.3), ASCE 41-17) = knl*VCoIo$$

$$VCoIo = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.5556$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 444.4444$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,

where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a_1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 463788.751$

$b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{ColO}}$

$V_{\text{ColO}} = 633070.334$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, α)|), with:

total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 463788.751

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

External Height, H = 400.00

External Width, W = 400.00

Internal Height, H = 200.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $bi = 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

 Stepwise Properties

Bending Moment, $M = -1.3974459E-010$
 Shear Force, $V2 = 5699.261$
 Shear Force, $V3 = -1.1783778E-013$
 Axial Force, $F = -5974.527$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $As_{lt} = 0.00$
 -Compression: $As_{lc} = 2676.637$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten} = 1137.257$
 -Compression: $As_{l,com} = 1137.257$
 -Middle: $As_{l,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,jacket} = 829.3805$
 -Compression: $As_{l,com,jacket} = 829.3805$
 -Middle: $As_{l,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,core} = 307.8761$
 -Compression: $As_{l,com,core} = 307.8761$
 -Middle: $As_{l,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 16.80$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.03871933$
 $u = y + p = 0.04555215$

 - Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00355215$ ((4.29), Biskinis Phd))
 $M_y = 1.2106E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1500.00
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7040E+013$
 $factor = 0.30$
 $A_g = 160000.00$
 Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 29.75$
 $N = 5974.527$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 5.6801E+013$

 Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.7839606E-006$
 with $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109378$
 $A = 0.01888488$
 $B = 0.01064174$
 with $pt = 0.00680079$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.527$
 $b = 400.00$
 $" = 0.12044818$

$y_{comp} = 2.3130541E-005$
 with $f_c^* (12.3, (ACI 440)) = 34.65043$
 $f_c = 33.00$
 $f_l = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $A_g = 160000.00$
 From (12.9), ACI 440: $k_a = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $A_e/A_c = 0.56518315$
 Effective FRP thickness, $t_f = NL \cdot t \cdot \text{Cos}(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975145$
 $A = 0.0186534$
 $B = 0.01050082$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.042$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b/l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.18171192$

$d = d_{external} = 357.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00680079$

jacket: $s_1 = A_{v1} \cdot h_1 / (s_1 \cdot A_g) = 0.00392699$

$A_{v1} = 157.0796$, is the total area of all stirrups parallel to loading (shear) direction

$h_1 = 400.00$

$s_1 = 100.00$

core: $s_2 = A_{v2} \cdot h_2 / (s_2 \cdot A_g) = 0.00050265$

$A_{v2} = 100.531$, is the total area of all stirrups parallel to loading (shear) direction

$h_2 = 200.00$

$s_2 = 250.00$

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5974.527$

$A_g = 160000.00$

$f_c E = (f_{c,jacket} \cdot \text{Area}_{jacket} + f_{c,core} \cdot \text{Area}_{core}) / \text{section_area} = 29.75$

$f_y E = (f_{y,ext_Long_Reinf} \cdot \text{Area}_{ext_Long_Reinf} + f_{y,int_Long_Reinf} \cdot \text{Area}_{int_Long_Reinf}) / \text{Area}_{Tot_Long_Rein} = 529.9948$

$f_y E = (f_{y,ext_Trans_Reinf} \cdot \text{Area}_{ext_Trans_Reinf} + f_{y,int_Trans_Reinf} \cdot \text{Area}_{int_Trans_Reinf}) / \text{Area}_{Tot_Trans_Rein} =$

542.9472

$pl = \text{Area_Tot_Long_Rein}/(b*d) = 0.01874396$

$b = 400.00$

$d = 357.00$

$f_{cE} = 29.75$

End Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 15

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 400.00$
Concrete Elasticity, $E_c = 21019.039$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of γ for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE 41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE 41-17).
Jacket
New material: Concrete Strength, $f_c = f_{cm} = 33.00$
New material: Steel Strength, $f_s = f_{sm} = 555.5556$
Existing Column
Existing material: Concrete Strength, $f_c = f_{cm} = 20.00$
Existing material: Steel Strength, $f_s = f_{sm} = 444.4444$

External Height, $H = 400.00$
External Width, $W = 400.00$
Internal Height, $H = 200.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -2.1377975E-010$
Shear Force, $V_a = 1.1783778E-013$
EDGE -B-
Bending Moment, $M_b = -1.3974459E-010$
Shear Force, $V_b = -1.1783778E-013$
BOTH EDGES
Axial Force, $F = -5974.527$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 2676.637$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 1137.257$
-Compression: $As_{l,com} = 1137.257$
-Middle: $As_{l,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 16.80$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $VR = *V_n = 475023.398$
 $V_n ((10.3), ASCE 41-17) = knl * V_{ColO} = 558851.057$
 $V_{Col} = 558851.057$
 $knl = 1.00$

displacement_ductility_demand = 0.00

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 22.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.3974459E-010$

$\nu_u = 1.1783778E-013$

$d = 0.8 \cdot h = 320.00$

$N_u = 5974.527$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 251327.412$

where:

$V_{s1} = 251327.412$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 400.00$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot_a) \sin a$ which is more a generalised expression, where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a_i)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 405571.497$

$b_w = 400.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END B -

for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 1.3486692E-022$

$y = (M_y \cdot L_s / 3) / E_{\text{eff}} = 0.00355215$ ((4.29), Biskinis Phd)

$M_y = 1.2106E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00

From table 10.5, ASCE 41_17: $E_{\text{eff}} = \text{factor} \cdot E_c \cdot I_g = 1.7040E+013$

factor = 0.30

$A_g = 160000.00$

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$

$N = 5974.527$

$E_c \cdot I_g = E_c \cdot I_{g_{\text{jacket}}} + E_c \cdot I_{g_{\text{core}}} = 5.6801E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 5.7839606\text{E-}006$$

$$\text{with } ((10.1), \text{ASCE 41-17}) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/l_d)^{2/3}) = 296.8901$$

$$d = 357.00$$

$$y = 0.28109378$$

$$A = 0.01888488$$

$$B = 0.01064174$$

$$\text{with } p_t = 0.00796398$$

$$p_c = 0.00796398$$

$$p_v = 0.00281599$$

$$N = 5974.527$$

$$b = 400.00$$

$$" = 0.12044818$$

$$y_{\text{comp}} = 2.3130541\text{E-}005$$

$$\text{with } f_c^* (12.3, \text{ACI 440}) = 34.65043$$

$$f_c = 33.00$$

$$f_l = 0.93147527$$

$$b = 400.00$$

$$h = 400.00$$

$$A_g = 160000.00$$

$$\text{From } (12.9), \text{ACI 440: } k_a = 0.56518315$$

$$g = p_t + p_c + p_v = 0.01874396$$

$$r_c = 40.00$$

$$A_e/A_c = 0.56518315$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cdot \text{Cos}(\theta_1) = 1.016$$

$$\text{effective strain from } (12.5) \text{ and } (12.12), e_{fe} = 0.004$$

$$f_u = 0.01$$

$$E_f = 64828.00$$

$$E_c = 26999.444$$

$$y = 0.27975145$$

$$A = 0.0186534$$

$$B = 0.01050082$$

$$\text{with } E_s = 200000.00$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 16

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_u)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $bi: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -1.8468314E-031$

EDGE -B-

Shear Force, $V_b = 1.8468314E-031$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 1137.257$

-Compression: $As_{c,com} = 1137.257$

-Middle: $As_{mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.18171192$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 115036.425$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 1.7255E+008$

$Mu_{1+} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 1.7255E+008$

$Mu_{2+} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

ϕ_o (5A.5, TBDY) = 0.002

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $ase^* sh_{\min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = af^* pf^* f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $f_y = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL^*t^* \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase_1^* A_{ext} + ase_2^* A_{int}) / A_{sec} = 0.24250288$

$ase_1 = 0.24250288$

$bo_1 = 340.00$

$ho_1 = 340.00$

$bi_2_1 = 462400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.24250288$

$bo_2 = 192.00$

$ho_2 = 192.00$

$bi_2_2 = 147456.00$

$psh_{\min} * Fy_{we} = \text{Min}(psh_x^* Fy_{we}, psh_y^* Fy_{we}) = 3.00633$

 $psh_x^* Fy_{we} = psh_1^* Fy_{we1} + ps_2^* Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1^* h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1^* ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2^* h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2^* ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $psh_y^* Fy_{we} = psh_1^* Fy_{we1} + ps_2^* Fy_{we2} = 3.00633$

ps_1 (external) = $(Ash_1^* h_1 / s_1) / A_{sec} = 0.00392699$

$Ash_1 = Astir_1^* ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 400.00$

ps_2 (internal) = $(Ash_2^* h_2 / s_2) / A_{sec} = 0.00050265$

$Ash_2 = Astir_2^* ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$h_2 = 200.00$

 $A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$fy_{we1} = 694.4444$

$fy_{we2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00332119$

$c =$ confinement factor = 1.13212

$y_1 = 0.00140044$

$sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484$
 with $Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 441.538$
 $fy2 = 367.9484$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$
 with $Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.813$
 $fyv = 389.0108$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$
 with $Es_v = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.19835408$

$$\begin{aligned} \text{Mu} &= \text{MRc} (4.14) = 1.7255\text{E}+008 \\ u &= \text{su} (4.1) = 1.7890363\text{E}-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature κ_u according to 4.1, Biskinis/Fardis 2013:

$$\begin{aligned} u &= 1.7890363\text{E}-005 \\ \text{Mu} &= 1.7255\text{E}+008 \end{aligned}$$

with full section properties:

$$\begin{aligned} b &= 400.00 \\ d &= 357.00 \\ d' &= 43.00 \\ v &= 0.00126831 \\ N &= 5976.808 \\ f_c &= 33.00 \\ c_o (5A.5, \text{TBDY}) &= 0.002 \\ \text{Final value of } \kappa_u &: \kappa_u^* = \text{shear_factor} * \text{Max}(\kappa_u, \kappa_c) = 0.01608084 \\ \text{The Shear_factor is considered equal to 1 (pure moment strength)} \\ \text{From (5.4b), TBDY: } \kappa_u &= 0.01608084 \\ \kappa_{ue} ((5.4c), \text{TBDY}) &= a_{se} * \text{sh}_{, \text{min}} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348 \\ \text{where } f &= a_f * p_f * f_{fe} / f_{ce} \text{ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)} \end{aligned}$$

$$\begin{aligned} f_x &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} f_y &= 0.07683125 \\ a_f &= 0.57333333 \\ b &= 400.00 \\ h &= 400.00 \\ \text{From EC8 A.4.4.3(6), } p_f &= 2t_f/b_w = 0.00508 \\ b_w &= 400.00 \\ \text{effective stress from (A.35), } f_{f,e} &= 870.5244 \end{aligned}$$

$$\begin{aligned} R &= 40.00 \\ \text{Effective FRP thickness, } t_f &= NL * t * \text{Cos}(b_1) = 1.016 \\ f_{u,f} &= 1055.00 \\ E_f &= 64828.00 \\ u_{,f} &= 0.015 \\ a_{se} ((5.4d), \text{TBDY}) &= (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.24250288 \\ a_{se1} &= 0.24250288 \\ b_{o,1} &= 340.00 \\ h_{o,1} &= 340.00 \\ b_{i,1} &= 462400.00 \\ a_{se2} &= \text{Max}(a_{se1}, a_{se2}) = 0.24250288 \\ b_{o,2} &= 192.00 \\ h_{o,2} &= 192.00 \\ b_{i,2} &= 147456.00 \\ p_{sh, \text{min}} * F_{ywe} &= \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633 \end{aligned}$$

$$\begin{aligned} p_{sh,x} * F_{ywe} &= p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633 \\ p_{s1} (\text{external}) &= (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699 \\ A_{sh1} &= A_{stir,1} * n_{s,1} = 157.0796 \end{aligned}$$

No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 3.00633
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00392699
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00050265
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 160000.00
s₁ = 100.00
s₂ = 250.00
fywe₁ = 694.4444
fywe₂ = 555.5556
fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y₁ = 0.00140044
sh₁ = 0.0044814
ft₁ = 441.538
fy₁ = 367.9484
su₁ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

su₁ = 0.4*esu₁_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu₁_nominal = 0.08,

For calculation of esu₁_nominal and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*As_{l,ten,jacket} + fs_{core}*As_{l,ten,core})/As_{l,ten} = 367.9484

with Es₁ = (Es_{jacket}*As_{l,ten,jacket} + Es_{core}*As_{l,ten,core})/As_{l,ten} = 200000.00

y₂ = 0.00140044
sh₂ = 0.0044814
ft₂ = 441.538
fy₂ = 367.9484
su₂ = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 0.30

su₂ = 0.4*esu₂_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu₂_nominal = 0.08,

For calculation of esu₂_nominal and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*As_{l,com,jacket} + fs_{core}*As_{l,com,core})/As_{l,com} = 367.9484

with Es₂ = (Es_{jacket}*As_{l,com,jacket} + Es_{core}*As_{l,com,core})/As_{l,com} = 200000.00

y_v = 0.00140044
sh_v = 0.0044814
ft_v = 466.813
fy_v = 389.0108
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 389.0108$

with $Esv = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.088798$

$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.088798$

$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

$c =$ confinement factor = 1.13212

$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.11405247$

$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.11405247$

$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < vs_{y2}$ - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

$Mu = MRc$ (4.14) = 1.7255E+008

$u = su$ (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

where ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + Min(fx, fy) = 0.09892348$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$fy = 0.07683125$

af = 0.57333333
b = 400.00
h = 400.00
From EC8 A.4.4.3(6), pf = 2tf/bw = 0.00508
bw = 400.00
effective stress from (A.35), ff,e = 870.5244

R = 40.00
Effective FRP thickness, tf = NL*t*cos(b1) = 1.016
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.24250288
ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00
From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30
su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.813

fyv = 389.0108

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798

2 = Asl,com/(b*d)*(fs2/fc) = 0.088798

v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551

and confined core properties:

b = 340.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247

2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247

v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.19835408

Mu = MRc (4.14) = 1.7255E+008

u = su (4.1) = 1.7890363E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.7890363E-005
Mu = 1.7255E+008

with full section properties:

b = 400.00
d = 357.00
d' = 43.00
v = 0.00126831
N = 5976.808
fc = 33.00
co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

w_e ((5.4c), TBDY) = $ase * sh_{\min} * fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.09892348$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

fy = 0.07683125
af = 0.57333333
b = 400.00
h = 400.00

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

bw = 400.00

effective stress from (A.35), $ff_e = 870.5244$

R = 40.00

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.24250288$

ase1 = 0.24250288

bo_1 = 340.00

ho_1 = 340.00

bi2_1 = 462400.00

ase2 = $\text{Max}(ase1, ase2) = 0.24250288$

bo_2 = 192.00

ho_2 = 192.00

bi2_2 = 147456.00

$psh_{\min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 3.00633$

$psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

$psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 3.00633$
ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00392699$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00050265$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

$$h_2 = 200.00$$

$$A_{sec} = 160000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$f_{ywe1} = 694.4444$$

$$f_{ywe2} = 555.5556$$

$$f_{ce} = 33.00$$

$$\text{From } ((5.A.5), \text{ TBDY}), \text{ TBDY: } c_c = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 441.538$$

$$fy_1 = 367.9484$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_1_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_1_{nominal} = 0.08$,

For calculation of $esu_1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (f_{s,jacket} * A_{sl,ten,jacket} + f_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 367.9484$$

$$\text{with } Es_1 = (E_{s,jacket} * A_{sl,ten,jacket} + E_{s,core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.538$$

$$fy_2 = 367.9484$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu_2_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_2_{nominal} = 0.08$,

For calculation of $esu_2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 367.9484$$

$$\text{with } Es_2 = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.813$$

$$fy_v = 389.0108$$

$$su_v = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{ou,min} = l_b/l_d = 0.30$$

$$su_v = 0.4 * esuv_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (f_{s,jacket} * A_{sl,mid,jacket} + f_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 389.0108$$

$$\text{with } Es_v = (E_{s,jacket} * A_{sl,mid,jacket} + E_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.088798$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.088798$$

$$v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{ TBDY}) = 37.35991$$

$$cc(5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.11405247$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11405247$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture
' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.19835408$$

$$M_u = MR_c(4.14) = 1.7255E+008$$

$$u = s_u(4.1) = 1.7890363E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 633070.334$

Calculation of Shear Strength at edge 1, $V_{r1} = 633070.334$

$$V_{r1} = V_{CoI}((10.3), ASCE 41-17) = k_{nl} * V_{CoI0}$$

$$V_{CoI0} = 633070.334$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v * f_y * d / s$ ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 29.75$, but $f'_c^{0.5} \leq 8.3$
MPa (22.5.3.1, ACI 318-14)

$$M/Vd = 2.00$$

$$M_u = 8.4878329E-012$$

$$V_u = 1.8468314E-031$$

$$d = 0.8 * h = 320.00$$

$$N_u = 5976.808$$

$$A_g = 160000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 279252.68$$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.5556$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 0.00$ is calculated for core, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 444.4444$$

$$s = 250.00$$

V_{s2} is multiplied by $Col2 = 0.00$

$$s/d = 1.5625$$

$$V_f((11-3)-(11.4), ACI 440) = 188111.148$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot_a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 90.00$

$$V_f = \text{Min}(|V_f(45, 1)|, |V_f(-45, a1)|), \text{ with:}$$

$$\text{total thickness per orientation, } t_{f1} = NL * t / \text{NoDir} = 1.016$$

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

Calculation of Shear Strength at edge 2, Vr2 = 633070.334
Vr2 = VCol ((10.3), ASCE 41-17) = knl*VCol0
VCol0 = 633070.334
knl = 1 (zero step-static loading)

NOTE: In expression (10-3) 'Vs = Av*fy*d/s' is replaced by 'Vs+ f*VF'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 29.75, but fc'^0.5 <= 8.3
MPa (22.5.3.1, ACI 318-14)

M/Vd = 2.00
Mu = 8.4878329E-012
Vu = 1.8468314E-031
d = 0.8*h = 320.00
Nu = 5976.808
Ag = 160000.00
From (11.5.4.8), ACI 318-14: Vs = Vs1 + Vs2 = 279252.68
where:

Vs1 = 279252.68 is calculated for jacket, with:
d = 320.00
Av = 157079.633
fy = 555.5556
s = 100.00

Vs1 is multiplied by Col1 = 1.00
s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:
d = 160.00
Av = 100530.965
fy = 444.4444
s = 250.00

Vs2 is multiplied by Col2 = 0.00
s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148
f = 0.95, for fully-wrapped sections
wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) sin + cos is replaced with (cot + cota)sin which is more a generalised expression,
where is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(,), is implemented for every different fiber orientation ai,
as well as for 2 crack directions, = 45° and = -45° to take into consideration the cyclic seismic loading.

orientation 1: 1 = b1 + 90° = 90.00

Vf = Min(|Vf(45, 1)|, |Vf(-45,a1)|), with:
total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00
ffe ((11-5), ACI 440) = 259.312
Ef = 64828.00
fe = 0.004, from (11.6a), ACI 440
with fu = 0.01
From (11-11), ACI 440: Vs + Vf <= 463788.751
bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1

At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.4444$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 555.5556$

#####

External Height, $H = 400.00$

External Width, $W = 400.00$

Internal Height, $H = 200.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.13212

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = 3.2548216E-032$

EDGE -B-

Shear Force, $V_b = -3.2548216E-032$

BOTH EDGES

Axial Force, $F = -5976.808$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 2676.637$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 1137.257$
-Compression: $Asl,com = 1137.257$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 0.18171192$

Member Controlled by Flexure ($Ve/Vr < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 115036.425$

with

$Mpr1 = \text{Max}(Mu1+, Mu1-) = 1.7255E+008$

$Mu1+ = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu1- = 1.7255E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$Mpr2 = \text{Max}(Mu2+, Mu2-) = 1.7255E+008$

$Mu2+ = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu2- = 1.7255E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$fc = 33.00$

$co (5A.5, TBDY) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01608084$

$we ((5.4c), TBDY) = ase * sh, \text{min} * fywe / fce + \text{Min}(fx, fy) = 0.09892348$

where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $ffe = 870.5244$

 $fy = 0.07683125$

$af = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $ffe = 870.5244$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$fu, f = 1055.00$

$Ef = 64828.00$

$u, f = 0.015$

$ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.24250288$

ase1 = 0.24250288
bo_1 = 340.00
ho_1 = 340.00
bi2_1 = 462400.00
ase2 = Max(ase1,ase2) = 0.24250288
bo_2 = 192.00
ho_2 = 192.00
bi2_2 = 147456.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 3.00633

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 3.00633
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00392699
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00050265
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 160000.00
s1 = 100.00
s2 = 250.00
fywe1 = 694.4444
fywe2 = 555.5556
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00332119
c = confinement factor = 1.13212

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 441.538
fy1 = 367.9484
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 367.9484

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 441.538
fy2 = 367.9484
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (f_s \cdot \text{jacket} \cdot A_{s, \text{com, jacket}} + f_s \cdot \text{core} \cdot A_{s, \text{com, core}}) / A_{s, \text{com}} = 367.9484$

with $Es_2 = (E_s \cdot \text{jacket} \cdot A_{s, \text{com, jacket}} + E_s \cdot \text{core} \cdot A_{s, \text{com, core}}) / A_{s, \text{com}} = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.813$

$fy_v = 389.0108$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o, \text{min}} = l_b/l_d = 0.30$

$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,

considering characteristic value $fs_yv = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $esuv_{\text{nominal}}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fs_yv = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_s \cdot \text{jacket} \cdot A_{s, \text{mid, jacket}} + f_s \cdot \text{mid} \cdot A_{s, \text{mid, core}}) / A_{s, \text{mid}} = 389.0108$

with $E_{sv} = (E_s \cdot \text{jacket} \cdot A_{s, \text{mid, jacket}} + E_s \cdot \text{mid} \cdot A_{s, \text{mid, core}}) / A_{s, \text{mid}} = 200000.00$

$1 = A_{s, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$2 = A_{s, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$v = A_{s, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, \text{TBDY}) = 37.35991$

$cc (5A.5, \text{TBDY}) = 0.00332119$

$c = \text{confinement factor} = 1.13212$

$1 = A_{s, \text{ten}} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$2 = A_{s, \text{com}} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$v = A_{s, \text{mid}} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s, y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.19835408$

$Mu = MRc (4.14) = 1.7255E+008$

$u = su (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$Mu = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

$cc (5A.5, \text{TBDY}) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01608084$

w_e ((5.4c), TBDY) = $a_{se} \cdot \text{sh}_{\min} \cdot f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$

where $f = a_f \cdot p_f \cdot f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f / b_w = 0.00508$

$b_w = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$f_y = 0.07683125$

$a_f = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f / b_w = 0.00508$

$b_w = 400.00$

effective stress from (A.35), $f_{f,e} = 870.5244$

$R = 40.00$

Effective FRP thickness, $t_f = N_L \cdot t \cdot \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

a_{se} ((5.4d), TBDY) = $(a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.24250288$

$a_{se1} = 0.24250288$

$b_{o,1} = 340.00$

$h_{o,1} = 340.00$

$b_{i,1} = 462400.00$

$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.24250288$

$b_{o,2} = 192.00$

$h_{o,2} = 192.00$

$b_{i,2} = 147456.00$

$p_{sh,\min} \cdot F_{ywe} = \text{Min}(p_{sh,x} \cdot F_{ywe}, p_{sh,y} \cdot F_{ywe}) = 3.00633$

$p_{sh,x} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.00633$

p_{s1} (external) = $(A_{sh1} \cdot h_1 / s_1) / A_{sec} = 0.00392699$

$A_{sh1} = A_{stir,1} \cdot n_{s,1} = 157.0796$

No stirups, $n_{s,1} = 2.00$

$h_1 = 400.00$

p_{s2} (internal) = $(A_{sh2} \cdot h_2 / s_2) / A_{sec} = 0.00050265$

$A_{sh2} = A_{stir,2} \cdot n_{s,2} = 100.531$

No stirups, $n_{s,2} = 2.00$

$h_2 = 200.00$

$p_{sh,y} \cdot F_{ywe} = p_{sh1} \cdot F_{ywe1} + p_{sh2} \cdot F_{ywe2} = 3.00633$

p_{s1} (external) = $(A_{sh1} \cdot h_1 / s_1) / A_{sec} = 0.00392699$

$A_{sh1} = A_{stir,1} \cdot n_{s,1} = 157.0796$

No stirups, $n_{s,1} = 2.00$

$h_1 = 400.00$

p_{s2} (internal) = $(A_{sh2} \cdot h_2 / s_2) / A_{sec} = 0.00050265$

$A_{sh2} = A_{stir,2} \cdot n_{s,2} = 100.531$

No stirups, $n_{s,2} = 2.00$

$h_2 = 200.00$

$A_{sec} = 160000.00$

$s_1 = 100.00$

$s_2 = 250.00$

$f_{ywe1} = 694.4444$

$f_{ywe2} = 555.5556$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00332119$

c = confinement factor = 1.13212

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 441.538$

$f_{y1} = 367.9484$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,
 For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{s1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s1} = (f_{s,jacket} * A_{s1,ten,jacket} + f_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 367.9484$
 with $E_{s1} = (E_{s,jacket} * A_{s1,ten,jacket} + E_{s,core} * A_{s1,ten,core}) / A_{s1,ten} = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 441.538$
 $f_{y2} = 367.9484$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,
 For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 367.9484$
 with $E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.813$
 $f_{y_v} = 389.0108$
 $s_{u_v} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u_v} = 0.4 * e_{s_{u_v}}_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{s_{u_v}}_nominal = 0.08$,
 considering characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY
 For calculation of $e_{s_{u_v}}_nominal$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
 characteristic value $f_{s_{u_v}} = f_{s_{u_v}}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s_{u_v}} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 389.0108$
 with $E_{s_{u_v}} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.088798$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.088798$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.03319551$
 and confined core properties:
 $b = 340.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 37.35991$
 $cc (5A.5, TBDY) = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.11405247$
 $2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.11405247$
 $v = A_{s1,mid} / (b * d) * (f_{s_{u_v}} / f_c) = 0.04263644$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.19835408$
 $M_u = M_{Rc} (4.14) = 1.7255E+008$
 $u = s_u (4.1) = 1.7890363E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$\mu_u = 1.7890363E-005$$

$$\mu_{2+} = 1.7255E+008$$

with full section properties:

$$b = 400.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00126831$$

$$N = 5976.808$$

$$f_c = 33.00$$

$$\alpha_{co} \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_{cu}: \mu_{cu}^* = \text{shear_factor} * \text{Max}(\mu_{cu}, \mu_{cc}) = 0.01608084$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_{cu} = 0.01608084$$

$$\mu_{we} \text{ ((5.4c), TBDY)} = \alpha_{se} * \text{sh}_{,\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.09892348$$

where $f_x = \alpha_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.07683125$$

$$\alpha_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{fe} = 870.5244$$

$$f_y = 0.07683125$$

$$\alpha_f = 0.57333333$$

$$b = 400.00$$

$$h = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.00508$$

$$b_w = 400.00$$

$$\text{effective stress from (A.35), } f_{fe} = 870.5244$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$\alpha_{se} \text{ ((5.4d), TBDY)} = (\alpha_{se1} * A_{ext} + \alpha_{se2} * A_{int}) / A_{sec} = 0.24250288$$

$$\alpha_{se1} = 0.24250288$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 340.00$$

$$b_{i,1} = 462400.00$$

$$\alpha_{se2} = \text{Max}(\alpha_{se1}, \alpha_{se2}) = 0.24250288$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 192.00$$

$$b_{i,2} = 147456.00$$

$$p_{sh,\min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 3.00633$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 3.00633$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00392699$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$ps_2 \text{ (internal)} = (Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$$

$$Ash_2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h_2 = 200.00$$

$$psh_y * Fy_{we} = psh_1 * Fy_{we1} + ps_2 * Fy_{we2} = 3.00633$$

$$ps_1 \text{ (external)} = (Ash_1 * h_1 / s_1) / A_{sec} = 0.00392699$$

$$Ash_1 = Astir_1 * ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h_1 = 400.00$$

$$ps_2 \text{ (internal)} = (Ash_2 * h_2 / s_2) / A_{sec} = 0.00050265$$

$$Ash_2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 160000.00$$

$$s_1 = 100.00$$

$$s_2 = 250.00$$

$$fy_{we1} = 694.4444$$

$$fy_{we2} = 555.5556$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } cc = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 441.538$$

$$fy_1 = 367.9484$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 0.30$$

$$su_1 = 0.4 * esu_1 \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_1 \text{ nominal} = 0.08,$$

For calculation of $esu_1 \text{ nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1 / 1.2$, from table 5.1, TBDY.

$$y_1, sh_1, ft_1, fy_1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 367.9484$$

$$\text{with } Es_1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 441.538$$

$$fy_2 = 367.9484$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 0.30$$

$$su_2 = 0.4 * esu_2 \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_2 \text{ nominal} = 0.08,$$

For calculation of $esu_2 \text{ nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2 / 1.2$, from table 5.1, TBDY.

$$y_2, sh_2, ft_2, fy_2, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 367.9484$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.813$$

$$fy_v = 389.0108$$

$$su_v = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 0.30$$

$$su_v = 0.4 * esu_v \text{ nominal ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_v \text{ nominal} = 0.08,$$

considering characteristic value $fsy_v = fs_v / 1.2$, from table 5.1, TBDY

For calculation of $\epsilon_{sv_nominal}$ and γ_v , η_v , f_{tv} , f_{yv} , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , η_1 , f_{t1} , f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 389.0108$

with $\epsilon_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.088798$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.088798$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.03319551$

and confined core properties:

$b = 340.00$

$d = 327.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 37.35991

cc (5A.5, TBDY) = 0.00332119

c = confinement factor = 1.13212

$\gamma_1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11405247$

$\gamma_2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11405247$

$\eta_v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04263644$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

μ_u (4.9) = 0.19835408

$M_u = M_{Rc}$ (4.14) = 1.7255E+008

$u = \mu_u$ (4.1) = 1.7890363E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_u -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7890363E-005$

$M_u = 1.7255E+008$

with full section properties:

$b = 400.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00126831$

$N = 5976.808$

$f_c = 33.00$

cc (5A.5, TBDY) = 0.002

Final value of μ_u : $\mu_u^* = \text{shear_factor} \cdot \text{Max}(\mu_u, cc) = 0.01608084$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\mu_u = 0.01608084$

η_v ((5.4c), TBDY) = $\eta_v \cdot \text{Min}(f_x, f_y) = 0.09892348$

where $f = \eta_v \cdot \text{Min}(f_x, f_y)$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.07683125$

$\eta_v = 0.57333333$

$b = 400.00$

$h = 400.00$

From EC8 A.4.4.3(6), $\eta_v = 2t_f/bw = 0.00508$

$bw = 400.00$

effective stress from (A.35), $f_{fe} = 870.5244$

$f_y = 0.07683125$

$\eta_v = 0.57333333$

$b = 400.00$

h = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.00508$
bw = 400.00
effective stress from (A.35), $ff,e = 870.5244$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$
 $ase((5.4d), \text{TBDY}) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.24250288$
 $ase1 = 0.24250288$
 $bo_1 = 340.00$
 $ho_1 = 340.00$
 $bi2_1 = 462400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.24250288$
 $bo_2 = 192.00$
 $ho_2 = 192.00$
 $bi2_2 = 147456.00$
 $psh_{,min}*F_{ywe} = \text{Min}(psh_{,x}*F_{ywe}, psh_{,y}*F_{ywe}) = 3.00633$

$psh_{,x}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$psh_{,y}*F_{ywe} = psh1*F_{ywe1} + ps2*F_{ywe2} = 3.00633$
 $ps1(\text{external}) = (Ash1*h1/s1)/A_{sec} = 0.00392699$
 $Ash1 = Astir_1*ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2(\text{internal}) = (Ash2*h2/s2)/A_{sec} = 0.00050265$
 $Ash2 = Astir_2*ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 160000.00$
 $s1 = 100.00$
 $s2 = 250.00$
 $f_{ywe1} = 694.4444$
 $f_{ywe2} = 555.5556$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $cc = 0.00332119$
 $c = \text{confinement factor} = 1.13212$
 $y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 441.538$
 $fy1 = 367.9484$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$
 $su1 = 0.4*esu1_{nominal}((5.5), \text{TBDY}) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket}*A_{sl,ten,jacket} + fs_{core}*A_{sl,ten,core})/A_{sl,ten} = 367.9484$

with $Es1 = (Es_{jacket}*A_{sl,ten,jacket} + Es_{core}*A_{sl,ten,core})/A_{sl,ten} = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$

$$ft2 = 441.538$$

$$fy2 = 367.9484$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y_2 , sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y_1 , sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 367.9484$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.813$$

$$fyv = 389.0108$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 0.30$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and y_v , shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y_1 , sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 389.0108$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.088798$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.088798$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.03319551$$

and confined core properties:

$$b = 340.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 37.35991$$

$$cc (5A.5, TBDY) = 0.00332119$$

$$c = \text{confinement factor} = 1.13212$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.11405247$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.11405247$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04263644$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.19835408$$

$$Mu = MRc (4.14) = 1.7255E+008$$

$$u = su (4.1) = 1.7890363E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 633070.334$

Calculation of Shear Strength at edge 1, $V_{r1} = 633070.334$

$$V_{r1} = V_{CoI} ((10.3), ASCE 41-17) = knl*V_{CoI0}$$

$$V_{CoI0} = 633070.334$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

$V_{s1} = 279252.68$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.5556$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 444.4444$

$s = 250.00$

V_{s2} is multiplied by $\text{Col2} = 0.00$

$s/d = 1.5625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \csc) \sin \alpha$ which is more a generalised expression,

where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / N_{\text{Dir}} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 463788.751$

$b_w = 400.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 633070.334$

$V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} \cdot V_{\text{Col0}}$

$V_{\text{Col0}} = 633070.334$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' $V_s = A_v \cdot f_y \cdot d / s$ ' is replaced by ' $V_s + f \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 29.75$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$

$\mu_u = 1.4989884E-012$

$V_u = 3.2548216E-032$

$d = 0.8 \cdot h = 320.00$

$N_u = 5976.808$

$A_g = 160000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 279252.68$

where:

Vs1 = 279252.68 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 555.5556

s = 100.00

Vs1 is multiplied by Col1 = 1.00

s/d = 0.3125

Vs2 = 0.00 is calculated for core, with:

d = 160.00

Av = 100530.965

fy = 444.4444

s = 250.00

Vs2 is multiplied by Col2 = 0.00

s/d = 1.5625

Vf ((11-3)-(11.4), ACI 440) = 188111.148

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, α)|), with:

total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 463788.751

bw = 400.00

End Of Calculation of Shear Capacity ratio for element: column JC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjrs

Constant Properties

Knowledge Factor, $\gamma = 0.85$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 555.5556$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 20.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 444.4444$

Concrete Elasticity, $E_c = 21019.039$

Steel Elasticity, $E_s = 200000.00$

External Height, H = 400.00

External Width, W = 400.00

Internal Height, H = 200.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Element Length, L = 3000.00

Primary Member

Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $b_i = 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

 Stepwise Properties

 Bending Moment, $M = 0.05279463$
 Shear Force, $V_2 = 5699.261$
 Shear Force, $V_3 = -1.1783778E-013$
 Axial Force, $F = -5974.527$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $As_{lt} = 0.00$
 -Compression: $As_{lc} = 2676.637$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten} = 1137.257$
 -Compression: $As_{l,com} = 1137.257$
 -Middle: $As_{l,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,jacket} = 829.3805$
 -Compression: $As_{l,com,jacket} = 829.3805$
 -Middle: $As_{l,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $As_{l,ten,core} = 307.8761$
 -Compression: $As_{l,com,core} = 307.8761$
 -Middle: $As_{l,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 16.80$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.03630387$
 $u = y + p = 0.04271043$

 - Calculation of y -

 $y = (M_y * L_s / 3) / E_{eff} = 0.00071043$ ((4.29), Biskinis Phd)
 $M_y = 1.2106E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 300.00
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.7040E+013$
 $factor = 0.30$
 $A_g = 160000.00$
 Mean concrete strength: $fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 29.75$
 $N = 5974.527$
 $E_c * I_g = E_{c,jacket} * I_{g,jacket} + E_{c,core} * I_{g,core} = 5.6801E+013$

 Calculation of Yielding Moment M_y

 Calculation of y and M_y according to Annex 7 -

 $y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.7839606E-006$
 with $((10.1), ASCE 41-17) f_y = \text{Min}(f_y, 1.25 * f_y * (l_b / l_d)^{2/3}) = 296.8901$
 $d = 357.00$
 $y = 0.28109378$
 $A = 0.01888488$
 $B = 0.01064174$
 with $pt = 0.00680079$
 $pc = 0.00796398$
 $pv = 0.00281599$
 $N = 5974.527$
 $b = 400.00$
 $" = 0.12044818$

$y_{comp} = 2.3130541E-005$
 with $f_c^* (12.3, (ACI 440)) = 34.65043$
 $f_c = 33.00$
 $f_l = 0.93147527$
 $b = 400.00$
 $h = 400.00$
 $A_g = 160000.00$
 From (12.9), ACI 440: $k_a = 0.56518315$
 $g = pt + pc + pv = 0.01874396$
 $rc = 40.00$
 $A_e / A_c = 0.56518315$
 Effective FRP thickness, $t_f = NL * t * \text{Cos}(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.27975145$
 $A = 0.0186534$
 $B = 0.01050082$
 with $E_s = 200000.00$

 Calculation of ratio l_b / l_d

Inadequate Lap Length with $l_b / l_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.042$

with:

- Columns controlled by inadequate development or splicing along the clear height because $l_b / l_d < 1$

shear control ratio $V_y E / V_{col} O E = 0.18171192$

$d = d_{external} = 357.00$

$s = s_{external} = 0.00$

$t = s_1 + s_2 + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00680079$

jacket: $s_1 = A_{v1} * h_1 / (s_1 * A_g) = 0.00392699$

$A_{v1} = 157.0796$, is the total area of all stirrups parallel to loading (shear) direction

$h_1 = 400.00$

$s_1 = 100.00$

core: $s_2 = A_{v2} * h_2 / (s_2 * A_g) = 0.00050265$

$A_{v2} = 100.531$, is the total area of all stirrups parallel to loading (shear) direction

$h_2 = 200.00$

$s_2 = 250.00$

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

For the normalisation f_s of jacket is used.

$N_{UD} = 5974.527$

$A_g = 160000.00$

$f_c E = (f_{c,jacket} * \text{Area}_{jacket} + f_{c,core} * \text{Area}_{core}) / \text{section_area} = 29.75$

$f_y E = (f_{y,ext_Long_Reinf} * \text{Area}_{ext_Long_Reinf} + f_{y,int_Long_Reinf} * \text{Area}_{int_Long_Reinf}) / \text{Area}_{Tot_Long_Rein} = 529.9948$

$f_y E = (f_{y,ext_Trans_Reinf} * \text{Area}_{ext_Trans_Reinf} + f_{y,int_Trans_Reinf} * \text{Area}_{int_Trans_Reinf}) / \text{Area}_{Tot_Trans_Rein} =$

542.9472

$\rho_l = \text{Area_Tot_Long_Rein}/(b*d) = 0.01874396$

b = 400.00

d = 357.00

$f_{cE} = 29.75$

End Of Calculation of Chord Rotation Capacity for element: column JC1 of floor 1

At local axis: 3

Integration Section: (b)
