

Detailed Member Calculations

Units: N&mm

Regulation: ASCE 41-17

Calculation No. 1

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE41-17).

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $N_{oDir} = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $N_L = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -1.2956E+007$

Shear Force, $V_a = -4291.279$

EDGE -B-

Bending Moment, $M_b = 80283.485$

Shear Force, $V_b = 4291.279$

BOTH EDGES

Axial Force, $F = -6361.069$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl} = 0.00$

-Compression: $A_{slc} = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 2890.265$

-Compression: $A_{sl,com} = 829.3805$

-Middle: $A_{sl,mid} = 402.1239$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.18182$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 379285.941$

V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{CoI} = 379285.941$

$V_{CoI} = 379285.941$

$k_n = 1.00$

displacement_ductility_demand = 0.00913711

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_s + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 25.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1.2956E+007$
 $V_u = 4291.279$
 $d = 0.8 \cdot h = 480.00$
 $N_u = 6361.069$
 $A_g = 120000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 502654.825$
 where:
 $V_{s1} = 125663.706$ is calculated for section web, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.625$
 $V_{s2} = 376991.118$ is calculated for section flange, with:
 $d = 480.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.20833333$
 V_f ((11-3)-(11.4), ACI 440) = 293495.545
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = N_L \cdot t / N_{oDir} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 557.00
 f_{fe} ((11-5), ACI 440) = 259.312
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 318865.838$
 $b_w = 200.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END A -
 for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 0.00010359$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.01133749$ ((4.29), Biskinis Phd))
 $M_y = 4.5015E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 3019.222
 From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} \cdot E_c \cdot I_g = 3.9959E+013$
 $\text{factor} = 0.30$
 $A_g = 160000.00$
 $f_c' = 33.00$
 $N = 6361.069$
 $E_c \cdot I_g = 1.3320E+014$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 4.9172287E-006$
 with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (I_b / I_d)^{2/3}) = 311.2112$
 $d = 557.00$

y = 0.43186761
A = 0.03718321
B = 0.02864736
with pt = 0.02594493
pc = 0.00744507
pv = 0.00360973
N = 6361.069
b = 200.00
" = 0.07719928
y_comp = 9.2351909E-006
with fc* (12.3, (ACI 440)) = 33.28275
fc = 33.00
fl = 0.73070932
b = bmax = 600.00
h = hmax = 400.00
Ag = 160000.00
g = pt + pc + pv = 0.03699973
rc = 40.00
Ae/Ac = 0.27772029
Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016
effective strain from (12.5) and (12.12), efe = 0.004
fu = 0.01
Ef = 64828.00
Ec = 26999.444
y = 0.431356
A = 0.03687106
B = 0.02846388
with Es = 200000.00

Calculation of ratio lb/l_d

Inadequate Lap Length with lb/l_d = 0.30

End Of Calculation of Shear Capacity for element: column LC1 of floor 1
At local axis: 2
Integration Section: (a)

Calculation No. 2

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$

 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

 Max Height, $H_{max} = 400.00$
 Min Height, $H_{min} = 200.00$
 Max Width, $W_{max} = 600.00$
 Min Width, $W_{min} = 200.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.06029
 Element Length, $L = 3000.00$

Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, $NoDir = 1$
 Fiber orientations, $b_i: 0.00^\circ$
 Number of layers, $NL = 1$
 Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3
 EDGE -A-
 Shear Force, $V_a = -0.00026803$
 EDGE -B-
 Shear Force, $V_b = 0.00026803$

BOTH EDGES

Axial Force, $F = -6093.866$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{,ten} = 829.3805$

-Compression: $As_{,com} = 1746.726$

-Middle: $As_{,mid} = 1545.664$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.71033407$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 206445.557$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.0967E+008$

$Mu_{1+} = 1.8333E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 3.0967E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.0967E+008$

$Mu_{2+} = 1.8333E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 3.0967E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7539345E-005$

$M_u = 1.8333E+008$

with full section properties:

$b = 600.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0008621$

$N = 6093.866$

$f_c = 33.00$

$\phi_{co} (5A.5, \text{TB DY}) = 0.002$

Final value of ϕ_{cu} : $\phi_{cu}^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TB DY: $\phi_{cu} = 0.01306815$

where $\phi_{cu} (5.4c, \text{TB DY}) = a_s e^* \phi_{sh, \min} * f_{ywe} / f_{ce} + \text{Min}(\phi_{fx}, \phi_{fy}) = 0.05721847$

where $\phi_{fx} = a_f * \phi_{pf} * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$\phi_{fx} = 0.0528506$

Expression ((15B.6), TB DY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$

$b_{\max} = 600.00$

$h_{\max} = 400.00$

From EC8 A.4.4.3(6), $\phi_{pf} = 2t_f / b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{fe} = 768.6287$

$\phi_{fy} = 0.0528506$

Expression ((15B.6), TB DY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$

$b_{\max} = 600.00$

$h_{\max} = 400.00$

From EC8 A.4.3(6), $pf = 2tf/bw = 0.01016$
 $bw = 200.00$
effective stress from (A.35), $ff,e = 768.6287$

R = 40.00

Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$ase = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{,min} = \text{Min}(psh_{,x}, psh_{,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $psh_{,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$psh_{,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$psh_{,y} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

s = 100.00

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{\text{nominal}} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu1_{\text{nominal}} = 0.08$,

For calculation of $esu1_{\text{nominal}}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 466.8167$

$fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{\text{nominal}} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu2_{\text{nominal}} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2 , $sh_{2,ft2,fy2}$, it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1 , $sh_{1,ft1,fy1}$, are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$suv = 0.4 \cdot es_{u2_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{u2_nominal} = 0.08$,

considering characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , $sh_{1,ft1,fy1}$, are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{sv} = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.0456442$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.09612944$

$v = As_{l,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.08506418$

and confined core properties:

$b = 540.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.0553686$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.11660962$

$v = As_{l,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.10318693$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.18231057$

$Mu = MRc (4.14) = 1.8333E+008$

$u = su (4.1) = 1.7539345E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 2.4056447E-005$

$Mu = 3.0967E+008$

with full section properties:

$b = 200.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00258631$

$N = 6093.866$

$f_c = 33.00$

$co (5A.5, TBDY) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01306815$

where $fywe = \text{ase} * \text{sh}_{\min} * fywe / fce + \text{Min}(fx, fy) = 0.05721847$

where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$

$b_{\max} = 600.00$

$h_{\max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ffe = 768.6287$

 $fy = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$

$b_{\max} = 600.00$

$h_{\max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ffe = 768.6287$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$fu,f = 1055.00$

$Ef = 64828.00$

$u,f = 0.015$

$ase = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$psh_{\min} = \text{Min}(psh_x, psh_y) = 0.00471239$

Expression ((5.4d), TBDY) for psh_{\min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 psh_x ((5.4d), TBDY) = $L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 psh_y ((5.4d), TBDY) = $L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $s = 100.00$

$fywe = 694.45$

$fce = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s1} = f_s = 389.0139$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s2} = f_s = 389.0139$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$s_{u_v} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_{u_v} = 0.4 * e_{s_{u_v}_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_{u_v}_nominal} = 0.08$,

considering characteristic value $f_{s_{u_v}} = f_{s_v}/1.2$, from table 5.1, TBDY
For calculation of $e_{s_{u_v}_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $f_{s_{u_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s_v} = f_s = 389.0139$$

$$\text{with } E_{s_v} = E_s = 200000.00$$

$$1 = A_{s,ten}/(b*d) * (f_{s1}/f_c) = 0.28838833$$

$$2 = A_{s,com}/(b*d) * (f_{s2}/f_c) = 0.13693259$$

$$v = A_{s,mid}/(b*d) * (f_{s_v}/f_c) = 0.25519255$$

and confined core properties:

$$b = 140.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{s,ten}/(b*d) * (f_{s1}/f_c) = 0.44977996$$

$$2 = A_{s,com}/(b*d) * (f_{s2}/f_c) = 0.21356459$$

$$v = A_{s,mid}/(b*d) * (f_{s_v}/f_c) = 0.39800673$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.4038298$$

$$M_u = M_{Rc} (4.15) = 3.0967E+008$$

$$u = s_u (4.1) = 2.4056447E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7539345E-005$$

$$\mu_{2+} = 1.8333E+008$$

with full section properties:

$$b = 600.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0008621$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$\omega (5A.5, \text{TB DY}) = 0.002$$

$$\text{Final value of } \mu_{cu}^* = \text{shear_factor} * \text{Max}(\mu_{cu}, \omega) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TB DY: } \mu_{cu} = 0.01306815$$

$$\omega (5.4c, \text{TB DY}) = a_s e * s_{h, \min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TB DY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TB DY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length

equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00471239$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00471239$$

$$Lstir \text{ (Length of stirrups along Y)} = 1360.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$psh,y \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00667588$$

$$Lstir \text{ (Length of stirrups along X)} = 960.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$fywe = 694.45$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 466.8167$$

$$fy1 = 389.0139$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs1 = fs = 389.0139$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 466.8167$$

$$fy2 = 389.0139$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs2 = fs = 389.0139$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.8167$$

$$fyv = 389.0139$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$suv = 0.4 * esuv_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

with $E_{sv} = E_s = 200000.00$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0456442$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.09612944$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.08506418$$

and confined core properties:

$$b = 540.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0553686$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11660962$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10318693$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18231057$$

$$M_u = M_{Rc} (4.14) = 1.8333E+008$$

$$u = s_u (4.1) = 1.7539345E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of M_{u2}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 2.4056447E-005$$

$$M_u = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

hmax = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.01016$
bw = 200.00
effective stress from (A.35), $ff,e = 768.6287$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$

$ase = \text{Max}((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}} * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{,min} = \text{Min}(psh_x, psh_y) = 0.00471239$

Expression ((5.4d), TBDY) for $psh_{,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$psh_x \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$psh_y \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

s = 100.00

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{\text{nominal}} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu1_{\text{nominal}} = 0.08$,

For calculation of $esu1_{\text{nominal}}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 466.8167$

$fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{\text{nominal}} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.
 with $fs2 = fs = 389.0139$
 with $Es2 = Es = 200000.00$

$yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.8167$
 $fyv = 389.0139$
 $suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$
 and also multiplied by the $shear_factor$ according to 15.7.1.4, with
 $Shear_factor = 1.00$

$lo/lo_{u,min} = lb/ld = 0.30$
 $suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.
 with $fsv = fs = 389.0139$
 with $Es_v = Es = 200000.00$

$1 = Asl,ten/(b \cdot d) \cdot (fs1/fc) = 0.28838833$
 $2 = Asl,com/(b \cdot d) \cdot (fs2/fc) = 0.13693259$
 $v = Asl,mid/(b \cdot d) \cdot (fsv/fc) = 0.25519255$

and confined core properties:

$b = 140.00$
 $d = 327.00$
 $d' = 13.00$
 f_{cc} (5A.2, TBDY) = 34.98946
 cc (5A.5, TBDY) = 0.00260287
 $c =$ confinement factor = 1.06029
 $1 = Asl,ten/(b \cdot d) \cdot (fs1/fc) = 0.44977996$
 $2 = Asl,com/(b \cdot d) \cdot (fs2/fc) = 0.21356459$
 $v = Asl,mid/(b \cdot d) \cdot (fsv/fc) = 0.39800673$

Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->
 su (4.8) = 0.4038298
 $Mu = MRc$ (4.15) = 3.0967E+008
 $u = su$ (4.1) = 2.4056447E-005

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of Shear Strength $Vr = Min(Vr1, Vr2) = 290631.642$

Calculation of Shear Strength at edge 1, $Vr1 = 290631.642$

$Vr1 = V_{Col}$ ((10.3), ASCE 41-17) = $knl \cdot V_{Col0}$
 $V_{Col0} = 290631.642$
 $knl = 1$ (zero step-static loading)

 NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)
 $fc' = 33.00$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 11.70883$
 $V_u = 0.00026803$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.625$
 $V_f ((11-3)-(11.4), ACI 440) = 188111.148$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = NL \cdot t / N_{oDir} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 357.00
 $f_{fe} ((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 244232.638$
 $b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 290631.642$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$
 $V_{Col0} = 290631.642$
 $k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$\lambda = 1$ (normal-weight concrete)
 $f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 11.914$
 $V_u = 0.00026803$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:

d = 160.00
 Av = 157079.633
 fy = 555.56
 s = 100.00
 Vs2 is multiplied by Col2 = 1.00
 s/d = 0.625
 Vf ((11-3)-(11.4), ACI 440) = 188111.148
 f = 0.95, for fully-wrapped sections
 wf/sf = 1 (FRP strips adjacent to one another).
 In (11.3) $\sin^2 + \cos^2$ is replaced with $(\cot^2 + \csc^2)\sin^2\alpha$ which is more a generalised expression,
 where α is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function Vf(α), is implemented for every different fiber orientation ai,
 as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\alpha_1 = \alpha_1 + 90^\circ = 90.00$
 Vf = Min(|Vf(45, 1)|, |Vf(-45, a1)|), with:
 total thickness per orientation, tf1 = NL*t/NoDir = 1.016
 dfv = d (figure 11.2, ACI 440) = 357.00
 ffe ((11-5), ACI 440) = 259.312
 Ef = 64828.00
 fe = 0.004, from (11.6a), ACI 440
 with fu = 0.01
 From (11-11), ACI 440: Vs + Vf <= 244232.638
 bw = 200.00

 End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At local axis: 3

 Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rclcs

Constant Properties

 Knowledge Factor, $\gamma = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 New material of Secondary Member: Concrete Strength, fc = fcm = 33.00
 New material of Secondary Member: Steel Strength, fs = fsm = 555.56
 Concrete Elasticity, Ec = 26999.444
 Steel Elasticity, Es = 200000.00
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 New material: Steel Strength, fs = 1.25*fsm = 694.45
 #####
 Max Height, Hmax = 400.00
 Min Height, Hmin = 200.00
 Max Width, Wmax = 600.00
 Min Width, Wmin = 200.00
 Cover Thickness, c = 25.00
 Mean Confinement Factor overall section = 1.06029
 Element Length, L = 3000.00
 Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with lo/lou,min = 0.30
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, t = 1.016

Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi = 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 0.00069415$
EDGE -B-
Shear Force, $V_b = -0.00069415$
BOTH EDGES
Axial Force, $F = -6093.866$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_{lt} = 0.00$
-Compression: $As_{lc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 2890.265$
-Compression: $As_{l,com} = 829.3805$
-Middle: $As_{l,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.00732$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 438835.425$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 6.5825E+008$
 $Mu_{1+} = 6.5825E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu_{1-} = 2.1740E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 6.5825E+008$
 $Mu_{2+} = 6.5825E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu_{2-} = 2.1740E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.4829616E-005$
 $M_u = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $f_c = 33.00$
 ϕ_o (5A.5, TBDY) = 0.002
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_o) = 0.01306815$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.01306815$
 ϕ_{we} ((5.4c), TBDY) = $ase * sh_{,min} * f_{ywe}/f_{ce} + \text{Min}(\phi_x, \phi_y) = 0.05721847$
where $f = af * pf * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$R = 40.00$$

Effective FRP thickness, $t_f = N_L * t * \cos(\beta_1) = 1.016$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 466.8167$

$fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou, min = lb/lb, min = 0.30$

$su2 = 0.4 \cdot esu2_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs2 = fs = 389.0139$

with $Es2 = Es = 200000.00$

$yv = 0.00140044$

$shv = 0.0044814$

$ftv = 466.8167$

$fyv = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou, min = lb/ld = 0.30$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fsv = fs = 389.0139$

with $Esv = Es = 200000.00$

$1 = Asl, ten / (b \cdot d) \cdot (fs1 / fc) = 0.30584665$

$2 = Asl, com / (b \cdot d) \cdot (fs2 / fc) = 0.08776469$

$v = Asl, mid / (b \cdot d) \cdot (fsv / fc) = 0.04255258$

and confined core properties:

$b = 140.00$

$d = 527.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

$1 = Asl, ten / (b \cdot d) \cdot (fs1 / fc) = 0.46179611$

$2 = Asl, com / (b \cdot d) \cdot (fs2 / fc) = 0.13251541$

$v = Asl, mid / (b \cdot d) \cdot (fsv / fc) = 0.06424989$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs, y2$ - LHS eq.(4.5) is not satisfied

$v < vs, c$ - RHS eq.(4.5) is satisfied

$su (4.8) = 0.38015251$

$Mu = MRc (4.15) = 6.5825E+008$

$u = su (4.1) = 1.4829616E-005$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0664224E-005$$

$$Mu = 2.1740E+008$$

with full section properties:

$$b = 400.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00082883$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_s e * s_{h,\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f,f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = Lstir*Astir/(Asec*s) = 0.00667588
Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00
fywe = 694.45
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287
c = confinement factor = 1.06029

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 466.8167
fy1 = 389.0139
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 466.8167
fy2 = 389.0139
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04388235

2 = Asl,com/(b*d)*(fs2/fc) = 0.15292333

v = Asl,mid/(b*d)*(fsv/fc) = 0.02127629

and confined core properties:

b = 340.00

$d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05456517$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.19015134$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.02645584$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.13804321$
 $Mu = MRc (4.14) = 2.1740E+008$
 $u = su (4.1) = 1.0664224E-005$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_{2+}

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
 $u = 1.4829616E-005$
 $Mu = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.01306815$
 $w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
 where $f = a_{pf} * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $pf = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $f_y = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $pf = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $R = 40.00$

Effective FRP thickness, $t_f = NL * t * \cos(b_1) = 1.016$

$f_u, f = 1055.00$

$E_f = 64828.00$

$u, f = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh,min = \text{Min}(psh,x, psh,y) = 0.00471239$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

psh,y ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^2/3), from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665

2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469

v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258

and confined core properties:

b = 140.00

d = 527.00

d' = 13.00

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

1 = Asl,ten/(b*d)*(fs1/fc) = 0.46179611

2 = Asl,com/(b*d)*(fs2/fc) = 0.13251541

v = Asl,mid/(b*d)*(fsv/fc) = 0.06424989

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

v < vs,y2 - LHS eq.(4.5) is not satisfied

v < vs,c - RHS eq.(4.5) is satisfied

su (4.8) = 0.38015251

Mu = MRc (4.15) = 6.5825E+008

u = su (4.1) = 1.4829616E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0664224E-005

Mu = 2.1740E+008

with full section properties:

b = 400.00

d = 557.00

d' = 43.00

v = 0.00082883

N = 6093.866

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu* = shear_factor * Max(cu, cc) = 0.01306815

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01306815

w_e ((5.4c), TBDY) = $a_{se} \cdot s_{h,min} \cdot f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
where $f = a_f \cdot p_f \cdot f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.0528506$
Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
effective stress from (A.35), $f_{f,e} = 768.6287$

$f_y = 0.0528506$
Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
effective stress from (A.35), $f_{f,e} = 768.6287$

$R = 40.00$
Effective FRP thickness, $t_f = N_L \cdot t \cdot \text{Cos}(b_1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{f} = 0.015$
 $a_{se} = \text{Max}(((A_{conf,max} - A_{noConf})/A_{conf,max}) \cdot (A_{conf,min}/A_{conf,max}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.
 $A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.
 $A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).
 $p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$
Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir}/(A_{sec} \cdot s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir}/(A_{sec} \cdot s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$s = 100.00$
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $y_1 = 0.00140044$
 $sh_1 = 0.0044814$
 $ft_1 = 466.8167$
 $fy_1 = 389.0139$
 $su_1 = 0.00512$
using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s1} = f_s = 389.0139$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s2} = f_s = 389.0139$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$s_{u,v} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_{u,v} = 0.4 * e_{s_{u,v}_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_{u,v}_nominal} = 0.08$,

considering characteristic value $f_{s_{y,v}} = f_{s_{v}}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u,v}_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $f_{s_{y,v}} = f_{s_{v}}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s_{v}} = f_s = 389.0139$$

$$\text{with } E_{s_{v}} = E_s = 200000.00$$

$$1 = A_{s1,ten}/(b*d) * (f_{s1}/f_c) = 0.04388235$$

$$2 = A_{s1,com}/(b*d) * (f_{s2}/f_c) = 0.15292333$$

$$v = A_{s1,mid}/(b*d) * (f_{s_{v}}/f_c) = 0.02127629$$

and confined core properties:

$$b = 340.00$$

$$d = 527.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{s1,ten}/(b*d) * (f_{s1}/f_c) = 0.05456517$$

$$2 = A_{s1,com}/(b*d) * (f_{s2}/f_c) = 0.19015134$$

$$v = A_{s1,mid}/(b*d) * (f_{s_{v}}/f_c) = 0.02645584$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

$$s_u (4.9) = 0.13804321$$

$$\mu = M_{Rc} (4.14) = 2.1740E+008$$

$$u = s_u (4.1) = 1.0664224E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 435646.093$

Calculation of Shear Strength at edge 1, $V_{r1} = 435646.093$

$V_{r1} = V_{Col} ((10.3), \text{ASCE } 41-17) = knl * V_{Col0}$

$V_{Col0} = 435646.093$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

$fc' = 33.00$, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 44.9328$

$V_u = 0.00069415$

$d = 0.8 * h = 480.00$

$N_u = 6093.866$

$A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.625$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.20833333$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 293495.545$

$f = 0.95$, for fully-wrapped sections

$wf/sf = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,

where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = NL * t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

$f_{fe} ((11-5), \text{ACI } 440) = 259.312$

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 366348.956$

$b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 435646.093$

$V_{r2} = V_{Col} ((10.3), \text{ASCE } 41-17) = knl * V_{Col0}$

$V_{Col0} = 435646.093$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

$fc' = 33.00$, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 44.60048$
 $\nu_u = 0.00069415$
 $d = 0.8 \cdot h = 480.00$
 $Nu = 6093.866$
 $Ag = 120000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$
 where:
 $V_{s1} = 139627.457$ is calculated for section web, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.625$
 $V_{s2} = 418882.372$ is calculated for section flange, with:
 $d = 480.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.20833333$
 $V_f ((11-3)-(11.4), ACI 440) = 293495.545$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = NL \cdot t / NoDir = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 557.00
 $f_{fe} ((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 366348.956$
 $b_w = 200.00$

 End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At local axis: 2

 Start Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1
 At local axis: 2
 Integration Section: (a)
 Section Type: rclcs

Constant Properties

 Knowledge Factor, $\phi = 1.00$
 Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE41-17.
 Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
 Consequently:
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$
 Max Height, $H_{max} = 400.00$
 Min Height, $H_{min} = 200.00$
 Max Width, $W_{max} = 600.00$
 Min Width, $W_{min} = 200.00$
 Cover Thickness, $c = 25.00$

Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, t = 1.016
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, NoDir = 1
Fiber orientations, $b_i = 0.00^\circ$
Number of layers, NL = 1
Radius of rounding corners, R = 40.00

Stepwise Properties

Bending Moment, M = -160913.077
Shear Force, V2 = -4291.279
Shear Force, V3 = 77.5414
Axial Force, F = -6361.069
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 829.3805$
-Compression: $A_{sc,com} = 1746.726$
-Middle: $A_{st,mid} = 1545.664$
Mean Diameter of Tension Reinforcement, $D_{bL} = 18.66667$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.00655562$
 $u = y + p = 0.00655562$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00655562$ ((4.29), Biskinis Phd))
 $M_y = 1.3306E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 2075.189
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.4040E+013$
factor = 0.30
 $A_g = 160000.00$
 $f_c' = 33.00$
 $N = 6361.069$
 $E_c * I_g = 4.6799E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:
flange width, b = 600.00
web width, $b_w = 200.00$
flange thickness, t = 200.00

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 5.8026993E-006$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 311.2112$

$d = 357.00$

$y = 0.24884964$

$A = 0.01933805$

$B = 0.00899219$

with $pt = 0.00387199$

$pc = 0.00815465$

$pv = 0.00721598$

$N = 6361.069$

$b = 600.00$

$" = 0.12044818$

$y_{comp} = 2.5091791E-005$

with $f_c^* (12.3, (ACI 440)) = 33.29607$

$f_c = 33.00$

$fl = 0.73070932$

$b = b_{max} = 600.00$

$h = h_{max} = 400.00$

$Ag = 160000.00$

$g = pt + pc + pv = 0.01924262$

$rc = 40.00$

$Ae/Ac = 0.29079753$

Effective FRP thickness, $tf = NL \cdot t \cdot \text{Cos}(b1) = 1.016$

effective strain from (12.5) and (12.12), $e_{fe} = 0.004$

$f_u = 0.01$

$E_f = 64828.00$

$E_c = 26999.444$

$y = 0.24780539$

$A = 0.01917573$

$B = 0.00889677$

with $E_s = 200000.00$

CONFIRMATION: $y = 0.24825313 < t/d$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/d \geq 1$
shear control ratio $V_y E / V_{col} E = 0.71033407$

$d = 357.00$

$s = 0.00$

$t = A_v / (b_w \cdot s) + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = A_v \cdot L_{stir} / (A_g \cdot s) + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00$

$A_v = 78.53982$, is the area of every stirrup

$L_{stir} = 960.00$, is the total Length of all stirrups parallel to loading (shear) direction

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$NUD = 6361.069$

$Ag = 160000.00$

$f_{cE} = 33.00$

$f_{tE} = f_{yE} = 0.00$

$pl = \text{Area_Tot_Long_Rein} / (b \cdot d) = 0.01924262$

$b = 600.00$

$d = 357.00$

$f_{cE} = 33.00$

End Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 3

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rdcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE41-17).

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, t = 1.016
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, NoDir = 1
Fiber orientations, $b_i: 0.00^\circ$
Number of layers, NL = 1
Radius of rounding corners, R = 40.00

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -160913.077$
Shear Force, $V_a = 77.5414$
EDGE -B-
Bending Moment, $M_b = -70821.725$
Shear Force, $V_b = -77.5414$
BOTH EDGES
Axial Force, F = -6361.069
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 0.00$
-Compression: $A_{sl,c} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 829.3805$
-Compression: $A_{sl,com} = 1746.726$
-Middle: $A_{sl,mid} = 1545.664$
Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 18.66667$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 253066.566$
 V_n ((10.3), ASCE 41-17) = $k_n l \cdot V_{CoIO} = 253066.566$
 $V_{CoI} = 253066.566$
 $k_n l = 1.00$
displacement_ductility_demand = 0.00633935

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+ f \cdot V_f}$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 $f_c' = 25.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $M_u = 160913.077$
 $V_u = 77.5414$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6361.069$
 $A_g = 80000.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 376991.118$
where:
 $V_{s1} = 251327.412$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

Vs2 = 125663.706 is calculated for section flange, with:

$$d = 160.00$$

$$Av = 157079.633$$

$$fy = 500.00$$

$$s = 100.00$$

Vs2 is multiplied by Col2 = 1.00

$$s/d = 0.625$$

Vf ((11-3)-(11.4), ACI 440) = 188111.148

$$f = 0.95, \text{ for fully-wrapped sections}$$

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a)\sin a$ which is more a generalised expression, where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(θ), is implemented for every different fiber orientation ai, as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, a1)|), with:

total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 357.00

ffe ((11-5), ACI 440) = 259.312

$$Ef = 64828.00$$

$$fe = 0.004, \text{ from (11.6a), ACI 440}$$

$$\text{with } fu = 0.01$$

From (11-11), ACI 440: Vs + Vf <= 212577.225

$$bw = 200.00$$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 4.1558319E-005$

$$y = (My * Ls / 3) / Eleff = 0.00655562 \text{ ((4.29), Biskinis Phd)}$$

$$My = 1.3306E+008$$

$$Ls = M/V \text{ (with } Ls > 0.1 * L \text{ and } Ls < 2 * L) = 2075.189$$

From table 10.5, ASCE 41_17: Eleff = factor * Ec * Ig = 1.4040E+013

$$\text{factor} = 0.30$$

$$Ag = 160000.00$$

$$fc' = 33.00$$

$$N = 6361.069$$

$$Ec * Ig = 4.6799E+013$$

Calculation of Yielding Moment My

Calculation of δ / y and My according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, b = 600.00

web width, bw = 200.00

flange thickness, t = 200.00

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 5.8026993E-006$$

$$\text{with ((10.1), ASCE 41-17) } fy = \text{Min}(fy, 1.25 * fy * (lb/d)^{2/3}) = 311.2112$$

$$d = 357.00$$

$$y = 0.24884964$$

$$A = 0.01933805$$

$$B = 0.00899219$$

$$\text{with } pt = 0.00387199$$

$$pc = 0.00815465$$

$$pv = 0.00721598$$

$$N = 6361.069$$

$$b = 600.00$$

" = 0.12044818
y_comp = 2.5091791E-005
with f_c^* (12.3, (ACI 440)) = 33.29607
fc = 33.00
fl = 0.73070932
b = bmax = 600.00
h = hmax = 400.00
Ag = 160000.00
g = pt + pc + pv = 0.01924262
rc = 40.00
Ae/Ac = 0.29079753
Effective FRP thickness, $t_f = NL \cdot t \cdot \cos(b1) = 1.016$
effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
fu = 0.01
Ef = 64828.00
Ec = 26999.444
y = 0.24780539
A = 0.01917573
B = 0.00889677
with Es = 200000.00
CONFIRMATION: $y = 0.24825313 < t/d$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column LC1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 4

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rclcs

Constant Properties

Knowledge Factor, $= 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.06029

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -0.00026803$

EDGE -B-

Shear Force, $V_b = 0.00026803$

BOTH EDGES

Axial Force, $F = -6093.866$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{,ten} = 829.3805$

-Compression: $As_{,com} = 1746.726$

-Middle: $As_{,mid} = 1545.664$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.71033407$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 206445.557$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.0967E+008$

$Mu_{1+} = 1.8333E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 3.0967E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.0967E+008$

$Mu_{2+} = 1.8333E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 3.0967E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7539345E-005$

$M_u = 1.8333E+008$

with full section properties:

$b = 600.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0008621$

$N = 6093.866$

$f_c = 33.00$

$\phi_{co} (5A.5, TBDY) = 0.002$

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_{co}) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.01306815$

where $\phi_u (5.4c, TBDY) = a_s e^* \phi_{sh, \min} * f_{ywe} / f_{ce} + \text{Min}(\phi_x, \phi_y) = 0.05721847$

where $\phi = a_f * \phi_{pf} * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$\phi_x = 0.0528506$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$

$b_{\max} = 600.00$

$h_{\max} = 400.00$

From EC8 A.4.4.3(6), $\phi_{pf} = 2t_f / b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{fe} = 768.6287$

$\phi_y = 0.0528506$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$

$b_{\max} = 600.00$

$h_{\max} = 400.00$

From EC8 A.4.3(6), $pf = 2t_f/bw = 0.01016$
 $bw = 200.00$
effective stress from (A.35), $ff_e = 768.6287$

R = 40.00

Effective FRP thickness, $t_f = NL \cdot t \cdot \cos(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{f} = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) \cdot (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} = \text{Min}(psh_x, psh_y) = 0.00471239$

Expression ((5.4d), TBDY) for psh_{min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh_x ((5.4d), TBDY) = $L_{stir} \cdot A_{stir} / (A_{sec} \cdot s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

psh_y ((5.4d), TBDY) = $L_{stir} \cdot A_{stir} / (A_{sec} \cdot s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

s = 100.00

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 \cdot esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 \cdot esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$s_{uv} = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$s_{uv} = 0.4 \cdot es_{uv_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{uv_nominal} = 0.08$,

considering characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{sv} = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.0456442$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.09612944$

$v = As_{l,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.08506418$

and confined core properties:

$b = 540.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.0553686$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.11660962$

$v = As_{l,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.10318693$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$s_u (4.9) = 0.18231057$

$\mu_u = MR_c (4.14) = 1.8333E+008$

$u = s_u (4.1) = 1.7539345E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u1} -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 2.4056447E-005$

$\mu_u = 3.0967E+008$

with full section properties:

$b = 200.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00258631$

$N = 6093.866$

$f_c = 33.00$

$cc (5A.5, TBDY) = 0.002$

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01306815$

v_e ((5.4c), TBDY) = $ase * sh_{min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ff_e = 768.6287$

 $f_y = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ff_e = 768.6287$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$psh_{min} = \text{Min}(psh_x, psh_y) = 0.00471239$

Expression ((5.4d), TBDY) for psh_{min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 psh_x ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 psh_y ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $f_{s1} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s1} = f_s = 389.0139$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $f_{s2} = f_s/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s2} = f_s = 389.0139$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$s_{u,v} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_{u,v} = 0.4 * e_{s_{u,v}_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_{u,v}_nominal} = 0.08$,

considering characteristic value $f_{s_{u,v}} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{s_{u,v}_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $f_{s_{u,v}} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s_{u,v}} = f_{sv} = 389.0139$$

$$\text{with } E_{s_{u,v}} = E_s = 200000.00$$

$$1 = A_{s,ten}/(b*d) * (f_{s1}/f_c) = 0.28838833$$

$$2 = A_{s,com}/(b*d) * (f_{s2}/f_c) = 0.13693259$$

$$v = A_{s,mid}/(b*d) * (f_{sv}/f_c) = 0.25519255$$

and confined core properties:

$$b = 140.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{s,ten}/(b*d) * (f_{s1}/f_c) = 0.44977996$$

$$2 = A_{s,com}/(b*d) * (f_{s2}/f_c) = 0.21356459$$

$$v = A_{s,mid}/(b*d) * (f_{sv}/f_c) = 0.39800673$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.4038298$$

$$M_u = M_{Rc} (4.15) = 3.0967E+008$$

$$u = s_u (4.1) = 2.4056447E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7539345E-005$$

$$\mu_{2+} = 1.8333E+008$$

with full section properties:

$$b = 600.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0008621$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_{cu}^* = \text{shear_factor} * \text{Max}(\mu_{cu}, \mu_{cc}) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_{cu} = 0.01306815$$

$$\mu_{we} \text{ ((5.4c), TBDY)} = a_{se} * s_{h,min} * f_{ywe} / f_{ce} + \text{Min}(\mu_{fx}, \mu_{fy}) = 0.05721847$$

where $\mu_f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$\mu_{fx} = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$\mu_{fy} = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$\mu_{u,f} = 0.015$$

$$a_{se} = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length

equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00471239$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00471239$$

$$Lstir \text{ (Length of stirrups along Y)} = 1360.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$psh,y \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00667588$$

$$Lstir \text{ (Length of stirrups along X)} = 960.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$fywe = 694.45$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 466.8167$$

$$fy1 = 389.0139$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs1 = fs = 389.0139$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 466.8167$$

$$fy2 = 389.0139$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs2 = fs = 389.0139$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.8167$$

$$fyv = 389.0139$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$suv = 0.4 * esuv_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

with $E_{sv} = E_s = 200000.00$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0456442$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.09612944$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.08506418$$

and confined core properties:

$$b = 540.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0553686$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11660962$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10318693$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18231057$$

$$\mu_u = M_{Rc} (4.14) = 1.8333E+008$$

$$u = s_u (4.1) = 1.7539345E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u2} -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 2.4056447E-005$$

$$\mu_u = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

hmax = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.01016$
bw = 200.00
effective stress from (A.35), $ff,e = 768.6287$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$

$ase = \text{Max}((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}} * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

s = 100.00
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$
c = confinement factor = 1.06029

$y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 466.8167$
 $fy1 = 389.0139$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 466.8167$
 $fy2 = 389.0139$
 $su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $es_{u2_nominal} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lo_{u,min} = lb/d = 0.30$

$suv = 0.4 \cdot es_{u2_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{uv_nominal} = 0.08$,

considering characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_v = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (fs_1/f_c) = 0.28838833$

2 = $As_{l,com}/(b \cdot d) \cdot (fs_2/f_c) = 0.13693259$

$v = As_{l,mid}/(b \cdot d) \cdot (fs_v/f_c) = 0.25519255$

and confined core properties:

$b = 140.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

1 = $As_{l,ten}/(b \cdot d) \cdot (fs_1/f_c) = 0.44977996$

2 = $As_{l,com}/(b \cdot d) \cdot (fs_2/f_c) = 0.21356459$

$v = As_{l,mid}/(b \cdot d) \cdot (fs_v/f_c) = 0.39800673$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$su (4.8) = 0.4038298$

$Mu = MRc (4.15) = 3.0967E+008$

$u = su (4.1) = 2.4056447E-005$

Calculation of ratio lb/d

Inadequate Lap Length with $lb/d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 290631.642$

Calculation of Shear Strength at edge 1, $V_{r1} = 290631.642$

$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = knl \cdot V_{Col0}$

$V_{Col0} = 290631.642$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu = 11.70883$
 $V_u = 0.00026803$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.625$
 $V_f ((11-3)-(11.4), ACI 440) = 188111.148$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a_i)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = NL \cdot t / N_{oDir} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 357.00
 $f_{fe} ((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 244232.638$
 $b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 290631.642$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$
 $V_{Col0} = 290631.642$
 $k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$\mu = 1$ (normal-weight concrete)
 $f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu = 11.914$
 $V_u = 0.00026803$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:

$d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.625$
 $V_f((11-3)-(11.4), ACI 440) = 188111.148$
 $f = 0.95$, for fully-wrapped sections
 $wf/sf = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a)\sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta_1 = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta_1)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $tf1 = NL * t / \text{NoDir} = 1.016$
 $dfv = d$ (figure 11.2, ACI 440) = 357.00
 $ffe((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 244232.638$
 $bw = 200.00$

 End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At local axis: 3

 Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rclcs

Constant Properties

 Knowledge Factor, $\gamma = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.45$
 #####
 Max Height, $H_{max} = 400.00$
 Min Height, $H_{min} = 200.00$
 Max Width, $W_{max} = 600.00$
 Min Width, $W_{min} = 200.00$
 Cover Thickness, $c = 25.00$
 Mean Confinement Factor overall section = 1.06029
 Element Length, $L = 3000.00$
 Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_o/l_{ou, min} = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi = 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 0.00069415$
EDGE -B-
Shear Force, $V_b = -0.00069415$
BOTH EDGES
Axial Force, $F = -6093.866$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_{lt} = 0.00$
-Compression: $As_{lc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 2890.265$
-Compression: $As_{l,com} = 829.3805$
-Middle: $As_{l,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.00732$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 438835.425$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 6.5825E+008$
 $Mu_{1+} = 6.5825E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu_{1-} = 2.1740E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 6.5825E+008$
 $Mu_{2+} = 6.5825E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu_{2-} = 2.1740E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.4829616E-005$
 $M_u = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $f_c = 33.00$
 ϕ_c (5A.5, TBDY) = 0.002
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_c, \phi_{cc}) = 0.01306815$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.01306815$
 ϕ_{we} ((5.4c), TBDY) = $ase * \text{sh}_{,min} * f_{ywe}/f_{ce} + \text{Min}(\phi_{fx}, \phi_{fy}) = 0.05721847$
where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$R = 40.00$$

Effective FRP thickness, $t_f = N_L * t * \cos(b_1) = 1.016$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 466.8167$

$fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou, min = lb/lb, min = 0.30$

$su2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs2 = fs = 389.0139$

with $Es2 = Es = 200000.00$

$yv = 0.00140044$

$shv = 0.0044814$

$ftv = 466.8167$

$fyv = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou, min = lb/ld = 0.30$

$suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fsv = fs = 389.0139$

with $Es = Es = 200000.00$

$1 = Asl, ten / (b \cdot d) \cdot (fs1 / fc) = 0.30584665$

$2 = Asl, com / (b \cdot d) \cdot (fs2 / fc) = 0.08776469$

$v = Asl, mid / (b \cdot d) \cdot (fsv / fc) = 0.04255258$

and confined core properties:

$b = 140.00$

$d = 527.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

$1 = Asl, ten / (b \cdot d) \cdot (fs1 / fc) = 0.46179611$

$2 = Asl, com / (b \cdot d) \cdot (fs2 / fc) = 0.13251541$

$v = Asl, mid / (b \cdot d) \cdot (fsv / fc) = 0.06424989$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs, y2$ - LHS eq.(4.5) is not satisfied

$v < vs, c$ - RHS eq.(4.5) is satisfied

su (4.8) = 0.38015251

$Mu = MRc$ (4.15) = 6.5825E+008

$u = su$ (4.1) = 1.4829616E-005

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0664224E-005$$

$$Mu = 2.1740E+008$$

with full section properties:

$$b = 400.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00082883$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_s e * s_{h,\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = Lstir*Astir/(Asec*s) = 0.00667588
Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00
fywe = 694.45
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287
c = confinement factor = 1.06029

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 466.8167
fy1 = 389.0139
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 466.8167
fy2 = 389.0139
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04388235

2 = Asl,com/(b*d)*(fs2/fc) = 0.15292333

v = Asl,mid/(b*d)*(fsv/fc) = 0.02127629

and confined core properties:

b = 340.00

$d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05456517$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.19015134$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.02645584$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.13804321$
 $Mu = MRc (4.14) = 2.1740E+008$
 $u = su (4.1) = 1.0664224E-005$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_{2+}

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
 $u = 1.4829616E-005$
 $Mu = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.01306815$
 $w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
 where $f = a_{pf} * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $pf = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $f_y = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $pf = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $R = 40.00$

Effective FRP thickness, $t_f = NL * t * \cos(b_1) = 1.016$

$f_u, f = 1055.00$

$E_f = 64828.00$

$u, f = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh,min = \text{Min}(psh,x, psh,y) = 0.00471239$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

psh,y ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^2/3), from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665

2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469

v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258

and confined core properties:

b = 140.00

d = 527.00

d' = 13.00

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

1 = Asl,ten/(b*d)*(fs1/fc) = 0.46179611

2 = Asl,com/(b*d)*(fs2/fc) = 0.13251541

v = Asl,mid/(b*d)*(fsv/fc) = 0.06424989

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

v < vs,y2 - LHS eq.(4.5) is not satisfied

v < vs,c - RHS eq.(4.5) is satisfied

su (4.8) = 0.38015251

Mu = MRc (4.15) = 6.5825E+008

u = su (4.1) = 1.4829616E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0664224E-005

Mu = 2.1740E+008

with full section properties:

b = 400.00

d = 557.00

d' = 43.00

v = 0.00082883

N = 6093.866

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu* = shear_factor * Max(cu, cc) = 0.01306815

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01306815

w_e ((5.4c), TBDY) = $a_{se} \cdot s_{h,min} \cdot f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
where $f = a_f \cdot p_f \cdot f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.0528506$
Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
effective stress from (A.35), $f_{f,e} = 768.6287$

$f_y = 0.0528506$
Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
effective stress from (A.35), $f_{f,e} = 768.6287$

$R = 40.00$
Effective FRP thickness, $t_f = N_L \cdot t \cdot \text{Cos}(b_1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{f} = 0.015$
 $a_{se} = \text{Max}(((A_{conf,max}-A_{noConf})/A_{conf,max}) \cdot (A_{conf,min}/A_{conf,max}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.
 $A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.
 $A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).
 $p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$
Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir}/(A_{sec} \cdot s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir}/(A_{sec} \cdot s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$s = 100.00$
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $y_1 = 0.00140044$
 $sh_1 = 0.0044814$
 $ft_1 = 466.8167$
 $fy_1 = 389.0139$
 $su_1 = 0.00512$
using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s1} = f_s = 389.0139$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_s/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s2} = f_s = 389.0139$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$s_uv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_uv = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{sv} = f_s = 389.0139$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.04388235$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.15292333$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02127629$$

and confined core properties:

$$b = 340.00$$

$$d = 527.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.05456517$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.19015134$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02645584$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

$$s_u (4.9) = 0.13804321$$

$$\mu = M_{Rc} (4.14) = 2.1740E+008$$

$$u = s_u (4.1) = 1.0664224E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 435646.093$

Calculation of Shear Strength at edge 1, $V_{r1} = 435646.093$

$V_{r1} = V_{Col} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{Col0}$

$V_{Col0} = 435646.093$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

 $\rho = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 44.9328$

$V_u = 0.00069415$

$d = 0.8 * h = 480.00$

$N_u = 6093.866$

$A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.625$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.20833333$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 293495.545$

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression,

where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L * t / N_{oDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

$f_{fe} ((11-5), \text{ACI } 440) = 259.312$

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 366348.956$

$b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 435646.093$

$V_{r2} = V_{Col} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{Col0}$

$V_{Col0} = 435646.093$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

 $\rho = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 44.60048$
 $\nu_u = 0.00069415$
 $d = 0.8 \cdot h = 480.00$
 $Nu = 6093.866$
 $Ag = 120000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$
 where:
 $V_{s1} = 139627.457$ is calculated for section web, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.625$
 $V_{s2} = 418882.372$ is calculated for section flange, with:
 $d = 480.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.20833333$
 $V_f ((11-3)-(11.4), ACI 440) = 293495.545$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = NL \cdot t / NoDir = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 557.00
 $f_{fe} ((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 366348.956$
 $b_w = 200.00$

 End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1
 At local axis: 3
 Integration Section: (a)
 Section Type: rclcs

Constant Properties

Knowledge Factor, $\phi = 1.00$
 Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE41-17.
 Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
 Consequently:
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$
 Max Height, $H_{max} = 400.00$
 Min Height, $H_{min} = 200.00$
 Max Width, $W_{max} = 600.00$
 Min Width, $W_{min} = 200.00$
 Cover Thickness, $c = 25.00$

Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, t = 1.016
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, NoDir = 1
Fiber orientations, $b_i = 0.00^\circ$
Number of layers, NL = 1
Radius of rounding corners, R = 40.00

Stepwise Properties

Bending Moment, M = -1.2956E+007
Shear Force, V2 = -4291.279
Shear Force, V3 = 77.5414
Axial Force, F = -6361.069
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 2890.265$
-Compression: $A_{st,com} = 829.3805$
-Middle: $A_{st,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $D_{bL} = 18.18182$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.01133749$
 $u = y + p = 0.01133749$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.01133749$ ((4.29), Biskinis Phd))
 $M_y = 4.5015E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 3019.222
From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} * E_c * I_g = 3.9959E+013$
factor = 0.30
 $A_g = 160000.00$
 $f_c' = 33.00$
 $N = 6361.069$
 $E_c * I_g = 1.3320E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 4.9172287E-006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (l_b/l_d)^{2/3}) = 311.2112$
 $d = 557.00$
 $y = 0.43186761$
 $A = 0.03718321$
 $B = 0.02864736$

with $p_t = 0.02594493$
 $p_c = 0.00744507$
 $p_v = 0.00360973$
 $N = 6361.069$
 $b = 200.00$
 $" = 0.07719928$
 $y_{comp} = 9.2351909E-006$
 with f_c^* (12.3, (ACI 440)) = 33.28275
 $f_c = 33.00$
 $f_l = 0.73070932$
 $b = b_{max} = 600.00$
 $h = h_{max} = 400.00$
 $A_g = 160000.00$
 $g = p_t + p_c + p_v = 0.03699973$
 $r_c = 40.00$
 $A_e/A_c = 0.27772029$
 Effective FRP thickness, $t_f = N L^* t^* \cos(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.431356$
 $A = 0.03687106$
 $B = 0.02846388$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

 - Calculation of p -

From table 10-8: $p = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$
 shear control ratio $V_y E / V_{col} O E = 1.00732$

$d = 557.00$

$s = 0.00$

$t = A_v / (b w^* s) + 2^* t_f / b w^* (f_{fe} / f_s) = A_v^* L_{stir} / (A_g^* s) + 2^* t_f / b w^* (f_{fe} / f_s) = 0.00$

$A_v = 78.53982$, is the area of every stirrup

$L_{stir} = 1360.00$, is the total Length of all stirrups parallel to loading (shear) direction

The term $2^* t_f / b w^* (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2^* t_f / b w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$N_{UD} = 6361.069$

$A_g = 160000.00$

$f_{cE} = 33.00$

$f_{ytE} = f_{ylE} = 0.00$

$p_l = \text{Area_Tot_Long_Rein} / (b^* d) = 0.03699973$

$b = 200.00$

$d = 557.00$

$f_{cE} = 33.00$

 End Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 5

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rdcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE41-17).

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = l_b/d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $b_i: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -1.2956E+007$
Shear Force, $V_a = -4291.279$
EDGE -B-
Bending Moment, $M_b = 80283.485$
Shear Force, $V_b = 4291.279$
BOTH EDGES
Axial Force, $F = -6361.069$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_{lt} = 0.00$
-Compression: $As_{lc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 2890.265$
-Compression: $As_{l,com} = 829.3805$
-Middle: $As_{l,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.18182$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 439706.044$
 V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{Col0} = 439706.044$
 $V_{Col} = 439706.044$
 $k_n = 1.00$
 $displacement_ductility_demand = 0.04395531$

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 $f_c' = 25.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.00$
 $M_u = 80283.485$
 $V_u = 4291.279$
 $d = 0.8 \cdot h = 480.00$
 $N_u = 6361.069$
 $A_g = 120000.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 502654.825$
where:
 $V_{s1} = 125663.706$ is calculated for section web, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.625$
 $V_{s2} = 376991.118$ is calculated for section flange, with:
 $d = 480.00$
 $A_v = 157079.633$
 $f_y = 500.00$

$s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.20833333$
 $V_f((11-3)-(11.4), ACI 440) = 293495.545$
 $f = 0.95$, for fully-wrapped sections
 $wf/sf = 1$ (FRP strips adjacent to one another).
 $\ln(11.3) \sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where θ is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, 1)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$
 $dfv = d$ (figure 11.2, ACI 440) = 557.00
 $ffe((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 318865.838$
 $bw = 200.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END B -
 for rotation axis 3 and integ. section (b)

From analysis, chord rotation $\theta = 4.9517037E-005$
 $y = (M_y * L_s / 3) / E_{eff} = 0.00112653$ ((4.29), Biskinis Phd)
 $M_y = 4.5015E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 300.00
 From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} * E_c * I_g = 3.9959E+013$
 $\text{factor} = 0.30$
 $A_g = 160000.00$
 $f_c' = 33.00$
 $N = 6361.069$
 $E_c * I_g = 1.3320E+014$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 4.9172287E-006$
 with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 311.2112$
 $d = 557.00$
 $y = 0.43186761$
 $A = 0.03718321$
 $B = 0.02864736$
 with $pt = 0.02594493$
 $pc = 0.00744507$
 $pv = 0.00360973$
 $N = 6361.069$
 $b = 200.00$
 $\theta = 0.07719928$
 $y_{comp} = 9.2351909E-006$
 with $f_c'((12.3), (ACI 440)) = 33.28275$
 $f_c = 33.00$
 $f_l = 0.73070932$
 $b = b_{max} = 600.00$
 $h = h_{max} = 400.00$
 $A_g = 160000.00$
 $g = pt + pc + pv = 0.03699973$
 $rc = 40.00$

$$A_e/A_c = 0.27772029$$

$$\text{Effective FRP thickness, } t_f = NL * t * \cos(b1) = 1.016$$

effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$

$$f_u = 0.01$$

$$E_f = 64828.00$$

$$E_c = 26999.444$$

$$y = 0.431356$$

$$A = 0.03687106$$

$$B = 0.02846388$$

with $E_s = 200000.00$

Calculation of ratio I_b/I_d

Inadequate Lap Length with $I_b/I_d = 0.30$

End Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 6

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rdcs

Constant Properties

```

Knowledge Factor,  $\phi = 1.00$ 
Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Secondary Member: Concrete Strength,  $f_c = f_{cm} = 33.00$ 
New material of Secondary Member: Steel Strength,  $f_s = f_{sm} = 555.56$ 
Concrete Elasticity,  $E_c = 26999.444$ 
Steel Elasticity,  $E_s = 200000.00$ 
#####
Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 694.45$ 
#####
Max Height,  $H_{max} = 400.00$ 
Min Height,  $H_{min} = 200.00$ 
Max Width,  $W_{max} = 600.00$ 
Min Width,  $W_{min} = 200.00$ 
Cover Thickness,  $c = 25.00$ 
Mean Confinement Factor overall section = 1.06029
Element Length,  $L = 3000.00$ 
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with  $l_o/l_{ou,min} = 0.30$ 
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness,  $t = 1.016$ 
Tensile Strength,  $f_{fu} = 1055.00$ 
Tensile Modulus,  $E_f = 64828.00$ 
Elongation,  $e_{fu} = 0.01$ 
Number of directions,  $N_{oDir} = 1$ 
Fiber orientations,  $b_i = 0.00^\circ$ 
Number of layers,  $N_L = 1$ 
Radius of rounding corners,  $R = 40.00$ 
-----

Stepwise Properties
-----
At local axis: 3
EDGE -A-
Shear Force,  $V_a = -0.00026803$ 
EDGE -B-
Shear Force,  $V_b = 0.00026803$ 
BOTH EDGES
Axial Force,  $F = -6093.866$ 
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension:  $A_{sl,t} = 0.00$ 
-Compression:  $A_{sl,c} = 4121.77$ 
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension:  $A_{sl,ten} = 829.3805$ 
-Compression:  $A_{sl,com} = 1746.726$ 
-Middle:  $A_{sl,mid} = 1545.664$ 
-----
-----

Calculation of Shear Capacity ratio ,  $V_e/V_r = 0.71033407$ 
Member Controlled by Flexure ( $V_e/V_r < 1$ )
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 206445.557$ 
with
 $M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 3.0967E+008$ 
 $M_{u1+} = 1.8333E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u1-} = 3.0967E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination

```

$$M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 3.0967E+008$$

$\mu_{2+} = 1.8333E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{2-} = 3.0967E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7539345E-005$$

$$M_u = 1.8333E+008$$

with full section properties:

$$b = 600.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0008621$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$\omega \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_c: \mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01306815$$

$$\omega_e \text{ ((5.4c), TBDY)} = a_{se} * \text{sh}_{\min} * f_{ywe} / f_{ce} + \text{Min}(\bar{f}_x, \bar{f}_y) = 0.05721847$$

where $\bar{f} = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$\bar{f}_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$\bar{f}_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = NL * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$\text{psh,x ((5.4d), TBDY)} = \text{Lstir} \cdot \text{Astir} / (\text{Asec} \cdot \text{s}) = 0.00471239$$

Lstir (Length of stirrups along Y) = 1360.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

$$\text{psh,y ((5.4d), TBDY)} = \text{Lstir} \cdot \text{Astir} / (\text{Asec} \cdot \text{s}) = 0.00667588$$

Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

$$\text{s} = 100.00$$

$$\text{fywe} = 694.45$$

$$\text{fce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: cc} = 0.00260287$$

$$\text{c} = \text{confinement factor} = 1.06029$$

$$\text{y1} = 0.00140044$$

$$\text{sh1} = 0.0044814$$

$$\text{ft1} = 466.8167$$

$$\text{fy1} = 389.0139$$

$$\text{su1} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{su1} = 0.4 \cdot \text{esu1_nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fs1} = \text{fs} = 389.0139$$

$$\text{with Es1} = \text{Es} = 200000.00$$

$$\text{y2} = 0.00140044$$

$$\text{sh2} = 0.0044814$$

$$\text{ft2} = 466.8167$$

$$\text{fy2} = 389.0139$$

$$\text{su2} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/lb,min} = 0.30$$

$$\text{su2} = 0.4 \cdot \text{esu2_nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fs2} = \text{fs} = 389.0139$$

$$\text{with Es2} = \text{Es} = 200000.00$$

$$\text{yv} = 0.00140044$$

$$\text{shv} = 0.0044814$$

$$\text{ftv} = 466.8167$$

$$\text{fyv} = 389.0139$$

$$\text{suv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{suv} = 0.4 \cdot \text{esuv_nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fsv} = \text{fs} = 389.0139$$

$$\text{with Esv} = \text{Es} = 200000.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0456442$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.09612944$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.08506418$$

and confined core properties:

$$b = 540.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0553686$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11660962$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10318693$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18231057$$

$$\mu_u = M_{Rc} (4.14) = 1.8333E+008$$

$$u = s_u (4.1) = 1.7539345E-005$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

Calculation of μ_{u1} -

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 2.4056447E-005$$

$$\mu_u = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

From EC8 A.4.3(6), $pf = 2t_f/bw = 0.01016$
 $bw = 200.00$
effective stress from (A.35), $ff_e = 768.6287$

$R = 40.00$
Effective FRP thickness, $t_f = NL * t * \cos(b_1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{,min} = \text{Min}(psh_{,x}, psh_{,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $psh_{,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$psh_{,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$psh_{,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$s = 100.00$
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$
 $c = \text{confinement factor} = 1.06029$

$y_1 = 0.00140044$
 $sh_1 = 0.0044814$
 $ft_1 = 466.8167$
 $fy_1 = 389.0139$
 $su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 466.8167$
 $fy_2 = 389.0139$
 $su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu_{2,nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$s_{uv} = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$

$s_{uv} = 0.4 \cdot es_{uv_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{uv_nominal} = 0.08$,

considering characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{sv} = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $Asl_{ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.28838833$

2 = $Asl_{com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.13693259$

$v = Asl_{mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.25519255$

and confined core properties:

$b = 140.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

1 = $Asl_{ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.44977996$

2 = $Asl_{com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.21356459$

$v = Asl_{mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.39800673$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$s_u (4.8) = 0.4038298$

$\mu_u = MR_c (4.15) = 3.0967E+008$

$u = s_u (4.1) = 2.4056447E-005$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7539345E-005$

$\mu_u = 1.8333E+008$

with full section properties:

$b = 600.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0008621$

$N = 6093.866$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_{se} * s_{h,\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N_L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

$$A_{\text{sec}} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$$

$$L_{\text{stir}} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

$$A_{\text{sec}} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$f_{y1} = 389.0139$
 $s_{u1} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{u1} = 0.4 * e_{su1,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,
 For calculation of $e_{su1,nominal}$ and y_1, sh_1, ft_1, f_{y1} , it is considered
 characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.
 with $f_{s1} = f_s = 389.0139$
 with $E_{s1} = E_s = 200000.00$
 $y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 466.8167$
 $f_{y2} = 389.0139$
 $s_{u2} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$
 $s_{u2} = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,
 For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, f_{y2} , it is considered
 characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_2, sh_2, ft_2, f_{y2} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.
 with $f_{s2} = f_s = 389.0139$
 with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.8167$
 $f_{yv} = 389.0139$
 $s_{uv} = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 0.30$
 $s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,
 considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, f_{yv} , it is considered
 characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.
 with $f_{sv} = f_s = 389.0139$
 with $E_{sv} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0456442$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.09612944$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.08506418$
 and confined core properties:
 $b = 540.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0553686$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11660962$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10318693$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $s_u (4.9) = 0.18231057$
 $M_u = M_{Rc} (4.14) = 1.8333E+008$
 $u = s_u (4.1) = 1.7539345E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 2.4056447E-005$$

$$\mu_2 = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_2: \mu_2^* = \text{shear_factor} * \text{Max}(\mu_2, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_2 = 0.01306815$$

$$\mu_2 \text{ (5.4c), TBDY} = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f_x = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = NL * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_{se} = \text{Max}(((A_{conf,max}-A_{noConf})/A_{conf,max}) * (A_{conf,min}/A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00471239$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00471239$$

$$Lstir \text{ (Length of stirrups along Y)} = 1360.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$psh,y \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00667588$$

$$Lstir \text{ (Length of stirrups along X)} = 960.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$fywe = 694.45$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 466.8167$$

$$fy1 = 389.0139$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs1 = fs = 389.0139$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 466.8167$$

$$fy2 = 389.0139$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs2 = fs = 389.0139$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.8167$$

$$fyv = 389.0139$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$suv = 0.4 * esuv_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

with $E_{sv} = E_s = 200000.00$

$$1 = A_{s1,ten}/(b*d)*(f_{s1}/f_c) = 0.28838833$$

$$2 = A_{s1,com}/(b*d)*(f_{s2}/f_c) = 0.13693259$$

$$v = A_{s1,mid}/(b*d)*(f_{sv}/f_c) = 0.25519255$$

and confined core properties:

$$b = 140.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{s1,ten}/(b*d)*(f_{s1}/f_c) = 0.44977996$$

$$2 = A_{s1,com}/(b*d)*(f_{s2}/f_c) = 0.21356459$$

$$v = A_{s1,mid}/(b*d)*(f_{sv}/f_c) = 0.39800673$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.4038298$$

$$M_u = M_{Rc} (4.15) = 3.0967E+008$$

$$u = s_u (4.1) = 2.4056447E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 290631.642$

Calculation of Shear Strength at edge 1, $V_{r1} = 290631.642$

$$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = k_{nl} * V_{Co10}$$

$$V_{Co10} = 290631.642$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 33.00, \text{ but } f_c'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 4.00$$

$$M_u = 11.70883$$

$$V_u = 0.00026803$$

$$d = 0.8 * h = 320.00$$

$$N_u = 6093.866$$

$$A_g = 80000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 418882.372$$

where:

$V_{s1} = 279254.914$ is calculated for section web, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 139627.457$ is calculated for section flange, with:

$$d = 160.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

V_{s2} is multiplied by $Col2 = 1.00$

$$s/d = 0.625$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 188111.148$$

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 135^\circ$

$V_f = \text{Min}(|V_f(45^\circ, \alpha)|, |V_f(-45^\circ, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L * t / N_{oDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 244232.638$

$b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 290631.642$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} * V_{Col0}$

$V_{Col0} = 290631.642$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f * V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

$\lambda = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 11.914$

$V_u = 0.00026803$

$d = 0.8 * h = 320.00$

$N_u = 6093.866$

$A_g = 80000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$

where:

$V_{s1} = 279254.914$ is calculated for section web, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.3125$

$V_{s2} = 139627.457$ is calculated for section flange, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 135^\circ$

$V_f = \text{Min}(|V_f(45^\circ, \alpha)|, |V_f(-45^\circ, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L * t / N_{oDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 244232.638$

bw = 200.00

End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rdcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$
Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Max Height, $H_{max} = 400.00$
Min Height, $H_{min} = 200.00$
Max Width, $W_{max} = 600.00$
Min Width, $W_{min} = 200.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.06029
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $N_{oDir} = 1$
Fiber orientations, $b_i = 0.00^\circ$
Number of layers, $N_L = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 0.00069415$
EDGE -B-
Shear Force, $V_b = -0.00069415$
BOTH EDGES
Axial Force, $F = -6093.866$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $Asl,ten = 2890.265$
-Compression: $Asl,com = 829.3805$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 1.00732$

Member Controlled by Shear ($Ve/Vr > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 438835.425$

with
 $Mpr1 = \text{Max}(Mu1+, Mu1-) = 6.5825E+008$
 $Mu1+ = 6.5825E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu1- = 2.1740E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $Mpr2 = \text{Max}(Mu2+, Mu2-) = 6.5825E+008$
 $Mu2+ = 6.5825E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu2- = 2.1740E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.4829616E-005$
 $Mu = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $fc = 33.00$
 $co (5A.5, TBDY) = 0.002$
Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $cu = 0.01306815$
 $w_e ((5.4c), TBDY) = ase * sh, \text{min} * fywe / fce + \text{Min}(fx, fy) = 0.05721847$
where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$fx = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((bmax-2R)^2 + (hmax-2R)^2) / 3 = 35733.333$

$bmax = 600.00$

$hmax = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ff,e = 768.6287$

$fy = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((bmax-2R)^2 + (hmax-2R)^2) / 3 = 0.00$

$bmax = 600.00$

$hmax = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ff,e = 768.6287$

$R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1,nominal} = 0.08,$$

For calculation of $esu_{1,nominal}$ and y_1 , sh_1 , ft_1 , fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs_1 = fs = 389.0139$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu_{2,nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{2,nominal} = 0.08,$$

For calculation of $esu_{2,nominal}$ and y_2 , sh_2 , ft_2 , fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2 , sh_2 , ft_2 , fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs_2 = fs = 389.0139$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00140044$$

$shv = 0.0044814$
 $ftv = 466.8167$
 $fyv = 389.0139$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.
 with $fsv = fs = 389.0139$
 with $Esv = Es = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258$
 and confined core properties:
 $b = 140.00$
 $d = 527.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = confinement\ factor = 1.06029$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.46179611$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.13251541$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.06424989$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < vs,y2$ - LHS eq.(4.5) is not satisfied
 --->
 $v < vs,c$ - RHS eq.(4.5) is satisfied
 --->
 $su (4.8) = 0.38015251$
 $Mu = MRc (4.15) = 6.5825E+008$
 $u = su (4.1) = 1.4829616E-005$

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of $Mu1$ -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.0664224E-005$
 $Mu = 2.1740E+008$

 with full section properties:

$b = 400.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00082883$
 $N = 6093.866$
 $fc = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.01306815$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.01306815$
 $we ((5.4c), TBDY) = ase * sh,min*fywe/fce + Min(fx, fy) = 0.05721847$

where $f = af \cdot pf \cdot ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$$af = 0.22333333$$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } pf = 2tf/bw = 0.01016$$

$$bw = 200.00$$

$$\text{effective stress from (A.35), } ffe = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$$af = 0.22333333$$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } pf = 2tf/bw = 0.01016$$

$$bw = 200.00$$

$$\text{effective stress from (A.35), } ffe = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } tf = NL \cdot t \cdot \cos(b1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) \cdot (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{,min} = \text{Min}(psh_{,x}, psh_{,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $psh_{,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_{,x} \text{ ((5.4d), TBDY)} = L_{stir} \cdot A_{stir} / (A_{sec} \cdot s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$psh_{,y} \text{ ((5.4d), TBDY)} = L_{stir} \cdot A_{stir} / (A_{sec} \cdot s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 466.8167$$

$$fy1 = 389.0139$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{ou,min} = l_b / l_d = 0.30$$

$$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs1 = fs = 389.0139$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 466.8167$$

$$fy2 = 389.0139$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou, \text{min} = lb/lb, \text{min} = 0.30$$

$$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y2, sh2, ft2, fy2$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs2 = fs = 389.0139$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.8167$$

$$fyv = 389.0139$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou, \text{min} = lb/ld = 0.30$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

yv, shv, ftv, fyv , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl, \text{ten} / (b * d) * (fs1 / fc) = 0.04388235$$

$$2 = Asl, \text{com} / (b * d) * (fs2 / fc) = 0.15292333$$

$$v = Asl, \text{mid} / (b * d) * (fsv / fc) = 0.02127629$$

and confined core properties:

$$b = 340.00$$

$$d = 527.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 34.98946$$

$$cc (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = Asl, \text{ten} / (b * d) * (fs1 / fc) = 0.05456517$$

$$2 = Asl, \text{com} / (b * d) * (fs2 / fc) = 0.19015134$$

$$v = Asl, \text{mid} / (b * d) * (fsv / fc) = 0.02645584$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs, y2$ - LHS eq.(4.5) is satisfied

$$su (4.9) = 0.13804321$$

$$Mu = MRc (4.14) = 2.1740E+008$$

$$u = su (4.1) = 1.0664224E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu2+

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.4829616E-005$$

$$Mu = 6.5825E+008$$

with full section properties:

$$b = 200.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00165765$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_s e * s_{h,\min} * f_{y,w} / f_{c,e} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{f,e} / f_{c,e}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cos(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = Lstir*Astir/(Asec*s) = 0.00667588
Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00
fywe = 694.45
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287
c = confinement factor = 1.06029

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 466.8167
fy1 = 389.0139
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 466.8167
fy2 = 389.0139
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665

2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469

v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258

and confined core properties:

b = 140.00

$d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.46179611$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13251541$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.06424989$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 --->

$s_u (4.8) = 0.38015251$
 $M_u = M_{Rc} (4.15) = 6.5825E+008$
 $u = s_u (4.1) = 1.4829616E-005$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of M_{u2} -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
 $u = 1.0664224E-005$
 $M_u = 2.1740E+008$

with full section properties:

$b = 400.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00082883$
 $N = 6093.866$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.01306815$
 $w_e ((5.4c), TBDY) = a_{se} * sh_{,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
 where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $f_y = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

R = 40.00

Effective FRP thickness, $t_f = NL \cdot t \cdot \cos(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$ase = \text{Max}((A_{conf,max} - A_{noConf}) / A_{conf,max}) \cdot (A_{conf,min} / A_{conf,max}, 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir} / (A_{sec} \cdot s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir} / (A_{sec} \cdot s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su_1 = 0.4 \cdot esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{s2} = f_s = 389.0139$
 with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.8167$
 $fy_v = 389.0139$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 0.30$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.
 with $f_{sv} = f_s = 389.0139$
 with $E_{sv} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.04388235$
 $2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.15292333$
 $v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02127629$
 and confined core properties:
 $b = 340.00$
 $d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.05456517$
 $2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.19015134$
 $v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02645584$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 435646.093$

Calculation of Shear Strength at edge 1, $V_{r1} = 435646.093$
 $V_{r1} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{ColO}$
 $V_{ColO} = 435646.093$
 $knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

$= 1$ (normal-weight concrete)
 $f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3 \text{ MPa}$ (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 44.9328$
 $V_u = 0.00069415$
 $d = 0.8 * h = 480.00$
 $N_u = 6093.866$
 $A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.625$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.20833333$

V_f ((11-3)-(11.4), ACI 440) = 293495.545

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a)\sin a$ which is more a generalised expression,

where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, \theta)|)$, with:

total thickness per orientation, $t_{f1} = NL \cdot t / NoDir = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 366348.956$

$b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 435646.093$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_n l \cdot V_{Col0}$

$V_{Col0} = 435646.093$

$k_n l = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_s + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

$\lambda = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 44.60048$

$\nu_u = 0.00069415$

$d = 0.8 \cdot h = 480.00$

$N_u = 6093.866$

$A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.625$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.20833333$

Vf ((11-3)-(11.4), ACI 440) = 293495.545

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \cot \alpha) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function Vf(θ , α), is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

Vf = Min(|Vf(45, θ)|, |Vf(-45, θ)|), with:

total thickness per orientation, tf1 = NL*t/NoDir = 1.016

dfv = d (figure 11.2, ACI 440) = 557.00

ffe ((11-5), ACI 440) = 259.312

Ef = 64828.00

fe = 0.004, from (11.6a), ACI 440

with fu = 0.01

From (11-11), ACI 440: Vs + Vf <= 366348.956

bw = 200.00

End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_b/l_d = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, NoDir = 1

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, NL = 1

Radius of rounding corners, R = 40.00

Stepwise Properties

Bending Moment, $M = -70821.725$
Shear Force, $V2 = 4291.279$
Shear Force, $V3 = -77.5414$
Axial Force, $F = -6361.069$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{,ten} = 829.3805$
-Compression: $As_{,com} = 1746.726$
-Middle: $As_{,mid} = 1545.664$
Mean Diameter of Tension Reinforcement, $Db_L = 18.66667$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.00288528$
 $u = y + p = 0.00288528$

- Calculation of y -

 $y = (My * Ls / 3) / Eleff = 0.00288528$ ((4.29), Biskinis Phd))
 $My = 1.3306E+008$
 $Ls = M/V$ (with $Ls > 0.1 * L$ and $Ls < 2 * L$) = 913.3408
From table 10.5, ASCE 41_17: $Eleff = factor * Ec * I_g = 1.4040E+013$
 $factor = 0.30$
 $Ag = 160000.00$
 $fc' = 33.00$
 $N = 6361.069$
 $Ec * I_g = 4.6799E+013$

Calculation of Yielding Moment My

Calculation of y and My according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, $b = 600.00$
web width, $bw = 200.00$
flange thickness, $t = 200.00$

 $y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 5.8026993E-006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (lb/d)^{2/3}) = 311.2112$
 $d = 357.00$
 $y = 0.24884964$
 $A = 0.01933805$
 $B = 0.00899219$
with $pt = 0.00387199$
 $pc = 0.00815465$
 $pv = 0.00721598$
 $N = 6361.069$
 $b = 600.00$
 $" = 0.12044818$
 $y_{comp} = 2.5091791E-005$
with fc^* (12.3, (ACI 440)) = 33.29607
 $fc = 33.00$
 $fl = 0.73070932$
 $b = b_{max} = 600.00$
 $h = h_{max} = 400.00$
 $Ag = 160000.00$
 $g = pt + pc + pv = 0.01924262$
 $rc = 40.00$
 $Ae/Ac = 0.29079753$
Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$

$f_u = 0.01$

$E_f = 64828.00$

$E_c = 26999.444$

$y = 0.24780539$

$A = 0.01917573$

$B = 0.00889677$

with $E_s = 200000.00$

CONFIRMATION: $y = 0.24825313 < t/d$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of ρ -

From table 10-8: $\rho = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$

shear control ratio $V_y E / C_o I_{OE} = 0.71033407$

$d = 357.00$

$s = 0.00$

$t = A_v / (b_w s) + 2 t_f / b_w (f_{fe} / f_s) = A_v L_{stir} / (A_g s) + 2 t_f / b_w (f_{fe} / f_s) = 0.00$

$A_v = 78.53982$, is the area of every stirrup

$L_{stir} = 960.00$, is the total Length of all stirrups parallel to loading (shear) direction

The term $2 t_f / b_w (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$NUD = 6361.069$

$A_g = 160000.00$

$f_{cE} = 33.00$

$f_{yE} = f_{yIE} = 0.00$

$\rho_l = \text{Area_Tot_Long_Rein} / (b d) = 0.01924262$

$b = 600.00$

$d = 357.00$

$f_{cE} = 33.00$

End Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 7

column C1, Floor 1


Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE41-17).

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = l_b/l_d = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -160913.077$
Shear Force, $V_a = 77.5414$
EDGE -B-
Bending Moment, $M_b = -70821.725$
Shear Force, $V_b = -77.5414$
BOTH EDGES
Axial Force, $F = -6361.069$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_{lt} = 0.00$
-Compression: $As_{lc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 829.3805$
-Compression: $As_{l,com} = 1746.726$
-Middle: $As_{l,mid} = 1545.664$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.66667$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 * V_n = 269320.945$
 V_n ((10.3), ASCE 41-17) = $knI * V_{CoI0} = 269320.945$
 $V_{CoI} = 269320.945$
 $knI = 1.00$
 $displacement_ductility_demand = 1.6212221E-005$

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f * V_f$ '
where V_f is the contribution of FRPs ((11.3), ACI 440).

= 1 (normal-weight concrete)
 $fc' = 25.00$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.85419$
 $M_u = 70821.725$
 $V_u = 77.5414$
 $d = 0.8 * h = 320.00$
 $N_u = 6361.069$
 $A_g = 80000.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 376991.118$
where:
 $V_{s1} = 251327.412$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 125663.706$ is calculated for section flange, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.625$
 V_f ((11-3)-(11.4), ACI 440) = 188111.148
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,

where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $t_{f1} = NL \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 212577.225$

$b_w = 200.00$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END B -

for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 4.6776878E-008$

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.00288528$ ((4.29), Biskinis Phd)

$M_y = 1.3306E+008$

$L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 913.3408

From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} \cdot E_c \cdot I_g = 1.4040E+013$

factor = 0.30

$A_g = 160000.00$

$f_c' = 33.00$

$N = 6361.069$

$E_c \cdot I_g = 4.6799E+013$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, $b = 600.00$

web width, $b_w = 200.00$

flange thickness, $t = 200.00$

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 5.8026993E-006$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (I_b / I_d)^{2/3}) = 311.2112$

$d = 357.00$

$y = 0.24884964$

$A = 0.01933805$

$B = 0.00899219$

with $p_t = 0.00387199$

$p_c = 0.00815465$

$p_v = 0.00721598$

$N = 6361.069$

$b = 600.00$

$\theta = 0.12044818$

$y_{comp} = 2.5091791E-005$

with $f_c' \cdot (12.3, \text{ACI 440}) = 33.29607$

$f_c = 33.00$

$f_l = 0.73070932$

$b = b_{max} = 600.00$

$h = h_{max} = 400.00$

$A_g = 160000.00$

$g = p_t + p_c + p_v = 0.01924262$

$r_c = 40.00$

$A_e / A_c = 0.29079753$

Effective FRP thickness, $t_f = NL \cdot t \cdot \text{Cos}(b1) = 1.016$

effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$

$f_u = 0.01$

$E_f = 64828.00$

$E_c = 26999.444$

$y = 0.24780539$

$A = 0.01917573$

$B = 0.00889677$

with $E_s = 200000.00$

CONFIRMATION: $y = 0.24825313 < t/d$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 8

column C1, Floor 1



Limit State: Immediate Occupancy (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rclcs

Constant Properties

Knowledge Factor, $= 1.00$

```

Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Secondary Member: Concrete Strength,  $f_c = f_{cm} = 33.00$ 
New material of Secondary Member: Steel Strength,  $f_s = f_{sm} = 555.56$ 
Concrete Elasticity,  $E_c = 26999.444$ 
Steel Elasticity,  $E_s = 200000.00$ 
#####
Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength,  $f_s = 1.25 \cdot f_{sm} = 694.45$ 
#####
Max Height,  $H_{max} = 400.00$ 
Min Height,  $H_{min} = 200.00$ 
Max Width,  $W_{max} = 600.00$ 
Min Width,  $W_{min} = 200.00$ 
Cover Thickness,  $c = 25.00$ 
Mean Confinement Factor overall section = 1.06029
Element Length,  $L = 3000.00$ 
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with  $l_o/l_{ou,min} = 0.30$ 
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness,  $t = 1.016$ 
Tensile Strength,  $f_{fu} = 1055.00$ 
Tensile Modulus,  $E_f = 64828.00$ 
Elongation,  $e_{fu} = 0.01$ 
Number of directions,  $N_{oDir} = 1$ 
Fiber orientations,  $b_i: 0.00^\circ$ 
Number of layers,  $N_L = 1$ 
Radius of rounding corners,  $R = 40.00$ 
-----

Stepwise Properties
-----
At local axis: 3
EDGE -A-
Shear Force,  $V_a = -0.00026803$ 
EDGE -B-
Shear Force,  $V_b = 0.00026803$ 
BOTH EDGES
Axial Force,  $F = -6093.866$ 
Longitudinal Reinforcement Area Distribution (in 2 divisions)
  -Tension:  $A_{sl,t} = 0.00$ 
  -Compression:  $A_{sl,c} = 4121.77$ 
Longitudinal Reinforcement Area Distribution (in 3 divisions)
  -Tension:  $A_{sl,ten} = 829.3805$ 
  -Compression:  $A_{sl,com} = 1746.726$ 
  -Middle:  $A_{sl,mid} = 1545.664$ 
-----
-----

Calculation of Shear Capacity ratio ,  $V_e/V_r = 0.71033407$ 
Member Controlled by Flexure ( $V_e/V_r < 1$ )
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14  $V_e = (M_{pr1} + M_{pr2})/l_n = 206445.557$ 
with
 $M_{pr1} = \text{Max}(\mu_{u1+}, \mu_{u1-}) = 3.0967E+008$ 
 $\mu_{u1+} = 1.8333E+008$ , is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{u1-} = 3.0967E+008$ , is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{u2+}, \mu_{u2-}) = 3.0967E+008$ 

```

$\mu_{2+} = 1.8333E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{2-} = 3.0967E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7539345E-005$$

$$\mu_{1+} = 1.8333E+008$$

with full section properties:

$$b = 600.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0008621$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_s e * s_{h, \min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh, \min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh, \min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without

earthquake detailing (90° closed stirrups)

$$\text{psh}_x ((5.4d), \text{TBDY}) = \text{Lstir} * \text{Astir} / (\text{Asec} * s) = 0.00471239$$

$$\text{Lstir (Length of stirrups along Y)} = 1360.00$$

$$\text{Astir (stirrups area)} = 78.53982$$

$$\text{Asec (section area)} = 160000.00$$

$$\text{psh}_y ((5.4d), \text{TBDY}) = \text{Lstir} * \text{Astir} / (\text{Asec} * s) = 0.00667588$$

$$\text{Lstir (Length of stirrups along X)} = 960.00$$

$$\text{Astir (stirrups area)} = 78.53982$$

$$\text{Asec (section area)} = 160000.00$$

$$s = 100.00$$

$$\text{fywe} = 694.45$$

$$\text{fce} = 33.00$$

$$\text{From } ((5.A5), \text{TBDY}), \text{TBDY: } \text{cc} = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$\text{sh1} = 0.0044814$$

$$\text{ft1} = 466.8167$$

$$\text{fy1} = 389.0139$$

$$\text{su1} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{su1} = 0.4 * \text{esu1_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fs1} = \text{fs} = 389.0139$$

$$\text{with Es1} = \text{Es} = 200000.00$$

$$y2 = 0.00140044$$

$$\text{sh2} = 0.0044814$$

$$\text{ft2} = 466.8167$$

$$\text{fy2} = 389.0139$$

$$\text{su2} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/lb,min} = 0.30$$

$$\text{su2} = 0.4 * \text{esu2_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fs2} = \text{fs} = 389.0139$$

$$\text{with Es2} = \text{Es} = 200000.00$$

$$yv = 0.00140044$$

$$\text{shv} = 0.0044814$$

$$\text{ftv} = 466.8167$$

$$\text{fyv} = 389.0139$$

$$\text{suv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{suv} = 0.4 * \text{esuv_nominal} ((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fsv} = \text{fs} = 389.0139$$

$$\text{with Esv} = \text{Es} = 200000.00$$

$$1 = \text{Asl,ten} / (\text{b} * \text{d}) * (\text{fs1} / \text{fc}) = 0.0456442$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.09612944$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.08506418$$

and confined core properties:

$$b = 540.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0553686$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11660962$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10318693$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18231057$$

$$M_u = M_{Rc} (4.14) = 1.8333E+008$$

$$u = s_u (4.1) = 1.7539345E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of M_{u1} -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 2.4056447E-005$$

$$M_u = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

bw = 200.00
effective stress from (A.35), $f_{f,e} = 768.6287$

R = 40.00
Effective FRP thickness, $t_f = NL * t * \cos(b_1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$

$a_{se} = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.
 $A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

s = 100.00
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$
c = confinement factor = 1.06029

$y_1 = 0.00140044$
 $sh_1 = 0.0044814$
 $ft_1 = 466.8167$
 $fy_1 = 389.0139$
 $su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 466.8167$
 $fy_2 = 389.0139$
 $su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.
with $f_{s2} = f_s = 389.0139$
with $E_{s2} = E_s = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.8167$
 $f_{y_v} = 389.0139$
 $s_{u_v} = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 0.30$

$s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,

considering characteristic value $f_{s_{y_v}} = f_{s_{y_v}}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered
characteristic value $f_{s_{y_v}} = f_{s_{y_v}}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.
with $f_{s_v} = f_s = 389.0139$
with $E_{s_v} = E_s = 200000.00$

1 = $A_{s1,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.28838833$

2 = $A_{s1,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.13693259$

v = $A_{s1,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.25519255$

and confined core properties:

$b = 140.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

c = confinement factor = 1.06029

1 = $A_{s1,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.44977996$

2 = $A_{s1,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.21356459$

v = $A_{s1,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.39800673$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$s_u (4.8) = 0.4038298$

$\mu_u = M_{Rc} (4.15) = 3.0967E+008$

u = $s_u (4.1) = 2.4056447E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

u = $1.7539345E-005$

$\mu_u = 1.8333E+008$

with full section properties:

$b = 600.00$

$d = 357.00$

$d' = 43.00$

v = 0.0008621

N = 6093.866

$f_c = 33.00$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_{se} * s_{h,\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N_L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

$$A_{\text{sec}} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$$

$$L_{\text{stir}} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

$$A_{\text{sec}} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

```

su1 = 0.00512
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/d = 0.30
su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esu1_nominal = 0.08,
For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.
with fs1 = fs = 389.0139
with Es1 = Es = 200000.00
y2 = 0.00140044
sh2 = 0.0044814
ft2 = 466.8167
fy2 = 389.0139
su2 = 0.00512
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/lb,min = 0.30
su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esu2_nominal = 0.08,
For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.
with fs2 = fs = 389.0139
with Es2 = Es = 200000.00
yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512
using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00
lo/lou,min = lb/d = 0.30
suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032
From table 5A.1, TBDY: esuv_nominal = 0.08,
considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.
y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.
with fsv = fs = 389.0139
with Esv = Es = 200000.00
1 = Asl,ten/(b*d)*(fs1/fc) = 0.0456442
2 = Asl,com/(b*d)*(fs2/fc) = 0.09612944
v = Asl,mid/(b*d)*(fsv/fc) = 0.08506418
and confined core properties:
b = 540.00
d = 327.00
d' = 13.00
fcc (5A.2, TBDY) = 34.98946
cc (5A.5, TBDY) = 0.00260287
c = confinement factor = 1.06029
1 = Asl,ten/(b*d)*(fs1/fc) = 0.0553686
2 = Asl,com/(b*d)*(fs2/fc) = 0.11660962
v = Asl,mid/(b*d)*(fsv/fc) = 0.10318693
Case/Assumption: Unconfined full section - Steel rupture
'satisfies Eq. (4.3)
--->
v < vs,y2 - LHS eq.(4.5) is satisfied
--->
su (4.9) = 0.18231057
Mu = MRc (4.14) = 1.8333E+008
u = su (4.1) = 1.7539345E-005

```

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 2.4056447E-005$$

$$\mu_2 = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$\omega (5A.5, \text{TB DY}) = 0.002$$

$$\text{Final value of } \mu_c: \mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TB DY: } \mu_c = 0.01306815$$

$$\mu_{we} \text{ ((5.4c), TB DY) } = a_{se} * \text{sh}_{,\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TB DY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TB DY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

Effective FRP thickness, $t_f = N L * t * \text{Cos}(b_1) = 1.016$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$\text{psh,x ((5.4d), TBDY)} = \text{Lstir} * \text{Astir} / (\text{Asec} * s) = 0.00471239$$

Lstir (Length of stirrups along Y) = 1360.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

$$\text{psh,y ((5.4d), TBDY)} = \text{Lstir} * \text{Astir} / (\text{Asec} * s) = 0.00667588$$

Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

$$s = 100.00$$

$$\text{fywe} = 694.45$$

$$\text{fce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$\text{sh1} = 0.0044814$$

$$\text{ft1} = 466.8167$$

$$\text{fy1} = 389.0139$$

$$\text{su1} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{su1} = 0.4 * \text{esu1_nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fs1} = \text{fs} = 389.0139$$

$$\text{with Es1} = \text{Es} = 200000.00$$

$$y2 = 0.00140044$$

$$\text{sh2} = 0.0044814$$

$$\text{ft2} = 466.8167$$

$$\text{fy2} = 389.0139$$

$$\text{su2} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/lb,min} = 0.30$$

$$\text{su2} = 0.4 * \text{esu2_nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fs2} = \text{fs} = 389.0139$$

$$\text{with Es2} = \text{Es} = 200000.00$$

$$yv = 0.00140044$$

$$\text{shv} = 0.0044814$$

$$\text{ftv} = 466.8167$$

$$\text{fyv} = 389.0139$$

$$\text{suv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$\text{lo/lou,min} = \text{lb/ld} = 0.30$$

$$\text{suv} = 0.4 * \text{esuv_nominal ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb/ld})^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with fsv} = \text{fs} = 389.0139$$

$$\text{with Esv} = \text{Es} = 200000.00$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.28838833$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13693259$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.25519255$$

and confined core properties:

$$b = 140.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.44977996$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.21356459$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.39800673$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.4038298$$

$$\mu_u = M_{Rc} (4.15) = 3.0967E+008$$

$$u = s_u (4.1) = 2.4056447E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 290631.642$

Calculation of Shear Strength at edge 1, $V_{r1} = 290631.642$

$$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} * V_{Col0}$$

$$V_{Col0} = 290631.642$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 33.00, \text{ but } f_c^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 4.00$$

$$\mu_u = 11.70883$$

$$V_u = 0.00026803$$

$$d = 0.8 * h = 320.00$$

$$N_u = 6093.866$$

$$A_g = 80000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 418882.372$$

where:

$V_{s1} = 279254.914$ is calculated for section web, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 139627.457$ is calculated for section flange, with:

$$d = 160.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

V_{s2} is multiplied by $Col2 = 1.00$

$$s/d = 0.625$$

$$V_f ((11-3)-(11.4), ACI 440) = 188111.148$$

$f = 0.95$, for fully-wrapped sections
 $wf/sf = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression,
 where θ is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, \theta)|)$, with:
 total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$
 $dfv = d$ (figure 11.2, ACI 440) = 357.00
 ffe ((11-5), ACI 440) = 259.312
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 244232.638$
 $bw = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 290631.642$
 $V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $knl * V_{ColO}$
 $V_{ColO} = 290631.642$
 $knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
 where Vf is the contribution of FRPs (11.3), ACI 440).

$\gamma_c = 1$ (normal-weight concrete)
 $fc' = 33.00$, but $fc'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 11.914$
 $V_u = 0.00026803$
 $d = 0.8 * h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.625$
 V_f ((11-3)-(11.4), ACI 440) = 188111.148
 $f = 0.95$, for fully-wrapped sections
 $wf/sf = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression,
 where θ is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, \theta)|)$, with:
 total thickness per orientation, $tf1 = NL * t / NoDir = 1.016$
 $dfv = d$ (figure 11.2, ACI 440) = 357.00
 ffe ((11-5), ACI 440) = 259.312
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 244232.638$
 $bw = 200.00$

End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rdcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$
Mean strength values are used for both shear and moment calculations.
Consequently:
New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

Max Height, $H_{max} = 400.00$
Min Height, $H_{min} = 200.00$
Max Width, $W_{max} = 600.00$
Min Width, $W_{min} = 200.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.06029
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $N_{oDir} = 1$
Fiber orientations, $b_i = 0.00^\circ$
Number of layers, $N_L = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 0.00069415$
EDGE -B-
Shear Force, $V_b = -0.00069415$
BOTH EDGES
Axial Force, $F = -6093.866$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl} = 0.00$
-Compression: $A_{slc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 2890.265$

-Compression: $Asl,com = 829.3805$
-Middle: $Asl,mid = 402.1239$

Calculation of Shear Capacity ratio , $Ve/Vr = 1.00732$

Member Controlled by Shear ($Ve/Vr > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $Ve = (Mpr1 + Mpr2)/ln = 438835.425$

with

$Mpr1 = \text{Max}(Mu1+, Mu1-) = 6.5825E+008$

$Mu1+ = 6.5825E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu1- = 2.1740E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$Mpr2 = \text{Max}(Mu2+, Mu2-) = 6.5825E+008$

$Mu2+ = 6.5825E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu2- = 2.1740E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of $Mu1+$

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.4829616E-005$

$Mu = 6.5825E+008$

with full section properties:

$b = 200.00$

$d = 557.00$

$d' = 43.00$

$v = 0.00165765$

$N = 6093.866$

$f_c = 33.00$

$\phi_{co} (5A.5, TBDY) = 0.002$

Final value of ϕ_{cu} : $\phi_{cu}^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_{cu} = 0.01306815$

$\phi_{we} ((5.4c), TBDY) = \text{ase} * \text{sh}_{,min} * f_{ywe}/f_{ce} + \text{Min}(\phi_{fx}, \phi_{fy}) = 0.05721847$

where $\phi_f = \text{af} * \text{pf} * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$\phi_{fx} = 0.0528506$

Expression ((15B.6), TBDY) is modified as $\text{af} = 1 - (\text{Unconfined area})/(\text{total area})$

$\text{af} = 0.22333333$

with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $\text{pf} = 2t_f/b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{fe} = 768.6287$

$\phi_{fy} = 0.0528506$

Expression ((15B.6), TBDY) is modified as $\text{af} = 1 - (\text{Unconfined area})/(\text{total area})$

$\text{af} = 0.22333333$

with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $\text{pf} = 2t_f/b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{fe} = 768.6287$

$R = 40.00$

Effective FRP thickness, $t_f = N L * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$$E_f = 64828.00$$

$$u, f = 0.015$$

$$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{min} = \text{Min}(psh_x, psh_y) = 0.00471239$$

Expression ((5.4d), TBDY) for psh_{min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$psh_y \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1 , sh_1 , ft_1 , fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs_1 = fs = 389.0139$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu_{2,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2 , sh_2 , ft_2 , fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2 , sh_2 , ft_2 , fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs_2 = fs = 389.0139$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ftv = 466.8167$$

$$fyv = 389.0139$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/ld = 0.30$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv , shv , ftv , fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1$, $sh1$, $ft1$, $fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl_{ten}/(b*d)*(fs1/fc) = 0.30584665$$

$$2 = Asl_{com}/(b*d)*(fs2/fc) = 0.08776469$$

$$v = Asl_{mid}/(b*d)*(fsv/fc) = 0.04255258$$

and confined core properties:

$$b = 140.00$$

$$d = 527.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 34.98946$$

$$cc (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = Asl_{ten}/(b*d)*(fs1/fc) = 0.46179611$$

$$2 = Asl_{com}/(b*d)*(fs2/fc) = 0.13251541$$

$$v = Asl_{mid}/(b*d)*(fsv/fc) = 0.06424989$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs_{y2}$ - LHS eq.(4.5) is not satisfied

$v < vs_c$ - RHS eq.(4.5) is satisfied

$$su (4.8) = 0.38015251$$

$$Mu = MRc (4.15) = 6.5825E+008$$

$$u = su (4.1) = 1.4829616E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 1.0664224E-005$$

$$Mu = 2.1740E+008$$

with full section properties:

$$b = 400.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00082883$$

$$N = 6093.866$$

$$fc = 33.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.01306815$$

$$we ((5.4c), TBDY) = ase * sh_{min} * fy_{we} / fce + \text{Min}(fx, fy) = 0.05721847$$

where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$R = 40.00$$

Effective FRP thickness, $t_f = N_L * t * \cos(b_1) = 1.016$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 466.8167$

$fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lou, min = lb/lb, min = 0.30$

$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs2 = fs = 389.0139$

with $Es2 = Es = 200000.00$

$yv = 0.00140044$

$shv = 0.0044814$

$ftv = 466.8167$

$fyv = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lou, min = lb/ld = 0.30$

$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fsv = fs = 389.0139$

with $Esv = Es = 200000.00$

$1 = Asl, ten / (b*d) * (fs1 / fc) = 0.04388235$

$2 = Asl, com / (b*d) * (fs2 / fc) = 0.15292333$

$v = Asl, mid / (b*d) * (fsv / fc) = 0.02127629$

and confined core properties:

$b = 340.00$

$d = 527.00$

$d' = 13.00$

$fcc (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = confinement\ factor = 1.06029$

$1 = Asl, ten / (b*d) * (fs1 / fc) = 0.05456517$

$2 = Asl, com / (b*d) * (fs2 / fc) = 0.19015134$

$v = Asl, mid / (b*d) * (fsv / fc) = 0.02645584$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs, y2$ - LHS eq.(4.5) is satisfied

$su (4.9) = 0.13804321$

$Mu = MRc (4.14) = 2.1740E+008$

$u = su (4.1) = 1.0664224E-005$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu2+

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.4829616E-005$$

$$Mu = 6.5825E+008$$

with full section properties:

$$b = 200.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00165765$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_s e^* s_{h,\min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t^* \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = Lstir*Astir/(Asec*s) = 0.00667588

Lstir (Length of stirrups along X) = 960.00

Astir (stirrups area) = 78.53982

Asec (section area) = 160000.00

s = 100.00

fywe = 694.45

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287

c = confinement factor = 1.06029

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 466.8167

fy1 = 389.0139

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 466.8167

fy2 = 389.0139

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.8167

fyv = 389.0139

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665

2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469

v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258

and confined core properties:

b = 140.00

d = 527.00

$d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.46179611$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13251541$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.06424989$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->
 $su (4.8) = 0.38015251$
 $Mu = MR_c (4.15) = 6.5825E+008$
 $u = su (4.1) = 1.4829616E-005$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_2 -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.0664224E-005$
 $Mu = 2.1740E+008$

 with full section properties:

$b = 400.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00082883$
 $N = 6093.866$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.01306815$
 $w_e ((5.4c), TBDY) = a_{se} * sh_{,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
 where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $f_y = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

R = 40.00

Effective FRP thickness, $t_f = NL \cdot t \cdot \cos(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$ase = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) \cdot (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x}$ ((5.4d), TBDY) = $L_{\text{stir}} \cdot A_{\text{stir}} / (A_{\text{sec}} \cdot s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $p_{sh,y}$ ((5.4d), TBDY) = $L_{\text{stir}} \cdot A_{\text{stir}} / (A_{\text{sec}} \cdot s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su_1 = 0.4 \cdot esu1_{\text{nominal}}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{\text{nominal}} = 0.08$,

For calculation of $esu1_{\text{nominal}}$ and y_1 , sh_1 , ft_1 , fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 \cdot esu2_{\text{nominal}}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{\text{nominal}} = 0.08$,

For calculation of $esu2_{\text{nominal}}$ and y_2 , sh_2 , ft_2 , fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $E_s = E_s = 200000.00$
 $y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.8167$
 $fy_v = 389.0139$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 0.30$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.
 with $fsv = fs = 389.0139$
 with $E_s = E_s = 200000.00$
 $1 = Asl_{ten}/(b * d) * (fs_1 / fc) = 0.04388235$
 $2 = Asl_{com}/(b * d) * (fs_2 / fc) = 0.15292333$
 $v = Asl_{mid}/(b * d) * (fsv / fc) = 0.02127629$
 and confined core properties:
 $b = 340.00$
 $d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = Asl_{ten}/(b * d) * (fs_1 / fc) = 0.05456517$
 $2 = Asl_{com}/(b * d) * (fs_2 / fc) = 0.19015134$
 $v = Asl_{mid}/(b * d) * (fsv / fc) = 0.02645584$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Shear Strength $V_r = Min(V_{r1}, V_{r2}) = 435646.093$

Calculation of Shear Strength at edge 1, $V_{r1} = 435646.093$

$V_{r1} = V_{Col} ((10.3), ASCE 41-17) = knl * V_{Col0}$

$V_{Col0} = 435646.093$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
 where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$fc' = 33.00$, but $fc^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 44.9328$

$V_u = 0.00069415$

$d = 0.8 * h = 480.00$

$N_u = 6093.866$

$A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.625$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.20833333$

V_f ((11-3)-(11.4), ACI 440) = 293495.545

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a)\sin a$ which is more a generalised expression,

where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, \theta)|)$, with:

total thickness per orientation, $t_{f1} = NL \cdot t / N_{oDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 366348.956$

$b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 435646.093$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$V_{Col0} = 435646.093$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_s + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

$\lambda = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$M_u = 44.60048$

$V_u = 0.00069415$

$d = 0.8 \cdot h = 480.00$

$N_u = 6093.866$

$A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.625$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.20833333$

V_f ((11-3)-(11.4), ACI 440) = 293495.545

f = 0.95, for fully-wrapped sections

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \cot \alpha) \sin \alpha$ which is more a generalised expression,

where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 135^\circ$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, \theta)|)$, with:

total thickness per orientation, $t_{f1} = NL * t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 366348.956$

$b_w = 200.00$

End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rclcs

Constant Properties

Knowledge Factor, $\phi = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_b / l_d = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $\text{NoDir} = 1$

Fiber orientations, $\theta_i: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

Bending Moment, $M = 80283.485$

Shear Force, V2 = 4291.279
Shear Force, V3 = -77.5414
Axial Force, F = -6361.069
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Aslt = 0.00
-Compression: Aslc = 4121.77
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 2890.265
-Compression: Asl,com = 829.3805
-Middle: Asl,mid = 402.1239
Mean Diameter of Tension Reinforcement, DbL = 18.18182

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u,R = 1.0^*$ $u = 0.00112653$
 $u = y + p = 0.00112653$

- Calculation of y -

$y = (My * Ls / 3) / Eleff = 0.00112653$ ((4.29), Biskinis Phd))
My = 4.5015E+008
Ls = M/V (with Ls > 0.1*L and Ls < 2*L) = 300.00
From table 10.5, ASCE 41_17: Eleff = factor * Ec * Ig = 3.9959E+013
factor = 0.30
Ag = 160000.00
fc' = 33.00
N = 6361.069
Ec * Ig = 1.3320E+014

Calculation of Yielding Moment My

Calculation of y and My according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 4.9172287E-006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 311.2112$
d = 557.00
y = 0.43186761
A = 0.03718321
B = 0.02864736
with pt = 0.02594493
pc = 0.00744507
pv = 0.00360973
N = 6361.069
b = 200.00
" = 0.07719928
 $y_{comp} = 9.2351909E-006$
with fc* (12.3, (ACI 440)) = 33.28275
fc = 33.00
fl = 0.73070932
b = bmax = 600.00
h = hmax = 400.00
Ag = 160000.00
g = pt + pc + pv = 0.03699973
rc = 40.00
Ae/Ac = 0.27772029
Effective FRP thickness, tf = NL*t*cos(b1) = 1.016
effective strain from (12.5) and (12.12), efe = 0.004
fu = 0.01
Ef = 64828.00
Ec = 26999.444
y = 0.431356
A = 0.03687106

B = 0.02846388
with Es = 200000.00

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

- Calculation of ρ -

From table 10-8: $\rho = 0.00$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$
shear control ratio $V_{yE}/V_{CoIE} = 1.00732$

$d = 557.00$

$s = 0.00$

$t = A_v/(b_w*s) + 2*t_f/b_w*(f_{fe}/f_s) = A_v*L_{stir}/(A_g*s) + 2*t_f/b_w*(f_{fe}/f_s) = 0.00$

$A_v = 78.53982$, is the area of every stirrup

$L_{stir} = 1360.00$, is the total Length of all stirrups parallel to loading (shear) direction

The term $2*t_f/b_w*(f_{fe}/f_s)$ is implemented to account for FRP contribution

where $f = 2*t_f/b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe}/f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$NUD = 6361.069$

$A_g = 160000.00$

$f_{cE} = 33.00$

$f_{ytE} = f_{ylE} = 0.00$

$\rho_l = \text{Area_Tot_Long_Rein}/(b*d) = 0.03699973$

$b = 200.00$

$d = 557.00$

$f_{cE} = 33.00$

End Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 9

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rdcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE41-17).

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = l_b/d = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -1.5643E+007$

Shear Force, $V_a = -5181.087$

EDGE -B-

Bending Moment, $M_b = 96939.725$

Shear Force, $V_b = 5181.087$

BOTH EDGES

Axial Force, $F = -6416.475$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{s,ten} = 2890.265$

-Compression: $A_{s,com} = 829.3805$

-Middle: $A_{s,mid} = 402.1239$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.18182$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 379291.423$

V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{CoI0} = 379291.423$

$V_{CoI} = 379291.423$

$k_n = 1.00$

displacement_ductility_demand = 0.01102969

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 25.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 1.5643E+007$

$V_u = 5181.087$

$d = 0.8 \cdot h = 480.00$

$N_u = 6416.475$

$A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 502654.825$

where:

$V_{s1} = 125663.706$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.625$

$V_{s2} = 376991.118$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.20833333$

V_f ((11-3)-(11.4), ACI 440) = 293495.545

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = 45^\circ + 90^\circ = 135^\circ$

$V_f = \text{Min}(|V_f(45^\circ, \alpha_1)|, |V_f(-45^\circ, \alpha_1)|)$, with:

total thickness per orientation, $t_{f1} = N_L \cdot t / N_{oDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 318865.838$

$b_w = 200.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 3 and integ. section (a)

From analysis, chord rotation $\theta = 0.00012505$
 $y = (M_y * L_s / 3) / E_{eff} = 0.01133777$ ((4.29), Biskinis Phd))
 $M_y = 4.5016E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 3019.223
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 3.9959E+013$
factor = 0.30
 $A_g = 160000.00$
 $f_c' = 33.00$
 $N = 6416.475$
 $E_c * I_g = 1.3320E+014$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 4.9173110E-006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (l_b / d)^{2/3}) = 311.2112$
 $d = 557.00$
 $y = 0.43187711$
 $A = 0.03718481$
 $B = 0.02864896$
with $pt = 0.02594493$
 $pc = 0.00744507$
 $pv = 0.00360973$
 $N = 6416.475$
 $b = 200.00$
 $\lambda = 0.07719928$
 $y_{comp} = 9.2350821E-006$
with $f_c' (12.3, (ACI 440)) = 33.28275$
 $f_c = 33.00$
 $f_l = 0.73070932$
 $b = b_{max} = 600.00$
 $h = h_{max} = 400.00$
 $A_g = 160000.00$
 $g = pt + pc + pv = 0.03699973$
 $rc = 40.00$
 $A_e / A_c = 0.27772029$
Effective FRP thickness, $t_f = NL * t * \text{Cos}(b_1) = 1.016$
effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.43136109$
 $A = 0.03686994$
 $B = 0.02846388$
with $E_s = 200000.00$

Calculation of ratio l_b / d

Inadequate Lap Length with $l_b / d = 0.30$

End Of Calculation of Shear Capacity for element: column LC1 of floor 1
At local axis: 2
Integration Section: (a)

Calculation No. 10

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ_r)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rdcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 * f_{sm} = 694.45$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.06029

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = -0.00026803$
EDGE -B-
Shear Force, $V_b = 0.00026803$
BOTH EDGES
Axial Force, $F = -6093.866$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 0.00$
-Compression: $A_{sc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 829.3805$
-Compression: $A_{st,com} = 1746.726$
-Middle: $A_{st,mid} = 1545.664$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.71033407$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 206445.557$
with
 $M_{pr1} = \text{Max}(Mu_{1+} , Mu_{1-}) = 3.0967E+008$
 $Mu_{1+} = 1.8333E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $Mu_{1-} = 3.0967E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+} , Mu_{2-}) = 3.0967E+008$
 $Mu_{2+} = 1.8333E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $Mu_{2-} = 3.0967E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.7539345E-005$
 $M_u = 1.8333E+008$

with full section properties:
 $b = 600.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0008621$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$\text{we ((5.4c), TBDY)} = a_s e^* \text{sh}_{\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cos(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

$$A_{\text{sec}} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$$

$$L_{\text{stir}} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

$$A_{\text{sec}} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft1 = 466.8167$$

$$fy1 = 389.0139$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs1 = fs = 389.0139$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 466.8167$$

$$fy2 = 389.0139$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs2 = fs = 389.0139$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.8167$$

$$fyv = 389.0139$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.0456442$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.09612944$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.08506418$$

and confined core properties:

$$b = 540.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 34.98946$$

$$cc (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = Asl,ten / (b * d) * (fs1 / fc) = 0.0553686$$

$$2 = Asl,com / (b * d) * (fs2 / fc) = 0.11660962$$

$$v = Asl,mid / (b * d) * (fsv / fc) = 0.10318693$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.18231057$$

$$Mu = MRc (4.14) = 1.8333E+008$$

$$u = s_u(4.1) = 1.7539345E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_1

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 2.4056447E-005$$

$$\mu = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$\alpha(5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \mu: \mu = \text{shear_factor} * \text{Max}(\mu_c, \mu_s) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.01306815$$

$$\mu_s \text{ ((5.4c), TBDY) } = \alpha * s_{h,\min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = \alpha * \rho_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $\alpha_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$\alpha_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } \rho_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{fe} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $\alpha_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$\alpha_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } \rho_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{fe} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = NL * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$\alpha_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

AnoConf = 79733.333 is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} = \text{Min}(psh_x, psh_y) = 0.00471239$

Expression ((5.4d), TBDY) for psh_{min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $psh_x \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $psh_y \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

$c = \text{confinement factor} = 1.06029$

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu_{2,nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$su_v = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_v = 0.4 * esu_{v,nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu_{v,nominal} = 0.08$,

considering characteristic value $fsy_v = fs_v/1.2$, from table 5.1, TBDY
For calculation of $esu_{v,nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsy_v = fs_v/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{sv} = f_s = 389.0139$
with $E_{sv} = E_s = 200000.00$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.28838833$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13693259$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.25519255$

and confined core properties:

$b = 140.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.44977996$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.21356459$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.39800673$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$su (4.8) = 0.4038298$
 $Mu = MRc (4.15) = 3.0967E+008$
 $u = su (4.1) = 2.4056447E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.7539345E-005$
 $Mu = 1.8333E+008$

with full section properties:

$b = 600.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0008621$
 $N = 6093.866$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $cu = 0.01306815$
 $w_e ((5.4c), TBDY) = a_{se} * sh_{,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{f,e} = 768.6287$

$f_y = 0.0528506$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

af = 0.22333333
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
bmax = 600.00
hmax = 400.00
From EC8 A.4.4.3(6), pf = $2t_f/b_w = 0.01016$
bw = 200.00
effective stress from (A.35), ff,e = 768.6287

R = 40.00
Effective FRP thickness, tf = $NL*t*Cos(b1) = 1.016$
fu,f = 1055.00
Ef = 64828.00
u,f = 0.015

ase = $Max(((A_{conf,max}-A_{noConf})/A_{conf,max})*(A_{conf,min}/A_{conf,max}),0) = 0.14681846$
The definitions of AnoConf, Aconf,min and Aconf,max are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

Aconf,max = 103600.00 is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

Aconf,min = 66025.00 is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area Aconf,max by a length equal to half the clear spacing between hoops.

AnoConf = 79733.333 is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

psh,min = $Min(psh,x, psh,y) = 0.00471239$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x ((5.4d), TBDY) = $L_{stir}*A_{stir}/(A_{sec}*s) = 0.00471239$
Lstir (Length of stirrups along Y) = 1360.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = $L_{stir}*A_{stir}/(A_{sec}*s) = 0.00667588$
Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00
fywe = 694.45
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287
c = confinement factor = 1.06029

y1 = 0.00140044
sh1 = 0.0044814

ft1 = 466.8167
fy1 = 389.0139

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

su1 = $0.4*es_{1_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: es_{1_nominal} = 0.08,

For calculation of es_{1_nominal} and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044
sh2 = 0.0044814

ft2 = 466.8167
fy2 = 389.0139

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.8167

fyv = 389.0139

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.0456442

2 = Asl,com/(b*d)*(fs2/fc) = 0.09612944

v = Asl,mid/(b*d)*(fsv/fc) = 0.08506418

and confined core properties:

b = 540.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

1 = Asl,ten/(b*d)*(fs1/fc) = 0.0553686

2 = Asl,com/(b*d)*(fs2/fc) = 0.11660962

v = Asl,mid/(b*d)*(fsv/fc) = 0.10318693

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.18231057

Mu = MRc (4.14) = 1.8333E+008

u = su (4.1) = 1.7539345E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 2.4056447E-005

Mu = 3.0967E+008

with full section properties:

b = 200.00

d = 357.00

d' = 43.00

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_{se} * s_{h,min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$sh1 = 0.0044814$
 $ft1 = 466.8167$
 $fy1 = 389.0139$
 $su1 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 0.30$
 $su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1$, $sh1,ft1,fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1$, $sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.
 with $fs1 = fs = 389.0139$
 with $Es1 = Es = 200000.00$
 $y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 466.8167$
 $fy2 = 389.0139$
 $su2 = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/lb,min = 0.30$
 $su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2$, $sh2,ft2,fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1$, $sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.
 with $fs2 = fs = 389.0139$
 with $Es2 = Es = 200000.00$
 $yv = 0.00140044$
 $shv = 0.0044814$
 $ftv = 466.8167$
 $fyv = 389.0139$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 0.30$
 $suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1$, $sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.
 with $fsv = fs = 389.0139$
 with $Esv = Es = 200000.00$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.28838833$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.13693259$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.25519255$
 and confined core properties:
 $b = 140.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = Asl,ten/(b*d)*(fs1/fc) = 0.44977996$
 $2 = Asl,com/(b*d)*(fs2/fc) = 0.21356459$
 $v = Asl,mid/(b*d)*(fsv/fc) = 0.39800673$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is not satisfied
 --->
 $v < vs,c$ - RHS eq.(4.5) is satisfied

--->

$$s_u(4.8) = 0.4038298$$

$$M_u = M_{Rc}(4.15) = 3.0967E+008$$

$$u = s_u(4.1) = 2.4056447E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 290631.642$

Calculation of Shear Strength at edge 1, $V_{r1} = 290631.642$

$$V_{r1} = V_{Col}((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$$

$$V_{Col0} = 290631.642$$

$$k_{nl} = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$f'_c = 33.00, \text{ but } f'_c^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 4.00$$

$$M_u = 11.70883$$

$$V_u = 0.00026803$$

$$d = 0.8 \cdot h = 320.00$$

$$N_u = 6093.866$$

$$A_g = 80000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 418882.372$$

where:

$V_{s1} = 279254.914$ is calculated for section web, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 139627.457$ is calculated for section flange, with:

$$d = 160.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

V_{s2} is multiplied by $Col2 = 1.00$

$$s/d = 0.625$$

$$V_f((11-3)-(11.4), ACI 440) = 188111.148$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

$$\text{orientation 1: } \theta = \theta_1 + 90^\circ = 90.00$$

$$V_f = \text{Min}(|V_f(45, \theta_1)|, |V_f(-45, a_1)|), \text{ with:}$$

$$\text{total thickness per orientation, } t_{f1} = N_L \cdot t / N_{oDir} = 1.016$$

$$d_{fv} = d \text{ (figure 11.2, ACI 440)} = 357.00$$

$$f_{fe}((11-5), ACI 440) = 259.312$$

$$E_f = 64828.00$$

$$f_e = 0.004, \text{ from (11.6a), ACI 440}$$

$$\text{with } f_u = 0.01$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 244232.638$$

$$b_w = 200.00$$

Calculation of Shear Strength at edge 2, $V_{r2} = 290631.642$

$$Vr2 = VCol \text{ ((10.3), ASCE 41-17)} = knl * VCol0$$

$$VCol0 = 290631.642$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

$$= 1 \text{ (normal-weight concrete)}$$

$$fc' = 33.00, \text{ but } fc^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 4.00$$

$$Mu = 11.914$$

$$Vu = 0.00026803$$

$$d = 0.8 * h = 320.00$$

$$Nu = 6093.866$$

$$Ag = 80000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } Vs = Vs1 + Vs2 = 418882.372$$

where:

Vs1 = 279254.914 is calculated for section web, with:

$$d = 320.00$$

$$Av = 157079.633$$

$$fy = 555.56$$

$$s = 100.00$$

Vs1 is multiplied by Col1 = 1.00

$$s/d = 0.3125$$

Vs2 = 139627.457 is calculated for section flange, with:

$$d = 160.00$$

$$Av = 157079.633$$

$$fy = 555.56$$

$$s = 100.00$$

Vs2 is multiplied by Col2 = 1.00

$$s/d = 0.625$$

$$Vf \text{ ((11-3)-(11.4), ACI 440)} = 188111.148$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

wf/sf = 1 (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,

where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\alpha, a)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

$$\text{orientation 1: } \alpha = b1 + 90^\circ = 90.00$$

$$Vf = \text{Min}(|Vf(45, a1)|, |Vf(-45, a1)|), \text{ with:}$$

$$\text{total thickness per orientation, } tf1 = NL * t / NoDir = 1.016$$

$$dfv = d \text{ (figure 11.2, ACI 440)} = 357.00$$

$$ffe \text{ ((11-5), ACI 440)} = 259.312$$

$$Ef = 64828.00$$

$$fe = 0.004, \text{ from (11.6a), ACI 440}$$

$$\text{with } fu = 0.01$$

$$\text{From (11-11), ACI 440: } Vs + Vf \leq 244232.638$$

$$bw = 200.00$$

End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Secondary Member: Concrete Strength, $fc = fcm = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
New material: Steel Strength, $f_s = 1.25*f_{sm} = 694.45$

Max Height, $H_{max} = 400.00$
Min Height, $H_{min} = 200.00$
Max Width, $W_{max} = 600.00$
Min Width, $W_{min} = 200.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.06029
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $N_{oDir} = 1$
Fiber orientations, $b_i: 0.00^\circ$
Number of layers, $N_L = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 0.00069415$
EDGE -B-
Shear Force, $V_b = -0.00069415$
BOTH EDGES
Axial Force, $F = -6093.866$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 0.00$
-Compression: $A_{sl,c} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 2890.265$
-Compression: $A_{sl,com} = 829.3805$
-Middle: $A_{sl,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.00732$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 438835.425$
with
 $M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 6.5825E+008$
 $M_{u1+} = 6.5825E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u1-} = 2.1740E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 6.5825E+008$
 $M_{u2+} = 6.5825E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u2-} = 2.1740E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment

direction which is defined for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.4829616E-005$$

$$\mu_{1+} = 6.5825E+008$$

with full section properties:

$$b = 200.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00165765$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_o) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_{se} * s_{h,min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cos(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_{se} = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

Lstir (Length of stirrups along Y) = 1360.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = Lstir*Astir/(Asec*s) = 0.00667588
Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00
fywe = 694.45
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287
c = confinement factor = 1.06029

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 466.8167
fy1 = 389.0139
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 466.8167
fy2 = 389.0139
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665

2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469

v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258

and confined core properties:

$b = 140.00$
 $d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.46179611$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.13251541$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.06424989$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->
 $\mu_u (4.8) = 0.38015251$
 $M_u = M_{Rc} (4.15) = 6.5825E+008$
 $u = \mu_u (4.1) = 1.4829616E-005$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of μ_{u1} -

 Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$u = 1.0664224E-005$
 $\mu_u = 2.1740E+008$

 with full section properties:

$b = 400.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00082883$
 $N = 6093.866$
 $f_c = 33.00$
 $cc (5A.5, TBDY) = 0.002$
 Final value of μ_u : $\mu_u^* = \text{shear_factor} * \text{Max}(\mu_u, cc) = 0.01306815$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $\mu_u = 0.01306815$
 $\mu_{we} ((5.4c), TBDY) = a_{se} * \text{sh}_{,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
 where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{fe} = 768.6287$

 $f_y = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$

effective stress from (A.35), $f_{f,e} = 768.6287$

$R = 40.00$

Effective FRP thickness, $t_f = NL \cdot t \cdot \cos(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{f} = 0.015$

$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) \cdot (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{\text{stir}} \cdot A_{\text{stir}} / (A_{\text{sec}} \cdot s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{\text{stir}} \cdot A_{\text{stir}} / (A_{\text{sec}} \cdot s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su_1 = 0.4 \cdot esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fsv = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $Asl_{ten}/(b \cdot d) \cdot (fs_1/fc) = 0.04388235$

2 = $Asl_{com}/(b \cdot d) \cdot (fs_2/fc) = 0.15292333$

v = $Asl_{mid}/(b \cdot d) \cdot (fsv/fc) = 0.02127629$

and confined core properties:

b = 340.00

d = 527.00

d' = 13.00

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

c = confinement factor = 1.06029

1 = $Asl_{ten}/(b \cdot d) \cdot (fs_1/fc) = 0.05456517$

2 = $Asl_{com}/(b \cdot d) \cdot (fs_2/fc) = 0.19015134$

v = $Asl_{mid}/(b \cdot d) \cdot (fsv/fc) = 0.02645584$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.13804321$

$Mu = MRc (4.14) = 2.1740E+008$

$u = su (4.1) = 1.0664224E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.4829616E-005$

$Mu = 6.5825E+008$

with full section properties:

b = 200.00

d = 557.00

d' = 43.00

v = 0.00165765

N = 6093.866

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01306815$

w_e ((5.4c), TBDY) = $ase * sh_{min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$

where $f = af * pf * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2t_f / b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{f,e} = 768.6287$

$f_y = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2t_f / b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{f,e} = 768.6287$

$R = 40.00$

Effective FRP thickness, $t_f = NL * t * \text{Cos}(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{f} = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 466.8167

fy2 = 389.0139

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.8167

fyv = 389.0139

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665

2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469

v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258

and confined core properties:

b = 140.00

d = 527.00

d' = 13.00

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

1 = Asl,ten/(b*d)*(fs1/fc) = 0.46179611

2 = Asl,com/(b*d)*(fs2/fc) = 0.13251541

v = Asl,mid/(b*d)*(fsv/fc) = 0.06424989

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is not satisfied

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.8) = 0.38015251

Mu = MRc (4.15) = 6.5825E+008

u = su (4.1) = 1.4829616E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0664224E-005$$

$$\mu_2 = 2.1740E+008$$

with full section properties:

$$b = 400.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00082883$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_{se} * s_{h,\min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t \cos(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without

earthquake detailing (90° closed stirrups)

$$\text{psh}_x \text{ ((5.4d), TBDY)} = \text{Lstir} * \text{Astir} / (\text{Asec} * s) = 0.00471239$$

$$\text{Lstir (Length of stirrups along Y)} = 1360.00$$

$$\text{Astir (stirrups area)} = 78.53982$$

$$\text{Asec (section area)} = 160000.00$$

$$\text{psh}_y \text{ ((5.4d), TBDY)} = \text{Lstir} * \text{Astir} / (\text{Asec} * s) = 0.00667588$$

$$\text{Lstir (Length of stirrups along X)} = 960.00$$

$$\text{Astir (stirrups area)} = 78.53982$$

$$\text{Asec (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs_1 = fs = 389.0139$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu_{2,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs_2 = fs = 389.0139$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$su_v = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$su_v = 0.4 * esuv_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

$$\text{with } Esv = Es = 200000.00$$

$$1 = \text{Asl,ten} / (b * d) * (fs_1 / fc) = 0.04388235$$

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.15292333$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.02127629$$

and confined core properties:

$$b = 340.00$$

$$d = 527.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05456517$$

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.19015134$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.02645584$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.13804321$$

$$M_u = M_{Rc} (4.14) = 2.1740E+008$$

$$u = s_u (4.1) = 1.0664224E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 435646.093$

Calculation of Shear Strength at edge 1, $V_{r1} = 435646.093$

$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = k_{nl} * V_{Co10}$

$$V_{Co10} = 435646.093$$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f * V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$f_c' = 33.00, \text{ but } f_c^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 4.00$$

$$M_u = 44.9328$$

$$V_u = 0.00069415$$

$$d = 0.8 * h = 480.00$$

$$N_u = 6093.866$$

$$A_g = 120000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } V_s = V_{s1} + V_{s2} = 558509.829$$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$$d = 160.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.625$$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$$d = 480.00$$

$$A_v = 157079.633$$

$$f_y = 555.56$$

$$s = 100.00$$

V_{s2} is multiplied by $Col2 = 1.00$

$$s/d = 0.20833333$$

$$V_f ((11-3)-(11.4), ACI 440) = 293495.545$$

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,

where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta_1 = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a_1)|)$, with:

total thickness per orientation, $t_{f1} = NL \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 366348.956$

$b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 435646.093$

$V_{r2} = V_{Col}$ ((10.3), ASCE 41-17) = $k_{nl} \cdot V_{Col0}$

$V_{Col0} = 435646.093$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+ f} \cdot V_f$ ' where V_f is the contribution of FRPs (11.3), ACI 440).

$\beta = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/d = 4.00$

$\mu_u = 44.60048$

$\nu_u = 0.00069415$

$d = 0.8 \cdot h = 480.00$

$N_u = 6093.866$

$A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.625$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $\text{Col2} = 1.00$

$s/d = 0.20833333$

V_f ((11-3)-(11.4), ACI 440) = 293495.545

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin a$ which is more a generalised expression, where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta_1 = b_1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a_1)|)$, with:

total thickness per orientation, $t_{f1} = NL \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 366348.956$

$b_w = 200.00$

End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_b/l_d = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $N_{oDir} = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $N_L = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

Bending Moment, $M = -194281.256$

Shear Force, $V_2 = -5181.087$

Shear Force, $V_3 = 93.61987$

Axial Force, $F = -6416.475$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 0.00$

-Compression: $A_{sc} = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 829.3805$

-Compression: $A_{st,com} = 1746.726$

-Middle: $A_{st,mid} = 1545.664$

Mean Diameter of Tension Reinforcement, $DbL = 18.66667$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.0485561$

$u = \gamma + \rho = 0.0485561$

- Calculation of y -

$$y = (M_y * L_s / 3) / E_{eff} = 0.0065561 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 1.3306E+008$$

$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 2075.214$$

$$\text{From table 10.5, ASCE 41-17: } E_{eff} = \text{factor} * E_c * I_g = 1.4040E+013$$

$$\text{factor} = 0.30$$

$$A_g = 160000.00$$

$$f_c' = 33.00$$

$$N = 6416.475$$

$$E_c * I_g = 4.6799E+013$$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

$$\text{flange width, } b = 600.00$$

$$\text{web width, } b_w = 200.00$$

$$\text{flange thickness, } t = 200.00$$

$$y = \text{Min}(y_{ten}, y_{com})$$

$$y_{ten} = 5.8027904E-006$$

$$\text{with ((10.1), ASCE 41-17) } f_y = \text{Min}(f_y, 1.25 * f_y * (b/d)^{2/3}) = 311.2112$$

$$d = 357.00$$

$$y = 0.24886144$$

$$A = 0.01933888$$

$$B = 0.00899303$$

$$\text{with } p_t = 0.00387199$$

$$p_c = 0.00815465$$

$$p_v = 0.00721598$$

$$N = 6416.475$$

$$b = 600.00$$

$$" = 0.12044818$$

$$y_{comp} = 2.5091513E-005$$

$$\text{with } f_c' \text{ (12.3, (ACI 440))} = 33.29607$$

$$f_c = 33.00$$

$$f_l = 0.73070932$$

$$b = b_{max} = 600.00$$

$$h = h_{max} = 400.00$$

$$A_g = 160000.00$$

$$g = p_t + p_c + p_v = 0.01924262$$

$$r_c = 40.00$$

$$A_e/A_c = 0.29079753$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$\text{effective strain from (12.5) and (12.12), } e_{fe} = 0.004$$

$$f_u = 0.01$$

$$E_f = 64828.00$$

$$E_c = 26999.444$$

$$y = 0.24780813$$

$$A = 0.01917515$$

$$B = 0.00889677$$

$$\text{with } E_s = 200000.00$$

CONFIRMATION: $y = 0.24825976 < t/d$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.042$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$

shear control ratio $V_{yE}/V_{CoI0E} = 0.71033407$

$d = 357.00$

$s = 0.00$

$t = A_v/(b_w*s) + 2*t_f/b_w*(f_{fe}/f_s) = A_v*L_{stir}/(A_g*s) + 2*t_f/b_w*(f_{fe}/f_s) = 0.00$

$A_v = 78.53982$, is the area of every stirrup

$L_{stir} = 960.00$, is the total Length of all stirrups parallel to loading (shear) direction

The term $2*t_f/b_w*(f_{fe}/f_s)$ is implemented to account for FRP contribution

where $f = 2*t_f/b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe}/f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$NUD = 6416.475$

$A_g = 160000.00$

$f_{cE} = 33.00$

$f_{yE} = f_{yI} = 0.00$

$\rho_l = \text{Area_Tot_Long_Rein}/(b*d) = 0.01924262$

$b = 600.00$

$d = 357.00$

$f_{cE} = 33.00$

End Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 11

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (a)
Section Type: rdcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$
Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE41-17.
Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$
New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$
Concrete Elasticity, $E_c = 26999.444$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of γ for displacement ductility demand,
the expected (mean value) strengths are used (7.5.1.3, ASCE41-17) because bending is considered as
Deformation-Controlled Action (Table C7-1, ASCE41-17).
New material: Concrete Strength, $f_c = f_{cm} = 33.00$
New material: Steel Strength, $f_s = f_{sm} = 555.56$

Max Height, $H_{max} = 400.00$
Min Height, $H_{min} = 200.00$
Max Width, $W_{max} = 600.00$
Min Width, $W_{min} = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, $t = 1.016$
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi: 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -194281.256$
Shear Force, $V_a = 93.61987$
EDGE -B-
Bending Moment, $M_b = -85504.326$
Shear Force, $V_b = -93.61987$
BOTH EDGES
Axial Force, $F = -6416.475$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 0.00$
-Compression: $As_c = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 829.3805$
-Compression: $As_{l,com} = 1746.726$
-Middle: $As_{l,mid} = 1545.664$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.66667$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 253072.019$
 V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{CoIO} = 253072.019$
 $V_{CoI} = 253072.019$
 $k_n = 1.00$
displacement_ductility_demand = 0.00765501

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 $f_c' = 25.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $M_u = 194281.256$
 $V_u = 93.61987$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6416.475$
 $A_g = 80000.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 376991.118$
where:
 $V_{s1} = 251327.412$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 125663.706$ is calculated for section flange, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.625$
 V_f ((11-3)-(11.4), ACI 440) = 188111.148
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
where a is the angle of the crack direction (see KANEPE).
This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
total thickness per orientation, $t_{f1} = N_L \cdot t / N_{Dir} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 357.00
 f_{fe} ((11-5), ACI 440) = 259.312
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
with $f_u = 0.01$
From (11-11), ACI 440: $V_s + V_f \leq 212577.225$
 $b_w = 200.00$

displacement_ductility_demand is calculated as δ / y

- Calculation of δ / y for END A -
for rotation axis 2 and integ. section (a)

From analysis, chord rotation $\theta = 5.0186994E-005$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.0065561$ ((4.29), Biskinis Phd)
 $M_y = 1.3306E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 2075.214
From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} \cdot E_c \cdot I_g = 1.4040E+013$
factor = 0.30
 $A_g = 160000.00$
 $f_c' = 33.00$
 $N = 6416.475$

$$E_c \cdot I_g = 4.6799E+013$$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, $b = 600.00$

web width, $b_w = 200.00$

flange thickness, $t = 200.00$

$$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$$

$$y_{\text{ten}} = 5.8027904E-006$$

$$\text{with } ((10.1), \text{ASCE 41-17}) f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 311.2112$$

$$d = 357.00$$

$$y = 0.24886144$$

$$A = 0.01933888$$

$$B = 0.00899303$$

$$\text{with } p_t = 0.00387199$$

$$p_c = 0.00815465$$

$$p_v = 0.00721598$$

$$N = 6416.475$$

$$b = 600.00$$

$$" = 0.12044818$$

$$y_{\text{comp}} = 2.5091513E-005$$

$$\text{with } f_c^* (12.3, \text{ACI 440}) = 33.29607$$

$$f_c = 33.00$$

$$f_l = 0.73070932$$

$$b = b_{\text{max}} = 600.00$$

$$h = h_{\text{max}} = 400.00$$

$$A_g = 160000.00$$

$$g = p_t + p_c + p_v = 0.01924262$$

$$r_c = 40.00$$

$$A_e/A_c = 0.29079753$$

$$\text{Effective FRP thickness, } t_f = N_L \cdot t \cdot \text{Cos}(b_1) = 1.016$$

$$\text{effective strain from (12.5) and (12.12), } \epsilon_{fe} = 0.004$$

$$f_u = 0.01$$

$$E_f = 64828.00$$

$$E_c = 26999.444$$

$$y = 0.24780813$$

$$A = 0.01917515$$

$$B = 0.00889677$$

$$\text{with } E_s = 200000.00$$

CONFIRMATION: $y = 0.24825976 < t/d$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

End Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 12

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rdcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.06029

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $\epsilon_{fu} = 0.01$

Number of directions, $N_{oDir} = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $N_L = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -0.00026803$

EDGE -B-

Shear Force, $V_b = 0.00026803$

BOTH EDGES

Axial Force, $F = -6093.866$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 0.00$

-Compression: $A_{sl,c} = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 829.3805$

-Compression: $A_{sl,com} = 1746.726$

-Middle: $A_{sl,mid} = 1545.664$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.71033407$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 206445.557$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 3.0967E+008$

$M_{u1+} = 1.8333E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 3.0967E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 3.0967E+008$

$M_{u2+} = 1.8333E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination

$M_{u2-} = 3.0967E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7539345E-005$

$M_u = 1.8333E+008$

with full section properties:

$b = 600.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0008621$

$N = 6093.866$

$f_c = 33.00$

$\omega (5A.5, \text{TBDY}) = 0.002$

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01306815$

w_e ((5.4c), TBDY) = $ase * sh_{min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$

where $f = af * pf * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area})/(\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $f_{f,e} = 768.6287$

$f_y = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area})/(\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf/bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $f_{f,e} = 768.6287$

$R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{f} = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf})/A_{conf,max}) * (A_{conf,min}/A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 466.8167

fy2 = 389.0139

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.8167

fyv = 389.0139

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.0456442

2 = Asl,com/(b*d)*(fs2/fc) = 0.09612944

v = Asl,mid/(b*d)*(fsv/fc) = 0.08506418

and confined core properties:

b = 540.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

1 = Asl,ten/(b*d)*(fs1/fc) = 0.0553686

2 = Asl,com/(b*d)*(fs2/fc) = 0.11660962

v = Asl,mid/(b*d)*(fsv/fc) = 0.10318693

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.18231057

Mu = MRc (4.14) = 1.8333E+008

u = su (4.1) = 1.7539345E-005

Calculation of ratio lb/d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 2.4056447E-005$$

$$\mu_1 = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} = \text{Max}(((A_{conf,max}-A_{noConf})/A_{conf,max}) * (A_{conf,min}/A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$
Lstir (Length of stirrups along Y) = 1360.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$
Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00
fywe = 694.45
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287
c = confinement factor = 1.06029

y1 = 0.00140044
sh1 = 0.0044814

ft1 = 466.8167
fy1 = 389.0139

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

su1 = $0.4 * esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044
sh2 = 0.0044814

ft2 = 466.8167
fy2 = 389.0139

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = $0.4 * esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044
shv = 0.0044814

ftv = 466.8167
fyv = 389.0139

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 0.30

suv = $0.4 * esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $Min(1, 1.25 * (lb/lb)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = $Asl,ten / (b * d) * (fs1 / fc) = 0.28838833$

2 = $Asl,com / (b * d) * (fs2 / fc) = 0.13693259$

v = $Asl,mid / (b * d) * (fsv / fc) = 0.25519255$

and confined core properties:

$$b = 140.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 34.98946$$

$$cc (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.44977996$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.21356459$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.39800673$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.4038298$$

$$M_u = M_{Rc} (4.15) = 3.0967E+008$$

$$u = s_u (4.1) = 2.4056447E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of M_{u2+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 1.7539345E-005$$

$$M_u = 1.8333E+008$$

with full section properties:

$$b = 600.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0008621$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

bw = 200.00
effective stress from (A.35), $f_{f,e} = 768.6287$

R = 40.00
Effective FRP thickness, $t_f = NL * t * \cos(b_1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$

$a_{se} = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete." J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

s = 100.00
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$
c = confinement factor = 1.06029

$y_1 = 0.00140044$
 $sh_1 = 0.0044814$
 $ft_1 = 466.8167$
 $fy_1 = 389.0139$
 $su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $E_{s1} = E_s = 200000.00$

$y_2 = 0.00140044$
 $sh_2 = 0.0044814$
 $ft_2 = 466.8167$
 $fy_2 = 389.0139$
 $su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered

characteristic value $f_{s2} = f_s/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{s2} = f_s = 389.0139$

with $E_{s2} = E_s = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$f_{y_v} = 389.0139$

$s_{u_v} = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,

considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered

characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{s_v} = f_s = 389.0139$

with $E_{s_v} = E_s = 200000.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.0456442$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.09612944$

$v = As_{l,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.08506418$

and confined core properties:

$b = 540.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c =$ confinement factor = 1.06029

1 = $As_{l,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.0553686$

2 = $As_{l,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.11660962$

$v = As_{l,mid}/(b \cdot d) \cdot (f_{s_v}/f_c) = 0.10318693$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$s_u (4.9) = 0.18231057$

$M_u = MR_c (4.14) = 1.8333E+008$

$u = s_u (4.1) = 1.7539345E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of M_{u2} -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$u = 2.4056447E-005$

$M_u = 3.0967E+008$

with full section properties:

$b = 200.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00258631$

$N = 6093.866$

$f_c = 33.00$

$cc (5A.5, TBDY) = 0.002$

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, cc) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.01306815$

we ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ff_e = 768.6287$

 $f_y = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ff_e = 768.6287$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 $p_{sh,x}$ ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $p_{sh,y}$ ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $s = 100.00$

$fy_{we} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

$c = \text{confinement factor} = 1.06029$

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 466.8167

fy2 = 389.0139

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.8167

fyv = 389.0139

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.28838833

2 = Asl,com/(b*d)*(fs2/fc) = 0.13693259

v = Asl,mid/(b*d)*(fsv/fc) = 0.25519255

and confined core properties:

b = 140.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

1 = Asl,ten/(b*d)*(fs1/fc) = 0.44977996

2 = Asl,com/(b*d)*(fs2/fc) = 0.21356459

v = Asl,mid/(b*d)*(fsv/fc) = 0.39800673

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is not satisfied

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.8) = 0.4038298

Mu = MRc (4.15) = 3.0967E+008

u = su (4.1) = 2.4056447E-005

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 290631.642$

Calculation of Shear Strength at edge 1, $V_{r1} = 290631.642$

$V_{r1} = V_{Col} \text{ ((10.3), ASCE 41-17)} = k_{nl} * V_{Col0}$

$V_{Col0} = 290631.642$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_s + f * V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

$\rho = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 11.70883$

$V_u = 0.00026803$

$d = 0.8 * h = 320.00$

$N_u = 6093.866$

$A_g = 80000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$

where:

$V_{s1} = 279254.914$ is calculated for section web, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $\text{Col1} = 1.00$

$s/d = 0.3125$

$V_{s2} = 139627.457$ is calculated for section flange, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $\text{Col2} = 1.00$

$s/d = 0.625$

$V_f \text{ ((11-3)-(11.4), ACI 440)} = 188111.148$

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \cot \alpha) \sin \alpha$ which is more a generalised expression,
where θ is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, \theta)|)$, with:

total thickness per orientation, $t_{f1} = N_L * t / N_{oDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

$f_{fe} \text{ ((11-5), ACI 440)} = 259.312$

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 244232.638$

$b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 290631.642$

$V_{r2} = V_{Col} \text{ ((10.3), ASCE 41-17)} = k_{nl} * V_{Col0}$

$V_{Col0} = 290631.642$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_s + f * V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f_c' = 33.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$M_u = 11.914$

$V_u = 0.00026803$

$d = 0.8 \cdot h = 320.00$

$N_u = 6093.866$

$A_g = 80000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$

where:

$V_{s1} = 279254.914$ is calculated for section web, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.3125$

$V_{s2} = 139627.457$ is calculated for section flange, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.625$

V_f ((11-3)-(11.4), ACI 440) = 188111.148

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,

where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $t_{f1} = NL \cdot t / \text{NoDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 357.00

f_{fe} ((11-5), ACI 440) = 259.312

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 244232.638$

$b_w = 200.00$

End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.06029

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = 0.00069415$

EDGE -B-

Shear Force, $V_b = -0.00069415$

BOTH EDGES

Axial Force, $F = -6093.866$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 0.00$

-Compression: $A_{sl,c} = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 2890.265$

-Compression: $A_{sl,com} = 829.3805$

-Middle: $A_{sl,mid} = 402.1239$

Calculation of Shear Capacity ratio , $V_e/V_r = 1.00732$

Member Controlled by Shear ($V_e/V_r > 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 438835.425$

with

$M_{pr1} = \text{Max}(\mu_{u1+}, \mu_{u1-}) = 6.5825E+008$

$\mu_{u1+} = 6.5825E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$\mu_{u1-} = 2.1740E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(\mu_{u2+}, \mu_{u2-}) = 6.5825E+008$

$\mu_{u2+} = 6.5825E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{u2-} = 2.1740E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of μ_{u1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.4829616E-005$$
$$Mu = 6.5825E+008$$

with full section properties:

$$b = 200.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00165765$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$co(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu, cc) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu = 0.01306815$$

$$\omega_e(5.4c, TBDY) = a_s e^* \text{sh}_{, \min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_s = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x}((5.4d), TBDY) = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} (\text{Length of stirrups along } Y) = 1360.00$$

$$A_{\text{stir}} (\text{stirrups area}) = 78.53982$$

$$A_{\text{sec}} (\text{section area}) = 160000.00$$

$$p_{sh,y}((5.4d), TBDY) = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$$

Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00

fywe = 694.45

fce = 33.00

From ((5.A.5), TBDY), TBDY: cc = 0.00260287

c = confinement factor = 1.06029

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 466.8167

fy1 = 389.0139

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 466.8167

fy2 = 389.0139

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.8167

fyv = 389.0139

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665

2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469

v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258

and confined core properties:

b = 140.00

d = 527.00

d' = 13.00

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

1 = $Asl_{ten}/(b*d)*(fs1/fc) = 0.46179611$

2 = $Asl_{com}/(b*d)*(fs2/fc) = 0.13251541$

v = $Asl_{mid}/(b*d)*(fsv/fc) = 0.06424989$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

v < vs,y2 - LHS eq.(4.5) is not satisfied

v < vs,c - RHS eq.(4.5) is satisfied

su (4.8) = 0.38015251

Mu = MRc (4.15) = 6.5825E+008

u = su (4.1) = 1.4829616E-005

Calculation of ratio lb/l_d

Inadequate Lap Length with lb/l_d = 0.30

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0664224E-005

Mu = 2.1740E+008

with full section properties:

b = 400.00

d = 557.00

d' = 43.00

v = 0.00082883

N = 6093.866

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.01306815

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01306815

we ((5.4c), TBDY) = ase* sh,min*fywe/fce+Min(fx, fy) = 0.05721847

where f = af*pf*ffe/fce is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

fx = 0.0528506

Expression ((15B.6), TBDY) is modified as af = 1 - (Unconfined area)/(total area)

af = 0.22333333

with Unconfined area = ((bmax-2R)^2 + (hmax-2R)^2)/3 = 35733.333

bmax = 600.00

hmax = 400.00

From EC8 A.4.4.3(6), pf = 2tf/bw = 0.01016

bw = 200.00

effective stress from (A.35), ffe = 768.6287

fy = 0.0528506

Expression ((15B.6), TBDY) is modified as af = 1 - (Unconfined area)/(total area)

af = 0.22333333

with Unconfined area = ((bmax-2R)^2 + (hmax-2R)^2)/3 = 0.00

bmax = 600.00

hmax = 400.00

From EC8 A.4.4.3(6), pf = 2tf/bw = 0.01016

bw = 200.00

effective stress from (A.35), ffe = 768.6287

R = 40.00

Effective FRP thickness, tf = NL*t*Cos(b1) = 1.016

fu,f = 1055.00

$$E_f = 64828.00$$

$$u, f = 0.015$$

$$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$su_1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y_1 , sh_1 , ft_1 , fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1 , sh_1 , ft_1 , fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs_1 = fs = 389.0139$$

$$\text{with } Es_1 = Es = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$su_2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$su_2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and y_2 , sh_2 , ft_2 , fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2 , sh_2 , ft_2 , fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs_2 = fs = 389.0139$$

$$\text{with } Es_2 = Es = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$f_{tv} = 466.8167$$

$$f_{yv} = 389.0139$$

$$s_{uv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and γ_v , sh_v, f_{tv}, f_{yv} , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

γ_1 , sh_1, f_{t1}, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{sv} = f_s = 389.0139$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.04388235$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.15292333$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02127629$$

and confined core properties:

$$b = 340.00$$

$$d = 527.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.05456517$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.19015134$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02645584$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.13804321$$

$$M_u = M_{Rc} (4.14) = 2.1740E+008$$

$$u = s_u (4.1) = 1.0664224E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of M_{u2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 1.4829616E-005$$

$$M_u = 6.5825E+008$$

with full section properties:

$$b = 200.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00165765$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e ((5.4c), TBDY) = a_s e * sh_{,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area})/(\text{total area})$

$$af = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } pf = 2tf/bw = 0.01016$$

$$bw = 200.00$$

$$\text{effective stress from (A.35), } ff,e = 768.6287$$

$$fy = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area})/(\text{total area})$

$$af = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } pf = 2tf/bw = 0.01016$$

$$bw = 200.00$$

$$\text{effective stress from (A.35), } ff,e = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } tf = NL * t * \cos(b1) = 1.016$$

$$fu,f = 1055.00$$

$$Ef = 64828.00$$

$$u,f = 0.015$$

$$ase = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh_{\min} = \text{Min}(psh_x, psh_y) = 0.00471239$$

Expression ((5.4d), TBDY) for psh_{\min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh_x \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

$$A_{\text{sec}} \text{ (section area)} = 160000.00$$

$$psh_y \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$$

$$L_{\text{stir}} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

$$A_{\text{sec}} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$fy_{we} = 694.45$$

$$f_{ce} = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 466.8167$$

$$fy1 = 389.0139$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with $\text{Shear_factor} = 1.00$

$$lo/lo_{\min} = lb/d = 0.30$$

$$su1 = 0.4 * esu1_{\text{nominal}} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_{\text{nominal}} = 0.08,$$

For calculation of $esu1_{\text{nominal}}$ and $y1, sh1, ft1, fy1$, it is considered

characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{s1} = f_s = 389.0139$

with $E_{s1} = E_s = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{s2} = f_s = 389.0139$

with $E_{s2} = E_s = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$su_v = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su_v = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $f_{sv} = f_s = 389.0139$

with $E_{sv} = E_s = 200000.00$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.30584665$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.08776469$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.04255258$

and confined core properties:

$b = 140.00$

$d = 527.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

$1 = A_{sl,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.46179611$

$2 = A_{sl,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.13251541$

$v = A_{sl,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.06424989$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$su (4.8) = 0.38015251$

$Mu = MRc (4.15) = 6.5825E+008$

$u = su (4.1) = 1.4829616E-005$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Mu2-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0664224E-005$$

$$\text{Mu} = 2.1740E+008$$

with full section properties:

$$b = 400.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00082883$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_s e^* s_{h,\min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t^* \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{\text{stir}} \text{ (stirrups area)} = 78.53982$$

Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = Lstir*Astir/(Asec*s) = 0.00667588

Lstir (Length of stirrups along X) = 960.00

Astir (stirrups area) = 78.53982

Asec (section area) = 160000.00

s = 100.00

fywe = 694.45

fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287

c = confinement factor = 1.06029

y1 = 0.00140044

sh1 = 0.0044814

ft1 = 466.8167

fy1 = 389.0139

su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044

sh2 = 0.0044814

ft2 = 466.8167

fy2 = 389.0139

su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044

shv = 0.0044814

ftv = 466.8167

fyv = 389.0139

suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04388235

2 = Asl,com/(b*d)*(fs2/fc) = 0.15292333

v = Asl,mid/(b*d)*(fsv/fc) = 0.02127629

and confined core properties:

b = 340.00

d = 527.00

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 34.98946$$

$$cc (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.05456517$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.19015134$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.02645584$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs,y2$ - LHS eq.(4.5) is satisfied

$$su (4.9) = 0.13804321$$

$$Mu = MRc (4.14) = 2.1740E+008$$

$$u = su (4.1) = 1.0664224E-005$$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 435646.093$

Calculation of Shear Strength at edge 1, $Vr1 = 435646.093$

$$Vr1 = VCol ((10.3), ASCE 41-17) = knl * VCol0$$

$$VCol0 = 435646.093$$

$$knl = 1 \text{ (zero step-static loading)}$$

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$$fc' = 33.00, \text{ but } fc'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$M/Vd = 4.00$$

$$Mu = 44.9328$$

$$Vu = 0.00069415$$

$$d = 0.8 * h = 480.00$$

$$Nu = 6093.866$$

$$Ag = 120000.00$$

$$\text{From (11.5.4.8), ACI 318-14: } Vs = Vs1 + Vs2 = 558509.829$$

where:

$Vs1 = 139627.457$ is calculated for section web, with:

$$d = 160.00$$

$$Av = 157079.633$$

$$fy = 555.56$$

$$s = 100.00$$

$Vs1$ is multiplied by $Col1 = 1.00$

$$s/d = 0.625$$

$Vs2 = 418882.372$ is calculated for section flange, with:

$$d = 480.00$$

$$Av = 157079.633$$

$$fy = 555.56$$

$$s = 100.00$$

$Vs2$ is multiplied by $Col2 = 1.00$

$$s/d = 0.20833333$$

$$Vf ((11-3)-(11.4), ACI 440) = 293495.545$$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$wf/sf = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \csc)\sin\alpha$ which is more a generalised expression, where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\alpha)$, is implemented for every different fiber orientation α_i , as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b1 + 90^\circ = 90.00$

$$Vf = \text{Min}(|Vf(45, 1)|, |Vf(-45, a1)|), \text{ with:}$$

total thickness per orientation, $tf1 = NL*t/NoDir = 1.016$
 $dfv = d$ (figure 11.2, ACI 440) = 557.00
 ffe ((11-5), ACI 440) = 259.312
 $Ef = 64828.00$
 $fe = 0.004$, from (11.6a), ACI 440
with $fu = 0.01$
From (11-11), ACI 440: $Vs + Vf <= 366348.956$
 $bw = 200.00$

Calculation of Shear Strength at edge 2, $Vr2 = 435646.093$
 $Vr2 = VCol$ ((10.3), ASCE 41-17) = $knl*VColO$
 $VColO = 435646.093$
 $knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 $fc' = 33.00$, but $fc^{0.5} <= 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $Mu = 44.60048$
 $Vu = 0.00069415$
 $d = 0.8*h = 480.00$
 $Nu = 6093.866$
 $Ag = 120000.00$
From (11.5.4.8), ACI 318-14: $Vs = Vs1 + Vs2 = 558509.829$
where:

$Vs1 = 139627.457$ is calculated for section web, with:
 $d = 160.00$
 $Av = 157079.633$
 $fy = 555.56$
 $s = 100.00$

$Vs1$ is multiplied by $Col1 = 1.00$
 $s/d = 0.625$

$Vs2 = 418882.372$ is calculated for section flange, with:
 $d = 480.00$
 $Av = 157079.633$
 $fy = 555.56$
 $s = 100.00$

$Vs2$ is multiplied by $Col2 = 1.00$
 $s/d = 0.20833333$

Vf ((11-3)-(11.4), ACI 440) = 293495.545
 $f = 0.95$, for fully-wrapped sections

$wf/sf = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot\alpha)\sin\alpha$ which is more a generalised expression,
where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $Vf(\alpha)$, is implemented for every different fiber orientation α_i ,
as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b1 + 90^\circ = 90.00$

$Vf = \text{Min}(|Vf(45, \alpha)|, |Vf(-45, \alpha)|)$, with:

total thickness per orientation, $tf1 = NL*t/NoDir = 1.016$
 $dfv = d$ (figure 11.2, ACI 440) = 557.00
 ffe ((11-5), ACI 440) = 259.312
 $Ef = 64828.00$
 $fe = 0.004$, from (11.6a), ACI 440
with $fu = 0.01$
From (11-11), ACI 440: $Vs + Vf <= 366348.956$
 $bw = 200.00$

End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_b/l_d = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $N_{oDir} = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $N_L = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

Bending Moment, $M = -1.5643E+007$

Shear Force, $V_2 = -5181.087$

Shear Force, $V_3 = 93.61987$

Axial Force, $F = -6416.475$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 0.00$

-Compression: $A_{sl,c} = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 2890.265$

-Compression: $A_{sl,com} = 829.3805$

-Middle: $A_{sl,mid} = 402.1239$

Mean Diameter of Tension Reinforcement, $DbL = 18.18182$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u,R = 1.0^*$ $u = 0.05333777$

$u = \gamma + \rho = 0.05333777$

- Calculation of γ -

$\gamma = (M_y * L_s / 3) / E_{eff} = 0.01133777$ ((4.29), Biskinis Phd))

$M_y = 4.5016E+008$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 3019.223

From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} * E_c * I_g = 3.9959E+013$

factor = 0.30

$A_g = 160000.00$

$f_c' = 33.00$

$N = 6416.475$

$E_c * I_g = 1.3320E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$

$y_{ten} = 4.9173110E-006$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b/I_d)^{2/3}) = 311.2112$

$d = 557.00$

$y = 0.43187711$

$A = 0.03718481$

$B = 0.02864896$

with $p_t = 0.02594493$

$p_c = 0.00744507$

$p_v = 0.00360973$

$N = 6416.475$

$b = 200.00$

$\alpha = 0.07719928$

$y_{comp} = 9.2350821E-006$

with f_c^* (12.3, (ACI 440)) = 33.28275

$f_c = 33.00$

$f_l = 0.73070932$

$b = b_{max} = 600.00$

$h = h_{max} = 400.00$

$A_g = 160000.00$

$g = p_t + p_c + p_v = 0.03699973$

$rc = 40.00$

$A_e/A_c = 0.27772029$

Effective FRP thickness, $t_f = N L * t * \text{Cos}(b_1) = 1.016$

effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$

$f_u = 0.01$

$E_f = 64828.00$

$E_c = 26999.444$

$y = 0.43136109$

$A = 0.03686994$

$B = 0.02846388$

with $E_s = 200000.00$

Calculation of ratio I_b/I_d

Inadequate Lap Length with $I_b/I_d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.042$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $I_b/I_d \geq 1$

shear control ratio $V_y E / V_{Col} O E = 1.00732$

$d = 557.00$

$s = 0.00$

$t = A_v / (b_w * s) + 2 * t_f / b_w * (f_{fe} / f_s) = A_v * L_{stir} / (A_g * s) + 2 * t_f / b_w * (f_{fe} / f_s) = 0.00$

$A_v = 78.53982$, is the area of every stirrup

$L_{stir} = 1360.00$, is the total length of all stirrups parallel to loading (shear) direction

The term $2 * t_f / b_w * (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 * t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength


All these variables have already been given in Shear control ratio calculation.

NUD = 6416.475
Ag = 160000.00
fcE = 33.00
fytE = fylE = 0.00
pl = Area_Tot_Long_Rein/(b*d) = 0.03699973
b = 200.00
d = 557.00
fcE = 33.00

End Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 13

column C1, Floor 1
Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)
Analysis: Uniform +X
Check: Shear capacity VRd
Edge: End
Local Axis: (2)



Start Of Calculation of Shear Capacity for element: column LC1 of floor 1
At local axis: 2
Integration Section: (b)
Section Type: rclcs

Constant Properties

Knowledge Factor, $\gamma = 1.00$
Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE41-17.
Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$
New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE41-17).

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $N_{oDir} = 1$

Fiber orientations, $b_i = 0.00^\circ$

Number of layers, $N_L = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -1.5643E+007$

Shear Force, $V_a = -5181.087$

EDGE -B-

Bending Moment, $M_b = 96939.725$

Shear Force, $V_b = 5181.087$

BOTH EDGES

Axial Force, $F = -6416.475$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 0.00$

-Compression: $A_{sl,c} = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 2890.265$

-Compression: $A_{sl,com} = 829.3805$

-Middle: $A_{sl,mid} = 402.1239$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 18.18182$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 439717.009$

V_n ((10.3), ASCE 41-17) = $k_n \cdot V_{Co10} = 439717.009$

$V_{Co10} = 439717.009$

$k_n = 1.00$

displacement_ductility_demand = 0.05305065

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)

$f'_c = 25.00$, but $f'_c \cdot 0.5 \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 2.00$
 $\mu_u = 96939.725$
 $V_u = 5181.087$
 $d = 0.8 \cdot h = 480.00$
 $N_u = 6416.475$
 $A_g = 120000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 502654.825$
 where:
 $V_{s1} = 125663.706$ is calculated for section web, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.625$
 $V_{s2} = 376991.118$ is calculated for section flange, with:
 $d = 480.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.20833333$
 V_f ((11-3)-(11.4), ACI 440) = 293495.545
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = 45^\circ + 90^\circ = 135^\circ$
 $V_f = \text{Min}(|V_f(45, a_1)|, |V_f(-45, a_1)|)$, with:
 total thickness per orientation, $t_{f1} = N_L \cdot t / N_{oDir} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 557.00
 f_{fe} ((11-5), ACI 440) = 259.312
 $E_f = 64828.00$
 $f_{e1} = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 318865.838$
 $b_w = 200.00$

displacement ductility demand is calculated as δ_u / y

- Calculation of δ_u / y for END B -
 for rotation axis 3 and integ. section (b)

From analysis, chord rotation $\theta = 5.9764675E-005$
 $y = (M_y \cdot L_s / 3) / E_{eff} = 0.00112656$ ((4.29), Biskinis Phd)
 $M_y = 4.5016E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 300.00
 From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} \cdot E_c \cdot I_g = 3.9959E+013$
 factor = 0.30
 $A_g = 160000.00$
 $f_c' = 33.00$
 $N = 6416.475$
 $E_c \cdot I_g = 1.3320E+014$

Calculation of Yielding Moment M_y

Calculation of δ_u / y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 4.9173110E-006$
 with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (I_b / I_d)^{2/3}) = 311.2112$

d = 557.00
y = 0.43187711
A = 0.03718481
B = 0.02864896
with pt = 0.02594493
pc = 0.00744507
pv = 0.00360973
N = 6416.475
b = 200.00
" = 0.07719928
y_comp = 9.2350821E-006
with fc* (12.3, (ACI 440)) = 33.28275
fc = 33.00
fl = 0.73070932
b = bmax = 600.00
h = hmax = 400.00
Ag = 160000.00
g = pt + pc + pv = 0.03699973
rc = 40.00
Ae/Ac = 0.27772029
Effective FRP thickness, tf = NL*t*cos(b1) = 1.016
effective strain from (12.5) and (12.12), efe = 0.004
fu = 0.01
Ef = 64828.00
Ec = 26999.444
y = 0.43136109
A = 0.03686994
B = 0.02846388
with Es = 200000.00

Calculation of ratio lb/d

Inadequate Lap Length with lb/d = 0.30

End Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 14

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rclcs

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.06029

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $bi: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -0.00026803$

EDGE -B-

Shear Force, $V_b = 0.00026803$

BOTH EDGES

Axial Force, $F = -6093.866$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{,ten} = 829.3805$

-Compression: $As_{,com} = 1746.726$

-Middle: $As_{,mid} = 1545.664$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.71033407$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 206445.557$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.0967E+008$

$Mu_{1+} = 1.8333E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 3.0967E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.0967E+008$

$Mu_{2+} = 1.8333E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 3.0967E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7539345E-005$

$M_u = 1.8333E+008$

with full section properties:

$b = 600.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0008621$

$N = 6093.866$

$f_c = 33.00$

$\phi_{co} (5A.5, \text{TBDY}) = 0.002$

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_{co}) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.01306815$

where $\phi_u = \phi_{se} * \phi_{s,min} * f_{y,se} / f_{c,se} + \text{Min}(\phi_x, \phi_y) = 0.05721847$

where $\phi_{se} = a_f * \phi_{f,se} / f_{c,se}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$\phi_x = 0.0528506$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $\phi_{f,se} = 2t_f / b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{f,se} = 768.6287$

$\phi_y = 0.0528506$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.3(6), $pf = 2t_f/bw = 0.01016$
 $bw = 200.00$
effective stress from (A.35), $ff_e = 768.6287$

R = 40.00

Effective FRP thickness, $t_f = NL * t * \cos(b_1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{f} = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{min} = \text{Min}(psh_x, psh_y) = 0.00471239$

Expression ((5.4d), TBDY) for psh_{min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$psh_x \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$psh_y \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

s = 100.00

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$

$suv = 0.4 \cdot es_{u2_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{u2_nominal} = 0.08$,

considering characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_v = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $Asl_{ten}/(b \cdot d) \cdot (fs_1/fc) = 0.0456442$

2 = $Asl_{com}/(b \cdot d) \cdot (fs_2/fc) = 0.09612944$

v = $Asl_{mid}/(b \cdot d) \cdot (fs_v/fc) = 0.08506418$

and confined core properties:

$b = 540.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

c = confinement factor = 1.06029

1 = $Asl_{ten}/(b \cdot d) \cdot (fs_1/fc) = 0.0553686$

2 = $Asl_{com}/(b \cdot d) \cdot (fs_2/fc) = 0.11660962$

v = $Asl_{mid}/(b \cdot d) \cdot (fs_v/fc) = 0.10318693$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.18231057$

$Mu = MRc (4.14) = 1.8333E+008$

$u = su (4.1) = 1.7539345E-005$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 2.4056447E-005$

$Mu = 3.0967E+008$

with full section properties:

$b = 200.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00258631$

$N = 6093.866$

$fc = 33.00$

$co (5A.5, TBDY) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01306815$

ve ((5.4c), TBDY) = $ase * sh_{min} * fy_{we} / f_{ce} + \text{Min}(fx, fy) = 0.05721847$

where $f = af * pf * ff_e / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 35733.333$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ff_e = 768.6287$

 $fy = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{max} - 2R)^2 + (h_{max} - 2R)^2) / 3 = 0.00$

$b_{max} = 600.00$

$h_{max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ff_e = 768.6287$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$psh_{min} = \text{Min}(psh_x, psh_y) = 0.00471239$

Expression ((5.4d), TBDY) for psh_{min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 psh_x ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 psh_y ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $s = 100.00$

$fy_{we} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{su1,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,

For calculation of $e_{su1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s1} = f_s = 389.0139$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,

For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s2} = f_s = 389.0139$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$s_{uv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{sv} = f_s = 389.0139$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.28838833$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.13693259$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.25519255$$

and confined core properties:

$$b = 140.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.44977996$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.21356459$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.39800673$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.4038298$$

$$M_u = M_{Rc} (4.15) = 3.0967E+008$$

$$u = s_u (4.1) = 2.4056447E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7539345E-005$$

$$\mu = 1.8333E+008$$

with full section properties:

$$b = 600.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0008621$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$\alpha (5A.5, \text{TB DY}) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TB DY: } \mu_c = 0.01306815$$

$$\mu_{cc} \text{ ((5.4c), TB DY) } = \alpha s_e * s_{h,\min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f_x = \alpha f_p f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TB DY) is modified as $\alpha f = 1 - (\text{Unconfined area})/(\text{total area})$

$$\alpha f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TB DY) is modified as $\alpha f = 1 - (\text{Unconfined area})/(\text{total area})$

$$\alpha f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = NL * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$\alpha s_e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length

equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00471239$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00471239$$

$$Lstir \text{ (Length of stirrups along Y)} = 1360.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$psh,y \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00667588$$

$$Lstir \text{ (Length of stirrups along X)} = 960.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$fywe = 694.45$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 466.8167$$

$$fy1 = 389.0139$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs1 = fs = 389.0139$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 466.8167$$

$$fy2 = 389.0139$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs2 = fs = 389.0139$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.8167$$

$$fyv = 389.0139$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$suv = 0.4 * esuv_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

with $E_{sv} = E_s = 200000.00$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0456442$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.09612944$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.08506418$$

and confined core properties:

$$b = 540.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0553686$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11660962$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10318693$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18231057$$

$$\mu_u = M_{Rc} (4.14) = 1.8333E+008$$

$$u = s_u (4.1) = 1.7539345E-005$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

Calculation of μ_{u2} -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 2.4056447E-005$$

$$\mu_u = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

hmax = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.01016$
bw = 200.00
effective stress from (A.35), $ff,e = 768.6287$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$

$ase = \text{Max}((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}} * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

s = 100.00
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$
c = confinement factor = 1.06029

$y1 = 0.00140044$
 $sh1 = 0.0044814$

$ft1 = 466.8167$
 $fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$

$ft2 = 466.8167$
 $fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $es_{u2_nominal} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$s_{uv} = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$

$s_{uv} = 0.4 \cdot es_{uv_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{uv_nominal} = 0.08$,

considering characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_v = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (fs_1/f_c) = 0.28838833$

2 = $As_{l,com}/(b \cdot d) \cdot (fs_2/f_c) = 0.13693259$

$v = As_{l,mid}/(b \cdot d) \cdot (fs_v/f_c) = 0.25519255$

and confined core properties:

$b = 140.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

1 = $As_{l,ten}/(b \cdot d) \cdot (fs_1/f_c) = 0.44977996$

2 = $As_{l,com}/(b \cdot d) \cdot (fs_2/f_c) = 0.21356459$

$v = As_{l,mid}/(b \cdot d) \cdot (fs_v/f_c) = 0.39800673$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$s_u (4.8) = 0.4038298$

$\mu_u = MR_c (4.15) = 3.0967E+008$

$u = s_u (4.1) = 2.4056447E-005$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 290631.642$

Calculation of Shear Strength at edge 1, $V_{r1} = 290631.642$

$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = knl \cdot V_{Co10}$

$V_{Co10} = 290631.642$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 11.70883$
 $V_u = 0.00026803$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.625$
 $V_f ((11-3)-(11.4), ACI 440) = 188111.148$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = NL \cdot t / N_{oDir} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 357.00
 $f_{fe} ((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 244232.638$
 $b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 290631.642$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$
 $V_{Col0} = 290631.642$
 $k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$\mu_u = 1$ (normal-weight concrete)
 $f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 11.914$
 $V_u = 0.00026803$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:

d = 160.00
 Av = 157079.633
 fy = 555.56
 s = 100.00
 Vs2 is multiplied by Col2 = 1.00
 s/d = 0.625
 Vf ((11-3)-(11.4), ACI 440) = 188111.148
 f = 0.95, for fully-wrapped sections
 wf/sf = 1 (FRP strips adjacent to one another).
 In (11.3) $\sin^2 + \cos^2$ is replaced with $(\cot^2 + \csc^2)\sin^2\alpha$ which is more a generalised expression,
 where α is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function Vf(α), is implemented for every different fiber orientation ai,
 as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\alpha_1 = \alpha_1 + 90^\circ = 90.00$
 Vf = Min(|Vf(45, 1)|, |Vf(-45, a1)|), with:
 total thickness per orientation, tf1 = NL*t/NoDir = 1.016
 dfv = d (figure 11.2, ACI 440) = 357.00
 ffe ((11-5), ACI 440) = 259.312
 Ef = 64828.00
 fe = 0.004, from (11.6a), ACI 440
 with fu = 0.01
 From (11-11), ACI 440: Vs + Vf <= 244232.638
 bw = 200.00

 End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At local axis: 3

 Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rclcs

Constant Properties

 Knowledge Factor, $\gamma = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 New material of Secondary Member: Concrete Strength, fc = fcm = 33.00
 New material of Secondary Member: Steel Strength, fs = fsm = 555.56
 Concrete Elasticity, Ec = 26999.444
 Steel Elasticity, Es = 200000.00
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 New material: Steel Strength, fs = 1.25*fsm = 694.45
 #####
 Max Height, Hmax = 400.00
 Min Height, Hmin = 200.00
 Max Width, Wmax = 600.00
 Min Width, Wmin = 200.00
 Cover Thickness, c = 25.00
 Mean Confinement Factor overall section = 1.06029
 Element Length, L = 3000.00
 Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with lo/lou,min = 0.30
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, t = 1.016

Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi = 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 0.00069415$
EDGE -B-
Shear Force, $V_b = -0.00069415$
BOTH EDGES
Axial Force, $F = -6093.866$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_{lt} = 0.00$
-Compression: $As_{lc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 2890.265$
-Compression: $As_{l,com} = 829.3805$
-Middle: $As_{l,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.00732$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 438835.425$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 6.5825E+008$
 $Mu_{1+} = 6.5825E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu_{1-} = 2.1740E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 6.5825E+008$
 $Mu_{2+} = 6.5825E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu_{2-} = 2.1740E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.4829616E-005$
 $M_u = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $f_c = 33.00$
 ϕ_o (5A.5, TBDY) = 0.002
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_o) = 0.01306815$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.01306815$
 ϕ_{we} ((5.4c), TBDY) = $\phi_u * \text{sh}_{,min} * f_{ywe}/f_{ce} + \text{Min}(\phi_{fx}, \phi_{fy}) = 0.05721847$
where $f = \alpha_f * \rho_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$R = 40.00$$

Effective FRP thickness, $t_f = N_L * t * \cos(b_1) = 1.016$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 466.8167$

$fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou, min = lb/lb, min = 0.30$

$su2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs2 = fs = 389.0139$

with $Es2 = Es = 200000.00$

$yv = 0.00140044$

$shv = 0.0044814$

$ftv = 466.8167$

$fyv = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou, min = lb/ld = 0.30$

$suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fsv = fs = 389.0139$

with $Esv = Es = 200000.00$

$1 = Asl, ten / (b \cdot d) \cdot (fs1 / fc) = 0.30584665$

$2 = Asl, com / (b \cdot d) \cdot (fs2 / fc) = 0.08776469$

$v = Asl, mid / (b \cdot d) \cdot (fsv / fc) = 0.04255258$

and confined core properties:

$b = 140.00$

$d = 527.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

$1 = Asl, ten / (b \cdot d) \cdot (fs1 / fc) = 0.46179611$

$2 = Asl, com / (b \cdot d) \cdot (fs2 / fc) = 0.13251541$

$v = Asl, mid / (b \cdot d) \cdot (fsv / fc) = 0.06424989$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs, y2$ - LHS eq.(4.5) is not satisfied

$v < vs, c$ - RHS eq.(4.5) is satisfied

su (4.8) = 0.38015251

$Mu = MRc$ (4.15) = 6.5825E+008

$u = su$ (4.1) = 1.4829616E-005

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0664224E-005$$

$$Mu = 2.1740E+008$$

with full section properties:

$$b = 400.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00082883$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_s e * s_{h,\min} * f_{y,w} / f_{c,e} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{f,e} / f_{c,e}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = Lstir*Astir/(Asec*s) = 0.00667588
Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00
fywe = 694.45
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287
c = confinement factor = 1.06029

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 466.8167
fy1 = 389.0139
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 466.8167
fy2 = 389.0139
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04388235

2 = Asl,com/(b*d)*(fs2/fc) = 0.15292333

v = Asl,mid/(b*d)*(fsv/fc) = 0.02127629

and confined core properties:

b = 340.00

$d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05456517$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.19015134$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.02645584$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.13804321$
 $Mu = MRc (4.14) = 2.1740E+008$
 $u = su (4.1) = 1.0664224E-005$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_{2+}

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
 $u = 1.4829616E-005$
 $Mu = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.01306815$
 $w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
 where $f = a_{pf} * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $pf = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $f_y = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $pf = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $R = 40.00$

Effective FRP thickness, $t_f = NL * t * \cos(b_1) = 1.016$

$f_u, f = 1055.00$

$E_f = 64828.00$

$u, f = 0.015$

$ase = \text{Max}(((A_{conf,max} - A_{noConf}) / A_{conf,max}) * (A_{conf,min} / A_{conf,max}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.

$A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh,min = \text{Min}(psh,x, psh,y) = 0.00471239$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

psh,x ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

psh,y ((5.4d), TBDY) = $L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu2_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$
 $sh_v = 0.0044814$
 $ft_v = 466.8167$
 $fy_v = 389.0139$
 $suv = 0.00512$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{u,min} = lb/ld = 0.30$
 $suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_v = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_v = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.
 with $fsv = fs = 389.0139$
 with $Esv = Es = 200000.00$
 $1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.30584665$
 $2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.08776469$
 $v = Asl_{mid}/(b*d) * (fsv/fc) = 0.04255258$

and confined core properties:

$b = 140.00$
 $d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = Asl_{ten}/(b*d) * (fs_1/fc) = 0.46179611$
 $2 = Asl_{com}/(b*d) * (fs_2/fc) = 0.13251541$
 $v = Asl_{mid}/(b*d) * (fsv/fc) = 0.06424989$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$su (4.8) = 0.38015251$

$Mu = MRc (4.15) = 6.5825E+008$

$u = su (4.1) = 1.4829616E-005$

 Calculation of ratio lb/ld

 Inadequate Lap Length with $lb/ld = 0.30$

 Calculation of Mu_2 -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 1.0664224E-005$

$Mu = 2.1740E+008$

with full section properties:

$b = 400.00$

$d = 557.00$

$d' = 43.00$

$v = 0.00082883$

$N = 6093.866$

$fc = 33.00$

$co (5A.5, TBDY) = 0.002$

Final value of $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01306815$

w_e ((5.4c), TBDY) = $a_{se} \cdot s_{h,min} \cdot f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
where $f = a_f \cdot p_f \cdot f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.0528506$
Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
effective stress from (A.35), $f_{f,e} = 768.6287$

$f_y = 0.0528506$
Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
effective stress from (A.35), $f_{f,e} = 768.6287$

$R = 40.00$
Effective FRP thickness, $t_f = N_L \cdot t \cdot \text{Cos}(b_1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{f} = 0.015$
 $a_{se} = \text{Max}(((A_{conf,max}-A_{noConf})/A_{conf,max}) \cdot (A_{conf,min}/A_{conf,max}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.
 $A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.
 $A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).
 $p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$
Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir}/(A_{sec} \cdot s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir}/(A_{sec} \cdot s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$s = 100.00$
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$
 c = confinement factor = 1.06029
 $y_1 = 0.00140044$
 $sh_1 = 0.0044814$
 $ft_1 = 466.8167$
 $fy_1 = 389.0139$
 $su_1 = 0.00512$
using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s1} = f_s = 389.0139$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s2} = f_s = 389.0139$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$s_uv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_uv = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{sv} = f_s = 389.0139$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.04388235$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.15292333$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02127629$$

and confined core properties:

$$b = 340.00$$

$$d = 527.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.05456517$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.19015134$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02645584$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

$$s_u (4.9) = 0.13804321$$

$$\mu = M_{Rc} (4.14) = 2.1740E+008$$

$$u = s_u (4.1) = 1.0664224E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 435646.093$

Calculation of Shear Strength at edge 1, $V_{r1} = 435646.093$

$V_{r1} = V_{Col} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{Col0}$

$V_{Col0} = 435646.093$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

 $\phi = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$

$\mu_u = 44.9328$

$V_u = 0.00069415$

$d = 0.8 * h = 480.00$

$N_u = 6093.866$

$A_g = 120000.00$

From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$

where:

$V_{s1} = 139627.457$ is calculated for section web, with:

$d = 160.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s1} is multiplied by $Col1 = 1.00$

$s/d = 0.625$

$V_{s2} = 418882.372$ is calculated for section flange, with:

$d = 480.00$

$A_v = 157079.633$

$f_y = 555.56$

$s = 100.00$

V_{s2} is multiplied by $Col2 = 1.00$

$s/d = 0.20833333$

$V_f ((11-3)-(11.4), \text{ACI } 440) = 293495.545$

$f = 0.95$, for fully-wrapped sections

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin \alpha + \cos \alpha$ is replaced with $(\cot \alpha + \cot \alpha) \sin \alpha$ which is more a generalised expression,
where α is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\alpha)$, is implemented for every different fiber orientation α_i ,
as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\alpha = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \alpha)|, |V_f(-45, \alpha)|)$, with:

total thickness per orientation, $t_{f1} = N_L * t / N_{oDir} = 1.016$

$d_{fv} = d$ (figure 11.2, ACI 440) = 557.00

$f_{fe} ((11-5), \text{ACI } 440) = 259.312$

$E_f = 64828.00$

$f_e = 0.004$, from (11.6a), ACI 440

with $f_u = 0.01$

From (11-11), ACI 440: $V_s + V_f \leq 366348.956$

$b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 435646.093$

$V_{r2} = V_{Col} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{Col0}$

$V_{Col0} = 435646.093$

$k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

 $\phi = 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 44.60048$
 $V_u = 0.00069415$
 $d = 0.8 \cdot h = 480.00$
 $N_u = 6093.866$
 $A_g = 120000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$
 where:
 $V_{s1} = 139627.457$ is calculated for section web, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.625$
 $V_{s2} = 418882.372$ is calculated for section flange, with:
 $d = 480.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.20833333$
 $V_f ((11-3)-(11.4), ACI 440) = 293495.545$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = NL \cdot t / N_{oDir} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 557.00
 $f_{fe} ((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 366348.956$
 $b_w = 200.00$

 End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At local axis: 2

 Start Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1
 At local axis: 2
 Integration Section: (b)
 Section Type: rclcs

Constant Properties

 Knowledge Factor, $\phi = 1.00$
 Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE41-17.
 Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
 Consequently:
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$
 Max Height, $H_{max} = 400.00$
 Min Height, $H_{min} = 200.00$
 Max Width, $W_{max} = 600.00$
 Min Width, $W_{min} = 200.00$
 Cover Thickness, $c = 25.00$

Element Length, L = 3000.00
 Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with $l_b/l_d = 0.30$
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, t = 1.016
 Tensile Strength, $f_{fu} = 1055.00$
 Tensile Modulus, $E_f = 64828.00$
 Elongation, $e_{fu} = 0.01$
 Number of directions, NoDir = 1
 Fiber orientations, $b_i = 0.00^\circ$
 Number of layers, NL = 1
 Radius of rounding corners, R = 40.00

 Stepwise Properties

Bending Moment, M = -85504.326
 Shear Force, V2 = 5181.087
 Shear Force, V3 = -93.61987
 Axial Force, F = -6416.475
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 0.00$
 -Compression: $A_{sc} = 4121.77$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 829.3805$
 -Compression: $A_{st,com} = 1746.726$
 -Middle: $A_{st,mid} = 1545.664$
 Mean Diameter of Tension Reinforcement, $D_{bL} = 18.66667$

 New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.04488538$
 $u = y + p = 0.04488538$

 - Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00288538$ ((4.29), Biskinis Phd))
 $M_y = 1.3306E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 913.3139
 From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 1.4040E+013$
 factor = 0.30
 $A_g = 160000.00$
 $f_c' = 33.00$
 N = 6416.475
 $E_c * I_g = 4.6799E+013$

 Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:
 flange width, b = 600.00
 web width, $b_w = 200.00$
 flange thickness, t = 200.00

 $y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 5.8027904E-006$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 \cdot f_y \cdot (l_b/d)^{2/3}) = 311.2112$

$d = 357.00$

$y = 0.24886144$

$A = 0.01933888$

$B = 0.00899303$

with $pt = 0.00387199$

$pc = 0.00815465$

$pv = 0.00721598$

$N = 6416.475$

$b = 600.00$

$" = 0.12044818$

$y_{comp} = 2.5091513E-005$

with f_c^* (12.3, (ACI 440)) = 33.29607

$f_c = 33.00$

$fl = 0.73070932$

$b = b_{max} = 600.00$

$h = h_{max} = 400.00$

$Ag = 160000.00$

$g = pt + pc + pv = 0.01924262$

$rc = 40.00$

$Ae/Ac = 0.29079753$

Effective FRP thickness, $tf = NL \cdot t \cdot \text{Cos}(b1) = 1.016$

effective strain from (12.5) and (12.12), $e_{fe} = 0.004$

$f_u = 0.01$

$E_f = 64828.00$

$E_c = 26999.444$

$y = 0.24780813$

$A = 0.01917515$

$B = 0.00889677$

with $E_s = 200000.00$

CONFIRMATION: $y = 0.24825976 < t/d$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

- Calculation of p -

From table 10-8: $p = 0.042$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/d \geq 1$
shear control ratio $V_y E / V_{col} E = 0.71033407$

$d = 357.00$

$s = 0.00$

$t = A_v / (b_w \cdot s) + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = A_v \cdot L_{stir} / (A_g \cdot s) + 2 \cdot t_f / b_w \cdot (f_{fe} / f_s) = 0.00$

$A_v = 78.53982$, is the area of every stirrup

$L_{stir} = 960.00$, is the total Length of all stirrups parallel to loading (shear) direction

The term $2 \cdot t_f / b_w \cdot (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2 \cdot t_f / b_w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$NUD = 6416.475$

$Ag = 160000.00$

$f_{cE} = 33.00$

$f_{tE} = f_{yE} = 0.00$

$pl = \text{Area_Tot_Long_Rein} / (b \cdot d) = 0.01924262$

$b = 600.00$

$d = 357.00$

$f_{cE} = 33.00$

End Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 15

column C1, Floor 1


Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rdc

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 25.00$

New material of Secondary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of γ for displacement ductility demand, the expected (mean value) strengths are used (7.5.1.3, ASCE41-17) because bending is considered as Deformation-Controlled Action (Table C7-1, ASCE41-17).

New material: Concrete Strength, $f_c = f_{cm} = 33.00$

New material: Steel Strength, $f_s = f_{sm} = 555.56$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_o/l_{o,min} = l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, t = 1.016
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, NoDir = 1
Fiber orientations, $b_i: 0.00^\circ$
Number of layers, NL = 1
Radius of rounding corners, R = 40.00

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -194281.256$
Shear Force, $V_a = 93.61987$
EDGE -B-
Bending Moment, $M_b = -85504.326$
Shear Force, $V_b = -93.61987$
BOTH EDGES
Axial Force, F = -6416.475
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 0.00$
-Compression: $A_{sl,c} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 829.3805$
-Compression: $A_{sl,com} = 1746.726$
-Middle: $A_{sl,mid} = 1545.664$
Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 18.66667$

New component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = 1.0 \cdot V_n = 269330.262$
 $V_n (10.3), ASCE 41-17 = k_n l \cdot V_{CoI0} = 269330.262$
 $V_{CoI} = 269330.262$
 $k_n l = 1.00$
 $displacement_ductility_demand = 1.5606114E-005$

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

= 1 (normal-weight concrete)
 $f_c' = 25.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 2.85411$
 $M_u = 85504.326$
 $V_u = 93.61987$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6416.475$
 $A_g = 80000.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 376991.118$
where:
 $V_{s1} = 251327.412$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$

$$s/d = 0.3125$$

$V_{s2} = 125663.706$ is calculated for section flange, with:

$$d = 160.00$$

$$A_v = 157079.633$$

$$f_y = 500.00$$

$$s = 100.00$$

V_{s2} is multiplied by $Col2 = 1.00$

$$s/d = 0.625$$

$V_f((11-3)-(11.4), ACI 440) = 188111.148$

$$f = 0.95, \text{ for fully-wrapped sections}$$

$w_f/s_f = 1$ (FRP strips adjacent to one another).

In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a)\sin a$ which is more a generalised expression, where a is the angle of the crack direction (see KANEPE).

This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i , as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.

orientation 1: $\theta = b1 + 90^\circ = 90.00$

$V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:

total thickness per orientation, $tf1 = NL*t/NoDir = 1.016$

$dfv = d$ (figure 11.2, ACI 440) = 357.00

$ffe((11-5), ACI 440) = 259.312$

$$E_f = 64828.00$$

$$f_e = 0.004, \text{ from (11.6a), ACI 440}$$

$$\text{with } f_u = 0.01$$

From (11-11), ACI 440: $V_s + V_f \leq 212577.225$

$$bw = 200.00$$

displacement ductility demand is calculated as δ / y

- Calculation of δ / y for END B -

for rotation axis 2 and integ. section (b)

From analysis, chord rotation $\theta = 4.5029555E-008$

$$y = (M_y * L_s / 3) / E_{eff} = 0.00288538 \text{ ((4.29), Biskinis Phd)}$$

$$M_y = 1.3306E+008$$

$$L_s = M/V \text{ (with } L_s > 0.1*L \text{ and } L_s < 2*L) = 913.3139$$

From table 10.5, ASCE 41_17: $E_{eff} = \text{factor} * E_c * I_g = 1.4040E+013$

$$\text{factor} = 0.30$$

$$A_g = 160000.00$$

$$f_c' = 33.00$$

$$N = 6416.475$$

$$E_c * I_g = 4.6799E+013$$

Calculation of Yielding Moment M_y

Calculation of δ / y and M_y according to Annex 7 -

Assuming neutral axis within flange ($y < t/d$, compression zone rectangular) with:

flange width, $b = 600.00$

web width, $bw = 200.00$

flange thickness, $t = 200.00$

$$y = \text{Min}(y_{ten}, y_{com})$$

$$y_{ten} = 5.8027904E-006$$

with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (I_b / I_d)^{2/3}) = 311.2112$

$$d = 357.00$$

$$y = 0.24886144$$

$$A = 0.01933888$$

$$B = 0.00899303$$

$$\text{with } pt = 0.00387199$$

$$pc = 0.00815465$$

$$pv = 0.00721598$$

$$N = 6416.475$$

$$b = 600.00$$

" = 0.12044818
y_comp = 2.5091513E-005
with f_c^* (12.3, (ACI 440)) = 33.29607
fc = 33.00
fl = 0.73070932
b = bmax = 600.00
h = hmax = 400.00
Ag = 160000.00
g = pt + pc + pv = 0.01924262
rc = 40.00
Ae/Ac = 0.29079753
Effective FRP thickness, $t_f = NL * t * \cos(b1) = 1.016$
effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
fu = 0.01
Ef = 64828.00
Ec = 26999.444
y = 0.24780813
A = 0.01917515
B = 0.00889677
with $E_s = 200000.00$
CONFIRMATION: $y = 0.24825976 < t/d$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

End Of Calculation of Shear Capacity for element: column LC1 of floor 1
At local axis: 3
Integration Section: (b)

Calculation No. 16

column C1, Floor 1



Limit State: Collapse Prevention (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rclcs

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$

New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$

Concrete Elasticity, $E_c = 26999.444$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 694.45$

#####

Max Height, $H_{max} = 400.00$

Min Height, $H_{min} = 200.00$

Max Width, $W_{max} = 600.00$

Min Width, $W_{min} = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.06029

Element Length, $L = 3000.00$

Secondary Member

Ribbed Bars

Ductile Steel

Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Inadequate Lap Length with $l_o/l_{ou,min} = 0.30$

FRP Wrapping Data

Type: Carbon

Cured laminate properties (design values)

Thickness, $t = 1.016$

Tensile Strength, $f_{fu} = 1055.00$

Tensile Modulus, $E_f = 64828.00$

Elongation, $e_{fu} = 0.01$

Number of directions, $NoDir = 1$

Fiber orientations, $b_i: 0.00^\circ$

Number of layers, $NL = 1$

Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = -0.00026803$

EDGE -B-

Shear Force, $V_b = 0.00026803$

BOTH EDGES

Axial Force, $F = -6093.866$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 0.00$

-Compression: $As_c = 4121.77$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{,ten} = 829.3805$

-Compression: $As_{,com} = 1746.726$

-Middle: $As_{,mid} = 1545.664$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.71033407$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 206445.557$

with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.0967E+008$

$Mu_{1+} = 1.8333E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 3.0967E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.0967E+008$

$Mu_{2+} = 1.8333E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 3.0967E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 1.7539345E-005$

$M_u = 1.8333E+008$

with full section properties:

$b = 600.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0008621$

$N = 6093.866$

$f_c = 33.00$

$\phi_{co} (5A.5, \text{TBDY}) = 0.002$

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_{co}) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.01306815$

where $\phi_u = \phi_{se} * \phi_{s, \text{min}} * f_{y, \text{se}} / f_{c, \text{se}} + \text{Min}(\phi_x, \phi_y) = 0.05721847$

where $\phi_{se} = a_f * p_f * f_{fe} / f_{c, \text{se}}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$\phi_x = 0.0528506$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{\text{max}} - 2R)^2 + (h_{\text{max}} - 2R)^2) / 3 = 35733.333$

$b_{\text{max}} = 600.00$

$h_{\text{max}} = 400.00$

From EC8 A.4.4.3(6), $p_f = 2t_f / b_w = 0.01016$

$b_w = 200.00$

effective stress from (A.35), $f_{f, e} = 768.6287$

$\phi_y = 0.0528506$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$a_f = 0.22333333$

with Unconfined area = $((b_{\text{max}} - 2R)^2 + (h_{\text{max}} - 2R)^2) / 3 = 0.00$

$b_{\text{max}} = 600.00$

$h_{\text{max}} = 400.00$

From EC8 A4.4.3(6), $pf = 2tf/bw = 0.01016$
 $bw = 200.00$
effective stress from (A.35), $ff,e = 768.6287$

R = 40.00

Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$

$f_{u,f} = 1055.00$

$E_f = 64828.00$

$u_{,f} = 0.015$

$ase = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$psh_{,min} = \text{Min}(psh_{,x}, psh_{,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $psh_{,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$psh_{,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$psh_{,y} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

s = 100.00

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y_1 = 0.00140044$

$sh_1 = 0.0044814$

$ft_1 = 466.8167$

$fy_1 = 389.0139$

$su_1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu_{1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_1 = fs = 389.0139$

with $Es_1 = Es = 200000.00$

$y_2 = 0.00140044$

$sh_2 = 0.0044814$

$ft_2 = 466.8167$

$fy_2 = 389.0139$

$su_2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su_2 = 0.4 * esu_{2,nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$

$suv = 0.4 \cdot es_{u2_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{u2_nominal} = 0.08$,

considering characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_v = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $Asl_{ten}/(b \cdot d) \cdot (fs_1/fc) = 0.0456442$

2 = $Asl_{com}/(b \cdot d) \cdot (fs_2/fc) = 0.09612944$

$v = Asl_{mid}/(b \cdot d) \cdot (fs_v/fc) = 0.08506418$

and confined core properties:

$b = 540.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

1 = $Asl_{ten}/(b \cdot d) \cdot (fs_1/fc) = 0.0553686$

2 = $Asl_{com}/(b \cdot d) \cdot (fs_2/fc) = 0.11660962$

$v = Asl_{mid}/(b \cdot d) \cdot (fs_v/fc) = 0.10318693$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.18231057$

$Mu = MRc (4.14) = 1.8333E+008$

$u = su (4.1) = 1.7539345E-005$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 2.4056447E-005$

$Mu = 3.0967E+008$

with full section properties:

$b = 200.00$

$d = 357.00$

$d' = 43.00$

$v = 0.00258631$

$N = 6093.866$

$fc = 33.00$

$co (5A.5, TBDY) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.01306815$

where $fywe = \text{ase} * \text{sh}_{\min} * fywe / fce + \text{Min}(fx, fy) = 0.05721847$

where $f = af * pf * ffe / fce$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $fx = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$

$b_{\max} = 600.00$

$h_{\max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ffe = 768.6287$

 $fy = 0.0528506$

Expression ((15B.6), TBDY) is modified as $af = 1 - (\text{Unconfined area}) / (\text{total area})$

$af = 0.22333333$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$

$b_{\max} = 600.00$

$h_{\max} = 400.00$

From EC8 A.4.4.3(6), $pf = 2tf / bw = 0.01016$

$bw = 200.00$

effective stress from (A.35), $ffe = 768.6287$

 $R = 40.00$

Effective FRP thickness, $tf = NL * t * \text{Cos}(b1) = 1.016$

$fu,f = 1055.00$

$Ef = 64828.00$

$u,f = 0.015$

$ase = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $bi^2/6$ as defined at (A.2).

$psh_{\min} = \text{Min}(psh,x, psh,y) = 0.00471239$

Expression ((5.4d), TBDY) for psh_{\min} has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

 psh,x ((5.4d), TBDY) = $L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 psh,y ((5.4d), TBDY) = $L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

 $s = 100.00$

$fywe = 694.45$

$fce = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{su1,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su1,nominal} = 0.08$,

For calculation of $e_{su1,nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s1} = f_s = 389.0139$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,

For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s2} = f_s = 389.0139$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$s_{uv} = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{ou,min} = l_b/l_d = 0.30$$

$$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{sv} = f_s = 389.0139$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{s1,ten}/(b*d) * (f_{s1}/f_c) = 0.28838833$$

$$2 = A_{s1,com}/(b*d) * (f_{s2}/f_c) = 0.13693259$$

$$v = A_{s1,mid}/(b*d) * (f_{sv}/f_c) = 0.25519255$$

and confined core properties:

$$b = 140.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{s1,ten}/(b*d) * (f_{s1}/f_c) = 0.44977996$$

$$2 = A_{s1,com}/(b*d) * (f_{s2}/f_c) = 0.21356459$$

$$v = A_{s1,mid}/(b*d) * (f_{sv}/f_c) = 0.39800673$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.4038298$$

$$M_u = M_{Rc} (4.15) = 3.0967E+008$$

$$u = s_u (4.1) = 2.4056447E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.7539345E-005$$

$$\mu_{2+} = 1.8333E+008$$

with full section properties:

$$b = 600.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0008621$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$\omega_{(5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_{cu}^* = \text{shear_factor} * \text{Max}(\mu_{cu}, \omega_{cc}) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_{cu} = 0.01306815$$

$$\omega_{(5.4c), TBDY} = a_{se} * \text{sh}_{, \min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L * t * \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{,f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and

is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and

is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length

equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$psh,min = \text{Min}(psh,x, psh,y) = 0.00471239$$

Expression ((5.4d), TBDY) for psh,min has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$psh,x \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00471239$$

$$Lstir \text{ (Length of stirrups along Y)} = 1360.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$psh,y \text{ ((5.4d), TBDY)} = Lstir * Astir / (Asec * s) = 0.00667588$$

$$Lstir \text{ (Length of stirrups along X)} = 960.00$$

$$Astir \text{ (stirrups area)} = 78.53982$$

$$Asec \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$fywe = 694.45$$

$$fce = 33.00$$

$$\text{From ((5.A5), TBDY), TBDY: } cc = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$y1 = 0.00140044$$

$$sh1 = 0.0044814$$

$$ft1 = 466.8167$$

$$fy1 = 389.0139$$

$$su1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$su1 = 0.4 * esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs1 = fs = 389.0139$$

$$\text{with } Es1 = Es = 200000.00$$

$$y2 = 0.00140044$$

$$sh2 = 0.0044814$$

$$ft2 = 466.8167$$

$$fy2 = 389.0139$$

$$su2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 0.30$$

$$su2 = 0.4 * esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fs2 = fs = 389.0139$$

$$\text{with } Es2 = Es = 200000.00$$

$$yv = 0.00140044$$

$$shv = 0.0044814$$

$$ftv = 466.8167$$

$$fyv = 389.0139$$

$$suv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/d = 0.30$$

$$suv = 0.4 * esuv_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } fsv = fs = 389.0139$$

with $E_{sv} = E_s = 200000.00$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0456442$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.09612944$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.08506418$$

and confined core properties:

$$b = 540.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.0553686$$

$$2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.11660962$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.10318693$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.18231057$$

$$\mu_u = M_{Rc} (4.14) = 1.8333E+008$$

$$u = s_u (4.1) = 1.7539345E-005$$

Calculation of ratio l_b/d

Inadequate Lap Length with $l_b/d = 0.30$

Calculation of μ_{u2} -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 2.4056447E-005$$

$$\mu_u = 3.0967E+008$$

with full section properties:

$$b = 200.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.00258631$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_c (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$$

$$b_{max} = 600.00$$

$$h_{max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f/b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$$

$$b_{max} = 600.00$$

hmax = 400.00
From EC8 A.4.3(6), $pf = 2tf/bw = 0.01016$
bw = 200.00
effective stress from (A.35), $ff,e = 768.6287$

R = 40.00
Effective FRP thickness, $tf = NL*t*\text{Cos}(b1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{,f} = 0.015$

$ase = \text{Max}((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}} * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

s = 100.00
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$
c = confinement factor = 1.06029

$y1 = 0.00140044$
 $sh1 = 0.0044814$
 $ft1 = 466.8167$
 $fy1 = 389.0139$
 $su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$
 $sh2 = 0.0044814$
 $ft2 = 466.8167$
 $fy2 = 389.0139$
 $su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{ou,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{nominal} \text{ ((5.5), TBDY)} = 0.032$

From table 5A.1, TBDY: $es_{u2_nominal} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_2 = fs = 389.0139$

with $Es_2 = Es = 200000.00$

$y_v = 0.00140044$

$sh_v = 0.0044814$

$ft_v = 466.8167$

$fy_v = 389.0139$

$s_{uv} = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 0.30$

$s_{uv} = 0.4 \cdot es_{uv_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{uv_nominal} = 0.08$,

considering characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $fs_{yv} = fs_v/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs_v = fs = 389.0139$

with $Es_v = Es = 200000.00$

1 = $As_{l,ten}/(b \cdot d) \cdot (fs_1/f_c) = 0.28838833$

2 = $As_{l,com}/(b \cdot d) \cdot (fs_2/f_c) = 0.13693259$

$v = As_{l,mid}/(b \cdot d) \cdot (fs_v/f_c) = 0.25519255$

and confined core properties:

$b = 140.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 34.98946$

$cc (5A.5, TBDY) = 0.00260287$

$c = \text{confinement factor} = 1.06029$

1 = $As_{l,ten}/(b \cdot d) \cdot (fs_1/f_c) = 0.44977996$

2 = $As_{l,com}/(b \cdot d) \cdot (fs_2/f_c) = 0.21356459$

$v = As_{l,mid}/(b \cdot d) \cdot (fs_v/f_c) = 0.39800673$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$s_u (4.8) = 0.4038298$

$\mu_u = MR_c (4.15) = 3.0967E+008$

$u = s_u (4.1) = 2.4056447E-005$

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 290631.642$

Calculation of Shear Strength at edge 1, $V_{r1} = 290631.642$

$V_{r1} = V_{Co1} ((10.3), ASCE 41-17) = knl \cdot V_{Co10}$

$V_{Co10} = 290631.642$

$knl = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

 $= 1$ (normal-weight concrete)

$f_c' = 33.00$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 11.70883$
 $V_u = 0.00026803$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.625$
 $V_f ((11-3)-(11.4), ACI 440) = 188111.148$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = NL \cdot t / N_{oDir} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 357.00
 $f_{fe} ((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 244232.638$
 $b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 290631.642$
 $V_{r2} = V_{Col} ((10.3), ASCE 41-17) = k_{nl} \cdot V_{Col0}$
 $V_{Col0} = 290631.642$
 $k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) ' V_s ' is replaced by ' $V_{s+} + f \cdot V_f$ '
 where V_f is the contribution of FRPs (11.3), ACI 440).

$\mu = 1$ (normal-weight concrete)
 $f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 11.914$
 $V_u = 0.00026803$
 $d = 0.8 \cdot h = 320.00$
 $N_u = 6093.866$
 $A_g = 80000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 418882.372$
 where:
 $V_{s1} = 279254.914$ is calculated for section web, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.3125$
 $V_{s2} = 139627.457$ is calculated for section flange, with:

d = 160.00
 Av = 157079.633
 fy = 555.56
 s = 100.00
 Vs2 is multiplied by Col2 = 1.00
 s/d = 0.625
 Vf ((11-3)-(11.4), ACI 440) = 188111.148
 f = 0.95, for fully-wrapped sections
 wf/sf = 1 (FRP strips adjacent to one another).
 In (11.3) $\sin^2 + \cos^2$ is replaced with $(\cot^2 + \csc^2)\sin^2\alpha$ which is more a generalised expression,
 where α is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function Vf(α), is implemented for every different fiber orientation ai,
 as well as for 2 crack directions, $\alpha = 45^\circ$ and $\alpha = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\alpha_1 = \alpha_1 + 90^\circ = 90.00$
 Vf = Min(|Vf(45, 1)|, |Vf(-45, a1)|), with:
 total thickness per orientation, tf1 = NL*t/NoDir = 1.016
 dfv = d (figure 11.2, ACI 440) = 357.00
 ffe ((11-5), ACI 440) = 259.312
 Ef = 64828.00
 fe = 0.004, from (11.6a), ACI 440
 with fu = 0.01
 From (11-11), ACI 440: Vs + Vf <= 244232.638
 bw = 200.00

 End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At local axis: 3

 Start Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At Shear local axis: 2
 (Bending local axis: 3)
 Section Type: rclcs

Constant Properties

 Knowledge Factor, $\lambda = 1.00$
 Mean strength values are used for both shear and moment calculations.
 Consequently:
 New material of Secondary Member: Concrete Strength, fc = fcm = 33.00
 New material of Secondary Member: Steel Strength, fs = fsm = 555.56
 Concrete Elasticity, Ec = 26999.444
 Steel Elasticity, Es = 200000.00
 #####
 Note: Especially for the calculation of moment strengths,
 the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
 New material: Steel Strength, fs = 1.25*fsm = 694.45
 #####
 Max Height, Hmax = 400.00
 Min Height, Hmin = 200.00
 Max Width, Wmax = 600.00
 Min Width, Wmin = 200.00
 Cover Thickness, c = 25.00
 Mean Confinement Factor overall section = 1.06029
 Element Length, L = 3000.00
 Secondary Member
 Ribbed Bars
 Ductile Steel
 Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Inadequate Lap Length with lo/lou,min = 0.30
 FRP Wrapping Data
 Type: Carbon
 Cured laminate properties (design values)
 Thickness, t = 1.016

Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, $NoDir = 1$
Fiber orientations, $bi = 0.00^\circ$
Number of layers, $NL = 1$
Radius of rounding corners, $R = 40.00$

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = 0.00069415$
EDGE -B-
Shear Force, $V_b = -0.00069415$
BOTH EDGES
Axial Force, $F = -6093.866$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_{lt} = 0.00$
-Compression: $As_{lc} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{l,ten} = 2890.265$
-Compression: $As_{l,com} = 829.3805$
-Middle: $As_{l,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 1.00732$
Member Controlled by Shear ($V_e/V_r > 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n = 438835.425$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 6.5825E+008$
 $Mu_{1+} = 6.5825E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu_{1-} = 2.1740E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 6.5825E+008$
 $Mu_{2+} = 6.5825E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu_{2-} = 2.1740E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 1.4829616E-005$
 $M_u = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $f_c = 33.00$
 ϕ_o (5A.5, TBDY) = 0.002
Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_o) = 0.01306815$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\phi_u = 0.01306815$
 ϕ_{we} ((5.4c), TBDY) = $ase * \text{sh}_{,min} * f_{ywe}/f_{ce} + \text{Min}(\phi_{fx}, \phi_{fy}) = 0.05721847$
where $f = af * p_f * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 35733.333$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$

$$a_f = 0.22333333$$

with Unconfined area = $((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2)/3 = 0.00$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$

$$b_w = 200.00$$

effective stress from (A.35), $f_{f,e} = 768.6287$

$$R = 40.00$$

Effective FRP thickness, $t_f = N_L * t * \cos(b_1) = 1.016$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f} = 0.015$$

$$a_{se} = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}})/A_{\text{conf,max}}) * (A_{\text{conf,min}}/A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00471239$$

$$L_{stir} \text{ (Length of stirrups along Y)} = 1360.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$p_{sh,y} \text{ ((5.4d), TBDY)} = L_{stir} * A_{stir} / (A_{sec} * s) = 0.00667588$$

$$L_{stir} \text{ (Length of stirrups along X)} = 960.00$$

$$A_{stir} \text{ (stirrups area)} = 78.53982$$

$$A_{sec} \text{ (section area)} = 160000.00$$

$$s = 100.00$$

$$f_{ywe} = 694.45$$

$$f_{ce} = 33.00$$

From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$

$$c = \text{confinement factor} = 1.06029$$

$$y_1 = 0.00140044$$

$$sh_1 = 0.0044814$$

$$ft_1 = 466.8167$$

$$fy_1 = 389.0139$$

$$su_1 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/d = 0.30$$

$$su_1 = 0.4 * esu_{1,nominal} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{1,nominal} = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 466.8167$

$fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou, min = lb/lb, min = 0.30$

$su2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs2 = fs = 389.0139$

with $Es2 = Es = 200000.00$

$yv = 0.00140044$

$shv = 0.0044814$

$ftv = 466.8167$

$fyv = 389.0139$

$suv = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lou, min = lb/ld = 0.30$

$suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE41-17.

with $fsv = fs = 389.0139$

with $Esv = Es = 200000.00$

$1 = Asl, ten / (b \cdot d) \cdot (fs1 / fc) = 0.30584665$

$2 = Asl, com / (b \cdot d) \cdot (fs2 / fc) = 0.08776469$

$v = Asl, mid / (b \cdot d) \cdot (fsv / fc) = 0.04255258$

and confined core properties:

$b = 140.00$

$d = 527.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

$1 = Asl, ten / (b \cdot d) \cdot (fs1 / fc) = 0.46179611$

$2 = Asl, com / (b \cdot d) \cdot (fs2 / fc) = 0.13251541$

$v = Asl, mid / (b \cdot d) \cdot (fsv / fc) = 0.06424989$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

$v < vs, y2$ - LHS eq.(4.5) is not satisfied

$v < vs, c$ - RHS eq.(4.5) is satisfied

su (4.8) = 0.38015251

$Mu = MRc$ (4.15) = 6.5825E+008

$u = su$ (4.1) = 1.4829616E-005

Calculation of ratio lb/ld

Inadequate Lap Length with $lb/ld = 0.30$

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 1.0664224E-005$$

$$Mu = 2.1740E+008$$

with full section properties:

$$b = 400.00$$

$$d = 557.00$$

$$d' = 43.00$$

$$v = 0.00082883$$

$$N = 6093.866$$

$$f_c = 33.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.01306815$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.01306815$$

$$w_e \text{ ((5.4c), TBDY)} = a_s e * s_{h,\min} * f_{ywe} / f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$$

where $f = a_f * p_f * f_{fe} / f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$$f_x = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 35733.333$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$f_y = 0.0528506$$

Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area}) / (\text{total area})$

$$a_f = 0.22333333$$

$$\text{with Unconfined area} = ((b_{\max} - 2R)^2 + (h_{\max} - 2R)^2) / 3 = 0.00$$

$$b_{\max} = 600.00$$

$$h_{\max} = 400.00$$

$$\text{From EC8 A.4.4.3(6), } p_f = 2t_f / b_w = 0.01016$$

$$b_w = 200.00$$

$$\text{effective stress from (A.35), } f_{f,e} = 768.6287$$

$$R = 40.00$$

$$\text{Effective FRP thickness, } t_f = N L^* t \text{Cos}(b_1) = 1.016$$

$$f_{u,f} = 1055.00$$

$$E_f = 64828.00$$

$$u_{f,f} = 0.015$$

$$a_s e = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2 / 6$ as defined at (A.2).

$$p_{sh,\min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$$

Expression ((5.4d), TBDY) for $p_{sh,\min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$$p_{sh,x} \text{ ((5.4d), TBDY)} = L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$$

$$L_{\text{stir}} \text{ (Length of stirrups along Y)} = 1360.00$$

Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

psh,y ((5.4d), TBDY) = Lstir*Astir/(Asec*s) = 0.00667588
Lstir (Length of stirrups along X) = 960.00
Astir (stirrups area) = 78.53982
Asec (section area) = 160000.00

s = 100.00
fywe = 694.45
fce = 33.00

From ((5.A5), TBDY), TBDY: cc = 0.00260287
c = confinement factor = 1.06029

y1 = 0.00140044
sh1 = 0.0044814
ft1 = 466.8167
fy1 = 389.0139
su1 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs1 = fs = 389.0139

with Es1 = Es = 200000.00

y2 = 0.00140044
sh2 = 0.0044814
ft2 = 466.8167
fy2 = 389.0139
su2 = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 0.30

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fs2 = fs = 389.0139

with Es2 = Es = 200000.00

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.04388235

2 = Asl,com/(b*d)*(fs2/fc) = 0.15292333

v = Asl,mid/(b*d)*(fsv/fc) = 0.02127629

and confined core properties:

b = 340.00

$d = 527.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 34.98946$
 $cc (5A.5, TBDY) = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $1 = A_{sl,ten}/(b*d)*(f_{s1}/f_c) = 0.05456517$
 $2 = A_{sl,com}/(b*d)*(f_{s2}/f_c) = 0.19015134$
 $v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.02645584$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

--->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.13804321$
 $Mu = MRc (4.14) = 2.1740E+008$
 $u = su (4.1) = 1.0664224E-005$

 Calculation of ratio l_b/l_d

 Inadequate Lap Length with $l_b/l_d = 0.30$

 Calculation of Mu_{2+}

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
 $u = 1.4829616E-005$
 $Mu = 6.5825E+008$

with full section properties:

$b = 200.00$
 $d = 557.00$
 $d' = 43.00$
 $v = 0.00165765$
 $N = 6093.866$
 $f_c = 33.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.01306815$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.01306815$
 $w_e ((5.4c), TBDY) = a_{se} * s_{h,min} * f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
 where $f = a_{pf} * f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

 $f_x = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $pf = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $f_y = 0.0528506$
 Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
 with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
 From EC8 A.4.4.3(6), $pf = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
 effective stress from (A.35), $f_{f,e} = 768.6287$

 $R = 40.00$

Effective FRP thickness, $t_f = NL*t*\text{Cos}(b1) = 1.016$

$f_u, f = 1055.00$

$E_f = 64828.00$

$u, f = 0.015$

$ase = \text{Max}(((A_{\text{conf,max}} - A_{\text{noConf}}) / A_{\text{conf,max}}) * (A_{\text{conf,min}} / A_{\text{conf,max}}), 0) = 0.14681846$

The definitions of A_{noConf} , $A_{\text{conf,min}}$ and $A_{\text{conf,max}}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).

The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988)

"Theoretical Stress-Strain Model for Confined Concrete."

J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.

$A_{\text{conf,max}} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.

$A_{\text{conf,min}} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{\text{conf,max}}$ by a length equal to half the clear spacing between hoops.

$A_{\text{noConf}} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).

$p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$

Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00471239$

L_{stir} (Length of stirrups along Y) = 1360.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{\text{stir}} * A_{\text{stir}} / (A_{\text{sec}} * s) = 0.00667588$

L_{stir} (Length of stirrups along X) = 960.00

A_{stir} (stirrups area) = 78.53982

A_{sec} (section area) = 160000.00

$s = 100.00$

$f_{ywe} = 694.45$

$f_{ce} = 33.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00260287$

c = confinement factor = 1.06029

$y1 = 0.00140044$

$sh1 = 0.0044814$

$ft1 = 466.8167$

$fy1 = 389.0139$

$su1 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 0.30$

$su1 = 0.4 * esu1_{\text{nominal}}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{\text{nominal}} = 0.08$,

For calculation of $esu1_{\text{nominal}}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs1 = fs = 389.0139$

with $Es1 = Es = 200000.00$

$y2 = 0.00140044$

$sh2 = 0.0044814$

$ft2 = 466.8167$

$fy2 = 389.0139$

$su2 = 0.00512$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$

$su2 = 0.4 * esu2_{\text{nominal}}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_{\text{nominal}} = 0.08$,

For calculation of $esu2_{\text{nominal}}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

with $fs2 = fs = 389.0139$

with $Es2 = Es = 200000.00$

yv = 0.00140044
shv = 0.0044814
ftv = 466.8167
fyv = 389.0139
suv = 0.00512

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 0.30

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^2/3), from 10.3.5, ASCE41-17.

with fsv = fs = 389.0139

with Esv = Es = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.30584665

2 = Asl,com/(b*d)*(fs2/fc) = 0.08776469

v = Asl,mid/(b*d)*(fsv/fc) = 0.04255258

and confined core properties:

b = 140.00

d = 527.00

d' = 13.00

fcc (5A.2, TBDY) = 34.98946

cc (5A.5, TBDY) = 0.00260287

c = confinement factor = 1.06029

1 = Asl,ten/(b*d)*(fs1/fc) = 0.46179611

2 = Asl,com/(b*d)*(fs2/fc) = 0.13251541

v = Asl,mid/(b*d)*(fsv/fc) = 0.06424989

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

v < vs,y2 - LHS eq.(4.5) is not satisfied

v < vs,c - RHS eq.(4.5) is satisfied

su (4.8) = 0.38015251

Mu = MRc (4.15) = 6.5825E+008

u = su (4.1) = 1.4829616E-005

Calculation of ratio lb/ld

Inadequate Lap Length with lb/ld = 0.30

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 1.0664224E-005

Mu = 2.1740E+008

with full section properties:

b = 400.00

d = 557.00

d' = 43.00

v = 0.00082883

N = 6093.866

fc = 33.00

co (5A.5, TBDY) = 0.002

Final value of cu* = shear_factor * Max(cu, cc) = 0.01306815

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.01306815

w_e ((5.4c), TBDY) = $a_{se} \cdot s_{h,min} \cdot f_{ywe}/f_{ce} + \text{Min}(f_x, f_y) = 0.05721847$
where $f = a_f \cdot p_f \cdot f_{fe}/f_{ce}$ is accounting for FRP contribution like EC8-part3 A.4.4.3(6)

$f_x = 0.0528506$
Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 35733.333$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
effective stress from (A.35), $f_{f,e} = 768.6287$

$f_y = 0.0528506$
Expression ((15B.6), TBDY) is modified as $a_f = 1 - (\text{Unconfined area})/(\text{total area})$
 $a_f = 0.22333333$
with Unconfined area = $((b_{max}-2R)^2 + (h_{max}-2R)^2)/3 = 0.00$
 $b_{max} = 600.00$
 $h_{max} = 400.00$
From EC8 A.4.4.3(6), $p_f = 2t_f/b_w = 0.01016$
 $b_w = 200.00$
effective stress from (A.35), $f_{f,e} = 768.6287$

$R = 40.00$
Effective FRP thickness, $t_f = N_L \cdot t \cdot \text{Cos}(b_1) = 1.016$
 $f_{u,f} = 1055.00$
 $E_f = 64828.00$
 $u_{f} = 0.015$
 $a_{se} = \text{Max}(((A_{conf,max} - A_{noConf})/A_{conf,max}) \cdot (A_{conf,min}/A_{conf,max}), 0) = 0.14681846$
The definitions of A_{noConf} , $A_{conf,min}$ and $A_{conf,max}$ are derived from generalization of the rectangular sections confinement, which is expressed by (5.4d).
The generalization is done according to Mander, J., Priestley, M., and Park, R. (1988) "Theoretical Stress-Strain Model for Confined Concrete."
J. Struct. Eng., 10.1061/(ASCE)0733-9445(1988)114:8(1804), 1804-1826.
 $A_{conf,max} = 103600.00$ is the confined core area at levels of member with hoops and is calculated as the area of core enclosed by the center lines of the perimeter hoops.
 $A_{conf,min} = 66025.00$ is the confined core area at midway between the levels of hoops and is calculated by reducing all the dimensions of the area $A_{conf,max}$ by a length equal to half the clear spacing between hoops.
 $A_{noConf} = 79733.333$ is the unconfined core area which is equal to $b_i^2/6$ as defined at (A.2).
 $p_{sh,min} = \text{Min}(p_{sh,x}, p_{sh,y}) = 0.00471239$
Expression ((5.4d), TBDY) for $p_{sh,min}$ has been multiplied by 0.3 according to 15.7.1.3 for members without earthquake detailing (90° closed stirrups)

$p_{sh,x}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir}/(A_{sec} \cdot s) = 0.00471239$
 L_{stir} (Length of stirrups along Y) = 1360.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$p_{sh,y}$ ((5.4d), TBDY) = $L_{stir} \cdot A_{stir}/(A_{sec} \cdot s) = 0.00667588$
 L_{stir} (Length of stirrups along X) = 960.00
 A_{stir} (stirrups area) = 78.53982
 A_{sec} (section area) = 160000.00

$s = 100.00$
 $f_{ywe} = 694.45$
 $f_{ce} = 33.00$
From ((5.A5), TBDY), TBDY: $c_c = 0.00260287$
 $c = \text{confinement factor} = 1.06029$
 $y_1 = 0.00140044$
 $sh_1 = 0.0044814$
 $ft_1 = 466.8167$
 $fy_1 = 389.0139$
 $su_1 = 0.00512$
using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s1_nominal} = 0.08$,

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s1} = f_s = 389.0139$$

$$\text{with } E_{s1} = E_s = 200000.00$$

$$y_2 = 0.00140044$$

$$sh_2 = 0.0044814$$

$$ft_2 = 466.8167$$

$$fy_2 = 389.0139$$

$$s_u2 = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_{b,min} = 0.30$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s2_nominal} = 0.08$,

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{s2} = f_s = 389.0139$$

$$\text{with } E_{s2} = E_s = 200000.00$$

$$y_v = 0.00140044$$

$$sh_v = 0.0044814$$

$$ft_v = 466.8167$$

$$fy_v = 389.0139$$

$$s_uv = 0.00512$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o/l_{o,min} = l_b/l_d = 0.30$$

$$s_uv = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{suv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE41-17.

$$\text{with } f_{sv} = f_s = 389.0139$$

$$\text{with } E_{sv} = E_s = 200000.00$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.04388235$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.15292333$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02127629$$

and confined core properties:

$$b = 340.00$$

$$d = 527.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 34.98946$$

$$c_c (5A.5, TBDY) = 0.00260287$$

$$c = \text{confinement factor} = 1.06029$$

$$1 = A_{sl,ten}/(b*d) * (f_{s1}/f_c) = 0.05456517$$

$$2 = A_{sl,com}/(b*d) * (f_{s2}/f_c) = 0.19015134$$

$$v = A_{sl,mid}/(b*d) * (f_{sv}/f_c) = 0.02645584$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u (4.9) = 0.13804321$$

$$\mu = M_{Rc} (4.14) = 2.1740E+008$$

$$u = s_u (4.1) = 1.0664224E-005$$

Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 435646.093$

Calculation of Shear Strength at edge 1, $V_{r1} = 435646.093$
 $V_{r1} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{\text{Col}0}$
 $V_{\text{Col}0} = 435646.093$
 $k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

 $\phi = 1$ (normal-weight concrete)
 $f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $M/Vd = 4.00$
 $\mu_u = 44.9328$
 $V_u = 0.00069415$
 $d = 0.8 * h = 480.00$
 $N_u = 6093.866$
 $A_g = 120000.00$
From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$
where:
 $V_{s1} = 139627.457$ is calculated for section web, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $\text{Col}1 = 1.00$
 $s/d = 0.625$
 $V_{s2} = 418882.372$ is calculated for section flange, with:
 $d = 480.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $\text{Col}2 = 1.00$
 $s/d = 0.20833333$
 $V_f ((11-3)-(11.4), \text{ACI } 440) = 293495.545$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
In (11.3) $\sin \theta + \cos \theta$ is replaced with $(\cot \theta + \csc \theta) \sin \alpha$ which is more a generalised expression,
where θ is the angle of the crack direction (see KANEPE).
This later relation, considered as a function $V_f(\theta, \alpha)$, is implemented for every different fiber orientation α_i ,
as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
orientation 1: $\theta = 45^\circ$
 $V_f = \text{Min}(|V_f(45, \alpha_1)|, |V_f(-45, \alpha_1)|)$, with:
total thickness per orientation, $t_{f1} = N_L * t / N_{\text{Dir}} = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 557.00
 $f_{fe} ((11-5), \text{ACI } 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
with $f_u = 0.01$
From (11-11), ACI 440: $V_s + V_f \leq 366348.956$
 $b_w = 200.00$

Calculation of Shear Strength at edge 2, $V_{r2} = 435646.093$
 $V_{r2} = V_{\text{Col}} ((10.3), \text{ASCE } 41-17) = k_{nl} * V_{\text{Col}0}$
 $V_{\text{Col}0} = 435646.093$
 $k_{nl} = 1$ (zero step-static loading)

NOTE: In expression (10-3) 'Vs' is replaced by 'Vs+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

 $\phi = 1$ (normal-weight concrete)
 $f_c' = 33.00$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$M/Vd = 4.00$
 $\mu_u = 44.60048$
 $\nu_u = 0.00069415$
 $d = 0.8 \cdot h = 480.00$
 $Nu = 6093.866$
 $Ag = 120000.00$
 From (11.5.4.8), ACI 318-14: $V_s = V_{s1} + V_{s2} = 558509.829$
 where:
 $V_{s1} = 139627.457$ is calculated for section web, with:
 $d = 160.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s1} is multiplied by $Col1 = 1.00$
 $s/d = 0.625$
 $V_{s2} = 418882.372$ is calculated for section flange, with:
 $d = 480.00$
 $A_v = 157079.633$
 $f_y = 555.56$
 $s = 100.00$
 V_{s2} is multiplied by $Col2 = 1.00$
 $s/d = 0.20833333$
 $V_f ((11-3)-(11.4), ACI 440) = 293495.545$
 $f = 0.95$, for fully-wrapped sections
 $w_f/s_f = 1$ (FRP strips adjacent to one another).
 In (11.3) $\sin + \cos$ is replaced with $(\cot + \cot a) \sin a$ which is more a generalised expression,
 where a is the angle of the crack direction (see KANEPE).
 This later relation, considered as a function $V_f(\theta, a)$, is implemented for every different fiber orientation a_i ,
 as well as for 2 crack directions, $\theta = 45^\circ$ and $\theta = -45^\circ$ to take into consideration the cyclic seismic loading.
 orientation 1: $\theta = b1 + 90^\circ = 90.00$
 $V_f = \text{Min}(|V_f(45, \theta)|, |V_f(-45, a1)|)$, with:
 total thickness per orientation, $t_{f1} = NL \cdot t / NoDir = 1.016$
 $d_{fv} = d$ (figure 11.2, ACI 440) = 557.00
 $f_{fe} ((11-5), ACI 440) = 259.312$
 $E_f = 64828.00$
 $f_e = 0.004$, from (11.6a), ACI 440
 with $f_u = 0.01$
 From (11-11), ACI 440: $V_s + V_f \leq 366348.956$
 $b_w = 200.00$

 End Of Calculation of Shear Capacity ratio for element: column LC1 of floor 1
 At local axis: 2

 Start Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1
 At local axis: 3
 Integration Section: (b)
 Section Type: rclcs

Constant Properties

 Knowledge Factor, $\phi = 1.00$
 Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE41-17.
 Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
 Consequently:
 New material of Secondary Member: Concrete Strength, $f_c = f_{cm} = 33.00$
 New material of Secondary Member: Steel Strength, $f_s = f_{sm} = 555.56$
 Concrete Elasticity, $E_c = 26999.444$
 Steel Elasticity, $E_s = 200000.00$
 Max Height, $H_{max} = 400.00$
 Min Height, $H_{min} = 200.00$
 Max Width, $W_{max} = 600.00$
 Min Width, $W_{min} = 200.00$
 Cover Thickness, $c = 25.00$

Element Length, L = 3000.00
Secondary Member
Ribbed Bars
Ductile Steel
Without Detailing for Earthquake Resistance (including stirrups not closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Inadequate Lap Length with $l_b/l_d = 0.30$
FRP Wrapping Data
Type: Carbon
Cured laminate properties (design values)
Thickness, t = 1.016
Tensile Strength, $f_{fu} = 1055.00$
Tensile Modulus, $E_f = 64828.00$
Elongation, $e_{fu} = 0.01$
Number of directions, NoDir = 1
Fiber orientations, $b_i = 0.00^\circ$
Number of layers, NL = 1
Radius of rounding corners, R = 40.00

Stepwise Properties

Bending Moment, M = 96939.725
Shear Force, V2 = 5181.087
Shear Force, V3 = -93.61987
Axial Force, F = -6416.475
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 0.00$
-Compression: $A_{sl,c} = 4121.77$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 2890.265$
-Compression: $A_{sl,com} = 829.3805$
-Middle: $A_{sl,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $DbL = 18.18182$

New component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = 1.0^*$ $u = 0.04312656$
 $u = y + p = 0.04312656$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00112656$ ((4.29), Biskinis Phd))
 $M_y = 4.5016E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 300.00
From table 10.5, ASCE 41_17: $E_{eff} = factor * E_c * I_g = 3.9959E+013$
factor = 0.30
 $A_g = 160000.00$
 $f_c' = 33.00$
 $N = 6416.475$
 $E_c * I_g = 1.3320E+014$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 4.9173110E-006$
with ((10.1), ASCE 41-17) $f_y = \text{Min}(f_y, 1.25 * f_y * (l_b/l_d)^{2/3}) = 311.2112$
 $d = 557.00$
 $y = 0.43187711$
 $A = 0.03718481$
 $B = 0.02864896$

with $p_t = 0.02594493$
 $p_c = 0.00744507$
 $p_v = 0.00360973$
 $N = 6416.475$
 $b = 200.00$
 $\rho = 0.07719928$
 $y_{comp} = 9.2350821E-006$
 with f_c^* (12.3, (ACI 440)) = 33.28275
 $f_c = 33.00$
 $f_l = 0.73070932$
 $b = b_{max} = 600.00$
 $h = h_{max} = 400.00$
 $A_g = 160000.00$
 $g = p_t + p_c + p_v = 0.03699973$
 $r_c = 40.00$
 $A_e/A_c = 0.27772029$
 Effective FRP thickness, $t_f = N L^* t^* \cos(b_1) = 1.016$
 effective strain from (12.5) and (12.12), $\epsilon_{fe} = 0.004$
 $f_u = 0.01$
 $E_f = 64828.00$
 $E_c = 26999.444$
 $y = 0.43136109$
 $A = 0.03686994$
 $B = 0.02846388$
 with $E_s = 200000.00$

 Calculation of ratio l_b/l_d

Inadequate Lap Length with $l_b/l_d = 0.30$

 - Calculation of p -

From table 10-8: $p = 0.042$

with:

- Columns not controlled by inadequate development or splicing along the clear height because $l_b/l_d \geq 1$
 shear control ratio $V_y E / V_{col} O E = 1.00732$

$d = 557.00$

$s = 0.00$

$t = A_v / (b w^* s) + 2^* t_f / b w^* (f_{fe} / f_s) = A_v^* L_{stir} / (A_g^* s) + 2^* t_f / b w^* (f_{fe} / f_s) = 0.00$

$A_v = 78.53982$, is the area of every stirrup

$L_{stir} = 1360.00$, is the total length of all stirrups parallel to loading (shear) direction

The term $2^* t_f / b w^* (f_{fe} / f_s)$ is implemented to account for FRP contribution

where $f = 2^* t_f / b w$ is FRP ratio (EC8 - 3, A.4.4.3(6)) and f_{fe} / f_s normalises f to steel strength

All these variables have already been given in Shear control ratio calculation.

$N_{UD} = 6416.475$

$A_g = 160000.00$

$f_c E = 33.00$

$f_{yt} E = f_{yl} E = 0.00$

$p_l = \text{Area_Tot_Long_Rein} / (b^* d) = 0.03699973$

$b = 200.00$

$d = 557.00$

$f_c E = 33.00$

 End Of Calculation of Chord Rotation Capacity for element: column LC1 of floor 1

At local axis: 3

Integration Section: (b)