

Detailed Member Calculations

Units: N&mm

Regulation: ASCE 41-17

Calculation No. 1

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 20.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 25742.96$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$
Concrete Elasticity, $E_c = 23025.204$
Steel Elasticity, $E_s = 200000.00$
External Height, $H = 670.00$
External Width, $W = 400.00$
Internal Height, $H = 500.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -8.4907098E-011$
Shear Force, $V_a = -5.4911670E-014$
EDGE -B-
Bending Moment, $M_b = -7.9998090E-011$
Shear Force, $V_b = 5.4911670E-014$
BOTH EDGES
Axial Force, $F = -7188.634$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 911.0619$
-Compression: $A_{sc,com} = 911.0619$
-Middle: $A_{st,mid} = 556.0619$
Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 15.20$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 315128.448$
 $V_n ((22.5.1.1), ACI 318-14) = 315128.448$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 147576.839$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot Area_{jacket} + f'_{c_core} \cdot Area_{core}) / Area_{section} = 18.50746$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 670.00$
 $d = 320.00$
 $V_u \cdot d / M_u < 1 = 0.00$
 $M_u = 8.4907098E-011$
 $V_u = 5.4911670E-014$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 167551.608$
 $V_{s1} = 167551.608$ is calculated for jacket, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 150.00$

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 420.00$

$s = 300.00$

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 612724.122$

End Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 2

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

```

Steel Elasticity, Es = 200000.00
Existing Column
Existing material of Primary Member: Concrete Strength, fc = fcm = 24.00
Existing material of Primary Member: Steel Strength, fs = fsm = 525.00
Concrete Elasticity, Ec = 23025.204
Steel Elasticity, Es = 200000.00
#####
Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength, fs = 1.25*fsm = 781.25
Existing Column
Existing material: Steel Strength, fs = 1.25*fsm = 656.25
#####
External Height, H = 670.00
External Width, W = 400.00
Internal Height, H = 500.00
Internal Width, W = 200.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.04251
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lo/lu,min>=1)
No FRP Wrapping
-----

Stepwise Properties
-----
At local axis: 3
EDGE -A-
Shear Force, Va = 9840.632
EDGE -B-
Shear Force, Vb = 9840.634
BOTH EDGES
Axial Force, F = -2309.834
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: Asl,t = 709.9999
-Compression: Asl,c = 1668.186
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: Asl,ten = 709.9999
-Compression: Asl,com = 1266.062
-Middle: Asl,mid = 402.1239
-----
-----

Calculation of Shear Capacity ratio , Ve/Vr = 0.92480584
Member Controlled by Flexure (Ve/Vr < 1)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 Ve = (Mpr1 + Mpr2)/ln ± wu*ln/2 = 535287.788
with
Mpr1 = Max(Mu1+ , Mu1-) = 7.8817E+008
Mu1+ = 4.6479E+008, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
Mu1- = 7.8817E+008, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
Mpr2 = Max(Mu2+ , Mu2-) = 7.8817E+008
Mu2+ = 4.6479E+008, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
Mu2- = 7.8817E+008, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination
and
± wu*ln = (|V1| + |V2|)/2
with

```

V1 = 9840.632, is the shear force acting at edge 1 for the the static loading combination
V2 = 9840.634, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu1+

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.6369735E-005$$

$$Mu = 4.6479E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00680405$$

$$w_e \text{ (5.4c)} = 0.00682295$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 872.4558$$

$$fy_1 = 727.0465$$

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 727.0465

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 882.7854

fy2 = 735.6545

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 735.6545

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 937.50

fyv = 781.25

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.06860752

2 = Asl,com/(b*d)*(fs2/fc) = 0.12378842

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00

d = 597.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08477074

2 = Asl,com/(b*d)*(fs2/fc) = 0.15295169

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.09460844

Mu = MRc (4.14) = 4.6479E+008

u = su (4.1) = 5.6369735E-005

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_1

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 6.0907698E-005$$

$$\mu_1 = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_c^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.00680405$$

$$\mu_{we} \text{ (5.4c)} = 0.00682295$$

$$\mu_{ase} \text{ ((5.4d), TBDY)} = (\mu_{ase1} * A_{ext} + \mu_{ase2} * A_{int}) / A_{sec} = 0.14776895$$

$$\mu_{ase1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$\mu_{ase2} = \text{Max}(\mu_{ase1}, \mu_{ase2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$\mu_{psh, \min} * F_{ywe} = \text{Min}(\mu_{psh, x} * F_{ywe}, \mu_{psh, y} * F_{ywe}) = 1.38519$$

$$\mu_{psh, x} * F_{ywe} = \mu_{psh1} * F_{ywe1} + \mu_{ps2} * F_{ywe2} = 2.45559$$

$$\mu_{ps1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$\mu_{ps2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$\mu_{psh, y} * F_{ywe} = \mu_{psh1} * F_{ywe1} + \mu_{ps2} * F_{ywe2} = 1.38519$$

$$\mu_{ps1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$\mu_{ps2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \mu_{cc} = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 882.7854$$

$$fy1 = 735.6545$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 735.6545$$

$$\text{with } Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 872.4558$$

$$fy2 = 727.0465$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 727.0465$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 937.50$$

$$fyv = 781.25$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.12378842$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.06860752$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.15295169$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.08477074$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is not satisfied

---->

v < vs,c - RHS eq.(4.5) is satisfied

--->

$$s_u(4.8) = 0.16206515$$

$$\mu = M_{Rc}(4.15) = 7.8817E+008$$

$$u = s_u(4.1) = 6.0907698E-005$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 5.6369735E-005$$

$$\mu = 4.6479E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.00680405$$

$$\mu_{cc}(5.4c) = 0.00682295$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o1} = 340.00$$

$$h_{o1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o2} = 192.00$$

$$h_{o2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.45559$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 1.38519$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$fy_{we2} = 656.25$$

$$f_{ce} = 30.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 872.4558$$

$$fy_1 = 727.0465$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su_1 = 0.4 * esu_{1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{1_nominal} = 0.08$,

For calculation of $esu_{1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 727.0465$$

$$\text{with } Es_1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 882.7854$$

$$fy_2 = 735.6545$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 1.00$$

$$su_2 = 0.4 * esu_{2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,

For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 735.6545$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 937.50$$

$$fy_v = 781.25$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 781.25$$

$$\text{with } Es_v = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.06860752$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.12378842$$

$$v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.08477074$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.15295169$$

$$v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.09460844$$

$$M_u = M_{Rc}(4.14) = 4.6479E+008$$

$$u = s_u(4.1) = 5.6369735E-005$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_2 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 6.0907698E-005$$

$$M_u = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.00680405$$

$$\mu_{cc}(5.4c) = 0.00682295$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o,1} = 340.00$$

$$h_{o,1} = 610.00$$

$$b_{i2,1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o,2} = 192.00$$

$$h_{o,2} = 492.00$$

$$b_{i2,2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh,x} * F_{ywe}, p_{sh,y} * F_{ywe}) = 1.38519$$

$$p_{sh,x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir,2} * n_{s,2} = 100.531$$

$$\text{No stirups, } n_{s,2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh,y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir,1} * n_{s,1} = 157.0796$$

$$\text{No stirups, } n_{s,1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir,2} * n_{s,2} = 100.531$$

$$\text{No stirups, } n_{s,2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 882.7854
fy1 = 735.6545
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 735.6545

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 872.4558
fy2 = 727.0465
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 727.0465

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 937.50
fyv = 781.25
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.12378842

2 = Asl,com/(b*d)*(fs2/fc) = 0.06860752

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00
d = 597.00
d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15295169

$$2 = A_{sl,com}/(b*d)*(f_s2/f_c) = 0.08477074$$

$$v = A_{sl,mid}/(b*d)*(f_{sv}/f_c) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->
 $v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$$s_u(4.8) = 0.16206515$$

$$M_u = M_{Rc}(4.15) = 7.8817E+008$$

$$u = s_u(4.1) = 6.0907698E-005$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 578810.994$

Calculation of Shear Strength at edge 1, $V_{r1} = 578810.994$

$$V_{r1} = V_n((22.5.1.1), \text{ACI } 318-14)$$

NOTE: In expression (22.5.1.1) 'V_w' is replaced by 'V_w + f*V_f'
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c_jacket} * \text{Area}_{jacket} + f'_{c_core} * \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$$p_w = A_s / (b_w * d) = 0.00331157$$

$$A_s (\text{tension reinf.}) = 709.9999$$

$$b_w = 400.00$$

$$d = 536.00$$

$$V_u * d / M_u < 1 = 1.00$$

$$M_u = 1.1510E+006$$

$$V_u = 9840.632$$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$

$V_{s1} = 350811.18$ is calculated for jacket, with:

$$d = 536.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 150.00$$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 35185.838$ is calculated for jacket, with:

$$d_2 = 400.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 300.00$$

V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$$2(1-s/d) = 0.50$$

$$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$$

$$\text{From } (11-11), \text{ACI } 440: V_s + V_f \leq 750430.726$$

Calculation of Shear Strength at edge 2, $V_{r2} = 578810.994$

$$V_{r2} = V_n((22.5.1.1), \text{ACI } 318-14)$$

NOTE: In expression (22.5.1.1) 'V_w' is replaced by 'V_w + f*V_f'
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c_jacket} * \text{Area}_{jacket} + f'_{c_core} * \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$pw = As/(bw*d) = 0.00331157$

As (tension reinf.) = 709.9999

$bw = 400.00$

$d = 536.00$

$Vu*d/Mu < 1 = 1.00$

$Mu = 1.1510E+006$

$Vu = 9840.634$

From (11.5.4.8), ACI 318-14: $Vs1 + Vs2 = 385997.017$

$Vs1 = 350811.18$ is calculated for jacket, with:

$d = 536.00$

$Av = 157079.633$

$fy = 625.00$

$s = 150.00$

$Vs1$ has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$Vs2 = 35185.838$ is calculated for jacket, with:

$d = 400.00$

$Av = 100530.965$

$fy = 525.00$

$s = 300.00$

$Vs2$ has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$2(1-s/d) = 0.50$

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $Vs + Vf <= 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $fc = fcm = 30.00$

New material of Primary Member: Steel Strength, $fs = fsm = 625.00$

Concrete Elasticity, $Ec = 25742.96$

Steel Elasticity, $Es = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $fc = fcm = 24.00$

Existing material of Primary Member: Steel Strength, $fs = fsm = 525.00$

Concrete Elasticity, $Ec = 23025.204$

Steel Elasticity, $Es = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $fs = 1.25*fsm = 781.25$

Existing Column

Existing material: Steel Strength, $fs = 1.25*fsm = 656.25$

#####

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.04251

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, \min} >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -6.9728406E-015$
EDGE -B-
Shear Force, $V_b = 6.9728406E-015$
BOTH EDGES
Axial Force, $F = -2309.834$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,t} = 709.9999$
-Compression: $A_{sl,c} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 911.0619$
-Compression: $A_{sl,com} = 911.0619$
-Middle: $A_{sl,mid} = 556.0619$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.55914272$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 218168.257$
with
 $M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.2725E+008$
 $Mu_{1+} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $Mu_{1-} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.2725E+008$
 $Mu_{2+} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
 $Mu_{2-} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = -6.9728406E-015$, is the shear force acting at edge 1 for the the static loading combination
 $V_2 = 6.9728406E-015$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 0.00010507$
 $M_u = 3.2725E+008$

with full section properties:

$b = 670.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$

$f_c = 30.00$

ϕ_o (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_o) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00680405$

w_e (5.4c) = 0.00682295
 $a_{se} ((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$
 $a_{se1} = 0.14776895$
 $b_{o_1} = 340.00$
 $h_{o_1} = 610.00$
 $b_{i2_1} = 975400.00$
 $a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$
 $b_{o_2} = 192.00$
 $h_{o_2} = 492.00$
 $b_{i2_2} = 557856.00$
 $p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$

$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$
 $p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$
 $A_{sh1} = A_{stir, 1} * n_{s, 1} = 157.0796$
 No stirrups, $n_{s, 1} = 2.00$
 $h_1 = 670.00$
 $p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$
 $A_{sh2} = A_{stir, 2} * n_{s, 2} = 100.531$
 No stirrups, $n_{s, 2} = 2.00$
 $h_2 = 500.00$

$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$
 $p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$
 $A_{sh1} = A_{stir, 1} * n_{s, 1} = 157.0796$
 No stirrups, $n_{s, 1} = 2.00$
 $h_1 = 400.00$
 $p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$
 $A_{sh2} = A_{stir, 2} * n_{s, 2} = 100.531$
 No stirrups, $n_{s, 2} = 2.00$
 $h_2 = 200.00$

$A_{sec} = 268000.00$
 $s_1 = 150.00$
 $s_2 = 300.00$
 $f_{ywe1} = 781.25$
 $f_{ywe2} = 656.25$
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00242514$
 $c = \text{confinement factor} = 1.04251$

$y_1 = 0.0025$
 $sh_1 = 0.008$
 $ft_1 = 886.8103$
 $fy_1 = 739.0086$
 $su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$

$l_o / l_{ou, \min} = l_b / l_d = 1.00$

$su_1 = 0.4 * esu_{1, \text{nominal}} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu_{1, \text{nominal}}$ and y_1, sh_1, ft_1, fy_1 , it is considered
 characteristic value $fs_{y1} = fs_1 / 1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (f_{s, \text{jacket}} * A_{s, \text{ten, jacket}} + f_{s, \text{core}} * A_{s, \text{ten, core}}) / A_{s, \text{ten}} = 739.0086$

with $Es_1 = (E_{s, \text{jacket}} * A_{s, \text{ten, jacket}} + E_{s, \text{core}} * A_{s, \text{ten, core}}) / A_{s, \text{ten}} = 200000.00$

$y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 886.8103$
 $fy_2 = 739.0086$
 $su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$

$l_o / l_{ou, \min} = l_b / l_{b, \min} = 1.00$

$su_2 = 0.4 * esu_{2, \text{nominal}} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu_{2, \text{nominal}} = 0.08$,

For calculation of $es_{2,nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 739.0086$

with $Es_2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$y_v = 0.0025$

$sh_v = 0.008$

$ft_v = 895.9746$

$fy_v = 746.6455$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 1.00$

$suv = 0.4 \cdot es_{uv,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{uv,nominal} = 0.08$,

considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY

For calculation of $es_{uv,nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_v = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 746.6455$

with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.09382814$

$2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.09382814$

$v = Asl_{mid} / (b \cdot d) \cdot (fs_v / fc) = 0.05785932$

and confined core properties:

$b = 610.00$

$d = 327.00$

$d' = 13.00$

$fcc (5A.2, TBDY) = 31.27541$

$cc (5A.5, TBDY) = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.11251192$

$2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.11251192$

$v = Asl_{mid} / (b \cdot d) \cdot (fs_v / fc) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.1468828$

$Mu = MRc (4.14) = 3.2725E+008$

$u = su (4.1) = 0.00010507$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$

$Mu = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$fc = 30.00$

$co (5A.5, TBDY) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 we (5.4c) = 0.00682295
 ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$
 $ase1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$
 $bi2_1 = 975400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.14776895$
 $bo_2 = 192.00$
 $ho_2 = 492.00$
 $bi2_2 = 557856.00$
 $psh_{min} * Fy_{we} = \text{Min}(psh_x * Fy_{we}, psh_y * Fy_{we}) = 1.38519$

 $psh_x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 2.45559$
 $ps1$ (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00261799$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 670.00$
 $ps2$ (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00062519$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 500.00$

 $psh_y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 1.38519$
 $ps1$ (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00156298$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2$ (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00025008$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

 $A_{sec} = 268000.00$
 $s1 = 150.00$
 $s2 = 300.00$
 $fy_{we1} = 781.25$
 $fy_{we2} = 656.25$
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00242514$
 $c = \text{confinement factor} = 1.04251$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 886.8103$
 $fy1 = 739.0086$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00

$lo/lou_{min} = lb/ld = 1.00$

$su1 = 0.4 * esu1_{nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 739.0086$

with $Es1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 886.8103$
 $fy2 = 739.0086$
 $su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,

For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 739.0086$$

$$\text{with } E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 895.9746$$

$$fy_v = 746.6455$$

$$s_{uv} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_d = 1.00$$

$$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 746.6455$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$$

$$1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.09382814$$

$$2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.09382814$$

$$v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.05785932$$

and confined core properties:

$$b = 610.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 31.27541$$

$$c_c (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.11251192$$

$$2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.11251192$$

$$v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.06938071$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$s_u (4.9) = 0.1468828$$

$$\mu_u = M_{Rc} (4.14) = 3.2725E+008$$

$$u = s_u (4.1) = 0.00010507$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_{u2+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010507$$

$$\mu_u = 3.2725E+008$$

with full section properties:

$$b = 670.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0003219$$

$$N = 2309.834$$

$$fc = 30.00$$

$$cc (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00680405$$

$$we (5.4c) = 0.00682295$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$$

$$ase1 = 0.14776895$$

$$bo_1 = 340.00$$

$$ho_1 = 610.00$$

$$bi2_1 = 975400.00$$

$$ase2 = \text{Max}(ase1, ase2) = 0.14776895$$

$$bo_2 = 192.00$$

$$ho_2 = 492.00$$

$$bi2_2 = 557856.00$$

$$psh, \min * Fywe = \text{Min}(psh, x * Fywe, psh, y * Fywe) = 1.38519$$

$$psh, x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.45559$$

$$ps1 (\text{external}) = (Ash1 * h1 / s1) / A_{sec} = 0.00261799$$

$$Ash1 = Astir_1 * ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h1 = 670.00$$

$$ps2 (\text{internal}) = (Ash2 * h2 / s2) / A_{sec} = 0.00062519$$

$$Ash2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 500.00$$

$$psh, y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 1.38519$$

$$ps1 (\text{external}) = (Ash1 * h1 / s1) / A_{sec} = 0.00156298$$

$$Ash1 = Astir_1 * ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h1 = 400.00$$

$$ps2 (\text{internal}) = (Ash2 * h2 / s2) / A_{sec} = 0.00025008$$

$$Ash2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s1 = 150.00$$

$$s2 = 300.00$$

$$fywe1 = 781.25$$

$$fywe2 = 656.25$$

$$fce = 30.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } cc = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 886.8103$$

$$fy1 = 739.0086$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_nominal = 0.08,$$

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs, \text{jacket} * A_{sl, \text{jacket}} + fs, \text{core} * A_{sl, \text{core}}) / A_{sl, \text{ten}} = 739.0086$$

$$\text{with } Es1 = (Es, \text{jacket} * A_{sl, \text{jacket}} + Es, \text{core} * A_{sl, \text{core}}) / A_{sl, \text{ten}} = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 886.8103$$

$$fy2 = 739.0086$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_{b,min} = 1.00$

$su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,

For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (fs_{jacket} \cdot A_{sl,com,jacket} + fs_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 739.0086$

with $Es_2 = (Es_{jacket} \cdot A_{sl,com,jacket} + Es_{core} \cdot A_{sl,com,core}) / A_{sl,com} = 200000.00$

$y_v = 0.0025$

$sh_v = 0.008$

$ft_v = 895.9746$

$fy_v = 746.6455$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 1.00$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot A_{sl,mid,jacket} + fs_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 746.6455$

with $Es_v = (Es_{jacket} \cdot A_{sl,mid,jacket} + Es_{mid} \cdot A_{sl,mid,core}) / A_{sl,mid} = 200000.00$

$1 = A_{sl,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.09382814$

$2 = A_{sl,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.09382814$

$v = A_{sl,mid} / (b \cdot d) \cdot (fsv / fc) = 0.05785932$

and confined core properties:

$b = 610.00$

$d = 327.00$

$d' = 13.00$

$fcc (5A.2, TBDY) = 31.27541$

$cc (5A.5, TBDY) = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$1 = A_{sl,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.11251192$

$2 = A_{sl,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.11251192$

$v = A_{sl,mid} / (b \cdot d) \cdot (fsv / fc) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.1468828$

$Mu = MRc (4.14) = 3.2725E+008$

$u = su (4.1) = 0.00010507$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_2 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$

$Mu = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$
 $fc = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $w_e (5.4c) = 0.00682295$
 $ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$
 $ase1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$
 $bi2_1 = 975400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.14776895$
 $bo_2 = 192.00$
 $ho_2 = 492.00$
 $bi2_2 = 557856.00$
 $psh, \min * F_{ywe} = \text{Min}(psh, x * F_{ywe}, psh, y * F_{ywe}) = 1.38519$

$psh, x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.45559$
 $ps1 (external) = (Ash1 * h1 / s1) / A_{sec} = 0.00261799$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 670.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / A_{sec} = 0.00062519$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 500.00$

$psh, y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 1.38519$
 $ps1 (external) = (Ash1 * h1 / s1) / A_{sec} = 0.00156298$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / A_{sec} = 0.00025008$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 268000.00$
 $s1 = 150.00$
 $s2 = 300.00$
 $fywe1 = 781.25$
 $fywe2 = 656.25$
 $fce = 30.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00242514$
 $c = \text{confinement factor} = 1.04251$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 886.8103$
 $fy1 = 739.0086$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$

$lo/lou, \min = lb/d = 1.00$
 $su1 = 0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs, \text{jacket} * A_{sl, \text{ten, jacket}} + fs, \text{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 739.0086$

with $Es1 = (Es, \text{jacket} * A_{sl, \text{ten, jacket}} + Es, \text{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$

$$ft2 = 886.8103$$

$$fy2 = 739.0086$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/lb_{u,min} = 1.00$$

$$su2 = 0.4 * esu2_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 739.0086$$

$$\text{with } Es2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 895.9746$$

$$fyv = 746.6455$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 746.6455$$

$$\text{with } Esv = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs1 / fc) = 0.09382814$$

$$2 = A_{sl,com} / (b * d) * (fs2 / fc) = 0.09382814$$

$$v = A_{sl,mid} / (b * d) * (fsv / fc) = 0.05785932$$

and confined core properties:

$$b = 610.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{sl,ten} / (b * d) * (fs1 / fc) = 0.11251192$$

$$2 = A_{sl,com} / (b * d) * (fs2 / fc) = 0.11251192$$

$$v = A_{sl,mid} / (b * d) * (fsv / fc) = 0.06938071$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.1468828$$

$$Mu = MRc (4.14) = 3.2725E+008$$

$$u = su (4.1) = 0.00010507$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $Vr = \text{Min}(Vr1, Vr2) = 390183.487$

Calculation of Shear Strength at edge 1, $Vr1 = 390183.487$

$$Vr1 = Vn ((22.5.1.1), ACI 318-14)$$

NOTE: In expression (22.5.1.1) ' Vw ' is replaced by ' $Vw + f * Vf$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 180743.977$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot Area_jacket + f'_{c_core} \cdot Area_core) / Area_section = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 670.00$
 $d = 320.00$
 $V_u \cdot d / \mu_u < 1 = 0.00$
 $\mu_u = 2.1102257E-011$
 $V_u = 6.9728406E-015$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 209439.51$
 $V_{s1} = 209439.51$ is calculated for jacket, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 0.00$ is calculated for jacket, with:
 $d_2 = 160.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 300.00$
 V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 390183.487$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 180743.977$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot Area_jacket + f'_{c_core} \cdot Area_core) / Area_section = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 670.00$
 $d = 320.00$
 $V_u \cdot d / \mu_u < 1 = 0.00$
 $\mu_u = 1.8034731E-013$
 $V_u = 6.9728406E-015$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 209439.51$
 $V_{s1} = 209439.51$ is calculated for jacket, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 0.00$ is calculated for jacket, with:
 $d = 160.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 300.00$
 V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d \geq 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 5.6603E+006$

Shear Force, $V_2 = -5.4911670E-014$

Shear Force, $V_3 = 4044.434$

Axial Force, $F = -7188.634$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl} = 709.9999$

-Compression: $A_{sc} = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 709.9999$

-Compression: $A_{sl,com} = 1266.062$

-Middle: $A_{sl,mid} = 402.1239$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,jacket} = 402.1239$

-Compression: $A_{sl,com,jacket} = 804.2477$

-Middle: $A_{sl,mid,jacket} = 402.1239$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,core} = 307.8761$

-Compression: $A_{sl,com,core} = 461.8141$

-Middle: $A_{sl,mid,core} = 0.00$

Mean Diameter of Tension Reinforcement, $DbL = 15.00$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = \gamma \cdot u = 0.01180116$

$u = \gamma \cdot u + p = 0.01180116$

- Calculation of ρ_y -

$$y = (M_y * L_s / 3) / E_{eff} = 0.00180116 \text{ ((4.29), Biskinis Phd)}$$
$$M_y = 2.9231E+008$$
$$L_s = M/V \text{ (with } L_s > 0.1 * L \text{ and } L_s < 2 * L) = 1399.522$$
$$\text{From table 10.5, ASCE 41-17: } E_{eff} = 0.3 * E_c * I_g = 7.5708E+013$$

Calculation of Yielding Moment M_y

Calculation of ρ_y and M_y according to Annex 7 -

$$y = \text{Min}(y_{ten}, y_{com})$$
$$y_{ten} = 5.8234912E-006$$
$$\text{with } f_y = 625.00$$
$$d = 627.00$$
$$y = 0.18846616$$
$$A = 0.00953076$$
$$B = 0.00408217$$
$$\text{with } p_t = 0.00283094$$
$$p_c = 0.00504809$$
$$p_v = 0.00160336$$
$$N = 7188.634$$
$$b = 400.00$$
$$\rho = 0.06858054$$
$$y_{comp} = 1.7825663E-005$$
$$\text{with } f_c = 27.76119$$
$$E_c = 25742.96$$
$$y = 0.18768175$$
$$A = 0.00941408$$
$$B = 0.0040338$$
$$\text{with } E_s = 200000.00$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ -

From table 10-7: $\rho = 0.01$

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.92480584$

- Transverse Reinforcement: C

- Stirrup Spacing $\leq d/3$

- Low ductility demand, $\rho_y / \rho < 2$ (table 10-6, ASCE 41-17)

$$= 5.9873569E-005$$

- Stirrup Spacing $\leq d/2$

$$d = d_{external} = 627.00$$

$$s = s_{external} = 150.00$$

- Strength provided by hoops $V_s < 3/4 * \text{design Shear}$

$V_s = 421182.855$, already given in calculation of shear control ratio

design Shear = 4044.434

- ($\rho_c - \rho'_{bal}$)/ $\rho_{bal} = -0.3178459$

$$= A_{st} / (b_w * d) = 0.00283094$$

Tension Reinf Area: $A_{st} = 709.9999$

$$\rho' = A_{sc} / (b_w * d) = 0.00665146$$

Compression Reinf Area: $A_{sc} = 1668.186$

From (B-1), ACI 318-11: $\rho_{bal} = 0.01202003$

$$f_c = (f_{c_jacket} * \text{Area}_{jacket} + f_{c_core} * \text{Area}_{core}) / \text{section_area} = 27.76119$$

$$f_y = f_{y_jacket_bars} = 625.00$$

From 10.2.7.3, ACI 318-11: $\rho_1 = 0.65$

$$\text{From fig R10.3.3, ACI 318-11 (Ence 454, too): } 87000 / (87000 + f_y) = c_b / d_t = 0.003 / (0.003 + \rho_y) = 0.48979592$$

$$y = 0.003125$$

$$- V/(bw*d*fc^{0.5}) = 0.03685823, \text{ NOTE: units in lb \& in}$$

$$bw = 400.00$$

End Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 3

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 20.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$
Concrete Elasticity, $E_c = 23025.204$
Steel Elasticity, $E_s = 200000.00$
External Height, $H = 670.00$
External Width, $W = 400.00$
Internal Height, $H = 500.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = 5.6603E+006$
Shear Force, $V_a = 4044.434$
EDGE -B-
Bending Moment, $M_b = 1.1729E+007$
Shear Force, $V_b = 15636.832$
BOTH EDGES
Axial Force, $F = -7188.634$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 709.9999$
-Compression: $A_{st,com} = 1266.062$
-Middle: $A_{st,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 15.00$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 460997.117$
 V_n ((22.5.1.1), ACI 318-14) = 460997.117

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f_v V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 152199.503$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} * Area_{jacket} + f'_{c_core} * Area_{core}) / Area_{section} = 18.50746$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w * d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 400.00$
 $d = 536.00$
 $V_u * d / M_u < 1 = 0.38298791$
 $M_u = 5.6603E+006$
 $V_u = 4044.434$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 308797.614$
 $V_{s1} = 280648.944$ is calculated for jacket, with:
 $d = 536.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 28148.67$ is calculated for core, with:
 $d = 400.00$
 $A_v = 100530.965$

$$f_y = 420.00$$

$$s = 300.00$$

Vs2 has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$$2(1-s/d) = 0.50$$

$$V_f ((11-3)-(11.4), \text{ACI 440}) = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 612724.122$$

End Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 4

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
Concrete Elasticity, $E_c = 23025.204$
Steel Elasticity, $E_s = 200000.00$

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$
Existing Column
Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$

External Height, $H = 670.00$
External Width, $W = 400.00$
Internal Height, $H = 500.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.04251
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou, min} >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = 9840.632$
EDGE -B-
Shear Force, $V_b = 9840.634$
BOTH EDGES
Axial Force, $F = -2309.834$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st, ten} = 709.9999$
-Compression: $A_{sc, com} = 1266.062$
-Middle: $A_{sc, mid} = 402.1239$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.92480584$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u * l_n / 2 = 535287.788$
with
 $M_{pr1} = \text{Max}(M_{u1+} , M_{u1-}) = 7.8817E+008$
 $M_{u1+} = 4.6479E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $M_{u1-} = 7.8817E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(M_{u2+} , M_{u2-}) = 7.8817E+008$
 $M_{u2+} = 4.6479E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $M_{u2-} = 7.8817E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination
and
 $\pm w_u * l_n = (|V1| + |V2|)/2$
with
 $V1 = 9840.632$, is the shear force acting at edge 1 for the the static loading combination
 $V2 = 9840.634$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu1+

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.6369735E-005$$

$$\text{Mu} = 4.6479E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00680405$$

$$w_e \text{ (5.4c)} = 0.00682295$$

$$\text{ase ((5.4d), TBDY)} = (\text{ase1} * A_{\text{ext}} + \text{ase2} * A_{\text{int}}) / A_{\text{sec}} = 0.14776895$$

$$\text{ase1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$\text{ase2} = \text{Max}(\text{ase1}, \text{ase2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$\text{psh}_{\text{min}} * F_{ywe} = \text{Min}(\text{psh}_{x} * F_{ywe}, \text{psh}_{y} * F_{ywe}) = 1.38519$$

$$\text{psh}_{x} * F_{ywe} = \text{psh1} * F_{ywe1} + \text{ps2} * F_{ywe2} = 2.45559$$

$$\text{ps1 (external)} = (A_{sh1} * h_1 / s_1) / A_{\text{sec}} = 0.00261799$$

$$A_{sh1} = A_{\text{stir}_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$\text{ps2 (internal)} = (A_{sh2} * h_2 / s_2) / A_{\text{sec}} = 0.00062519$$

$$A_{sh2} = A_{\text{stir}_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$\text{psh}_{y} * F_{ywe} = \text{psh1} * F_{ywe1} + \text{ps2} * F_{ywe2} = 1.38519$$

$$\text{ps1 (external)} = (A_{sh1} * h_1 / s_1) / A_{\text{sec}} = 0.00156298$$

$$A_{sh1} = A_{\text{stir}_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$\text{ps2 (internal)} = (A_{sh2} * h_2 / s_2) / A_{\text{sec}} = 0.00025008$$

$$A_{sh2} = A_{\text{stir}_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{\text{sec}} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } c_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 872.4558$$

$$fy_1 = 727.0465$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 727.0465

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 882.7854

fy2 = 735.6545

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 735.6545

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 937.50

fyv = 781.25

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.06860752

2 = Asl,com/(b*d)*(fs2/fc) = 0.12378842

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00

d = 597.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08477074

2 = Asl,com/(b*d)*(fs2/fc) = 0.15295169

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.09460844

Mu = MRc (4.14) = 4.6479E+008

u = su (4.1) = 5.6369735E-005

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_1 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 6.0907698E-005$$

$$\mu_1 = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_1: \mu_1^* = \text{shear_factor} * \text{Max}(\mu_1, c_o) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_1 = 0.00680405$$

$$w_e \text{ (5.4c)} = 0.00682295$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{sh1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{sh2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{sh1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{sh2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } c_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 735.6545

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 872.4558

fy2 = 727.0465

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 727.0465

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 937.50

fyv = 781.25

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.12378842

2 = Asl,com/(b*d)*(fs2/fc) = 0.06860752

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00

d = 597.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15295169

2 = Asl,com/(b*d)*(fs2/fc) = 0.08477074

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is not satisfied

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

su (4.8) = 0.16206515

Mu = MRc (4.15) = 7.8817E+008

$$u = s_u(4.1) = 6.0907698E-005$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 5.6369735E-005$$

$$\mu = 4.6479E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.00680405$$

$$\mu_{cc} \text{ (5.4c)} = 0.00682295$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } \mu_{cc} = 0.00242514$$

$c = \text{confinement factor} = 1.04251$
 $y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 872.4558$
 $fy1 = 727.0465$
 $su1 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/ld = 1.00$
 $su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu1_nominal = 0.08$,
 For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs1 = (fs,jacket * Asl,ten,jacket + fs,core * Asl,ten,core) / Asl,ten = 727.0465$
 with $Es1 = (Es,jacket * Asl,ten,jacket + Es,core * Asl,ten,core) / Asl,ten = 200000.00$
 $y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 882.7854$
 $fy2 = 735.6545$
 $su2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/lb,min = 1.00$
 $su2 = 0.4 * esu2_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_nominal = 0.08$,
 For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs,jacket * Asl,com,jacket + fs,core * Asl,com,core) / Asl,com = 735.6545$
 with $Es2 = (Es,jacket * Asl,com,jacket + Es,core * Asl,com,core) / Asl,com = 200000.00$
 $yv = 0.0025$
 $shv = 0.008$
 $ftv = 937.50$
 $fyv = 781.25$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$
 $lo/lou,min = lb/ld = 1.00$
 $suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_nominal = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs,jacket * Asl,mid,jacket + fs,mid * Asl,mid,core) / Asl,mid = 781.25$
 with $Es_v = (Es,jacket * Asl,mid,jacket + Es,mid * Asl,mid,core) / Asl,mid = 200000.00$
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.06860752$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.12378842$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.04175429$
 and confined core properties:
 $b = 340.00$
 $d = 597.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = Asl,ten / (b * d) * (fs1 / fc) = 0.08477074$
 $2 = Asl,com / (b * d) * (fs2 / fc) = 0.15295169$
 $v = Asl,mid / (b * d) * (fsv / fc) = 0.05159117$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied

--->

$$s_u(4.9) = 0.09460844$$

$$\mu = M_{Rc}(4.14) = 4.6479E+008$$

$$u = s_u(4.1) = 5.6369735E-005$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 6.0907698E-005$$

$$\mu = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, TBDY) = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.00680405$$

$$\mu_{cc}(5.4c) = 0.00682295$$

$$a_{se}((5.4d), TBDY) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o1} = 340.00$$

$$h_{o1} = 610.00$$

$$b_{i21} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o2} = 192.00$$

$$h_{o2} = 492.00$$

$$b_{i22} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

 $p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.45559$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir, 1} * n_{s, 1} = 157.0796$$

$$\text{No stirups, } n_{s, 1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir, 2} * n_{s, 2} = 100.531$$

$$\text{No stirups, } n_{s, 2} = 2.00$$

$$h_2 = 500.00$$

 $p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 1.38519$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir, 1} * n_{s, 1} = 157.0796$$

$$\text{No stirups, } n_{s, 1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir, 2} * n_{s, 2} = 100.531$$

$$\text{No stirups, } n_{s, 2} = 2.00$$

$$h_2 = 200.00$$

 $A_{sec} = 268000.00$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$fy_{we2} = 656.25$$

$$f_{ce} = 30.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$su_1 = 0.4 * esu_{1_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{1_nominal} = 0.08$,

For calculation of $esu_{1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fsy_1 = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{jacket} * A_{sl,ten,jacket} + fs_{core} * A_{sl,ten,core}) / A_{sl,ten} = 735.6545$$

$$\text{with } Es_1 = (Es_{jacket} * A_{sl,ten,jacket} + Es_{core} * A_{sl,ten,core}) / A_{sl,ten} = 200000.00$$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 872.4558$$

$$fy_2 = 727.0465$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/lb, \min = 1.00$$

$$su_2 = 0.4 * esu_{2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,

For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
characteristic value $fsy_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{jacket} * A_{sl,com,jacket} + fs_{core} * A_{sl,com,core}) / A_{sl,com} = 727.0465$$

$$\text{with } Es_2 = (Es_{jacket} * A_{sl,com,jacket} + Es_{core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 937.50$$

$$fy_v = 781.25$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou, \min = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * A_{sl,mid,jacket} + fs_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 781.25$$

$$\text{with } Es_v = (Es_{jacket} * A_{sl,mid,jacket} + Es_{mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.12378842$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.06860752$$

$$v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{sl,ten} / (b * d) * (fs_1 / f_c) = 0.15295169$$

$$2 = A_{sl,com} / (b * d) * (fs_2 / f_c) = 0.08477074$$

$$v = A_{sl,mid} / (b * d) * (fsv / f_c) = 0.05159117$$

Case/Assumption: Unconfinedsd full section - Steel rupture

satisfies Eq. (4.3)

---->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

μ (4.8) = 0.16206515

$\mu_u = M/R_c$ (4.15) = 7.8817E+008

$u = \mu$ (4.1) = 6.0907698E-005

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 578810.994$

Calculation of Shear Strength at edge 1, $V_{r1} = 578810.994$

$V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot \text{Area}_{jacket} + f'_{c,core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$\rho_w = A_s / (b_w \cdot d) = 0.00331157$

A_s (tension reinf.) = 709.9999

$b_w = 400.00$

$d = 536.00$

$V_u \cdot d / \mu_u < 1 = 1.00$

$\mu_u = 1.1510E+006$

$V_u = 9840.632$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$

$V_{s1} = 350811.18$ is calculated for jacket, with:

$d = 536.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 150.00$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 35185.838$ is calculated for jacket, with:

$d_2 = 400.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 300.00$

V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$2(1-s/d) = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 578810.994$

$V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot \text{Area}_{jacket} + f'_{c,core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$\rho_w = A_s / (b_w \cdot d) = 0.00331157$

A_s (tension reinf.) = 709.9999

$b_w = 400.00$

d = 536.00
Vu*d/Mu < 1 = 1.00
Mu = 1.1510E+006
Vu = 9840.634

From (11.5.4.8), ACI 318-14: Vs1 + Vs2 = 385997.017

Vs1 = 350811.18 is calculated for jacket, with:

d = 536.00
Av = 157079.633
fy = 625.00
s = 150.00

Vs1 has been multiplied by 1 (s < d/2, according to ASCE 41-17,10.3.4)

Vs2 = 35185.838 is calculated for jacket, with:

d = 400.00
Av = 100530.965
fy = 525.00
s = 300.00

Vs2 has been multiplied by 2(1-s/d) (s > d/2, according to ASCE 41-17,10.3.4)

2(1-s/d) = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 750430.726

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00
Mean strength values are used for both shear and moment calculations.
Consequently:

Jacket

New material of Primary Member: Concrete Strength, fc = fcm = 30.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 25742.96

Steel Elasticity, Es = 200000.00

Existing Column

Existing material of Primary Member: Concrete Strength, fc = fcm = 24.00

Existing material of Primary Member: Steel Strength, fs = fsm = 525.00

Concrete Elasticity, Ec = 23025.204

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, fs = 1.25*fsm = 781.25

Existing Column

Existing material: Steel Strength, fs = 1.25*fsm = 656.25

#####

External Height, H = 670.00

External Width, W = 400.00

Internal Height, H = 500.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Mean Confinement Factor overall section = 1.04251

Element Length, L = 3000.00

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou}, \min \geq 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, $V_a = -6.9728406E-015$
EDGE -B-
Shear Force, $V_b = 6.9728406E-015$
BOTH EDGES
Axial Force, $F = -2309.834$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $As_t = 709.9999$
-Compression: $As_c = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $As_{t,ten} = 911.0619$
-Compression: $As_{c,com} = 911.0619$
-Middle: $As_{c,mid} = 556.0619$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.55914272$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 218168.257$
with
 $M_{pr1} = \max(\mu_{1+}, \mu_{1-}) = 3.2725E+008$
 $\mu_{1+} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination
 $\mu_{1-} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination
 $M_{pr2} = \max(\mu_{2+}, \mu_{2-}) = 3.2725E+008$
 $\mu_{2+} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination
 $\mu_{2-} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = -6.9728406E-015$, is the shear force acting at edge 1 for the the static loading combination
 $V_2 = 6.9728406E-015$, is the shear force acting at edge 2 for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:
 $\mu = 0.00010507$
 $\mu_u = 3.2725E+008$

with full section properties:

$b = 670.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$
 $f_c = 30.00$
 $\epsilon_{co} (5A.5, TBDY) = 0.002$
Final value of μ_u : $\mu_u^* = \text{shear_factor} * \max(\mu_u, \mu_{cc}) = 0.00680405$
The Shear_factor is considered equal to 1 (pure moment strength)
From (5.4b), TBDY: $\mu_u = 0.00680405$
 $\mu_{we} (5.4c) = 0.00682295$
 $\mu_{ase} ((5.4d), TBDY) = (ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.14776895$
 $ase_1 = 0.14776895$

bo_1 = 340.00
ho_1 = 610.00
bi2_1 = 975400.00
ase2 = Max(ase1,ase2) = 0.14776895
bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^ 2/3), from 10.3.5, ASCE 41-17.

with $f_{s2} = (f_{s,jacket} \cdot A_{s1,com,jacket} + f_{s,core} \cdot A_{s1,com,core}) / A_{s1,com} = 739.0086$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s1,com,jacket} + E_{s,core} \cdot A_{s1,com,core}) / A_{s1,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 895.9746$
 $fy_v = 746.6455$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{o,min} = l_b/l_d = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = (f_{s,jacket} \cdot A_{s1,mid,jacket} + f_{s,mid} \cdot A_{s1,mid,core}) / A_{s1,mid} = 746.6455$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s1,mid,jacket} + E_{s,mid} \cdot A_{s1,mid,core}) / A_{s1,mid} = 200000.00$
 $1 = A_{s1,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.09382814$
 $2 = A_{s1,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.09382814$
 $v = A_{s1,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.05785932$

and confined core properties:

$b = 610.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = A_{s1,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11251192$
 $2 = A_{s1,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11251192$
 $v = A_{s1,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$su (4.9) = 0.1468828$
 $Mu = MRc (4.14) = 3.2725E+008$
 $u = su (4.1) = 0.00010507$

 Calculation of ratio l_b/l_d

 Adequate Lap Length: $l_b/l_d \geq 1$

 Calculation of Mu_1 -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$
 $Mu = 3.2725E+008$

 with full section properties:

$b = 670.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$
 $f_c = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295
ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895
ase1 = 0.14776895
bo_1 = 340.00
ho_1 = 610.00
bi2_1 = 975400.00
ase2 = Max(ase1,ase2) = 0.14776895
bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fsjacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Esjacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of $es_{2_nominal}$ and y_2 , sh_2, ft_2, fy_2 , it is considered characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 739.0086$

with $Es_2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$y_v = 0.0025$

$sh_v = 0.008$

$ft_v = 895.9746$

$fy_v = 746.6455$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{u,min} = lb/ld = 1.00$

$suv = 0.4 \cdot es_{uv_nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $es_{uv_nominal} = 0.08$,

considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v , sh_v, ft_v, fy_v , it is considered characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.

y_1 , sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_v = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 746.6455$

with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.09382814$

$2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.09382814$

$v = Asl_{mid} / (b \cdot d) \cdot (fs_v / fc) = 0.05785932$

and confined core properties:

$b = 610.00$

$d = 327.00$

$d' = 13.00$

$fcc (5A.2, TBDY) = 31.27541$

$cc (5A.5, TBDY) = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.11251192$

$2 = Asl_{com} / (b \cdot d) \cdot (fs_2 / fc) = 0.11251192$

$v = Asl_{mid} / (b \cdot d) \cdot (fs_v / fc) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.1468828$

$Mu = MRc (4.14) = 3.2725E+008$

$u = su (4.1) = 0.00010507$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$

$Mu = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$fc = 30.00$

$co (5A.5, TBDY) = 0.002$

Final value of c_u : $c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.00680405$

w_e (5.4c) = 0.00682295

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$

$a_{se1} = 0.14776895$

$b_{o_1} = 340.00$

$h_{o_1} = 610.00$

$b_{i2_1} = 975400.00$

$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$

$b_{o_2} = 192.00$

$h_{o_2} = 492.00$

$b_{i2_2} = 557856.00$

$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$

 $p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$

p_{s1} (external) = $(A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$

$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$

No stirups, $n_{s_1} = 2.00$

$h_1 = 670.00$

p_{s2} (internal) = $(A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$

$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$

No stirups, $n_{s_2} = 2.00$

$h_2 = 500.00$

 $p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$

p_{s1} (external) = $(A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$

$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$

No stirups, $n_{s_1} = 2.00$

$h_1 = 400.00$

p_{s2} (internal) = $(A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$

$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$

No stirups, $n_{s_2} = 2.00$

$h_2 = 200.00$

 $A_{sec} = 268000.00$

$s_1 = 150.00$

$s_2 = 300.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$y_1 = 0.0025$

$sh_1 = 0.008$

$ft_1 = 886.8103$

$fy_1 = 739.0086$

$su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_o / l_{o, \min} = l_b / l_d = 1.00$

$su_1 = 0.4 * esu_{1, \text{nominal}}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu_{1, \text{nominal}}$ and y_1, sh_1, ft_1, fy_1 , it is considered
characteristic value $fs_1 = fs_1 / 1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (f_{s, \text{jacket}} * A_{s, \text{ten, jacket}} + f_{s, \text{core}} * A_{s, \text{ten, core}}) / A_{s, \text{ten}} = 739.0086$

with $Es_1 = (E_{s, \text{jacket}} * A_{s, \text{ten, jacket}} + E_{s, \text{core}} * A_{s, \text{ten, core}}) / A_{s, \text{ten}} = 200000.00$

$y_2 = 0.0025$

$sh_2 = 0.008$

$ft_2 = 886.8103$

$fy_2 = 739.0086$

$su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,

For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = (f_{s,jacket} * A_{sl,com,jacket} + f_{s,core} * A_{sl,com,core}) / A_{sl,com} = 739.0086$$

$$\text{with } E_{s2} = (E_{s,jacket} * A_{sl,com,jacket} + E_{s,core} * A_{sl,com,core}) / A_{sl,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 895.9746$$

$$fy_v = 746.6455$$

$$s_{uv} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_d = 1.00$$

$$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{sl,mid,jacket} + f_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 746.6455$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{sl,mid,jacket} + E_{s,mid} * A_{sl,mid,core}) / A_{sl,mid} = 200000.00$$

$$1 = A_{sl,ten} / (b * d) * (f_{s1} / f_c) = 0.09382814$$

$$2 = A_{sl,com} / (b * d) * (f_{s2} / f_c) = 0.09382814$$

$$v = A_{sl,mid} / (b * d) * (f_{sv} / f_c) = 0.05785932$$

and confined core properties:

$$b = 610.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 31.27541$$

$$c_c (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{sl,ten} / (b * d) * (f_{s1} / f_c) = 0.11251192$$

$$2 = A_{sl,com} / (b * d) * (f_{s2} / f_c) = 0.11251192$$

$$v = A_{sl,mid} / (b * d) * (f_{sv} / f_c) = 0.06938071$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$s_u (4.9) = 0.1468828$$

$$\mu_u = M_{Rc} (4.14) = 3.2725E+008$$

$$u = s_u (4.1) = 0.00010507$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_u

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010507$$

$$\mu_u = 3.2725E+008$$

with full section properties:

$$b = 670.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0003219$$

$$N = 2309.834$$

$$fc = 30.00$$

$$cc \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00680405$$

$$we \text{ (5.4c)} = 0.00682295$$

$$ase \text{ ((5.4d), TBDY)} = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$$

$$ase1 = 0.14776895$$

$$bo_1 = 340.00$$

$$ho_1 = 610.00$$

$$bi2_1 = 975400.00$$

$$ase2 = \text{Max}(ase1, ase2) = 0.14776895$$

$$bo_2 = 192.00$$

$$ho_2 = 492.00$$

$$bi2_2 = 557856.00$$

$$psh, \min * Fy_{we} = \text{Min}(psh, x * Fy_{we}, psh, y * Fy_{we}) = 1.38519$$

$$psh, x * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 2.45559$$

$$ps1 \text{ (external)} = (Ash1 * h1 / s1) / A_{sec} = 0.00261799$$

$$Ash1 = Astir_1 * ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h1 = 670.00$$

$$ps2 \text{ (internal)} = (Ash2 * h2 / s2) / A_{sec} = 0.00062519$$

$$Ash2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 500.00$$

$$psh, y * Fy_{we} = psh1 * Fy_{we1} + ps2 * Fy_{we2} = 1.38519$$

$$ps1 \text{ (external)} = (Ash1 * h1 / s1) / A_{sec} = 0.00156298$$

$$Ash1 = Astir_1 * ns_1 = 157.0796$$

$$\text{No stirups, } ns_1 = 2.00$$

$$h1 = 400.00$$

$$ps2 \text{ (internal)} = (Ash2 * h2 / s2) / A_{sec} = 0.00025008$$

$$Ash2 = Astir_2 * ns_2 = 100.531$$

$$\text{No stirups, } ns_2 = 2.00$$

$$h2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s1 = 150.00$$

$$s2 = 300.00$$

$$fy_{we1} = 781.25$$

$$fy_{we2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } cc = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 886.8103$$

$$fy1 = 739.0086$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lo, \min = lb/ld = 1.00$$

$$su1 = 0.4 * esu1_{nominal} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu1_{nominal} = 0.08,$$

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

$$y1, sh1, ft1, fy1, \text{ are also multiplied by } \text{Min}(1, 1.25 * (lb/ld)^{2/3}), \text{ from 10.3.5, ASCE 41-17.}$$

$$\text{with } fs1 = (fs, \text{jacket} * A_{sl, \text{ten, jacket}} + fs, \text{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 739.0086$$

$$\text{with } Es1 = (Es, \text{jacket} * A_{sl, \text{ten, jacket}} + Es, \text{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 886.8103$$

$$fy2 = 739.0086$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 895.9746

fyv = 746.6455

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09382814

2 = Asl,com/(b*d)*(fs2/fc) = 0.09382814

v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11251192

2 = Asl,com/(b*d)*(fs2/fc) = 0.11251192

v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/ld

Adequate Lap Length: lb/ld >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 390183.487

Calculation of Shear Strength at edge 1, Vr1 = 390183.487

Vr1 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 180743.977

= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 27.76119$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 670.00$
 $d = 320.00$
 $V_u \cdot d / \mu_u < 1 = 0.00$
 $\mu_u = 2.1102257E-011$
 $V_u = 6.9728406E-015$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 209439.51$
 $V_{s1} = 209439.51$ is calculated for jacket, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 0.00$ is calculated for jacket, with:
 $d_2 = 160.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 300.00$
 V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 390183.487$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 180743.977$
= 1 (normal-weight concrete)
Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 27.76119$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 670.00$
 $d = 320.00$
 $V_u \cdot d / \mu_u < 1 = 0.00$
 $\mu_u = 1.8034731E-013$
 $V_u = 6.9728406E-015$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 209439.51$
 $V_{s1} = 209439.51$ is calculated for jacket, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 0.00$ is calculated for jacket, with:
 $d = 160.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 300.00$
 V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1
At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1
At local axis: 3

Integration Section: (a)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/l_d > 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -8.4907098E-011$

Shear Force, $V_2 = -5.4911670E-014$

Shear Force, $V_3 = 4044.434$

Axial Force, $F = -7188.634$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl,t} = 709.9999$

-Compression: $A_{sl,c} = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten} = 911.0619$

-Compression: $A_{sl,com} = 911.0619$

-Middle: $A_{sl,mid} = 556.0619$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,jacket} = 603.1858$

-Compression: $A_{sl,com,jacket} = 603.1858$

-Middle: $A_{sl,mid,jacket} = 402.1239$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl,ten,core} = 307.8761$

-Compression: $A_{sl,com,core} = 307.8761$

-Middle: $A_{sl,mid,core} = 153.938$

Mean Diameter of Tension Reinforcement, $DbL = 15.20$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = \gamma \cdot u = 0.00910271$

$u = \gamma \cdot p = 0.00910271$

- Calculation of γ -

$\gamma = (M_y \cdot L_s / 3) / E_{eff} = 0.00410271$ ((4.29), Biskinis Phd))

My = 2.1250E+008
Ls = M/V (with Ls > 0.1*L and Ls < 2*L) = 1500.00
From table 10.5, ASCE 41_17: Eleff = 0.3*Ec*Ig = 2.5898E+013

Calculation of Yielding Moment My

Calculation of ϕ_y and My according to Annex 7 -

y = Min(y_{ten} , y_{com})
 $y_{ten} = 1.0750437E-005$
with $f_y = 625.00$
d = 357.00
y = 0.22791832
A = 0.00999338
B = 0.00562083
with $p_t = 0.00380895$
pc = 0.00380895
pv = 0.00232477
N = 7188.634
b = 670.00
" = 0.12044818
 $y_{comp} = 2.5846378E-005$
with $f_c = 27.76119$
Ec = 25742.96
y = 0.22733556
A = 0.00987103
B = 0.00557012
with Es = 200000.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of ϕ_p -

From table 10-7: $\phi_p = 0.005$



with:

- Condition i occurred
Beam controlled by flexure: $V_p/V_o \leq 1$
shear control ratio $V_p/V_o = 0.55914272$
- Transverse Reinforcement: NC
- Stirrup Spacing > d/3
- Low ductility demand, $\phi_y < 2$ (table 10-6, ASCE 41-17)
= 8.0465315E-022
- Stirrup Spacing <= d/2
d = d_external = 357.00
s = s_external = 150.00
- Strength provided by hoops $V_s < 3/4$ *design Shear
Vs = 237588.18, already given in calculation of shear control ratio
design Shear = 5.4911670E-014
- (- ')/ bal = -0.33327376
= $A_{sl}/(b_w*d) = 0.00296835$
Tension Reinf Area: $A_{sl} = 709.9999$
' = $A_{slc}/(b_w*d) = 0.00697431$
Compression Reinf Area: $A_{slc} = 1668.186$
- From (B-1), ACI 318-11: bal = 0.01202003
 $f_c = (f_{c_jacket}*Area_jacket + f_{c_core}*Area_core)/section_area = 27.76119$
 $f_y = f_{y_jacket_bars} = 625.00$
From 10.2.7.3, ACI 318-11: $\phi = 0.65$
From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + \phi) = 0.48979592$
y = 0.003125
- $V/(b_w*d*f_c^{0.5}) = 5.2471780E-019$, NOTE: units in lb & in
bw = 670.00

End Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1
At local axis: 3
Integration Section: (a)

Calculation No. 5

beam B1, Floor 1
Limit State: Operational Level (data interpolation between analysis steps 1 and 2)
Analysis: Uniform +X
Check: Shear capacity VRd
Edge: End
Local Axis: (2)



Start Of Calculation of Shear Capacity for element: beam JB1 of floor 1
At local axis: 2
Integration Section: (b)
Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$
Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.
Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17
Consequently:
Jacket
New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 20.00$
New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$
Concrete Elasticity, $E_c = 25742.96$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$
Concrete Elasticity, $E_c = 23025.204$
Steel Elasticity, $E_s = 200000.00$

External Height, H = 670.00
External Width, W = 400.00
Internal Height, H = 500.00
Internal Width, W = 200.00
Cover Thickness, c = 25.00
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -8.4907098E-011$
Shear Force, $V_a = -5.4911670E-014$
EDGE -B-
Bending Moment, $M_b = -7.9998090E-011$
Shear Force, $V_b = 5.4911670E-014$
BOTH EDGES
Axial Force, $F = -7188.634$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 911.0619$
-Compression: $A_{sc,com} = 911.0619$
-Middle: $A_{st,mid} = 556.0619$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 15.20$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 315128.448$
 V_n ((22.5.1.1), ACI 318-14) = 315128.448

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw + ϕV_f '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 147576.839$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 18.50746$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 670.00$
 $d = 320.00$
 $V_u \cdot d / M_u < 1 = 0.00$
 $M_u = 7.9998090E-011$
 $V_u = 5.4911670E-014$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 167551.608$
 $V_{s1} = 167551.608$ is calculated for jacket, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 0.00$ is calculated for core, with:
 $d = 160.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 300.00$
 V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00
 From (11-11), ACI 440: Vs + Vf <= 612724.122

End Of Calculation of Shear Capacity for element: beam JB1 of floor 1
 At local axis: 2
 Integration Section: (b)

Calculation No. 6

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (u)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 3
 (Bending local axis: 2)
 Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.04251

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = 9840.632$

EDGE -B-

Shear Force, $V_b = 9840.634$

BOTH EDGES

Axial Force, $F = -2309.834$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{sl} = 709.9999$

-Compression: $A_{sc} = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{sl, \text{ten}} = 709.9999$

-Compression: $A_{sl, \text{com}} = 1266.062$

-Middle: $A_{sl, \text{mid}} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.92480584$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 535287.788$
with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 7.8817E+008$

$M_{u1+} = 4.6479E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction
which is defined for the static loading combination

$M_{u1-} = 7.8817E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment
direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 7.8817E+008$

$M_{u2+} = 4.6479E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction
which is defined for the the static loading combination

$M_{u2-} = 7.8817E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment
direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|) / 2$

with

$V_1 = 9840.632$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 9840.634$, is the shear force acting at edge 2 for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 5.6369735E-005$$

$$Mu = 4.6479E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.00680405$$

$$\phi_{we} \text{ (5.4c)} = 0.00682295$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_{cc} = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 872.4558$$

$$fy_1 = 727.0465$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{ou, \min} = l_b / d = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}} \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $es1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 727.0465$

with $Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 882.7854$

$fy2 = 735.6545$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{min} = lb/lb_{min} = 1.00$

$su2 = 0.4 \cdot esu2_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 735.6545$

with $Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 937.50$

$fyv = 781.25$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{min} = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 781.25$

with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.06860752$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.12378842$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.04175429$

and confined core properties:

$b = 340.00$

$d = 597.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 31.27541$

$cc (5A.5, TBDY) = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.08477074$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.15295169$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.05159117$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is satisfied

--->

$su (4.9) = 0.09460844$

$Mu = MRc (4.14) = 4.6479E+008$

$u = su (4.1) = 5.6369735E-005$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu1-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$u = 6.0907698E-005$$

$$\mu = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o (5A.5, TBDY) = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00680405$$

$$w_e (5.4c) = 0.00682295$$

$$\text{ase ((5.4d), TBDY) = (ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.14776895}$$

$$\text{ase1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$\text{ase2} = \text{Max}(\text{ase1}, \text{ase2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$\text{psh}_{\min} * F_{ywe} = \text{Min}(\text{psh}_{x} * F_{ywe}, \text{psh}_{y} * F_{ywe}) = 1.38519$$

$$\text{psh}_{x} * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 2.45559$$

$$\text{ps}_1 (\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$\text{ps}_2 (\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$\text{psh}_{y} * F_{ywe} = \text{psh}_1 * F_{ywe1} + \text{ps}_2 * F_{ywe2} = 1.38519$$

$$\text{ps}_1 (\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$\text{ps}_2 (\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_d = 1.00$$

$$s_u1 = 0.4 * e_{s1_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{s1_nominal} = 0.08,$$

For calculation of $e_{s1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_{s1}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s1} = (f_{s,jacket} * A_{s,ten,jacket} + f_{s,core} * A_{s,ten,core}) / A_{s,ten} = 735.6545$$

$$\text{with } E_{s1} = (E_{s,jacket} * A_{s,ten,jacket} + E_{s,core} * A_{s,ten,core}) / A_{s,ten} = 200000.00$$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 872.4558$$

$$fy_2 = 727.0465$$

$$s_u2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{s2_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{s2_nominal} = 0.08,$$

For calculation of $e_{s2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = (f_{s,jacket} * A_{s,com,jacket} + f_{s,core} * A_{s,com,core}) / A_{s,com} = 727.0465$$

$$\text{with } E_{s2} = (E_{s,jacket} * A_{s,com,jacket} + E_{s,core} * A_{s,com,core}) / A_{s,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 937.50$$

$$fy_v = 781.25$$

$$s_{uv} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_0/l_{0u,min} = l_b/l_d = 1.00$$

$$s_{uv} = 0.4 * e_{suv_nominal} ((5.5), TBDY) = 0.032$$

$$\text{From table 5A.1, TBDY: } e_{suv_nominal} = 0.08,$$

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
For calculation of $e_{suv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 781.25$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.12378842$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.06860752$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 31.27541$$

$$c_c (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.15295169$$

$$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.08477074$$

$$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.16206515$$

$$\mu_u = M_{Rc} (4.15) = 7.8817E+008$$

$$u = s_u (4.1) = 6.0907698E-005$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of μ_{2+}

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 5.6369735E-005$$

$$\mu_u = 4.6479E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_u: \mu_u^* = \text{shear_factor} * \text{Max}(\mu_u, \mu_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_u = 0.00680405$$

$$\mu_{ue} \text{ (5.4c)} = 0.00682295$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \mu_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 872.4558$$

$$fy1 = 727.0465$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 727.0465$$

$$\text{with } Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 882.7854$$

$$fy2 = 735.6545$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 735.6545$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 937.50$$

$$fyv = 781.25$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.06860752$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.12378842$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.08477074$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.15295169$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.09460844$$

$$Mu = MRc (4.14) = 4.6479E+008$$

$$u = su (4.1) = 5.6369735E-005$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 6.0907698E-005$$

$$\mu = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu: \mu^* = \text{shear_factor} * \text{Max}(\mu_c, \mu_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_c = 0.00680405$$

$$\mu_{cc} \text{ (5.4c)} = 0.00682295$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o1} = 340.00$$

$$h_{o1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o2} = 192.00$$

$$h_{o2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \mu_{cc} = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

y1 = 0.0025
sh1 = 0.008
ft1 = 882.7854
fy1 = 735.6545
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 735.6545

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 872.4558
fy2 = 727.0465
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 727.0465

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 937.50
fyv = 781.25
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.12378842
2 = Asl,com/(b*d)*(fs2/fc) = 0.06860752
v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00
d = 597.00
d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15295169

2 = Asl,com/(b*d)*(fs2/fc) = 0.08477074

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is not satisfied

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u(4.8) = 0.16206515$$

$$\mu_u = M_{Rc}(4.15) = 7.8817E+008$$

$$u = s_u(4.1) = 6.0907698E-005$$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 578810.994$

Calculation of Shear Strength at edge 1, $V_{r1} = 578810.994$

$$V_{r1} = V_n \text{ ((22.5.1.1), ACI 318-14)}$$

NOTE: In expression (22.5.1.1) 'V_w' is replaced by 'V_w + f*V_f'
where V_f is the contribution of FRPs (11.3), ACI 440).

$$\text{From Table (22.5.5.1), ACI 318-14: } V_c = 192813.976$$

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119, \text{ but } f_c^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$p_w = A_s / (b_w \cdot d) = 0.00331157$$

$$A_s \text{ (tension reinf.)} = 709.9999$$

$$b_w = 400.00$$

$$d = 536.00$$

$$V_u \cdot d / \mu_u < 1 = 1.00$$

$$\mu_u = 1.1510E+006$$

$$V_u = 9840.632$$

$$\text{From (11.5.4.8), ACI 318-14: } V_{s1} + V_{s2} = 385997.017$$

$V_{s1} = 350811.18$ is calculated for jacket, with:

$$d = 536.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 150.00$$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 35185.838$ is calculated for jacket, with:

$$d_2 = 400.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 300.00$$

V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$$2(1-s/d) = 0.50$$

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 750430.726$$

Calculation of Shear Strength at edge 2, $V_{r2} = 578810.994$

$$V_{r2} = V_n \text{ ((22.5.1.1), ACI 318-14)}$$

NOTE: In expression (22.5.1.1) 'V_w' is replaced by 'V_w + f*V_f'
where V_f is the contribution of FRPs (11.3), ACI 440).

$$\text{From Table (22.5.5.1), ACI 318-14: } V_c = 192813.976$$

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119, \text{ but } f_c^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$p_w = A_s / (b_w \cdot d) = 0.00331157$$

$$A_s \text{ (tension reinf.)} = 709.9999$$

$$b_w = 400.00$$

$$d = 536.00$$

$$V_u \cdot d / \mu_u < 1 = 1.00$$

$$\mu_u = 1.1510E+006$$

$$V_u = 9840.634$$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$

$V_{s1} = 350811.18$ is calculated for jacket, with:

$d = 536.00$

$A_v = 157079.633$

$f_y = 625.00$

$s = 150.00$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 35185.838$ is calculated for jacket, with:

$d = 400.00$

$A_v = 100530.965$

$f_y = 525.00$

$s = 300.00$

V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$2(1-s/d) = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$

#####

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.04251

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -6.9728406E-015$

EDGE -B-

Shear Force, $V_b = 6.9728406E-015$

BOTH EDGES

Axial Force, $F = -2309.834$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 709.9999$

-Compression: $As_c = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 911.0619$

-Compression: $As_{c,com} = 911.0619$

-Middle: $As_{l,mid} = 556.0619$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.55914272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 218168.257$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.2725E+008$

$Mu_{1+} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.2725E+008$

$Mu_{2+} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -6.9728406E-015$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 6.9728406E-015$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010507$

$M_u = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$f_c = 30.00$

$\phi_{co} (5A.5, TBDY) = 0.002$

Final value of ϕ_{cu} : $\phi_{cu}^* = \text{shear_factor} \cdot \text{Max}(\phi_{cu}, \phi_{cc}) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_{cu} = 0.00680405$

$w_e (5.4c) = 0.00682295$

$a_{se} ((5.4d), TBDY) = (a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.14776895$

$a_{se1} = 0.14776895$

$bo_1 = 340.00$

$ho_1 = 610.00$

$bi2_1 = 975400.00$

$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$

bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008

$$ftv = 895.9746$$

$$fyv = 746.6455$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv , shv , ftv , fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1$, $sh1$, $ft1$, $fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 746.6455$$

$$\text{with } Es_v = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.09382814$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.09382814$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.05785932$$

and confined core properties:

$$b = 610.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.11251192$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.11251192$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.06938071$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.1468828$$

$$Mu = MRc (4.14) = 3.2725E+008$$

$$u = su (4.1) = 0.00010507$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010507$$

$$Mu = 3.2725E+008$$

with full section properties:

$$b = 670.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0003219$$

$$N = 2309.834$$

$$fc = 30.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00680405$$

$$we (5.4c) = 0.00682295$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$$

$$ase1 = 0.14776895$$

$$bo_1 = 340.00$$

ho_1 = 610.00
bi2_1 = 975400.00
ase2 = Max(ase1,ase2) = 0.14776895
bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb,min)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb,min)^ 2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 895.9746$
 $fy_v = 746.6455$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_y = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_y = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 746.6455$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.09382814$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.09382814$
 $v = A_{s,mid} / (b \cdot d) \cdot (fsv / fc) = 0.05785932$

and confined core properties:

$b = 610.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.11251192$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.11251192$
 $v = A_{s,mid} / (b \cdot d) \cdot (fsv / fc) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$su (4.9) = 0.1468828$
 $Mu = MRc (4.14) = 3.2725E+008$
 $u = su (4.1) = 0.00010507$

 Calculation of ratio lb/ld

 Adequate Lap Length: $lb/ld \geq 1$

 Calculation of Mu_{2+}

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$
 $Mu = 3.2725E+008$

 with full section properties:

$b = 670.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$
 $fc = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $we (5.4c) = 0.00682295$

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895
ase1 = 0.14776895
bo_1 = 340.00
ho_1 = 610.00
bi2_1 = 975400.00
ase2 = Max(ase1,ase2) = 0.14776895
bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered

characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s2} = (f_{sjacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core})/A_{s,com} = 739.0086$

with $E_{s2} = (E_{sjacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core})/A_{s,com} = 200000.00$

$y_v = 0.0025$

$sh_v = 0.008$

$ft_v = 895.9746$

$fy_v = 746.6455$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 1.00$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered

characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{sjacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 746.6455$

with $E_{sv} = (E_{sjacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 200000.00$

1 = $A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.09382814$

2 = $A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.09382814$

v = $A_{s,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.05785932$

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

f_{cc} (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = $A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.11251192$

2 = $A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.11251192$

v = $A_{s,mid}/(b \cdot d) \cdot (f_{sv}/f_c) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu2-

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

u = 0.00010507

Mu = 3.2725E+008

with full section properties:

b = 670.00

d = 357.00

d' = 43.00

v = 0.0003219

N = 2309.834

f_c = 30.00

co (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.00680405$

w_e (5.4c) = 0.00682295

a_{se} ((5.4d), TBDY) = $(a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$

$a_{se1} = 0.14776895$

$b_{o_1} = 340.00$

$h_{o_1} = 610.00$

$b_{i2_1} = 975400.00$

$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$

$b_{o_2} = 192.00$

$h_{o_2} = 492.00$

$b_{i2_2} = 557856.00$

$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$

$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$

p_{s1} (external) = $(A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$

$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$

No stirups, $n_{s_1} = 2.00$

$h_1 = 670.00$

p_{s2} (internal) = $(A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$

$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$

No stirups, $n_{s_2} = 2.00$

$h_2 = 500.00$

$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$

p_{s1} (external) = $(A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$

$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$

No stirups, $n_{s_1} = 2.00$

$h_1 = 400.00$

p_{s2} (internal) = $(A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$

$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$

No stirups, $n_{s_2} = 2.00$

$h_2 = 200.00$

$A_{sec} = 268000.00$

$s_1 = 150.00$

$s_2 = 300.00$

$f_{ywe1} = 781.25$

$f_{ywe2} = 656.25$

$f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY: $c_c = 0.00242514$

c = confinement factor = 1.04251

$y_1 = 0.0025$

$sh_1 = 0.008$

$ft_1 = 886.8103$

$fy_1 = 739.0086$

$su_1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o / l_{ou, \min} = l_b / l_d = 1.00$

$su_1 = 0.4 * e_{su1_nominal}$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $e_{su1_nominal} = 0.08$,

For calculation of $e_{su1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $f_{sy1} = f_s / 1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b / l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s, \text{jacket}} * A_{s1, \text{ten, jacket}} + f_{s, \text{core}} * A_{s1, \text{ten, core}}) / A_{s1, \text{ten}} = 739.0086$

with $E_{s1} = (E_{s, \text{jacket}} * A_{s1, \text{ten, jacket}} + E_{s, \text{core}} * A_{s1, \text{ten, core}}) / A_{s1, \text{ten}} = 200000.00$

$y_2 = 0.0025$

$sh_2 = 0.008$

$ft_2 = 886.8103$

$fy_2 = 739.0086$

$su_2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$l_o / l_{ou, \min} = l_b / l_{b, \min} = 1.00$

$$su_2 = 0.4 * esu_{2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esu_{2_nominal} = 0.08$,

For calculation of $esu_{2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fs_2 = fs_2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_2 = (fs_{jacket} * Asl_{,com,jacket} + fs_{core} * Asl_{,com,core}) / Asl_{,com} = 739.0086$$

$$\text{with } Es_2 = (Es_{jacket} * Asl_{,com,jacket} + Es_{core} * Asl_{,com,core}) / Asl_{,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 895.9746$$

$$fy_v = 746.6455$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou_{,min} = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY
For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $fs_v = fs_v/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_v = (fs_{jacket} * Asl_{,mid,jacket} + fs_{mid} * Asl_{,mid,core}) / Asl_{,mid} = 746.6455$$

$$\text{with } Es_v = (Es_{jacket} * Asl_{,mid,jacket} + Es_{mid} * Asl_{,mid,core}) / Asl_{,mid} = 200000.00$$

$$1 = Asl_{,ten} / (b * d) * (fs_1 / fc) = 0.09382814$$

$$2 = Asl_{,com} / (b * d) * (fs_2 / fc) = 0.09382814$$

$$v = Asl_{,mid} / (b * d) * (fs_v / fc) = 0.05785932$$

and confined core properties:

$$b = 610.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl_{,ten} / (b * d) * (fs_1 / fc) = 0.11251192$$

$$2 = Asl_{,com} / (b * d) * (fs_2 / fc) = 0.11251192$$

$$v = Asl_{,mid} / (b * d) * (fs_v / fc) = 0.06938071$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.1468828$$

$$\mu_u = MR_c (4.14) = 3.2725E+008$$

$$u = su (4.1) = 0.00010507$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 390183.487$

Calculation of Shear Strength at edge 1, $V_{r1} = 390183.487$

$$V_{r1} = V_n ((22.5.1.1), ACI 318-14)$$

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

$$\text{From Table (22.5.5.1), ACI 318-14: } V_c = 180743.977$$

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } fc' = (fc'_{jacket} * Area_{jacket} + fc'_{core} * Area_{core}) / Area_{section} = 27.76119, \text{ but } fc'^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$pw = As / (bw * d) = 0.00331157$$

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

$V_u*d/\mu < 1 = 0.00$

$\mu = 2.1102257E-011$

$V_u = 6.9728406E-015$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 209439.51$

$V_{s1} = 209439.51$ is calculated for jacket, with:

d = 320.00

$A_v = 157079.633$

$f_y = 625.00$

s = 150.00

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 0.00$ is calculated for jacket, with:

d2 = 160.00

$A_v = 100530.965$

$f_y = 525.00$

s = 300.00

V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 390183.487$

$V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f*V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 180743.977$

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c_jacket}*Area_jacket + f'_{c_core}*Area_core)/Area_section = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$p_w = A_s/(b_w*d) = 0.00331157$

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

$V_u*d/\mu < 1 = 0.00$

$\mu = 1.8034731E-013$

$V_u = 6.9728406E-015$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 209439.51$

$V_{s1} = 209439.51$ is calculated for jacket, with:

d = 320.00

$A_v = 157079.633$

$f_y = 625.00$

s = 150.00

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 0.00$ is calculated for jacket, with:

d = 160.00

$A_v = 100530.965$

$f_y = 525.00$

s = 300.00

V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\phi = 1.00$
 Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.
 Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17
 Consequently:
 Jacket
 New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$
 New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
 Concrete Elasticity, $E_c = 25742.96$
 Steel Elasticity, $E_s = 200000.00$
 Existing Column
 Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
 Concrete Elasticity, $E_c = 23025.204$
 Steel Elasticity, $E_s = 200000.00$
 External Height, $H = 670.00$
 External Width, $W = 400.00$
 Internal Height, $H = 500.00$
 Internal Width, $W = 200.00$
 Cover Thickness, $c = 25.00$
 Element Length, $L = 3000.00$
 Primary Member
 Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_b/l_d > 1$)
 No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 1.1729E+007$
 Shear Force, $V_2 = 5.4911670E-014$
 Shear Force, $V_3 = 15636.832$
 Axial Force, $F = -7188.634$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 709.9999$
 -Compression: $A_{sc} = 1668.186$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 709.9999$
 -Compression: $A_{st,com} = 1266.062$
 -Middle: $A_{st,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten,jacket} = 402.1239$
 -Compression: $A_{st,com,jacket} = 804.2477$
 -Middle: $A_{st,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten,core} = 307.8761$
 -Compression: $A_{st,com,core} = 461.8141$
 -Middle: $A_{st,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $D_bL = 15.00$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \phi \cdot u = 0.01096533$
 $u = y + p = 0.01096533$

- Calculation of y -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.00096533$ ((4.29), Biskinis Phd)
 $M_y = 2.9231E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 750.0722
 From table 10.5, ASCE 41_17: $E_{eff} = 0.3 \cdot E_c \cdot I_g = 7.5708E+013$

Calculation of Yielding Moment M_y

Calculation of ρ_y and M_y according to Annex 7 -

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 5.8234912\text{E-}006$
with $f_y = 625.00$
 $d = 627.00$
 $y = 0.18846616$
 $A = 0.00953076$
 $B = 0.00408217$
with $p_t = 0.00283094$
 $p_c = 0.00504809$
 $p_v = 0.00160336$
 $N = 7188.634$
 $b = 400.00$
 $\rho = 0.06858054$
 $y_{\text{comp}} = 1.7825663\text{E-}005$
with $f_c = 27.76119$
 $E_c = 25742.96$
 $y = 0.18768175$
 $A = 0.00941408$
 $B = 0.0040338$
with $E_s = 200000.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ -

From table 10-7: $\rho = 0.01$

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.92480584$

- Transverse Reinforcement: C

- Stirrup Spacing $\leq d/3$

- Low ductility demand, $\rho / y < 2$ (table 10-6, ASCE 41-17)

$= 4.9990391\text{E-}006$

- Stirrup Spacing $\leq d/2$

$d = d_{\text{external}} = 627.00$

$s = s_{\text{external}} = 150.00$

- Strength provided by hoops $V_s < 3/4 \cdot \text{design Shear}$

$V_s = 421182.855$, already given in calculation of shear control ratio

design Shear = 15636.832

- ($\rho - \rho'$)/ $\rho_{\text{bal}} = -0.3178459$

$= A_{\text{st}}/(b_w \cdot d) = 0.00283094$

Tension Reinf Area: $A_{\text{st}} = 709.9999$

$\rho' = A_{\text{sc}}/(b_w \cdot d) = 0.00665146$

Compression Reinf Area: $A_{\text{sc}} = 1668.186$

From (B-1), ACI 318-11: $\rho_{\text{bal}} = 0.01202003$

$f_c = (f_{c,\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_{c,\text{core}} \cdot \text{Area}_{\text{core}}) / \text{section_area} = 27.76119$

$f_y = f_{y,\text{jacket_bars}} = 625.00$

From 10.2.7.3, ACI 318-11: $\beta_1 = 0.65$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000 / (87000 + f_y) = c_b/d_t = 0.003 / (0.003 + y) = 0.48979592$

$y = 0.003125$

- $V / (b_w \cdot d \cdot f_c^{0.5}) = 0.14250345$, NOTE: units in lb & in

$b_w = 400.00$

End Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 7

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjars

Constant Properties

Knowledge Factor, $k = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 20.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{o,u,min} = l_b/d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = 5.6603E+006$
Shear Force, $V_a = 4044.434$
EDGE -B-
Bending Moment, $M_b = 1.1729E+007$
Shear Force, $V_b = 15636.832$
BOTH EDGES
Axial Force, $F = -7188.634$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{s,t} = 709.9999$
-Compression: $A_{s,c} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{s,ten} = 709.9999$
-Compression: $A_{s,com} = 1266.062$
-Middle: $A_{s,mid} = 402.1239$
Mean Diameter of Tension Reinforcement, $D_{bL,ten} = 15.00$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = *V_n = 464999.649$
 V_n ((22.5.1.1), ACI 318-14) = 464999.649

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f*V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 156202.035$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_c_{jacket} * Area_{jacket} + f'_c_{core} * Area_{core}) / Area_{section} = 18.50746$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w * d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 400.00$
 $d = 536.00$
 $V_u * d / M_u < 1 = 0.71459785$
 $M_u = 1.1729E+007$
 $V_u = 15636.832$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 308797.614$
 $V_{s1} = 280648.944$ is calculated for jacket, with:
 $d = 536.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 28148.67$ is calculated for core, with:
 $d = 400.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 300.00$
 V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.50$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 612724.122$

End Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 8

beam B1, Floor 1



Limit State: Operational Level (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.04251

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} > 1$)

No FRP Wrapping

Stepwise Properties

At local axis: 3

EDGE -A-

Shear Force, $V_a = 9840.632$

EDGE -B-

Shear Force, $V_b = 9840.634$

BOTH EDGES

Axial Force, $F = -2309.834$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 709.9999$

-Compression: $A_{sc} = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st, \text{ten}} = 709.9999$

-Compression: $A_{sl, \text{com}} = 1266.062$

-Middle: $A_{sl, \text{mid}} = 402.1239$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.92480584$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 535287.788$
with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 7.8817E+008$

$M_{u1+} = 4.6479E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 7.8817E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 7.8817E+008$

$M_{u2+} = 4.6479E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 7.8817E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = 9840.632$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 9840.634$, is the shear force acting at edge 2 for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 5.6369735E-005$

Mu = 4.6479E+008

with full section properties:

b = 400.00

d = 627.00

d' = 43.00

v = 0.000307

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = $\text{Max}(ase1, ase2) = 0.14776895$

bo_2 = 192.00

ho_2 = 492.00

bi2_2 = 557856.00

$psh, \min * F_{ywe} = \text{Min}(psh, x * F_{ywe}, psh, y * F_{ywe}) = 1.38519$

$psh, x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.45559$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00261799$

Ash1 = $A_{stir,1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 670.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00062519$

Ash2 = $A_{stir,2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 500.00

$psh, y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 1.38519$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00156298$

Ash1 = $A_{stir,1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00025008$

Ash2 = $A_{stir,2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 872.4558

fy1 = 727.0465

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = $0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y1, sh1, ft1, fy1, it is considered characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 727.0465$
 with $Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$
 $y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 882.7854$
 $fy2 = 735.6545$
 $su2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/lb_{min} = 1.00$
 $su2 = 0.4 \cdot esu2_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,
 For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 735.6545$
 with $Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$
 $yv = 0.0025$
 $shv = 0.008$
 $ftv = 937.50$
 $fyv = 781.25$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 781.25$
 with $Esv = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.06860752$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.12378842$
 $v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.04175429$
 and confined core properties:
 $b = 340.00$
 $d = 597.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.08477074$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.15295169$
 $v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.05159117$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs, y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.09460844$
 $Mu = MRc (4.14) = 4.6479E+008$
 $u = su (4.1) = 5.6369735E-005$

 Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of $Mu1$ -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.0907698E-005$$

$$Mu = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00680405$$

$$w_e(5.4c) = 0.00682295$$

$$a_{se}((5.4d), \text{TBDY}) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirups, $n_{s_1} = 2.00$

$$h_1 = 670.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirups, $n_{s_2} = 2.00$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirups, $n_{s_1} = 2.00$

$$h_1 = 400.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirups, $n_{s_2} = 2.00$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{ou, \min} = l_b / d = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}}((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 735.6545$

with $Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 872.4558$

$fy2 = 727.0465$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lo_{ou,min} = lb/lb_{,min} = 1.00$

$su2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 727.0465$

with $Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 937.50$

$fyv = 781.25$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$ and also multiplied by the $shear_factor$ according to 15.7.1.4, with $Shear_factor = 1.00$

$lo/lo_{ou,min} = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 781.25$

with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.12378842$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.06860752$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.04175429$

and confined core properties:

$b = 340.00$

$d = 597.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.15295169$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.08477074$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.05159117$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < vs,y2$ - LHS eq.(4.5) is not satisfied

--->

$v < vs,c$ - RHS eq.(4.5) is satisfied

--->

su (4.8) = 0.16206515

$Mu = MRc$ (4.15) = 7.8817E+008

$u = su$ (4.1) = 6.0907698E-005

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu2+

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$\phi_u = 5.6369735E-005$$

$$Mu = 4.6479E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \phi_{cu}: \phi_{cu}^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.00680405$$

$$\phi_{we} \text{ (5.4c)} = 0.00682295$$

$$\phi_{ase} \text{ ((5.4d), TBDY)} = (\phi_{ase1} * A_{ext} + \phi_{ase2} * A_{int}) / A_{sec} = 0.14776895$$

$$\phi_{ase1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$\phi_{ase2} = \text{Max}(\phi_{ase1}, \phi_{ase2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$\phi_{psh, \min} * F_{ywe} = \text{Min}(\phi_{psh, x} * F_{ywe}, \phi_{psh, y} * F_{ywe}) = 1.38519$$

$$\phi_{psh, x} * F_{ywe} = \phi_{psh1} * F_{ywe1} + \phi_{psh2} * F_{ywe2} = 2.45559$$

$$\phi_{ps1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirrups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$\phi_{ps2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirrups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$\phi_{psh, y} * F_{ywe} = \phi_{psh1} * F_{ywe1} + \phi_{psh2} * F_{ywe2} = 1.38519$$

$$\phi_{ps1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirrups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$\phi_{ps2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirrups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } \phi_{cc} = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 872.4558$$

$$fy_1 = 727.0465$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 727.0465

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 882.7854

fy2 = 735.6545

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 735.6545

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 937.50

fyv = 781.25

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.06860752

2 = Asl,com/(b*d)*(fs2/fc) = 0.12378842

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00

d = 597.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08477074

2 = Asl,com/(b*d)*(fs2/fc) = 0.15295169

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.09460844

Mu = MRc (4.14) = 4.6479E+008

u = su (4.1) = 5.6369735E-005

Calculation of ratio lb/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of μ_2 -

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 6.0907698E-005$$

$$\mu_2 = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } \mu_2: \mu_2^* = \text{shear_factor} * \text{Max}(\mu_2, c_o) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \mu_2 = 0.00680405$$

$$w_e \text{ (5.4c)} = 0.00682295$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy1 = 735.6545$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 735.6545$$

$$\text{with } Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 872.4558$$

$$fy2 = 727.0465$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 727.0465$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 937.50$$

$$fyv = 781.25$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY
For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.12378842$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.06860752$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.15295169$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.08477074$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

v < vs,y2 - LHS eq.(4.5) is not satisfied

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

$$su (4.8) = 0.16206515$$

$$\begin{aligned} \mu &= MRC(4.15) = 7.8817E+008 \\ u &= su(4.1) = 6.0907698E-005 \end{aligned}$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Shear Strength $V_r = \min(V_{r1}, V_{r2}) = 578810.994$

Calculation of Shear Strength at edge 1, $V_{r1} = 578810.994$
 $V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'V_w' is replaced by 'V_w + f_tV_f' where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot Area_jacket + f'_{c_core} \cdot Area_core) / Area_section = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 400.00$
 $d = 536.00$
 $V_u \cdot d / \mu < 1 = 1.00$
 $\mu = 1.1510E+006$
 $V_u = 9840.632$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$
 $V_{s1} = 350811.18$ is calculated for jacket, with:
 $d = 536.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 35185.838$ is calculated for jacket, with:
 $d_2 = 400.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 300.00$
 V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.50$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 578810.994$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'V_w' is replaced by 'V_w + f_tV_f' where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot Area_jacket + f'_{c_core} \cdot Area_core) / Area_section = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 400.00$
 $d = 536.00$
 $V_u \cdot d / \mu < 1 = 1.00$
 $\mu = 1.1510E+006$
 $V_u = 9840.634$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$
 $V_{s1} = 350811.18$ is calculated for jacket, with:
 $d = 536.00$

Av = 157079.633
fy = 625.00
s = 150.00

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
Vs2 = 35185.838 is calculated for jacket, with:

d = 400.00
Av = 100530.965
fy = 525.00
s = 300.00

Vs2 has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$2(1-s/d) = 0.50$

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $Vs + Vf \leq 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 * f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 * f_{sm} = 656.25$

#####

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Mean Confinement Factor overall section = 1.04251

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, min} > 1$)

No FRP Wrapping

----- Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, $V_a = -6.9728406E-015$

EDGE -B-

Shear Force, $V_b = 6.9728406E-015$

BOTH EDGES

Axial Force, $F = -2309.834$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 709.9999$

-Compression: $A_{sc} = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st,ten} = 911.0619$

-Compression: $A_{sl,com} = 911.0619$

-Middle: $A_{sl,mid} = 556.0619$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.55914272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n / 2 = 218168.257$

with

$M_{pr1} = \text{Max}(M_{u1+}, M_{u1-}) = 3.2725E+008$

$M_{u1+} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$M_{u1-} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(M_{u2+}, M_{u2-}) = 3.2725E+008$

$M_{u2+} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$M_{u2-} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -6.9728406E-015$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 6.9728406E-015$, is the shear force acting at edge 2 for the the static loading combination

Calculation of M_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010507$

$M_u = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$f_c = 30.00$

α (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00680405$

w_e (5.4c) = 0.00682295

a_{se} ((5.4d), TBDY) = $(a_{se1} \cdot A_{ext} + a_{se2} \cdot A_{int}) / A_{sec} = 0.14776895$

$a_{se1} = 0.14776895$

$b_{o_1} = 340.00$

$h_{o_1} = 610.00$

$b_{i2_1} = 975400.00$

$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$

$b_{o_2} = 192.00$

$h_{o_2} = 492.00$

$b_{i2_2} = 557856.00$

$$psh_{min} * Fywe = \text{Min}(psh_x * Fywe, psh_y * Fywe) = 1.38519$$

$$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.45559$$

ps1 (external) = $(Ash1 * h1 / s1) / Asec = 0.00261799$
Ash1 = Astir_1 * ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00

ps2 (internal) = $(Ash2 * h2 / s2) / Asec = 0.00062519$
Ash2 = Astir_2 * ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

$$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 1.38519$$

ps1 (external) = $(Ash1 * h1 / s1) / Asec = 0.00156298$
Ash1 = Astir_1 * ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / Asec = 0.00025008$
Ash2 = Astir_2 * ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

$$Asec = 268000.00$$

$$s1 = 150.00$$

$$s2 = 300.00$$

$$fywe1 = 781.25$$

$$fywe2 = 656.25$$

$$fce = 30.00$$

$$\text{From } ((5.A.5), \text{ TBDY}), \text{ TBDY: } cc = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 886.8103$$

$$fy1 = 739.0086$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/ld = 1.00$$

$$su1 = 0.4 * esu1_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs_{jacket} * Asl_{ten,jacket} + fs_{core} * Asl_{ten,core}) / Asl_{ten} = 739.0086$$

$$\text{with } Es1 = (Es_{jacket} * Asl_{ten,jacket} + Es_{core} * Asl_{ten,core}) / Asl_{ten} = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 886.8103$$

$$fy2 = 739.0086$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou_{min} = lb/lb_{min} = 1.00$$

$$su2 = 0.4 * esu2_{nominal} ((5.5), \text{ TBDY}) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_{jacket} * Asl_{com,jacket} + fs_{core} * Asl_{com,core}) / Asl_{com} = 739.0086$$

$$\text{with } Es2 = (Es_{jacket} * Asl_{com,jacket} + Es_{core} * Asl_{com,core}) / Asl_{com} = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 895.9746$$

$$fyv = 746.6455$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$l_0/l_{0u,min} = l_b/l_d = 1.00$

$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and γ_v , sh_v, ft_v, fy_v , it is considered
characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

$\gamma_1, sh_1, ft_1, fy_1$, are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 746.6455$

with $E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.09382814$

$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.09382814$

$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.05785932$

and confined core properties:

$b = 610.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 31.27541$

$cc (5A.5, TBDY) = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.11251192$

$2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.11251192$

$v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$s_u (4.9) = 0.1468828$

$M_u = MR_c (4.14) = 3.2725E+008$

$u = s_u (4.1) = 0.00010507$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_u1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$

$M_u = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$f_c = 30.00$

$co (5A.5, TBDY) = 0.002$

Final value of c_u : $c_u * = \text{shear_factor} * \text{Max}(c_u, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $c_u = 0.00680405$

$w_e (5.4c) = 0.00682295$

$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$

$ase1 = 0.14776895$

$bo_1 = 340.00$

$ho_1 = 610.00$

$bi2_1 = 975400.00$

$ase2 = \text{Max}(ase1, ase2) = 0.14776895$

bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008

$$ftv = 895.9746$$

$$fyv = 746.6455$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lo_{u,min} = lb/ld = 1.00$$

$$suv = 0.4 * esuv_{nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv , shv , ftv , fyv , it is considered
characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1$, $sh1$, $ft1$, $fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{jacket} * Asl_{mid,jacket} + fs_{mid} * Asl_{mid,core}) / Asl_{mid} = 746.6455$$

$$\text{with } Es_v = (Es_{jacket} * Asl_{mid,jacket} + Es_{mid} * Asl_{mid,core}) / Asl_{mid} = 200000.00$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.09382814$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.09382814$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.05785932$$

and confined core properties:

$$b = 610.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl_{ten} / (b * d) * (fs1 / fc) = 0.11251192$$

$$2 = Asl_{com} / (b * d) * (fs2 / fc) = 0.11251192$$

$$v = Asl_{mid} / (b * d) * (fsv / fc) = 0.06938071$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.1468828$$

$$Mu = MRc (4.14) = 3.2725E+008$$

$$u = su (4.1) = 0.00010507$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010507$$

$$Mu = 3.2725E+008$$

with full section properties:

$$b = 670.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0003219$$

$$N = 2309.834$$

$$fc = 30.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu: cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00680405$$

$$we (5.4c) = 0.00682295$$

$$ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$$

$$ase1 = 0.14776895$$

$$bo_1 = 340.00$$

ho_1 = 610.00
bi2_1 = 975400.00
ase2 = Max(ase1,ase2) = 0.14776895
bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered

characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb,min)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered

characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb,min)^ 2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with $E_s2 = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 895.9746$
 $fy_v = 746.6455$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lo_{min} = lb/ld = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fs_yv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $fs_yv = fsv/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 746.6455$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.09382814$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.09382814$
 $v = A_{s,mid} / (b \cdot d) \cdot (fsv / fc) = 0.05785932$

and confined core properties:

$b = 610.00$
 $d = 327.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.11251192$
 $2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.11251192$
 $v = A_{s,mid} / (b \cdot d) \cdot (fsv / fc) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

$su (4.9) = 0.1468828$
 $Mu = MRc (4.14) = 3.2725E+008$
 $u = su (4.1) = 0.00010507$

 Calculation of ratio lb/ld

 Adequate Lap Length: $lb/ld \geq 1$

 Calculation of Mu_2 -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$
 $Mu = 3.2725E+008$

 with full section properties:

$b = 670.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$
 $fc = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $we (5.4c) = 0.00682295$

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895
ase1 = 0.14776895
bo_1 = 340.00
ho_1 = 610.00
bi2_1 = 975400.00
ase2 = Max(ase1,ase2) = 0.14776895
bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered

characteristic value $f_{s2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core})/A_{s,com} = 739.0086$

with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core})/A_{s,com} = 200000.00$

$y_v = 0.0025$

$sh_v = 0.008$

$ft_v = 895.9746$

$f_{y_v} = 746.6455$

$s_{u_v} = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

$l_o/l_{o,min} = l_b/l_d = 1.00$

$s_{u_v} = 0.4 \cdot e_{s_{u_v,nominal}} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $e_{s_{u_v,nominal}} = 0.08$,

considering characteristic value $f_{s_{y_v}} = f_{s_{y_v}}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u_v,nominal}}$ and y_v, sh_v, ft_v, f_{y_v} , it is considered

characteristic value $f_{s_{y_v}} = f_{s_{y_v}}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_{y1} , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s_{y_v}} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 746.6455$

with $E_{s_{y_v}} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core})/A_{s,mid} = 200000.00$

$1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.09382814$

$2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.09382814$

$v = A_{s,mid}/(b \cdot d) \cdot (f_{s_{y_v}}/f_c) = 0.05785932$

and confined core properties:

$b = 610.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 31.27541$

$cc (5A.5, TBDY) = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$1 = A_{s,ten}/(b \cdot d) \cdot (f_{s1}/f_c) = 0.11251192$

$2 = A_{s,com}/(b \cdot d) \cdot (f_{s2}/f_c) = 0.11251192$

$v = A_{s,mid}/(b \cdot d) \cdot (f_{s_{y_v}}/f_c) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$s_u (4.9) = 0.1468828$

$M_u = M_{Rc} (4.14) = 3.2725E+008$

$u = s_u (4.1) = 0.00010507$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 390183.487$

Calculation of Shear Strength at edge 1, $V_{r1} = 390183.487$

$V_{r1} = V_n ((22.5.1.1), ACI 318-14)$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '

where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 180743.977$

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot \text{Area}_{jacket} + f'_{c,core} \cdot \text{Area}_{core})/\text{Area}_{section} = 27.76119$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$p_w = A_s/(b_w \cdot d) = 0.00331157$

A_s (tension reinf.) = 709.9999

$b_w = 670.00$

$d = 320.00$

$$V_u \cdot d / \mu < 1 = 0.00$$

$$\mu = 2.1102257E-011$$

$$V_u = 6.9728406E-015$$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 209439.51$

$V_{s1} = 209439.51$ is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 150.00$$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 0.00$ is calculated for jacket, with:

$$d_2 = 160.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 300.00$$

V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

$$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$$

$$\text{From (11-11), ACI } 440: V_s + V_f \leq 750430.726$$

Calculation of Shear Strength at edge 2, $V_{r2} = 390183.487$

$$V_{r2} = V_n ((22.5.1.1), \text{ACI } 318-14)$$

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

$$\text{From Table (22.5.5.1), ACI } 318-14: V_c = 180743.977$$

$$= 1 \text{ (normal-weight concrete)}$$

$$\text{Mean concrete strength: } f'_c = (f'_{c \text{ jacket}} \cdot \text{Area}_{\text{jacket}} + f'_{c \text{ core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 27.76119, \text{ but } f_c^{0.5} < = 8.3 \text{ MPa (22.5.3.1, ACI } 318-14)$$

$$p_w = A_s / (b_w \cdot d) = 0.00331157$$

$$A_s \text{ (tension reinf.)} = 709.9999$$

$$b_w = 670.00$$

$$d = 320.00$$

$$V_u \cdot d / \mu < 1 = 0.00$$

$$\mu = 1.8034731E-013$$

$$V_u = 6.9728406E-015$$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 209439.51$

$V_{s1} = 209439.51$ is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 150.00$$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 0.00$ is calculated for jacket, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 300.00$$

V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

$$V_f ((11-3)-(11.4), \text{ACI } 440) = 0.00$$

$$\text{From (11-11), ACI } 440: V_s + V_f \leq 750430.726$$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_b/d >= 1$)

No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -7.9998090E-011$

Shear Force, $V_2 = 5.4911670E-014$

Shear Force, $V_3 = 15636.832$

Axial Force, $F = -7188.634$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 709.9999$

-Compression: $As_c = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 911.0619$

-Compression: $As_{c,com} = 911.0619$

-Middle: $As_{mid} = 556.0619$

Longitudinal External Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten,jacket} = 603.1858$

-Compression: $As_{c,com,jacket} = 603.1858$

-Middle: $As_{mid,jacket} = 402.1239$

Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten,core} = 307.8761$

-Compression: $As_{c,com,core} = 307.8761$

-Middle: $As_{mid,core} = 153.938$

Mean Diameter of Tension Reinforcement, $Db_L = 15.20$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{,R} = * u = 0.00910271$

$u = y + p = 0.00910271$

- Calculation of y -

$y = (M_y * L_s / 3) / E_{eff} = 0.00410271$ ((4.29), Biskinis Phd)

$M_y = 2.1250E+008$

$L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 1500.00

From table 10.5, ASCE 41_17: $E_{eff} = 0.3 * E_c * I_g = 2.5898E+013$

Calculation of Yielding Moment M_y

Calculation of ρ_y and M_y according to Annex 7 -

$y = \text{Min}(y_{\text{ten}}, y_{\text{com}})$
 $y_{\text{ten}} = 1.0750437\text{E}-005$
with $f_y = 625.00$
 $d = 357.00$
 $y = 0.22791832$
 $A = 0.00999338$
 $B = 0.00562083$
with $p_t = 0.00380895$
 $p_c = 0.00380895$
 $p_v = 0.00232477$
 $N = 7188.634$
 $b = 670.00$
 $\rho = 0.12044818$
 $y_{\text{comp}} = 2.5846378\text{E}-005$
with $f_c = 27.76119$
 $E_c = 25742.96$
 $y = 0.22733556$
 $A = 0.00987103$
 $B = 0.00557012$
with $E_s = 200000.00$

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

- Calculation of ρ_p -

From table 10-7: $\rho_p = 0.005$

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.55914272$

- Transverse Reinforcement: NC

- Stirrup Spacing $> d/3$

- Low ductility demand, $\rho_p / y < 2$ (table 10-6, ASCE 41-17)

$= -2.6687906\text{E}-023$

- Stirrup Spacing $\leq d/2$

$d = d_{\text{external}} = 357.00$

$s = s_{\text{external}} = 150.00$

- Strength provided by hoops $V_s < 3/4$ *design Shear

$V_s = 237588.18$, already given in calculation of shear control ratio

design Shear = $5.4911670\text{E}-014$

- ($\rho_p - \rho_p'$)/ $\rho_{\text{bal}} = -0.33327376$

$= A_{s1}/(b_w*d) = 0.00296835$

Tension Reinf Area: $A_{s1} = 709.9999$

$\rho_p' = A_{s2}/(b_w*d) = 0.00697431$

Compression Reinf Area: $A_{s2} = 1668.186$

From (B-1), ACI 318-11: $\rho_{\text{bal}} = 0.01202003$

$f_c = (f_{c_{\text{jacket}}*Area_{\text{jacket}} + f_{c_{\text{core}}*Area_{\text{core}}})/section_area = 27.76119$

$f_y = f_{y_{\text{jacket_bars}}} = 625.00$

From 10.2.7.3, ACI 318-11: $\rho_p = 0.65$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + y) = 0.48979592$

$y = 0.003125$

- $V/(b_w*d*f_c^{0.5}) = 5.2471780\text{E}-019$, NOTE: units in lb & in

$b_w = 670.00$

End Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 9

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VRd

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 20.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-
Bending Moment, $M_a = -7.2842051E-011$
Shear Force, $V_a = -4.5846775E-014$
EDGE -B-
Bending Moment, $M_b = -6.4836912E-011$
Shear Force, $V_b = 4.5846775E-014$
BOTH EDGES
Axial Force, $F = -6266.087$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,ten} = 709.9999$
-Compression: $A_{sl,com} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 911.0619$
-Compression: $A_{sl,com} = 911.0619$
-Middle: $A_{sl,mid} = 556.0619$
Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 15.20$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = \phi V_n = 315128.448$
 V_n ((22.5.1.1), ACI 318-14) = 315128.448

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + \phi V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 147576.839$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 18.50746$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 670.00$
 $d = 320.00$
 $V_u \cdot d / M_u < 1 = 0.00$
 $M_u = 7.2842051E-011$
 $V_u = 4.5846775E-014$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 167551.608$
 $V_{s1} = 167551.608$ is calculated for jacket, with:
 $d = 320.00$
 $A_v = 157079.633$
 $f_y = 500.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 0.00$ is calculated for core, with:
 $d = 160.00$
 $A_v = 100530.965$
 $f_y = 420.00$
 $s = 300.00$
 V_{s2} is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 612724.122$

End Of Calculation of Shear Capacity for element: beam JB1 of floor 1
At local axis: 2
Integration Section: (a)

Calculation No. 10

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\phi = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

External Height, H = 670.00
External Width, W = 400.00
Internal Height, H = 500.00
Internal Width, W = 200.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.04251
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{o,u}, \min > = 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, V_a = 9840.632
EDGE -B-
Shear Force, V_b = 9840.634
BOTH EDGES
Axial Force, F = -2309.834
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: A_{sl,t} = 709.9999
-Compression: A_{sl,c} = 1668.186
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: A_{sl,ten} = 709.9999
-Compression: A_{sl,com} = 1266.062
-Middle: A_{sl,mid} = 402.1239

Calculation of Shear Capacity ratio, $V_e/V_r = 0.92480584$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u * l_n / 2 = 535287.788$
with
 $M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 7.8817E+008$
Mu₁₊ = 4.6479E+008, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
Mu₁₋ = 7.8817E+008, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 7.8817E+008$
Mu₂₊ = 4.6479E+008, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination
Mu₂₋ = 7.8817E+008, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination
and
 $\pm w_u * l_n = (|V_1| + |V_2|)/2$
with
V₁ = 9840.632, is the shear force acting at edge 1 for the the static loading combination
V₂ = 9840.634, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu₁₊

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 5.6369735E-005$
Mu = 4.6479E+008

with full section properties:
b = 400.00

$d = 627.00$
 $d' = 43.00$
 $v = 0.000307$
 $N = 2309.834$
 $fc = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $w_e (5.4c) = 0.00682295$
 $ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$
 $ase1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$
 $bi2_1 = 975400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.14776895$
 $bo_2 = 192.00$
 $ho_2 = 492.00$
 $bi2_2 = 557856.00$
 $psh, \min * F_{ywe} = \text{Min}(psh, x * F_{ywe}, psh, y * F_{ywe}) = 1.38519$

$psh, x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.45559$
 $ps1 (external) = (Ash1 * h1 / s1) / A_{sec} = 0.00261799$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 670.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / A_{sec} = 0.00062519$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 500.00$

$psh, y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 1.38519$
 $ps1 (external) = (Ash1 * h1 / s1) / A_{sec} = 0.00156298$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / A_{sec} = 0.00025008$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 268000.00$
 $s1 = 150.00$
 $s2 = 300.00$
 $fy_{we1} = 781.25$
 $fy_{we2} = 656.25$
 $f_{ce} = 30.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00242514$
 $c = \text{confinement factor} = 1.04251$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 872.4558$
 $fy1 = 727.0465$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$

$lo/lou, \min = lb/d = 1.00$
 $su1 = 0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs, \text{jacket} * A_{sl, \text{ten, jacket}} + fs, \text{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 727.0465$

with $Es1 = (Es, \text{jacket} * A_{sl, \text{ten, jacket}} + Es, \text{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$

$$ft2 = 882.7854$$

$$fy2 = 735.6545$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 735.6545$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 937.50$$

$$fyv = 781.25$$

$$suv = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/ld = 1.00$$

$$suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25$$

$$\text{with } Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.06860752$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.12378842$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl,ten/(b*d)*(fs1/fc) = 0.08477074$$

$$2 = Asl,com/(b*d)*(fs2/fc) = 0.15295169$$

$$v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

---->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

---->

$$su (4.9) = 0.09460844$$

$$Mu = MRc (4.14) = 4.6479E+008$$

$$u = su (4.1) = 5.6369735E-005$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.0907698E-005$$

$$Mu = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00680405$$

$$w_e \text{ (5.4c)} = 0.00682295$$

$$a_{se} \text{ ((5.4d), TBDY)} = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 2.45559$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{s2} * F_{ywe2} = 1.38519$$

$$p_{s1} \text{ (external)} = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$p_{s2} \text{ (internal)} = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } c_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{o, \min} = l_b / d = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}} \text{ ((5.5), TBDY)} = 0.032$$

$$\text{From table 5A.1, TBDY: } esu_{1, \text{nominal}} = 0.08,$$

For calculation of $esu_{1, \text{nominal}}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fsy_1 = fs_1 / 1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b / d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs_1 = (fs_{\text{jacket}} * A_{sl, \text{jacket}} + fs_{\text{core}} * A_{sl, \text{core}}) / A_{sl, \text{ten}} = 735.6545$$

$$\text{with } Es1 = (Es_{\text{jacket}} \cdot Asl_{\text{ten,jacket}} + Es_{\text{core}} \cdot Asl_{\text{ten,core}}) / Asl_{\text{ten}} = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 872.4558$$

$$fy2 = 727.0465$$

$$su2 = 0.032$$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00

$$lo/lo_{\text{min}} = lb/lb_{\text{min}} = 1.00$$

$$su2 = 0.4 \cdot esu2_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$
 From table 5A.1, TBDY: $esu2_{\text{nominal}} = 0.08$,
 For calculation of $esu2_{\text{nominal}}$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs_{\text{jacket}} \cdot Asl_{\text{com,jacket}} + fs_{\text{core}} \cdot Asl_{\text{com,core}}) / Asl_{\text{com}} = 727.0465$$

$$\text{with } Es2 = (Es_{\text{jacket}} \cdot Asl_{\text{com,jacket}} + Es_{\text{core}} \cdot Asl_{\text{com,core}}) / Asl_{\text{com}} = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 937.50$$

$$fyv = 781.25$$

$$suv = 0.032$$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00

$$lo/lo_{\text{min}} = lb/ld = 1.00$$

$$suv = 0.4 \cdot esuv_{\text{nominal}} ((5.5), \text{TBDY}) = 0.032$$
 From table 5A.1, TBDY: $esuv_{\text{nominal}} = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{\text{nominal}}$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_{\text{jacket}} \cdot Asl_{\text{mid,jacket}} + fs_{\text{mid}} \cdot Asl_{\text{mid,core}}) / Asl_{\text{mid}} = 781.25$$

$$\text{with } Esv = (Es_{\text{jacket}} \cdot Asl_{\text{mid,jacket}} + Es_{\text{mid}} \cdot Asl_{\text{mid,core}}) / Asl_{\text{mid}} = 200000.00$$

$$1 = Asl_{\text{ten}} / (b \cdot d) \cdot (fs1 / fc) = 0.12378842$$

$$2 = Asl_{\text{com}} / (b \cdot d) \cdot (fs2 / fc) = 0.06860752$$

$$v = Asl_{\text{mid}} / (b \cdot d) \cdot (fsv / fc) = 0.04175429$$
 and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$fcc (5A.2, \text{TBDY}) = 31.27541$$

$$cc (5A.5, \text{TBDY}) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl_{\text{ten}} / (b \cdot d) \cdot (fs1 / fc) = 0.15295169$$

$$2 = Asl_{\text{com}} / (b \cdot d) \cdot (fs2 / fc) = 0.08477074$$

$$v = Asl_{\text{mid}} / (b \cdot d) \cdot (fsv / fc) = 0.05159117$$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)

---->
 $v < vs,y2$ - LHS eq.(4.5) is not satisfied
 ---->
 $v < vs,c$ - RHS eq.(4.5) is satisfied
 ---->

$$su (4.8) = 0.16206515$$

$$Mu = MRc (4.15) = 7.8817E+008$$

$$u = su (4.1) = 6.0907698E-005$$

 Calculation of ratio lb/ld

 Adequate Lap Length: $lb/ld \geq 1$

 Calculation of $Mu2+$

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 5.6369735E-005$$

$$\mu = 4.6479E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_{cu}, \phi_{cc}) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_{cu} = 0.00680405$$

$$\phi_{we}(5.4c) = 0.00682295$$

$$a_{se}((5.4d), \text{TBDY}) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirrups, $n_{s_1} = 2.00$

$$h_1 = 670.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirrups, $n_{s_2} = 2.00$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirrups, $n_{s_1} = 2.00$

$$h_1 = 400.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirrups, $n_{s_2} = 2.00$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A.5), TBDY), TBDY: } \phi_{cc} = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 872.4558$$

$$fy_1 = 727.0465$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o / l_{o, \min} = l_b / d = 1.00$$

$$su_1 = 0.4 * e_{su1_nominal}((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_jacket \cdot Asl,ten,jacket + fs_core \cdot Asl,ten,core) / Asl,ten = 727.0465$

with $Es1 = (Es_jacket \cdot Asl,ten,jacket + Es_core \cdot Asl,ten,core) / Asl,ten = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 882.7854$

$fy2 = 735.6545$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lou,min = lb/lb,min = 1.00$

$su2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_jacket \cdot Asl,com,jacket + fs_core \cdot Asl,com,core) / Asl,com = 735.6545$

with $Es2 = (Es_jacket \cdot Asl,com,jacket + Es_core \cdot Asl,com,core) / Asl,com = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 937.50$

$fyv = 781.25$

$su = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lou,min = lb/ld = 1.00$

$su = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_jacket \cdot Asl,mid,jacket + fs_mid \cdot Asl,mid,core) / Asl,mid = 781.25$

with $Esv = (Es_jacket \cdot Asl,mid,jacket + Es_mid \cdot Asl,mid,core) / Asl,mid = 200000.00$

$1 = Asl,ten / (b \cdot d) \cdot (fs1 / fc) = 0.06860752$

$2 = Asl,com / (b \cdot d) \cdot (fs2 / fc) = 0.12378842$

$v = Asl,mid / (b \cdot d) \cdot (fsv / fc) = 0.04175429$

and confined core properties:

$b = 340.00$

$d = 597.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

$c =$ confinement factor = 1.04251

$1 = Asl,ten / (b \cdot d) \cdot (fs1 / fc) = 0.08477074$

$2 = Asl,com / (b \cdot d) \cdot (fs2 / fc) = 0.15295169$

$v = Asl,mid / (b \cdot d) \cdot (fsv / fc) = 0.05159117$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < vs,y2$ - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.09460844

$Mu = MRc$ (4.14) = 4.6479E+008

$u = su$ (4.1) = 5.6369735E-005

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu2-

Calculation of ultimate curvature μ according to 4.1, Biskinis/Fardis 2013:

$$\mu = 6.0907698E-005$$

$$\text{Mu} = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o \text{ (5A.5, TBDY)} = 0.002$$

$$\text{Final value of } c_u: c_u^* = \text{shear_factor} * \text{Max}(c_u, c_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } c_u = 0.00680405$$

$$w_e \text{ (5.4c)} = 0.00682295$$

$$\text{ase ((5.4d), TBDY)} = (\text{ase1} * A_{\text{ext}} + \text{ase2} * A_{\text{int}}) / A_{\text{sec}} = 0.14776895$$

$$\text{ase1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$\text{ase2} = \text{Max}(\text{ase1}, \text{ase2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$\text{psh}_{\text{min}} * F_{ywe} = \text{Min}(\text{psh}_{x} * F_{ywe}, \text{psh}_{y} * F_{ywe}) = 1.38519$$

$$\text{psh}_{x} * F_{ywe} = \text{psh1} * F_{ywe1} + \text{ps2} * F_{ywe2} = 2.45559$$

$$\text{ps1 (external)} = (A_{sh1} * h_1 / s_1) / A_{\text{sec}} = 0.00261799$$

$$A_{sh1} = A_{\text{stir}_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 670.00$$

$$\text{ps2 (internal)} = (A_{sh2} * h_2 / s_2) / A_{\text{sec}} = 0.00062519$$

$$A_{sh2} = A_{\text{stir}_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 500.00$$

$$\text{psh}_{y} * F_{ywe} = \text{psh1} * F_{ywe1} + \text{ps2} * F_{ywe2} = 1.38519$$

$$\text{ps1 (external)} = (A_{sh1} * h_1 / s_1) / A_{\text{sec}} = 0.00156298$$

$$A_{sh1} = A_{\text{stir}_1} * n_{s_1} = 157.0796$$

$$\text{No stirups, } n_{s_1} = 2.00$$

$$h_1 = 400.00$$

$$\text{ps2 (internal)} = (A_{sh2} * h_2 / s_2) / A_{\text{sec}} = 0.00025008$$

$$A_{sh2} = A_{\text{stir}_2} * n_{s_2} = 100.531$$

$$\text{No stirups, } n_{s_2} = 2.00$$

$$h_2 = 200.00$$

$$A_{\text{sec}} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } c_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 735.6545

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 872.4558

fy2 = 727.0465

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 727.0465

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 937.50

fyv = 781.25

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.12378842

2 = Asl,com/(b*d)*(fs2/fc) = 0.06860752

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00

d = 597.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.15295169

2 = Asl,com/(b*d)*(fs2/fc) = 0.08477074

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is not satisfied

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.8) = 0.16206515

Mu = MRc (4.15) = 7.8817E+008

u = su (4.1) = 6.0907698E-005

Calculation of ratio l_b/d

Adequate Lap Length: $l_b/d \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 578810.994$

Calculation of Shear Strength at edge 1, $V_{r1} = 578810.994$
 $V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 400.00$
 $d = 536.00$
 $V_u \cdot d / M_u < 1 = 1.00$
 $M_u = 1.1510E+006$
 $V_u = 9840.632$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$
 $V_{s1} = 350811.18$ is calculated for jacket, with:
 $d = 536.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 35185.838$ is calculated for jacket, with:
 $d_2 = 400.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 300.00$
 V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.50$
 V_f ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 578810.994$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f'_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $\rho_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 400.00$
 $d = 536.00$
 $V_u \cdot d / M_u < 1 = 1.00$
 $M_u = 1.1510E+006$
 $V_u = 9840.634$
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$
 $V_{s1} = 350811.18$ is calculated for jacket, with:
 $d = 536.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$
 V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 35185.838 is calculated for jacket, with:
d = 400.00
Av = 100530.965
fy = 525.00
s = 300.00
Vs2 has been multiplied by 2(1-s/d) (s>d/2, according to ASCE 41-17,10.3.4)
2(1-s/d) = 0.50
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: Vs + Vf <= 750430.726

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1
At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1
At Shear local axis: 2
(Bending local axis: 3)
Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00
Mean strength values are used for both shear and moment calculations.
Consequently:
Jacket
New material of Primary Member: Concrete Strength, fc = fcm = 30.00
New material of Primary Member: Steel Strength, fs = fsm = 625.00
Concrete Elasticity, Ec = 25742.96
Steel Elasticity, Es = 200000.00
Existing Column
Existing material of Primary Member: Concrete Strength, fc = fcm = 24.00
Existing material of Primary Member: Steel Strength, fs = fsm = 525.00
Concrete Elasticity, Ec = 23025.204
Steel Elasticity, Es = 200000.00

Note: Especially for the calculation of moment strengths,
the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14
Jacket
New material: Steel Strength, fs = 1.25*fsm = 781.25
Existing Column
Existing material: Steel Strength, fs = 1.25*fsm = 656.25

External Height, H = 670.00
External Width, W = 400.00
Internal Height, H = 500.00
Internal Width, W = 200.00
Cover Thickness, c = 25.00
Mean Confinement Factor overall section = 1.04251
Element Length, L = 3000.00
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length (lo/lou,min>=1)
No FRP Wrapping

Stepwise Properties

At local axis: 2
EDGE -A-
Shear Force, Va = -6.9728406E-015
EDGE -B-
Shear Force, Vb = 6.9728406E-015

BOTH EDGES

Axial Force, $F = -2309.834$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 709.9999$

-Compression: $As_c = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 911.0619$

-Compression: $As_{c,com} = 911.0619$

-Middle: $As_{mid} = 556.0619$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.55914272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 218168.257$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.2725E+008$

$Mu_{1+} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.2725E+008$

$Mu_{2+} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -6.9728406E-015$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 6.9728406E-015$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010507$

$M_u = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$f_c = 30.00$

ϕ_c (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase_1 \cdot A_{ext} + ase_2 \cdot A_{int})/A_{sec} = 0.14776895$

$ase_1 = 0.14776895$

$bo_1 = 340.00$

$ho_1 = 610.00$

$bi_2_1 = 975400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.14776895$

$bo_2 = 192.00$

$ho_2 = 492.00$

$bi_2_2 = 557856.00$

$psh_{min} \cdot F_{ywe} = \text{Min}(psh_x \cdot F_{ywe}, psh_y \cdot F_{ywe}) = 1.38519$

$psh_x \cdot F_{ywe} = psh_1 \cdot F_{ywe1} + ps_2 \cdot F_{ywe2} = 2.45559$

ps_1 (external) = $(A_{sh1} \cdot h_1/s_1)/A_{sec} = 0.00261799$

Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (\text{lb}/\text{d})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 895.9746
fyv = 746.6455
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

$$suv = 0.4 * esuv_nominal ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv , shv,ftv,fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1$, $sh1,ft1,fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fsv = (fs_jacket * Asl_mid_jacket + fs_mid * Asl_mid_core) / Asl_mid = 746.6455$$

$$\text{with } Esv = (Es_jacket * Asl_mid_jacket + Es_mid * Asl_mid_core) / Asl_mid = 200000.00$$

$$1 = Asl_ten / (b * d) * (fs1 / fc) = 0.09382814$$

$$2 = Asl_com / (b * d) * (fs2 / fc) = 0.09382814$$

$$v = Asl_mid / (b * d) * (fsv / fc) = 0.05785932$$

and confined core properties:

$$b = 610.00$$

$$d = 327.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = Asl_ten / (b * d) * (fs1 / fc) = 0.11251192$$

$$2 = Asl_com / (b * d) * (fs2 / fc) = 0.11251192$$

$$v = Asl_mid / (b * d) * (fsv / fc) = 0.06938071$$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

$v < vs,c$ - RHS eq.(4.5) is satisfied

--->

$$su (4.9) = 0.1468828$$

$$Mu = MRc (4.14) = 3.2725E+008$$

$$u = su (4.1) = 0.00010507$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of $Mu1$ -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 0.00010507$$

$$Mu = 3.2725E+008$$

with full section properties:

$$b = 670.00$$

$$d = 357.00$$

$$d' = 43.00$$

$$v = 0.0003219$$

$$N = 2309.834$$

$$fc = 30.00$$

$$co (5A.5, TBDY) = 0.002$$

$$\text{Final value of } cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } cu = 0.00680405$$

$$we (5.4c) = 0.00682295$$

$$ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.14776895$$

$$ase1 = 0.14776895$$

$$bo_1 = 340.00$$

$$ho_1 = 610.00$$

$$bi2_1 = 975400.00$$

$$ase2 = \text{Max}(ase1, ase2) = 0.14776895$$

$$bo_2 = 192.00$$

$$ho_2 = 492.00$$

$$bi2_2 = 557856.00$$

$$psh_min * Fywe = \text{Min}(psh_x * Fywe, psh_y * Fywe) = 1.38519$$

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 886.8103

fy1 = 739.0086

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 886.8103

fy2 = 739.0086

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 895.9746

fyv = 746.6455

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lo_{u,min} = lb/d = 1.00

su_v = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fs_{yv} = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and y_v, sh_v,ft_v,fy_v, it is considered characteristic value fs_{yv} = fsv/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/d)^{2/3}), from 10.3.5, ASCE 41-17.

with fsv = (fs_{jacket}*As_{l,mid,jacket} + fs_{mid}*As_{l,mid,core})/As_{l,mid} = 746.6455

with Es_v = (Es_{jacket}*As_{l,mid,jacket} + Es_{mid}*As_{l,mid,core})/As_{l,mid} = 200000.00

1 = As_{l,ten}/(b*d)*(fs₁/fc) = 0.09382814

2 = As_{l,com}/(b*d)*(fs₂/fc) = 0.09382814

v = As_{l,mid}/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = As_{l,ten}/(b*d)*(fs₁/fc) = 0.11251192

2 = As_{l,com}/(b*d)*(fs₂/fc) = 0.11251192

v = As_{l,mid}/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < v_{s,c} - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu₂₊

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 0.00010507

Mu = 3.2725E+008

with full section properties:

b = 670.00

d = 357.00

d' = 43.00

v = 0.0003219

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00680405

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00680405

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi_{2,1} = 975400.00

ase2 = Max(ase1,ase2) = 0.14776895

bo_2 = 192.00

ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 895.9746

$f_{yv} = 746.6455$
 $s_{uv} = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_o/l_{ou,min} = l_b/l_d = 1.00$
 $s_{uv} = 0.4 * e_{suv_nominal} ((5,5), TBDY) = 0.032$
 From table 5A.1, TBDY: $e_{suv_nominal} = 0.08$,
 considering characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $e_{suv_nominal}$ and y_v , sh_v , ft_v , f_{yv} , it is considered
 characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1 , sh_1 , ft_1 , f_{y1} , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = (f_{s,jacket} * A_{s,mid,jacket} + f_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 746.6455$
 with $E_{sv} = (E_{s,jacket} * A_{s,mid,jacket} + E_{s,mid} * A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.09382814$
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.09382814$
 $v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.05785932$
 and confined core properties:
 $b = 610.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = A_{s,ten} / (b * d) * (f_{s1} / f_c) = 0.11251192$
 $2 = A_{s,com} / (b * d) * (f_{s2} / f_c) = 0.11251192$
 $v = A_{s,mid} / (b * d) * (f_{sv} / f_c) = 0.06938071$
 Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)
 --->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.1468828$
 $Mu = MRc (4.14) = 3.2725E+008$
 $u = su (4.1) = 0.00010507$

 Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_2 -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$
 $Mu = 3.2725E+008$

with full section properties:

$b = 670.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$
 $f_c = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $w_e (5.4c) = 0.00682295$
 $ase ((5.4d), TBDY) = (ase_1 * A_{ext} + ase_2 * A_{int}) / A_{sec} = 0.14776895$
 $ase_1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$

bi2_1 = 975400.00
ase2 = Max(ase1,ase2) = 0.14776895
bo_2 = 192.00
ho_2 = 492.00
bi2_2 = 557856.00
psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00
s1 = 150.00
s2 = 300.00
fywe1 = 781.25
fywe2 = 656.25
fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y1 = 0.0025
sh1 = 0.008
ft1 = 886.8103
fy1 = 739.0086
su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025
sh2 = 0.008
ft2 = 886.8103
fy2 = 739.0086
su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/d)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025
shv = 0.008
ftv = 895.9746
fyv = 746.6455
suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09382814

2 = Asl,com/(b*d)*(fs2/fc) = 0.09382814

v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11251192

2 = Asl,com/(b*d)*(fs2/fc) = 0.11251192

v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

--->

v < vs,c - RHS eq.(4.5) is satisfied

--->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/ld

Adequate Lap Length: lb/ld >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 390183.487

Calculation of Shear Strength at edge 1, Vr1 = 390183.487

Vr1 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 180743.977

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 27.76119, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

pw = As/(bw*d) = 0.00331157

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

Vu*d/Mu < 1 = 0.00

Mu = 2.1102257E-011

Vu = 6.9728406E-015

From (11.5.4.8), ACI 318-14: Vs1 + Vs2 = 209439.51

Vs1 = 209439.51 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 150.00

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for jacket, with:

d2 = 160.00

Av = 100530.965

fy = 525.00

s = 300.00

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, Vr2 = 390183.487

Vr2 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 180743.977

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 27.76119$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

pw = $A_s / (b_w \cdot d) = 0.00331157$

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

$V_u \cdot d / \mu_u < 1 = 0.00$

$\mu_u = 1.8034731E-013$

$V_u = 6.9728406E-015$

From (11.5.4.8), ACI 318-14: Vs1 + Vs2 = 209439.51

Vs1 = 209439.51 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 150.00

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for jacket, with:

d = 160.00

Av = 100530.965

fy = 525.00

s = 300.00

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (a)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$
Concrete Elasticity, $E_c = 25742.96$
Steel Elasticity, $E_s = 200000.00$
Existing Column
Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
Concrete Elasticity, $E_c = 23025.204$
Steel Elasticity, $E_s = 200000.00$
External Height, $H = 670.00$
External Width, $W = 400.00$
Internal Height, $H = 500.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/l_d >= 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = 4.3723E+006$
Shear Force, $V_2 = -4.5846775E-014$
Shear Force, $V_3 = 5140.455$
Axial Force, $F = -6266.087$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 709.9999$
-Compression: $A_{sc,com} = 1266.062$
-Middle: $A_{sc,mid} = 402.1239$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten,jacket} = 402.1239$
-Compression: $A_{sc,com,jacket} = 804.2477$
-Middle: $A_{sc,mid,jacket} = 402.1239$
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten,core} = 307.8761$
-Compression: $A_{sc,com,core} = 461.8141$
-Middle: $A_{sc,mid,core} = 0.00$
Mean Diameter of Tension Reinforcement, $D_bL = 15.00$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \phi u = 0.02609372$
 $u = \phi u + \psi = 0.02609372$

- Calculation of ϕ -

$\phi = (M_y * L_s / 3) / E_{eff} = 0.00109372$ ((4.29), Biskinis Phd))
 $M_y = 2.9205E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 850.5703
From table 10.5, ASCE 41_17: $E_{eff} = 0.3 * E_c * I_g = 7.5708E+013$

Calculation of Yielding Moment M_y

Calculation of ϕ and M_y according to Annex 7 -

$\phi = \text{Min}(\phi_{ten}, \phi_{com})$

$y_{ten} = 5.8224212E-006$
 with $f_y = 625.00$
 $d = 627.00$
 $y = 0.18831702$
 $A = 0.00952456$
 $B = 0.00407596$
 with $pt = 0.00283094$
 $pc = 0.00504809$
 $pv = 0.00160336$
 $N = 6266.087$
 $b = 400.00$
 $" = 0.06858054$
 $y_{comp} = 1.7830319E-005$
 with $f_c = 27.76119$
 $E_c = 25742.96$
 $y = 0.18763274$
 $A = 0.00942285$
 $B = 0.0040338$
 with $E_s = 200000.00$

 Calculation of ratio I_b/I_d

 Adequate Lap Length: $I_b/I_d \geq 1$

 - Calculation of p -

 From table 10-7: $p = 0.025$

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.92480584$

- Transverse Reinforcement: C

- Stirrup Spacing $\leq d/3$

- Low ductility demand, $\lambda / y < 2$ (table 10-6, ASCE 41-17)

$= 5.2671840E-005$

- Stirrup Spacing $\leq d/2$

$d = d_{external} = 627.00$

$s = s_{external} = 150.00$

- Strength provided by hoops $V_s < 3/4 * \text{design Shear}$

$V_s = 421182.855$, already given in calculation of shear control ratio

design Shear = 5140.455

- ($\lambda - \lambda'$)/ $bal = -0.3178459$

$= A_{slt}/(bw*d) = 0.00283094$

Tension Reinf Area: $A_{slt} = 709.9999$

$\lambda' = A_{slc}/(bw*d) = 0.00665146$

Compression Reinf Area: $A_{slc} = 1668.186$

From (B-1), ACI 318-11: $bal = 0.01202003$

$f_c = (f_{c_jacket} * Area_{jacket} + f_{c_core} * Area_{core}) / \text{section_area} = 27.76119$

$f_y = f_{y_jacket_bars} = 625.00$

From 10.2.7.3, ACI 318-11: $\lambda = 0.65$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = cb/dt = 0.003/(0.003 + y) = 0.48979592$

$y = 0.003125$

- $V/(bw*d*f_c^{0.5}) = 0.04684661$, NOTE: units in lb & in

$bw = 400.00$

 End Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (a)

Calculation No. 11

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity V_{Rd}

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 20.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou,min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 4.3723E+006$

Shear Force, $V_a = 5140.455$

EDGE -B-

Bending Moment, $M_b = 9.7286E+006$

Shear Force, $V_b = 14540.811$

BOTH EDGES

Axial Force, $F = -6266.087$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 709.9999$

-Compression: $As_c = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 709.9999$

-Compression: $As_{c,com} = 1266.062$

-Middle: $As_{mid} = 402.1239$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 15.00$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 463980.549$
 V_n ((22.5.1.1), ACI 318-14) = 463980.549

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 155182.936$

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} \cdot Area_{jacket} + f'_{c,core} \cdot Area_{core}) / Area_{section} = 18.50746$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$\rho_w = A_s / (b_w \cdot d) = 0.00331157$

A_s (tension reinf.) = 709.9999

$b_w = 400.00$

$d = 536.00$

$V_u \cdot d / M_u < 1 = 0.63016543$

$M_u = 4.3723E+006$

$V_u = 5140.455$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 308797.614$

$V_{s1} = 280648.944$ is calculated for jacket, with:

$d = 536.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 150.00$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 28148.67$ is calculated for core, with:

$d = 400.00$

$A_v = 100530.965$

$f_y = 420.00$

$s = 300.00$

V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$2(1-s/d) = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 612724.122$

End Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 12

beam B1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: Start

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.04251
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou}, \min >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = 9840.632$
EDGE -B-
Shear Force, $V_b = 9840.634$
BOTH EDGES
Axial Force, $F = -2309.834$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{sl,ten} = 709.9999$
-Compression: $A_{sl,com} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{sl,ten} = 709.9999$
-Compression: $A_{sl,com} = 1266.062$
-Middle: $A_{sl,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.92480584$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 535287.788$
with
 $M_{pr1} = \max(\mu_{u1+}, \mu_{u1-}) = 7.8817E+008$
 $\mu_{u1+} = 4.6479E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $\mu_{u1-} = 7.8817E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \max(\mu_{u2+}, \mu_{u2-}) = 7.8817E+008$
 $\mu_{u2+} = 4.6479E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination
 $\mu_{u2-} = 7.8817E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = 9840.632$, is the shear force acting at edge 1 for the static loading combination
 $V_2 = 9840.634$, is the shear force acting at edge 2 for the static loading combination

Calculation of μ_{u1+}

Calculation of ultimate curvature μ_u according to 4.1, Biskinis/Fardis 2013:
 $\mu_u = 5.6369735E-005$
 $\mu_u = 4.6479E+008$

with full section properties:
 $b = 400.00$
 $d = 627.00$
 $d' = 43.00$
 $v = 0.000307$
 $N = 2309.834$

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu* = shear_factor * Max(cu, cc) = 0.00680405

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00680405

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = Max(ase1,ase2) = 0.14776895

bo_2 = 192.00

ho_2 = 492.00

bi2_2 = 557856.00

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559

ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 670.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519

ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 400.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 872.4558

fy1 = 727.0465

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 727.0465

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 882.7854

fy2 = 735.6545

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 735.6545

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 937.50

fyv = 781.25

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.06860752

2 = Asl,com/(b*d)*(fs2/fc) = 0.12378842

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00

d = 597.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08477074

2 = Asl,com/(b*d)*(fs2/fc) = 0.15295169

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.09460844

Mu = MRc (4.14) = 4.6479E+008

u = su (4.1) = 5.6369735E-005

Calculation of ratio lb/ld

Adequate Lap Length: lb/ld >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 6.0907698E-005

Mu = 7.8817E+008

with full section properties:

b = 400.00

d = 627.00

$d' = 43.00$
 $v = 0.000307$
 $N = 2309.834$
 $fc = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $we (5.4c) = 0.00682295$
 $ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.14776895$
 $ase1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$
 $bi2_1 = 975400.00$
 $ase2 = Max(ase1, ase2) = 0.14776895$
 $bo_2 = 192.00$
 $ho_2 = 492.00$
 $bi2_2 = 557856.00$
 $psh, min * Fywe = Min(psh, x * Fywe, psh, y * Fywe) = 1.38519$

$psh_x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.45559$
 $ps1 (external) = (Ash1 * h1 / s1) / Asec = 0.00261799$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 670.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / Asec = 0.00062519$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 500.00$

$psh_y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 1.38519$
 $ps1 (external) = (Ash1 * h1 / s1) / Asec = 0.00156298$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / Asec = 0.00025008$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$Asec = 268000.00$
 $s1 = 150.00$
 $s2 = 300.00$
 $fywe1 = 781.25$
 $fywe2 = 656.25$
 $fce = 30.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00242514$
 $c = confinement\ factor = 1.04251$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 882.7854$
 $fy1 = 735.6545$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$

$lo/lou, min = lb/ld = 1.00$

$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs, jacket * Asl, ten, jacket + fs, core * Asl, ten, core) / Asl, ten = 735.6545$

with $Es1 = (Es, jacket * Asl, ten, jacket + Es, core * Asl, ten, core) / Asl, ten = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 872.4558$

$$f_y2 = 727.0465$$

$$s_u2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{s_u2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_u2,nominal} = 0.08$,

For calculation of $e_{s_u2,nominal}$ and y_2, sh_2, ft_2, f_y2 , it is considered
characteristic value $f_{s_y2} = f_{s_2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_y1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s_2} = (f_{s,jacket} * A_{s_l,com,jacket} + f_{s,core} * A_{s_l,com,core}) / A_{s_l,com} = 727.0465$$

$$\text{with } E_{s_2} = (E_{s,jacket} * A_{s_l,com,jacket} + E_{s,core} * A_{s_l,com,core}) / A_{s_l,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$f_{t_v} = 937.50$$

$$f_{y_v} = 781.25$$

$$s_{u_v} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_d = 1.00$$

$$s_{u_v} = 0.4 * e_{s_{u_v},nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{s_{u_v},nominal} = 0.08$,

considering characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY

For calculation of $e_{s_{u_v},nominal}$ and $y_v, sh_v, f_{t_v}, f_{y_v}$, it is considered
characteristic value $f_{s_{y_v}} = f_{s_v}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_y1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s_v} = (f_{s,jacket} * A_{s_l,mid,jacket} + f_{s,mid} * A_{s_l,mid,core}) / A_{s_l,mid} = 781.25$$

$$\text{with } E_{s_v} = (E_{s,jacket} * A_{s_l,mid,jacket} + E_{s,mid} * A_{s_l,mid,core}) / A_{s_l,mid} = 200000.00$$

$$1 = A_{s_l,ten} / (b * d) * (f_{s_1} / f_c) = 0.12378842$$

$$2 = A_{s_l,com} / (b * d) * (f_{s_2} / f_c) = 0.06860752$$

$$v = A_{s_l,mid} / (b * d) * (f_{s_v} / f_c) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{s_l,ten} / (b * d) * (f_{s_1} / f_c) = 0.15295169$$

$$2 = A_{s_l,com} / (b * d) * (f_{s_2} / f_c) = 0.08477074$$

$$v = A_{s_l,mid} / (b * d) * (f_{s_v} / f_c) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y_2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.16206515$$

$$M_u = M_{Rc} (4.15) = 7.8817E+008$$

$$u = s_u (4.1) = 6.0907698E-005$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 5.6369735E-005$$

Mu = 4.6479E+008

with full section properties:

b = 400.00

d = 627.00

d' = 43.00

v = 0.000307

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = $\text{Max}(ase1, ase2) = 0.14776895$

bo_2 = 192.00

ho_2 = 492.00

bi2_2 = 557856.00

$psh_{min} * F_{ywe} = \text{Min}(psh_x * F_{ywe}, psh_y * F_{ywe}) = 1.38519$

$psh_x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.45559$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00261799$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 670.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00062519$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 500.00

$psh_y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 1.38519$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00156298$

Ash1 = $A_{stir_1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00025008$

Ash2 = $A_{stir_2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 872.4558

fy1 = 727.0465

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = $0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y1, sh1, ft1, fy1, it is considered

characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s,jacket} \cdot A_{s,ten,jacket} + f_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 727.0465$
 with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 882.7854$
 $fy_2 = 735.6545$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_{b,min} = 1.00$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 735.6545$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 937.50$
 $fy_v = 781.25$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_d = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 781.25$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.06860752$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.12378842$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04175429$
 and confined core properties:
 $b = 340.00$
 $d = 597.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08477074$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.15295169$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.05159117$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.09460844$
 $Mu = MRc (4.14) = 4.6479E+008$
 $u = su (4.1) = 5.6369735E-005$

 Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_2 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.0907698E-005$$

$$Mu = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00680405$$

$$w_e(5.4c) = 0.00682295$$

$$a_{se}((5.4d), \text{TBDY}) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirups, $n_{s_1} = 2.00$

$$h_1 = 670.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirups, $n_{s_2} = 2.00$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirups, $n_{s_1} = 2.00$

$$h_1 = 400.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirups, $n_{s_2} = 2.00$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{ou, \min} = l_b / d = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}}((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 735.6545$

with $Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 872.4558$

$fy2 = 727.0465$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lo_{ou,min} = lb/lb_{,min} = 1.00$

$su2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered

characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 727.0465$

with $Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 937.50$

$fyv = 781.25$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with $shear_factor$

and also multiplied by the $shear_factor$ according to 15.7.1.4, with

$Shear_factor = 1.00$

$lo/lo_{ou,min} = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_nominal$ and yv, shv, ftv, fyv , it is considered

characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 781.25$

with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.12378842$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.06860752$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.04175429$

and confined core properties:

$b = 340.00$

$d = 597.00$

$d' = 13.00$

f_{cc} (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.15295169$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.08477074$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.05159117$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

su (4.8) = 0.16206515

$Mu = MRc$ (4.15) = 7.8817E+008

$u = su$ (4.1) = 6.0907698E-005

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 578810.994$

Calculation of Shear Strength at edge 1, $V_{r1} = 578810.994$
 $V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
As (tension reinf.) = 709.9999
bw = 400.00
d = 536.00
 $V_u \cdot d / \mu < 1 = 1.00$
 $\mu = 1.1510E+006$
Vu = 9840.632

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$

$V_{s1} = 350811.18$ is calculated for jacket, with:

d = 536.00
Av = 157079.633
fy = 625.00
s = 150.00

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 35185.838$ is calculated for jacket, with:

d2 = 400.00
Av = 100530.965
fy = 525.00
s = 300.00

V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$2(1-s/d) = 0.50$

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 578810.994$

$V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
As (tension reinf.) = 709.9999
bw = 400.00
d = 536.00
 $V_u \cdot d / \mu < 1 = 1.00$
 $\mu = 1.1510E+006$
Vu = 9840.634

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$

$V_{s1} = 350811.18$ is calculated for jacket, with:

d = 536.00
Av = 157079.633
fy = 625.00
s = 150.00

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 35185.838$ is calculated for jacket, with:

d = 400.00
Av = 100530.965
fy = 525.00

s = 300.00

Vs2 has been multiplied by 2(1-s/d) (s>d/2, according to ASCE 41-17,10.3.4)

2(1-s/d) = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 750430.726

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, fc = fcm = 30.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 25742.96

Steel Elasticity, Es = 200000.00

Existing Column

Existing material of Primary Member: Concrete Strength, fc = fcm = 24.00

Existing material of Primary Member: Steel Strength, fs = fsm = 525.00

Concrete Elasticity, Ec = 23025.204

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, fs = 1.25*fsm = 781.25

Existing Column

Existing material: Steel Strength, fs = 1.25*fsm = 656.25

#####

External Height, H = 670.00

External Width, W = 400.00

Internal Height, H = 500.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Mean Confinement Factor overall section = 1.04251

Element Length, L = 3000.00

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length (lo/lou,min>= 1)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, Va = -6.9728406E-015

EDGE -B-

Shear Force, Vb = 6.9728406E-015

BOTH EDGES

Axial Force, F = -2309.834

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: Aslt = 709.9999

-Compression: $Asl,c = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $Asl,t = 911.0619$
-Compression: $Asl,c = 911.0619$
-Middle: $Asl,m = 556.0619$

Calculation of Shear Capacity ratio , $V_e/V_r = 0.55914272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 218168.257$
with

$M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 3.2725E+008$

$\mu_{1+} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$\mu_{1-} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 3.2725E+008$

$\mu_{2+} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{2-} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -6.9728406E-015$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 6.9728406E-015$, is the shear force acting at edge 2 for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010507$

$M_u = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$f_c = 30.00$

ϕ_c (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00680405$

ϕ_u (5.4c) = 0.00682295

$\phi_{u,ase}$ ((5.4d), TBDY) = $(\phi_{u,ase1} \cdot A_{ext} + \phi_{u,ase2} \cdot A_{int})/A_{sec} = 0.14776895$

$\phi_{u,ase1} = 0.14776895$

$b_{o,1} = 340.00$

$h_{o,1} = 610.00$

$b_{i,1} = 975400.00$

$\phi_{u,ase2} = \text{Max}(\phi_{u,ase1}, \phi_{u,ase2}) = 0.14776895$

$b_{o,2} = 192.00$

$h_{o,2} = 492.00$

$b_{i,2} = 557856.00$

$\phi_{sh,min} \cdot F_{ywe} = \text{Min}(\phi_{sh,x} \cdot F_{ywe}, \phi_{sh,y} \cdot F_{ywe}) = 1.38519$

$\phi_{sh,x} \cdot F_{ywe} = \phi_{sh1} \cdot F_{ywe1} + \phi_{sh2} \cdot F_{ywe2} = 2.45559$

ϕ_{sh1} (external) = $(A_{sh1} \cdot h_1/s_1)/A_{sec} = 0.00261799$

$A_{sh1} = A_{stir,1} \cdot n_{s,1} = 157.0796$

No stirups, $n_{s,1} = 2.00$

$h_1 = 670.00$

ϕ_{sh2} (internal) = $(A_{sh2} \cdot h_2/s_2)/A_{sec} = 0.00062519$

Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 886.8103

fy1 = 739.0086

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 886.8103

fy2 = 739.0086

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 895.9746

fyv = 746.6455

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 746.6455$

with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.09382814$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.09382814$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.05785932$

and confined core properties:

$b = 610.00$

$d = 327.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 31.27541$

$cc (5A.5, TBDY) = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11251192$

$2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11251192$

$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

---->

$su (4.9) = 0.1468828$

$Mu = MRc (4.14) = 3.2725E+008$

$u = su (4.1) = 0.00010507$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu_1 -

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$

$Mu = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$f_c = 30.00$

$co (5A.5, TBDY) = 0.002$

Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase_1 \cdot A_{ext} + ase_2 \cdot A_{int}) / A_{sec} = 0.14776895$

$ase_1 = 0.14776895$

$bo_1 = 340.00$

$ho_1 = 610.00$

$bi_2_1 = 975400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.14776895$

$bo_2 = 192.00$

$ho_2 = 492.00$

$bi_2_2 = 557856.00$

$psh_{min} \cdot F_{ywe} = \text{Min}(psh_x \cdot F_{ywe}, psh_y \cdot F_{ywe}) = 1.38519$

 $psh_x \cdot F_{ywe} = psh_1 \cdot F_{ywe1} + ps_2 \cdot F_{ywe2} = 2.45559$

ps_1 (external) = $(Ash_1 \cdot h_1 / s_1) / A_{sec} = 0.00261799$

$Ash_1 = Astir_1 \cdot ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$
 $h1 = 670.00$
 $ps2$ (internal) = $(Ash2 \cdot h2 / s2) / Asec = 0.00062519$
 $Ash2 = Astir_2 \cdot ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 500.00$

 $psh_y \cdot Fywe = psh1 \cdot Fywe1 + ps2 \cdot Fywe2 = 1.38519$
 $ps1$ (external) = $(Ash1 \cdot h1 / s1) / Asec = 0.00156298$
 $Ash1 = Astir_1 \cdot ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2$ (internal) = $(Ash2 \cdot h2 / s2) / Asec = 0.00025008$
 $Ash2 = Astir_2 \cdot ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

 $Asec = 268000.00$
 $s1 = 150.00$
 $s2 = 300.00$
 $fywe1 = 781.25$
 $fywe2 = 656.25$
 $fce = 30.00$

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$
 $c =$ confinement factor = 1.04251

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 886.8103$
 $fy1 = 739.0086$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou, min = lb/ld = 1.00$

$su1 = 0.4 \cdot esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_jacket \cdot Asl, ten, jacket + fs_core \cdot Asl, ten, core) / Asl, ten = 739.0086$

with $Es1 = (Es_jacket \cdot Asl, ten, jacket + Es_core \cdot Asl, ten, core) / Asl, ten = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 886.8103$
 $fy2 = 739.0086$
 $su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou, min = lb/lb, min = 1.00$

$su2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_jacket \cdot Asl, com, jacket + fs_core \cdot Asl, com, core) / Asl, com = 739.0086$

with $Es2 = (Es_jacket \cdot Asl, com, jacket + Es_core \cdot Asl, com, core) / Asl, com = 200000.00$

$yv = 0.0025$
 $shv = 0.008$
 $ftv = 895.9746$
 $fyv = 746.6455$
 $suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou, min = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455$

with $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$

1 = $Asl,ten/(b*d)*(fs1/fc) = 0.09382814$

2 = $Asl,com/(b*d)*(fs2/fc) = 0.09382814$

$v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932$

and confined core properties:

$b = 610.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

$c =$ confinement factor = 1.04251

1 = $Asl,ten/(b*d)*(fs1/fc) = 0.11251192$

2 = $Asl,com/(b*d)*(fs2/fc) = 0.11251192$

$v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < vs,c$ - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

$Mu = MRc$ (4.14) = 3.2725E+008

$u = su$ (4.1) = 0.00010507

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$

$Mu = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$fc = 30.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase1*Aext+ase2*Aint)/Asec = 0.14776895$

$ase1 = 0.14776895$

$bo_1 = 340.00$

$ho_1 = 610.00$

$bi2_1 = 975400.00$

$ase2 = Max(ase1,ase2) = 0.14776895$

$bo_2 = 192.00$

$ho_2 = 492.00$

$bi2_2 = 557856.00$

$psh,min*Fywe = Min(psh,x*Fywe, psh,y*Fywe) = 1.38519$

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 886.8103

fy1 = 739.0086

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 886.8103

fy2 = 739.0086

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 895.9746

fyv = 746.6455

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fsjacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09382814

2 = Asl,com/(b*d)*(fs2/fc) = 0.09382814

v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11251192

2 = Asl,com/(b*d)*(fs2/fc) = 0.11251192

v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 0.00010507

Mu = 3.2725E+008

with full section properties:

b = 670.00

d = 357.00

d' = 43.00

v = 0.0003219

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00680405

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00680405

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = Max(ase1,ase2) = 0.14776895

bo_2 = 192.00

ho_2 = 492.00

$$bi2_2 = 557856.00$$
$$psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 1.38519$$

$$psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.45559$$
$$ps1 \text{ (external)} = (Ash1*h1/s1)/Asec = 0.00261799$$
$$Ash1 = Astir_1*ns_1 = 157.0796$$
$$\text{No stirups, } ns_1 = 2.00$$
$$h1 = 670.00$$
$$ps2 \text{ (internal)} = (Ash2*h2/s2)/Asec = 0.00062519$$
$$Ash2 = Astir_2*ns_2 = 100.531$$
$$\text{No stirups, } ns_2 = 2.00$$
$$h2 = 500.00$$

$$psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 1.38519$$
$$ps1 \text{ (external)} = (Ash1*h1/s1)/Asec = 0.00156298$$
$$Ash1 = Astir_1*ns_1 = 157.0796$$
$$\text{No stirups, } ns_1 = 2.00$$
$$h1 = 400.00$$
$$ps2 \text{ (internal)} = (Ash2*h2/s2)/Asec = 0.00025008$$
$$Ash2 = Astir_2*ns_2 = 100.531$$
$$\text{No stirups, } ns_2 = 2.00$$
$$h2 = 200.00$$

$$Asec = 268000.00$$

$$s1 = 150.00$$

$$s2 = 300.00$$

$$fywe1 = 781.25$$

$$fywe2 = 656.25$$

$$fce = 30.00$$

$$\text{From } ((5.A.5), \text{ TBDY}), \text{ TBDY: } cc = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 886.8103$$

$$fy1 = 739.0086$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_d = 1.00$$

$$su1 = 0.4*esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086$$

$$\text{with } Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 886.8103$$

$$fy2 = 739.0086$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_b,min = 1.00$$

$$su2 = 0.4*esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 895.9746$$

$$fyv = 746.6455$$

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fsjacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09382814

2 = Asl,com/(b*d)*(fs2/fc) = 0.09382814

v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11251192

2 = Asl,com/(b*d)*(fs2/fc) = 0.11251192

v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 390183.487

Calculation of Shear Strength at edge 1, Vr1 = 390183.487

Vr1 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 180743.977

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 27.76119, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

pw = As/(bw*d) = 0.00331157

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

Vu*d/Mu < 1 = 0.00

Mu = 2.1102257E-011

Vu = 6.9728406E-015

From (11.5.4.8), ACI 318-14: Vs1 + Vs2 = 209439.51

Vs1 = 209439.51 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 150.00

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for jacket, with:

d2 = 160.00

Av = 100530.965

fy = 525.00

s = 300.00

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, Vr2 = 390183.487

Vr2 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 180743.977

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 27.76119$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

pw = $As / (bw * d) = 0.00331157$

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

$V_u * d / Mu < 1 = 0.00$

Mu = 1.8034731E-013

Vu = 6.9728406E-015

From (11.5.4.8), ACI 318-14: Vs1 + Vs2 = 209439.51

Vs1 = 209439.51 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 150.00

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for jacket, with:

d = 160.00

Av = 100530.965

fy = 525.00

s = 300.00

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (a)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
Concrete Elasticity, $E_c = 23025.204$
Steel Elasticity, $E_s = 200000.00$
External Height, $H = 670.00$
External Width, $W = 400.00$
Internal Height, $H = 500.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/l_d >= 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -7.2842051E-011$
Shear Force, $V_2 = -4.5846775E-014$
Shear Force, $V_3 = 5140.455$
Axial Force, $F = -6266.087$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 911.0619$
-Compression: $A_{st,com} = 911.0619$
-Middle: $A_{st,mid} = 556.0619$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten,jacket} = 603.1858$
-Compression: $A_{st,com,jacket} = 603.1858$
-Middle: $A_{st,mid,jacket} = 402.1239$
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten,core} = 307.8761$
-Compression: $A_{st,com,core} = 307.8761$
-Middle: $A_{st,mid,core} = 153.938$
Mean Diameter of Tension Reinforcement, $DbL = 15.20$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \phi \cdot u = 0.02409992$
 $u = \phi \cdot y + \rho = 0.02409992$

- Calculation of y -

$y = (M_y \cdot L_s / 3) / E_{eff} = 0.00409992$ ((4.29), Biskinis Phd))
 $M_y = 2.1236E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00
From table 10.5, ASCE 41_17: $E_{eff} = 0.3 \cdot E_c \cdot I_g = 2.5898E+013$

Calculation of Yielding Moment M_y

Calculation of y and M_y according to Annex 7 -

$y = \text{Min}(y_{ten}, y_{com})$
 $y_{ten} = 1.0748658E-005$
with $f_y = 625.00$
 $d = 357.00$
 $y = 0.22779052$

A = 0.00998687
B = 0.00561432
with pt = 0.00380895
pc = 0.00380895
pv = 0.00232477
N = 6266.087
b = 670.00
" = 0.12044818
y_comp = 2.5852450E-005
with fc = 27.76119
Ec = 25742.96
y = 0.22728216
A = 0.00988022
B = 0.00557012
with Es = 200000.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of p -

From table 10-7: p = 0.02

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.55914272$

- Transverse Reinforcement: NC

- Stirrup Spacing > d/3

- Low ductility demand, $\lambda < 2$ (table 10-6, ASCE 41-17)

= 6.2952160E-022

- Stirrup Spacing <= d/2

d = d_external = 357.00

s = s_external = 150.00

- Strength provided by hoops $V_s < 3/4$ *design Shear

$V_s = 237588.18$, already given in calculation of shear control ratio

design Shear = 4.5846775E-014

- (- ')/ bal = -0.33327376

= $A_{st}/(b_w*d) = 0.00296835$

Tension Reinf Area: $A_{st} = 709.9999$

' = $A_{sc}/(b_w*d) = 0.00697431$

Compression Reinf Area: $A_{sc} = 1668.186$

From (B-1), ACI 318-11: bal = 0.01202003

$f_c = (f_{c_jacket}*Area_jacket + f_{c_core}*Area_core)/section_area = 27.76119$

$f_y = f_{y_jacket_bars} = 625.00$

From 10.2.7.3, ACI 318-11: $\lambda = 0.65$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + \lambda) = 0.48979592$

$\lambda = 0.003125$

- $V/(b_w*d*f_c^{0.5}) = 4.3809665E-019$, NOTE: units in lb & in

$b_w = 670.00$

End Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (a)

Calculation No. 13

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VR_d

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 20.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{ou, \min} = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = -7.2842051E-011$

Shear Force, $V_a = -4.5846775E-014$

EDGE -B-

Bending Moment, $M_b = -6.4836912E-011$

Shear Force, $V_b = 4.5846775E-014$

BOTH EDGES

Axial Force, $F = -6266.087$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $A_{st} = 709.9999$

-Compression: $A_{sc} = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $A_{st, \text{ten}} = 911.0619$

-Compression: $A_{sc, \text{com}} = 911.0619$

-Middle: $A_{sc, \text{mid}} = 556.0619$

Mean Diameter of Tension Reinforcement, $D_{bL, \text{ten}} = 15.20$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 315128.448$
 V_n ((22.5.1.1), ACI 318-14) = 315128.448

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f_v V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 147576.839$

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{\text{jacket}} \cdot \text{Area}_{\text{jacket}} + f_c'_{\text{core}} \cdot \text{Area}_{\text{core}}) / \text{Area}_{\text{section}} = 18.50746$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

$\rho_w = A_s / (b_w \cdot d) = 0.00331157$

A_s (tension reinf.) = 709.9999

$b_w = 670.00$

$d = 320.00$

$V_u \cdot d / M_u < 1 = 0.00$

$M_u = 6.4836912E-011$

$V_u = 4.5846775E-014$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 167551.608$

$V_{s1} = 167551.608$ is calculated for jacket, with:

$d = 320.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 150.00$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17, 10.3.4)

$V_{s2} = 0.00$ is calculated for core, with:

$d = 160.00$

$A_v = 100530.965$

$f_y = 420.00$

$s = 300.00$

V_{s2} is considered 0 ($s > d$, according to ASCE 41-17, 10.3.4)

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 612724.122$

End Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 14

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (2)



Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.04251
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou}, \min >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = 9840.632$
EDGE -B-
Shear Force, $V_b = 9840.634$
BOTH EDGES
Axial Force, $F = -2309.834$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 709.9999$
-Compression: $A_{sc,com} = 1266.062$
-Middle: $A_{st,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.92480584$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 535287.788$
with
 $M_{pr1} = \text{Max}(\mu_{u1+}, \mu_{u1-}) = 7.8817E+008$
 $\mu_{u1+} = 4.6479E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $\mu_{u1-} = 7.8817E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{u2+}, \mu_{u2-}) = 7.8817E+008$
 $\mu_{u2+} = 4.6479E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination
 $\mu_{u2-} = 7.8817E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = 9840.632$, is the shear force acting at edge 1 for the static loading combination
 $V_2 = 9840.634$, is the shear force acting at edge 2 for the static loading combination

Calculation of μ_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 5.6369735E-005$
 $\mu_u = 4.6479E+008$

with full section properties:
 $b = 400.00$
 $d = 627.00$
 $d' = 43.00$
 $v = 0.000307$
 $N = 2309.834$

fc = 30.00

cc (5A.5, TBDY) = 0.002

Final value of cu* = shear_factor * Max(cu, cc) = 0.00680405

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00680405

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = Max(ase1,ase2) = 0.14776895

bo_2 = 192.00

ho_2 = 492.00

bi2_2 = 557856.00

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559

ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 670.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519

ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 400.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 872.4558

fy1 = 727.0465

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 727.0465

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 882.7854

fy2 = 735.6545

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 735.6545

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 937.50

fyv = 781.25

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.06860752

2 = Asl,com/(b*d)*(fs2/fc) = 0.12378842

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00

d = 597.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08477074

2 = Asl,com/(b*d)*(fs2/fc) = 0.15295169

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.09460844

Mu = MRc (4.14) = 4.6479E+008

u = su (4.1) = 5.6369735E-005

Calculation of ratio lb/ld

Adequate Lap Length: lb/ld >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 6.0907698E-005

Mu = 7.8817E+008

with full section properties:

b = 400.00

d = 627.00

$d' = 43.00$
 $v = 0.000307$
 $N = 2309.834$
 $fc = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $we (5.4c) = 0.00682295$
 $ase ((5.4d), TBDY) = (ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$
 $ase1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$
 $bi2_1 = 975400.00$
 $ase2 = \text{Max}(ase1, ase2) = 0.14776895$
 $bo_2 = 192.00$
 $ho_2 = 492.00$
 $bi2_2 = 557856.00$
 $psh, \min * F_{ywe} = \text{Min}(psh, x * F_{ywe}, psh, y * F_{ywe}) = 1.38519$

$psh, x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.45559$
 $ps1 (external) = (Ash1 * h1 / s1) / A_{sec} = 0.00261799$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 670.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / A_{sec} = 0.00062519$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 500.00$

$psh, y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 1.38519$
 $ps1 (external) = (Ash1 * h1 / s1) / A_{sec} = 0.00156298$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / A_{sec} = 0.00025008$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$A_{sec} = 268000.00$
 $s1 = 150.00$
 $s2 = 300.00$
 $fywe1 = 781.25$
 $fywe2 = 656.25$
 $fce = 30.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00242514$
 $c = \text{confinement factor} = 1.04251$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 882.7854$
 $fy1 = 735.6545$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $\text{Shear_factor} = 1.00$

$lo/lou, \min = lb/ld = 1.00$

$su1 = 0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs, \text{jacket} * A_{sl, \text{ten, jacket}} + fs, \text{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 735.6545$

with $Es1 = (Es, \text{jacket} * A_{sl, \text{ten, jacket}} + Es, \text{core} * A_{sl, \text{ten, core}}) / A_{sl, \text{ten}} = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 872.4558$

$$f_y2 = 727.0465$$

$$s_u2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,

For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, f_y2 , it is considered
characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_y1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 727.0465$$

$$\text{with } E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$f_{tv} = 937.50$$

$$f_{yv} = 781.25$$

$$s_{uv} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_d = 1.00$$

$$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and $y_v, sh_v, f_{tv}, f_{yv}$, it is considered
characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_y1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 781.25$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$$

$$1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.12378842$$

$$2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.06860752$$

$$v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 31.27541$$

$$c_c (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.15295169$$

$$2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.08477074$$

$$v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.16206515$$

$$M_u = M_{Rc} (4.15) = 7.8817E+008$$

$$u = s_u (4.1) = 6.0907698E-005$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 5.6369735E-005$$

Mu = 4.6479E+008

with full section properties:

b = 400.00

d = 627.00

d' = 43.00

v = 0.000307

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = $\text{Max}(ase1, ase2) = 0.14776895$

bo_2 = 192.00

ho_2 = 492.00

bi2_2 = 557856.00

$psh, \min * F_{ywe} = \text{Min}(psh, x * F_{ywe}, psh, y * F_{ywe}) = 1.38519$

$psh, x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.45559$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00261799$

Ash1 = $A_{stir,1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 670.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00062519$

Ash2 = $A_{stir,2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 500.00

$psh, y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 1.38519$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00156298$

Ash1 = $A_{stir,1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00025008$

Ash2 = $A_{stir,2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 872.4558

fy1 = 727.0465

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = $0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y1, sh1, ft1, fy1, it is considered characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{s1} = (f_{s,jacket} \cdot A_{s,ten,jacket} + f_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 727.0465$
 with $E_{s1} = (E_{s,jacket} \cdot A_{s,ten,jacket} + E_{s,core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$
 $y_2 = 0.0025$
 $sh_2 = 0.008$
 $ft_2 = 882.7854$
 $fy_2 = 735.6545$
 $su_2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_{b,min} = 1.00$
 $su_2 = 0.4 \cdot esu_{2,nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu_{2,nominal} = 0.08$,
 For calculation of $esu_{2,nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered
 characteristic value $f_{sy2} = f_{s2}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{s2} = (f_{s,jacket} \cdot A_{s,com,jacket} + f_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 735.6545$
 with $E_{s2} = (E_{s,jacket} \cdot A_{s,com,jacket} + E_{s,core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$
 $y_v = 0.0025$
 $sh_v = 0.008$
 $ft_v = 937.50$
 $fy_v = 781.25$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $l_0/l_{ou,min} = l_b/l_d = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered
 characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 781.25$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.06860752$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.12378842$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.04175429$
 and confined core properties:
 $b = 340.00$
 $d = 597.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.08477074$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.15295169$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.05159117$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < v_{s,y2}$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.09460844$
 $Mu = MRc (4.14) = 4.6479E+008$
 $u = su (4.1) = 5.6369735E-005$

 Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of Mu_2 -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.0907698E-005$$

$$Mu = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00680405$$

$$w_e(5.4c) = 0.00682295$$

$$a_{se}((5.4d), \text{TBDY}) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirups, $n_{s_1} = 2.00$

$$h_1 = 670.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirups, $n_{s_2} = 2.00$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirups, $n_{s_1} = 2.00$

$$h_1 = 400.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirups, $n_{s_2} = 2.00$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{ou, \min} = l_b / d = 1.00$$

$$su_1 = 0.4 * esu_{1, \text{nominal}}((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $esu_{1, \text{nominal}} = 0.08$,

For calculation of $es_{u1_nominal}$ and y_1, sh_1, ft_1, fy_1 , it is considered characteristic value $fs_{y1} = fs_1/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_1 = (fs_{jacket} \cdot A_{s,ten,jacket} + fs_{core} \cdot A_{s,ten,core}) / A_{s,ten} = 735.6545$

with $Es_1 = (Es_{jacket} \cdot A_{s,ten,jacket} + Es_{core} \cdot A_{s,ten,core}) / A_{s,ten} = 200000.00$

$$y_2 = 0.0025$$

$$sh_2 = 0.008$$

$$ft_2 = 872.4558$$

$$fy_2 = 727.0465$$

$$su_2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lo_{ou,min} = lb/lb_{,min} = 1.00$$

$$su_2 = 0.4 \cdot es_{u2_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $es_{u2_nominal} = 0.08$,

For calculation of $es_{u2_nominal}$ and y_2, sh_2, ft_2, fy_2 , it is considered characteristic value $fs_{y2} = fs_2/1.2$, from table 5.1, TBDY.

y_2, sh_2, ft_2, fy_2 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs_2 = (fs_{jacket} \cdot A_{s,com,jacket} + fs_{core} \cdot A_{s,com,core}) / A_{s,com} = 727.0465$

with $Es_2 = (Es_{jacket} \cdot A_{s,com,jacket} + Es_{core} \cdot A_{s,com,core}) / A_{s,com} = 200000.00$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$ft_v = 937.50$$

$$fy_v = 781.25$$

$$su_v = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lo_{ou,min} = lb/ld = 1.00$$

$$su_v = 0.4 \cdot es_{uv_nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $es_{uv_nominal} = 0.08$,

considering characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $es_{uv_nominal}$ and y_v, sh_v, ft_v, fy_v , it is considered characteristic value $fs_{yv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 781.25$

with $Es_v = (Es_{jacket} \cdot A_{s,mid,jacket} + Es_{mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$

$$1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.12378842$$

$$2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.06860752$$

$$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / fc) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$fcc (5A.2, TBDY) = 31.27541$$

$$cc (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{s,ten} / (b \cdot d) \cdot (fs_1 / fc) = 0.15295169$$

$$2 = A_{s,com} / (b \cdot d) \cdot (fs_2 / fc) = 0.08477074$$

$$v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / fc) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$su (4.8) = 0.16206515$$

$$\mu = MR_c (4.15) = 7.8817E+008$$

$$u = su (4.1) = 6.0907698E-005$$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 578810.994$

Calculation of Shear Strength at edge 1, $V_{r1} = 578810.994$
 $V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 400.00$
 $d = 536.00$
 $V_u \cdot d / \mu < 1 = 1.00$
 $\mu = 1.1510E+006$
 $V_u = 9840.632$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$

$V_{s1} = 350811.18$ is calculated for jacket, with:

$d = 536.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 35185.838$ is calculated for jacket, with:

$d_2 = 400.00$
 $A_v = 100530.965$
 $f_y = 525.00$
 $s = 300.00$

V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$2(1-s/d) = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 578810.994$

$V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) ' V_w ' is replaced by ' $V_w + f \cdot V_f$ '
where V_f is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
 A_s (tension reinf.) = 709.9999
 $b_w = 400.00$
 $d = 536.00$
 $V_u \cdot d / \mu < 1 = 1.00$
 $\mu = 1.1510E+006$
 $V_u = 9840.634$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$

$V_{s1} = 350811.18$ is calculated for jacket, with:

$d = 536.00$
 $A_v = 157079.633$
 $f_y = 625.00$
 $s = 150.00$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 35185.838$ is calculated for jacket, with:

$d = 400.00$
 $A_v = 100530.965$
 $f_y = 525.00$

s = 300.00

Vs2 has been multiplied by 2(1-s/d) (s>d/2, according to ASCE 41-17,10.3.4)

2(1-s/d) = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 750430.726

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, fc = fcm = 30.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 25742.96

Steel Elasticity, Es = 200000.00

Existing Column

Existing material of Primary Member: Concrete Strength, fc = fcm = 24.00

Existing material of Primary Member: Steel Strength, fs = fsm = 525.00

Concrete Elasticity, Ec = 23025.204

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, fs = 1.25*fsm = 781.25

Existing Column

Existing material: Steel Strength, fs = 1.25*fsm = 656.25

#####

External Height, H = 670.00

External Width, W = 400.00

Internal Height, H = 500.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Mean Confinement Factor overall section = 1.04251

Element Length, L = 3000.00

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length (lo/lo_u,min>= 1)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, Va = -6.9728406E-015

EDGE -B-

Shear Force, Vb = 6.9728406E-015

BOTH EDGES

Axial Force, F = -2309.834

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: Aslt = 709.9999

-Compression: $Asl,c = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $Asl,t = 911.0619$
-Compression: $Asl,c = 911.0619$
-Middle: $Asl,m = 556.0619$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.55914272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 218168.257$
with

$M_{pr1} = \text{Max}(\mu_{1+}, \mu_{1-}) = 3.2725E+008$

$\mu_{1+} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$\mu_{1-} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(\mu_{2+}, \mu_{2-}) = 3.2725E+008$

$\mu_{2+} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$\mu_{2-} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -6.9728406E-015$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 6.9728406E-015$, is the shear force acting at edge 2 for the the static loading combination

Calculation of μ_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010507$

$M_u = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$f_c = 30.00$

ϕ_c (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase_1 \cdot A_{ext} + ase_2 \cdot A_{int})/A_{sec} = 0.14776895$

$ase_1 = 0.14776895$

$bo_1 = 340.00$

$ho_1 = 610.00$

$bi_2_1 = 975400.00$

$ase_2 = \text{Max}(ase_1, ase_2) = 0.14776895$

$bo_2 = 192.00$

$ho_2 = 492.00$

$bi_2_2 = 557856.00$

$psh_{min} \cdot F_{ywe} = \text{Min}(psh_x \cdot F_{ywe}, psh_y \cdot F_{ywe}) = 1.38519$

$psh_x \cdot F_{ywe} = psh_1 \cdot F_{ywe1} + ps_2 \cdot F_{ywe2} = 2.45559$

ps_1 (external) = $(A_{sh1} \cdot h_1/s_1)/A_{sec} = 0.00261799$

$A_{sh1} = Astir_1 \cdot ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

$h_1 = 670.00$

ps_2 (internal) = $(A_{sh2} \cdot h_2/s_2)/A_{sec} = 0.00062519$

Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 886.8103

fy1 = 739.0086

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 886.8103

fy2 = 739.0086

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/lb)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 895.9746

fyv = 746.6455

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 746.6455$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.09382814$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.09382814$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.05785932$

and confined core properties:

$b = 610.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11251192$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11251192$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)

---->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 ---->
 $su (4.9) = 0.1468828$
 $Mu = MRc (4.14) = 3.2725E+008$
 $u = su (4.1) = 0.00010507$

 Calculation of ratio lb/ld

 Adequate Lap Length: $lb/ld \geq 1$

 Calculation of Mu_1 -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
 $u = 0.00010507$
 $Mu = 3.2725E+008$

with full section properties:

$b = 670.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$
 $f_c = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $w_e (5.4c) = 0.00682295$
 $ase ((5.4d), TBDY) = (ase_1 \cdot A_{ext} + ase_2 \cdot A_{int}) / A_{sec} = 0.14776895$
 $ase_1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$
 $bi_2_1 = 975400.00$
 $ase_2 = \text{Max}(ase_1, ase_2) = 0.14776895$
 $bo_2 = 192.00$
 $ho_2 = 492.00$
 $bi_2_2 = 557856.00$
 $psh_{,min} \cdot F_{ywe} = \text{Min}(psh_x \cdot F_{ywe}, psh_y \cdot F_{ywe}) = 1.38519$

 $psh_x \cdot F_{ywe} = psh_1 \cdot F_{ywe1} + ps_2 \cdot F_{ywe2} = 2.45559$
 $ps_1 (\text{external}) = (A_{sh1} \cdot h_1 / s_1) / A_{sec} = 0.00261799$
 $A_{sh1} = A_{stir_1} \cdot n_{s_1} = 157.0796$

No stirups, $ns_1 = 2.00$
 $h1 = 670.00$
 $ps2$ (internal) = $(Ash2 \cdot h2 / s2) / Asec = 0.00062519$
 $Ash2 = Astir_2 \cdot ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 500.00$

 $psh_y \cdot Fywe = psh1 \cdot Fywe1 + ps2 \cdot Fywe2 = 1.38519$
 $ps1$ (external) = $(Ash1 \cdot h1 / s1) / Asec = 0.00156298$
 $Ash1 = Astir_1 \cdot ns_1 = 157.0796$
No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2$ (internal) = $(Ash2 \cdot h2 / s2) / Asec = 0.00025008$
 $Ash2 = Astir_2 \cdot ns_2 = 100.531$
No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

 $Asec = 268000.00$
 $s1 = 150.00$
 $s2 = 300.00$
 $fywe1 = 781.25$
 $fywe2 = 656.25$
 $fce = 30.00$

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$
 $c =$ confinement factor = 1.04251

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 886.8103$
 $fy1 = 739.0086$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou, min = lb/ld = 1.00$

$su1 = 0.4 \cdot esu1_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_jacket \cdot Asl, ten, jacket + fs_core \cdot Asl, ten, core) / Asl, ten = 739.0086$

with $Es1 = (Es_jacket \cdot Asl, ten, jacket + Es_core \cdot Asl, ten, core) / Asl, ten = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 886.8103$
 $fy2 = 739.0086$
 $su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou, min = lb/lb, min = 1.00$

$su2 = 0.4 \cdot esu2_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_jacket \cdot Asl, com, jacket + fs_core \cdot Asl, com, core) / Asl, com = 739.0086$

with $Es2 = (Es_jacket \cdot Asl, com, jacket + Es_core \cdot Asl, com, core) / Asl, com = 200000.00$

$yv = 0.0025$
 $shv = 0.008$
 $ftv = 895.9746$
 $fyv = 746.6455$
 $suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$lo/lou, min = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_nominal$ ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket}*Asl_{mid,jacket} + fs_{mid}*Asl_{mid,core})/Asl_{mid} = 746.6455$

with $Esv = (Es_{jacket}*Asl_{mid,jacket} + Es_{mid}*Asl_{mid,core})/Asl_{mid} = 200000.00$

1 = $Asl_{ten}/(b*d)*(fs1/fc) = 0.09382814$

2 = $Asl_{com}/(b*d)*(fs2/fc) = 0.09382814$

v = $Asl_{mid}/(b*d)*(fsv/fc) = 0.05785932$

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = $Asl_{ten}/(b*d)*(fs1/fc) = 0.11251192$

2 = $Asl_{com}/(b*d)*(fs2/fc) = 0.11251192$

v = $Asl_{mid}/(b*d)*(fsv/fc) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/l_d

Adequate Lap Length: lb/l_d >= 1

Calculation of Mu₂₊

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 0.00010507

Mu = 3.2725E+008

with full section properties:

b = 670.00

d = 357.00

d' = 43.00

v = 0.0003219

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = shear_factor * Max(cu, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase1*A_{ext} + ase2*A_{int})/A_{sec} = 0.14776895$

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = $Max(ase1, ase2) = 0.14776895$

bo_2 = 192.00

ho_2 = 492.00

bi2_2 = 557856.00

psh,min*Fywe = $Min(psh,x*Fywe, psh,y*Fywe) = 1.38519$

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 886.8103

fy1 = 739.0086

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 886.8103

fy2 = 739.0086

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 895.9746

fyv = 746.6455

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fsjacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09382814

2 = Asl,com/(b*d)*(fs2/fc) = 0.09382814

v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11251192

2 = Asl,com/(b*d)*(fs2/fc) = 0.11251192

v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 0.00010507

Mu = 3.2725E+008

with full section properties:

b = 670.00

d = 357.00

d' = 43.00

v = 0.0003219

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00680405

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00680405

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = Max(ase1,ase2) = 0.14776895

bo_2 = 192.00

ho_2 = 492.00

$$bi2_2 = 557856.00$$
$$psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 1.38519$$

$$psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.45559$$
$$ps1 \text{ (external)} = (Ash1*h1/s1)/Asec = 0.00261799$$
$$Ash1 = Astir_1*ns_1 = 157.0796$$
$$\text{No stirups, } ns_1 = 2.00$$
$$h1 = 670.00$$
$$ps2 \text{ (internal)} = (Ash2*h2/s2)/Asec = 0.00062519$$
$$Ash2 = Astir_2*ns_2 = 100.531$$
$$\text{No stirups, } ns_2 = 2.00$$
$$h2 = 500.00$$

$$psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 1.38519$$
$$ps1 \text{ (external)} = (Ash1*h1/s1)/Asec = 0.00156298$$
$$Ash1 = Astir_1*ns_1 = 157.0796$$
$$\text{No stirups, } ns_1 = 2.00$$
$$h1 = 400.00$$
$$ps2 \text{ (internal)} = (Ash2*h2/s2)/Asec = 0.00025008$$
$$Ash2 = Astir_2*ns_2 = 100.531$$
$$\text{No stirups, } ns_2 = 2.00$$
$$h2 = 200.00$$

$$Asec = 268000.00$$
$$s1 = 150.00$$
$$s2 = 300.00$$
$$fywe1 = 781.25$$
$$fywe2 = 656.25$$
$$fce = 30.00$$

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$
 $c = \text{confinement factor} = 1.04251$

$$y1 = 0.0025$$
$$sh1 = 0.008$$
$$ft1 = 886.8103$$
$$fy1 = 739.0086$$
$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/l_d = 1.00$$

$$su1 = 0.4*esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086$$

$$\text{with } Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$$

$$y2 = 0.0025$$
$$sh2 = 0.008$$
$$ft2 = 886.8103$$
$$fy2 = 739.0086$$
$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$lo/lou,min = lb/l_b,min = 1.00$$

$$su2 = 0.4*esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: $esu2_nominal = 0.08$,

For calculation of $esu2_nominal$ and $y2, sh2, ft2, fy2$, it is considered
characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.0025$$
$$shv = 0.008$$
$$ftv = 895.9746$$
$$fyv = 746.6455$$

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fsjacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09382814

2 = Asl,com/(b*d)*(fs2/fc) = 0.09382814

v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11251192

2 = Asl,com/(b*d)*(fs2/fc) = 0.11251192

v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 390183.487

Calculation of Shear Strength at edge 1, Vr1 = 390183.487

Vr1 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 180743.977

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 27.76119, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

pw = As/(bw*d) = 0.00331157

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

Vu*d/Mu < 1 = 0.00

Mu = 2.1102257E-011

Vu = 6.9728406E-015

From (11.5.4.8), ACI 318-14: Vs1 + Vs2 = 209439.51

Vs1 = 209439.51 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 150.00

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for jacket, with:

d2 = 160.00

Av = 100530.965

fy = 525.00

s = 300.00

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, Vr2 = 390183.487

Vr2 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 180743.977

= 1 (normal-weight concrete)

Mean concrete strength: $f_c' = (f_c'_{jacket} * Area_{jacket} + f_c'_{core} * Area_{core}) / Area_{section} = 27.76119$, but $f_c'^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)

pw = As/(bw*d) = 0.00331157

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

Vu*d/Mu < 1 = 0.00

Mu = 1.8034731E-013

Vu = 6.9728406E-015

From (11.5.4.8), ACI 318-14: Vs1 + Vs2 = 209439.51

Vs1 = 209439.51 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

s = 150.00

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for jacket, with:

d = 160.00

Av = 100530.965

fy = 525.00

s = 300.00

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (b)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$
 Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
 Concrete Elasticity, $E_c = 23025.204$
 Steel Elasticity, $E_s = 200000.00$
 External Height, $H = 670.00$
 External Width, $W = 400.00$
 Internal Height, $H = 500.00$
 Internal Width, $W = 200.00$
 Cover Thickness, $c = 25.00$
 Element Length, $L = 3000.00$
 Primary Member
 Smooth Bars
 Ductile Steel
 With Detailing for Earthquake Resistance (including stirrups closed at 135°)
 Longitudinal Bars With Ends Lapped Starting at the End Sections
 Adequate Lap Length ($l_b/l_d >= 1$)
 No FRP Wrapping

 Stepwise Properties

Bending Moment, $M = 9.7286E+006$
 Shear Force, $V_2 = 4.5846775E-014$
 Shear Force, $V_3 = 14540.811$
 Axial Force, $F = -6266.087$
 Longitudinal Reinforcement Area Distribution (in 2 divisions)
 -Tension: $A_{st} = 709.9999$
 -Compression: $A_{sc} = 1668.186$
 Longitudinal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten} = 709.9999$
 -Compression: $A_{st,com} = 1266.062$
 -Middle: $A_{st,mid} = 402.1239$
 Longitudinal External Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten,jacket} = 402.1239$
 -Compression: $A_{st,com,jacket} = 804.2477$
 -Middle: $A_{st,mid,jacket} = 402.1239$
 Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
 -Tension: $A_{st,ten,core} = 307.8761$
 -Compression: $A_{st,com,core} = 461.8141$
 -Middle: $A_{st,mid,core} = 0.00$
 Mean Diameter of Tension Reinforcement, $DbL = 15.00$

 Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $\phi_{u,R} = \phi_u = 0.02586031$
 $\phi_u = \phi_y + \phi_p = 0.02586031$

 - Calculation of ϕ_y -

$\phi_y = (M_y * L_s / 3) / E_{eff} = 0.00086031$ ((4.29), Biskinis Phd)
 $M_y = 2.9205E+008$
 $L_s = M/V$ (with $L_s > 0.1 * L$ and $L_s < 2 * L$) = 669.0526
 From table 10.5, ASCE 41_17: $E_{eff} = 0.3 * E_c * I_g = 7.5708E+013$

 Calculation of Yielding Moment M_y

Calculation of ϕ_y and M_y according to Annex 7 -

$\phi_y = \text{Min}(\phi_{y,ten}, \phi_{y,com})$
 $\phi_{y,ten} = 5.8224212E-006$
 with $f_y = 625.00$
 $d = 627.00$
 $\phi_y = 0.18831702$

A = 0.00952456
B = 0.00407596
with pt = 0.00283094
pc = 0.00504809
pv = 0.00160336
N = 6266.087
b = 400.00
" = 0.06858054
y_comp = 1.7830319E-005
with fc = 27.76119
Ec = 25742.96
y = 0.18763274
A = 0.00942285
B = 0.0040338
with Es = 200000.00

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

- Calculation of p -

From table 10-7: p = 0.025

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.92480584$

- Transverse Reinforcement: C

- Stirrup Spacing $\leq d/3$

- Low ductility demand, $\lambda / y < 2$ (table 10-6, ASCE 41-17)

= -6.6185134E-008

- Stirrup Spacing $\leq d/2$

d = d_external = 627.00

s = s_external = 150.00

- Strength provided by hoops $V_s < 3/4$ *design Shear

$V_s = 421182.855$, already given in calculation of shear control ratio

design Shear = 14540.811

- (- ')/ bal = -0.3178459

= $A_{st}/(b_w*d) = 0.00283094$

Tension Reinf Area: $A_{st} = 709.9999$

' = $A_{sc}/(b_w*d) = 0.00665146$

Compression Reinf Area: $A_{sc} = 1668.186$

From (B-1), ACI 318-11: bal = 0.01202003

$f_c = (f_{c_jacket}*Area_jacket + f_{c_core}*Area_core)/section_area = 27.76119$

$f_y = f_{y_jacket_bars} = 625.00$

From 10.2.7.3, ACI 318-11: $\lambda = 0.65$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + y) = 0.48979592$

y = 0.003125

- $V/(b_w*d*f_c^{0.5}) = 0.13251507$, NOTE: units in lb & in

$b_w = 400.00$

End Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 2

Integration Section: (b)

Calculation No. 15

beam B1, Floor 1



Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Shear capacity VR_d

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Member Shear Force is generally considered as Force-Controlled Action according to Table C7-1, ASCE 41-17.

Lower-bound strengths are used for Force-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 20.00$

New material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 500.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{c_lower_bound} = 16.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{s_lower_bound} = 420.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$

Element Length, $L = 3000.00$

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length ($l_o/l_{o,u}, \min = l_b/l_d \geq 1$)
No FRP Wrapping

Stepwise Properties

EDGE -A-

Bending Moment, $M_a = 4.3723E+006$

Shear Force, $V_a = 5140.455$

EDGE -B-

Bending Moment, $M_b = 9.7286E+006$

Shear Force, $V_b = 14540.811$

BOTH EDGES

Axial Force, $F = -6266.087$

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: $As_t = 709.9999$

-Compression: $As_c = 1668.186$

Longitudinal Reinforcement Area Distribution (in 3 divisions)

-Tension: $As_{t,ten} = 709.9999$

-Compression: $As_{c,com} = 1266.062$

-Middle: $As_{mid} = 402.1239$

Mean Diameter of Tension Reinforcement, $Db_{L,ten} = 15.00$

Existing component: From table 7-7, ASCE 41_17: Final Shear Capacity $V_R = V_n = 466044.126$
 V_n ((22.5.1.1), ACI 318-14) = 466044.126

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw + f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 157246.512$

= 1 (normal-weight concrete)

Mean concrete strength: $f'_c = (f'_{c,jacket} * Area_{jacket} + f'_{c,core} * Area_{core}) / Area_{section} = 18.50746$, but $f_c^{0.5} < = 8.3$ MPa (22.5.3.1, ACI 318-14)

$\rho_w = A_s / (b_w * d) = 0.00331157$

A_s (tension reinf.) = 709.9999

$b_w = 400.00$

$d = 536.00$

$V_u * d / M_u < 1 = 0.80113283$

$M_u = 9.7286E+006$

$V_u = 14540.811$

From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 308797.614$

$V_{s1} = 280648.944$ is calculated for jacket, with:

$d = 536.00$

$A_v = 157079.633$

$f_y = 500.00$

$s = 150.00$

V_{s1} has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

$V_{s2} = 28148.67$ is calculated for core, with:

$d = 400.00$

$A_v = 100530.965$

$f_y = 420.00$

$s = 300.00$

V_{s2} has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)

$2(1-s/d) = 0.50$

V_f ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: $V_s + V_f < = 612724.122$

End Of Calculation of Shear Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (b)

Calculation No. 16

beam B1, Floor 1


Limit State: Life Safety (data interpolation between analysis steps 1 and 2)

Analysis: Uniform +X

Check: Chord rotation capacity (θ)

Edge: End

Local Axis: (3)



Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 3

(Bending local axis: 2)

Section Type: rcjars

Constant Properties

Knowledge Factor, $\gamma = 1.00$

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$

Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$

Concrete Elasticity, $E_c = 23025.204$

Steel Elasticity, $E_s = 200000.00$

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 781.25$

Existing Column

Existing material: Steel Strength, $f_s = 1.25 \cdot f_{sm} = 656.25$

#####

External Height, $H = 670.00$

External Width, $W = 400.00$

Internal Height, $H = 500.00$

Internal Width, $W = 200.00$

Cover Thickness, $c = 25.00$
Mean Confinement Factor overall section = 1.04251
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_o/l_{ou}, \min >= 1$)
No FRP Wrapping

Stepwise Properties

At local axis: 3
EDGE -A-
Shear Force, $V_a = 9840.632$
EDGE -B-
Shear Force, $V_b = 9840.634$
BOTH EDGES
Axial Force, $F = -2309.834$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 709.9999$
-Compression: $A_{sc,com} = 1266.062$
-Middle: $A_{st,mid} = 402.1239$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.92480584$
Member Controlled by Flexure ($V_e/V_r < 1$)
Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 535287.788$
with
 $M_{pr1} = \text{Max}(\mu_{u1+}, \mu_{u1-}) = 7.8817E+008$
 $\mu_{u1+} = 4.6479E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination
 $\mu_{u1-} = 7.8817E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination
 $M_{pr2} = \text{Max}(\mu_{u2+}, \mu_{u2-}) = 7.8817E+008$
 $\mu_{u2+} = 4.6479E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the static loading combination
 $\mu_{u2-} = 7.8817E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the static loading combination
and
 $\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$
with
 $V_1 = 9840.632$, is the shear force acting at edge 1 for the static loading combination
 $V_2 = 9840.634$, is the shear force acting at edge 2 for the static loading combination

Calculation of μ_{u1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:
 $\phi_u = 5.6369735E-005$
 $\mu_u = 4.6479E+008$

with full section properties:

$b = 400.00$
 $d = 627.00$
 $d' = 43.00$
 $v = 0.000307$
 $N = 2309.834$

fc = 30.00

cc (5A.5, TBDY) = 0.002

Final value of cu* = shear_factor * Max(cu, cc) = 0.00680405

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00680405

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = Max(ase1,ase2) = 0.14776895

bo_2 = 192.00

ho_2 = 492.00

bi2_2 = 557856.00

psh,min*Fywe = Min(psh,x*Fywe , psh,y*Fywe) = 1.38519

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559

ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 670.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519

ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298

Ash1 = Astir_1*ns_1 = 157.0796

No stirups, ns_1 = 2.00

h1 = 400.00

ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008

Ash2 = Astir_2*ns_2 = 100.531

No stirups, ns_2 = 2.00

h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 872.4558

fy1 = 727.0465

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/ld)^ 2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 727.0465

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 882.7854

fy2 = 735.6545

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered

characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 735.6545

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 937.50

fyv = 781.25

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor

and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/ld = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 781.25

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.06860752

2 = Asl,com/(b*d)*(fs2/fc) = 0.12378842

v = Asl,mid/(b*d)*(fsv/fc) = 0.04175429

and confined core properties:

b = 340.00

d = 597.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.08477074

2 = Asl,com/(b*d)*(fs2/fc) = 0.15295169

v = Asl,mid/(b*d)*(fsv/fc) = 0.05159117

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

v < vs,y2 - LHS eq.(4.5) is satisfied

--->

su (4.9) = 0.09460844

Mu = MRc (4.14) = 4.6479E+008

u = su (4.1) = 5.6369735E-005

Calculation of ratio lb/ld

Adequate Lap Length: lb/ld >= 1

Calculation of Mu1-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 6.0907698E-005

Mu = 7.8817E+008

with full section properties:

b = 400.00

d = 627.00

$d' = 43.00$
 $v = 0.000307$
 $N = 2309.834$
 $fc = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $we (5.4c) = 0.00682295$
 $ase ((5.4d), TBDY) = (ase1 * Aext + ase2 * Aint) / Asec = 0.14776895$
 $ase1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$
 $bi2_1 = 975400.00$
 $ase2 = Max(ase1, ase2) = 0.14776895$
 $bo_2 = 192.00$
 $ho_2 = 492.00$
 $bi2_2 = 557856.00$
 $psh, min * Fywe = Min(psh, x * Fywe, psh, y * Fywe) = 1.38519$

$psh, x * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 2.45559$
 $ps1 (external) = (Ash1 * h1 / s1) / Asec = 0.00261799$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 670.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / Asec = 0.00062519$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 500.00$

$psh, y * Fywe = psh1 * Fywe1 + ps2 * Fywe2 = 1.38519$
 $ps1 (external) = (Ash1 * h1 / s1) / Asec = 0.00156298$
 $Ash1 = Astir_1 * ns_1 = 157.0796$
 No stirups, $ns_1 = 2.00$
 $h1 = 400.00$
 $ps2 (internal) = (Ash2 * h2 / s2) / Asec = 0.00025008$
 $Ash2 = Astir_2 * ns_2 = 100.531$
 No stirups, $ns_2 = 2.00$
 $h2 = 200.00$

$Asec = 268000.00$
 $s1 = 150.00$
 $s2 = 300.00$
 $fywe1 = 781.25$
 $fywe2 = 656.25$
 $fce = 30.00$

From ((5.A5), TBDY), TBDY: $cc = 0.00242514$
 $c = confinement\ factor = 1.04251$

$y1 = 0.0025$
 $sh1 = 0.008$
 $ft1 = 882.7854$
 $fy1 = 735.6545$
 $su1 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 $Shear_factor = 1.00$

$lo/lo, min = lb/ld = 1.00$

$su1 = 0.4 * esu1_nominal ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_nominal = 0.08$,

For calculation of $esu1_nominal$ and $y1, sh1, ft1, fy1$, it is considered
 characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $Min(1, 1.25 * (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs, jacket * Asl, ten, jacket + fs, core * Asl, ten, core) / Asl, ten = 735.6545$

with $Es1 = (Es, jacket * Asl, ten, jacket + Es, core * Asl, ten, core) / Asl, ten = 200000.00$

$y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 872.4558$

$$f_y2 = 727.0465$$

$$s_u2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_{b,min} = 1.00$$

$$s_u2 = 0.4 * e_{su2,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{su2,nominal} = 0.08$,

For calculation of $e_{su2,nominal}$ and y_2, sh_2, ft_2, f_y2 , it is considered
characteristic value $f_{sy2} = f_s2/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_y1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{s2} = (f_{s,jacket} * A_{s1,com,jacket} + f_{s,core} * A_{s1,com,core}) / A_{s1,com} = 727.0465$$

$$\text{with } E_{s2} = (E_{s,jacket} * A_{s1,com,jacket} + E_{s,core} * A_{s1,com,core}) / A_{s1,com} = 200000.00$$

$$y_v = 0.0025$$

$$sh_v = 0.008$$

$$f_{tv} = 937.50$$

$$f_{yv} = 781.25$$

$$s_{uv} = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

$$l_o/l_{o,u,min} = l_b/l_d = 1.00$$

$$s_{uv} = 0.4 * e_{suv,nominal} ((5.5), TBDY) = 0.032$$

From table 5A.1, TBDY: $e_{suv,nominal} = 0.08$,

considering characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY

For calculation of $e_{suv,nominal}$ and $y_v, sh_v, f_{tv}, f_{yv}$, it is considered
characteristic value $f_{syv} = f_{sv}/1.2$, from table 5.1, TBDY.

y_1, sh_1, ft_1, f_y1 , are also multiplied by $\text{Min}(1, 1.25 * (l_b/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } f_{sv} = (f_{s,jacket} * A_{s1,mid,jacket} + f_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 781.25$$

$$\text{with } E_{sv} = (E_{s,jacket} * A_{s1,mid,jacket} + E_{s,mid} * A_{s1,mid,core}) / A_{s1,mid} = 200000.00$$

$$1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.12378842$$

$$2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.06860752$$

$$v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.04175429$$

and confined core properties:

$$b = 340.00$$

$$d = 597.00$$

$$d' = 13.00$$

$$f_{cc} (5A.2, TBDY) = 31.27541$$

$$c_c (5A.5, TBDY) = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$1 = A_{s1,ten} / (b * d) * (f_{s1} / f_c) = 0.15295169$$

$$2 = A_{s1,com} / (b * d) * (f_{s2} / f_c) = 0.08477074$$

$$v = A_{s1,mid} / (b * d) * (f_{sv} / f_c) = 0.05159117$$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$$s_u (4.8) = 0.16206515$$

$$M_u = M_{Rc} (4.15) = 7.8817E+008$$

$$u = s_u (4.1) = 6.0907698E-005$$

Calculation of ratio l_b/l_d

Adequate Lap Length: $l_b/l_d \geq 1$

Calculation of M_{u2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$$u = 5.6369735E-005$$

Mu = 4.6479E+008

with full section properties:

b = 400.00

d = 627.00

d' = 43.00

v = 0.000307

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: $cu^* = \text{shear_factor} * \text{Max}(cu, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase1 * A_{ext} + ase2 * A_{int}) / A_{sec} = 0.14776895$

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = $\text{Max}(ase1, ase2) = 0.14776895$

bo_2 = 192.00

ho_2 = 492.00

bi2_2 = 557856.00

$psh, \min * F_{ywe} = \text{Min}(psh, x * F_{ywe}, psh, y * F_{ywe}) = 1.38519$

$psh, x * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 2.45559$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00261799$

Ash1 = $A_{stir,1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 670.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00062519$

Ash2 = $A_{stir,2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 500.00

$psh, y * F_{ywe} = psh1 * F_{ywe1} + ps2 * F_{ywe2} = 1.38519$

ps1 (external) = $(Ash1 * h1 / s1) / A_{sec} = 0.00156298$

Ash1 = $A_{stir,1} * ns_1 = 157.0796$

No stirups, $ns_1 = 2.00$

h1 = 400.00

ps2 (internal) = $(Ash2 * h2 / s2) / A_{sec} = 0.00025008$

Ash2 = $A_{stir,2} * ns_2 = 100.531$

No stirups, $ns_2 = 2.00$

h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A.5), TBDY), TBDY: $cc = 0.00242514$

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 872.4558

fy1 = 727.0465

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

su1 = $0.4 * esu1_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu1_{nominal} = 0.08$,

For calculation of $esu1_{nominal}$ and y1, sh1, ft1, fy1, it is considered characteristic value $fsy1 = fs1 / 1.2$, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25 * (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 727.0465$
 with $Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$
 $y2 = 0.0025$
 $sh2 = 0.008$
 $ft2 = 882.7854$
 $fy2 = 735.6545$
 $su2 = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/lb,min = 1.00$
 $su2 = 0.4 \cdot esu2_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,
 For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered
 characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 735.6545$
 with $Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$
 $yv = 0.0025$
 $shv = 0.008$
 $ftv = 937.50$
 $fyv = 781.25$
 $suv = 0.032$
 using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
 and also multiplied by the shear_factor according to 15.7.1.4, with
 Shear_factor = 1.00
 $lo/lou,min = lb/ld = 1.00$
 $suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$
 From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,
 considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY
 For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered
 characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.
 $y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 781.25$
 with $Esv = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.06860752$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.12378842$
 $v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.04175429$
 and confined core properties:
 $b = 340.00$
 $d = 597.00$
 $d' = 13.00$
 $fcc (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.08477074$
 $2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.15295169$
 $v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.05159117$
 Case/Assumption: Unconfined full section - Steel rupture
 ' satisfies Eq. (4.3)
 --->
 $v < vs,y2$ - LHS eq.(4.5) is satisfied
 --->
 $su (4.9) = 0.09460844$
 $Mu = MRc (4.14) = 4.6479E+008$
 $u = su (4.1) = 5.6369735E-005$

 Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

 Calculation of $Mu2$ -

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$$u = 6.0907698E-005$$

$$Mu = 7.8817E+008$$

with full section properties:

$$b = 400.00$$

$$d = 627.00$$

$$d' = 43.00$$

$$v = 0.000307$$

$$N = 2309.834$$

$$f_c = 30.00$$

$$c_o(5A.5, \text{TBDY}) = 0.002$$

$$\text{Final value of } \phi_u: \phi_u^* = \text{shear_factor} * \text{Max}(\phi_u, \phi_c) = 0.00680405$$

The Shear_factor is considered equal to 1 (pure moment strength)

$$\text{From (5.4b), TBDY: } \phi_u = 0.00680405$$

$$w_e(5.4c) = 0.00682295$$

$$a_{se}((5.4d), \text{TBDY}) = (a_{se1} * A_{ext} + a_{se2} * A_{int}) / A_{sec} = 0.14776895$$

$$a_{se1} = 0.14776895$$

$$b_{o_1} = 340.00$$

$$h_{o_1} = 610.00$$

$$b_{i2_1} = 975400.00$$

$$a_{se2} = \text{Max}(a_{se1}, a_{se2}) = 0.14776895$$

$$b_{o_2} = 192.00$$

$$h_{o_2} = 492.00$$

$$b_{i2_2} = 557856.00$$

$$p_{sh, \min} * F_{ywe} = \text{Min}(p_{sh, x} * F_{ywe}, p_{sh, y} * F_{ywe}) = 1.38519$$

$$p_{sh, x} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 2.45559$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00261799$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirups, $n_{s_1} = 2.00$

$$h_1 = 670.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00062519$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirups, $n_{s_2} = 2.00$

$$h_2 = 500.00$$

$$p_{sh, y} * F_{ywe} = p_{sh1} * F_{ywe1} + p_{sh2} * F_{ywe2} = 1.38519$$

$$p_{s1}(\text{external}) = (A_{sh1} * h_1 / s_1) / A_{sec} = 0.00156298$$

$$A_{sh1} = A_{stir_1} * n_{s_1} = 157.0796$$

No stirups, $n_{s_1} = 2.00$

$$h_1 = 400.00$$

$$p_{s2}(\text{internal}) = (A_{sh2} * h_2 / s_2) / A_{sec} = 0.00025008$$

$$A_{sh2} = A_{stir_2} * n_{s_2} = 100.531$$

No stirups, $n_{s_2} = 2.00$

$$h_2 = 200.00$$

$$A_{sec} = 268000.00$$

$$s_1 = 150.00$$

$$s_2 = 300.00$$

$$f_{ywe1} = 781.25$$

$$f_{ywe2} = 656.25$$

$$f_{ce} = 30.00$$

$$\text{From ((5.A5), TBDY), TBDY: } \phi_c = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y_1 = 0.0025$$

$$sh_1 = 0.008$$

$$ft_1 = 882.7854$$

$$fy_1 = 735.6545$$

$$su_1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$l_o / l_{o, \min} = l_b / d = 1.00$$

$$su_1 = 0.4 * e_{su1_nominal}((5.5), \text{TBDY}) = 0.032$$

From table 5A.1, TBDY: $e_{su1_nominal} = 0.08$,

For calculation of $es1_{nominal}$ and $y1, sh1, ft1, fy1$, it is considered characteristic value $fsy1 = fs1/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs1 = (fs_{jacket} \cdot Asl_{ten,jacket} + fs_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 735.6545$

with $Es1 = (Es_{jacket} \cdot Asl_{ten,jacket} + Es_{core} \cdot Asl_{ten,core}) / Asl_{ten} = 200000.00$

$y2 = 0.0025$

$sh2 = 0.008$

$ft2 = 872.4558$

$fy2 = 727.0465$

$su2 = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{min} = lb/lb_{min} = 1.00$

$su2 = 0.4 \cdot esu2_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esu2_{nominal} = 0.08$,

For calculation of $esu2_{nominal}$ and $y2, sh2, ft2, fy2$, it is considered characteristic value $fsy2 = fs2/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fs2 = (fs_{jacket} \cdot Asl_{com,jacket} + fs_{core} \cdot Asl_{com,core}) / Asl_{com} = 727.0465$

with $Es2 = (Es_{jacket} \cdot Asl_{com,jacket} + Es_{core} \cdot Asl_{com,core}) / Asl_{com} = 200000.00$

$yv = 0.0025$

$shv = 0.008$

$ftv = 937.50$

$fyv = 781.25$

$suv = 0.032$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$lo/lo_{min} = lb/ld = 1.00$

$suv = 0.4 \cdot esuv_{nominal} ((5.5), TBDY) = 0.032$

From table 5A.1, TBDY: $esuv_{nominal} = 0.08$,

considering characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY

For calculation of $esuv_{nominal}$ and yv, shv, ftv, fyv , it is considered characteristic value $fsyv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1, ft1, fy1$, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs_{jacket} \cdot Asl_{mid,jacket} + fs_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 781.25$

with $Es_v = (Es_{jacket} \cdot Asl_{mid,jacket} + Es_{mid} \cdot Asl_{mid,core}) / Asl_{mid} = 200000.00$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.12378842$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.06860752$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.04175429$

and confined core properties:

$b = 340.00$

$d = 597.00$

$d' = 13.00$

$f_{cc} (5A.2, TBDY) = 31.27541$

$cc (5A.5, TBDY) = 0.00242514$

$c = \text{confinement factor} = 1.04251$

$1 = Asl_{ten} / (b \cdot d) \cdot (fs1 / fc) = 0.15295169$

$2 = Asl_{com} / (b \cdot d) \cdot (fs2 / fc) = 0.08477074$

$v = Asl_{mid} / (b \cdot d) \cdot (fsv / fc) = 0.05159117$

Case/Assumption: Unconfined full section - Steel rupture

' satisfies Eq. (4.3)

--->

$v < v_{s,y2}$ - LHS eq.(4.5) is not satisfied

--->

$v < v_{s,c}$ - RHS eq.(4.5) is satisfied

--->

$su (4.8) = 0.16206515$

$Mu = MRc (4.15) = 7.8817E+008$

$u = su (4.1) = 6.0907698E-005$

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Shear Strength $V_r = \text{Min}(V_{r1}, V_{r2}) = 578810.994$

Calculation of Shear Strength at edge 1, $V_{r1} = 578810.994$
 $V_{r1} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
As (tension reinf.) = 709.9999
bw = 400.00
d = 536.00
 $V_u \cdot d / \mu < 1 = 1.00$
 $\mu = 1.1510E+006$
Vu = 9840.632
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$
 $V_{s1} = 350811.18$ is calculated for jacket, with:
d = 536.00
Av = 157079.633
fy = 625.00
s = 150.00
Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 35185.838$ is calculated for jacket, with:
d2 = 400.00
Av = 100530.965
fy = 525.00
s = 300.00
Vs2 has been multiplied by $2(1-s/d)$ ($s > d/2$, according to ASCE 41-17,10.3.4)
 $2(1-s/d) = 0.50$
Vf ((11-3)-(11.4), ACI 440) = 0.00
From (11-11), ACI 440: $V_s + V_f \leq 750430.726$

Calculation of Shear Strength at edge 2, $V_{r2} = 578810.994$
 $V_{r2} = V_n$ ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: $V_c = 192813.976$
= 1 (normal-weight concrete)
Mean concrete strength: $f'_c = (f'_{c_jacket} \cdot \text{Area}_{jacket} + f'_{c_core} \cdot \text{Area}_{core}) / \text{Area}_{section} = 27.76119$, but $f_c^{0.5} \leq 8.3$ MPa (22.5.3.1, ACI 318-14)
 $p_w = A_s / (b_w \cdot d) = 0.00331157$
As (tension reinf.) = 709.9999
bw = 400.00
d = 536.00
 $V_u \cdot d / \mu < 1 = 1.00$
 $\mu = 1.1510E+006$
Vu = 9840.634
From (11.5.4.8), ACI 318-14: $V_{s1} + V_{s2} = 385997.017$
 $V_{s1} = 350811.18$ is calculated for jacket, with:
d = 536.00
Av = 157079.633
fy = 625.00
s = 150.00
Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)
 $V_{s2} = 35185.838$ is calculated for jacket, with:
d = 400.00
Av = 100530.965
fy = 525.00

s = 300.00

Vs2 has been multiplied by 2(1-s/d) (s>d/2, according to ASCE 41-17,10.3.4)

2(1-s/d) = 0.50

Vf ((11-3)-(11.4), ACI 440) = 0.00

From (11-11), ACI 440: Vs + Vf <= 750430.726

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 3

Start Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At Shear local axis: 2

(Bending local axis: 3)

Section Type: rcjars

Constant Properties

Knowledge Factor, = 1.00

Mean strength values are used for both shear and moment calculations.

Consequently:

Jacket

New material of Primary Member: Concrete Strength, fc = fcm = 30.00

New material of Primary Member: Steel Strength, fs = fsm = 625.00

Concrete Elasticity, Ec = 25742.96

Steel Elasticity, Es = 200000.00

Existing Column

Existing material of Primary Member: Concrete Strength, fc = fcm = 24.00

Existing material of Primary Member: Steel Strength, fs = fsm = 525.00

Concrete Elasticity, Ec = 23025.204

Steel Elasticity, Es = 200000.00

#####

Note: Especially for the calculation of moment strengths,

the above steel re-bar strengths are multiplied by 1.25 according to R18.6.5, ACI 318-14

Jacket

New material: Steel Strength, fs = 1.25*fsm = 781.25

Existing Column

Existing material: Steel Strength, fs = 1.25*fsm = 656.25

#####

External Height, H = 670.00

External Width, W = 400.00

Internal Height, H = 500.00

Internal Width, W = 200.00

Cover Thickness, c = 25.00

Mean Confinement Factor overall section = 1.04251

Element Length, L = 3000.00

Primary Member

Smooth Bars

Ductile Steel

With Detailing for Earthquake Resistance (including stirrups closed at 135°)

Longitudinal Bars With Ends Lapped Starting at the End Sections

Adequate Lap Length (lo/lo_u,min>= 1)

No FRP Wrapping

Stepwise Properties

At local axis: 2

EDGE -A-

Shear Force, Va = -6.9728406E-015

EDGE -B-

Shear Force, Vb = 6.9728406E-015

BOTH EDGES

Axial Force, F = -2309.834

Longitudinal Reinforcement Area Distribution (in 2 divisions)

-Tension: Aslt = 709.9999

-Compression: $Asl,c = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $Asl,t = 911.0619$
-Compression: $Asl,c = 911.0619$
-Middle: $Asl,m = 556.0619$

Calculation of Shear Capacity ratio, $V_e/V_r = 0.55914272$

Member Controlled by Flexure ($V_e/V_r < 1$)

Calculation of Shear Demand from fig. R18.6.5, ACI 318-14 $V_e = (M_{pr1} + M_{pr2})/l_n \pm w_u \cdot l_n/2 = 218168.257$
with

$M_{pr1} = \text{Max}(Mu_{1+}, Mu_{1-}) = 3.2725E+008$

$Mu_{1+} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the actual moment direction which is defined for the static loading combination

$Mu_{1-} = 3.2725E+008$, is the ultimate moment strength at the edge 1 of the member in the opposite moment direction which is defined for the static loading combination

$M_{pr2} = \text{Max}(Mu_{2+}, Mu_{2-}) = 3.2725E+008$

$Mu_{2+} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the actual moment direction which is defined for the the static loading combination

$Mu_{2-} = 3.2725E+008$, is the ultimate moment strength at the edge 2 of the member in the opposite moment direction which is defined for the the static loading combination

and

$\pm w_u \cdot l_n = (|V_1| + |V_2|)/2$

with

$V_1 = -6.9728406E-015$, is the shear force acting at edge 1 for the the static loading combination

$V_2 = 6.9728406E-015$, is the shear force acting at edge 2 for the the static loading combination

Calculation of Mu_{1+}

Calculation of ultimate curvature ϕ_u according to 4.1, Biskinis/Fardis 2013:

$\phi_u = 0.00010507$

$M_u = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$f_c = 30.00$

ϕ_c (5A.5, TBDY) = 0.002

Final value of ϕ_u : $\phi_u^* = \text{shear_factor} \cdot \text{Max}(\phi_u, \phi_c) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $\phi_u = 0.00680405$

ϕ_u (5.4c) = 0.00682295

$\phi_{u,ase}$ ((5.4d), TBDY) = $(\phi_{u,ase1} \cdot A_{ext} + \phi_{u,ase2} \cdot A_{int})/A_{sec} = 0.14776895$

$\phi_{u,ase1} = 0.14776895$

$b_{o,1} = 340.00$

$h_{o,1} = 610.00$

$b_{i,1} = 975400.00$

$\phi_{u,ase2} = \text{Max}(\phi_{u,ase1}, \phi_{u,ase2}) = 0.14776895$

$b_{o,2} = 192.00$

$h_{o,2} = 492.00$

$b_{i,2} = 557856.00$

$\phi_{sh,min} \cdot F_{ywe} = \text{Min}(\phi_{sh,x} \cdot F_{ywe}, \phi_{sh,y} \cdot F_{ywe}) = 1.38519$

$\phi_{sh,x} \cdot F_{ywe} = \phi_{sh1} \cdot F_{ywe1} + \phi_{sh2} \cdot F_{ywe2} = 2.45559$

ϕ_{sh1} (external) = $(A_{sh1} \cdot h_1/s_1)/A_{sec} = 0.00261799$

$A_{sh1} = A_{stir,1} \cdot n_{s,1} = 157.0796$

No stirups, $n_{s,1} = 2.00$

$h_1 = 670.00$

ϕ_{sh2} (internal) = $(A_{sh2} \cdot h_2/s_2)/A_{sec} = 0.00062519$

Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 886.8103

fy1 = 739.0086

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 886.8103

fy2 = 739.0086

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by Min(1,1.25*(lb/lb)^2/3), from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 895.9746

fyv = 746.6455

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered

characteristic value $f_{sv} = f_{sv}/1.2$, from table 5.1, TBDY.
 y_1, sh_1, ft_1, fy_1 , are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.
 with $f_{sv} = (f_{s,jacket} \cdot A_{s,mid,jacket} + f_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 746.6455$
 with $E_{sv} = (E_{s,jacket} \cdot A_{s,mid,jacket} + E_{s,mid} \cdot A_{s,mid,core}) / A_{s,mid} = 200000.00$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.09382814$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.09382814$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.05785932$

and confined core properties:

$b = 610.00$
 $d = 327.00$
 $d' = 13.00$
 $f_{cc} (5A.2, TBDY) = 31.27541$
 $cc (5A.5, TBDY) = 0.00242514$
 $c = \text{confinement factor} = 1.04251$
 $1 = A_{s,ten} / (b \cdot d) \cdot (f_{s1} / f_c) = 0.11251192$
 $2 = A_{s,com} / (b \cdot d) \cdot (f_{s2} / f_c) = 0.11251192$
 $v = A_{s,mid} / (b \cdot d) \cdot (f_{sv} / f_c) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture
 ' does not satisfy Eq. (4.3)

---->
 $v < v_{s,c}$ - RHS eq.(4.5) is satisfied
 ---->
 $su (4.9) = 0.1468828$
 $Mu = MRc (4.14) = 3.2725E+008$
 $u = su (4.1) = 0.00010507$

 Calculation of ratio lb/ld

 Adequate Lap Length: $lb/ld \geq 1$

 Calculation of Mu_1 -

 Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:
 $u = 0.00010507$
 $Mu = 3.2725E+008$

 with full section properties:

$b = 670.00$
 $d = 357.00$
 $d' = 43.00$
 $v = 0.0003219$
 $N = 2309.834$
 $f_c = 30.00$
 $co (5A.5, TBDY) = 0.002$
 Final value of cu : $cu^* = \text{shear_factor} \cdot \text{Max}(cu, cc) = 0.00680405$
 The Shear_factor is considered equal to 1 (pure moment strength)
 From (5.4b), TBDY: $cu = 0.00680405$
 $w_e (5.4c) = 0.00682295$
 $ase ((5.4d), TBDY) = (ase_1 \cdot A_{ext} + ase_2 \cdot A_{int}) / A_{sec} = 0.14776895$
 $ase_1 = 0.14776895$
 $bo_1 = 340.00$
 $ho_1 = 610.00$
 $bi_2_1 = 975400.00$
 $ase_2 = \text{Max}(ase_1, ase_2) = 0.14776895$
 $bo_2 = 192.00$
 $ho_2 = 492.00$
 $bi_2_2 = 557856.00$
 $psh, \text{min} \cdot F_{ywe} = \text{Min}(psh, x \cdot F_{ywe}, psh, y \cdot F_{ywe}) = 1.38519$

 $psh, x \cdot F_{ywe} = psh_1 \cdot F_{ywe1} + ps_2 \cdot F_{ywe2} = 2.45559$
 $ps_1 (\text{external}) = (A_{sh1} \cdot h_1 / s_1) / A_{sec} = 0.00261799$
 $A_{sh1} = A_{stir_1} \cdot n_{s_1} = 157.0796$

No stirups, ns₁ = 2.00
h₁ = 670.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00062519
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 500.00

psh_y*Fywe = psh₁*Fywe₁+ps₂*Fywe₂ = 1.38519
ps₁ (external) = (Ash₁*h₁/s₁)/Asec = 0.00156298
Ash₁ = Astir₁*ns₁ = 157.0796
No stirups, ns₁ = 2.00
h₁ = 400.00
ps₂ (internal) = (Ash₂*h₂/s₂)/Asec = 0.00025008
Ash₂ = Astir₂*ns₂ = 100.531
No stirups, ns₂ = 2.00
h₂ = 200.00

Asec = 268000.00
s₁ = 150.00
s₂ = 300.00
fywe₁ = 781.25
fywe₂ = 656.25
fce = 30.00

From ((5.A.5), TBDY), TBDY: cc = 0.00242514
c = confinement factor = 1.04251

y₁ = 0.0025
sh₁ = 0.008
ft₁ = 886.8103
fy₁ = 739.0086
su₁ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 1.00

su₁ = 0.4*esu_{1_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{1_nominal} = 0.08,

For calculation of esu_{1_nominal} and y₁, sh₁,ft₁,fy₁, it is considered
characteristic value fsy₁ = fs₁/1.2, from table 5.1, TBDY.

y₁, sh₁,ft₁,fy₁, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₁ = (fs_{jacket}*As_{l,ten,jacket} + fs_{core}*As_{l,ten,core})/As_{l,ten} = 739.0086

with Es₁ = (Es_{jacket}*As_{l,ten,jacket} + Es_{core}*As_{l,ten,core})/As_{l,ten} = 200000.00

y₂ = 0.0025
sh₂ = 0.008
ft₂ = 886.8103
fy₂ = 739.0086
su₂ = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_{b,min} = 1.00

su₂ = 0.4*esu_{2_nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu_{2_nominal} = 0.08,

For calculation of esu_{2_nominal} and y₂, sh₂,ft₂,fy₂, it is considered
characteristic value fsy₂ = fs₂/1.2, from table 5.1, TBDY.

y₂, sh₂,ft₂,fy₂, are also multiplied by Min(1,1.25*(lb/l_d)^{2/3}), from 10.3.5, ASCE 41-17.

with fs₂ = (fs_{jacket}*As_{l,com,jacket} + fs_{core}*As_{l,com,core})/As_{l,com} = 739.0086

with Es₂ = (Es_{jacket}*As_{l,com,jacket} + Es_{core}*As_{l,com,core})/As_{l,com} = 200000.00

y_v = 0.0025
sh_v = 0.008
ft_v = 895.9746
fy_v = 746.6455
su_v = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/l_d = 1.00

su_v = 0.4*esuv_{nominal} ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: $esuv_nominal = 0.08$,
considering characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY
For calculation of $esuv_nominal$ and yv, shv,ftv,fyv , it is considered
characteristic value $fsv = fsv/1.2$, from table 5.1, TBDY.

$y1, sh1,ft1,fy1$, are also multiplied by $Min(1,1.25*(lb/ld)^{2/3})$, from 10.3.5, ASCE 41-17.

with $fsv = (fs,jacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455$

with $Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00$

1 = $Asl,ten/(b*d)*(fs1/fc) = 0.09382814$

2 = $Asl,com/(b*d)*(fs2/fc) = 0.09382814$

$v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932$

and confined core properties:

$b = 610.00$

$d = 327.00$

$d' = 13.00$

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

$c =$ confinement factor = 1.04251

1 = $Asl,ten/(b*d)*(fs1/fc) = 0.11251192$

2 = $Asl,com/(b*d)*(fs2/fc) = 0.11251192$

$v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071$

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

$v < vs,c$ - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

$Mu = MRc$ (4.14) = 3.2725E+008

$u = su$ (4.1) = 0.00010507

Calculation of ratio lb/ld

Adequate Lap Length: $lb/ld \geq 1$

Calculation of Mu_{2+}

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

$u = 0.00010507$

$Mu = 3.2725E+008$

with full section properties:

$b = 670.00$

$d = 357.00$

$d' = 43.00$

$v = 0.0003219$

$N = 2309.834$

$fc = 30.00$

co (5A.5, TBDY) = 0.002

Final value of cu : $cu^* = shear_factor * Max(cu, cc) = 0.00680405$

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: $cu = 0.00680405$

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = $(ase1*Aext+ase2*Aint)/Asec = 0.14776895$

$ase1 = 0.14776895$

$bo_1 = 340.00$

$ho_1 = 610.00$

$bi2_1 = 975400.00$

$ase2 = Max(ase1,ase2) = 0.14776895$

$bo_2 = 192.00$

$ho_2 = 492.00$

$bi2_2 = 557856.00$

$psh,min*Fywe = Min(psh,x*Fywe, psh,y*Fywe) = 1.38519$

psh_x*Fywe = psh1*Fywe1+ps2*Fywe2 = 2.45559
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00261799
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 670.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00062519
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 500.00

psh_y*Fywe = psh1*Fywe1+ps2*Fywe2 = 1.38519
ps1 (external) = (Ash1*h1/s1)/Asec = 0.00156298
Ash1 = Astir_1*ns_1 = 157.0796
No stirups, ns_1 = 2.00
h1 = 400.00
ps2 (internal) = (Ash2*h2/s2)/Asec = 0.00025008
Ash2 = Astir_2*ns_2 = 100.531
No stirups, ns_2 = 2.00
h2 = 200.00

Asec = 268000.00

s1 = 150.00

s2 = 300.00

fywe1 = 781.25

fywe2 = 656.25

fce = 30.00

From ((5.A5), TBDY), TBDY: cc = 0.00242514

c = confinement factor = 1.04251

y1 = 0.0025

sh1 = 0.008

ft1 = 886.8103

fy1 = 739.0086

su1 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb = 1.00

su1 = 0.4*esu1_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1,ft1,fy1, it is considered
characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086

with Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00

y2 = 0.0025

sh2 = 0.008

ft2 = 886.8103

fy2 = 739.0086

su2 = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/lb,min = 1.00

su2 = 0.4*esu2_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2,ft2,fy2, it is considered
characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 * (\text{lb}/\text{ld})^{2/3})$, from 10.3.5, ASCE 41-17.

with fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086

with Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00

yv = 0.0025

shv = 0.008

ftv = 895.9746

fyv = 746.6455

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with

Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fsjacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09382814

2 = Asl,com/(b*d)*(fs2/fc) = 0.09382814

v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11251192

2 = Asl,com/(b*d)*(fs2/fc) = 0.11251192

v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Mu2-

Calculation of ultimate curvature u according to 4.1, Biskinis/Fardis 2013:

u = 0.00010507

Mu = 3.2725E+008

with full section properties:

b = 670.00

d = 357.00

d' = 43.00

v = 0.0003219

N = 2309.834

fc = 30.00

co (5A.5, TBDY) = 0.002

Final value of cu: cu* = shear_factor * Max(cu, cc) = 0.00680405

The Shear_factor is considered equal to 1 (pure moment strength)

From (5.4b), TBDY: cu = 0.00680405

we (5.4c) = 0.00682295

ase ((5.4d), TBDY) = (ase1*Aext+ase2*Aint)/Asec = 0.14776895

ase1 = 0.14776895

bo_1 = 340.00

ho_1 = 610.00

bi2_1 = 975400.00

ase2 = Max(ase1,ase2) = 0.14776895

bo_2 = 192.00

ho_2 = 492.00

$$bi2_2 = 557856.00$$
$$psh,min*Fywe = \text{Min}(psh,x*Fywe, psh,y*Fywe) = 1.38519$$

$$psh_x*Fywe = psh1*Fywe1 + ps2*Fywe2 = 2.45559$$
$$ps1 \text{ (external)} = (Ash1*h1/s1)/Asec = 0.00261799$$
$$Ash1 = Astir_1*ns_1 = 157.0796$$
$$\text{No stirups, } ns_1 = 2.00$$
$$h1 = 670.00$$
$$ps2 \text{ (internal)} = (Ash2*h2/s2)/Asec = 0.00062519$$
$$Ash2 = Astir_2*ns_2 = 100.531$$
$$\text{No stirups, } ns_2 = 2.00$$
$$h2 = 500.00$$

$$psh_y*Fywe = psh1*Fywe1 + ps2*Fywe2 = 1.38519$$
$$ps1 \text{ (external)} = (Ash1*h1/s1)/Asec = 0.00156298$$
$$Ash1 = Astir_1*ns_1 = 157.0796$$
$$\text{No stirups, } ns_1 = 2.00$$
$$h1 = 400.00$$
$$ps2 \text{ (internal)} = (Ash2*h2/s2)/Asec = 0.00025008$$
$$Ash2 = Astir_2*ns_2 = 100.531$$
$$\text{No stirups, } ns_2 = 2.00$$
$$h2 = 200.00$$

$$Asec = 268000.00$$

$$s1 = 150.00$$

$$s2 = 300.00$$

$$fywe1 = 781.25$$

$$fywe2 = 656.25$$

$$fce = 30.00$$

$$\text{From } ((5.A.5), \text{ TBDY}), \text{ TBDY: } cc = 0.00242514$$

$$c = \text{confinement factor} = 1.04251$$

$$y1 = 0.0025$$

$$sh1 = 0.008$$

$$ft1 = 886.8103$$

$$fy1 = 739.0086$$

$$su1 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/l_d = 1.00$$

$$su1 = 0.4*esu1_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu1_nominal = 0.08,

For calculation of esu1_nominal and y1, sh1, ft1, fy1, it is considered characteristic value fsy1 = fs1/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs1 = (fs,jacket*Asl,ten,jacket + fs,core*Asl,ten,core)/Asl,ten = 739.0086$$

$$\text{with } Es1 = (Es,jacket*Asl,ten,jacket + Es,core*Asl,ten,core)/Asl,ten = 200000.00$$

$$y2 = 0.0025$$

$$sh2 = 0.008$$

$$ft2 = 886.8103$$

$$fy2 = 739.0086$$

$$su2 = 0.032$$

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor and also multiplied by the shear_factor according to 15.7.1.4, with Shear_factor = 1.00

$$lo/lou,min = lb/lb,min = 1.00$$

$$su2 = 0.4*esu2_nominal \text{ ((5.5), TBDY)} = 0.032$$

From table 5A.1, TBDY: esu2_nominal = 0.08,

For calculation of esu2_nominal and y2, sh2, ft2, fy2, it is considered characteristic value fsy2 = fs2/1.2, from table 5.1, TBDY.

y1, sh1, ft1, fy1, are also multiplied by $\text{Min}(1, 1.25*(lb/l_d)^{2/3})$, from 10.3.5, ASCE 41-17.

$$\text{with } fs2 = (fs,jacket*Asl,com,jacket + fs,core*Asl,com,core)/Asl,com = 739.0086$$

$$\text{with } Es2 = (Es,jacket*Asl,com,jacket + Es,core*Asl,com,core)/Asl,com = 200000.00$$

$$yv = 0.0025$$

$$shv = 0.008$$

$$ftv = 895.9746$$

$$fyv = 746.6455$$

suv = 0.032

using (30) in Biskinis/Fardis (2013) multiplied with shear_factor
and also multiplied by the shear_factor according to 15.7.1.4, with
Shear_factor = 1.00

lo/lou,min = lb/d = 1.00

suv = 0.4*esuv_nominal ((5.5), TBDY) = 0.032

From table 5A.1, TBDY: esuv_nominal = 0.08,

considering characteristic value fsyv = fsv/1.2, from table 5.1, TBDY

For calculation of esuv_nominal and yv, shv,ftv,fyv, it is considered
characteristic value fsyv = fsv/1.2, from table 5.1, TBDY.

y1, sh1,ft1,fy1, are also multiplied by $\text{Min}(1, 1.25 \cdot (lb/d)^{2/3})$, from 10.3.5, ASCE 41-17.

with fsv = (fsjacket*Asl,mid,jacket + fs,mid*Asl,mid,core)/Asl,mid = 746.6455

with Esv = (Es,jacket*Asl,mid,jacket + Es,mid*Asl,mid,core)/Asl,mid = 200000.00

1 = Asl,ten/(b*d)*(fs1/fc) = 0.09382814

2 = Asl,com/(b*d)*(fs2/fc) = 0.09382814

v = Asl,mid/(b*d)*(fsv/fc) = 0.05785932

and confined core properties:

b = 610.00

d = 327.00

d' = 13.00

fcc (5A.2, TBDY) = 31.27541

cc (5A.5, TBDY) = 0.00242514

c = confinement factor = 1.04251

1 = Asl,ten/(b*d)*(fs1/fc) = 0.11251192

2 = Asl,com/(b*d)*(fs2/fc) = 0.11251192

v = Asl,mid/(b*d)*(fsv/fc) = 0.06938071

Case/Assumption: Unconfined full section - Steel rupture

' does not satisfy Eq. (4.3)

---->

v < vs,c - RHS eq.(4.5) is satisfied

---->

su (4.9) = 0.1468828

Mu = MRc (4.14) = 3.2725E+008

u = su (4.1) = 0.00010507

Calculation of ratio lb/d

Adequate Lap Length: lb/d >= 1

Calculation of Shear Strength Vr = Min(Vr1,Vr2) = 390183.487

Calculation of Shear Strength at edge 1, Vr1 = 390183.487

Vr1 = Vn ((22.5.1.1), ACI 318-14)

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw+ f*Vf'
where Vf is the contribution of FRPs (11.3), ACI 440).

From Table (22.5.5.1), ACI 318-14: Vc = 180743.977

= 1 (normal-weight concrete)

Mean concrete strength: fc' = (fc'_jacket*Area_jacket + fc'_core*Area_core)/Area_section = 27.76119, but fc'^0.5 <= 8.3 MPa (22.5.3.1, ACI 318-14)

pw = As/(bw*d) = 0.00331157

As (tension reinf.) = 709.9999

bw = 670.00

d = 320.00

Vu*d/Mu < 1 = 0.00

Mu = 2.1102257E-011

Vu = 6.9728406E-015

From (11.5.4.8), ACI 318-14: Vs1 + Vs2 = 209439.51

Vs1 = 209439.51 is calculated for jacket, with:

d = 320.00

Av = 157079.633

fy = 625.00

$$s = 150.00$$

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for jacket, with:

$$d_2 = 160.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 300.00$$

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 750430.726$$

Calculation of Shear Strength at edge 2, $V_{r2} = 390183.487$

$$V_{r2} = V_n \text{ ((22.5.1.1), ACI 318-14)}$$

NOTE: In expression (22.5.1.1) 'Vw' is replaced by 'Vw + f*Vf' where Vf is the contribution of FRPs (11.3), ACI 440).

$$\text{From Table (22.5.5.1), ACI 318-14: } V_c = 180743.977$$

= 1 (normal-weight concrete)

$$\text{Mean concrete strength: } f'_c = (f'_{c_jacket} * \text{Area}_{jacket} + f'_{c_core} * \text{Area}_{core}) / \text{Area}_{section} = 27.76119, \text{ but } f_c^{0.5} \leq 8.3 \text{ MPa (22.5.3.1, ACI 318-14)}$$

$$p_w = A_s / (b_w * d) = 0.00331157$$

$$A_s \text{ (tension reinf.)} = 709.9999$$

$$b_w = 670.00$$

$$d = 320.00$$

$$V_u * d / \mu_u < 1 = 0.00$$

$$\mu_u = 1.8034731E-013$$

$$V_u = 6.9728406E-015$$

$$\text{From (11.5.4.8), ACI 318-14: } V_{s1} + V_{s2} = 209439.51$$

Vs1 = 209439.51 is calculated for jacket, with:

$$d = 320.00$$

$$A_v = 157079.633$$

$$f_y = 625.00$$

$$s = 150.00$$

Vs1 has been multiplied by 1 ($s < d/2$, according to ASCE 41-17,10.3.4)

Vs2 = 0.00 is calculated for jacket, with:

$$d = 160.00$$

$$A_v = 100530.965$$

$$f_y = 525.00$$

$$s = 300.00$$

Vs2 is considered 0 ($s > d$, according to ASCE 41-17,10.3.4)

$$V_f \text{ ((11-3)-(11.4), ACI 440)} = 0.00$$

$$\text{From (11-11), ACI 440: } V_s + V_f \leq 750430.726$$

End Of Calculation of Shear Capacity ratio for element: beam JB1 of floor 1

At local axis: 2

Start Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (b)

Section Type: rcjars

Constant Properties

$$\text{Knowledge Factor, } = 1.00$$

Chord Rotation is generally considered as Deformation-Controlled Action according to Table C7-1, ASCE 41-17.

Mean strengths are used for Deformation-Controlled Actions according to 7.5.1.3, ASCE 41-17

Consequently:

Jacket

New material of Primary Member: Concrete Strength, $f_c = f_{cm} = 30.00$

New material of Primary Member: Steel Strength, $f_s = f_{sm} = 625.00$

Concrete Elasticity, $E_c = 25742.96$

Steel Elasticity, $E_s = 200000.00$

Existing Column

Existing material of Primary Member: Concrete Strength, $f_c = f_{cm} = 24.00$
Existing material of Primary Member: Steel Strength, $f_s = f_{sm} = 525.00$
Concrete Elasticity, $E_c = 23025.204$
Steel Elasticity, $E_s = 200000.00$
External Height, $H = 670.00$
External Width, $W = 400.00$
Internal Height, $H = 500.00$
Internal Width, $W = 200.00$
Cover Thickness, $c = 25.00$
Element Length, $L = 3000.00$
Primary Member
Smooth Bars
Ductile Steel
With Detailing for Earthquake Resistance (including stirrups closed at 135°)
Longitudinal Bars With Ends Lapped Starting at the End Sections
Adequate Lap Length ($l_b/l_d >= 1$)
No FRP Wrapping

Stepwise Properties

Bending Moment, $M = -6.4836912E-011$
Shear Force, $V_2 = 4.5846775E-014$
Shear Force, $V_3 = 14540.811$
Axial Force, $F = -6266.087$
Longitudinal Reinforcement Area Distribution (in 2 divisions)
-Tension: $A_{st} = 709.9999$
-Compression: $A_{sc} = 1668.186$
Longitudinal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten} = 911.0619$
-Compression: $A_{st,com} = 911.0619$
-Middle: $A_{st,mid} = 556.0619$
Longitudinal External Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten,jacket} = 603.1858$
-Compression: $A_{st,com,jacket} = 603.1858$
-Middle: $A_{st,mid,jacket} = 402.1239$
Longitudinal Internal Reinforcement Area Distribution (in 3 divisions)
-Tension: $A_{st,ten,core} = 307.8761$
-Compression: $A_{st,com,core} = 307.8761$
-Middle: $A_{st,mid,core} = 153.938$
Mean Diameter of Tension Reinforcement, $DbL = 15.20$

Existing component: From table 7-7, ASCE 41_17: Final chord rotation Capacity $u_{R} = \phi \cdot u = 0.02409992$
 $u = \phi \cdot u_{p} = 0.02409992$

- Calculation of ϕ -

$\phi = (M_y \cdot L_s / 3) / E_{eff} = 0.00409992$ ((4.29), Biskinis Phd))
 $M_y = 2.1236E+008$
 $L_s = M/V$ (with $L_s > 0.1 \cdot L$ and $L_s < 2 \cdot L$) = 1500.00
From table 10.5, ASCE 41_17: $E_{eff} = 0.3 \cdot E_c \cdot I_g = 2.5898E+013$

Calculation of Yielding Moment M_y

Calculation of ϕ and M_y according to Annex 7 -

$\phi = \text{Min}(\phi_{ten}, \phi_{com})$
 $\phi_{ten} = 1.0748658E-005$
with $f_y = 625.00$
 $d = 357.00$
 $\phi = 0.22779052$

A = 0.00998687
 B = 0.00561432
 with pt = 0.00380895
 pc = 0.00380895
 pv = 0.00232477
 N = 6266.087
 b = 670.00
 " = 0.12044818
 y_comp = 2.5852450E-005
 with fc = 27.76119
 Ec = 25742.96
 y = 0.22728216
 A = 0.00988022
 B = 0.00557012
 with Es = 200000.00

 Calculation of ratio lb/d

 Adequate Lap Length: lb/d >= 1

 - Calculation of p -

 From table 10-7: p = 0.02

with:

- Condition i occurred

Beam controlled by flexure: $V_p/V_o \leq 1$

shear control ratio $V_p/V_o = 0.55914272$

- Transverse Reinforcement: NC

- Stirrup Spacing > d/3

- Low ductility demand, $\lambda < 2$ (table 10-6, ASCE 41-17)

= -7.5574920E-023

- Stirrup Spacing <= d/2

d = d_external = 357.00

s = s_external = 150.00

- Strength provided by hoops $V_s < 3/4$ *design Shear

$V_s = 237588.18$, already given in calculation of shear control ratio

design Shear = 4.5846775E-014

- (- ')/ bal = -0.33327376

= $A_{st}/(b_w*d) = 0.00296835$

Tension Reinf Area: $A_{st} = 709.9999$

' = $A_{sc}/(b_w*d) = 0.00697431$

Compression Reinf Area: $A_{sc} = 1668.186$

From (B-1), ACI 318-11: bal = 0.01202003

$f_c = (f_{c_jacket}*Area_jacket + f_{c_core}*Area_core)/section_area = 27.76119$

$f_y = f_{y_jacket_bars} = 625.00$

From 10.2.7.3, ACI 318-11: $\lambda = 0.65$

From fig R10.3.3, ACI 318-11 (Ence 454, too): $87000/(87000 + f_y) = c_b/d_t = 0.003/(0.003 + \lambda) = 0.48979592$

$\lambda = 0.003125$

- $V/(b_w*d*f_c^{0.5}) = 4.3809665E-019$, NOTE: units in lb & in

$b_w = 670.00$

 End Of Calculation of Chord Rotation Capacity for element: beam JB1 of floor 1

At local axis: 3

Integration Section: (b)